BEHAVIOR PRIOR REPRESENTATION LEARNING FOR OFFLINE REINFORCEMENT LEARNING

ABSTRACT

Offline reinforcement learning (RL) struggles in environments with rich and noisy inputs, where the agent only has access to a fixed dataset without environment interactions. Past works have proposed common workarounds based on the pre-training of state representations, followed by policy training. In this work, we introduce a simple, yet effective approach for learning state representations. Our method, Behavior Prior Representation (BPR), learns state representations with an easy-to-integrate objective based on behavior cloning of the dataset: we first learn a state representation by mimicking actions from the dataset, and then train a policy on top of the fixed representation, using any off-the-shelf Offline RL algorithm. Theoretically, we prove that BPR carries out performance guarantees when integrated into algorithms that have either policy improvement guarantees (conservative algorithms) or produce lower bounds of the policy values (pessimistic algorithms). Empirically, we show that BPR combined with existing state-of-the-art Offline RL algorithms leads to significant improvements across several offline control benchmarks.

1 INTRODUCTION

Offline Reinforcement Learning (Offline RL) is one of the most promising data-driven ways of optimizing sequential decision-making. Offline RL differs from the typical settings of Deep Reinforcement Learning (DRL) in that the agent is trained on a fixed dataset that was previously collected by some arbitrary process, and does not interact with the environment during learning (Lange et al., 2012; Levine et al., 2020). Consequently, it benefits the scenarios where online exploration is challenging and/or unsafe, especially for application domains such as healthcare (Wang et al., 2018; Gottesman et al., 2019; Satija et al., 2021) and autonomous driving (Bojarski et al., 2016; Yurtsever et al., 2020).

A common baseline of Offline RL is *Behavior Cloning* (BC) (Pomerleau, 1991). BC performs maximum-likelihood training on a collected set of demonstrations, essentially mimicking the behavior policy to produce predictions (actions) conditioned on observations. While BC can only achieve proficient policies when dealing with expert demonstrations, Offline RL goes beyond the goal of simply imitating and aims to train a policy that improves over the behavior one. Despite promising results, Offline RL algorithms still suffer from two main issues: i) difficulty dealing with limited high-dimensional data, especially visual observations with continuous action space (Lu et al., 2022); ii) implicit under-parameterization of value networks exacerbated by highly re-used data, that is, an expressive value network implicitly behaves as an under-parameterized one when trained using bootstrapping (Kumar et al., 2021a;b).

In this paper, we focus on state representation learning for Offline RL to mitigate the above issues: projecting the high-dimensional observations to a low-dimensional space can lead to better performance given limited data in the Offline RL scenario. Moreover, disentangling representation learning from policy training (or value function learning), referred to as pre-training the state representations, can potentially mitigate the "implicit under-parameterization" phenomenon associated with the emergence of low-rank features in the value network (Wang et al., 2022). In contrast to previous work that pre-train state representations by specifying the required properties, *e.g.*, maximizing the diversity of states encountered by the agent (Liu & Abbeel, 2021; Eysenbach et al., 2019), exploring the attentive knowledge on sub-trajectory (Yang & Nachum, 2021), or capturing temporal information about the environment (Schwarzer et al., 2021a), we consider using the behavior policy to learn generic state representations instead of specifying specific properties.

Many existing Offline RL methods regularize the policy to be close to the behavior policy (Fujimoto et al., 2019; Laroche et al., 2019b; Kumar et al., 2019) or constrain the learned value function of OOD actions not to be overestimated (Kumar et al., 2020; Kostrikov et al., 2021). Beyond these use, the behavior policy is often ignored, as it does not directly provide information on the environment. However, the choice of behavior has a huge impact on the Offline RL task. As shown by recent theoretical work (Xiao et al., 2022; Foster et al., 2022), under an agnostic baseline, the Offline RL task is intractable (near optimality is exponential in the state space size), but it becomes tractable with a well-designed behavior (*e.g.* the optimal policy or a policy trained online). This impact indicates that the information collected from the behavior policy might deserve more attention.

To this end, we propose Behavior Prior Representation (BPR), a state representation learning method tailored to Offline RL settings (Figure 1). BPR learns state representations implicitly by enforcing them to be predictive of the action performed by the behavior policy, normalized to be on the unit sphere. Then, the learned encoder is frozen and utilized to train a downstream policy with any Offline RL algorithms. Intuitively, to be predictive of the normalized actions, BPR encourages the encoder to ignore the task-irrelevant information while maintaining the task-specific knowledge relative to the behavior, which we posit is efficient for learning a state representation. Theoretically, we prove that BPR carries out performance guarantees when combined with conservative or pes-

Figure 1: Illustration of Behavior Prior Representations and comparison with Behavior Cloning.

simistic Offline RL algorithms. Furthermore, since the learning procedure of BPR does not involve value functions or bootstrapping methods like Temporal-Difference, it can naturally mitigate the "implicit under-parameterization" phenomenon. We prove this empirically by utilizing effective dimensions measurement to evaluate feature compactness in the value network's penultimate layer. The key contributions of our work are summarized below:

- We propose a simple, yet effective method for state representation learning in Offline RL, relying on the behavior cloning of actions; and find that this approach is effective across several offline benchmarks, including raw state and pixel based ones. Our approach can be combined to any existing Offline RL pipeline with minimal changes.

- Behavior prior representation (BPR) is theoretically grounded: we show, under strong assumptions, that policy improvement guarantees from offline RL algorithms are retained through the BPR, at the only expense of an additive behavior cloning error term.

- We provide extensive empirical studies, comparing BPR to several state representation objectives for Offline RL, and show that it outperforms the baselines across a wide range of tasks.

2 RELATED WORK

Offline RL with behavior regularization. Although to the best of our knowledge, we are the first to leverage behavior cloning (BC) to learn a state representation in Offline RL, we remark that combining Offline RL with behavior regularization has been considered previously by many works. A common way of combining BC with RL is to utilize it as a reference for policy optimization with baseline methods, such as natural policy gradient (Rajeswaran et al., 2018), DDPG (Nair et al., 2018; Goecks et al., 2020), BCQ (Fujimoto et al., 2019), SPIBB (Laroche et al., 2019a; Nadjahi et al., 2019; Simão et al., 2020; Satija et al., 2021; Brandfonbrener et al., 2022), CQL (Kumar et al., 2020), and TD3 (Fujimoto & Gu, 2021). Other previous works include learning adaptive behavior policies that are biased towards higher-rewards trajectories (Cang et al., 2021), and pretraining behavior policies to guide downstream policies training (Zhang et al., 2021b). However, all these approaches neglect the potential of using the behavior policy to guide representation learning. In contrast, we investigate state representation learning via a BC-style approach and show that the downstream policy can be greatly boosted in that regime.

Representation learning in Offline RL. Pretraining representation has been recently studied in Offline RL settings, where several studies presented its effectiveness (Arora et al., 2020; Schwarzer et al., 2021a; Nachum & Yang, 2021a). Some typical auxiliary tasks for pretraining state representations include capturing the dynamical (Nachum & Yang, 2021b) and temporal (Schwarzer et al., 2021a) information of the environment, exploring the attentive knowledge on sub-trajectory (Yang & Nachum, 2021), improving policy performance by applying data augmentations techniques to the pixel-based inputs (Chen et al., 2021; Lu et al., 2022)... While driven by various motivations, most of these methods can be thought of as including different inductive biases via the specific design of the target properties of the representation. In this paper, the inductive bias we enforce is that the representation should allow matching the behavior action normalized to the unit hypersphere, we demonstrate its effectiveness on both raw-state and visual-observation inputs tasks. Additional related works are discussed in appendix B.

3 Preliminaries

Offline RL We consider the standard Markov decision process (MDP) framework, in which the environment is given by a tuple $\mathcal{M} = (\mathcal{S}, \mathcal{A}, T, \rho, r, \gamma)$, with state space $\mathcal{S}$, action space $\mathcal{A}$, transition function T that decides the next state $s' \sim T(\cdot|s, a)$, initial state distribution ρ, reward function $r(s, a)$ bounded by $R_{\max}$, and a discount factor $\gamma \in [0, 1)$. The agent in state $s \in \mathcal{S}$ selects an action $a \in \mathcal{A}$ according to its policy, mapping states to a probability distribution over actions: $a \sim \pi(\cdot|s)$. We make use of the state value function $V^\pi(s) = \mathbb{E}_{\mathcal{M}, \pi} \left[\sum_{t=0}^\infty \gamma^t r(s_t, a_t) \mid s_0 = s \right]$ to describe the long term discounted reward of policy π starting at state s. In Offline RL, we are given a fixed dataset of environment interactions that include N transition samples, i.e., $\mathcal{D} = \{s_i, a_i, s_i', r_i\}_{i=1}^N$. We assume that the dataset $\mathcal{D}$ is generated i.i.d. from a distribution $\mu(s, a)$ that specifies the effective behavior policy $\pi_\beta(a|s) = \mu(s, a) / \sum_a \mu(s, a)$, and denote by $d^{\pi_\beta}(s)$ its discounted state occupancy density. Following Rashidinejad et al. (2021), the goal of Offline RL is to minimize the suboptimality of π with respect to the optimal policy $\pi^\star$ given a dataset $\mathcal{D}$:

$$\text{SubOpt}(\pi) = \mathbb{E}_{\mathcal{D} \sim \mu} \left[\mathcal{J}(\pi^\star) - \mathcal{J}(\pi) \right] = \mathbb{E}_{\mathcal{D} \sim \mu} \left[\mathbb{E}_{\mathbf{s}_0 \sim \rho} \left[V^\star(\mathbf{s}_0) - V^\pi(\mathbf{s}_0) \right] \right], \quad (1)$$

where $\mathcal{J}(\pi) = \mathbb{E}_{\mathbf{s}_0 \sim \rho} \left[V^\pi(\mathbf{s}_0) \right]$ is the performance of the policy π.

State Representation Learning In this paper, our objective is to find a state representation function $\phi : \mathcal{S} \to \mathcal{Z}$ that maps each state $s \in \mathcal{S}$ to its representation $z = \phi(s) \in \mathcal{Z}$. The desired representations should provide necessary and useful information to summarize the task-relevant knowledge and facilitate policy learning. To investigate the capacity of state representation learning for mitigating the "implicit under-parameterization" phenomenon, following Lyle et al. (2022) and Kumar et al. (2021a), we measure the compactness of the feature in the penultimate layer of the value network by utilizing the *Effective Dimension*, where we refer to the output of the penultimate layer of the state-action value network as the feature matrix $\Psi \in \mathbb{R}^{|\mathcal{S}||\mathcal{A}| \times d}$ [1]:

Definition 1. *Effective Dimension Let* $\text{ED}(M)$ *denote the eigenvalues of a square matrix* M, $\mathcal{D}$ *be the offline dataset, and* ϵ *be a fixed hyperparameter. Then, the effective dimension of* Ψ *is defined as*

$$\zeta(\Psi, \mathcal{D}, \epsilon) = \mathbb{E}_{\mathcal{D}} \left[\left| \left\{ \sigma \in ED \left(|\mathcal{S}|^{-1} |\mathcal{A}|^{-1} \Psi^\top \Psi \right) \mid \sigma > \epsilon \right\} \right| \right], \quad (2)$$

It is the expected number of eigenvalues of $\Psi^\top \Psi$ that are larger than $|\mathcal{S}||\mathcal{A}|\epsilon$. By studying this quantity, we can explicitly observe the usefulness of the state representation objective in mitigating the "implicit under-parameterization" problem in value networks (see Section 6.3 for the results).

4 Behavior Prior Representation

Given an offline dataset $\mathcal{D}$ consisting of (s, a) pairs, our goal is to learn an encoder $\phi(s)$ that produces state representations $z = \phi(s)$ allowing efficient and successful downstream policy learning. During pre-training, the BPR network is comprised of two connected components: an *encoder* ϕ_θ and a *predictor* f_ω. The encoder maps the state to the representation space, while the predictor

---

[1]Notably, when we characterize the state by its corresponding state representation, the dimension of the feature matrix changes accordingly as $\mathbb{R}^{|\mathcal{Z}||\mathcal{A}| \times d}$. We defer a detailed discussion to Appendix D.

projects the representations onto the unit sphere in dimension $|\mathcal{A}|$. In state s, the BPR network outputs a *representation* $z_\theta = \phi_\theta(s)$, and a *prediction* $y = f_\omega(z_\theta)$. We then ℓ_2-normalize the prediction y and the action a to $\overline{y} = y/\|y\|_2$ and $\overline{a} = a/\|a\|_2$ and minimize the mean squared error to train the state representation (or equivalently maximize the cosine similarity between y and a):

$$\mathcal{L}_{\theta,\omega} = \mathbb{E}_{(s,a)\sim\mathcal{D}}\left[\|\overline{y} - \overline{a}\|_2^2\right] = \mathbb{E}_{(s,a)\sim\mathcal{D}}\left[2 - 2 \cdot \frac{\langle f_\omega(\phi_\theta(s)), a\rangle}{\|f_\omega(\phi_\theta(s))\|_2 \cdot \|a\|_2}\right], \tag{3}$$

where we set the action from the pair (s, a) as the target. During the training process, stochastic optimization is performed to minimize $\mathcal{L}_{\theta,\omega}$ with respect to θ and ω. Note that although the encoder and predictor are updated together through this optimization procedure, **only the encoder ϕ_θ is used in the downstream task**. At the end of the training, we keep the encoder ϕ_θ fixed and build the downstream Offline RL agents on top of the state representation that BPR learnt.

Implementation details   BPR method does not rely on any specific architecture as its encoder network. Depending on the nature of given inputs, it can either be a convolutional neural network (CNN) for visual observation inputs, or a multi-layer perceptron (MLP) for physically meaningful state inputs. The representation z_θ that corresponds to the output of the encoder is then projected to the action space. In this paper, the projection is done by an MLP consisting of two linear layers followed by rectified linear units (ReLU) (Nair & Hinton, 2010), and a final linear layer followed by a tanh activation layer.

5   THEORETICAL ANALYSIS

For simplicity, we consider the optimization problem of BPR without the normalization term as:

$$\min \frac{1}{n}\sum_{i=1}^{n}\|f(\phi(s_i)) - a_i\|_2^2 : \phi \in \Phi, f \in \mathcal{F}, \tag{4}$$

where (s_i, a_i) is an i.i.d. sample from the offline dataset (of size n). BPR consists in learning a representation ϕ impacting the policy search. In other words, with BPR, the function class for the policy consists in $\Pi_{\mathrm{BPR}} \doteq \{\pi, \text{s.t. } \exists\,\omega \text{ with } \pi(\cdot|s) = f_\omega(\phi_\theta(s))\ \forall s\}$, where f_ω is the neural model parameterized with ω characterizing the policy on top of embedding $\phi_\theta(\cdot)$. Like any representation learning technique, the potential benefits are (i) enhancing the signal-to-noise ratio and (ii) reducing the size of the policy search. In this section, we develop an analysis showing that the potential harm of using BPR is upper bounded by an error ϵ_β that we control in Section 5.3. To our knowledge, this is the first representation learning technique for Offline RL with such guarantees.

Idealized assumptions :   Letting $\hat{x}$ denote an estimate of a quantity x computed using $\mathcal{D}$, we start by considering the following idealized assumptions:

Assumption 1. *(1.1) Access to the true behavior: $\pi_{\hat{\beta}} = \pi_\beta$. (1.2) Access to the true performance of policies: $\hat{\mathcal{J}}(\pi) = \mathcal{J}(\pi)$ for all policies π. (1.3) The embedding ϕ allows to represent the behavior policy estimate: $\pi_{\hat{\beta}}(a|\phi(s)) = \pi_{\hat{\beta}}(a|s) \in \Pi_{\mathrm{BPR}}$. (1.4) The Offline RL algorithm performs perfect optimization on top of ϕ: $\mathcal{J}_{\mathrm{BPR}} = \max_{\pi\in\Pi_{\mathrm{BPR}}}\hat{\mathcal{J}}(\pi)$.*

Theorem 2. *Under idealized Assumption 1, BPR returns a policy that improves over the behavior policy: $\mathcal{J}_{\mathrm{BPR}} \geq \mathcal{J}(\pi_\beta)$.*

Its proof[2] is immediate: under perfect estimation and optimization, the fact that $\beta \in \Pi_{\mathrm{BPR}}$ guarantees policy improvement. The above assumptions are stringent, and we propose to relax them in two different ways: for conservative algorithms that derive safe policy improvement guarantees (Petrik et al., 2016; Fujimoto et al., 2019; Laroche et al., 2019b; Simão et al., 2020), and for pessimistic algorithms that derive a value function lower bound (Kumar et al., 2020; Buckman et al., 2021).

5.1   SAFE POLICY IMPROVEMENT

Conservative algorithms constrain the policy search to the set of policies Π_{PI} for which the true policy improvement $\Delta_{\pi,\pi_{\hat{\beta}}} \doteq \mathcal{J}(\pi) - \mathcal{J}(\pi_{\hat{\beta}})$ can be safely estimated from $\hat{\Delta}_{\pi,\pi_{\hat{\beta}}} \doteq \hat{\mathcal{J}}(\pi) - \hat{\mathcal{J}}(\pi_{\hat{\beta}})$:

$$\forall \pi \in \Pi_{\mathrm{PI}}, \quad \hat{\Delta}_{\pi,\pi_{\hat{\beta}}} - \Delta_{\pi,\pi_{\hat{\beta}}} \leq \epsilon_\Delta. \tag{5}$$

---

[2]For readability, we defer rigorous proofs of theorems to the Appendix E.

It is worth noting that the estimated behavior policy $\pi_{\hat{\beta}}$ necessarily belongs to Π_{PI}, since trivially $\hat{\Delta}_{\pi_{\hat{\beta}}, \pi_{\hat{\beta}}} = \Delta_{\pi_{\hat{\beta}}, \pi_{\hat{\beta}}} = 0$. Combined with BPR, conservative algorithms optimize on the policy set $\Pi_{\mathrm{PI}} \cap \Pi_{\mathrm{BPR}}$, and we consider the following relaxed assumptions, corresponding respectively to Assumptions 1.1 and 1.2:

Assumption 2. *(2.1) Access to an accurate estimate $\pi_{\hat{\beta}}$ of the true behavior π_{β}: $\mathcal{J}(\pi_{\beta}) - \mathcal{J}(\pi_{\hat{\beta}}) \leq \epsilon_{\beta}$. (2.2) Access to an accurate estimate $\hat{\Delta}_{\pi, \pi_{\hat{\beta}}}$ of the true policy improvement $\Delta_{\pi, \pi_{\hat{\beta}}}$ for all policies $\pi \in \Pi_{\mathrm{PI}} \cap \Pi_{\mathrm{BPR}}$: $\hat{\Delta}_{\pi, \pi_{\hat{\beta}}} - \Delta_{\pi, \pi_{\hat{\beta}}} \leq \epsilon_{\Delta}$.*

Theorem 3. *Under Assumption 2, BPR returns a policy π_{BPR} with the following performance bounds: $\mathcal{J}_{\mathrm{BPR}} \geq \mathcal{J}(\pi_{\beta}) + \hat{\Delta}_{\pi_{\mathrm{BPR}}, \pi_{\hat{\beta}}} - \epsilon_{\Delta} - \epsilon_{\beta}$.*

Assumption 2.1 amounts to behavior cloning (BC) guarantees. It is generally assumed as being an easier task than policy optimization, as BC is supervised learning. Theorem 5 provides bounds on ϵ_{β}. Assumption 2.2 reflects the policy improvement objective. For instance, the SPIBB principle guarantees it with high probability in finite MDPs (Laroche et al., 2019b; Nadjahi et al., 2019; Simão et al., 2020). It is important to notice that Assumption 2.2 forbids, in theory, the use of the BPR representation to estimate the value directly. But in practice, we show that the representation learned by BPR is still useful to estimate the value function. We provide some experimental results in Appendix G.6 and a counterexample in Appendix F.

Additionally, it is worth noting that ensuring that $\hat{\Delta}_{\pi_{\mathrm{BPR}}, \pi_{\hat{\beta}}}$ is positive is necessary to obtain approximate policy improvement guarantees. To do so, it suffices to fall back to $\pi_{\hat{\beta}}$ when the optimization of π_{BPR} does not lead to a positive expected improvement $\hat{\Delta}_{\pi_{\mathrm{BPR}}, \pi_{\hat{\beta}}}$.

5.2 VALUE FUNCTION LOWER BOUND

In this section, we propose an alternative to Assumption 2.2 following the performance lower bound principle derived in pessimistic algorithms:

Assumption 3. *(3.1) Access to a lower bound of the performance $\mathcal{J}_{\perp}(\pi) \leq \mathcal{J}(\pi)$ for all policies, which is accurate for $\pi_{\hat{\beta}}$: $\mathcal{J}_{\perp}(\pi_{\hat{\beta}}) \geq \mathcal{J}(\pi_{\hat{\beta}}) - \epsilon_{\perp}$.*

In order to provide performance improvement bounds, we make use of the lower bound value gap $\Delta_{\pi, \pi_{\hat{\beta}}}^{\perp} \doteq \mathcal{J}_{\perp}(\pi) - \mathcal{J}_{\perp}(\pi_{\hat{\beta}})$.

Theorem 4. *Under Assumption 2.1 and 3.1, BPR returns a policy π_{BPR} with the following performance bounds: $\mathcal{J}_{\mathrm{BPR}} \geq \mathcal{J}(\pi_{\beta}) + \Delta_{\pi_{\mathrm{BPR}}, \pi_{\hat{\beta}}}^{\perp} - \epsilon_{\perp} - \epsilon_{\beta}$.*

Assumption 3.1 is satisfied by the Offline RL algorithm that is used in combination with BPR. For instance, CQL (Kumar et al., 2020; Yu et al., 2021) relies on the computation of a lower bound of the value function of the considered policies. More generally, pessimistic algorithms (Petrik et al., 2016; Yu et al., 2020; Kidambi et al., 2020; Jin et al., 2021; Buckman et al., 2021) have for principle to add an uncertainty-based penalty to the reward function, in order to control its risk to be overestimated. It is important to notice that, like for Assumption 2.2, this assumption would forbid (in theory) the use of the BPR representation to estimate the value.

Both approaches (safe policy improvement and value function lower bounds) suffer the same cost ϵ_{β}, in comparison to their guarantees without BPR. The next subsection controls this quantity.

5.3 PERFORMANCE BOUND WITH BPR OBJECTIVE

In this section, we are concerned with the statistical property of the error between the estimated behavior based on the representation and the true behavior. To this end, we have the upper bound of the ϵ_{β} as:

Theorem 5. *With probability at least $1 - \delta$, for any $\delta \in (0, 1)$:*

$$\epsilon_{\beta} \leq CK \cdot \frac{1}{n} \sum_{i=1}^{n} \left\| \pi_{\beta}(\cdot | s_i) - \pi_{\hat{\beta}}(\cdot | \phi(s_i)) \right\|_2 + 2\sqrt{2} K \cdot \mathrm{Rad}(\Phi) + K \cdot \sqrt{\frac{2 \ln \frac{1}{\delta}}{n}} \tag{6}$$

where n is the size of the dataset, $Rad(\Phi)$ is the Rademacher complexity of ϕ's function class Φ, π_β is the behavior policy over the dataset, C is a constant, and $K = \frac{R_{max}}{1-\gamma}$.

Note that the first term in Equation 6 is the exact optimization problem of BPR in Equation 4 multiplied by constant $C \cdot K$, where the action a_i is sampled from the offline dataset pairs (s_i, a_i) whose behavior policy is π_β, and the predictor f plays the similar role as the policy $\pi_{\hat{\beta}}$. The second and the third term are both irrelevant to the specific representation, or the estimated behavior. This indicates that the potential harm of utilizing BPR can be reduced as the representation training procedure goes on.

6 EXPERIMENTS

BPR can be easily combined with *any existing* Offline RL pipeline. In this section, we empirically study the effectiveness of BPR on a wide range of Offline RL benchmarks and show that pre-training representations with the BPR objective leads to sample-efficient downstream policy learning. Our experimental results can be broken down into the following sections[3]:

- Does BPR outperform baseline Offline RL algorithms on standard raw-state inputs benchmarks?other representation objectives?
- Is BPR effective to learn policies on high-dimensional pixel-based inputs? Can BPR improve the robustness of the representation when the input contains complex distractors?
- Can BPR successfully improve the effective dimension of the feature in the value network?

6.1 EFFECTIVENESS OF BEHAVIOR REPRESENTATIONS IN D4RL OFFLINE BENCHMARK

Figure 2: Performance comparison on D4RL dataset. The x-axis indicates the number of environment steps. The vertical axis reports the normalized cumulative returns. We train our 6 algorithms (*EDAC*, *TD3+BC*, *CQL*, and their BPR variants) on 6 different random seeds, and evaluate each one every 5,000 environment steps by computing the average return over 10 evaluation episodes. The lighter lines correspond to the baselines, the darker ones to the versions pretrained with BPR.

Performance Comparison in D4RL Benchmark   *Experimental Setup:* We analyze our proposed method BPR on the D4RL benchmark (Fu et al., 2020) of OpenAI gym MuJoCo tasks (Todorov et al., 2012) which includes a variety of datasets that have been commonly used in the Offline RL community. We evaluate our method by integrating it into three Offline RL methods: **TD3+BC** (Fujimoto & Gu, 2021), **CQL** (Kumar et al., 2020), and **EDAC** (An et al., 2021). We consider three environments: halfcheetah, hopper and walker2d, and two datasets per task: expert and medium-expert. Instead of passing the raw state as input to the value and policy networks as in the baseline methods, we first pretrain the encoder during $100k$ timesteps, then freeze it, pass the raw state

---

[3]Due to the page limit, we provide some additional experiment results in Appendix G.

through the frozen encoder to obtain its representation, and use that as the input of the Offline RL algorithm. Further details on the experiment setup are included in appendix G.

Analysis: Figure 2 shows the performance of all models on the D4RL tasks. We observe that pre-training the encoder with BPR leads to faster convergence for all Offline RL algorithms, and can improve policy performance. Notably, since different Offline RL algorithms share the same encoder network architecture, the pretrained BPR encoder can be reused across them, which substantially amortizes the pretraining cost.

Table 1: Interquartile mean, median, and mean normalized scores, evaluated over all six runs for each of 16 DMC tasks. Confidence intervals computed by percentile bootstrap with 5000 resamples.

Method	IQM	95% CI	Median	95% CI	Mean	95% CI
BPR	**89.99**	(85.55, 93.97)	**87.04**	(77.04, 91.53)	**81.70**	(77.38, 86.21)
ACL	70.79	(66.09, 75.53)	67.50	(57.73, 77.28)	69.91	(65.98, 74.05)
Fourier	82.24	(77.86, 86.17)	85.23	(73.25, 88.99)	72.61	(68.01, 76.51)
Forward	18.59	(16.35, 20.90)	9.26	(6.68, 14.48)	29.68	(27.25, 32.20)
Contrastive	44.87	(38.36, 51.52)	41.48	(35.82, 54.39)	43.56	(39.18, 47.98)
Inverse	42.79	(34.97, 50.83)	40.33	(33.38, 47.47)	44.58	(39.20, 49.99)

Performance Comparison among Different Representation Objectives ***Experimental Setup:*** We follow the pre-training and fine-tuning paradigm of Yang & Nachum (2021), where we first pre-train the encoder for $100k$ timesteps, and then fine-tune a BRAC (Wu et al., 2019) agent on downstream tasks. We conduct performance comparison by training the encoder with different objectives, including BPR and several other state-of-the-art representation objectives, namely *ACL* (Yang & Nachum, 2021), *Fourier* (Nachum & Yang, 2021a), *Forward model* (Pathak et al., 2017), *Inverse model* (Pathak et al., 2017), and *Contrastive method* (Laskin et al., 2020)[4].

Figure 3: Bootstrapping distributions for uncertainty in IQM measurements with 5000 resamples

Analysis: We follow the performance criterion from Schwarzer et al. (2021b); Agarwal et al. (2021), and use the inter-quartile mean (IQM) normalized score, which is calculated over runs rather than tasks, and the percentile bootstrap confidence intervals, to compare the performance of the different objectives. The detailed results are provided in appendix G. Figure 3 presents the IQM normalized return and 95% bootstrap confidence intervals for all methods, the numerical values can be found in Table 1. The performance gain of BPR over the two most competitive baselines, Fourier and ACL, is statistically significant($p < 0.05$).

6.2 EFFECTIVENESS OF BEHAVIOR REPRESENTATIONS IN VISUAL OFFLINE RL BENCHMARK

Performance comparison in V-D4RL benchmark ***Experimental Setup:*** In this section, we evaluate our method on a benchmarking suite for Offline RL from visual observations of DMControl suite (DMC) tasks (Lu et al., 2022). We consider three domains: walker-walk, humanoid-walk, and cheetah-run, and two different datasets per environment: medium-expert and expert. We include two baselines from Lu et al. (2022): DrQ+BC and DrQ+CQL. Similarly, in this experiment, we pretrain the encoder with the BPR objective for 100k time steps, followed by a fine-tuning stage where we keep the encoder fixed and apply the two baselines on the learned encoder.

---

[4]We use the codebase from Yang & Nachum (2021) in these experiments: `https://github.com/google-research/google-research/tree/master/rl_repr`

Figure 4: Performance comparison on v-d4rl benchmark, the results are averaged over 10 evaluations and 6 seeds.

Analysis: Figure 4 shows the performance of the four models on V-D4RL. We emphasize that these tasks are more challenging than their conventional D4RL counterparts. Neither DrQ+BC nor DrQ+CQL can solve them without further modifications. By integrating the frozen encoder learned from BPR, both of them obtain significant performance gains. Note that DrQ+CQL typically requires a longer training time to achieve similar performance to DrQ+BC. Nevertheless, the substantial improvement of the modified variant of DrQ+CQL suggests that BPR can be effective to improve sample efficiency, decrease computational cost, and reach better final performance.

Robustness to Visual Distractions ***Experimental Setup:*** To test the policy robustness brought by BPR, we use three levels of distractors: easy, medium and hard, to evaluate the performance of the model, following Lu et al. (2022). Each distraction represents a shift in the data distribution, where task-irrelevant visual factors are added (i.e., backgrounds, agent colors, and camera positions). Those factors of variation disturb the model training (see the demonstrations provided in Appendix G.7). We train the baseline agent, DrQ+BC, and its variant using a fixed encoder pretrained by BPR, on the three levels of the distraction of the *cheetah-run-medium-expert* dataset with 1 million data points. In the experiment, the agent is evaluated on three different test environments: i) *Original Env*, the evaluation environment is the original environment *i.e.*, without any distractors; ii) *Distractor Train*, the evaluation environment has the same distraction configuration as the training dataset, and the configuration is fixed during the evaluation procedure; iii) *Distractor Test*, the specific distractions of the evaluation environment changes over evaluation, while the level of the distractions remains the same.

Table 2: Cumulative return on *cheetah-run-medium-expert* dataset with visual distractions ranging from easy to hard. For each setting, we compare DrQ+BC (before →) to DrQ+BC with an encoder pretrained with BPR (after →). The final mean performance is averaged over 6 seeds. The highest result for each task is underlined.

Level of Distractions	Original	Eval. Return Dis. Train	Dis. Test
easy	45.50(± 37.02) → 113.64(± 24.83)	425.15(± 65.67) → 710.11(± 56.70)	45.16(± 24.96) → 113.27(± 26.48)
medium	37.35(± 25.66) → 104.30(± 22.95)	586.17(± 99.66) → 702.00(± 90.44)	14.70(± 5.93) → 27.53(± 11.62)
hard	13.49(± 10.66) → 64.79(± 33.47)	497.41(± 103.85) → 608.98(± 64.64)	18.88(± 11.32) → 16.72(± 6.88)

Analysis: The final performances are shown in Table 2. As can be seen, BPR improves the policy performance in most cases, except for the task with a combination of the *hard level* and the *distractor test* setting where the averaged performance of the agent with BPR is close to the one without BPR but has a lower variance. Besides, the different evaluation environment corresponds to different degrees of the distribution shift from the training dataset. It is therefore not surprising to see that the agent performs better in *Distractor train* environment than the others. This experiment shows that much better (more robust) policies can be obtained against distractions with the help of BPR,

indicating that BPR objective can somehow disentangle sources of distractions through training, facilitating the learning of general features.

6.3 Effective Dimension of the value network

Experimental Setup: We investigate whether utilizing the fixed encoder learned from BPR can alleviate the "under-parameterization" phenomenon of the value network. To this end, we propose to use the effective dimension (defined in Definition 1) as a way to evaluate the compactness of features represented in the value network. We first sample a batch of state-action pairs from the offline dataset, and then compute the effective dimension of the output of the penultimate layer of the value network. In this experiment, we evaluate the effective dimension of the value network of the CQL agent on *Halfcheetah-medium-expert-v2* task in D4RL datasets which operates on the physically meaning raw state inputs. For comparison, we also develop a variant of CQL whose input is still the raw state, but a shared encoder head is applied to both value network and policy network, and is trained with the critic loss along the policy learning procedure.

Analysis: Figure 5 illustrates that over the course of training, BPR objective successfully improves the effective dimensions of the state representation, meanwhile

Figure 5: Effective dimension of the penultimate layer of the value network (top) and performance (bottom) over the course of training on the Halfcheetah-medium-expert-v2 task.

achieving better performance compared to the agent that is without an encoder and the agent whose encoder is trained with the critic loss. Notably, when training the encoder via the critic loss along the policy learning procedure, the effective dimension increases significantly early in training, suggesting that even without any specific representation loss, the encoder can still disentangle some similar states. When the training goes on, the agent will observe more diverse states over time as the policy improves, which induces a mismatch between the learnt representations and the newly observed states, leading to a decline in the effective dimension. In contrast, with a fixed encoder learned using the BPR objective, CQL produces more effective dimensions than its vanilla version, leading to better performance, which indicates that BPR is capable of providing compact information for downstream Offline RL training.

7 Discussion

Limitations and Future Work Although this work has shown effectiveness in learning representations that are robust to visual distractions, it still struggles when the distribution of evaluation environments shifts too much from the training environment, this suggests that further improvement on the generalization abilities of the representation is required. Another limitation is that although we have shown that it is harmless to estimate the value function by leveraging BPR representations, it is still theoretically unsupported. Further development of a more theoretically grounded representation objective is needed. A potential future work is to combine the BPR objective with the reconstruction for reward and transition functions.

Conclusion Offline RL algorithms typically suffer from two main issues: one is the difficulty of learning from high-dimensional visual input data, the other is the implicit under-parameterization phenomenon that can lead to low-rank features of the value network, further resulting in low performance. In this work, we propose a simple yet effective method for state representation learning in an Offline RL setting which can be combined with any existing Offline RL pipeline with minimal changes. Theoretically, we prove that the representation objective carries out performance guarantees when combining conservative or pessimistic Offline RL algorithms. Empirically, we show that the proposed objective is practical across a wide range of tasks and outperforms many state-of-the-art representation approaches. We hope this work will drive future interest in a close study of representations in Offline RL settings.

8 REPRODUCIBILITY STATEMENT

To ensure the reproducibility of all empirical results, we provide the code base in the supplementary material, which contains: training scripts, requirements for virtual environment. All datasets and code platform (PyTorch and Tensorflow) we use are public. All training details are specified in Section 6 and Appendix G. To rebuild the architecture of BPR model and plug BPR in any other Offline RL algorithms, the readers are suggested to check the descriptions in Section 4, especially the **Implementation details** paragraph. All proofs are stated in the Appendix E with explanations and underlying assumptions.

REFERENCES

Alekh Agarwal, Yuda Song, Wen Sun, Kaiwen Wang, Mengdi Wang, and Xuezhou Zhang. Provable benefits of representational transfer in reinforcement learning. *CoRR*, abs/2205.14571, 2022.

Rishabh Agarwal, Max Schwarzer, Pablo Samuel Castro, Aaron C. Courville, and Marc G. Bellemare. Deep reinforcement learning at the edge of the statistical precipice. In *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 29304–29320, 2021.

Gaon An, Seungyong Moon, Jang-Hyun Kim, and Hyun Oh Song. Uncertainty-based offline reinforcement learning with diversified q-ensemble. In *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 7436–7447, 2021.

David Andre and Stuart J. Russell. State abstraction for programmable reinforcement learning agents. In *Proceedings of the Eighteenth National Conference on Artificial Intelligence and Fourteenth Conference on Innovative Applications of Artificial Intelligence, July 28 - August 1, 2002, Edmonton, Alberta, Canada*, pp. 119–125. AAAI Press / The MIT Press, 2002.

Sanjeev Arora, Simon S. Du, Sham M. Kakade, Yuping Luo, and Nikunj Saunshi. Provable representation learning for imitation learning via bi-level optimization. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pp. 367–376. PMLR, 2020.

Kavosh Asadi, David Abel, and Michael L. Littman. Learning state abstractions for transfer in continuous control. *CoRR*, abs/2002.05518, 2020.

Mariusz Bojarski, Davide Del Testa, Daniel Dworakowski, Bernhard Firner, Beat Flepp, Prasoon Goyal, Lawrence D. Jackel, Mathew Monfort, Urs Muller, Jiakai Zhang, Xin Zhang, Jake Zhao, and Karol Zieba. End to end learning for self-driving cars. *CoRR*, abs/1604.07316, 2016.

David Brandfonbrener, Rémi Tachet des Combes, and Romain Laroche. Deep-SPIBB: Scaling up safe policy improvement for offline reinforcement learning. *Proceedings of the 5th Reinforcement Learning and Decision Making (RLDM)*, 2022.

Jacob Buckman, Carles Gelada, and Marc G Bellemare. The importance of pessimism in fixed-dataset policy optimization. In *Proceedings of the 10th International Conference on Learning Representations (ICLR)*, 2021.

Catherine Cang, Aravind Rajeswaran, Pieter Abbeel, and Michael Laskin. Behavioral priors and dynamics models: Improving performance and domain transfer in offline RL. *CoRR*, abs/2106.09119, 2021.

Pablo Samuel Castro, Tyler Kastner, Prakash Panangaden, and Mark Rowland. MICo: Improved representations via sampling-based state similarity for markov decision processes. In *Advances in Neural Information Processing Systems*, 2021.

Xin Chen, Sam Toyer, Cody Wild, Scott Emmons, Ian Fischer, Kuang-Huei Lee, Neel Alex, Steven H Wang, Ping Luo, Stuart Russell, Pieter Abbeel, and Rohin Shah. An empirical investigation of representation learning for imitation. In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 2)*, 2021.

Gheorghe Comanici, Prakash Panangaden, and Doina Precup. On-the-fly algorithms for bisimulation metrics. In *Ninth International Conference on Quantitative Evaluation of Systems, QEST 2012, London, United Kingdom, September 17-20, 2012*, pp. 94–103. IEEE Computer Society, 2012.

Benjamin Eysenbach, Abhishek Gupta, Julian Ibarz, and Sergey Levine. Diversity is all you need: Learning skills without a reward function. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net, 2019.

Norm Ferns, Pablo Samuel Castro, Doina Precup, and Prakash Panangaden. Methods for computing state similarity in markov decision processes. In *UAI '06, Proceedings of the 22nd Conference in Uncertainty in Artificial Intelligence, Cambridge, MA, USA, July 13-16, 2006*. AUAI Press, 2006.

Dylan J Foster, Akshay Krishnamurthy, David Simchi-Levi, and Yunzong Xu. Offline reinforcement learning: Fundamental barriers for value function approximation. 2022.

Justin Fu, Aviral Kumar, Ofir Nachum, George Tucker, and Sergey Levine. D4RL: datasets for deep data-driven reinforcement learning. *CoRR*, abs/2004.07219, 2020.

Scott Fujimoto and Shixiang Shane Gu. A minimalist approach to offline reinforcement learning. In *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 20132–20145, 2021.

Scott Fujimoto, David Meger, and Doina Precup. Off-policy deep reinforcement learning without exploration. In *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pp. 2052–2062. PMLR, 2019.

Vinicius G. Goecks, Gregory M. Gremillion, Vernon J. Lawhern, John Valasek, and Nicholas R. Waytowich. Integrating behavior cloning and reinforcement learning for improved performance in dense and sparse reward environments. In *Proceedings of the 19th International Conference on Autonomous Agents and Multiagent Systems, AAMAS '20, Auckland, New Zealand, May 9-13, 2020*, pp. 465–473. International Foundation for Autonomous Agents and Multiagent Systems, 2020.

O Gottesman, F Johansson, M Komorowski, A Faisal, D Sontag, F Doshi-Velez, and LA Celi. Guidelines for reinforcement learning in healthcare. *Nature medicine*, 25:16–18, 2019.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre H. Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Ávila Pires, Zhaohan Guo, Mohammad Gheshlaghi Azar, Bilal Piot, Koray Kavukcuoglu, Rémi Munos, and Michal Valko. Bootstrap your own latent - A new approach to self-supervised learning. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.

Danijar Hafner, Timothy P. Lillicrap, Ian Fischer, Ruben Villegas, David Ha, Honglak Lee, and James Davidson. Learning latent dynamics for planning from pixels. In *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pp. 2555–2565. PMLR, 2019.

Ying Jin, Zhuoran Yang, and Zhaoran Wang. Is pessimism provably efficient for Offline RL? In *Proceedings of the 38th International Conference on Machine Learning (ICML)*, pp. 5084–5096. PMLR, 2021.

Rahul Kidambi, Aravind Rajeswaran, Praneeth Netrapalli, and Thorsten Joachims. MOReL: Model-based offline reinforcement learning. In *Proceedings of the 34th Annual Conference on Neural Information Processing Systems (NeurIPS)*, volume 33, pp. 21810–21823, 2020.

Ilya Kostrikov, Rob Fergus, Jonathan Tompson, and Ofir Nachum. Offline reinforcement learning with fisher divergence critic regularization. In *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pp. 5774–5783. PMLR, 2021.

Ramnandan Krishnamurthy, Aravind S. Lakshminarayanan, Peeyush Kumar, and Balaraman Ravindran. Hierarchical reinforcement learning using spatio-temporal abstractions and deep neural networks. *CoRR*, abs/1605.05359, 2016.

Aviral Kumar, Justin Fu, Matthew Soh, George Tucker, and Sergey Levine. Stabilizing off-policy q-learning via bootstrapping error reduction. In *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pp. 11761–11771, 2019.

Aviral Kumar, Aurick Zhou, George Tucker, and Sergey Levine. Conservative q-learning for offline reinforcement learning. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.

Aviral Kumar, Rishabh Agarwal, Dibya Ghosh, and Sergey Levine. Implicit under-parameterization inhibits data-efficient deep reinforcement learning. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021a.

Aviral Kumar, Rishabh Agarwal, Tengyu Ma, Aaron C. Courville, George Tucker, and Sergey Levine. DR3: value-based deep reinforcement learning requires explicit regularization. *CoRR*, abs/2112.04716, 2021b.

Sascha Lange, Thomas Gabel, and Martin A. Riedmiller. Batch reinforcement learning. In *Reinforcement Learning*, volume 12 of *Adaptation, Learning, and Optimization*, pp. 45–73. Springer, 2012.

Romain Laroche, Paul Trichelair, and Remi Tachet des Combes. Safe policy improvement with baseline bootstrapping. In *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pp. 3652–3661. PMLR, 2019a.

Romain Laroche, Paul Trichelair, and Rémi Tachet des Combes. Safe policy improvement with baseline bootstrapping. In *Proceedings of the 36th International Conference on Machine Learning (ICML)*, 2019b.

Michael Laskin, Aravind Srinivas, and Pieter Abbeel. CURL: contrastive unsupervised representations for reinforcement learning. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pp. 5639–5650. PMLR, 2020.

Alex X. Lee, Anusha Nagabandi, Pieter Abbeel, and Sergey Levine. Stochastic latent actor-critic: Deep reinforcement learning with a latent variable model. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.

Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *CoRR*, abs/2005.01643, 2020.

Hao Liu and Pieter Abbeel. Behavior from the void: Unsupervised active pre-training. In Marc'Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 18459–18473, 2021.

Cong Lu, Philip J. Ball, Tim G. J. Rudner, Jack Parker-Holder, Michael A. Osborne, and Yee Whye Teh. Challenges and opportunities in offline reinforcement learning from visual observations. *CoRR*, abs/2206.04779, 2022.

Clare Lyle, Mark Rowland, and Will Dabney. Understanding and preventing capacity loss in reinforcement learning. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*. OpenReview.net, 2022.

Shie Mannor, Ishai Menache, Amit Hoze, and Uri Klein. Dynamic abstraction in reinforcement learning via clustering. In *Machine Learning, Proceedings of the Twenty-first International Conference (ICML 2004), Banff, Alberta, Canada, July 4-8, 2004*, volume 69 of *ACM International Conference Proceeding Series*. ACM, 2004.

Bogdan Mazoure, Remi Tachet des Combes, Thang Doan, Philip Bachman, and R. Devon Hjelm. Deep reinforcement and infomax learning. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.

Dipendra Misra, Mikael Henaff, Akshay Krishnamurthy, and John Langford. Kinematic state abstraction and provably efficient rich-observation reinforcement learning. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pp. 6961–6971. PMLR, 2020.

Aditya Modi, Jinglin Chen, Akshay Krishnamurthy, Nan Jiang, and Alekh Agarwal. Model-free representation learning and exploration in low-rank mdps. *CoRR*, abs/2102.07035, 2021.

Ofir Nachum and Mengjiao Yang. Provable representation learning for imitation with contrastive fourier features. In *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 30100–30112, 2021a.

Ofir Nachum and Mengjiao Yang. Provable representation learning for imitation with contrastive fourier features. *CoRR*, abs/2105.12272, 2021b.

Kimia Nadjahi, Romain Laroche, and Rémi Tachet des Combes. Safe policy improvement with soft baseline bootstrapping. In *Proceedings of the 17th European Conference on Machine Learning and Principles and Practice of Knowledge Discovery in Databases (ECML-PKDD)*, 2019.

Ashvin Nair, Bob McGrew, Marcin Andrychowicz, Wojciech Zaremba, and Pieter Abbeel. Overcoming exploration in reinforcement learning with demonstrations. In *2018 IEEE International Conference on Robotics and Automation, ICRA 2018, Brisbane, Australia, May 21-25, 2018*, pp. 6292–6299. IEEE, 2018.

Vinod Nair and Geoffrey E. Hinton. Rectified linear units improve restricted boltzmann machines. In *Proceedings of the 27th International Conference on Machine Learning (ICML-10), June 21-24, 2010, Haifa, Israel*, pp. 807–814. Omnipress, 2010.

Deepak Pathak, Pulkit Agrawal, Alexei A. Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017*, volume 70 of *Proceedings of Machine Learning Research*, pp. 2778–2787. PMLR, 2017.

Marek Petrik, Mohammad Ghavamzadeh, and Yinlam Chow. Safe policy improvement by minimizing robust baseline regret. In *Proceedings of the 29th Advances in Neural Information Processing Systems (NIPS)*, 2016.

Dean Pomerleau. Efficient training of artificial neural networks for autonomous navigation. *Neural Comput.*, 3:88–97, 1991.

Aravind Rajeswaran, Vikash Kumar, Abhishek Gupta, Giulia Vezzani, John Schulman, Emanuel Todorov, and Sergey Levine. Learning complex dexterous manipulation with deep reinforcement learning and demonstrations. In *Robotics: Science and Systems XIV, Carnegie Mellon University, Pittsburgh, Pennsylvania, USA, June 26-30, 2018*, 2018.

Paria Rashidinejad, Banghua Zhu, Cong Ma, Jiantao Jiao, and Stuart Russell. Bridging offline reinforcement learning and imitation learning: A tale of pessimism. In *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 11702–11716, 2021.

Harsh Satija, Philip S. Thomas, Joelle Pineau, and Romain Laroche. Multi-objective spibb: Seldonian offline policy improvement with safety constraints in finite mdps. In *Proceedings of the 35th Advances in Neural Information Processing Systems (NeurIPS)*, October 2021.

Max Schwarzer, Nitarshan Rajkumar, Michael Noukhovitch, Ankesh Anand, Laurent Charlin, R. Devon Hjelm, Philip Bachman, and Aaron C. Courville. Pretraining representations for data-efficient reinforcement learning. In *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 12686–12699, 2021a.

Max Schwarzer, Nitarshan Rajkumar, Michael Noukhovitch, Ankesh Anand, Laurent Charlin, R. Devon Hjelm, Philip Bachman, and Aaron C. Courville. Pretraining representations for data-efficient reinforcement learning. *CoRR*, abs/2106.04799, 2021b.

Kajetan Schweighofer, Markus Hofmarcher, Marius-Constantin Dinu, Philipp Renz, Angela Bitto-Nemling, Vihang P. Patil, and Sepp Hochreiter. Understanding the effects of dataset characteristics on offline reinforcement learning. *CoRR*, abs/2111.04714, 2021.

Evan Shelhamer, Parsa Mahmoudieh, Max Argus, and Trevor Darrell. Loss is its own reward: Self-supervision for reinforcement learning. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Workshop Track Proceedings*. OpenReview.net, 2017.

Thiago D. Simão, Romain Laroche, and Rémi Tachet des Combes. Safe policy improvement with estimated baseline bootstrapping. In *Proceedings of the 19th International Conference on Autonomous Agents and Multi-Agent Systems (AAMAS)*, 2020.

Adam Stooke, Kimin Lee, Pieter Abbeel, and Michael Laskin. Decoupling representation learning from reinforcement learning. In *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pp. 9870–9879. PMLR, 2021.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems, IROS 2012*, pp. 5026–5033. IEEE, 2012.

Aäron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *CoRR*, abs/1807.03748, 2018.

Han Wang, Erfan Miahi, Martha White, Marlos C. Machado, Zaheer Abbas, Raksha Kumaraswamy, Vincent Liu, and Adam White. Investigating the properties of neural network representations in reinforcement learning. *CoRR*, abs/2203.15955, 2022.

Lu Wang, Wei Zhang, Xiaofeng He, and Hongyuan Zha. Supervised reinforcement learning with recurrent neural network for dynamic treatment recommendation. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining, KDD 2018, London, UK, August 19-23, 2018*, pp. 2447–2456. ACM, 2018.

Tongzhou Wang and Phillip Isola. Understanding contrastive representation learning through alignment and uniformity on the hypersphere. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pp. 9929–9939. PMLR, 2020.

Yifan Wu, George Tucker, and Ofir Nachum. Behavior regularized offline reinforcement learning. *CoRR*, abs/1911.11361, 2019.

Chenjun Xiao, Ilbin Lee, Bo Dai, Dale Schuurmans, and Csaba Szepesvari. The curse of passive data collection in batch reinforcement learning. In *Proceedings of the 25th International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2022.

Xin Xu, Zhenhua Huang, Daniel Graves, and Witold Pedrycz. A clustering-based graph laplacian framework for value function approximation in reinforcement learning. *IEEE Trans. Cybern.*, 44: 2613–2625, 2014.

Mengjiao Yang and Ofir Nachum. Representation matters: Offline pretraining for sequential decision making. In *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pp. 11784–11794. PMLR, 2021.

Denis Yarats, Rob Fergus, Alessandro Lazaric, and Lerrel Pinto. Reinforcement learning with proto-typical representations. In *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pp. 11920–11931. PMLR, 2021a.

Denis Yarats, Amy Zhang, Ilya Kostrikov, Brandon Amos, Joelle Pineau, and Rob Fergus. Improving sample efficiency in model-free reinforcement learning from images. In *Thirty-Fifth AAAI Conference on Artificial Intelligence, AAAI 2021, Thirty-Third Conference on Innovative Applications of Artificial Intelligence, IAAI 2021, The Eleventh Symposium on Educational Advances in Artificial Intelligence, EAAI 2021, Virtual Event, February 2-9, 2021*, pp. 10674–10681. AAAI Press, 2021b.

Tianhe Yu, Garrett Thomas, Lantao Yu, Stefano Ermon, James Y Zou, Sergey Levine, Chelsea Finn, and Tengyu Ma. MOPO: Model-based offline policy optimization. In *Proceedings of the 34th Annual Conference on Neural Information Processing Systems (NeurIPS)*, volume 33, pp. 14129–14142, 2020.

Tianhe Yu, Aviral Kumar, Rafael Rafailov, Aravind Rajeswaran, Sergey Levine, and Chelsea Finn. COMBO: Conservative offline model-based policy optimization. In *Proceedings of the 35th Annual Conference on Neural Information Processing Systems (NeurIPS)*, volume 34, 2021.

Ekim Yurtsever, Jacob Lambert, Alexander Carballo, and Kazuya Takeda. A survey of autonomous driving: Common practices and emerging technologies. *IEEE Access*, 8:58443–58469, 2020.

Hongyu Zang, Xin Li, and Mingzhong Wang. Simsr: Simple distance-based state representations for deep reinforcement learning. In *Thirty-Sixth AAAI Conference on Artificial Intelligence, AAAI 2022, Thirty-Fourth Conference on Innovative Applications of Artificial Intelligence, IAAI 2022, The Twelveth Symposium on Educational Advances in Artificial Intelligence, EAAI 2022 Virtual Event, February 22 - March 1, 2022*, pp. 8997–9005. AAAI Press, 2022.

Amy Zhang, Rowan Thomas McAllister, Roberto Calandra, Yarin Gal, and Sergey Levine. Learning invariant representations for reinforcement learning without reconstruction. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021a.

Chi Zhang, Sanmukh R. Kuppannagari, and Viktor K. Prasanna. BRAC+: improved behavior regularized actor critic for offline reinforcement learning. In *Asian Conference on Machine Learning, ACML 2021, 17-19 November 2021, Virtual Event*, volume 157 of *Proceedings of Machine Learning Research*, pp. 204–219. PMLR, 2021b.

A NOTATION

Table 3 summarizes our notation.

Table 3: Table of Notation.

Notation	Meaning	Notation	Meaning
ϕ	state encoder network	$\mathcal{A}$	action space
f	predictor network	$\mathcal{Z}$	state representation space
ρ	initial state distribution	n_s	dimension of state space
ζ	effective dimension	n_a	dimension of action space
γ	discounted factor	T	transition probability function
s	state	$\mathcal{D}$	offline dataset
a	action	Ψ	feature matrix
r	reward	$\pi_\beta(a\|s)$	behavior policy of offline dataset
d	the feature dimension	$\pi_{\hat{\beta}}(a\|s)$	the estimated behavior policy
y	state prediction	$d^{\pi_\beta}(s)$	discounted state occupancy density
z	state representation	$V^\pi(s)$	state value function
n	the numbers of datapoints	$\mathcal{J}(\pi)$	the performance of policy π
$\mathcal{S}$	state space	$\mathcal{J}_\perp(\pi)$	the lower bound of the performance

B ADDITIONAL RELATED WORK

Representation learning in Online RL State representation learning lies at the heart of the empirical successes of deep RL. Traditionally, state representation learning has been framed as learning state abstractions / aggregations (Andre & Russell, 2002; Ferns et al., 2006; Mannor et al., 2004; Comanici et al., 2012), and most of these methods aim to reduce the original state space size and to minimize the system complexity. Recent studies present promising results on learning robust representations that can then be used to accelerate policy learning in pixel-based observation spaces. Lee et al. (2020); Yarats et al. (2021b) propose to train deep auto-encoders with a reconstruction loss to learn compact representations, Shelhamer et al. (2017); Hafner et al. (2019) learn state representations from predictive losses to maintain trajectory consistency, van den Oord et al. (2018); Laskin et al. (2020); Stooke et al. (2021) use contrastive losses as auxiliary tasks to improve performance, Xu et al. (2014); Krishnamurthy et al. (2016); Yarats et al. (2021a) develop state clustering methods to improve sample-efficiency, and finally Zhang et al. (2021a); Castro et al. (2021); Zang et al. (2022) measure state distance by bisimulation similarity to shape state representations.

C COMPARISON

C.1 BEHAVIOR CLONING

One would consider BPR is similar to the behavior cloning method that imitates the behavior policy of the data since they both learn a projection from state to action. Despite resembling behavior cloning in form, we emphasize that the goal of BPR is not to approximate the exact behavior policy. Instead, it is a two-stage process that reutilizes the learned encoder on downstream tasks to accelerate policy learning, while discarding the initial projection layer. Additionally, this allows us to apply ℓ_2-normalization to the prediction and action rather than using their true values. This normalization has been shown to be important for representation learning (Wang & Isola, 2020; Grill et al., 2020; Zang et al., 2022). The difference is illustrated in Figure 6.

C.2 FOURIER

Nachum & Yang (2021a) developed a representation objective which combines contrastive learning with linear dynamic model (i.e., a learnable function whose input is the pair of next state and action (s', a), the output is a representation of the current state), where the contrastive objective is approximated by leveraging the Random Fourier Features. Though effective, this method assumes

Figure 6: A summary of the BPR algorithm shows its difference from Behavior Cloning. BPR focus on learning state representation to benefit the downstream Offline RL algorithms instead of concentrating on learning the behavior policy.

the underlying dynamic model being linear, while BPR objective does not show the reliance on such an assumption. Since BPR objective can be oblivious to the reward function and transition model, it can be applied to a wild range of domains where the reward or the transition could be hard to approximate. On the other hand, without modeling the reward function or transition dynamics, BPR objective is slightly theoretical weaker (see the counterexample in appendix). A combination with BPR and the methods like Fourier should be further investigated in the future work, which will provide a more theoretical grounded yet still simple approach.

C.3 ACL

Yang & Nachum (2021) introduced Attentive Contrastive Learning (ACL) to learn state representation, which uses the transformer-based architecture as a skeleton, where a subset of sub-trajectories are randomly masked to make predictions. Similar to the Fourier approach described above, ACL also utilizes contrastive learning objective to update its feature mapping, while further reconstructing the action and the reward to stablize the training. BPR, on the other hand, can be seen as a representation objective that with only a reconstruction module for predicting actions, is far more simple than the transformer-based module that require sequential prediction. Another potential benefit of BPR objective is that it can possibly integrate into other kinds of representation objectives due to its independence from the encoder architecture.

D EFFECTIVE DIMENSION AND FEATURE RANK

The desirable state representation should not only be able to guide a good policy learning procedure, but also be compact enough to provide concise yet effective information. We focus on measuring the "compactness" of the state representation to show that BPR suffices for the agent to benefit from learning representation with auxiliary representation loss, which can alleviate the "implicit underparameterization" phenomenon.

Assumption 4. *(Feature reachability) Denote $\lambda_{\min}(A)$ as the smallest eigenvalue of a positive-definite matrix A. With a mapping function $\phi^\star$, we assume that there exists $\epsilon \in \mathbb{R}^+$ such that,*

$$\sup_\pi \lambda_{\min}\left(\mathbb{E}_{s \sim d^{\pi_\beta}(s)}\left[\phi^\star(s)\phi^\star(s)^\top\right]\right) \geq \epsilon. \tag{7}$$

Assumption 4 posits that in MDP $\mathcal{M}$, for each latent state in representation space $\mathbb{R}^d$, there exists a policy that reaches it with a non-zero probability. This ensures the optimal state representation should have no redundant dimensions, which is a reasonable assumption for a compact latent space.

While similar assumption is commonly made in previous work (Agarwal et al., 2022; Modi et al., 2021), seldom of them consider leveraging it to measure the feature effectiveness. Based on this assumption, we define the following measurement:

Definition 6. *Effective Dimension Let* $\mathrm{ED}(M)$ *denote the multiset of eigenvalues of a square matrix* M*. Then the effective dimension of* Ψ *is defined to be*

$$\zeta(\Psi, \mathcal{D}, \epsilon) = \mathbb{E}_{\mathcal{D}}\left[\left|\left\{\sigma \in ED\left(\left(\frac{1}{\sqrt{|\mathcal{S}||\mathcal{A}|}}\Psi^{\top}\right)\left(\frac{1}{\sqrt{|\mathcal{S}||\mathcal{A}|}}\Psi\right)\right) |\sigma > \epsilon\right\}\right|\right], \qquad (8)$$

where $\Psi \in \mathbb{R}^{|\mathcal{S}||\mathcal{A}| \times d}$ *is the feature matrix with respect to the output of the penultimate layer of the state-action value network.*

Lemma 7. *Let* $\mathbf{X}_n \subset \mathbb{R}^{|\mathcal{S}||\mathcal{A}|}$ *be a set of* n *state-action pairs in* $\mathbb{R}^{|\mathcal{S}||\mathcal{A}|}$ *sampled from a fixed distribution* $d^{\pi_\beta}(s, a)$*, and the corresponding feature matrix being* Ψ_n*, a consistent estimator can be conducted as:*

$$\hat{\zeta}(\Psi, \mathcal{D}, \epsilon) = \left|\left\{\sigma \in ED\left(\left(\frac{1}{\sqrt{n}}\Psi_n\right)^{\top}\left(\frac{1}{\sqrt{n}}\Psi_n\right)\right) |\sigma > \epsilon\right\}\right|. \qquad (9)$$

Proof. The following proof mimics the derivation in Lyle et al. (2022). Recall that

$$\left(\frac{1}{\sqrt{n}}\Psi_n\right)^{\top}\left(\frac{1}{\sqrt{n}}\Psi_n\right) = \frac{1}{n}\sum_{i=1}^{n}\psi(x_i)\psi(x_i)^{\top} \qquad (10)$$

The following property of the expected value holds

$$\mathbb{E}_{\mathcal{D}}\left[\psi(x)\psi(x)^{\top}\right] = \mathbb{E}\left[\frac{1}{n}\sum_{i=1}^{n}\psi(x_i)\psi(x_i)^{\top}\right] \qquad (11)$$

Then, consider each element of the matrix M:

$$\mathbb{E}\left[\left(\psi(x)\psi(x)^{\top}\right)_{ij}\right] = M_{ij} = \mathbb{E}\left[\psi_i(x)\psi_j(x)\right] \implies \sum_{k=1}^{n}\frac{1}{n}\psi_i(x_k)\psi_j(x_k) \overset{a.s.}{\to} M_{ij} \qquad (12)$$

Since we have convergence for any M_{ij}, we get convergence of the resulting matrix to M. And since the eigenvalues are continuous functions of M, the eigenvalues of M_n converge to those of M almost surely. □

Intuitively, it possess the similar equivalent form of feature reachability. Empirically, we set ϵ as 0.01 where only higher eigenvalues are considered, eliminating the distraction caused by small noise. With the effective dimensions measurement, we can show that BPR can stabilize the training procedure, provides higher effective feature dimension for the value network, thus helps to alleviate the "implicit under-parameterization" phenomenon. Notably, Equation 8 can also be used to measure the effective dimension of the state representation, i.e. $\zeta(\Phi, \mathcal{D}, \epsilon)$, when we substitute the feature matrix Ψ by the representation matrix $\Phi \in \mathbb{R}^{|\mathcal{S}| \times |\mathcal{Z}|}$ where $\mathcal{Z}$ is the latent state representation space.

E PROOFS

E.1 USEFUL TECHNICAL RESULTS

We begin this section by introducing Rademacher complexity, which can be used to derive data-dependent upper-bounds on the learnability of function classes.

Definition 8. *Let* $\mathcal{X}$ *be any set,* $X_1, X_2, \cdots, X_n$ *be i.i.d. random variables with values in* $\mathcal{X}$*. We have* $\mathcal{G}$ *a class of functions* $g : \mathcal{X} \to \mathbb{R}$*. The quality*

$$\mathrm{Rad}(\mathcal{G}) := \mathbb{E}_{X_j, \sigma_j}\left[\sup_{g \in \mathcal{G}} \frac{1}{n}\sum_{j=1}^{n}\sigma_j g(X_j)\right] \qquad (13)$$

is called Rademacher complexity of the class $\mathcal{G}$ *on the sample* $X = (X_1, X_2, \cdots, X_n) \in \mathcal{X}^n$*, where* σ *is the Rademacher random variables that are drawn uniformly at random from* $\{\pm 1\}$*.*

The corresponding vectorized version of Rademacher complexity is:

$$\text{Rad}(\mathcal{G}) := \mathbb{E}_{X_j, \sigma_{ji}} \left[\sup_{g \in \mathcal{G}} \frac{1}{n} \sum_{j=1}^{n} \sum_{i=1}^{K} \sigma_{ji} g(X_j)_i \right], \tag{14}$$

where $\mathcal{G}$ is a class of functions $g : \mathcal{X} \to \mathbb{R}^K$.

E.2 THEORETICAL ANALYSIS

Assumption 1. *(1.1) Access to the true behavior: $\pi_{\hat{\beta}} = \pi_{\beta}$. (1.2) Access to the true performance of policies: $\hat{\mathcal{J}}(\pi) = \mathcal{J}(\pi)$ for all policies π. (1.3) The embedding ϕ allows to represent the behavior policy estimate: $\pi_{\hat{\beta}}(a|\phi(s)) = \pi_{\hat{\beta}}(a|s) \in \Pi_{\text{BPR}}$. (1.4) The algorithm performs perfect optimization: $\mathcal{J}_{\text{BPR}} = \max_{\pi \in \Pi_{\text{BPR}}} \hat{\mathcal{J}}(\pi)$.*

Theorem 2. *Under idealized Assumption 1.1-1.4, BPR returns a policy that improves over the behavior policy: $\mathcal{J}_{\text{BPR}} \geq \mathcal{J}(\pi_{\beta})$.*

Proof.

$$\mathcal{J}_{\text{BPR}} = \mathcal{J} \left(\arg\max_{\pi \in \Pi_{\text{BPR}}} \hat{\mathcal{J}}(\pi) \right) \qquad \text{(Assumption 1.4)}$$

$$= \max_{\pi \in \Pi_{\text{BPR}}} \mathcal{J}(\pi) \qquad \text{(Assumption 1.2)}$$

$$\geq \mathcal{J}(\pi_{\hat{\beta}}) \qquad \text{(Assumption 1.3)}$$

$$\geq \mathcal{J}(\pi_{\beta}) \qquad \text{(Assumption 1.1)}$$

which concludes the proof. $\qquad \square$

Assumption 2. *(2.1) Access to an accurate estimate $\pi_{\hat{\beta}}$ of the true behavior β: $\mathcal{J}(\pi_{\beta}) - \mathcal{J}(\pi_{\hat{\beta}}) \leq \epsilon_{\beta}$. (2.2) Access to an accurate estimate $\hat{\Delta}_{\pi, \pi_{\hat{\beta}}}$ of the true policy improvement $\Delta_{\pi, \pi_{\hat{\beta}}}$ for all policies $\pi \in \Pi_{\text{PI}} \cap \Pi_{\text{BPR}}$: $\hat{\Delta}_{\pi, \pi_{\hat{\beta}}} - \Delta_{\pi, \pi_{\hat{\beta}}} \leq \epsilon_{\Delta}$.*

Theorem 3. *Under Assumption 2, BPR returns a policy π_{BPR} with the following performance bounds: $\mathcal{J}_{\text{BPR}} \geq \mathcal{J}(\pi_{\beta}) + \hat{\Delta}_{\pi_{\text{BPR}}, \pi_{\hat{\beta}}} - \epsilon_{\Delta} - \epsilon_{\beta}$.*

Proof.

$$\mathcal{J}_{\text{BPR}} = \mathcal{J}(\pi_{\text{BPR}}) \qquad \text{(by definition)}$$

$$\geq \mathcal{J}(\pi_{\hat{\beta}}) + \hat{\Delta}_{\pi_{\text{BPR}}, \pi_{\hat{\beta}}} - \epsilon_{\Delta} \qquad \text{(Assumption 2.2)}$$

$$\geq \mathcal{J}(\pi_{\beta}) + \hat{\Delta}_{\pi_{\text{BPR}}, \pi_{\hat{\beta}}} - \epsilon_{\Delta} - \epsilon_{\beta} \qquad \text{(Assumption 2.1)}$$

which concludes the proof. $\qquad \square$

Assumption 3. *(3.1) access to a lower bound of the performance $\mathcal{J}_{\perp}(\pi) \leq \mathcal{J}(\pi)$ for all policies, which is tight for $\hat{\beta}$: $\mathcal{J}_{\perp}(\pi_{\hat{\beta}}) \geq \mathcal{J}(\pi_{\hat{\beta}}) - \epsilon_{\perp}$.*

Theorem 4. *Under Assumptions 2.1 and 3.1, BPR returns a policy π_{BPR} with the following performance bounds: $\mathcal{J}_{\text{BPR}} \geq \mathcal{J}(\pi_{\beta}) + \Delta^{\perp}_{\pi_{\text{BPR}}, \pi_{\hat{\beta}}} - \epsilon_{\perp} - \epsilon_{\beta}$.*

Proof.

$$\mathcal{J}_{\text{BPR}} = \mathcal{J}(\pi_{\text{BPR}}) \qquad \text{(by definition)}$$

$$\geq \mathcal{J}_{\perp}(\pi_{\text{BPR}}) \qquad \text{(Assumption 3.1)}$$

$$= \mathcal{J}_{\perp}(\pi_{\hat{\beta}}) + \Delta^{\perp}_{\pi_{\text{BPR}}, \pi_{\hat{\beta}}} \qquad \text{(by definition)}$$

$$\geq \mathcal{J}(\pi_{\hat{\beta}}) + \Delta^{\perp}_{\pi_{\text{BPR}}, \pi_{\hat{\beta}}} - \epsilon_{\perp} \qquad \text{(Assumption 3.1)}$$

$$\geq \mathcal{J}(\pi_{\beta}) + \Delta^{\perp}_{\pi_{\text{BPR}}, \pi_{\hat{\beta}}} - \epsilon_{\perp} - \epsilon_{\beta} \qquad \text{(Assumption 2.1)}$$

which concludes the proof. $\qquad \square$

E.3 Performance bound with BPR objective

BPR solve the optimization problem:

$$\min \frac{1}{n} \sum_{i=1}^{n} \|f(\phi(s_i)) - a_i\|_2 : \phi \in \Phi, f \in \mathcal{F}, \tag{15}$$

where (s_i, a_i) is an i.i.d. sample from the offline dataset with the size of n.

The difference between the estimated behavior policy and the true behavior policy is:

$$\mathbb{E}\left[J(\pi_{\hat{\beta}}) - J(\pi_\beta)|\mathcal{D}\right] = \mathbb{E}_{s \sim \rho}\left[V^{\pi_{\hat{\beta}}}(s) - V^{\pi_\beta}(s)\right]. \tag{16}$$

Lemma 5. *Consider a fixed dataset $\mathcal{D}$ and the reward is bounded by R_{max}, then the difference between $\pi_{\hat{\beta}}$ and π_β will be bounded as:*

$$\mathbb{E}\left[J(\pi_{\hat{\beta}}) - J(\pi_\beta)|\mathcal{D}\right] \leq \frac{2R_{max}}{(1-\gamma)^2} \cdot \mathbb{E}\left[D_{\mathrm{TV}}\left(\pi_{\hat{\beta}}(s)\|\pi_\beta(s)\right)|\mathcal{D}\right] \tag{17}$$

Proof. Recall that the total variation distance (TVD) between the estimated policy $\pi_{\hat{\beta}}$ and the behavior policy π_β for a given state s is defined as:

$$D_{\mathrm{TV}}(\pi_{\hat{\beta}}(s), \pi_\beta(s)) = \sup_{a \in \mathcal{A}} \left|\pi_{\hat{\beta}}(a|s) - \pi_\beta(a|s)\right| = \frac{1}{2} \sum_a \|\pi_{\hat{\beta}}(a|s) - \pi_\beta(a|s)\|_1. \tag{18}$$

We expand the expectation in the value bound:

$$\mathbb{E}_{s \sim \rho}\left[V^{\pi_{\hat{\beta}}}(s) - V^{\pi_\beta}(s)\right]$$

$$\leq \sum_s \rho(s) \left(\sum_a \left|\pi_{\hat{\beta}}(a \mid s) - \pi_\beta(a \mid s)\right| \left(\mathcal{R}(s,a) + \gamma \sum_{s'} T(s,a,s') |V^{\pi_{\hat{\beta}}}(s') - V^{\pi_\beta}(s')|\right)\right)$$

$$= \sum_s \sum_a \rho(s) \left|\pi_{\hat{\beta}}(a \mid s) - \pi_\beta(a \mid s)\right| \left(\mathcal{R}(s,a) + \gamma \sum_{s'} T(s,a,s') |V^{\pi_{\hat{\beta}}}(s') - V^{\pi_\beta}(s')|\right). \tag{19}$$

Apply the upper bound of the value function $R_{max}/(1-\gamma)$ to the above equation:

$$\begin{aligned}
\mathbb{E}\left[J(\pi_{\hat{\beta}}) - J(\pi_\beta)|\mathcal{D}\right] &= \mathbb{E}_{s \sim \rho}\left[V^{\pi_{\hat{\beta}}}(s) - V^{\pi_\beta}(s)\right] \\
&\leq \frac{R_{max}}{1-\gamma} \mathbb{E}_{s \sim \rho}\left[\sum_a \left|\pi_{\hat{\beta}}(a \mid s) - \pi_\beta(a \mid s)\right|\right] \\
&= \frac{2R_{max}}{1-\gamma} \cdot \mathbb{E}\left[\mathbb{E}_{s \sim \rho}\left[D_{\mathrm{TV}}\left(\pi_{\hat{\beta}}(s)\|\pi_\beta(s)\right)\right]|\mathcal{D}\right] \\
&= \frac{2R_{max}}{(1-\gamma)^2} \mathbb{E}_{s \sim d^{\pi_\rho}}\left[D_{\mathrm{TV}}\left(\pi_{\hat{\beta}}(s)\|\pi_\beta(s)\right)\right].
\end{aligned} \tag{20}$$

For simplicity, we denote $\mathbb{E}_{s \sim d^{\pi_\rho}}\left[D_{\mathrm{TV}}\left(\pi_{\hat{\beta}}(s)\|\pi_\beta(s)\right)\right]$ as $\mathbb{E}\left[D_{\mathrm{TV}}\left(\pi_{\hat{\beta}}(s)\|\pi_\beta(s)\right)|\mathcal{D}\right]$. $\square$

This lemma tells us the suboptimality of an arbitrary policy is upper-bounded by the TVD between the optimal policy and itself over the dataset $\mathcal{D}$.

Consider we learn the representation mapping $\phi : \mathcal{S} \to \mathcal{Z}$, and we learn a policy $\pi_\phi : \mathcal{Z} \to \mathcal{A}$ based on the fixed mapping ϕ, instead of learning the policy $\pi : \mathcal{S} \to \mathcal{A}$. The following theorem will provide an upper bound of the suboptimality of the policy π_ϕ[5].

---

[5]Note that we will abuse the notation of π_ϕ, $\pi(\phi(s))$, and $\pi(\cdot|\phi(s))$ for readability and simplicity.

Theorem 5. *With probability at least $1 - \delta$, for any $\delta \in (0, 1)$:*

$$\epsilon_\beta = \mathbb{E}\left[J(\pi_{\hat{\beta}}) - J(\pi_\beta) \,\Big|\, \mathcal{D}\right] \leq CK \cdot \frac{1}{n} \sum_{i=1}^{n} \left\|\pi_\beta(\cdot|s_i) - \pi_{\hat{\beta}}\left(\cdot \mid \phi(s_i)\right)\right\|_2$$

$$+ 2\sqrt{2}K \cdot \mathrm{Rad}(\Phi) + K \cdot \sqrt{\frac{2\ln\frac{1}{\delta}}{n}} \tag{21}$$

where n is the size of the dataset, Rad is the Rademacher complexity, π_β is the behavior policy over the dataset, C is a constant, $K = \frac{R_{max}}{1-\gamma}$.

Proof. The following proves are build on techniques provided by Asadi et al. (2020). First, for $\forall \phi$, we have:

$$\mathbb{E}_{s \sim d^{\pi_\beta}}\left[\left\|\pi_\beta(\cdot \mid s) - \pi_{\hat{\beta}}(\cdot \mid \phi(s))\right\|_1\right] - \frac{1}{n}\sum_{i=1}^{n}\left\|\pi_\beta\left(\cdot \mid s_i\right) - \pi_{\hat{\beta}}\left(\cdot \mid \phi(s_i)\right)\right\|_1 \leq$$

$$\underbrace{\sup_{\phi \in \Phi}\left\{\mathbb{E}_{s \sim d^{\pi_\beta}}\left[\left\|\pi_\beta(\cdot \mid s) - \pi_{\hat{\beta}}(\cdot \mid \phi(s))\right\|_1\right] - \frac{1}{n}\sum_{i=1}^{n}\left\|\pi_\beta\left(\cdot \mid s_i\right) - \pi_{\hat{\beta}}\left(\cdot \mid \phi(s_i)\right)\right\|_1\right\}}_{:=\Xi(s_1,\ldots,s_n)} \tag{22}$$

Lemma 6. *(Asadi et al., 2020) The expected value of Ξ can be bounded as:*

$$\mathbb{E}\left[\Xi\right] \leq 2\sqrt{2}\,\mathrm{Rad}(\Phi), \tag{23}$$

where Rad is the Rademacher complexity.

Given the fact that $|\Xi\left(s_1, \ldots, s_i, \ldots s_n\right) - \Xi\left(s_1, \ldots, s_i', \ldots s_n\right)| \leq \frac{2}{n}$ and apply McDiarmid's inequality, $\forall \delta \in (0, 1)$, we have:

$$\Pr\left(\Xi \leq \mathbb{E}[\Xi] + \sqrt{\frac{2\ln\frac{1}{\delta}}{n}}\right) \geq 1 - \delta \tag{24}$$

Combining Equation 23 and Equation 24 with Equation 22, we get the following holds with probability at least $1 - \delta$:

$$\mathbb{E}_\rho\left[\left\|\pi_\beta(\cdot \mid s) - \pi_{\hat{\beta}}(\cdot \mid \phi(s))\right\|_1\right] \leq \frac{1}{n}\sum_{i=1}^{n}\left\|\pi_\beta\left(\cdot \mid s_i\right) - \pi_{\hat{\beta}}\left(\cdot \mid \phi(s_i)\right)\right\|_1 + 2\sqrt{2}\,\mathrm{Rad}(\Phi) + \sqrt{\frac{2\ln\frac{1}{\delta}}{n}} \tag{25}$$

Now from the left hand side, with the help of Lemma 5, we get:

$$\mathbb{E}\left[J(\pi_{\hat{\beta}}) - J(\pi_\beta)|\mathcal{D}\right] \leq \frac{2R_{\max}}{(1-\gamma)^2} \cdot \mathbb{E}\left[D_{\mathrm{TV}}\left(\pi_{\hat{\beta}}(s)\|\pi_\beta(s)\right)|\mathcal{D}\right]$$

$$= \frac{R_{\max}}{1-\gamma} \cdot \mathbb{E}_\rho\left[\left\|\pi_\beta(\cdot \mid s) - \pi_{\hat{\beta}}(\cdot \mid \phi(s))\right\|_1\right]. \tag{26}$$

And from the right hand side, we have:

$$\frac{1}{n}\sum_{i=1}^{n}\left\|\pi_\beta\left(\cdot \mid s_i\right) - \pi_{\hat{\beta}}\left(\cdot \mid \phi(s_i)\right)\right\|_1 + 2\sqrt{2}\,\mathrm{Rad}(\Phi) + \sqrt{\frac{2\ln\frac{1}{\delta}}{n}}$$

$$\leq C \cdot \frac{1}{n}\sum_{i=1}^{n}\left\|\pi_\beta\left(\cdot \mid s_i\right) - \pi_{\hat{\beta}}\left(\cdot \mid \phi(s_i)\right)\right\|_2 + 2\sqrt{2}\,\mathrm{Rad}(\Phi) + \sqrt{\frac{2\ln\frac{1}{\delta}}{n}} \tag{27}$$

With combining Equation 26 and Equation 27 together, we can conclude the proof:

$$\epsilon_\beta = \mathbb{E}\left[J(\pi_{\hat{\beta}}) - J(\pi_\beta) \,\Big|\, \mathcal{D}\right] \leq C\frac{R_{\max}}{1-\gamma} \cdot \frac{1}{n}\sum_{i=1}^{n}\left\|\pi_\beta(\cdot|s_i) - \pi_{\hat{\beta}}\left(\cdot \mid \phi(s_i)\right)\right\|_2$$

$$+ 2\sqrt{2}\frac{R_{\max}}{1-\gamma} \cdot \mathrm{Rad}(\Phi) + \frac{R_{\max}}{1-\gamma} \cdot \sqrt{\frac{2\ln\frac{1}{\delta}}{n}} \tag{28}$$

with probability at least $1 - \delta$. $\qquad\square$

Note that the second term and the last term do not depend on the exact form of the representation. Minimizing the first term can decrease the different between the learned policy and the behavior policy, where the first term iteself aligns with the optimization problem of BPR (Equation 4), indicating that with BPR objective, we can improve the performance of the policy. And the potential harm of using BPR is bounded by the error ϵ_β that we can control.

F COUNTEREXAMPLE

We consider the following dataset composed of four trajectories τ_1, τ_2, τ_3, and τ_4 in deterministic MDP $m = \langle \{s_0, s_1\}, \{a_0, a_1\}, p_0(s_0) = 1, p, r, \gamma = 1 \rangle$:

$$\mathcal{D} = \left\{ \underbrace{\langle s_0, a_0, s_f, 0\rangle}_{\tau_1}, \underbrace{\langle s_0, a_0, s_f, 0\rangle}_{\tau_2}, \underbrace{\langle s_0, a_1, s_1, 0\rangle, \langle s_1, a_0, s_f, 1\rangle}_{\tau_3}, \underbrace{\langle s_0, a_1, s_1, 0\rangle, \langle s_1, a_1, s_f, 0\rangle}_{\tau_4} \right\},$$

where final state s_f denotes the termination of the trajectory. Then, BPR may collapse s_0 and s_1 to a single embedding z where the estimated behavior policy is uniform:

$$\pi_{\hat\beta}(a_0|z) = \pi_{\hat\beta}(a_1|z) = \pi_{\hat\beta}(a_0|s_0) = \cdots . \tag{29}$$

Then, we have:

$$\mathcal{J}(\pi_{\hat\beta}) = \frac{1}{4} \tag{30}$$

$$\mathcal{J}_{\text{BPR}}(\pi(a_0|z) = 1) = \frac{1}{3} \tag{31}$$

$$\mathcal{J}_{\text{BPR}}(\pi(a_1|z) = 1) = 0 \tag{32}$$

$$\mathcal{J}_{\text{BPR}}(\pi(a_0|z) = 0.5) = \frac{1}{2} \times \frac{1}{3} + \frac{1}{2} \times \frac{2}{3} \times \mathcal{J}_{\text{BPR}}(\pi(a_0|z) = 0.5) \tag{33}$$

$$= \frac{1}{6} + \frac{1}{3} \times \mathcal{J}_{\text{BPR}}(\pi(a_0|z) = 0.5) \tag{34}$$

$$= \frac{3}{2} \times \frac{1}{6} = \frac{1}{4} \tag{35}$$

As a conclusion, with a BPR value, a greedy algorithm would converge to $\pi(a_0|z) = 1$, which has the performance of 0 in the environment MDP m, and is therefore not a policy improvement.

G ALL EXPERIMENTAL RESULTS

G.1 EFFECTIVENESS OF BPR IN D4RL BENCHMARK

Experimental Setup We analyze our proposed method BPR on the D4RL benchmark (Fu et al., 2020) of OpenAI gym MuJoCo tasks (Todorov et al., 2012) which includes a variety of dataset domains that have been commonly used in the Offline RL community. We evaluate our method by integrating it into three Offline RL methods, including: i)TD3+BC agent (Fujimoto & Gu, 2021), which is one of the existing state-of-the-art Offline RL approaches combining Behavior Cloning with TD3 together and has a good balancing on the simplicity and efficiency; ii) CQL agent (Kumar et al., 2020), which learns a conservative Q-function such that the expected value of a policy under this Q-function lower-bounds its true value; iii) EDAC agent (An et al., 2021), which is an uncertainty-based ensemble-diversified Offline RL algorithm. We consider three simulated tasks from the Mujoco control domain with D4RL benchmark (halfcheetah, hopper, and walker2d) and consider the expert and medium-expert datasets. For our experiments, the baseline methods take the raw state as the input of both value network and policy network, while we also pre-training the representations with $100k$ timesteps and then freezing the encoder and taking it as the input during the Offline RL optimization; and follow the standard evaluation procedure as in D4RL benchmark.

Figure 7: Performance comparison on D4RL mujoco dataset.

Figure 8: Performance comparison with different representation objectives on D4RL Mujoco dataset at 100K timestep. x-axis shows the average normalized score over the final 10 evaluations and 6 seeds. Blue dotted lines show the average normalized return without pretraining.

G.2 RESULTS COMPARISON WITH OTHER REPRESENTATION BASELINES

Experimental Setup   The purpose of this experiment is to demonstrate that, when compared to the state-of-the-art representation objectives, BPR still has a competitive advantage. In this experiment, we follow the pretrain-finetune paradigm suggested by Yang & Nachum (2021), i.e., we first pretrain state representations of 100k time steps, then the learned encoder is fixed and applied to the downstream task, which performs the BRAC (Wu et al., 2019) agent for 100K steps. Same as the configuration from Yang & Nachum (2021), we also fix the regularization strengths and policy learning rates in BRAC for all domains. And since representation is more valuable in informative data, our experiment does not include interaction pairs collected by a random policy, but rather has interest in the dataset collected from a learned (or at least partially learned) agent. The experiment is still conducted on the D4RL mujoco tasks, with 16 tasks in total included. In this setting, the pretraining datasets and downstream datasets are the same, determined by a single choice of task. We compare our method to several published leading representation RL algorithms which include: (1) **ACL** (Yang & Nachum, 2021), applys contrastive learning on the transformer-based architecture; (2) **Fourier** (Nachum & Yang, 2021a), is implemented as contrastive learning where the transition dynamics are approximated by an implicit linear model with representations given by random Fourier features; (3) **Forward model**, uses the state representation and the action to predict the reward and next state given a sub-trajectory, where the transition probability is defined as an entropy-based model; (4) **Inverse model**, similar to Forward model but rather use the current state representation and the next state representation to predict the current action; (5) **Contrastive**, learn state representation with contrastive objective.

Analysis   Figure 7 and Figure 8 provides the performance comparison results for BPR and other representation objectives on D4RL mujoco dataset. We find that BPR outperforms or at least is competitive with the previous state-of-the-art methods in the majority of environments. Notably, the variance on expert and medium datasets is much smaller than that on medium-expert and medium-replay datasets, especially for BPR, which indicates that the learned representation is more stable when the dataset is from the same level of the agent. The underlying reason may be that the behavior policy of the mixed dataset could differ even in the same mini-batch in the training stage, which will limit the ability of the neural network to learn the information related to (near) optimal decision making. This suggests that the representation quality could be impacted more by the characteristics of the dataset, than the representation objectives, which confirms the observation of Schweighofer et al. (2021). We also notice that even with the pretrained encoder learned from BPR, there still remains a large performance gap between the BRAC agent and the baseline TD3+BC agent, indicates that despite the representation objective being helpful for Offline RL, choosing the suitable offline agent for different tasks is still essential for improving the performance, which may also partially solve the aforementioned high variance issue of the different dataset. Furthermore, to understand the performance difference of different representation objectives comprehensively, we additionally use uncertainty-aware comparisons for all these methods.

G.3 PRE-TRAINING V.S. CO-TRAINING

Experimental Setup   There are two design choices of representation learning in the experiment: i) learn state representations via pretraining, then freeze the encoder and apply it to the downstream tasks, ii) learn state representations simultaneously with the policy, where both the representation and the policy will be learned shoulder-by-shoulder. One will wonder how does BPR performs with the different design of choices. Here we evaluate both designs for their effectiveness compared to the TD3+BC method. For the first choice, we still set the pretraining stage as 100,000 time steps.

Analysis   Figure 9 shows the performance of three models on D4RL tasks, indicating that BPR objective can improve sample efficiency in most cases. BPR consistently outperforms the baseline method, TD3+BC, for the majority of tasks and has a considerably lower variance, demonstrating that our approach has the advantage of convergence rate and stability. On the walker2d tasks, the baseline method performs better than the model with BPRs, we consider the possible reason could be that the baseline is sufficient to solve this task, therefore adding extra auxiliary losses may in turn damage the performance. Meanwhile, this finding is consistent with our hypothesis that the representation objective becomes more valuable as the difficulty of the task increases. Another impressive result is that compared to co-training BPR objective with the policy, BPR yields more

Figure 9: Performance comparison on D4RL mujoco dataset. The horizontal axis indicates number of environment steps. The vertical axis indicates the normalized cumulative returns. We trained 6 different instances of each algorithm with different random seeds, with each instance performing an evaluation every 5,000 environment steps by computing the average episode return over 10 evaluation episodes. The solid lines represent the mean over the 6 trials.

performance gains and faster convergence under the pretrain-finetune paradigm, illustrating that learning policy from a "good" fixed encoder might be more suitable for Offline RL.

G.4 PERFORMANCE COMPARISON IN V-D4RL BENCHMARK

Experimental Setup: We evaluate our method on a benchmarking suite for Offline RL from visual observations of DMControl suite (DMC) tasks (Lu et al., 2022). We consider three domains of environments (walker-walk, humanoid-walk, and cheetah-run) and two different datasets per environment (medium-expert and expert). We include two baselines from Lu et al. (2022) in this experiment:

- DrQ+BC: combining data augmentation techneques with the TD3+BC method which applies TD3 in offline setting with a regularizing behavioral-cloning term to the policy loss. The policy objective is: $\pi = \underset{\pi}{\mathrm{argmax}}\mathbb{E}_{(s,a)\sim\mathcal{D}}\left[\lambda Q(s,\pi(s)) - (\pi(s) - a)^2\right]$

- DrQ+CQL: adding the regularization in CQL to the Q-function of an actor-critic approach, which is DrQ-v2.

To investigate if BPR learns valuable representation, we pretrain the encoder by using BPR objective for 100k time steps, followed by a fine-tune stage where we keep the encoder fixed and apply two baselines based on the learned encoder.

G.5 PERFORMANCE COMPARISON WITH OTHER REPRESENTATION OBJECTIVES ON VISUAL D4RL BENCHMARK

Experimental Setup We evaluate our method with 4 other representation objectives that are considered as state-of-the-art methods on a benchmarking suite for Offline RL from visual observations of DMControl suite (DMC) tasks (Lu et al., 2022). We note that not all methods have been shown to be effective for visual-based continuous control problems. The baselines include: (i) Temporal contrastive learning methods such as DRIML (Mazoure et al., 2020) and HOMER (Misra et al., 2020); (ii) spatial contrastive approach, CURL (Laskin et al., 2020) (iii) Inverse model, one-step inverse action prediction (Pathak et al., 2017).

Analysis As shown in Figure 10, BPR shows a significant improvement over the other state-of-the-art algorithms, suggesting that BPR objective can improve sample efficiency more effectively than the other representation objectives. It is worth noting that although BPR performs better than

Figure 10: Performance comparison of BPR with several other baselines on DMC environments.

the other approaches on *Humanoid_walk* task, the cumulative return is still low compared to the best agent running on the online settings (about 750), suggesting that further performance improvement may require the development of the more efficient Offline RL algorithms.

G.6 REPRESENTATION AS THE INPUT OF VALUE NETWORK

Experimental Setup As we stated in Section 5, Assumption 2 forbids in theory the use of the BPR representation to estimate the value. In this experiment, the purpose is to show that the utilization of taking BPR representation as the input of the value network is acceptable empirically. We still pretrain the encoder and then fix it, while developing two variants of the architechture afterwards: i) the learned encoder is only used for training the policy network, while the value network takes the raw state as its input; ii) the learned encoder is used as the input of both the policy network and the value network.

Analysis As shown in Figure 11, the performance of the both variants are almost equivalent, which means that $\phi(s)$ is good enough to learn the state-action value empirically. Notably, when taking $\phi(s)$ as the input, the agent will have a lower variance along the training procedure in 2 of 6 tasks, which is the empirical evidence of that $\phi(s)$ as the input of value network is an acceptable choice.

Figure 11: Performance comparison on D4RL mujoco dataset, $\phi(s)$ v.s. s as input of value network.

G.7 VISUAL D4RL BENCHMARK WITH DISTRACTORS

Figure 12: Pixel observations on visual d4rl benchmark with distractors.

We use three levels of distractions (i.e., easy, medium, hard) to evaluate the performance of the model (See Figure 12. Each distractions represents a shift in the data distribution, where we add task-irrelevant visual factors (i.e., backgrounds, agent colors, and camera positions) that vary with environments to disturb the model training.