MimicPlay: Long-Horizon Imitation Learning by Watching Human Play

Abstract: Imitation learning from human demonstrations is a promising paradigm for teaching robots manipulation skills in the real world. However, learning complex long-horizon tasks often requires an unattainable amount of demonstrations. To reduce the high data requirement, we resort to *human play data*—video sequences of people freely interacting with the environment using their hands. Even with different morphologies, we hypothesize that human play data contain rich and salient information about physical interactions that can readily facilitate robot policy learning. Motivated by this, we introduce a hierarchical learning framework named MIMICPLAY that learns latent plans from human play data to guide low-level visuomotor control trained on a small number of teleoperated demonstrations. With systematic evaluations of 14 long-horizon manipulation tasks in the real world, we show that MIMICPLAY dramatically outperforms state-of-the-art imitation learning methods in task success rate, generalization ability, and robustness to disturbances. More details and video results can be found at `https://mimicplaysub.github.io`.

Keywords: Imitation Learning, Learning from Human, Long-Horizon Manipulation

Figure 1: Human is able to complete a long-horizon task much faster than a teleoperated robot. This observation inspires us to develop **MIMICPLAY**, a hierarchical imitation learning algorithm that learns a high-level planner from cheap human play data and a low-level control policy from a small amount of multi-task teleoperated robot demonstrations. We show that MIMICPLAY significantly improves sample efficiency and robustness of imitation learning algorithms in long-horizon tasks.

1 Introduction

Efficiently teaching robots to perform general-purpose manipulation tasks is a long-standing challenge. Imitation Learning (IL) has recently made considerable strides towards this goal, especially through supervised training using either human teleoperated demonstrations or trajectories of expert policies [1, 2]. Despite this promise, IL methods have been confined to learning short-horizon primitives, such as opening a door or picking up a specific object. The time cost and labor intensity of collecting long-horizon

demonstrations, especially for complex real-world tasks with wide initial and goal condition distributions, remains a key barrier to the widespread adoption of IL methods.

Two connected directions have emerged in recent literature to scale up imitation learning to complex long-horizon tasks: *hierarchical imitation learning* and *learning from play data*. The former aims to increase learning sample efficiency by decoupling end-to-end deep imitation learning into the learning of high-level planners and low-level visuomotor controllers [3, 4]. The latter leverages an alternative form of robot training data, named *play data* [5]. Play data is typically collected through human-teleoperated robots interacting with their environment without specific task goals or guidance. Prior works show that data collected this way covers more diverse behaviors and situations compared to typical task-oriented demonstrations [5, 6]. The methods for learning from such play data often seek to uncover such diverse behaviors by training a hierarchical policy [5], where the high-level planner captures the distribution of intent and the low-level policies learn goal-directed control. However, collecting such play data in the real world can be very costly. For example, C-BeT [6] requires 4.5 hours of play data to learn manipulation skills in a specific scene, and TACO-RL [7] needs 6 hours of play data for one 3D tabletop environment.

In this work, we argue that the data required for learning high-level plan and low-level control can come in different forms, and doing so could substantially reduce the cost of imitation learning for complex long-horizon tasks. Based on this argument, we introduce a new learning paradigm, in which robots learn high-level plans from *human play data*, where humans use their hands to interact with the environment freely. Human play data is much faster and easier to collect than robot teleoperation data (Fig. 1). It allows us to collect data *at scale* and cover a wide variety of situations and behaviors. We show that such scalability plays a key role in strong policy generalization. The robot then learns low-level manipulation policies from a small amount of *demonstration data*, which is collected by humans teleoperating with the robots. Unlike human play data, demonstration data is expensive to collect but does not lead to issues due to the mismatch between human and robot embodiments.

To scale imitation learning to long-horizon manipulation tasks, we present MIMICPLAY, a new imitation learning algorithm that leverages the complementary strengths of two data sources mentioned above: human play data and robot teleoperation data. MIMICPLAY trains a goal-conditioned latent planner from *human play data* to predict the future 3D human hand trajectories conditioned on the goal images. Such latent plans provide rich 3D guidance (*what* to do and *where* to interact) at each time step, tackling the challenging long-horizon manipulation problem by converting it into a guided motion generation process. Conditioned on these latent plans, the low-level controller incorporates state information essential for fined-grained manipulation to generate the final actions. We evaluate our method on 14 real-world long-horizon manipulation tasks in six environments. Our results demonstrate significant improvement over state-of-the-art imitation learning methods in terms of sample efficiency and generalization abilities. Moreover, MIMIC-PLAY integrates human motion and robotic skills into a joint latent plan space, which enables an interface that allows using human videos directly as "prompts" for specifying goals in robot manipulation tasks.

To summarize, the main contributions of our work are as follows:

- A **novel paradigm** for learning 3D-aware latent plans from cheap human play data.
- A **hierarchical framework** that trains a plan-guided multi-task robot controller to accomplish challenging long-horizon manipulation tasks sample-efficiently.
- In 14 real-world long-horizon evaluation tasks, MIMICPLAY shows state-of-the-art performance with generalization to novel tasks and robustness against disturbance, which further allows prompting robot motion with simple human videos.

2   Related Work

Imitation learning from demonstrations.   Imitation Learning (IL) has enabled robots to successfully perform various manipulation tasks [8–15]. Traditional IL algorithms such as DMP and PrMP [16–19] enjoy high learning sample efficiency but are limited in their ability to handle high-dimensional observations and settings that require closed-loop control. In contrast, recent IL methods built upon deep neural networks can learn reactive policies from raw demonstration data [20, 2, 3, 21–24]. While these methods offer greater flexibility, they require a large number of human demonstrations to learn even simple

pick-and-place tasks, which remains labor- and resource-intensive [25, 26]. Our work instead proposes to leverage human play data, which does not require robot hardware and can be collected efficiently, to reduce the need for on-robot demonstration data dramatically.

Hierarchical imitation learning. Our idea of learning a hierarchical policy from demonstrations is also related to prior works [27, 3, 5, 4, 28]. However, all previous methods focus on learning both planning and control with a single type of data—teleoperated robot demonstrations, which is expensive to collect. Our approach uses cheap human play data for learning high-level planning and a small number of robot demonstrations for learning low-level control, which significantly strengthens the model's planning capability while keeping a low demand on demonstration data.

Learning from human videos. A plethora of recent research has explored leveraging large-scale human video data to improve robot policy learning [29–39]. Closely related to our work are R3M [40] and MVP [41], which use an Internet-scale human video dataset Ego4D [42] to pretrain visual representations for subsequent imitation learning. However, due to diversity in the data source and large domain gaps, transferring the pre-trained representation to a specific manipulation task might be difficult. Notably, Hansen et al. [43] found simple data augmentation techniques could have similar effects as these pre-trained representations. To reduce the domain gap, another thread of work [29, 44, 35, 45, 34, 46, 47] utilizes in-domain human videos, where human directly interacts with the robot task environment with their own hands. Such type of data has a smaller gap between human and robot domains, which allows sample-efficient reward shaping for training RL agents [35, 45–47] and imitation learning [29, 44, 34]. However, these works focus on learning either task rewards or features from human videos, which doesn't directly help the low-level robot action generation. In this work, we extract meaningful trajectory-level task plans from human play data, which provides high-level guidance for the low-level controller for solving challenging long-horizon manipulation tasks.

Learning from play data. Our idea of leveraging human play data is heavily inspired by learning from play [5, 48, 6], an alternative imitation learning paradigm that focuses on multi-task learning from play data, a form of teleoperated robot demonstration provided without a specific goal. Although play data exhibits high diversity in behavior [5], it requires the laborious teleoperation process (4.5 hours [6] and 6 hours [7]). In this work, we instead learn from human play data, where humans freely interact with the scene with their hands. This method of data collection is not only time-effective, requiring a mere 10 minutes, but it also provides rich trajectory-level guidance for the robot's motion generation. Consequently, the robot only requires a minimal amount of teleoperation data, empirically less than 30 minutes, to translate the guidance into its own motor commands and successfully perform complex long-horizon manipulation tasks.

3 MimicPlay

Training a robot for long-horizon tasks is challenging, as it requires high-level planning to determine *where* and *what* to interact during different task stages, as well as low-level motor controls to handle *how* to achieve the goals. MIMICPLAY is based on the key insight that high-level planning can be effectively learned from human play data that are fast to collect. Meanwhile, low-level control skills are best acquired from teleoperated demonstration data that do not have any embodiment gap. In particular, due to the difference in the embodiments of humans and robots, it is critical to find an intermediate representation that can bridge the gap between the two data sources. MIMICPLAY addresses this challenge by learning a 3D-aware latent planning space to extract diverse plans from cost-effective human play data. The overview of MIMICPLAY is illustrated in Fig. 2.

3.1 Collecting human play data

Human play data. We leverage human play data, where a human operator freely interacts with the scene with one hand driven by their curiosity. For instance, in the kitchen, the operator might open the oven then pull out the tray or pick up a pan and place it on the stove. This type of data contains rich state transitions and implicit human knowledge of objects' affordance and part functionalities. More importantly, collecting human play data is cheaper and much more efficient than teleoperation, as it does not require task labeling or environment resetting and takes only a small fraction of time—a human operator can

(a) Training stage 1 - Learning latent plans   (b) Training stage 2 - Plan-guided imitation learning   (c) Testing stage

Figure 2: Overview of MIMICPLAY. **(a) Training Stage 1**: using cheap *human play data* to train a goal-conditioned trajectory generation model to build a latent plan space that contains high-level guidance for diverse task goals. **(b) Training Stage 2**: using a small amount of *teleoperation data* to train a low-level robot controller conditioned on the latent plans generated by the pre-trained (frozen) planner. **(c) Testing**: Given a single long-horizon task video prompt (either human motion video or robot teleoperation video), MIMICPLAY generates latent plans and guides the low-level controller to accomplish the task.

121   finish a task that would take 90-second robot teleoperation time in just five seconds (Fig. 1). In this work,
122   we collect 10 minutes of human play video as the training dataset for each task environment, which is
123   approximately equivalent to a 3-hour dataset of robot teleoperation video.

124   **Tracking 3D human hand trajectories.**   When performing the play, human constructs a sequence of
125   movements within their mind, then engages its hand to physically interact with the environment. This
126   interaction creates a hand trajectory that contains rich information regarding the individual's underlying
127   intentions. Based on the hand trajectories, the robot can learn to mimic human's motion planning capability
128   by reconstructing the hand trajectory conditioned on the goals. We will show how to train a latent
129   planner from human hand trajectory data in Sec. 3.2. However, common human video datasets comprise
130   single-view observations, providing only 2D hand trajectories. Such trajectories present ambiguities
131   along the depth axis and suffer from occlusions. We instead use two calibrated cameras to track 3D hand
132   trajectories from human play data. We use an off-the-shelf hand detector [49] to identify hand locations
133   from two viewpoints, reconstructing a 3D hand trajectory based on the calibrated camera parameters.
134   Details of the data collection process and system are introduced in the Appendix.

3.2   Learning 3D-aware latent plans from human play data

136   Given a long-term task represented by a goal image, the policy should generate actions conditioned on this
137   goal. We formalize the problem into a hierarchical policy learning task, where a goal-conditioned high-level
138   planner $\mathcal{P}$ distills key features from the goal observation g_t and transforms them into low-dimensional
139   latent plans p_t. These plans are then employed to guide the low-level motor controller toward the goal.
140   However, learning such a vision-based motion planner $\mathcal{P}$ requires a large dataset since it needs to be
141   capable of handling the multimodality inherent in the goal distribution. We address this issue by leveraging
142   a cheap and easy-to-collect data source—*human play data*.

143   **Learning multimodal latent plans.**   With the collected human play data and corresponding 3D hand
144   trajectory $\boldsymbol{\tau}$, we formalize the latent plan learning process as a goal-conditioned 3D trajectory generation
145   task. More specifically, an observation encoder E, implemented as convolutional networks, processes
146   the visual observations o_t^h and goal image g_t^h from the human video $\mathcal{V}^h$ into low-dimensional features,
147   which are further processed by an MLP-based encoder network into a latent plan vector p_t (as shown in
148   Fig. 2(a)). Based on the latent plan p_t and the hand location l_t, an MLP-based decoder network generates
149   the prediction of the 3D hand trajectory. However, simple regression of the trajectory cannot fully cover
150   the rich multimodal distribution of human motions. Even for the same human operator, one task goal can
151   be achieved with different strategies. To address this issue, we use an MLP-based Gaussian Mixture Model
152   (GMM) [50] to model the trajectory distribution from the latent plan p_t. For a GMM as Eq. (1) shows:

$$p(\boldsymbol{\tau}|\boldsymbol{\theta}) = \sum_{\boldsymbol{z}} p(\boldsymbol{\tau}|\boldsymbol{\theta},\boldsymbol{z})p(\boldsymbol{z}|\boldsymbol{\theta}), \tag{1}$$

(a) Kitchen   **(b) Study desk**

(c) Flower   **(d) Whiteboard**   **(e) Sandwich**   **(f) Cloth**

Figure 3: **Evaluation Tasks.** We design six environments with long-horizon tasks for a Franka Emika robot arm, with initial (left) and goal (right) states shown in images. Tasks include: **(a) Kitchen environment**: 3 individual tasks including cooking food with oven. **(b) Study Desk environment**: 7 individual tasks including tidying up the desk. **(c) Flower**: flower insertion into a vase. **(d) Whiteboard**: erasing curve lines. **(e) Sandwich**: ingredient selection for cheeseburger or sandwich. **(f) Cloth**: folding a towel twice. See the Appendix for details.

where $\boldsymbol{\theta} = \{\boldsymbol{\mu}_k, \boldsymbol{\sigma}_k, \eta_k\}_{k=1}^{K}$ are the parameters of the GMM and $p(\boldsymbol{\tau}|\boldsymbol{\theta}, \boldsymbol{z}_k)$ is a Gaussian distribution $\mathcal{N}(\boldsymbol{\tau}|\boldsymbol{\mu}_k, \boldsymbol{\sigma}_k)$ with $\boldsymbol{z}$ consisting of K components. A specific weight η_k represents the probability of the k-th component. GMMs are more expressive than simple MLPs, because they are designed to capture the multi-modality which is inherited in the human play data. The final learning objective of our GMM model is to minimize the negative log-likelihood of the detected 3D human hand trajectory $\boldsymbol{\tau}$ as Eq. (2)

$$\mathcal{L}_{\text{GMM}}(\boldsymbol{\theta}) = -\mathbb{E}_{\boldsymbol{\tau}} \log\left(\sum_{k=1}^{K} \eta_k \mathcal{N}(\boldsymbol{\tau}|\boldsymbol{\mu}_k, \boldsymbol{\sigma}_k)\right), \text{where } 0 \leq \eta_k \leq 1, \sum_{k=1}^{K} \eta_k = 1 \qquad (2)$$

Handling visual gap between human and robot domains. We consider the setup where the human and the robot interact in the same environment. However, different visual appearances (for example, top vs. bottom row in Fig. 1) between human and robot domains pose a challenge in transferring the learned latent planner to the downstream robot policy learning problem. We handle this challenge by introducing a representation matching objective. Given human video frames $o^h \in \mathcal{V}^h$ and frames from a small batch of on-robot data $o^r \in \mathcal{V}^r$ (more detail in Sec. 3.3), we first calculate the feature distribution outputted by the visual encoder E of the human domain $\mathcal{Q}^h = E(o^h)$ and the robot domain $\mathcal{Q}^r = E(o^r)$ in each data batch. We then minimize the distance between $\mathcal{Q}^h$ and $\mathcal{Q}^r$ with a Kullback–Leibler (KL) divergence loss: $\mathcal{L}_{\text{KL}} = D_{\text{KL}}(\mathcal{Q}^r || \mathcal{Q}^h)$. The final loss function for training the latent planner is: $\mathcal{L} = \mathcal{L}_{\text{GMM}} + \lambda \cdot \mathcal{L}_{\text{KL}}$, where λ is a hyperparameter that controls the weights between the two losses.

3.3 Plan-guided multi-task imitation learning

MIMICPLAY focuses on multi-task imitation learning settings, where a single policy is trained to perform multiple tasks conditioned on different goals. Prior works often learn multi-task visuomotor policies end-to-end from scratch [6, 48, 5]. However, given the high dimensionality of the observation and goal image space, these methods require a large amount of teleoperation data for policy training (4.5 hours [6] and 6 hours [7]). In this work, we leverage the latent planner $\mathcal{P}$, pretrained with cost-effective human play data (10 minutes), to condense high-dimensional inputs into low-dimensional latent plan vectors p_t. Since these latent plans p_t can offer rich 3D guidance for formulating low-level robot actions a_t, the low-level policy π can focus on learning the conversion between the low-dimensional plans p_t and actions a_t - a task it can learn efficiently due to the decreased dimensionality. In the following, we introduce how to generate the latent plan p_t and the details of training the plan-guided low-level controller π with a small amount of data.

| | Subgoal (first subgoal) | | | | | | | | Long horizon ($\geq$ 3 subgoals) | | | | | | | |
| | 20 demos | | | | 40 demos | | | | 20 demos | | | | 40 demos | | | |
	Task-1	Task-2	Task-3	ALL	Task-1	Task-2	Task-3	ALL	Task-1	Task-2	Task-3	ALL	Task-1	Task-2	Task-3	ALL
GC-BC (BC-RNN) [20]	0.1	0.0	0.1	0.07	0.1	0.2	0.2	0.17	0.0	0.0	0.0	0.00	0.0	0.0	0.1	0.03
GC-BC (BC-trans) [52]	0.2	0.0	0.0	0.07	0.3	0.7	0.6	0.53	0.0	0.0	0.0	0.00	0.0	0.0	0.1	0.03
C-BeT [6]	0.5	0.6	0.0	0.37	0.4	**1.0**	0.0	0.47	0.0	0.0	0.0	0.00	0.0	0.0	0.0	0.00
LMP [5]	0.3	0.1	0.2	0.20	0.6	0.3	0.2	0.37	0.1	0.0	0.1	0.07	0.3	0.1	0.0	0.13
R3M-BC [40]	0.9	0.0	0.0	0.30	0.5	0.4	0.0	0.30	0.0	0.0	0.0	0.00	0.5	0.0	0.0	0.17
Ours (0% human)	**1.0**	0.5	0.3	0.60	**1.0**	0.5	0.5	0.67	0.3	0.1	0.3	0.23	0.4	0.3	0.5	0.40
Ours	**1.0**	**0.8**	**0.7**	**0.83**	**1.0**	0.9	**0.8**	**0.90**	**0.7**	**0.3**	**0.4**	**0.47**	**0.7**	**0.6**	**0.8**	**0.70**

Table 1: Quantitative evaluation results in the Kitchen environment. For a fair comparison, baseline methods get 10 more training demos than Ours, offsetting their lack of 10-minute human play data.

Video prompting for latent plan generation. Instructing a robot to perform multiple visuomotor long-horizon tasks can be complex due to the need for explicit specifications of multiple subgoals. Our latent planner $\mathcal{P}$, learned from human play videos, is capable of interpolating 3D-aware task-level plans directly from an unlabeled human motion video, which can serve as an intuitive interface for promoting long-horizon robot manipulation. More specifically, we use a one-shot video $\mathcal{V}$ (either human video $\mathcal{V}^h$ or robot video $\mathcal{V}^r$) to prompt the pre-trained latent planner to generate corresponding plans $p_t = \mathcal{P}(o_t, g_t), g_t \in \mathcal{V}$. During training (Fig. 2(b)), we specify the goal image g_t^r ($g_t^r \in \mathcal{V}^r$) as the frame H steps after the input observation o_t^r in the robot demonstration. H is a uniformly sampled integer number within the range of $[200,600]$, which equals 10-30 seconds in wall-clock time. During inference (Fig. 2(c)), given a one-shot task video prompt (either human or robot video), the latent planner samples the goal image from the video and generates a latent plan vector p_t of shape $\mathbb{R}^{1 \times d}$, which is used to guide the generation of low-level robot actions.

Transformer-based plan-guided imitation. Decoupling planning from control allows the low-level policy π to focus on learning *how* to control the robot by following the guidance p_t. The plan-guided imitation learning process is illustrated in Fig. 2(b). However, to execute fine-grained behaviors like grasping an oven handle, merely having high-level guidance is insufficient. It is equally important to consider low-level specifics of the robot end-effector during the action-generation process. Therefore, we convert the robot's wrist camera observation w_t and proprioception data e_t into low-dimensional feature vectors, both with a shape of $\mathbb{R}^{1 \times d}$. We then combine these features with the generated latent plan p_t to create a one-step token embedding $s_t = [w_t, e_t, p_t]$. The sequence of these embeddings over T time steps, $s_{[t:t+T]}$, is processed through a transformer architecture[51] f_{trans}. The transformer-based policy, known for its efficacy in managing long-horizon action generation, produces an embedding of action prediction x_t in an autoregressive manner. The final robot control commands a_t are computed by processing the action feature x_t through a two-layer fully connected network. To address the multimodal distribution of robot actions, we utilize an MLP-based Gaussian Mixture Model (GMM) [50] for action generation. Details regarding the model architecture are outlined in the Appendix.

Multi-task prompting. Learning from human play data enables the planner to handle diverse task goals. We demonstrate this empirically by designing all of our evaluation environments to be multi-task and share the same planner $\mathcal{P}$ and the policy π models across all tasks in the same environment. For each training sample, the prompting video is uniformly sampled from the training videos of the same task category.

4 Experiments

4.1 Experiment setups

Environments and Tasks. We create six environments with 14 tasks for a Franka Emika robot arm (Fig. 3), featuring manipulation challenges like contact-rich tool use, articulated-object handling, high-precision tasks, and deformable object manipulation. Three tasks are designed for the Kitchen environment and four for the Study Desk environment, focusing on long-horizon tasks with different goals. We assess methods using *Subgoal* and *Long horizon* task categories. The Study Desk environment examines compositional generalization with three unseen tasks: *Easy*, *Medium*, and *Hard*. The *Easy* task combines two trained tasks, while the *Medium* and *Hard* tasks require novel motions for unseen subgoal compositions, i.e., the transition from subgoal A to subgoal B is new. For more details about the environments and tasks details, please refer to the Appendix.

	Trained tasks					Unseen tasks			
	Task-1	Task-2	Task-3	Task-4	ALL	Easy	Medium	Hard	ALL
GC-BC (BC-trans) [52]	0.0	0.0	0.0	0.0	0.00	0.0	0.0	0.0	0.00
LMP [5]	0.0	0.0	0.0	0.0	0.00	0.0	0.0	0.0	0.00
Ours (0% human)	0.2	0.3	0.1	0.2	0.20	0.2	0.1	0.0	0.10
Ours (50% human)	0.3	0.4	0.1	0.4	0.30	0.4	0.3	0.1	0.27
Ours (w/o KL)	0.3	**0.7**	0.3	0.2	0.38	0.4	0.2	0.0	0.20
Ours (w/o GMM)	0.4	0.2	0.2	0.3	0.28	0.2	0.0	0.0	0.07
Ours	**0.6**	**0.7**	**0.4**	**0.5**	**0.55**	**0.7**	**0.5**	**0.2**	**0.47**

Table 2: Ablation evaluation results in the Study Desk environment (20 demos).

	Spatial generalization		Extreme long horizon	Deformable	
	Flower	Whiteboard	Sandwich	Cloth	ALL
LMP-single	0.1	0.0	0.1	0.3	0.13
LMP [5]	0.0	0.0	0.0	0.2	0.05
R3M-single	0.2	0.1	0.3	0.4	0.25
R3M [40]	0.1	0.1	0.2	0.2	0.15
Ours-single	**0.5**	**0.5**	0.6	0.7	**0.58**
Ours	0.4	0.2	**0.8**	**0.8**	0.55

Table 3: Quantitative evaluation results of multi-task learning.

Baselines. We compare five existing approaches: 1) GC-BC (BC-RNN) and 2) GC-BC (BC-trans), goal-conditioned behavior cloning algorithms [5] using RNN and GPT-like transformer architectures, respectively; 3) C-BeT [6], a goal-conditioned imitation learning algorithm trained from teleoperated robot play data using Behavior Transformer [53]; 4) LMP [5], an imitation learning algorithm, trained on teleoperated robot play data, manages play motion variability by learning an embedding space; and 5) R3M-BC [40], an imitation learning framework using R3M pre-trained visual representation.

4.2   Results

Learning latent plans from human play data significantly improves performance. Our method outperforms Ours (0% human) by more than 23% in long-horizon task settings over all trained tasks, as shown in both Tab. 1 (ALL) and 2 (Trained tasks ALL). This result showcases that learning a latent plan space does not need to rely fully on teleoperated robot demonstration data. A 10-minute of cheap and unlabelled human play data brings large improvements in the task success rate and sample efficiency.

Hierarchical policy is important for learning long-horizon tasks. Ours (0% human) trained with our two-stage framework outperform prior end-to-end learning methods in the long-horizon task settings by more than 15%, as is shown in Tab. 1 (ALL) and 2 (Trained tasks ALL). This result shows that end-to-end learning for planning and control is less effective than learning to act based on pre-trained latent plans for long-horizon tasks.

Latent plan pre-training benefits multi-task learning. In Tab. 3, we study how each method performs when training each task with a separate model. For end-to-end learning approaches (e.g., LMP and R3M-BC), training task-specific models will lead to better performance (LMP-single vs. LMP; R3M-single vs. R3M). These results showcase the difficulty of learning multiple tasks with a single model. However, our approach has the smallest performance drop in multi-task training (Ours-single vs. Ours). These findings highlight the advantage of learning plan-guided low-level robot motions based on the pre-trained latent plan space. However, we do observe an uneven performance drop with our method (the success rate of the whiteboard task drops from 0.5 to 0.2). We hypothesize this is due to the reason that the length of the demonstration for the whiteboard task is shorter than the other tasks, which leads to an imbalanced training dataset.

GMM is crucial for learning latent plans from human play data. In Tab. 2, our full with GMM model largely outperforms Ours (w/o GMM). Although being trained with full human play data, Ours (w/o GMM) even fails to match the performance of Ours (0% human) in the generalization task settings. We visualize the trajectories generated by all of the model variants in the Appendix, where we found Ours (w/o GMM) has the worst quality of trajectory generation. This result highlights the importance of using the GMM model to handle the multimodal distribution of the hand trajectory when learning the latent plan space from human play data.

Figure 4: Evaluation of multi-task policy prompted with robot/human videos in the Study Desk environment.

KL loss helps minimize the visual gap between human and robot data. In Tab. 2, although Ours (w/o KL) baseline outperforms most baselines in trained tasks, its success rate is 17% lower than Ours. In the generalization setting, Ours (w/o KL) fails to match the performance of Ours (50% human). These results showcase that the visual gap between the human play

data and robot data exists, and KL loss helps close the gap when training the latent planner. More analysis of the distribution shifts between human play data and robot data can be found in the Appendix.

The scale of the human play data matters. In Tab. 2, we compared the model variants with 50% human play data (Ours (50% human)) and found it fails to match the performance of Ours, which has access to 100% human play data. Most critically, in the unseen task settings, using more human play data to cover unseen cases in the training set significantly benefits generalization (Ours vs Ours (50% human)).

Human play data improves generalization to new subgoal compositions. In Tab. 2 unseen tasks, Ours surpasses all baselines by more than 35%. This result highlights that our approach extracts novel latent plans from human play data and guides the robot's low-level policy to generalize to new compositions of subgoals.

An intuitive interface for prompting robot motion with human videos. Fig. 4 shows that our policy model, when prompted with human videos, retains competitive performances as prompted with robot oracle videos

Figure 5: Qualitative visualization of the latent plans before the disturbance and re-planning. **Column 1**: third-person view. **Column 2**: visualization of the latent plan before disturbance. **Column 3**: human disturbance; the red arrow indicts the direction of disturbance. **Column 4**: visualization of real-time re-planning capabilities, which show robustness against disturbance. **Column 5**: robot recovers with the updated task plan.

across three Study Desk tasks. The reason is that MIMICPLAY integrates human motion and robot skills into a joint latent plan space, which enables an intuitive interface for directly specifying robot manipulation goals with human videos. More results can be found in the supplementary video.

Real-time planning capability is robust against disturbance. In Fig. 5, we showcase how our model reacts to unexpected human disturbance. None of these disturbances appears in the teleoperated robot demonstration data. For instance, in the cloth folding task (Fig. 5 third row), the human unfolds the towel after the robot has folded it, and the robot replans and folds the towel again. Since our whole system (including the vision-based latent planner, low-level guided policy, and robot control) is running at a speed of 17Hz, our model is able to achieve real-time re-planning capability against disturbance and manipulation errors. For more details and results, please refer to the supplementary video.

5 Conclusion

We introduce MIMICPLAY, a scalable imitation learning algorithm that exploits the complementary strengths of two data sources: cost-effective human play data and small-scale teleoperated robot demonstration. Using human play data, the high-level controller learns goal-conditioned latent plans by predicting future 3D human hand trajectories given the goal image. Using robot demonstration data, the low-level controller then generates the robot actions from the latent plans. With this hierarchical design, MIMICPLAY outperforms prior arts by over 50% in 14 challenging long-horizon manipulation tasks. MIMICPLAY paves the path for future research to scale up robot imitation learning with affordable human costs.

Existing limitations of the MIMICPLAY include: 1) The current high-level latent plan is learned from scene-specific human play data. The scalability of MIMICPLAY can greatly benefit from training on Internet-scale data. We will explore this direction in future work, and 2) The current tasks are limited to table-top settings. However, humans are mobile and their navigation behaviors contain rich high-level planning information. The current work can be extended to more challenging mobile manipulation tasks.

References

[1] D. A. Pomerleau. Alvinn: An autonomous land vehicle in a neural network. *Advances in neural information processing systems*, 1, 1988.

[2] T. Zhang, Z. McCarthy, O. Jow, D. Lee, X. Chen, K. Goldberg, and P. Abbeel. Deep imitation learning for complex manipulation tasks from virtual reality teleoperation. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pages 5628–5635. IEEE, 2018.

[3] A. Mandlekar, D. Xu, R. Martín-Martín, S. Savarese, and L. Fei-Fei. Learning to generalize across long-horizon tasks from human demonstrations. *arXiv preprint arXiv:2003.06085*, 2020.

[4] K. Shiarlis, M. Wulfmeier, S. Salter, S. Whiteson, and I. Posner. Taco: Learning task decomposition via temporal alignment for control. In *International Conference on Machine Learning*, pages 4654–4663. PMLR, 2018.

[5] C. Lynch, M. Khansari, T. Xiao, V. Kumar, J. Tompson, S. Levine, and P. Sermanet. Learning latent plans from play. In *Conference on robot learning*, pages 1113–1132. PMLR, 2020.

[6] Z. J. Cui, Y. Wang, N. Muhammad, L. Pinto, et al. From play to policy: Conditional behavior generation from uncurated robot data. *arXiv preprint arXiv:2210.10047*, 2022.

[7] E. Rosete-Beas, O. Mees, G. Kalweit, J. Boedecker, and W. Burgard. Latent plans for task-agnostic offline reinforcement learning. *arXiv preprint arXiv:2209.08959*, 2022.

[8] S. Calinon, F. D'halluin, E. L. Sauser, D. G. Caldwell, and A. G. Billard. Learning and reproduction of gestures by imitation. *IEEE Robotics & Automation Magazine*, 17(2):44–54, 2010.

[9] A. Ijspeert, J. Nakanishi, and S. Schaal. Movement imitation with nonlinear dynamical systems in humanoid robots. In *Proceedings 2002 IEEE International Conference on Robotics and Automation (Cat. No.02CH37292)*, volume 2, pages 1398–1403 vol.2, 2002. doi:10.1109/ROBOT.2002.1014739.

[10] S. Schaal. Is imitation learning the route to humanoid robots? *Trends in cognitive sciences*, 3(6): 233–242, 1999.

[11] J. Kober and J. Peters. Imitation and reinforcement learning. *IEEE Robotics & Automation Magazine*, 17(2):55–62, 2010.

[12] P. Englert and M. Toussaint. Learning manipulation skills from a single demonstration. *The International Journal of Robotics Research*, 37(1):137–154, 2018.

[13] C. Finn, T. Yu, T. Zhang, P. Abbeel, and S. Levine. One-shot visual imitation learning via meta-learning. In *Conference on robot learning*, pages 357–368. PMLR, 2017.

[14] A. Billard, S. Calinon, R. Dillmann, and S. Schaal. Robot programming by demonstration. In *Springer handbook of robotics*, pages 1371–1394. Springer, 2008.

[15] B. D. Argall, S. Chernova, M. Veloso, and B. Browning. A survey of robot learning from demonstration. *Robotics and autonomous systems*, 57(5):469–483, 2009.

[16] S. Schaal. Dynamic movement primitives-a framework for motor control in humans and humanoid robotics. In *Adaptive motion of animals and machines*, pages 261–280. Springer, 2006.

[17] J. Kober and J. Peters. Learning motor primitives for robotics. In *2009 IEEE International Conference on Robotics and Automation*, pages 2112–2118. IEEE, 2009.

[18] A. Paraschos, C. Daniel, J. R. Peters, and G. Neumann. Probabilistic movement primitives. In C. Burges, L. Bottou, M. Welling, Z. Ghahramani, and K. Weinberger, editors, *Advances in Neural Information Processing Systems*, volume 26. Curran Associates, Inc., 2013. URL https://proceedings.neurips.cc/paper/2013/file/e53a0a2978c28872a4505bdb51db06dc-Paper.pdf.

[19] A. Paraschos, C. Daniel, J. Peters, and G. Neumann. Using probabilistic movement primitives in robotics. *Autonomous Robots*, 42(3):529–551, 2018.

[20] A. Mandlekar, D. Xu, J. Wong, S. Nasiriany, C. Wang, R. Kulkarni, L. Fei-Fei, S. Savarese, Y. Zhu, and R. Martín-Martín. What matters in learning from offline human demonstrations for robot manipulation. In *5th Annual Conference on Robot Learning*, 2021. URL https://openreview.net/forum?id=JrsfBJtDFdI.

[21] P. Florence, L. Manuelli, and R. Tedrake. Self-supervised correspondence in visuomotor policy learning. *IEEE Robotics and Automation Letters*, 5(2):492–499, 2019.

[22] Y. Zhu, A. Joshi, P. Stone, and Y. Zhu. VIOLA: Object-centric imitation learning for vision-based robot manipulation. In *6th Annual Conference on Robot Learning*, 2022. URL https://openreview.net/forum?id=L8hCfhPbFho.

[23] C. Wang, R. Wang, A. Mandlekar, L. Fei-Fei, S. Savarese, and D. Xu. Generalization through hand-eye coordination: An action space for learning spatially-invariant visuomotor control. In *2021 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 8913–8920. IEEE, 2021.

[24] P. Florence, C. Lynch, A. Zeng, O. Ramirez, A. Wahid, L. Downs, A. Wong, J. Lee, I. Mordatch, and J. Tompson. Implicit behavioral cloning. *Conference on Robot Learning (CoRL)*, 2021.

[25] A. Brohan, N. Brown, J. Carbajal, Y. Chebotar, J. Dabis, C. Finn, K. Gopalakrishnan, K. Hausman, A. Herzog, J. Hsu, J. Ibarz, B. Ichter, A. Irpan, T. Jackson, S. Jesmonth, N. Joshi, R. Julian, D. Kalashnikov, Y. Kuang, I. Leal, K.-H. Lee, S. Levine, Y. Lu, U. Malla, D. Manjunath, I. Mordatch, O. Nachum, C. Parada, J. Peralta, E. Perez, K. Pertsch, J. Quiambao, K. Rao, M. Ryoo, G. Salazar, P. Sanketi, K. Sayed, J. Singh, S. Sontakke, A. Stone, C. Tan, H. Tran, V. Vanhoucke, S. Vega, Q. Vuong, F. Xia, T. Xiao, P. Xu, S. Xu, T. Yu, and B. Zitkovich. Rt-1: Robotics transformer for real-world control at scale. In *arXiv preprint arXiv:2212.06817*, 2022.

[26] brian ichter, A. Brohan, Y. Chebotar, C. Finn, K. Hausman, A. Herzog, D. Ho, J. Ibarz, A. Irpan, E. Jang, R. Julian, D. Kalashnikov, S. Levine, Y. Lu, C. Parada, K. Rao, P. Sermanet, A. T. Toshev, V. Vanhoucke, F. Xia, T. Xiao, P. Xu, M. Yan, N. Brown, M. Ahn, O. Cortes, N. Sievers, C. Tan, S. Xu, D. Reyes, J. Rettinghouse, J. Quiambao, P. Pastor, L. Luu, K.-H. Lee, Y. Kuang, S. Jesmonth, K. Jeffrey, R. J. Ruano, J. Hsu, K. Gopalakrishnan, B. David, A. Zeng, and C. K. Fu. Do as i can, not as i say: Grounding language in robotic affordances. In *6th Annual Conference on Robot Learning*, 2022.

[27] A. Mandlekar, F. Ramos, B. Boots, S. Savarese, L. Fei-Fei, A. Garg, and D. Fox. Iris: Implicit reinforcement without interaction at scale for learning control from offline robot manipulation data. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 4414–4420. IEEE, 2020.

[28] D. Xu, S. Nair, Y. Zhu, J. Gao, A. Garg, L. Fei-Fei, and S. Savarese. Neural task programming: Learning to generalize across hierarchical tasks. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pages 3795–3802. IEEE, 2018.

[29] H. Xiong, Q. Li, Y.-C. Chen, H. Bharadhwaj, S. Sinha, and A. Garg. Learning by watching: Physical imitation of manipulation skills from human videos. In *2021 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 7827–7834. IEEE, 2021.

[30] N. Das, S. Bechtle, T. Davchev, D. Jayaraman, A. Rai, and F. Meier. Model-based inverse reinforcement learning from visual demonstrations. In *Conference on Robot Learning*, pages 1930–1942. PMLR, 2021.

[31] K. Zakka, A. Zeng, P. Florence, J. Tompson, J. Bohg, and D. Dwibedi. Xirl: Cross-embodiment inverse reinforcement learning. In *Conference on Robot Learning*, pages 537–546. PMLR, 2022.

[32] L. Shao, T. Migimatsu, Q. Zhang, K. Yang, and J. Bohg. Concept2robot: Learning manipulation concepts from instructions and human demonstrations. *The International Journal of Robotics Research*, 40(12-14):1419–1434, 2021.

[33] A. S. Chen, S. Nair, and C. Finn. Learning generalizable robotic reward functions from" in-the-wild" human videos. *Robotics: Science and Systems (RSS)*, 2021.

[34] P. Sharma, D. Pathak, and A. Gupta. Third-person visual imitation learning via decoupled hierarchical controller. *Advances in Neural Information Processing Systems*, 32, 2019.

[35] L. Smith, N. Dhawan, M. Zhang, P. Abbeel, and S. Levine. Avid: Learning multi-stage tasks via pixel-level translation of human videos. *arXiv preprint arXiv:1912.04443*, 2019.

[36] K. Schmeckpeper, A. Xie, O. Rybkin, S. Tian, K. Daniilidis, S. Levine, and C. Finn. Learning predictive models from observation and interaction. In *European Conference on Computer Vision*, pages 708–725. Springer, 2020.

[37] A. D. Edwards and C. L. Isbell. Perceptual values from observation. *arXiv preprint arXiv:1905.07861*, 2019.

[38] K. Schmeckpeper, O. Rybkin, K. Daniilidis, S. Levine, and C. Finn. Reinforcement learning with videos: Combining offline observations with interaction. In J. Kober, F. Ramos, and C. Tomlin, editors, *Proceedings of the 2020 Conference on Robot Learning*, volume 155 of *Proceedings of Machine Learning Research*, pages 339–354. PMLR, 16–18 Nov 2021. URL https://proceedings.mlr.press/v155/schmeckpeper21a.html.

[39] K. Shaw, S. Bahl, and D. Pathak. Videodex: Learning dexterity from internet videos. *CoRL*, 2022.

[40] S. Nair, A. Rajeswaran, V. Kumar, C. Finn, and A. Gupta. R3m: A universal visual representation for robot manipulation. In *6th Annual Conference on Robot Learning*, 2022. URL https://openreview.net/forum?id=tGbpgz6yOrI.

[41] T. Xiao, I. Radosavovic, T. Darrell, and J. Malik. Masked visual pre-training for motor control. *arXiv preprint arXiv:2203.06173*, 2022.

[42] K. Grauman, A. Westbury, E. Byrne, Z. Chavis, A. Furnari, R. Girdhar, J. Hamburger, H. Jiang, M. Liu, X. Liu, et al. Ego4d: Around the world in 3,000 hours of egocentric video. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 18995–19012, 2022.

[43] N. Hansen, Z. Yuan, Y. Ze, T. Mu, A. Rajeswaran, H. Su, H. Xu, and X. Wang. On pre-training for visuo-motor control: Revisiting a learning-from-scratch baseline. *arXiv preprint arXiv:2212.05749*, 2022.

[44] Y. Liu, A. Gupta, P. Abbeel, and S. Levine. Imitation from observation: Learning to imitate behaviors from raw video via context translation. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pages 1118–1125. IEEE, 2018.

[45] S. Kumar, J. Zamora, N. Hansen, R. Jangir, and X. Wang. Graph inverse reinforcement learning from diverse videos. *Conference on Robot Learning (CoRL)*, 2022.

[46] M. Sieb, Z. Xian, A. Huang, O. Kroemer, and K. Fragkiadaki. Graph-structured visual imitation. In *Conference on Robot Learning*, pages 979–989. PMLR, 2020.

[47] S. Bahl, A. Gupta, and D. Pathak. Human-to-robot imitation in the wild. *arXiv preprint arXiv:2207.09450*, 2022.

[48] E. Rosete-Beas, O. Mees, G. Kalweit, J. Boedecker, and W. Burgard. Latent plans for task agnostic offline reinforcement learning. In *Proceedings of the 6th Conference on Robot Learning (CoRL)*, 2022.

[49] D. Shan, J. Geng, M. Shu, and D. Fouhey. Understanding human hands in contact at internet scale. In *CVPR*, 2020.

[50] C. M. Bishop. Mixture density networks. 1994.

[51] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

[52] T. Brown, B. Mann, N. Ryder, M. Subbiah, J. D. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

[53] N. M. M. Shafiullah, Z. J. Cui, A. Altanzaya, and L. Pinto. Behavior transformers: Cloning k modes with one stone. *arXiv preprint arXiv:2206.11251*, 2022.

[54] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[55] A. Mandlekar, Y. Zhu, A. Garg, J. Booher, M. Spero, A. Tung, J. Gao, J. Emmons, A. Gupta, E. Orbay, et al. Roboturk: A crowdsourcing platform for robotic skill learning through imitation. In *Conference on Robot Learning*, pages 879–893. PMLR, 2018.

[56] O. Khatib. A unified approach for motion and force control of robot manipulators: The operational space formulation. *IEEE Journal on Robotics and Automation*, 3(1):43–53, 1987. doi:10.1109/JRA. 1987.1087068.

[57] A. Graves and A. Graves. Long short-term memory. *Supervised sequence labelling with recurrent neural networks*, pages 37–45, 2012.

[58] L. van der Maaten and G. Hinton. Visualizing data using t-SNE. *Journal of Machine Learning Research*, 9:2579–2605, 2008. URL http://www.jmlr.org/papers/v9/vandermaaten08a.html.