# How and Why LLMs Generalize: A Fine-Grained Analysis of LLM Reasoning from Cognitive Behaviors to Low-Level Patterns

## Abstract

Large Language Models (LLMs) display strikingly different generalization behaviors: supervised fine-tuning (SFT) often narrows capability, whereas reinforcement-learning (RL) tuning tends to preserve it. The reasons behind this divergence remain unclear, as prior studies have largely relied on coarse accuracy metrics. We address this gap by introducing a novel benchmark that decomposes reasoning into atomic core skills such as calculation, fact retrieval, simulation, enumeration, and diagnostic, providing a concrete framework for addressing the fundamental question of what constitutes reasoning in LLMs. By isolating and measuring these core skills, the benchmark offers a more granular view of how specific cognitive abilities emerge, transfer, and sometimes collapse during post-training. Combined with analyses of low-level statistical patterns such as distributional divergence and parameter statistics, it enables a fine-grained study of how generalization evolves under SFT and RL across mathematical, scientific reasoning, and non-reasoning tasks. Our meta-probing framework tracks model behavior at different training stages and reveals that RL-tuned models maintain more stable behavioral profiles and resist collapse in reasoning skills, whereas SFT models exhibit sharper drift and overfit to surface patterns. This work provides new insights into the nature of reasoning in LLMs and points toward principles for designing training strategies that foster broad, robust generalization.

## 1 Introduction

LLMs fine-tuned with long Chain-of-Thought (CoT) reasoning, DeepSeek-R1 [18], OpenAI-o1 [42], Claude-Sonnet [56], achieve strong results on math and science benchmarks, yet their ability to *generalize* remains fragile. A notable pattern has emerged: models trained with supervised fine-tuning (SFT) often narrow their capability and overfit to surface patterns [54], while those tuned with

Figure 1: Decomposing reasoning into atomic cognitive skills. A spring–block example is solved step by step: fact retrieval, simulation, calculation, and diagnostic, checking each function as an isolated cognitive skill. When combined, these skills form a coherent reasoning trace that enables solving real-world problems, illustrating how complex reasoning emerges from the composition of simpler, specialized components.

reinforcement learning (RL) better preserve or even enhance generalization [23; 52]. The underlying reasons remain unclear, partly because prior studies rely on coarse metrics such as end-to-end accuracy or pass@k, which obscure the behavioral dynamics that drive reasoning success or failure [61; 41].

We argue that reasoning is not a monolithic property but rather an emergent composition of *atomic core skills*, calculation, simulation, fact retrieval, enumeration, and diagnostic self-checking, that interact with statistical patterns acquired during training [28; 39]. Accuracy on a final answer can mask weaknesses in these intermediate skills: a model may recall the correct formula yet incorrectly simulate a process, or arrive at the right solution through superficial pattern matching. Understanding how post-training reshapes these skills is crucial for explaining divergent generalization trends.

**Illustrative Example.** Figure 1 shows a classic spring block problem: a 2 kg block attached to a spring is pulled 0.10 m from equilibrium and released. Solving it requires sequential use of several atomic core skills. The solver first **retrieves** the conservation of energy relation for a spring, then

**simulates** the block's motion as potential energy converts to kinetic, **calculates** the peak speed at the equilibrium point, and finally performs a **diagnostic** of units and boundary conditions. Each skill plays a distinct functional role; failure at any stage breaks the reasoning chain. While not needed in this particular example, a separate **enumeration** skill, systematically listing possible cases or configurations, is equally crucial for comprehensive reasoning, especially in combinatorial or case-based problem settings. This illustrates that what we call "reasoning" in practice is the coordinated composition of such simpler cognitive elements.

Existing benchmarks and analyses fall short of capturing this structure. Large mixed-domain corpora such as *Numina-Math* [32] and *Omni-Math* [17] obscure which skills drive success; controlled datasets like *GSM-Symbolic* [36] and *GSM-PLUS* [33] target narrow sub-skills; and conventional accuracy metrics hide shifts in intermediate behavior [13]. To fill this gap, we introduce a novel benchmark that explicitly decomposes reasoning into atomic core skills across mathematics, scientific reasoning, coding, and non-reasoning tasks, complemented by probes for low-level statistical patterns such as distributional divergence and shifts in word-frequency profiles. This design enables us to track how individual skills and statistical tendencies evolve through the course of post-training.

Our empirical results reveal several findings: (a) **RL preserves balanced cognitive skills.** RL-tuned models maintain rounded radar profiles across core skills: calculation, enumeration, simulation, fact retrieval, and diagnostic, indicating more stable and broad-spectrum reasoning. This balance persists across both in-domain (math) and out-of-domain (e.g., physics) settings. (b) **SFT induces over-specialization and drift.** SFT-tuned models display jagged radar shapes, with strong spikes in a narrow skill (often diagnostic or calculation) but dips below baseline in others, such as simulation and enumeration. This pattern signals over-fitting to surface heuristics and loss of transferable reasoning capacity. (c) **Training objective matters more than parameter magnitude.** The observed divergence arises despite SFT and RL modifying a comparable proportion of model parameters. The difference stems from their optimization objectives, which shape how cognitive skills are retained or distorted during post-training.

Our findings provide a behavioral account of why post-training strategies diverge in their gen-eralization effects and highlight the importance of strengthening atomic core skills as a foundation for robust and interpretable reasoning.

## 2   Related Works

**Post-training for Reasoning in LLMs.** Recent progress in large language models has underscored the importance of specialized post-training strategies, especially fine-tuning for reasoning [65; 54; 49; 35; 48]. Chain-of-thought (CoT) prompting introduced by [61] encourages step-by-step explanation and significantly improves performance on symbolic and multi-step reasoning tasks [34; 29]. Recent extensions such as DeepSeek-R1 (Team, 2025a) combine CoT with reinforcement-learning-based optimization to further enhance reasoning and have achieved state-of-the-art results on math, logic, and competitive programming benchmarks [20; 18].

Post-training methods for reasoning typically fall into two categories: supervised fine-tuning (SFT) and reinforcement-learning-based tuning (RL) [65; 12]. SFT trains models to replicate explicit reasoning traces collected from annotated solutions [60; 61], whereas RL rewards models for accurate and logically coherent reasoning without requiring explicit intermediate supervision [12; 65]. This difference in optimization objective leads to distinct generalization patterns: SFT often narrows the behavioral diversity of models and overfits to surface heuristics [45], whereas RL tends to preserve or even enhance broader reasoning capacities but can introduce reward hacking and biases [43; 8]. Despite these insights, most prior analyses rely primarily on coarse outcome-based metrics such as final-task accuracy, leaving the process-level and representation-level dynamics of post-training effects underexplored.

**Generalization and cross-domain reasoning.** Generalization to tasks or domains outside the training distribution, remains a central challenge for LLMs. This challenge has been extensively studied in discriminative models, where systems often fail under covariate, diversity, or semantic shifts despite strong in-distribution performance [5; 7; 62; 4; 6; 55]. While scaling laws highlight global performance trends across model size and data [26; 21], fine-tuning often induces qualitative shifts in reasoning robustness and error modes [63; 20]. Comparative studies suggest that SFT-dominated reasoning models frequently over-

specialize, losing robustness to new task formats or domains, whereas RL-based fine-tuning helps retain transferable skills [41]. For example, OpenAI's o1 model excels in STEM reasoning but has raised concerns about versatility on other tasks [24]. Recent evaluations emphasize that reasoning-oriented fine-tuning can improve performance on target tasks but sometimes comes at the cost of cross-domain generalization [53; 11]. Our work complements these studies by moving beyond aggregate accuracy to analyze reasoning at a finer granularity. We decompose reasoning into core cognitive behaviors: calculation, simulation, enumeration, fact retrieval, and diagnostic, and reveal how SFT and RL tuning differentially shape these components, providing a clearer account of divergent generalization effects.

**Cognitive behaviors and representation-level shifts.** Accuracy alone can hide weaknesses in intermediate reasoning. We therefore decompose performance into five measurable behaviors, *calculation*, *simulation*, *fact retrieval*, *enumeration*, and *diagnostic checking*, making these skills explicit and comparable across domains and training stages. While BIG-bench, MATH, and related psychometric work touch on similar abilities [51; 20; 30; 16; 46; 27], our framework operationalizes them with targeted prompts and metrics; see also domain-specific analyses such as *From Scores to Skills* in finance [28] and broader links to cognitive science [39].

Fine-tuning not only changes outward behavior but also the internal representations that support it. CoT can elicit more systematic reasoning [61], yet traces may be unfaithful to internal computations [58]. Sparse autoencoders and activation steering reveal interpretable subspaces tied to reasoning features [59; 57]. By jointly measuring behavioral skills and representational structure, we characterize how SFT and RL differentially shape both the internal and external facets of LLM reasoning.

## 3 Decompose "Reasoning" into Fine-grained Cognitive Behaviors

A central question of this study is how different post-training regimes, supervised fine-tuning (SFT) versus reinforcement-learning-based tuning (RL), reshape not only the overall accuracy of large language models (LLMs) but also the composition of their underlying reasoning skills. To answer this, we develop a controlled benchmark and a meta-

Figure 2: Overview of our three-stage benchmark construction pipeline. **(1) Seed Design** defines atomic seeds by domain and behavior; **(2) Candidate Retrieval** expands them via embedding search over public datasets; **(3) Manual Verification** filters for coverage, diversity, and difficulty, yielding a curated benchmark for fine-grained reasoning analysis.

analysis framework that reveals how individual cognitive behaviors evolve under these regimes.

Our approach proceeds in three stages (Figure 2). First, we identify representative model families and collect checkpoints at multiple stages of SFT and RL. Second, we construct a structured benchmark spanning four domains (Mathematics, Scientific Reasoning, Coding, and Non-Reasoning QA) and targeting five core cognitive behaviors: *calculation*, *enumeration*, *simulation*, *fact retrieval*, and *diagnostic checking*. While real-world reasoning typically involves tightly intertwined cognitive skills, our benchmark adopts a controlled decomposition strategy to reduce multi-skill confounds and enable more interpretable analysis of individual behaviors. The goal is not to claim that reasoning is inherently atomic, but rather to isolate dominant skill components that are otherwise difficult to disentangle in fully entangled tasks. Third, we use behavior-focused probes to analyze how training dynamics affect the balance among these sub-skills and associated statistical patterns (e.g., distributional divergence). This controlled design complements end-to-end evaluations by moving beyond aggregate accuracy to trace how SFT and RL redistribute effort across fundamental cognitive behaviors, thereby clarifying their distinct generalization profiles.

### 3.1 Cognitive Grounding and Functional Completeness of Atomic Skills

We define "reasoning" at a functional level as a composition of elementary information-processing operations, rather than in neuroanatomical terms, following classic cognitive accounts of goal-directed problem solving. In the problem-space

Table 1: Example problem templates across four domains and five cognitive behaviors. Representative tasks illustrate the diversity of problem types used to evaluate model capabilities.

| Category | Math Reasoning | Scientific Reasoning | Coding | Non-reasoning |
|---|---|---|---|---|
| **Calculation** | **Definition:** The execution of arithmetic, algebraic, or symbolic operations to derive quantitative or formal results from given inputs. **Example:** Find the second largest prime factor of 49766. | **Classical mechanics:** A proton enters a uniform magnetic field perpendicularly, compute the radius of its circular path. **Magnetism:** In an RC circuit, compute capacitor's charge at a given time after the circuit is closed. | **Matrix primitivity:** Given a non-negative matrix $A \in \mathbb{R}_{\geq 0}^{n \times n}$, decide whether there exists an integer $k \geq 1$ such that $A^k > 0$ **Unique array.** Unique $s$, construct $a, b \geq 0$, $a_i + b_i = s_i$, each unique after removing $\leq \lfloor n/2 \rfloor$ entries. | N/A |
| **Enumeration** | **Definition:** The systematic and exhaustive generation of all elements, cases, or options satisfying a set of explicit constraints. **Example:** You have letters 'q': 4, 'l': 2, 'b': 2. Distribute them into 3 labeled boxes of capacities [4, 2, 2]. How many ways? | **Spin Projection:** 8 non-interacting spin-$\frac{1}{2}$ particles, find number of microstates with total spin projection $M_s = +1$. **Atomic-Orbital Counting:** The number of microstates for a $d^3$ electron configuration consistent with the Pauli principle. | **Set Partitions:** All partitions of $\{1..n\}$ in canonical order; consecutive partitions differ by moving one element between blocks. **Primes in Ranges:** For $t$ queries $[m, n]$ (with $n - m \leq 10^5$), list all primes in each range. | **Rewards program features enumeration:** Create a webpage section listing Eventsfy's Sparks Awards program features. **Article structure enumeration:** Create academic article on integrating ASHA workers into geriatric care and NCD clinic limitations. |
| **Simulation** | **Definition:** The symbolic enactment of a process, system, or sequence of operations to predict or trace its behavior over time. **Example:** Integers $1 - 120$ on board. Each minute replace $n$ by $d(n+3)$, divisor-count. Find total sum on board after 1 day. | **Cooling Process:** An object cools from $90°C$ to ambient $20°C$ Newton's law; compute $T$ after $30\,\text{min}$ with $k = 0.02\,\text{min}^{-1}$. **Decay Chain:** Nuclide $A$ decays to $B$ (half-life 2 h), then $B$ decays to stable $C$ (half-life 8 h); find the time when $B$ peaks. | **Robot Path with One Extra Move.** Given a walk $s$ over $\{W, A, S, D\}$, , insert one move to minimize the bounding box area. **Furlo/Rublo Coin Game.** Replace $x$ by $y \in [\lfloor x/4 \rfloor, \lfloor x/2 \rfloor]$; winner given by xor of Grundy $g(x)$, which periodic in $\log x$. | **Weather Simulator:** A program forecasts weather and suggests clothing based on temperature and rain conditions. **Gaming-related simulation:** Creating a vodcast script analyzing how sound displays mood in the mobile game Pixel Gun 3D. |
| **Fact Retrieval** | **Definition:** (1) Pose the problem naming the required theorem. (2) Pose it without the theorem and check if the model applies it correctly. **Example:** Surface distance on radius r sphere between $(p_1, q_1)$, and $(p_2, q_2)$. | **Cylindrical Capacitor:** Recall the capacitance formula for a long cylindrical capacitor; compute $C$ for $a = 1\,\text{mm}$, $b = 5\,\text{mm}$, $L = 0.5\,\text{m}$. **Bragg's Law:** Recall $2d \sin\theta = n\lambda$; find the smallest $\theta$ for $d = 0.2\,\text{nm}$, $\lambda = 0.15\,\text{nm}$. | **Mixing Rule in the Minimum-Smoke:** When combining adjacent mixtures of colors a and b, what are the smoke produced and the resulting color? **GCD-Constrained BST:** What gcd condition must each edge between adjacent vertices satisfy? | **Cross-Cultural Information Retrieval:** Identify sources for an article on the Alcatraz occupation and Indigenous Peoples' Day. **Procedural Knowledge:** Prerequisites for AP Chemistry topics (stoichiometry, electrochemistry). |
| **Diagnostic** | **Definition:** Diagnostic in LLMs often accompanied by explicit self-check (e.g., "wait", "let's recheck"). **Example:** $f_n = \frac{nx_1 + n^2 x_2}{nx}$ is perturbed as $\frac{nx_1 - n^2 x_2}{nx}$. | **Pursuit of a fox by a hound:** Centripetal-acceleration perturbed with false small-deviation expansion. **Falling hinged rods:** Energy-conservation problem perturbed to suggest small-angle oscillation approach. | **Uniqueness vs. Duplicates:** counting the same solution twice because it appears in different positions. **Optimal vs. Sub-optimal:** Picking the shortest edge next in a path problem that needs full DP. | **Counter-Factual:** "Is tree planting an eco-social activity?" with perturbed response claiming it is not. **Self-contradictory:** Document identifies "Villainous" as Cartoon Network series, then labels incorrectly. |

tradition, reasoning proceeds through a recurrent loop of (i) retrieving relevant knowledge, (ii) generating candidate states or hypotheses, (iii) applying operators that transform internal representations, and (iv) evaluating and monitoring intermediate results to guide control and termination [38; 31; 40].

This functional cycle provides a principled basis for our taxonomy. Fact retrieval instantiates access to declarative knowledge [3; 2]; enumeration corresponds to structured candidate generation and hypothesis search in problem spaces [38; 31]; calculation and simulation partition operator application into symbolic transformation versus model-based rollout of consequences, aligning with mental-model theories of reasoning [25]; and diagnostic checking operationalizes evaluation and metacognitive control, consistent with classical accounts of metacognition, conflict monitoring, and error detection [37; 14; 10; 22].

Under this characterization, the set of five behaviors is complete at our level of analysis: every step in a reasoning trace performs one of these functions, while higher-level reasoning modes such as analogy or abduction arise from structured compositions of these primitives rather than requiring additional atomic categories [31; 25; 37]. For a more detailed theoretical grounding, see Appendix H.

### 3.2 Benchmark Construction

**Principles.** Each item targets a single atomic behavior (calculation, enumeration, simulation, fact retrieval, diagnostic) and is curated for *skill isolation*, coverage, diversity, and calibrated difficulty. Implementation details (templates, keyword lists, perturbations, rubrics) appear in Appendix F.

**Pipeline.** Figure 2 summarizes the process.

1. **Stage 1: Seed Design** creates atomic seeds for each behavior–domain pair, avoiding multi-skill conflation.

2. **Stage 2: Candidate Retrieval** performs embedding-based nearest-neighbor search over large open repositories (e.g., Nemotron [9], Polaris [1], DeepMath [19]) to harvest surface variants that instantiate the same behavior in diverse contexts.

3. **Stage 3: Manual Verification** applies human-in-the-loop filtering for skill isolation, coverage, diversity, and difficulty. The result is a high-fidelity benchmark that decouples reasoning behaviors from surface task formats.

**Behavior Assembly.** *Calculation, Enumeration,*

*Simulation*: template seeds plus keyword queries retrieve items with explicit single-behavior traces from open sources, followed by deduplication and removal of multi-skill bleed. *Fact Retrieval*: select questions whose solution hinges on a named person, theorem, or definition. We use two modes: *Guided* (theorem named in the prompt) and *Unguided* (theorem not named; verify its use in the solution). *Diagnostic*: sample questions and apply minimal perturbations to a valid trace (logical contradiction, dropped condition, counterfactual). The prompt includes the question and the perturbed trace; the model must detect and correct the error (see example in Appendix F.2).

**Difficulty.** Items are bucketed as *easy*, *medium*, or *hard* using: (i) lightweight heuristics (operand scale, step count, constraint breadth, perturbation subtlety); (ii) reference-model success rates; and (iii) human adjustment prioritizing skill purity.

**Prompting (Appendix).** Prompts consist of a standardized instruction header, behavior-specific payload (e.g., theorem tag or perturbed trace), output format, and fixed decoding settings, which are summarized in Appendix F.1.

**Human Evaluation.** We check coverage across (behavior, domain, difficulty) cells, diversity of forms and entities, and the validity of difficulty labels; disagreements are adjudicated.

**Metrics.** The primary metric is **accuracy** under standardized decoding. For Calculation, Enumeration, and Simulation, we use an exact match with unit normalization. For Fact Retrieval, *Guided* requires a correct answer and theorem-consistent steps; *Unguided* requires a correct answer and verified theorem use. For Diagnostic, we require correct answer and explicit identification of self-check.

### 3.3 Behavior–Domain Grid

To support interpretable analysis, we organize the benchmark as a two-dimensional grid crossing five cognitive behaviors with four domains (Table 1). For each behavior–domain cell, the table provides a concise behavior definition and, in most cases, two representative examples. Due to space constraints, the *Math* column anchors the behavior definitions and includes only one representative example per behavior; additional mathematical examples are provided in Appendix J, Table G.

The five behaviors capture complementary facets of reasoning: (1) Calculation: quantitative manipulation of explicit formulas or equations; (2) Enumeration: systematic generation of combinatorial

(a) Math (14B)  (b) Physics (14B)  (c) Math (4B)  (d) Physics (4B)

Figure 3: Radar plots of five cognitive behaviors (calculation, enumeration, simulation, fact retrieval, diagnostic checking). Each panel contrasts SFT (blue) vs. RL (orange) for (a) Math-14B, (b) Physics-14B, (c) Math-4B, and (d) Physics-4B. RL is more balanced; SFT often concentrates on a few skills.

possibilities; (3) Simulation: mental or symbolic rollout of dynamics; (4) Fact Retrieval: access to stored knowledge such as definitions or constants; and (5) Diagnostic: identifying and correcting faulty reasoning or self-contradictions.

For example, calculation tasks range from prime-factor queries in mathematics to computing capacitor charge in physics; enumeration spans classical combinatorics to set partitioning in code; simulation includes Newtonian cooling and other dynamical rollouts; fact-retrieval probes recall of theorems or scientific laws; and diagnostic checking tests recognition of flawed proofs or perturbed reasoning templates. This grid yields comprehensive yet disentangled coverage of reasoning behaviors, enabling us to track how SFT and RL affect each component skill within and across domains.

## 4 Experiments

**Experimental setup.** We evaluate Qwen3-14B-Base and its SFT- and RL-tuned variants, along with smaller Qwen3-4-Base and Qwen3-1.7B-Base counterparts. To analyze training dynamics, we evaluate intermediate checkpoints throughout training. Following models used in [23], the RL model uses the Verl framework [50] with a GRPO setup [47] for RL fine-tuning, optimizing for answer-correctness rewards. The SFT model uses LLaMA-Factory [64] to train on teacher-generated chain-of-thought traces through reject sampling. Evaluation is conducted on the above cognitive skills benchmark using accuracy. Detailed subcategory distributions for the proposed benchmark are provided in Appendix G. More details about training datasets, baseline models, and hyperparameters can be found in Appendix A.

### 4.1 Cognitive-skill Profiles

**RL yields balanced skills and SFT over-specializes.** A striking pattern in Figure 3 is the irregular, jagged shape of the SFT curves com-

(a) Math Domain  (b) Non-reasoning Domain

Figure 4: Radar plots of post-training effects on math (a) and non-reasoning (b) using math-trained models. Both transfer weakly to non-reasoning; RL preserves a more balanced skill profile.

pared to the rounded RL curves. The SFT-tuned models consistently exhibit asymmetric profiles, often showing pronounced spikes in a single skill (most commonly diagnostic) while dipping well below baseline in others, such as enumeration and simulation. This shape reflects a tendency toward over-specialization or over-fitting, where the model exploits superficial patterns in a limited subset of reasoning behaviors rather than maintaining a balanced skill set. For example, in Math-4B, SFT shows a sharp spike on diagnostic, while enumeration and simulation fall below baseline; in Math-14B, it drops below baseline for calculation, simulation, and especially fact retrieval. In contrast, the RL-tuned profiles remain rounded and smoother in performance across all five cognitive behaviors, indicating that reinforcement-learning post-training promotes more even retention of diverse reasoning skills. This shape contrast is informative even when raw accuracy gaps between SFT and RL are modest, emphasizing that the training regime, not merely model scale or base capability, drives these differences in cognitive skill balance. Appendix B provides quantitative evidence using behavior-wise accuracies and smoothness metrics, confirming that RL yields significantly more balanced cognitive-skill profiles than SFT.

**Long CoT rebalances SFT toward systematic reasoning.** Prior work shows that SFT with teach-

(a) Math (think vs no think)    (b) Physics (think vs no think)

Figure 5: Shape comparison of SFT profiles with thinking (orange) vs no thinking (blue) on (a) Math and (b) Physics. Compared to the think model, the no-think model is even more spiky and calculation-dominated. All models are derived from the Qwen3-14B base; SFT and RL share the same base.

Figure 6: Skewness–kurtosis of logit weights across layers. RL shifts distributions from near-Gaussian (layer 3) to heavy-tailed, structured patterns (layer 32). At layer 16, base is compact and symmetric, SFT slightly broadens, while RL introduces more dispersed, structured variations.

ers in thinking mode, producing long CoT data, generally outperforms SFT with short CoT [23]. Figure 5 compares SFT skill profiles under think vs. no-think modes for Math and Physics. The no-think models spike on calculation but lag on simulation, diagnostic checking, and enumeration, whereas long-CoT models exhibit more rounded profiles, redistributing capacity toward complementary processes essential for multi-step reasoning. This effect is especially pronounced in the out-of-domain Physics setting, where long CoT reduces calculation dominance and strengthens other components. Overall, long-CoT training reshapes not only absolute performance but also the geometry of skill profiles, yielding more systematic, transferable reasoning behaviors.

### 4.2 Cross-Domain Generalization

**RL preserves a more balanced skill mix and degrades less than SFT under cross-domain transfer.** Prior work [23] shows that both RL and SFT degrade when transferring from math to non-reasoning domains, but RL typically degrades less and maintains a more balanced skill profile. As shown in Figure 4, RL-tuned models exhibit smoother, more uniform radar shapes in the non-reasoning setting, whereas SFT displays irregular profiles with sharp spikes and drops across skills. This contrast suggests that RL post-training acts as a regularizer that preserves general reasoning competencies, while SFT tends to overfit to math-specific patterns at the expense of cross-domain transfer. Although absolute gains remain limited outside math, RL consistently retains broader cognitive behaviors under domain shift.

### 4.3 Behaviors to Sparse Latent Features

**Shallow layers are near-Gaussian; deeper layers become heavier-tailed across base, SFT, and RL.**

We analyze joint skewness–kurtosis of SAE [15] latent weight distributions to characterize how training regimes reshape higher-order structure. In shallow layers, the base model is approximately symmetric and near-Gaussian, indicating relatively homogeneous activations, while SFT introduces mild increases in skewness and kurtosis consistent with modest sharpening of feature selectivity. With depth, all three models transition toward heavier-tailed, non-Gaussian regimes, reflecting growing feature specialization. RL slightly amplifies this trend, exhibiting broader skewness–kurtosis dispersion, but does not induce a qualitatively different latent regime. Overall, RL increases heterogeneity and sparsity while preserving the depth-dependent progression present in the base and SFT models.

**Interpretable subspaces tied to reasoning-related features.** Figure 7 uses sparse autoencoders (SAEs) [15] to analyze Qwen3-4B and its SFT/RL variants, revealing behavior-aligned latent subspaces. We focus on Layer 16, the model midpoint, where representations are most compositional and provide a stable basis for comparison. At this depth, both post-training strategies selectively reallocate capacity toward knowledge access (*Fact Retrieval*) and self-verification (*Diagnostic*), while *Calculation* and *Simulation* remain largely stable and *Enumeration* stays sparse. Across depth in the base model, *Calculation* and *Simulation* increase gradually, whereas *Fact Retrieval* and *Diagnostic* follow a U-shaped trajectory, prominent in early and late layers. Together, these trends suggest a functional pipeline, retrieval and checking in early and deep layers, transformation in mid layers, with post-training amplifying retrieval and diagnostic subspaces without disrupting core computational circuits. These patterns also generalize to physics-

(a) Different Strategy

(b) Different Layers

Figure 7: SAE-based cognitive-feature composition across strategies and layers. We train sparse autoencoders (SAEs) on hidden states for different models (Base, SFT, RL) and layers, then compute the fraction of SAE features aligned with five cognitive behaviors: Calculation, Enumeration, Simulation, Fact Retrieval, and Diagnostic. Panel (a) compares post-training strategies at layer 16; panel (b) shows layer-wise trends for the Base model.

| Metric | SFT (no-think) | SFT (think) | RL |
|---|---|---|---|
| *Global parameter shift vs. Qwen3-14B base* | | | |
| Changed parameters (#) | $1.44 \times 10^9$ | $1.44 \times 10^9$ | $1.44 \times 10^9$ |
| Change percentage (%) | 97.83 | 97.80 | 97.81 |
| Total change magnitude | 29 462.2 | 29 033.8 | 29 134.1 |
| Average change magnitude | 66.51 | 65.54 | 65.77 |
| Maximum change magnitude | 1 544.5 | 1 540.9 | 1 556.3 |
| *Distribution of change across major components* | | | |
| Embed tokens change (%) | 97.04 | 97.04 | 97.03 |
| Layer-wise change (%) | 97.87 | 97.84 | 97.94 |
| Norm change (%) | 55.23 | 55.23 | 55.23 |
| LM-head change (%) | 97.89 | 97.88 | 97.94 |

Table 2: Parameter-space shifts of Qwen3-14B under SFT (no-think/think) and RL relative to the base. All methods update a similar share of parameters with comparable magnitudes, and changes are distributed similarly across embeddings, layers, norms, and the LM head, indicating that behavioral differences stem from training objectives rather than update scope.

domain reasoning (Appendix E).

### 4.4 Low-Level Statistics & Surface Patterns

**Parameter-space shifts under post-training.** To quantify post-training effects, we measure the fraction of parameters updated and their shift magnitudes for Qwen3-14B variants. As Table 2 shows, roughly 98% of parameters change in every variant, indicating that updates are pervasive rather than sparse. RL's total change magnitude is slightly below SFT (no-think) and comparable to SFT (think), suggesting that reward-based tuning does not necessarily induce larger global perturbations.

**Component-level differences.** Decomposing changes by module (Table 2) shows that embeddings and transformer layers account for most shifts across regimes, while normalization layers change much less (55.23%). Although the overall update magnitudes remain comparable between SFT and RL, RL exhibits a slightly larger maximum shift in the LM head than SFT (think). We interpret this as consistent with the RL objective, which directly optimizes the output distribution through reward signals on generated responses and may therefore induce relatively stronger adjustments near the final prediction layers. Importantly, this difference is localized rather than indicative of a broader increase in parameter shifts across the network.

## 5 Conclusion

We introduce a controlled benchmark that decomposes LLM reasoning into five core cognitive behaviors: calculation, enumeration, simulation, fact retrieval, and diagnostic checking across mathematics, scientific reasoning, coding, and non-reasoning QA. Our three-stage pipeline enables reproducible and interpretable analysis of how post-training reshapes these skills. Our results reveal three key findings. First, RL-tuned models maintain a more balanced distribution of cognitive skills, supporting broader generalization. Second, SFT often induces over-specialization, strengthening narrow abilities such as diagnostic checking while weakening others like simulation. Third, these differences stem primarily from the training objective rather than model scale. We discuss the complementary roles of SFT and RL in Appendix C.

These findings suggest that future reasoning-oriented LLMs should prioritize balanced skill development alongside aggregate accuracy. Promising directions include behavior-aware objectives to prevent skill collapse, curriculum strategies that reinforce both domain-specific and transferable skills, and representation-level methods such as sparse autoencoders and activation steering to monitor and guide reasoning-related subspaces. By revealing how post-training reshapes cognitive behaviors, our benchmark offers a path toward more robust, interpretable, and transferable reasoning systems.

## Limitations

Our analysis leverages SAEs to link behavior-level signals to internal features; while informative, current SAEs techniques are compute-heavy and sensitive to design choices (e.g., hookpoints, sparsity targets). We therefore treat them as high-fidelity but non-definitive probes. A next step is to develop lightweight methods that still connect low-level statistics to hidden representations.

## References

[1] Chenxin An, Zhihui Xie, Xiaonan Li, Lei Li, Jun Zhang, Shansan Gong, Ming Zhong, Jingjing Xu, Xipeng Qiu, Mingxuan Wang, and Lingpeng Kong. 2025. Polaris: A post-training recipe for scaling reinforcement learning on advanced reasoning models.

[2] John R Anderson. 2014. *Rules of the mind*. Psychology Press.

[3] John R Anderson and Christian J Lebiere. 2014. *The atomic components of thought*. Psychology Press.

[4] Haoyue Bai, Yifei Ming, Julian Katz-Samuels, and Yixuan Li. Hypo: Hyperspherical out-of-distribution generalization. In *The Twelfth International Conference on Learning Representations*.

[5] Haoyue Bai, Rui Sun, Lanqing Hong, Fengwei Zhou, Nanyang Ye, Han-Jia Ye, S-H Gary Chan, and Zhenguo Li. 2021. Decaug: Out-of-distribution generalization via decomposed feature representation and semantic augmentation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 6705–6713.

[6] Haoyue Bai, Jifan Zhang, and Robert Nowak. 2024. Aha: Human-assisted out-of-distribution generalization and detection. *Advances in Neural Information Processing Systems*, 37:33863–33890.

[7] Haoyue Bai, Fengwei Zhou, Lanqing Hong, Nanyang Ye, S-H Gary Chan, and Zhenguo Li. 2021. Nas-ood: Neural architecture search for out-of-distribution generalization. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 8320–8329.

[8] Yuntao Bai, Saurav Kadavath, Sandipan Kundu, and 1 others. 2022. Constitutional ai: Harmlessness from ai feedback. *arXiv preprint arXiv:2212.08073*.

[9] Akhiad Bercovich, Itay Levy, Izik Golan, Mohammad Dabbah, Ran El-Yaniv, Omri Puny, Ido Galil, Zach Moshe, Tomer Ronen, Najeeb Nabwani, and 1 others. 2025. Llama-nemotron: Efficient reasoning models. *arXiv preprint arXiv:2505.00949*.

[10] Matthew M Botvinick, Todd S Braver, Deanna M Barch, Cameron S Carter, and Jonathan D Cohen. 2001. Conflict monitoring and cognitive control. *Psychological review*, 108(3):624.

[11] Zhoujun Cheng, Shibo Hao, Tianyang Liu, Fan Zhou, Yutao Xie, Feng Yao, Yuexin Bian, Yonghao Zhuang, Nilabjo Dey, Yuheng Zha, and 1 others. 2025. Revisiting reinforcement learning for llm reasoning from a cross-domain perspective. *arXiv preprint arXiv:2506.14965*.

[12] Tianzhe Chu, Yuexiang Zhai, Jihan Yang, Shengbang Tong, Saining Xie, Dale Schuurmans, Quoc V Le, Sergey Levine, and Yi Ma. 2025. Sft memorizes, rl generalizes: A comparative study of foundation model post-training. *arXiv preprint arXiv:2501.17161*.

[13] Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, and 1 others. 2021. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*.

[14] Jonathon D Crystal and Allison L Foote. 2011. Evaluating information-seeking approaches to metacognition. *Current zoology*, 57(4):531–542.

[15] Hoagy Cunningham, Aidan Ewart, Logan Riggs, Robert Huben, and Lee Sharkey. 2023. Sparse autoencoders find highly interpretable features in language models. *arXiv preprint arXiv:2309.08600*.

[16] Kanishk Gandhi, Ayush Chakravarthy, Anikait Singh, Nathan Lile, and Noah D Goodman. 2025. Cognitive behaviors that enable self-improving reasoners, or, four habits of highly effective stars. *arXiv preprint arXiv:2503.01307*.

[17] Bofei Gao, Feifan Song, Zhe Yang, Zefan Cai, Yibo Miao, Qingxiu Dong, Lei Li, Chenghao Ma, Liang Chen, Runxin Xu, and 1 others. 2024. Omnimath: A universal olympiad level mathematic benchmark for large language models. *arXiv preprint arXiv:2410.07985*.

[18] Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, and 1 others. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

[19] Zhiwei He, Tian Liang, Jiahao Xu, Qiuzhi Liu, Xingyu Chen, Yue Wang, Linfeng Song, Dian Yu, Zhenwen Liang, Wenxuan Wang, and 1 others. 2025. Deepmath-103k: A large-scale, challenging, decontaminated, and verifiable mathematical dataset for advancing reasoning. *arXiv preprint arXiv:2504.11456*.

[20] Dan Hendrycks, Collin Burns, Steven Basart, and 1 others. 2021. Measuring massive multitask language understanding. In *International Conference on Learning Representations (ICLR)*.

[21] Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, and 1 others. 2022. Training compute-optimal large language models. *arXiv preprint arXiv:2203.15556*.

[22] Clay B Holroyd and Michael GH Coles. 2002. The neural basis of human error processing: reinforcement learning, dopamine, and the error-related negativity. *Psychological review*, 109(4):679.

[23] Maggie Huan, Yuetai Li, Tuney Zheng, Xiaoyu Xu, Seungone Kim, Minxin Du, Radha Poovendran, Graham Neubig, and Xiang Yue. 2025. Does math reasoning improve general llm capabilities? understanding transferability of llm reasoning. *arXiv preprint arXiv:2507.00432*.

[24] Aaron Jaech, Adam Kalai, Adam Lerer, Adam Richardson, Ahmed El-Kishky, Aiden Low, Alec Helyar, Aleksander Madry, Alex Beutel, Alex Carney, and 1 others. 2024. Openai o1 system card. *arXiv preprint arXiv:2412.16720*.

[25] Philip N Johnson-Laird. 2010. Mental models and human reasoning. *Proceedings of the National Academy of Sciences*, 107(43):18243–18250.

[26] Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B Brown, and 1 others. 2020. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*.

[27] Jiayi Kuang, Haojing Huang, Yinghui Li, Xinnian Liang, Zhikun Xu, Yangning Li, Xiaoyu Tan, Chao Qu, Meishan Zhang, Ying Shen, and 1 others. 2026. Atomic thinking of llms: Decoupling and exploring mathematical reasoning abilities. *Advances in Neural Information Processing Systems*, 38:166142–166167.

[28] Ziyan Kuang, Feiyu Zhu, Maowei Jiang, Yanzhao Lai, Zelin Wang, Zhitong Wang, Meikang Qiu, Jiajia Huang, Min Peng, Qianqian Xie, and 1 others. 2025. From scores to skills: A cognitive diagnosis framework for evaluating financial large language models. *arXiv preprint arXiv:2508.13491*.

[29] Nathan Lambert, Jacob Morrison, Valentina Pyatkin, Shengyi Huang, Hamish Ivison, Faeze Brahman, Lester James V Miranda, Alisa Liu, Nouha Dziri, Shane Lyu, and 1 others. 2024. Tulu 3: Pushing frontiers in open language model post-training. *arXiv preprint arXiv:2411.15124*.

[30] Andrew K Lampinen, Ishita Dasgupta, Stephanie CY Chan, Kory Matthewson, Michael Henry Tessler, Antonia Creswell, James L McClelland, Jane X Wang, and Felix Hill. 2022. Can language models learn from explanations in context? *arXiv preprint arXiv:2204.02329*.

[31] Pat Langley, Lorenzo Magnani, Christian Schunn, and Paul Thagard. 2005. An extended theory of human problem solving. In *Proceedings of the annual meeting of the cognitive science society*, volume 27.

[32] Jia Li, Edward Beeching, Lewis Tunstall, Ben Lipkin, Roman Soletskyi, Shengyi Costa Huang, Kashif Rasul, Longhui Yu, Albert Jiang, Ziju Shen, Zihan Qin, Bin Dong, Li Zhou, Yann Fleureau, Guillaume Lample, and Stanislas Polu. 2024. Numinamath. [https://huggingface.co/AI-MO/NuminaMath-1.5](https://github.com/project-numina/aimo-progress-prize/blob/main/report/numina_dataset.pdf).

[33] Qintong Li, Leyang Cui, Xueliang Zhao, Lingpeng Kong, and Wei Bi. 2024. Gsm-plus: A comprehensive benchmark for evaluating the robustness of llms as mathematical problem solvers. *arXiv preprint arXiv:2402.19255*.

[34] Shayne Longpre, Le Hou, Tu Vu, Albert Webson, Hyung Won Chung, Yi Tay, Denny Zhou, Quoc V Le, Barret Zoph, Jason Wei, and 1 others. 2023. The flan collection: Designing data and methods for effective instruction tuning. In *International Conference on Machine Learning*, pages 22631–22648. PMLR.

[35] Kohsei Matsutani, Shota Takashiro, Gouki Minegishi, Takeshi Kojima, Yusuke Iwasawa, and Yutaka Matsuo. 2025. Rl squeezes, sft expands: A comparative study of reasoning llms. *arXiv preprint arXiv:2509.21128*.

[36] Iman Mirzadeh, Keivan Alizadeh, Hooman Shahrokhi, Oncel Tuzel, Samy Bengio, and Mehrdad Farajtabar. 2024. Gsm-symbolic: Understanding the limitations of mathematical reasoning in large language models. *arXiv preprint arXiv:2410.05229*.

[37] Thomas O Nelson. 1990. Metamemory: A theoretical framework and new findings. In *Psychology of learning and motivation*, volume 26, pages 125–173. Elsevier.

[38] Allen Newell, Herbert Alexander Simon, and 1 others. 1972. *Human problem solving*, volume 104. Prentice-hall Englewood Cliffs, NJ.

[39] Qian Niu, Junyu Liu, Ziqian Bi, Pohsun Feng, Benji Peng, Keyu Chen, Ming Li, Lawrence KQ Yan, Yichao Zhang, Caitlyn Heqi Yin, and 1 others. 2024. Large language models and cognitive science: A comprehensive review of similarities, differences, and challenges. *arXiv preprint arXiv:2409.02387*.

[40] Stellan Ohlsson. 2012. The problems with problem solving: Reflections on the rise, current status, and possible future of a cognitive research paradigm. *The Journal of problem solving*, 5(1):7.

[41] OpenAI. 2023. Gpt-4 technical report. arXiv preprint arXiv:2303.08774.

[42] OpenAI. 2024. Learning to reason with llms.

[43] Long Ouyang, Jeff Wu, Xu Jiang, and 1 others. 2022. Training language models to follow instructions with human feedback. *arXiv preprint arXiv:2203.02155*.

[44] Gonçalo Paulo, Alex Mallen, Caden Juang, and Nora Belrose. 2024. Automatically interpreting millions of features in large language models. *arXiv preprint arXiv:2410.13928*.

[45] Ethan Perez, Douwe Kiela, and Kyunghyun Cho. 2021. True few-shot learning with language models. In *Advances in Neural Information Processing Systems (NeurIPS)*.

[46] Tian Qin, Core Francisco Park, Mujin Kwun, Aaron Walsman, Eran Malach, Nikhil Anand, Hidenori Tanaka, and David Alvarez-Melis. 2025. Decomposing elements of problem solving: What" math" does rl teach? *arXiv preprint arXiv:2505.22756*.

[47] Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Yang Wu, and 1 others. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*.

[48] Arsalan Sharifnassab, Saber Salehkaleybar, Sina Ghiassian, Surya Kanoria, and Dale Schuurmans. 2024. Soft preference optimization: Aligning language models to expert distributions. *arXiv preprint arXiv:2405.00747*.

[49] Idan Shenfeld, Jyothish Pari, and Pulkit Agrawal. 2025. Rl's razor: Why online reinforcement learning forgets less. *arXiv preprint arXiv:2509.04259*.

[50] Guangming Sheng, Chi Zhang, Zilingfeng Ye, Xibin Wu, Wang Zhang, Ru Zhang, Yanghua Peng, Haibin Lin, and Chuan Wu. 2025. Hybridflow: A flexible and efficient rlhf framework. In *Proceedings of the Twentieth European Conference on Computer Systems*, pages 1279–1297.

[51] Aarohi Srivastava, Abhinav Rastogi, Abhishek Rao, and 1 others. 2022. Beyond the imitation game benchmark for measuring and extrapolating the capabilities of language models. *arXiv preprint arXiv:2206.04615*.

[52] Yiyou Sun, Yuhan Cao, Pohao Huang, Haoyue Bai, Hannaneh Hajishirzi, Nouha Dziri, and Dawn Song. 2025. Delta-code: How does rl unlock and transfer new programming algorithms in llms? *arXiv preprint arXiv:2509.21016*.

[53] Yiyou Sun, Shawn Hu, Georgia Zhou, Ken Zheng, Hannaneh Hajishirzi, Nouha Dziri, and Dawn Song. 2025. Omega: Can llms reason outside the box in math? evaluating exploratory, compositional, and transformative generalization. *arXiv preprint arXiv:2506.18880*.

[54] Yiyou Sun, Georgia Zhou, Haoyue Bai, Hao Wang, Dacheng Li, Nouha Dziri, and Dawn Song. 2025. Climbing the ladder of reasoning: What llms can- and still can't-solve after sft? *arXiv preprint arXiv:2504.11741*.

[55] Zechen Sun, Yisheng Xiao, Juntao Li, Yixin Ji, Wenliang Chen, and Min Zhang. 2024. Exploring and mitigating shortcut learning for generative large language models. In *Proceedings of the 2024 joint international conference on computational linguistics, language resources and evaluation (LREC-COLING 2024)*, pages 6883–6893.

[56] Anthropic Team. The claude 3 model family: Opus, sonnet, haiku.

[57] Alexander Matt Turner, Lisa Thiergart, Gavin Leech, David Udell, Juan J Vazquez, Ulisse Mini, and Monte MacDiarmid. 2023. Activation addition: Steering language models without optimization. *arXiv e-prints*, pages arXiv–2308.

[58] Miles Turpin, Julian Michael, Ethan Perez, and Samuel Bowman. 2023. Language models don't always say what they think: Unfaithful explanations in chain-of-thought prompting. *Advances in Neural Information Processing Systems*, 36:74952–74965.

[59] Various Contributors. 2024. Hookedsaetransformer: Sparse autoencoder interpretability toolkit. GitHub repository.

[60] Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. 2022. Self-consistency improves chain of thought reasoning in language models. *arXiv preprint arXiv:2203.11171*.

[61] Jason Wei, Xuezhi Wang, Dale Schuurmans, and 1 others. 2022. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems (NeurIPS)*.

[62] Nanyang Ye, Kaican Li, Haoyue Bai, Runpeng Yu, Lanqing Hong, Fengwei Zhou, Zhenguo Li, and Jun Zhu. 2022. Ood-bench: Quantifying and understanding two dimensions of out-of-distribution generalization. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 7947–7958.

[63] Chiyuan Zhang, Samy Bengio, Moritz Hardt, and 1 others. 2021. Understanding deep learning requires rethinking generalization under distribution shift. In *International Conference on Learning Representations (ICLR)*.

[64] Yaowei Zheng, Richong Zhang, Junhao Zhang, Yanhan Ye, Zheyan Luo, Zhangchi Feng, and Yongqiang Ma. 2024. Llamafactory: Unified efficient fine-tuning of 100+ language models. *arXiv preprint arXiv:2403.13372*.

[65] Daniel M Ziegler, Nisan Stiennon, Jeffrey Wu, Tom B Brown, Alec Radford, Dario Amodei, Paul Christiano, and Geoffrey Irving. 2019. Fine-tuning language models from human preferences. *arXiv preprint arXiv:1909.08593*.

# A Additional Experimental Details

## A.1 Setup for Base, SFT, and RL Model Training and Evaluation

**Models.** We adopt the training recipe of [23]: (i) we use their released Qwen3-14B SFT and RL checkpoints, (ii) we replicate the same procedure at 4B to obtain Qwen3-4B SFT/RL models, and (iii) we train Qwen3-1.7B SFT/RL models while saving intermediate checkpoints for dynamics visualization. We focus on the Qwen3 family to maintain a controlled comparison across post-training regimes and model scales, while keeping the architecture, tokenizer, and pre-training distribution fixed. Our RL setup uses GRPO with answer-correctness rewards, following a widely adopted reasoning-oriented RL recipe rather than a model-specific optimization scheme.

We choose Qwen3 because it is one of the few publicly available model families that provides reproducible base, SFT, and RL variants under a consistent training framework, enabling controlled comparisons across multiple scales. Training aligned SFT and RL variants at 1.7B, 4B, and 14B scales already requires substantial computational and engineering effort, making a single-family setup the most feasible and controlled experimental design. While our conclusions are therefore scoped to the Qwen3 backbone and this RL setting, we observe highly consistent qualitative trends across all three scales, suggesting that the findings are unlikely to be artifacts of a single checkpoint or model size. Moreover, the behaviors we observe—such as SFT over-specialization and RL's comparatively balanced skill preservation—appear closely tied to the training objectives themselves, consistent with observations reported across other model families in prior work.

Using Verl with GRPO and answer-correctness rewards for RL, we set: lr $= 1 \times 10^{-6}$; global batch $= 512$; clip $= 0.22$–$0.28$; context $= 16k$ tokens; 16 rollouts/prompt; mini-batch $= 128$; KL/entropy coeffs $= 0$; train 140 steps (and use the corresponding checkpoint). For SFT, we fine-tune with LLaMA-Factory on teacher CoT traces from Qwen3-32B-Instruct via reject sampling; lr $= 5 \times 10^{-5}$; global batch $= 512$; 1.5 epochs (mirroring the RL horizon). The training dataset consists of 47K curated mathematical reasoning problems, with CoT traces generated by Qwen3-32B-Instruct. We intentionally use the same math-centric training distribution for both SFT and RL in order to isolate the effects of the post-training objective itself, rather than confounding differences in data composition. Although the training corpus is primarily mathematical, our evaluation benchmark spans multiple domains beyond mathematics, where we still observe consistent differences in reasoning decomposition and cognitive skill utilization. This suggests that the observed effects reflect broader shifts in reasoning behavior induced by RL training, rather than purely STEM-specific transfer. The baselines are Qwen3-14B-Base and Qwen3-14B-Instruct (evaluated in *think/no-think* modes).

**Generation settings.** Unless noted otherwise, we use nucleus sampling with temperature 0.6 and top-$p = 0.95$. For reasoning tasks, we cap generation at $32\,\mathrm{k}$ new tokens and apply stop sequences aligned with our standardized output headers. All decoding settings are held fixed across models for fair comparison.

**Prompt template.** We use a single minimal prompt for all tasks:

```
{problem}

Please reason step by step,
and put your final answer within \boxed{...}.
```

Here, `{problem}` contains the task statement and, when applicable, any behavior-specific context (e.g., theorem tags for *Guided* fact-retrieval or a lightly perturbed trace for diagnostic). Decoding settings are identical across models; evaluation reads only the final boxed answer.

**Core metrics.** Primary metric is **accuracy** under fixed decoding. We also compute behavior profiles (per-behavior accuracy vectors), normalized skill indices relative to the base model, and distributional drift of intermediate features when applicable.

**Evaluation harness.** We run batched inference with `vLLM` and a deterministic evaluation harness that records per-item seeds, prompts, responses, and scores. All artifacts (prompts, outputs, logs) are versioned and exported for audit.

## A.2 Setup for SAE Training and Interpretation

**Activation collection.** We extract activations from specified transformer layers (e.g., blocks 3, 16, 32) at `hook_mlp_out` with context length 2048 over a balanced mixture of behavior-labeled prompts. We follow a stratified sampler to equalize behaviors and difficulties.

**SAE objective & launch.** We train per-layer sparse autoencoders (SAEs) on transformer MLP outputs by minimizing $\mathcal{L} = \|h - Dz\|_2^2 + \lambda\|z\|_1$, where $h$ is the hidden activation at `blocks.<L>.hook_mlp_out`, $z$ the sparse code, and $D$ the decoder. We use the open-source `sparsify` repo. Unless noted: `-ctx_len 2048` and `-batch_size 5`.

Example command (single layer):

```
python -m sparsify <BASE_MODEL_NAME> <DATASET_OR_REPO> \
  --layers 16 --batch_size 5 --ctx_len 2048 \
  --data_preprocessing_num_proc 5 --k 250 \
  --run_name SAE-layer16-example
```

Replace `<BASE_MODEL_NAME>` (e.g., `Qwen3-4B-Base`) and `<DATASET_OR_REPO>` with model tag and dataset identifier or local path.

**SAE interpretation with Delphi.** For automated explanation of sparse autoencoder (SAE) and transcoder features, we use the open-source Delphi library [44]. Delphi programmatically *generates* and *scores* natural-language explanations for features, enabling large-scale interpretability; models can run locally or via OpenRouter. In our pipeline, for each learned feature we feed top-activating examples, obtain $k$ candidate explanations, score them with DELPHI's built-in scorer, and keep the top-ranked explanation subject to a quality threshold.

Example generation command:

```
python -m delphi <BASE_MODEL> <SAE_CHECKPOINT_DIR> \
  --hookpoints layers.16 \
  --scorers detection \
  --n_tokens 10_000_000 \
  --max_latents 10000 \
  --dataset_repo <DATASET_REPO> \
  --dataset_split 'train[:100%]' \
  --filter_bos \
  --name sae-layer16-explain
```

Replace placeholders with model tag, the directory containing the trained SAE for the target layer, and the dataset source. The flag `-hookpoints layers.16` selects the MLP-out features of layer 16 (other layers analogous); `-filter_bos` removes BOS tokens; `-scorers detection` invokes the default explanation scorer.

**Scoring SAE features for cognitive behaviors.** After obtaining per-feature natural-language explanations with DELPHI, we assign scores for the five behaviors (calculation, enumeration, simulation, fact retrieval, diagnostic) using a lightweight LLM grader. For each behavior, we supply a behavior-specific rubric (name, description, keywords, indicators) and batch a list of feature explanations; the model returns a JSON record per feature with a soft score, confidence, and a binary label. We decode *greedily* (no sampling) to ensure schema validity and reproducibility. A feature is counted as "related" to a behavior if $\text{score} \geq 0.5$; we also report confidence–weighted variants ($\tilde{s} = \text{score} \times \text{confidence}$). Percentages are computed per layer and per model.

**Behavior-parameterized prompt:**

```
You are analyzing feature explanations to
    determine if they relate to <BEHAVIOR>.

Category: <NAME>
Description: <DESCRIPTION>
Keywords: <KEYWORDS>
Indicators: <INDICATORS>

Analyze the following <N> features:
Feature 1 (ID: <feature_id_1>): <explanation_1>

...

For each feature, determine:
1) The extent to which it relates to <BEHAVIOR>
    (score 0.0-1.0).
2) Your confidence in this judgment (0.0-1.0).
3) A binary classification (0 or 1) for whether
    it relates to <BEHAVIOR>.

Respond with a JSON array (one element per
    feature) using EXACTLY:
[
  {"feature_id":"<feature_id_1>","score
    ":<0.0-1.0>,
   "confidence":<0.0-1.0>,"classification":<0 or
    1>},
  ...
]
Only return the JSON array.
```

*Example instantiation (diagnostic).* Replace `<BEHAVIOR>` with `mathematical diagnostics` and populate `<NAME>`, `<DESCRIPTION>`, `<KEYWORDS>`, `<INDICATORS>` from our diagnostic rubric (Appendix F). The same template is used for the other four behaviors by swapping in the corresponding rubrics.

**Interpretation.** We align SAE latents to the five behaviors with a two–stage procedure. *(i) Text-based alignment:* using DELPHI, we generate per–feature explanations and grade them with

a behavior-parameterized LLM prompt (shown above), which returns a soft score $s \in [0, 1]$, a confidence $\hat{c} \in [0, 1]$, and a binary label; a feature is considered related if $s \geq 0.5$, and we also report confidence-weighted scores $s \cdot \hat{c}$. *(ii) Signal-based validation:* we fit linear probes and compute mutual information between latent activations and behavior labels; any discrepancies trigger manual auditing of top-activating tokens/spans. We further summarize higher-order structure via skewness–kurtosis of decoder weights and visualize feature selectivity with activation-triggered exemplars, reporting layer-wise percentages for each model.

### A.3 Additional Details

**Reproducibility and runtime.** We fix seeds for our experiments, and the evaluation harness, enable deterministic kernels where supported, and pin vLLM to a specific engine build. Experiments run on H100 (80 GB) GPUs; inference uses tensor parallelism with static max sequence lengths, and batch sizes are tuned to avoid OOM while keeping GPU utilization $\geq 80\%$. We cache tokenizer outputs and KV states when permitted by the harness to ensure identical re-runs.

**Scope and generalization.** Our study is designed to compare SFT and RL objectives under a controlled and standardized post-training pipeline. To isolate the distinct effects of each training objective, we apply SFT and RL independently to the same base model rather than using a staged SFT+RL pipeline. This design enables clearer attribution of observed behavioral differences to the training objective itself, without confounding effects from training order or pipeline interactions.

Accordingly, our goal is not to claim broad domain generalization from math training alone, but rather to analyze how different post-training paradigms shape reasoning behavior and internal representations under controlled conditions. Our analysis focuses on mechanistic differences at the behavioral, representational, and statistical levels, rather than solely on downstream accuracy gains. The cognitive-skill decomposition presented here may help explain how RL and SFT contribute differently within broader post-training pipelines and suggests potential hypotheses regarding complementary or recovery effects. Extending the analysis to staged SFT+RL pipelines, more diverse post-training corpora, additional backbone families, and alternative RL algorithms remains an important direction for future work.

**AI Assistance in Research and Writing.** This work uses AI tools for sentence-level proofreading.

## B Quantifying Skill Balance Beyond Radar Plots

**Quantifying skill-balance beyond radar visualizations.** In the main text, we argue that reinforcement learning (RL) tends to produce a more balanced cognitive-skill profile than supervised fine-tuning (SFT), as illustrated by radar plots. To provide quantitative support for this claim, we report both raw behavior-wise accuracies (Table 3) and three complementary smoothness metrics that directly capture how uniformly skills are distributed across cognitive dimensions: (i) the coefficient of variation (CV), measuring dispersion across skills; (ii) adjacent-difference smoothness (AdjDiff), measuring local jaggedness in the skill profile; and (iii) circularity, defined as the ratio between the minimum and maximum radius in the radar plot, capturing overall profile roundness.

Across all evaluated settings, RL consistently exhibits lower CV and lower AdjDiff than SFT, indicating substantially reduced variance and smoother transitions across cognitive skills. At the same time, RL achieves higher circularity, reflecting a more uniform distribution of behavioral competencies. Averaged across all models, RL reduces CV from 0.59 to 0.40 and AdjDiff from 17.3 to 10.6, while increasing circularity from 0.15 to 0.34, corresponding to roughly a 33% reduction in overall variance, a 39% reduction in local unevenness, and a 2.3× increase in profile uniformity. All numbers are averaged over five independent runs.

Importantly, the accuracies reported in Table 3 are measured relative to the base model, rather than as absolute accuracies, ensuring a fair comparison of how different post-training objectives reshape the distribution of skills. Together, these quantitative results align closely with the radar visualizations and confirm that RL yields a smoother and more evenly balanced cognitive-skill profile.

## C Interpreting the Roles of SFT and RL

**Complementary roles of SFT and RL in post-training.** Our findings should not be interpreted as suggesting that supervised fine-tuning is unnecessary or that reinforcement learning alone is sufficient for post-training. In our experimental design, SFT and RL are applied independently to the same

| Setting | Strategy | Calculation | Enumeration | Simulation | Fact Retrieval | Diagnostic |
|---|---|---|---|---|---|---|
| Math (14B) | SFT | 13.90 | 16.22 | 28.19 | 1.54 | 43.24 |
| Math (14B) | RL | 17.70 | 29.67 | 21.69 | 16.59 | 14.00 |
| Physics (14B) | SFT | 7.20 | 27.37 | 9.60 | 21.61 | 34.21 |
| Physics (14B) | RL | 13.89 | 32.60 | 5.56 | 19.44 | 28.89 |
| Math (4B) | SFT | 27.90 | 10.70 | 6.98 | 8.84 | 46.05 |
| Math (4B) | RL | 27.82 | 13.63 | 15.33 | 16.47 | 26.76 |
| Physics (4B) | SFT | 17.60 | 24.88 | 6.09 | 32.15 | 19.29 |
| Physics (4B) | RL | 26.39 | 8.27 | 9.52 | 35.91 | 19.90 |

Table 3: Behavior-wise accuracy improvements across cognitive skills. Accuracy is reported relative to the base model for five reasoning-related behaviors, Calculation, Enumeration, Simulation, Fact Retrieval, and Diagnostic, under SFT and RL across math and physics domains and two model scales (14B and 4B). These results provide the raw behavioral profiles that underlie the smoothness metrics reported in Table 4.

| Setting | Strategy | CV ↓ | AdjDiff ↓ | Circularity ↑ |
|---|---|---|---|---|
| Math (14B) | SFT | 0.6851 | 22.396 | 0.0356 |
| Math (14B) | RL | 0.2741 | 6.268 | 0.4719 |
| Physics (14B) | SFT | 0.5152 | 17.912 | 0.2105 |
| Physics (14B) | RL | 0.4900 | 16.816 | 0.1706 |
| Math (4B) | SFT | 0.7453 | 15.628 | 0.1516 |
| Math (4B) | RL | 0.3014 | 5.676 | 0.4899 |
| Physics (4B) | SFT | 0.4308 | 13.336 | 0.1894 |
| Physics (4B) | RL | 0.5203 | 13.652 | 0.2303 |
| **Average** | **SFT** | **0.5941** | **17.3180** | **0.1468** |
| **Average** | **RL** | **0.3965** | **10.6030** | **0.3407** |

Table 4: Quantitative smoothness metrics for cognitive-skill profiles under SFT and RL. We report three complementary measures of skill balance: coefficient of variation (CV, lower is better), adjacent-difference smoothness (AdjDiff, lower is better), and circularity (higher is better). Across all settings, RL consistently yields smoother and more uniformly distributed skill profiles than SFT.

base model in order to enable a controlled comparison of how each objective reshapes the distribution of cognitive behaviors. This setup isolates their inductive effects on skill organization, but does not evaluate broader dimensions such as alignment, safety, or instruction-following, where SFT plays a central role in practice.

More broadly, the two objectives exhibit complementary strengths. In our experiments, RL primarily rebalances and smooths existing competencies, reducing over-specialization and promoting a more uniform distribution of skills across behaviors. By contrast, SFT often produces sharper peaks and valleys, and by reconstructing output distributions from supervised examples, can introduce or amplify capabilities that are not prominent in the base model. These differences suggest distinct but synergistic roles: RL is particularly effective at

mitigating unevenness and stabilizing general reasoning performance, while SFT remains essential for alignment-oriented behaviors and for extending the usable knowledge of the base model.

Accordingly, our conclusions should be read as clarifying when and how each post-training objective is most effective, rather than advocating an RL-only pipeline.

## D  Training Dynamic

Under 1.7B RL, all five skills improve over training, with fast early gains that settle into a stable plateau. In math, simulation is consistently strongest, diagnostic rises steadily, and calculation shows clear improvement; enumeration and fact retrieval make smaller but persistent gains (see Fig. 8). In physics, calculation leads throughout, fact retrieval strengthens over time, simulation improves to a moderate level, and enumeration and diagnostic advance more gradually. The shaded bands in Fig. 8 remain tight, indicating stable progress without regressions and balanced multi-skill benefits from RL.

## E  Additional Results on Sparse Latent Features

Figure 9 extends our SAE-based cognitive-feature analysis to the physics domain. At the midpoint layer (Layer 16), we observe a pattern closely aligned with the math domain: both SFT and RL selectively reweight semantic capacity toward *Fact Retrieval* and *Diagnostic* features, while leaving *Calculation* and *Simulation* largely stable and *Enumeration* consistently sparse. This suggests that post-training enhances knowledge access and self-verification behaviors in physics reasoning without disrupting core computational and forward-modeling circuits.

(a) Math dynamic            (b) Physics dynamic

Figure 8: Training dynamics (Qwen3-1.7B-RL). Accuracy vs. step for math (a) and physics (b), with shaded variability. Calculation dominates; enumeration stays weakest/most volatile. Fact-retrieval, diagnostic, and simulation rise steadily (simulation relatively stronger in physics), indicating balanced RL gains rather than specialization.

Across depth in the base model, physics tasks exhibit the same functional organization observed in math. *Calculation* and *Simulation* strengthen with depth, whereas *Fact Retrieval* and *Diagnostic* follow a U-shaped trajectory, prominent in early and late layers, with reduced emphasis in the mid stack. Together, these results indicate that the pipeline structure identified in the main text—retrieval and checking in early and deep layers, transformation and transport in mid layers, generalizes beyond mathematics to scientific reasoning more broadly.

# F Cognitive Behaviors: Definitions, Keywords, and Indicators

Definition of the five cognitive behaviors: These behaviors represent fundamental modes of reasoning and problem solving—calculation, diagnosis, fact retrieval, simulation, and enumeration—each capturing a distinct way in which a system or learner processes information, manipulates symbols, and monitors or generates solutions across mathematical, scientific, and general domains.

- **Calculation:** The execution of arithmetic, algebraic, or symbolic operations to derive quantitative or formal results from given inputs. Calculation emphasizes step-by-step manipulation under well-defined mathematical or logical rules, and may involve simplification, substitution, or transformation of expressions to reach a final result.

  **Keywords:** compute, calculate, derive, simplify, evaluate, solve, result, step-by-step, formula, expression.

  **Indicators:** explicit arithmetic/algebraic operations, transformations of equations, numerical outputs.

- **Enumeration:** The systematic and exhaustive generation of all elements, cases, or options satisfying a set of explicit constraints. Enumeration emphasizes coverage and completeness, often under conditions where solution space must be fully explored or cataloged for correctness, diversity, or comprehensiveness.

  **Keywords:** list, all cases, options, possibilities, exhaustive, generate, under constraints, coverage.

  **Indicators:** systematic listing, covering search space, combinatorial completeness.

- **Simulation:** The mental or symbolic enactment of a process, system, or sequence of operations to predict or trace its behavior over time. Simulation requires stepwise reasoning consistent with formal rules (e.g., algebraic manipulation, causal transitions, or state-machine updates) and supports forecasting, testing, or illustrating dynamic evolution.

  **Keywords:** simulate, step, next state, transition, apply rule, run through, dynamic, causal, evolve, predict.

  **Indicators:** walking through process rules, state transitions, mental enactment of system behavior.

- **Fact retrieval:** The recall or extraction of canonical, domain-grounded knowledge units (e.g., theorems, definitions, constants, statutes, or factual attributes). Fact retrieval emphasizes accuracy, grounding, and direct mapping

(a) Different Strategy

(b) Different Layers

Figure 9: SAE-based cognitive-feature composition in the physics domain across strategies and layers. We train sparse autoencoders (SAEs) on hidden states of Qwen3-4B, Qwen3-4B-SFT, and Qwen3-4B-RL for physics-domain tasks, and compute the fraction of SAE features aligned with five reasoning-related behaviors: Calculation, Enumeration, Simulation, Fact Retrieval, and Diagnostic. Panel (a) compares post-training strategies at Layer 16; panel (b) shows layer-wise trends (Layers 3/16/32) for the Base model. Overall, the physics domain exhibits patterns consistent with the math domain: post-training selectively amplifies retrieval and diagnostic subspaces, while depth organizes a pipeline from transformation-focused mid layers to retrieval and verification in early and late layers.

to authoritative sources, rather than inference or elaboration.

**Keywords:** recall, definition, theorem, law, constant, fact, property, known, canonical, from memory.

**Indicators:** citing established knowledge, direct recall of named entities or rules without derivation.

- **Diagnostic:** The act of identifying, localizing, and explaining the source of an error, inconsistency, or divergence in a reasoning process, system execution, or narrative account. In the context of LLMs, diagnostic reasoning is often accompanied by explicit self-monitoring or self-check language (e.g., "wait," "let's recheck," "that step seems wrong"), which signals recognition of potential failure modes, causal attribution, and corrective reasoning.

  **Keywords:** error, mistake, wrong, recheck, bug, contradiction, mismatch, correction, failure mode.

  **Indicators:** self-check language ("wait," "let's recheck"), identifying divergence, explaining why an approach fails.

### F.1 Template and prompt for the dataset construction

**Candidate retrieval.** We retrieve candidates via dense *embedding* search using `text-embedding-3-small`. Each item is indexed by the concatenation of its *question* and *reasoning trace*. For every behavior–domain seed, we compose a query from the seed summary,

behavior keywords, and a few template sentences, then select the top-$k$ nearest items by embedding similarity (the model's native similarity). We de-duplicate with an embedding-similarity threshold $\tau$, retaining the highest-scoring item among any pairs above $\tau$.

**Retrieval query template:**

```
{SEED_SUMMARY}
Behavior: {BEHAVIOR} | Domain: {DOMAIN}
Keywords: {k1}, {k2}, {k3}
Template sentences: {TEMPLATE_SENTENCES}
(Find items semantically similar to this query
    using embedding similarity in
text-embedding-3-small.)
```

### F.2 Diagnostic Example

For the example in figure J, starting from $\sqrt{x+4} = x - 2$, a first pass squares both sides to obtain $x + 4 = (x-2)^2$, which simplifies to $x^2 - 5x = 0$ and yields candidate solutions $x \in \{0, 5\}$. A diagnostic self-check then enforces the original domain $\sqrt{x+4} \geq 0$, giving $x - 2 \geq 0$ and thus $x \geq 2$, which rules out $x = 0$. Substituting into the original equation confirms the extraneous nature of $x = 0$ since $\sqrt{4} = 2 \neq -2$. Therefore the only valid solution is $x = 5$. This sequence—derivation, reflection, constraint checking, and correction—illustrates diagnostic behavior by identifying an error introduced by a non-invertible operation (squaring) and revising the solution accordingly.

### F.3 Benchmark Scale and Extensibility.

The benchmark spans $5 \times 4$ (behavior $\times$ domain) cells, with each cell containing 50 to 200 carefully

curated, high quality examples vetted for skill isolation, correctness, and calibrated difficulty. Seed questions are templatable and can be faithfully expanded, for example by renaming variables, rescaling parameters, swapping units or entities, or controlled paraphrasing, thereby increasing coverage without altering the targeted skill.

## G  Datasets Statistics

**Dataset statistics.** Figures 10, 11, 12, and 13 present the distributions of subcategories across our newly created mathematics, scientific reasoning (physics), coding, and non-reasoning datasets, each further grouped by key behavioral facets: Calculation, Enumeration, Fact Retrieval, Simulation, and Diagnostic. The figures showcase a balanced and comprehensive coverage of both domain-specific and cross-domain skills, from core mathematical topics such as prime factorization, combinatorics, and binomial theorems, to scientific reasoning tasks in physics such as mechanics, thermodynamics, and optics, to algorithmic and computational challenges including graph/tree problems, dynamic programming, and simulation-based tasks, and finally to non-reasoning tasks such as writing and summarization, error detection, knowledge retrieval, and scenario-based simulations. This deliberate and systematic construction ensures that the dataset spans diverse problem types and cognitive demands, enabling robust evaluation of both reasoning-intensive and non-reasoning capabilities of large language models. The broad yet well-curated distributions highlight the quality, diversity, and representativeness of our benchmark, establishing it as a reliable resource for comprehensive assessment of models across reasoning, problem-solving, and real-world task performance.

## H  Cognitive Grounding and Functional Completeness of the Atomic Skill Taxonomy

We conceptualize "reasoning" at a functional level as the coordinated operation of elementary information-processing mechanisms, rather than in neuroanatomical or implementation-specific terms. This perspective follows a long tradition in cognitive science that characterizes problem solving as goal-directed search in a problem space, governed by representations, operators, and control processes [38; 31; 40].

In the classic problem-space framework, reasoning unfolds through a recurring control loop: (i) retrieving relevant knowledge from long-term memory, (ii) generating candidate states, hypotheses, or partial solutions, (iii) applying operators that transform internal representations, and (iv) evaluating intermediate results to guide further search, revision, or termination [38; 31]. This loop provides an abstract and operational description of how humans and artificial systems organize complex reasoning across domains.

Our five atomic skills map directly onto this functional decomposition. Fact retrieval instantiates access to declarative and semantic knowledge, consistent with cognitive architectures that distinguish retrieval of stored facts from procedural transformation [3; 2]. Enumeration corresponds to structured candidate generation and hypothesis search, a core component of problem-space exploration in both symbolic and connectionist models [38; 31]. Calculation and simulation jointly operationalize operator application, but capture two distinct modes: (a) static symbolic or arithmetic transformation over well-defined representations (calculation), and (b) model-based rollout over time, counterfactuals, or hypothetical scenarios (simulation). This distinction aligns with mental-model theories of reasoning, which posit that reasoners construct internal models of situations and draw inferences by simulating their consequences [25]. Finally, diagnostic checking implements evaluation and metacognitive control, processes that monitor uncertainty, detect conflict or error, and trigger revision, additional search, or termination, consistent with classical accounts of metacognition, conflict monitoring, and error detection [37; 14; 10; 22].

Under this standard functional characterization, the proposed set of atomic skills is complete at our level of analysis. Any step in a reasoning trace can be classified as one of four fundamental operations: retrieving information, generating alternatives, transforming representations via calculation or simulation, or evaluating and controlling the process through diagnostic checking. Higher-level reasoning modes such as analogy, abduction, or causal inference do not require additional primitives; rather, they emerge from structured compositions of these same operations. For example, analogy combines retrieval of prior cases with simulation of relational mappings and diagnostic evaluation of fit, while abduction integrates enumeration of hypotheses with simulation of explanatory consequences and diagnostic selection [31; 25; 37].

This functional completeness is not only theoretically motivated but also empirically supported by our analysis. Across domains and training regimes, we find that observed reasoning behaviors can be consistently decomposed into these five skills, and that performance shifts under SFT and RL manifest as redistributions among them rather than as the emergence of qualitatively new categories. In this sense, our benchmark operationalizes a long-standing cognitive-science view of reasoning, translating it into a measurable and model-agnostic framework for analyzing generalization, robustness, and skill transfer in large language models.

# I  Detailed Description of the Meta-Evaluation Benchmark

Table 1 provides a comprehensive overview of meta-evaluation benchmark, which systematically categorizes evaluation tasks across 20 distinct problem types (4 domains × 5 cognitive behaviors). This structured framework enables granular assessment of LLM capabilities while maintaining consistency in evaluation methodology.

## I.1  Domain Categories

The benchmark spans four complementary domains that represent core areas of AI capability assessment:

**Math Reasoning** encompasses problems requiring mathematical logic, symbolic manipulation, and quantitative reasoning. Tasks in this domain range from elementary arithmetic operations to advanced mathematical proof construction, testing models' ability to handle formal symbolic systems and rigorous logical deduction.

**Scientific Reasoning** evaluates understanding of physical principles, scientific methodologies, and domain-specific knowledge from fields such as physics, chemistry, and biology. These tasks assess whether models can apply scientific laws, perform calculations with physical units, and reason about real-world phenomena governed by natural principles.

**Coding** tests computational thinking, algorithm design, and programming proficiency. Problems in this category require models to understand data structures, optimize algorithms, debug code, and translate problem specifications into executable solutions across various programming paradigms.

**Non-reasoning** captures tasks that depend primarily on factual knowledge retrieval, procedural execution, or creative generation rather than complex logical inference. This category serves as a control to distinguish reasoning capabilities from memorization or pattern matching.

## I.2  Cognitive Behaviors

The five cognitive behaviors represent fundamental modes of thinking that cut across domains:

**Calculation** involves executing well-defined computational procedures to derive quantitative or symbolic results. These tasks test precision, attention to detail, and mastery of algorithmic processes. Examples include computing prime factorizations, determining molecular radii from physical constants, implementing matrix operations, and calculating environmental metrics from model equations. The complexity varies from single-step arithmetic to multi-stage computations requiring careful tracking of intermediate results.

**Enumeration** requires systematic generation of all elements satisfying specified constraints. This behavior tests completeness, organizational thinking, and the ability to explore solution spaces exhaustively without omission or duplication. Tasks include combinatorial problems (such as distributing items into labeled boxes), generating quantum mechanical states (atomic orbital configurations), partitioning data structures (set partitions with ordering constraints), and cataloging instances (program features or article structures). Success demands both algorithmic rigor and verification that all cases have been considered.

**Simulation** involves mental or symbolic enactment of dynamic processes over time or through state transitions. These tasks evaluate sequential reasoning, state tracking, and the ability to project forward through cause-and-effect chains. Examples include iterating mathematical functions on a board, modeling physical processes (cooling or radioactive decay), tracing algorithmic execution (robot pathfinding or coin replacement dynamics), and predicting outcomes (weather forecasting or game simulation). The challenge lies in maintaining consistency across multiple steps while managing increasing complexity.

**Fact Retrieval** tests access to declarative knowledge and the ability to recall, recognize, or apply learned information. Tasks range from theorem retrieval in mathematics, recalling physical laws and formulas in science, accessing API documentation in coding, to retrieving cultural or procedural knowledge in non-reasoning contexts. This

behavior assesses both the breadth of a model's knowledge base and its ability to retrieve relevant information when needed. Unlike pure memorization, many tasks require applying retrieved facts to novel situations.

**Diagnostic** evaluates meta-cognitive abilities, including error detection, consistency checking, and critical evaluation of reasoning processes. This highest-level cognitive behavior requires models to step back from problem-solving to assess the validity of solutions, identify logical flaws, or recognize ambiguities. Examples include verifying mathematical proofs, identifying errors in physical reasoning (such as perturbation analysis), debugging code, and detecting logical inconsistencies in arguments. Diagnostic tasks are particularly challenging because they require models to reason about reasoning itself.

### I.3 Problem Design Principles

Each problem template follows several key design principles. First, problems are *self-contained*, providing all necessary information within the problem statement to avoid ambiguity. Second, they have *verifiable solutions*, enabling objective evaluation without subjective judgment. Third, they exhibit *scalable difficulty*, allowing generation of instances ranging from simple to complex by adjusting parameters. Fourth, they are *domain-representative*, reflecting authentic tasks that practitioners in each field actually encounter. Finally, problems are designed to be *minimally ambiguous*, with clear success criteria that reduce evaluation uncertainty.

### I.4 Cross-Domain Patterns

Several interesting patterns emerge from the taxonomy. Calculation tasks share common structure across domains—all involve applying defined procedures to inputs—but differ in the nature of operations (arithmetic vs. physical vs. algorithmic). Enumeration tasks universally require exhaustive search but vary in the combinatorial structure being explored. Simulation tasks all involve temporal or sequential progression but differ in whether the dynamics are deterministic or stochastic, discrete or continuous. Fact Retrieval varies most dramatically across domains, reflecting the distinct knowledge bases required. Diagnostic tasks converge on common meta-cognitive skills despite different surface manifestations.

### I.5 Use Cases

This benchmark serves multiple purposes in AI evaluation research. It enables *comparative analysis* of different models across specific cognitive dimensions, revealing whether a model excels at calculation but struggles with enumeration, for instance. It facilitates *targeted improvement* by identifying precise capability gaps. It supports *meta-evaluation* by providing a diverse testbed for assessing evaluation methods themselves—different evaluation approaches may perform better or worse across different cells of the taxonomy. Finally, it enables *robustness testing* by generating multiple problem instances within each template to assess consistency of model performance.

## J Additional Math Examples

Table G illustrates representative problem templates for each behavior in mathematics. *Calculation* covers core symbolic and numeric skills such as greatest common divisor, prime factors, eigenvalues and singular values of small matrices, and solving linear equations. *Enumeration* includes combinatorial distributions, grid path counting, lattice enumeration, seating permutations with constraints, symmetry counting on polyhedra, and expression rationalization. *Simulation* features stepwise processes such as number sequence updates, random walk boundary hitting, expected stopping time, iterative redistribution, and compound interest growth. *Fact retrieval* targets canonically stated results (Euler's circle geometry formulae, Chinese Remainder Theorem and totient, multiple–angle identities, inclusion–exclusion, spherical distance). *Diagnostic* provides templated failure modes—including statement drift, inconsistent traces, theorem misuse, domain or legality mistakes, and answer or format mismatch—so models must detect and correct errors rather than compute alone. Each template admits numeric instantiations with a unique short answer, enabling scalable generation while preserving skill isolation.

## Math Diagnostic Example

**Problem:** Solve for all real $x$:

$$\sqrt{x + 4} = x - 2$$

**First Attempt:** The square root is always non-negative, so $x - 2 \geq 0$, hence $x \geq 2$. Squaring both sides:

$$x + 4 = (x-2)^2 \implies x + 4 = x^2 - 4x + 4$$

Simplify:

$$0 = x^2 - 5x \implies x(x - 5) = 0$$

Therefore, $x = 0$ or $x = 5$.

**Self-check/correction: Wait, let's re-check:**

Since $x \geq 2$, the candidate solution $x = 0$ is invalid.

Also, substituting $x = 0$ into the original equation gives

$$\sqrt{4} \neq -2$$

so it does not satisfy the equation.

Thus, the only valid solution is $x = 5$.

**Final Answer:**

$$x = 5$$

**Diagnostic:**

The diagnostic behavior is marked by the phrase "Wait, let's re-check" (or similar), followed by detecting a domain or consistency issue and revising the solution.

Table 5: Example problem templates across different mathematical domains. Each row shows a problem category, specific problem type, a template example with its solution, illustrating the diversity of mathematical reasoning tasks from basic arithmetic to error diagnosis.

| Category | Problem Name | Template Example | Answer |
|---|---|---|---|
| **Calculation** | Arithmetic gcd | Calculate the greatest common divisor of 702 and 86814. | 234 |
| | prime factors | Find the second-largest prime factor of 49766. | 149 |
| | arithmetic matrix eigenvalues | Determine the largest eigenvalue by absolute value of the matrix: $[-8, 4, 4], [4, -1, 6], [4, 6, 5]$ | 10 |
| | arithmetic matrix svd | Calculate the rounded sum of all singular values from the SVD of: $[[3, -1, -3, 3], [-2, 2, 3, 4], [-2, 2, -3, 3], [-3, -4, 2, -1]]$ | 21 |
| | algebra linear equation | Solve $-523x + 5q + 30 = -522x, 4x + 0x - 33q = 146$ for $x$. | 20 |
| **Enumeration** | combinatory distribution | You have letters $\{'q' : 4, 'l' : 2, 'b' : 2\}$. Distribute them into 3 labeled boxes of capacities $[4, 2, 2]$. How many ways? | 26 |
| | logic gridworld | In a $7 \times 6$ grid, count all monotone paths from $(0, 0)$ to $(6, 5)$ avoiding cells $(6, 0), (3, 5), (1, 1)$. | 183 |
| | geometric lattice enumeration | Determine the largest eigenvalue by absolute value of the matrix: $[-8, 4, 4], [4, -1, 6], [4, 6, 5]$ | 1540 |
| | combinatorial permutation constraint | Five couples sit in a row of 10 seats; no one sits next to their partner. How many seating arrangements are possible? | 1263360 |
| | geometric symmetry counting | How many distinct ways to color the faces of a cube with 6 distinct colors so that adjacent faces have different colors? | 30 |
| **Simulation** | Number-sequence simulation | The integers 1–120 are written on a board. Each minute replace each $n$ by $d(n + 3)$, the divisor-count function. After a day, what is the sum of the numbers on the board? | 240 |
| | Stochastic walk / boundary-hitting | A frog starts at $(1, 2)$ inside a $4 \times 4$ square, jumping randomly by unit steps along coordinate axes until it hits the boundary. What is the probability it stops on a vertical side? | $\frac{5}{8}$ |
| | Expected-value stopping time | Joseph rolls a fair die repeatedly until he gets 3 identical consecutive rolls. What is the expected number of rolls? | 43 |
| | Iterated redistribution process | Five balls are placed in the first five boxes of a row of six boxes. If any box has $\geq 2$ balls, move one ball to the next box on the right. Repeat until all first five boxes have $\leq 1$ ball. In how many initial placements does the last box end up empty? | 1296 |
| | Financial iterative growth | Bao invests \$1000 at $10\%$ annual compound interest. How much total interest is earned after 3 years? | 331 |
| **Fact Retrieval** | Euler's formula / circle geometry | Midpoint $H$ of chord $PQ$ in unit circle; chord length $2 \sin \frac{t}{2}$. Find $H$ in terms of $t$. | $\left(\cos \frac{t}{2} \cos t, \cos \frac{t}{2} \sin t\right)$ |
| | Chinese Remainder Theorem / Euler's totient | Smallest $x \in \mathbb{N}$ with $x \equiv 3^{234} \pmod{700}$. | 169 |
| | Binomial/Chebyshev cosine multiple-angle | If $\cos \theta = \frac{1}{4}$, find $\cos 5\theta$. | $\frac{61}{64}$ |
| | Inclusion–Exclusion | Count integers $7 \leq n \leq 59$ relatively prime to 15. | 29 |
| | Great-circle distance (spherical law of cosines) | Surface distance on radius-$r$ sphere between $(p_1, q_1)$ and $(p_2, q_2)$. | $r \arccos(\sin q_1 \sin q_2 \cos(p_2 - p_1) + \cos q_1 \cos q_2)$ |
| **Diagnostic** | Problem-statement drift (sign/parameter flip) | Solver inadvertently changes the original problem (flips sign, replaces parameter), solving a different equation. **Example:** Asked to solve $x^2 - 3x + 2 = 0$ but solves $x^2 + 3x + 2 = 0$. | NA |
| | Internal inconsistency in trace | Derivation steps contradict stated givens or earlier results (e.g., variable values change mid-solution). **Example:** Declares $f(0) = 1$ initially but later uses $f(0) = 0$. | NA |
| | Tool / theorem mislabeling or misuse | Applies wrong theorem or uses one without meeting its conditions. **Example:** Uses Mean Value Theorem on a non-continuous or non-differentiable function. | NA |
| | Domain / legality mistakes | Ignores domain restrictions (division by zero, square roots of negatives, invalid trig ranges). **Example:** Cancels $(x - 1)$ without noting $x = 1$ is excluded. | NA |
| | Answer / format mismatch | Final answer doesn't match derived quantity or required format (units, boxed form, multiple-part). **Example:** Computes 12 but reports $3x^2 = 12$, or omits required components. | NA |

Figure 10: Distribution of math problems subcategories in our newly created dataset, grouped by behavioral facets: Calculation, Enumeration, Fact Retrieval, Simulation, and Diagnostic. Each bar shows the proportion (percentage) of problems belonging to a subcategory, with colored segments indicating the corresponding facet. This visualization highlights the relative prevalence of different cognitive skill types across the dataset.

Figure 11: Distribution of physics subcategories in our newly created dataset, grouped by behavioral facets: Calculation, Enumeration, Fact Retrieval, Simulation, and Diagnostic. Each bar indicates the percentage of problems belonging to a specific subcategory, with colors corresponding to the facet type. The plot highlights the diverse coverage of physics domains such as Mechanics, Electromagnetism, Thermodynamics, Optics, and others across different cognitive skill requirements.

Figure 12: Distribution of code problem subcategories in our dataset, grouped by behavioral facets: Calculation, Diagnostic, Enumeration, Fact Retrieval, and Simulation. The figure highlights a diverse and well-balanced coverage of programming tasks including graph/tree problems, string manipulation, enumeration, dynamic programming, and simulation-based challenges, demonstrating the dataset's quality and breadth for evaluating reasoning in algorithmic contexts.

Figure 13: Distribution of non-reasoning subcategories in our dataset, grouped by behavioral facets: Calculation, Diagnostic, Enumeration, Fact Retrieval, and Simulation. The figure shows a diverse and balanced coverage of real-world tasks including writing and summarization, error detection, enumeration of content, knowledge retrieval, and interactive or scenario-based activities, underscoring the dataset's breadth and quality for evaluating models beyond core reasoning skills.