Agentic Aggregation for Parallel Scaling of Long-Horizon Agentic Tasks

Yoonsang Lee [1]   Howard Yen [1]   Xi Ye [1]   Danqi Chen [1]

Abstract

We study parallel test-time scaling for long-horizon agentic tasks such as agentic search and deep research, where multiple rollouts are generated in parallel and aggregated into a final response. While such scaling has proven effective for chain-of-thought reasoning, agentic tasks pose unique challenges: trajectories are long, multi-turn, and tool-augmented, and outputs are often open-ended. Aggregating only final answers discards rich information from trajectories, while concatenating all trajectories exceeds the model's context window. To address this, we propose **AggAgent**, an *aggregation agent that treats parallel trajectories as an environment*. We equip it with lightweight tools to inspect candidate solutions and search across trajectories, enabling it to navigate and synthesize information on demand. Across six benchmarks and three model families (GLM-4.7, Qwen3.5, MiniMax-M2.5), AggAgent outperforms all existing aggregation methods— by up to 5.3% absolute on average and 10.3% on two deep research tasks—while adding minimal overhead, as the aggregation cost remains bounded by a single agentic rollout. Our findings establish agentic aggregation as an effective and cost-efficient approach to parallel scaling.

1. Introduction

Scaling test-time compute has emerged as a promising avenue for enhancing the performance of large language models (LLMs) (Wei et al., 2022; Wang et al., 2023; Brown et al., 2024; Welleck et al., 2024; Snell et al., 2025; Muennighoff et al., 2025). This success has largely been demonstrated in standard chain-of-thought (CoT) tasks such as mathematical reasoning and coding (Qi et al., 2025; Zhao et al., 2025). However, *long-horizon agentic tasks* (e.g., deep

Figure 1. **AggAgent consistently outperforms existing aggregation methods.** We measure the average performance across six long-horizon agentic benchmarks (Section 4) against the number of parallel trajectories. The same model as the rollout agent serves as the aggregator.

research, software engineering, web navigation) present a fundamentally different challenge: trajectories are multi-turn, spanning hundreds of steps with interleaved tool calls and observations (Yao et al., 2022b).

In this work, we study *parallel scaling* for long-horizon agentic tasks, an approach proven effective for CoT reasoning tasks yet largely unexplored for agentic search and deep research. Parallel scaling enables simultaneous generation of multiple independent trajectories, offering a natural computational advantage (Zhao et al., 2025). Furthermore, parallel scaling offers substantial improvement over single-agent performance (Wei et al., 2025; Li et al., 2026): for instance, GLM-4.7-Flash (Zeng et al., 2025) improves from 27% to 59% on BrowseComp (Wei et al., 2025) and 25% to 51% on HLE (Phan et al., 2025) when scaling from Pass@1 to Pass@8, confirming that correct solutions frequently exist within the parallel rollouts.

The central question then becomes how to effectively *aggregate* these trajectories. While voting and solution aggregation methods have proven effective for mathematical reasoning and coding (Wang et al., 2023; Fu et al., 2026; Zhao et al., 2025), long-horizon agentic tasks pose distinct challenges: evidence is sparse and distributed across multi-turn trajectories, demanding reasoning far beyond shallow heuristics and final solutions (Li et al., 2025a). Furthermore, individual trajectories may each capture only partial progress toward a complex task, requiring cross-trajectory synthesis to assemble a complete solution (Chang et al., 2026). However, existing approaches fall short (Table 1): aggregating only final solutions discards the rich informa-

[1]Princeton Language and Intelligence, Princeton University. Correspondence to: Yoonsang Lee <yoonsang@cs.princeton.edu>.

Published at the Second Workshop on Agents in the Wild: Safety, Security, and Beyond (AIWILD) at ICML 2026. Copyright 2026 by the author(s).

Figure 2. **Overview of aggregation methods for parallel scaling. (Top)** An agent produces $K = 3$ independent rollouts on a long-horizon task. **(Bottom)** *Solution Aggregation* feeds only final solutions to an LLM, discarding intermediate reasoning. *Summary Aggregation* compresses each trajectory into a lossy summary. **AggAgent** (ours) navigates trajectories via tools in an agentic manner, enabling full-fidelity cross-trajectory reasoning at low cost.

tion in trajectories, summarizing trajectories is expensive and lossy, and concatenating all trajectories into a single context is infeasible, as each trajectory spans hundreds of thousands of tokens.

To address these challenges, we propose **AggAgent**, which frames aggregation itself as an agentic task, treating the set of trajectories as an environment to interact with (Figure 2). AggAgent interacts with trajectories on demand through three lightweight tools: `get_solution` (retrieve final solutions of one or all trajectories), `search_trajectory` (keyword search within a trajectory), and `get_segment` (read a specific range of steps). Since these tools operate entirely over an array of completed trajectories—rather than invoking external services like web search or code execution—they incur none of the API cost or latency of such external tools. This agentic aggregation allows for cross-trajectory reasoning and synthesis without the cost of loading all trajectories into context, preserving full fidelity while keeping the aggregation cost bounded by a single agentic rollout.

We evaluate AggAgent on six agentic search and deep research benchmarks across three model families (GLM-4.7, Qwen3.5, MiniMax-M2.5). AggAgent consistently outperforms all baselines (Figure 1), improving performance by up to 5.3 points on average and 10.3 points on deep research tasks. Furthermore, AggAgent is Pareto-optimal in cost and performance (Figure 3), adding only a 5.7% overhead over the cost of running 8 parallel agents—compared to 41% for Summary Aggregation—by selectively reading portions of trajectories rather than loading them entirely into context. Notably, AggAgent even surpasses Pass@8 (Section 6.1),

demonstrating that effective aggregation can synthesize correct solutions beyond what any single rollout achieves. To summarize, our results show that agentic aggregation is a scalable and effective paradigm for test-time scaling in long-horizon tasks. We demonstrate that AggAgent is effective with off-the-shelf LLMs, and our framework further opens a promising direction for training aggregator agents.[1]

2. Problem Formulation

We study long-horizon tasks such as agentic search and deep research. Given a problem q, the goal is to produce an output y, which may be either a short answer, a set of answers, or a long-form report. An agent A interacts with an external environment to solve q by generating a trajectory $T = (q, r_1, a_1, o_1, \ldots, r_m, a_m, o_m, y)$, where each step consists of internal thinking r_j, tool call a_j, and resulting observation o_j. In parallel scaling, we run the same agent independently for K times, yielding $\mathcal{T} = \{T_1, T_2, \ldots, T_K\}$. This setting is natural in production deployments of frontier systems (Anthropic, 2025; Cursor, 2025; Kimi Team et al., 2026), as the latency is determined by the slowest of the K rollouts.

The core problem centers around how to aggregate these K trajectories and synthesize a better solution y. We formalize aggregation as a function $f : (q, \mathcal{T}) \mapsto \hat{y}$, where $\hat{y}$ is the aggregated final solution. For agentic search, $\hat{y}$ is evaluated against the ground-truth answer y^*, while for deep research, it is evaluated against problem-specific rubrics.

---

[1] Our code is available at https://github.com/princeton-pli/AggAgent.

Criterion	MV	WMV	BoN	FewTool	SolAgg	SummAgg	AggAgent (Ours)
Task-agnostic	✗	✗	✓	✓	✓	✓	✓
Non-heuristic	✗	✗	✗	✗	✓	✓	✓
Trajectory Info.	✗	✗	✗	✗	✗	✓	✓
Full Fidelity	✗	✗	✗	✗	✗	✗	✓
Aggregation Cost	Zero	Zero	Zero	Zero	Low	High	Low

Table 1. **Comparison of aggregation methods**. **Task-agnostic**: not restricted to single short answers, applicable to multi-answer and long-form tasks. **Non-heuristic**: does not rely on shallow signals such as frequency or confidence. **Trajectory Info.**: reasons over full trajectories beyond final solutions. **Full Fidelity**: accesses trajectories without compression or information loss. **Aggregation Cost**: additional inference cost beyond the rollouts.

Existing methods We adopt the following aggregation methods from prior works:

- **Majority Voting** (MV) (Wang et al., 2023): selects the most frequent solution. However, voting methods do not work for multi-answer or long-form generation tasks.
- **Best-of-N** (BoN) (Cobbe et al., 2021; Uesato et al., 2022): selects the solution with the highest self-reported confidence. While reward model scores are commonly used as the weight for CoT reasoning tasks, recent works on agentic tasks have adopted the model's self-reported confidence as the weight (Wei et al., 2025; Zhu et al., 2026).
- **Weighted Majority Voting** (WMV) (Li et al., 2023; Wu et al., 2024): selects the solution with the highest total weight, where each solution is weighted by self-reported confidence.
- **Fewest Tool Calls** (FewTool) (Liu et al., 2025; Lu et al., 2025): selects the solution from the trajectory that required the fewest tool calls.
- **Solution Aggregation** (SolAgg) (Qi et al., 2025; Zhao et al., 2025; Qiao et al., 2025): concatenates all K solutions and prompts an LLM to synthesize a final solution.
- **Summary Aggregation** (SummAgg) (Li et al., 2025a; Hu et al., 2026): compresses each trajectory into a summary report, concatenates all reports, and prompts an LLM to generate a final solution.

We classify these baselines into two groups. *Heuristic methods* (MV, WMV, BoN, FewTool) rely on shallow signals such as answer frequency, confidence scores, or trajectory length, without inspecting trajectory content. *LLM-based methods* (SolAgg, SummAgg) leverage LLM reasoning for solution synthesis but remain limited: Solution Aggregation aggregates only final solutions, discarding all intermediate evidence, while Summary Aggregation compresses each trajectory into a summary report before aggregation, incurring irreversible information loss and requiring K additional LLM calls. Table 1 summarizes these limitations.

3. Our Approach: AggAgent

To address the aforementioned limitations, we propose AggAgent, where the aggregator interacts with $\mathcal{T}$ directly in an agentic manner. The initial user message provides the problem q and trajectory metadata, which consists of the number of steps, total token count, and tool usage statistics for each trajectory T_i. The trajectories themselves are not pre-loaded into the context but reside in the environment and are retrieved on-demand, keeping the aggregation cost bounded by a single context window independent of K. This design enables cross-trajectory reasoning at full fidelity and low cost (Table 1).

Tool design We provide AggAgent with four tools as follows[2]:

- `get_solution(traj_id)`: Retrieves the final solution from each trajectory's last step. Unless traj_id is specified, returns all K solutions by default.
- `search_trajectory(traj_id, query, role, k)`: Searches for keywords within a single trajectory. Returns the top matching k steps ranked by ROUGE-L score (Lin, 2004).
- `get_segment(traj_id, start_step, end_step)`: Reads the full content of a contiguous range of steps from a single trajectory. Returns raw thinking and tool observations for the specified window.
- `finish()`: Submits the final solution along with a reason for the aggregation.

Workflow The tool design reflects a natural coarse-to-fine investigative workflow. Rather than reading every trajectory in full, the agent first surveys the metadata and solutions loaded by `get_solution` to identify consensus and disagreements across the rollouts, and to pinpoint trajectories worth closer inspection. It then selectively dives into individual trajectories via `search_trajectory` and `get_segment` to verify key claims against think-

---

[2]We provide the full tool descriptions in Figure 18 in the appendix.

ing blocks and tool observations. After sufficient cross-trajectory validation, it calls `finish` to submit the final synthesized solution. We provide the full prompts in Appendix B.

Cost analysis   Aggregation cost is measured in additional LLM calls beyond the K rollouts. Heuristic methods require zero additional calls, while Solution Aggregation requires a single LLM call to synthesize the K solution candidates. Summary Aggregation is the most expensive, as it requires K separate LLM calls before aggregation, each of which can be as long as the maximum context window. In contrast, AggAgent's total context is bounded by a single context window of the model, keeping aggregation cost independent of K and comparable to Solution Aggregation. Moreover, as AggAgent's tools operate entirely over the in-memory trajectory array, they incur none of the latency or cost of external tools like web search and code execution.

4. Experimental Setup

Tasks   We evaluate on six long-horizon agentic tasks broadly in two categories: 1) **Agentic search**: **BrowseComp** (Wei et al., 2025) consists of challenging factual questions demanding exhaustive multi-step web browsing; **BrowseComp-Plus** (Chen et al., 2025) enables controlled evaluation on BrowseComp questions by replacing web search with a local knowledge base; **HLE** (Phan et al., 2025) covers expert-level questions across diverse academic disciplines, emphasizing rigorous reasoning; **DeepSearchQA** (Gupta et al., 2026) targets multi-answer queries where completeness across all valid answers is required. 2) **Deep research**: **Healthbench-Hard** (Arora et al., 2025) requires generating comprehensive long-form responses to challenging medical queries; **ResearchRubrics** (Sharma et al., 2025) poses open-ended research tasks evaluated against detailed, multi-criterion rubrics.

Due to high costs of long-horizon rollouts, we randomly sample subsets for evaluation[3]. For HLE, we use 155 search-focused questions (Li et al., 2025a). For ResearchRubrics, we use the full 101 problems. For Healthbench-Hard, we randomly sample 100 instances. For all other tasks, we randomly sample 150 questions following Sun et al. (2025); Zhang et al. (2025a).

Models   We employ three model families of varying sizes for base trajectory rollouts: GLM-4.7-Flash (30B) (Zeng et al., 2025), Qwen3.5-122B-A10B (122B) (Qwen Team, 2026), and MiniMax-M2.5 (229B) (MiniMax, 2026). We adopt Tongyi DeepResearch (Tongyi DeepResearch Team et al., 2025) as the agent scaffold, use native function call-

ing, allow at most 128K context length with 100 tool calls, and sample 8 independent trajectories. For LLM-based aggregation, we use the same model as the rollout agent.

Rollout agent tools   For BrowseComp-Plus, we follow the official implementation and provide `search` and `get_document` tools using Qwen3-Embedding-8B (Zhang et al., 2025b) as the retriever. For all other tasks, we provide `search` and `visit` tools following prior work (Yen et al., 2025; Li et al., 2025b; Wu et al., 2025; Gao et al., 2026), where `search` uses Serper API[4] for Google search and `visit` uses crawl4ai[5] to scrape a specific web page.

Cost and latency   We report total cost and latency per query. Cost includes rollout, tool calls, and aggregation, while latency includes rollout and aggregation.

Evaluation   We employ LLM-as-a-judge, following the official evaluation setting. Specifically, we use Qwen3.5-397B-A17B for ResearchRubrics and GPT-4.1 (Achiam et al., 2023) for all other datasets. We evaluate Metric@$K \in \{1, 2, 4, 8\}$ over $N = 8$ independent trajectories via bootstrapped sampling:

$$\text{Metric@}K = \frac{1}{|Q|} \sum_{q \in Q} \left(\frac{1}{\binom{N}{K}} \sum_{\substack{S \subseteq \{1,\dots,N\} \\ |S|=K}} \mathcal{M}(\hat{y}, y^*) \right) \tag{1}$$

where Q is the dataset, S is a bootstrap sample of size K, and $\mathcal{M}$ is the scoring function between the predicted solution $\hat{y}$ and ground truth y^*. For LLM-based aggregation, evaluating all $\binom{N}{K}$ combinations is prohibitively expensive, so we cap the number of combinations to 3. For BrowseComp, BrowseComp-Plus, and HLE, $\hat{y}$ is evaluated against the gold answer y^*. For DeepSearchQA, the predicted answer set is considered correct if it exactly matches the gold answer set. For Healthbench-Hard and ResearchRubrics, the long-form response is evaluated across multiple problem-specific rubrics, and the scores are averaged. The rubrics contain negative scores, hence the total score could also be negative.

We provide further experimental details in Appendix A.

---

[3] We report standard deviation in Appendix C.1.

[4] https://serper.dev
[5] https://github.com/unclecode/crawl4ai

	Task	Pass@1	Heuristic Aggregation@8				LLM-based Aggregation@8		
			MV	WMV	BoN	FewTool	SolAgg	SummAgg	AggAgent
GLM-4.7-Flash	BrowseComp	27.42	32.67	50.67	51.33	41.33	53.33	55.33	**56.00**
	BrowseComp-Plus	49.08	59.33	68.67	68.67	62.00	70.67	70.67	**71.33**
	HLE	25.00	26.45	27.74	30.97	27.10	32.90	34.84	**37.42**
	DeepSearchQA	32.42	–	–	35.33	33.33	46.00	47.33	**49.33**
	Healthbench-Hard	8.67	–	–	9.91	8.90	15.72	7.35	**27.99**
	ResearchRubrics	37.47	–	–	37.70	35.21	36.84	31.72	**45.31**
	Average	30.01	32.84	37.61	38.99	34.65	42.58	41.21	**47.90**
Qwen3.5-122B	BrowseComp	40.25	47.33	60.00	58.67	56.00	61.33	62.00	**62.67**
	BrowseComp-Plus	58.67	66.67	69.33	74.00	70.67	73.33	73.33	**74.67**
	HLE	39.35	43.87	45.16	53.55	41.29	50.97	50.32	**54.19**
	DeepSearchQA	49.25	–	–	57.33	54.67	62.67	64.00	**66.00**
	Healthbench-Hard	12.87	–	–	13.01	12.83	26.30	23.00	**28.06**
	ResearchRubrics	40.50	–	–	42.37	39.58	42.10	37.47	**49.36**
	Average	40.15	43.42	46.19	49.82	45.84	52.78	51.69	**55.83**
MiniMax-M2.5	BrowseComp	50.17	60.67	66.67	70.67	67.33	70.67	70.00	**71.33**
	BrowseComp-Plus	64.17	68.67	75.33	76.00	74.67	76.67	76.67	**77.33**
	HLE	45.73	53.55	57.42	58.06	46.45	54.19	58.06	**60.00**
	DeepSearchQA	54.42	–	–	64.00	56.00	62.00	61.33	**65.33**
	Healthbench-Hard	9.67	–	–	8.79	5.34	21.84	16.92	**24.46**
	ResearchRubrics	39.97	–	–	39.00	38.44	44.00	40.29	**45.42**
	Average	44.02	47.83	50.58	52.75	48.04	54.90	53.88	**57.31**

Table 2. **AggAgent performs the best across all settings.** We evaluate on six long-horizon tasks using three model families, each generating $K=8$ independent rollouts. For LLM-based aggregation methods, the same model is used for both rollout and aggregation. Best metric per row is bolded. – denotes that voting-based methods are not applicable, and we use Pass@1 instead to calculate the average.

5. Results

5.1. Main Results

We present the main results on $K = 8$ in Table 2, and present the full results ($K \in \{1, 2, 4, 8\}$) in Appendix C.1. AggAgent consistently outperforms all baselines across all three models, improving over Pass@1 by 13.3–17.9 points and over the strongest baseline (SolAgg) by 2.4–5.3 points in average score.

Among the heuristic baselines, Majority Voting performs the worst, while confidence-based methods (WMV, BoN) yield substantial improvements, consistent with prior observations (Wei et al., 2025). However, the gains are less pronounced on DeepSearchQA, Healthbench-Hard, and ResearchRubrics, where the model is poorly calibrated (see Section 6.5 for details). Notably, voting methods are not applicable to multi-answer or long-form tasks, so their performance gains are limited to single-answer tasks only.[6] Fewest Tool Calls has been popular on BrowseComp due to its simplicity (Liu et al., 2025; Lu et al., 2025), but our results show that it also does not generalize well beyond such tasks.

---

[6]We use Pass@1 instead to calculate the average score.

Meanwhile, LLM-based methods consistently outperform heuristic baselines. Summary Aggregation outperforms all other baselines on agentic search tasks, as access to full trajectory evidence aids answer verification. However, it falls significantly behind Solution Aggregation on deep research tasks, as trajectory compression harms the detail and coherence of long-form responses. While no single baseline is universally optimal, AggAgent achieves strong performance by enabling fine-grained reasoning over trajectories without sacrificing detail or coherence.

5.2. Cost and Latency vs. Performance

We compare cost and latency versus performance for different numbers of samples $K \in \{2, 4, 8\}$ in Figure 3 (full breakdown in Appendix C.2). As K increases, all methods become more expensive and slower due to additional rollouts. AggAgent and Solution Aggregation introduce only minimal overhead beyond heuristic baselines—at $K=8$, their overhead over the rollout cost is 5.7% and 3.7%, respectively—yet substantially outperform them. Interestingly, their overhead does not increase proportionally to K, suggesting that having more samples can sometimes make aggregation easier by providing stronger supporting evidence, partially offsetting the extra computation spent on harder instances. In contrast, Summary Aggregation in-

Figure 3. **AggAgent achieves a Pareto-optimal performance–efficiency tradeoff**. We compare aggregation methods at $K \in \{2, 4, 8\}$ parallel samples, averaging performance across six benchmarks, with the same model serving as both rollout agent and aggregator. For each model, the top chart plots average cost (USD per query) vs. performance and the bottom chart plots average latency (seconds per query) vs. performance.

curs 41% overhead at $K=8$ because it must compress each trajectory before aggregation. Overall, AggAgent achieves Pareto-optimal performance and efficiency across benchmarks, showing that agentic aggregation scales efficiently with test-time compute without incurring substantial additional cost.

6. Analysis and Discussion

6.1. Stronger Models for Aggregation

Could aggregation benefit from employing a stronger model? We investigate this by replacing the aggregator with MiniMax-M2.5 while keeping GLM-4.7-Flash as the base rollout agent. As shown in Figure 4 (full results in Table 11 in the appendix), using a stronger aggregator generally improves performance, with MiniMax-based AggAgent achieving the highest average score and even surpassing Pass@8 on BrowseComp-Plus. This points to *asymmetric model allocation*—a stronger model for aggregation, weaker models for parallel rollouts—as a practical strategy for designing multi-agent systems, consistent with prior work employing stronger models as orchestrators over multiple weaker subagents (Qiao et al., 2025; Zhang et al., 2025a; Akay et al., 2026). In our setting, the aggregator plays the orchestrating role, reasoning across parallel trajectories to produce a final solution.

6.2. Output Design Ablation: Synthesis vs. Selection

We ablate the output design of AggAgent by comparing it against a selection variant, which selects the single best trajectory and adopts its solution directly instead of synthesizing a new solution. As shown in Figure 5, AggAgent performs better overall, though the selection variant remains competitive in some settings. Notably, the selection variant performs poorly on deep research benchmarks, where AggAgent outperforms it by a large margin. We attribute this to a mismatch between selection and the nature of open-ended research tasks: quality is distributed across trajectories so no single trajectory dominates, yet selection forces an all-or-nothing commitment. Synthesis mitigates this by making local, compositional judgments about which parts of each trajectory to incorporate, rather than committing to a global winner. This distinction is less pronounced for agentic search, where trajectories tend to be clearly correct or clearly wrong, making selection more straightforward. These results suggest that synthesis is often the preferable output design, consistent with our findings in Section 6.1 and 6.4 that AggAgent can compose a correct solution from individually incorrect trajectories. We leave a more thorough ablation of output design to future work.

6.3. Tool Usage Patterns

In this section, we analyze the tool usage behaviour of AggAgent. As depicted in Figure 6,

Figure 4. **Employing a stronger aggregator improves performance on LLM-based aggregation methods**. In all cases, GLM-4.7-Flash serves as the rollout agent; blue bars replace the aggregator with the stronger MiniMax-M2.5, while red bars use GLM-4.7-Flash for both roles. Yellow hatched bars denote the Pass@K. All methods are evaluated at $K=8$.

search_trajectory accounts for the majority of tool calls, while get_solution and finish are each invoked approximately once per query, consistent with the intended workflow: solutions are surveyed once at the start and the agent terminates after the final synthesis. Meanwhile, get_segment is used relatively less than search_trajectory, suggesting that AggAgent reserves full-content reads for cases where keyword-level search alone is insufficient, diving deep only when actually needed. We also observe that stronger models tend to require fewer tool calls overall, suggesting more capable models reach a final solution more efficiently. Deep research tasks similarly exhibit fewer tool calls, potentially due to less need for resolving precise factual conflicts across trajectories.

6.4. Qualitative Analysis

We qualitatively analyze cases where AggAgent succeeds in producing correct answers. AggAgent demonstrates four key behaviours (Figure 7): (1) **Minority answer identification**: identifying the correct answer from multiple trajectories, even when it is held by only a minority, (2) **Disagreement resolution**: resolving inconsistencies and conflicts across trajectories to arrive at a coherent answer, (3) **Cross-trajectory synthesis**: constructing a correct solution by reasoning over trajectories that are all incorrect, and (4) **Heuristic interpretation**: leveraging heuristic signals such as majority vote and confidence scores to guide aggregation, while not relying on them entirely. Together, these behaviours highlight AggAgent's capacity for nuanced, evidence-driven reasoning across parallel trajectories beyond simple voting or selection.

6.5. Confidence Calibration

While prior work has demonstrated the effectiveness of confidence-based aggregation strategies such as Weighted Majority Voting and Best-of-N (Wei et al., 2025; Li et al., 2025a), we find that these methods do not consistently generalize across benchmarks. All three models show well-calibrated confidence on BrowseComp-Plus and BrowseComp (large $C - W$ gap), but are less calibrated on HLE and DeepSearchQA. Moreover, on Healthbench-Hard and ResearchRubrics, confidence is essentially uncorrelated with quality ($r \approx 0$; see Figure 11 in the appendix). We hypothesize that this miscalibration explains why confidence-based methods plateau or even degrade as K increases on those tasks. In contrast, LLM-based aggregation, and especially AggAgent, scales reliably with K across all benchmarks.

7. Related Work

Long-horizon agents LLM agents have emerged as a powerful paradigm, extending language models beyond pure parametric generation to interactive problem solving in external environments. ReAct (Yao et al., 2022b) has been the most prominent workflow, interleaving reasoning, action selection, and environment observations. This has enabled a wide range of applications, including agentic RAG (Jin et al., 2025b; Li et al., 2025c; Jin et al., 2025a), software engineering (Jimenez et al., 2024; Yang et al., 2024; Wang et al., 2025), web navigation (Yao et al., 2022a; Chae et al., 2025; Gandhi & Neubig, 2026), and deep research systems (OpenAI, 2025; Anthropic, 2025; Roucher et al., 2025). Recent work has sought to improve agentic capabilities through advances in RL algorithms (Shao et al., 2024; 2025; Ritter et al., 2026), agentic mid-training (Su et al., 2025), and environment scaling (Fang et al., 2025). Our work is com-

Figure 5. **Ablation of solution synthesis vs. best-trajectory selection**. AggAgent synthesizes a new solution from the collected trajectories; the selection variant selects the single best trajectory directly. Color indicates model (red: GLM-4.7-Flash, green: Qwen3.5-122B, blue: MiniMax-M2.5); line style and marker indicate method (solid + circle: AggAgent, dashed + diamond: selection variant).

Figure 6. **Average number of tool calls per query by AggAgent.** Numbers above each bar indicate the average total tool calls per query. search_trajectory dominates tool usage, while get_solution and finish are each called approximately once per query. get_segment is used more selectively, reflecting a coarse-to-fine strategy where AggAgent commits to full-content reads only when keyword-level search is insufficient.

plementary to these efforts: we treat these agents as rollout models and study how to aggregate parallel trajectories into a single high-quality solution.

Test-time scaling Early work on test-time scaling for CoT tasks (Kojima et al., 2022; Wei et al., 2022) such as math reasoning and coding showed clear gains from search-based strategies (Yao et al., 2023), extended thinking budgets (Muennighoff et al., 2025; Guo et al., 2025; Snell et al., 2025), majority voting (Wang et al., 2023; Brown et al., 2024), and learning-based aggregation (Qi et al., 2025; Zhao et al., 2025).

However, test-time scaling for long-horizon agents is more challenging, as trajectories are lengthy, heterogeneous, and difficult to compare using simple surface-level signals (e.g., majority or confidence). Parallel scaling with LLM-based aggregation mitigates this problem by generating multiple independent trajectories and reasoning over them to produce a final solution. WebResearcher (Qiao et al., 2025) concatenates final answers and prompts an LLM to synthesize a solution, while ParallelMuse (Li et al., 2025a) compresses each trajectory into a summary report before aggregation, incurring high cost and information loss. Concurrent with our work, KARL (Chang et al., 2026) feeds final answers back to the rollout agent with the same tools enabled, but it disregards full trajectories, and reusing rollout tools can be costly in practice. In contrast, AggAgent enables the aggregator to interact with trajectories in an agentic manner, supporting cross-trajectory reasoning without lossy compression or excessive cost. While AggAgent is training-free and effective with off-the-shelf LLMs, we leave fine-tuning the aggregator as a promising direction for future work.

Figure 7. Qualitative examples illustrating four key behaviours of AggAgent.

Orthogonal to our focus on parallel scaling, several works have studied sequential scaling to extend the effective horizon of a single agent through context management (Wu et al., 2025; Yen et al., 2025; Tang et al., 2025; Zeng et al., 2026), context folding (Sun et al., 2025; Ye et al., 2026), or iterative refinement (Zhu et al., 2026; Xiao et al., 2026).

8. Conclusion

We introduce AggAgent, an aggregation agent for parallel scaling of long-horizon agentic tasks. By treating parallel trajectories as an interactive environment and navigating them via lightweight in-memory tools, AggAgent enables cross-trajectory reasoning at full fidelity, while avoiding both the information loss of compression and the prohibitive cost of loading all trajectories into context. Across six benchmarks and three models, AggAgent consistently outperforms all baselines, achieving Pareto-optimal performance and efficiency. Our findings establish agentic aggregation as a principled and cost-efficient paradigm for parallel test-time scaling.

References

Achiam, J., Adler, S., Agarwal, S., Ahmad, L., Akkaya, I., Aleman, F. L., Almeida, D., Altenschmidt, J., Altman, S., Anadkat, S., et al. GPT-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.

Akay, Y. C., Kartal, M. Y., Alparslan, E., Ortakoyluoglu, F., and Akpinar, A. SPD-RAG: Sub-agent per document retrieval-augmented generation. *arXiv preprint arXiv:2603.08329*, 2026.

Anthropic. How we built our multi-agent research system, June 2025. URL https://www.anthropic.com/engineering/multi-agent-research-system.

Arora, R. K., Wei, J., Hicks, R. S., Bowman, P., Quiñonero-Candela, J., Tsimpourlas, F., Sharman, M., Shah, M., Vallone, A., Beutel, A., et al. HealthBench: Evaluating large language models towards improved human health. *arXiv preprint arXiv:2505.08775*, 2025.

Brown, B., Juravsky, J., Ehrlich, R., Clark, R., Le, Q. V., Ré, C., and Mirhoseini, A. Large language monkeys:

Scaling inference compute with repeated sampling. *arXiv preprint arXiv:2407.21787*, 2024.

Chae, H., Kim, S., Cho, J., Kim, S., Moon, S., Hwangbo, G., Lim, D., Kim, M., Hwang, Y., Gwak, M., Choi, D., Kang, M., Im, G., Cho, B., Kim, H., Han, J. H., Kwon, T., Kim, M., woo Kwak, B., Kang, D., and Yeo, J. Web-Shepherd: Advancing PRMs for reinforcing web agents. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025. URL https://openreview.net/forum?id=G2kMroO9UV.

Chang, J. D., Drozdov, A., Toshniwal, S., Oertell, O., Trott, A., Portes, J., Gupta, A., Koppol, P., Baheti, A., Kulinski, S., et al. KARL: Knowledge agents via reinforcement learning. *arXiv preprint arXiv:2603.05218*, 2026.

Chen, Z., Ma, X., Zhuang, S., Nie, P., Zou, K., Liu, A., Green, J., Patel, K., Meng, R., Su, M., et al. BrowseComp-Plus: A more fair and transparent evaluation benchmark of deep-research agent. *arXiv preprint arXiv:2508.06600*, 2025.

Cobbe, K., Kosaraju, V., Bavarian, M., Chen, M., Jun, H., Kaiser, L., Plappert, M., Tworek, J., Hilton, J., Nakano, R., et al. Training verifiers to solve math word problems, 2021. *URL https://arxiv. org/abs/2110.14168*, 9, 2021.

Cursor. Introducing cursor 2.0 and composer, October 2025. URL https://cursor.com/blog/2-0.

Fang, R., Cai, S., Li, B., Wu, J., Li, G., Yin, W., Wang, X., Wang, X., Su, L., Zhang, Z., et al. Towards general agentic intelligence via environment scaling. *arXiv preprint arXiv:2509.13311*, 2025.

Fu, Y., Wang, X., Zhang, H., Tian, Y., and Zhao, J. Deep think with confidence. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=8LqHs0KIM7.

Gandhi, A. and Neubig, G. Go-Browse: Training web agents with structured exploration. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=IpzRWE52yw.

Gao, J., Fu, W., Xie, M., Xu, S., He, C., Mei, Z., Zhu, B., and Wu, Y. Unlocking long-horizon agentic search with large-scale end-to-end RL. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=MfPDdPUGKi.

Guo, D., Yang, D., Zhang, H., Song, J., Wang, P., Zhu, Q., Xu, R., Zhang, R., Ma, S., Bi, X., et al. DeepSeek-R1: Incentivizing reasoning capability in LLMs via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025.

Gupta, N., Chatterjee, R., Haas, L., Tao, C., Wang, A., Liu, C., Oiwa, H., Gribovskaya, E., Ackermann, J., Blitzer, J., et al. DeepSearchQA: Bridging the comprehensiveness gap for deep research agents. *arXiv preprint arXiv:2601.20975*, 2026.

Hu, C., Du, H., Wang, H., Lin, L., Chen, M., Liu, P., Miao, R., Yue, T., You, W., Ji, W., et al. Step-DeepResearch technical report. *arXiv preprint arXiv:2512.20491*, 2025.

Hu, J., Zhang, Y., Shang, S., Yang, X., Peng, Y., Huang, Z., Zhou, H., Wu, X., Cheng, J., Wan, F., et al. PaCoRe: Learning to scale test-time compute with parallel coordinated reasoning. *arXiv preprint arXiv:2601.05593*, 2026.

Jimenez, C. E., Yang, J., Wettig, A., Yao, S., Pei, K., Press, O., and Narasimhan, K. R. SWE-bench: Can language models resolve real-world github issues? In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=VTF8yNQM66.

Jin, B., Yoon, J., Kargupta, P., Arik, S. O., and Han, J. An empirical study on reinforcement learning for reasoning-search interleaved LLM agents. *arXiv preprint arXiv:2505.15117*, 2025a.

Jin, B., Zeng, H., Yue, Z., Yoon, J., Arik, S. O., Wang, D., Zamani, H., and Han, J. Search-R1: Training LLMs to reason and leverage search engines with reinforcement learning. In *Second Conference on Language Modeling*, 2025b. URL https://openreview.net/forum?id=Rwhi91ideu.

Kimi Team, Bai, T., Bai, Y., Bao, Y., Cai, S., Cao, Y., Charles, Y., Che, H., Chen, C., Chen, G., et al. Kimi K2.5: Visual agentic intelligence. *arXiv preprint arXiv:2602.02276*, 2026.

Kojima, T., Gu, S. S., Reid, M., Matsuo, Y., and Iwasawa, Y. Large language models are zero-shot reasoners. *Advances in neural information processing systems*, 35: 22199–22213, 2022.

Kwon, W., Li, Z., Zhuang, S., Sheng, Y., Zheng, L., Yu, C. H., Gonzalez, J., Zhang, H., and Stoica, I. Efficient memory management for large language model serving with pagedattention. In *Proceedings of the 29th symposium on operating systems principles*, pp. 611–626, 2023.

Li, B., Zhang, D., Wu, J., Yin, W., Tao, Z., Zhao, Y., Zhang, L., Shen, H., Fang, R., Xie, P., et al. ParallelMuse: Agentic parallel thinking for deep information seeking. *arXiv preprint arXiv:2510.24698*, 2025a.

Li, K., Zhang, Z., Yin, H., Zhang, L., Ou, L., Wu, J., Yin, W., Li, B., Tao, Z., Wang, X., et al. WebSailor: Navigating super-human reasoning for web agent. *arXiv preprint arXiv:2507.02592*, 2025b.

Li, X., Dong, G., Jin, J., Zhang, Y., Zhou, Y., Zhu, Y., Zhang, P., and Dou, Z. Search-o1: Agentic search-enhanced large reasoning models. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 5420–5438, 2025c.

Li, Y., Lin, Z., Zhang, S., Fu, Q., Chen, B., Lou, J.-G., and Chen, W. Making language models better reasoners with step-aware verifier. In Rogers, A., Boyd-Graber, J., and Okazaki, N. (eds.), *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 5315–5333, Toronto, Canada, July 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.acl-long.291. URL https://aclanthology.org/2023.acl-long.291/.

Li, Z., Jiang, D., Ma, X., Zhang, H., Nie, P., Zhang, Y., Zou, K., Xie, J., Zhang, Y., and Chen, W. OpenResearcher: A Fully Open Pipeline for Long-Horizon Deep Research Trajectory Synthesis. *arXiv preprint arXiv:2603.20278*, 2026.

Lin, C.-Y. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pp. 74–81, Barcelona, Spain, July 2004. Association for Computational Linguistics. URL https://aclanthology.org/W04-1013/.

Liu, A., Mei, A., Lin, B., Xue, B., Wang, B., Xu, B., Wu, B., Zhang, B., Lin, C., Dong, C., et al. DeepSeek-V3.2: Pushing the frontier of open large language models. *arXiv preprint arXiv:2512.02556*, 2025.

Lu, R., Hou, Z., Wang, Z., Zhang, H., Liu, X., Li, Y., Feng, S., Tang, J., and Dong, Y. DeepDive: Advancing deep search agents with knowledge graphs and multi-turn RL. *arXiv preprint arXiv:2509.10446*, 2025.

MiniMax. MiniMax-M2.5, February 2026. URL https://huggingface.co/MiniMaxAI/MiniMax-M2.5.

Muennighoff, N., Yang, Z., Shi, W., Li, X. L., Fei-Fei, L., Hajishirzi, H., Zettlemoyer, L., Liang, P., Candès, E., and Hashimoto, T. B. s1: Simple test-time scaling. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 20286–20332, 2025.

OpenAI. Introducing deep research, February 2025. URL https://openai.com/index/introducing-deep-research/.

Phan, L., Gatti, A., Han, Z., Li, N., Hu, J., Zhang, H., Zhang, C. B. C., Shaaban, M., Ling, J., Shi, S., et al. Humanity's last exam. *arXiv preprint arXiv:2501.14249*, 2025.

Qi, J., Ye, X., Tang, H., Zhu, Z., and Choi, E. Learning to reason across parallel samples for LLM reasoning. *arXiv preprint arXiv:2506.09014*, 2025.

Qiao, Z., Chen, G., Chen, X., Yu, D., Yin, W., Wang, X., Zhang, Z., Li, B., Yin, H., Li, K., et al. WebResearcher: Unleashing unbounded reasoning capability in long-horizon agents. *arXiv preprint arXiv:2509.13309*, 2025.

Qwen Team. Qwen3.5: Towards native multimodal agents, February 2026. URL https://qwen.ai/blog?id=qwen3.5.

Ritter, D., Oertell, O., Guo, B., Chang, J., Brantley, K., and Sun, W. LLMs can learn to reason via off-policy RL. *arXiv preprint arXiv:2602.19362*, 2026.

Roucher, A., Villanova del Moral, A., Noyan, M., Wolf, T., and Fourrier, C. Open-source deepresearch - freeing our search agents, February 2025. URL https://huggingface.co/blog/open-deep-research.

Shao, R., Asai, A., Shen, S. Z., Ivison, H., Kishore, V., Zhuo, J., Zhao, X., Park, M., Finlayson, S. G., Sontag, D., et al. Dr. Tulu: Reinforcement learning with evolving rubrics for deep research. *arXiv preprint arXiv:2511.19399*, 2025.

Shao, Z., Wang, P., Zhu, Q., Xu, R., Song, J., Bi, X., Zhang, H., Zhang, M., Li, Y., Wu, Y., et al. DeepSeekMath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.

Sharma, M., Zhang, C. B. C., Bandi, C., Wang, C., Aich, A., Nghiem, H., Rabbani, T., Htet, Y., Jang, B., Basu, S., et al. ResearchRubrics: A benchmark of prompts and rubrics for evaluating deep research agents. *arXiv preprint arXiv:2511.07685*, 2025.

Snell, C. V., Lee, J., Xu, K., and Kumar, A. Scaling LLM test-time compute optimally can be more effective than scaling parameters for reasoning. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=4FWAwZtd2n.

Su, L., Zhang, Z., Li, G., Chen, Z., Wang, C., Song, M., Wang, X., Li, K., Wu, J., Chen, X., et al. Scaling agents via continual pre-training. *arXiv preprint arXiv:2509.13310*, 2025.

Sun, W., Lu, M., Ling, Z., Liu, K., Yao, X., Yang, Y., and Chen, J. Scaling long-horizon llm agent via context-folding. *arXiv preprint arXiv:2510.11967*, 2025.

Tang, Q., Xiang, H., Yu, L., Yu, B., Lu, Y., Han, X., Sun, L., Zhang, W., Wang, P., Liu, S., et al. Beyond turn limits: Training deep search agents with dynamic context window. *arXiv preprint arXiv:2510.08276*, 2025.

Tongyi DeepResearch Team, Li, B., Zhang, B., Zhang, D., Huang, F., Li, G., Chen, G., Yin, H., Wu, J., Zhou, J., et al. Tongyi deepresearch technical report. *arXiv preprint arXiv:2510.24701*, 2025.

Uesato, J., Kushman, N., Kumar, R., Song, F., Siegel, N., Wang, L., Creswell, A., Irving, G., and Higgins, I. Solving math word problems with process-and outcome-based feedback. *arXiv preprint arXiv:2211.14275*, 2022.

Wang, X., Wei, J., Schuurmans, D., Le, Q. V., Chi, E. H., Narang, S., Chowdhery, A., and Zhou, D. Self-consistency improves chain of thought reasoning in language models. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=1PL1NIMMrw.

Wang, X., Li, B., Song, Y., Xu, F. F., Tang, X., Zhuge, M., Pan, J., Song, Y., Li, B., Singh, J., Tran, H. H., Li, F., Ma, R., Zheng, M., Qian, B., Shao, Y., Muennighoff, N., Zhang, Y., Hui, B., Lin, J., Brennan, R., Peng, H., Ji, H., and Neubig, G. Openhands: An open platform for AI software developers as generalist agents. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=OJd3ayDDoF.

Wei, J., Wang, X., Schuurmans, D., Bosma, M., Xia, F., Chi, E., Le, Q. V., Zhou, D., et al. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837, 2022.

Wei, J., Sun, Z., Papay, S., McKinney, S., Han, J., Fulford, I., Chung, H. W., Passos, A. T., Fedus, W., and Glaese, A. BrowseComp: A simple yet challenging benchmark for browsing agents. *arXiv preprint arXiv:2504.12516*, 2025.

Welleck, S., Bertsch, A., Finlayson, M., Schoelkopf, H., Xie, A., Neubig, G., Kulikov, I., and Harchaoui, Z. From decoding to meta-generation: Inference-time algorithms for large language models. *Transactions on Machine Learning Research*, 2024. ISSN 2835-8856. URL https://openreview.net/forum?id=eskQMcIbMS. Survey Certification.

Wu, X., Li, K., Zhao, Y., Zhang, L., Ou, L., Yin, H., Zhang, Z., Yu, X., Zhang, D., Jiang, Y., et al. ReSum: Unlocking long-horizon search intelligence via context summarization. *arXiv preprint arXiv:2509.13313*, 2025.

Wu, Y., Sun, Z., Li, S., Welleck, S., and Yang, Y. Scaling inference computation: Compute-optimal inference for problem-solving with language models. In *The 4th Workshop on Mathematical Reasoning and AI at NeurIPS'24*, 2024. URL https://openreview.net/forum?id=j7DZWSc8qu.

Xiao, T., Yuan, Y., Ivison, H., Zhu, H., Brahman, F., Lambert, N., Dasigi, P., Smith, N. A., and Hajishirzi, H. Meta-reinforcement learning with self-reflection for agentic search. *arXiv preprint arXiv:2603.11327*, 2026.

Yang, J., Jimenez, C. E., Wettig, A., Lieret, K., Yao, S., Narasimhan, K., and Press, O. SWE-agent: Agent-computer interfaces enable automated software engineering. *Advances in Neural Information Processing Systems*, 37:50528–50652, 2024.

Yao, S., Chen, H., Yang, J., and Narasimhan, K. Web-Shop: Towards scalable real-world web interaction with grounded language agents. *Advances in Neural Information Processing Systems*, 35:20744–20757, 2022a.

Yao, S., Zhao, J., Yu, D., Du, N., Shafran, I., Narasimhan, K. R., and Cao, Y. ReAct: Synergizing reasoning and acting in language models. In *The eleventh international conference on learning representations*, 2022b.

Yao, S., Yu, D., Zhao, J., Shafran, I., Griffiths, T., Cao, Y., and Narasimhan, K. Tree of thoughts: Deliberate problem solving with large language models. *Advances in neural information processing systems*, 36:11809–11822, 2023.

Ye, R., Zhang, Z., Li, K., Yin, H., Tao, Z., Zhao, Y., Su, L., Zhang, L., Qiao, Z., Wang, X., Jiang, Y., Xie, P., Huang, F., Chen, S., and Zhou, J. AgentFold: Long-horizon web agents with proactive context folding. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=IuZoTgsUws.

Yen, H., Paranjape, A., Xia, M., Venkatesh, T., Hessel, J., Chen, D., and Zhang, Y. Lost in the maze: Overcoming context limitations in long-horizon agentic search. *arXiv preprint arXiv:2510.18939*, 2025.

Zeng, A., Lv, X., Zheng, Q., Hou, Z., Chen, B., Xie, C., Wang, C., Yin, D., Zeng, H., Zhang, J., et al. GLM-4.5: Agentic, reasoning, and coding (ARC) foundation models. *arXiv preprint arXiv:2508.06471*, 2025.

Zeng, A., Lv, X., Hou, Z., Du, Z., Zheng, Q., Chen, B., Yin, D., Ge, C., Xie, C., Wang, C., et al. GLM-5: from vibe coding to agentic engineering. *arXiv preprint arXiv:2602.15763*, 2026.

Zhang, A. L., Kraska, T., and Khattab, O. Recursive language models. *arXiv preprint arXiv:2512.24601*, 2025a.

Zhang, Y., Li, M., Long, D., Zhang, X., Lin, H., Yang, B., Xie, P., Yang, A., Liu, D., Lin, J., et al. Qwen3 embedding: Advancing text embedding and reranking through foundation models. *arXiv preprint arXiv:2506.05176*, 2025b.

Zhao, W., Aggarwal, P., Saha, S., Celikyilmaz, A., Weston, J., and Kulikov, I. The majority is not always right: RL training for solution aggregation. *arXiv preprint arXiv:2509.06870*, 2025.

Zhu, J., Zhang, G., Ma, X., Xu, L., Zhang, M., Yang, R., Wang, S., Qiu, K., Wu, Z., Dai, Q., et al. RE-TRAC: REcursive TRAjectory compression for deep search agents. *arXiv preprint arXiv:2602.02486*, 2026.

A. Experimental Details

A.1. Implementation

We serve all models via vLLM (Kwon et al., 2023) and use the Tongyi DeepResearch scaffold (Tongyi DeepResearch Team et al., 2025) for agentic workflow. We enable interleaved reasoning and native function calling, with temperature 1.0, top-p 0.95, a 128K context window, 10K max output tokens, and at most 100 tool calls per rollout. Upon exhausting the context limit or tool call budget, the model is given one final opportunity to submit an answer without tool access. All experiments are conducted on 4×H100 GPUs.

A.2. Rollout Agent Tools

BrowseComp-Plus The local corpus contains 100,195 documents. `search` uses Qwen3-Embedding-8B to retrieve the top-5 documents by score, with each snippet truncated to 512 tokens. `get_document` returns the full text of a document by docid, truncated to 4,096 tokens following Su et al. (2025).

- **`search(query)`**: Perform a search on a knowledge source. Returns top-5 hits with docid, score, and snippet. The snippet contains the document's contents (may be truncated based on token limits).
- **`get_document(docid)`**: Retrieve a full document by its docid.

All other datasets We adopt the tool implementation from SLIM (Yen et al., 2025). `search` queries Google Search via the Serper API (`https://serper.dev`), returning the top-10 results with snippets of at most 150 characters. `visit` scrapes a URL via crawl4ai (`https://github.com/unclecode/crawl4ai`) and extracts the snippet most relevant to a goal, ranked by ROUGE-L score (Lin, 2004).

- **`search(query)`**: Performs a web search: supply a string 'query'; the tool retrieves the top 10 results for the query.
- **`visit(url, goal)`**: Visit a webpage and return the relevant content based on the goal.

A.3. Cost Calculation

Let g_{in} and g_{out} denote the per-token input and output costs of a language model, and let g_s and g_v denote the per-call costs of `search` and `visit`, respectively. The total cost per question is $c = c_r + c_t + c_a$.

Rollout cost (c_r): Following Yen et al. (2025), cached input tokens are excluded from the token count, as caching is standard in long-trajectory settings with shared context. The total rollout cost is $c_r = \sum_i \left(g_{in} \cdot \Delta t_{in}^{(i)} + g_{out} \cdot t_{out}^{(i)} \right)$, where $\Delta t_{in}^{(i)} = t_{in}^{(i)} - t_{in}^{(i-1)}$.

Tool call cost (c_t): For BrowseComp-Plus, which uses a local corpus, $c_t = 0$. For all other tasks, $c_t = g_s \cdot n_s + g_v \cdot n_v$, where n_s and n_v are the total numbers of `search` and `visit` calls.

Aggregation cost (c_a): Only LLM-based aggregation methods incur additional aggregation cost. For Solution Aggregation, c_a is a single LLM call: $g_{in} \cdot t_{in} + g_{out} \cdot t_{out}$. For Summary Aggregation, this is summed over $K + 1$ calls. For AggAgent, c_a is computed identically to c_r, as it forms an agentic trajectory.

Cost is averaged over all instances for each benchmark. Pricing rates are given in Table 3. Prices are sourced from the respective provider websites: GLM-4.7-Flash (`https://docs.z.ai/guides/overview/pricing`), Qwen3.5-122B (`https://openrouter.ai/qwen/qwen3.5-122b-a10b`), MiniMax-M2.5 (`https://platform.minimax.io/docs/guides/pricing-paygo`), and tool calls (`https://www.firecrawl.dev/pricing`).

A.4. Latency Measurement

We measure latency by processing one problem at a time, using 2×H100 for GLM-4.7-Flash and 4×H100 for Qwen3.5-122B and MiniMax-M2.5.

Rollout latency (ℓ_r): Wall-clock time from the first step of the trajectory until termination.

Aggregation latency (ℓ_a): For Solution Aggregation, the time of the single LLM call. For Summary Aggregation, we spawn K summarization calls in parallel, wait for all to complete, then issue the final aggregation call; ℓ_a covers the full span. For AggAgent, ℓ_a is measured the same way as ℓ_r.

	Input	Output
Language Models (per 1M tokens)		
GLM-4.7-Flash	$0.07	$0.40
Qwen-3.5-122B	$0.26	$2.08
MiniMax-M2.5	$0.30	$1.20
Tool Calls (per 1K queries)		
`search`		$0.50
`visit`		$0.83

Table 3. Pricing used for cost calculation.

For latency, we sample 30 instances and report the median for efficiency, as latency must be measured sequentially. All other experiments run with batched generation.

A.5. Rollout Trajectory Statistics

We provide the statistics of base rollout trajectories in Table 4.

	Task	# Inst.	# Turns	Tokens (K)	Output (K)	# Tool Calls	Uniq. URLs
GLM-4.7-Flash	BrowseComp	150	$71.4_{0.9}$	$64.8_{1.0}$	$0.64_{0.05}$	$70.4_{0.9}$ (59.0/11.4)	$324.6_{9.4}$
	BrowseComp-Plus	150	$26.0_{0.8}$	$72.0_{1.8}$	$0.53_{0.01}$	$25.1_{0.8}$ (23.1/2.0)	$50.1_{0.7}$
	HLE	155	$34.4_{1.7}$	$40.9_{2.2}$	$1.39_{0.12}$	$31.9_{1.5}$ (22.8/9.1)	$86.8_{5.1}$
	DeepSearchQA	150	$53.4_{2.4}$	$48.3_{1.5}$	$0.71_{0.09}$	$52.6_{2.4}$ (37.9/14.7)	$126.8_{3.9}$
	Healthbench-Hard	100	$17.8_{1.6}$	$27.0_{2.5}$	$1.74_{0.07}$	$16.9_{1.6}$ (7.9/9.0)	$52.5_{6.1}$
	ResearchRubrics	101	$34.0_{1.8}$	$48.2_{2.1}$	$4.23_{0.11}$	$33.1_{1.8}$ (15.9/17.2)	$121.4_{6.7}$
Qwen3.5-122B	BrowseComp	150	$59.4_{1.0}$	$61.7_{1.8}$	$1.36_{0.19}$	$58.7_{1.0}$ (52.2/6.5)	$349.2_{9.4}$
	BrowseComp-Plus	150	$21.2_{0.3}$	$60.2_{1.0}$	$1.23_{0.11}$	$20.4_{0.4}$ (18.8/1.7)	$38.7_{0.6}$
	HLE	155	$26.5_{0.8}$	$35.6_{1.0}$	$1.86_{0.10}$	$25.2_{0.8}$ (18.2/7.0)	$84.2_{2.8}$
	DeepSearchQA	150	$40.4_{1.4}$	$45.9_{1.6}$	$1.04_{0.04}$	$39.4_{1.4}$ (26.9/12.6)	$116.5_{3.9}$
	Healthbench-Hard	100	$7.4_{0.2}$	$12.1_{0.3}$	$1.71_{0.03}$	$6.4_{0.2}$ (2.3/4.1)	$20.2_{1.0}$
	ResearchRubrics	101	$15.1_{0.0}$	$24.0_{0.0}$	$4.66_{0.00}$	$14.1_{0.0}$ (7.4/6.6)	$65.6_{0.0}$
MiniMax-M2.5	BrowseComp	150	$54.1_{1.2}$	$50.1_{1.4}$	$1.41_{0.10}$	$53.0_{1.2}$ (42.1/10.9)	$189.5_{5.8}$
	BrowseComp-Plus	150	$23.7_{0.5}$	$64.8_{1.3}$	$1.11_{0.12}$	$22.8_{0.5}$ (21.4/1.3)	$48.6_{1.2}$
	HLE	155	$28.4_{1.0}$	$42.3_{1.7}$	$2.08_{0.19}$	$26.8_{1.1}$ (17.9/8.9)	$79.4_{5.3}$
	DeepSearchQA	150	$44.0_{0.7}$	$49.1_{1.1}$	$1.33_{0.06}$	$42.9_{0.7}$ (26.6/16.3)	$122.0_{2.3}$
	Healthbench-Hard	100	$8.7_{0.4}$	$13.2_{0.6}$	$1.68_{0.08}$	$7.6_{0.4}$ (3.4/4.3)	$27.6_{1.6}$
	ResearchRubrics	101	$20.9_{0.6}$	$27.7_{0.5}$	$3.89_{0.07}$	$19.9_{0.6}$ (12.2/7.7)	$101.8_{5.1}$

Table 4. Trajectory statistics of base rollouts (8 per problem) across three models and six benchmarks. **# Inst.**: number of evaluation instances. **# Turns**: number of agent turns per trajectory. **Tokens (K)**: total input+output tokens in thousands. **Output (K)**: output tokens in thousands. **# Tool Calls**: total tool calls, broken down into search and visit calls (shown in parentheses; get_document is used instead of visit for BrowseComp-Plus). **Uniq. URLs**: number of unique URLs visited. All values are averaged over problems and rollouts, and subscripts denote standard deviation across rollout sets.

B. Prompts

Rollout agent   We use the system prompt from Tongyi DeepResearch (Tongyi DeepResearch Team et al., 2025) (Figure 12), with an additional instruction from Dr. Tulu (Shao et al., 2025) appended for deep research tasks (Figure 13). For agentic search tasks, we format the user message following BrowseComp (Wei et al., 2025) (Figure 14).

LLM-as-a-Judge   For BrowseComp, BrowseComp-Plus, and HLE, we find that the original evaluation prompt occasionally produces false judgments, hence we instead use the prompt from Zhu et al. (2026). For ResearchRubrics, we find that the original prompt is unreliable for negative rubrics — consistent with Hu et al. (2025) — so we append a clarifying section to the original prompt (Figure 15). For DeepSearchQA and Healthbench-Hard, we use the official evaluation prompts.

LLM-based aggregation For Solution Aggregation and Summary Aggregation, we use the prompt from Li et al. (2025a). For AggAgent, we present the prompts in Figure 16 (agentic search) and Figure 17 (deep research), and the full tool descriptions in Figure 18. We vary the solution field description of the `finish` tool (Figure 19) in the following cases: 1) Deep research tasks: the model is instructed to generate a long-form report. 2) Qwen3.5-122B: instructing the model to output in XML format sometimes causes tool parsing errors, so we use plain text format instead. This applies only to agentic search tasks.

C. Results

C.1. Main Results

We present the full results for Section 5.1 in Tables 5, 6, and 7. AggAgent achieves competitive performance not only at $K = 8$ but also at $K = 2$ and $K = 4$.

C.2. Cost and Latency vs. Performance

We present the full results for Section 5.2 in Figures 8, 9, and 10. The per-benchmark results are consistent with the averaged figures in the main paper, with AggAgent achieving optimal performance relative to cost and latency.

We also present the cost and latency breakdown in Tables 8, 9, and 10. Across all settings, AggAgent consistently incurs aggregation cost much below Summary Aggregation and comparable to Solution Aggregation.

C.3. Stronger Models for Aggregation

We present the full results for Section 6.1 in Table 11. While a stronger aggregator (MiniMax) generally improves performance across all LLM-based aggregation methods, AggAgent remains the most effective.

C.4. Confidence Calibration

We present the confidence calibration results in Figure 11; see Section 6.5 in the main text for discussion.

Task	K	Pass	Heuristic Aggregation				LLM-based Aggregation		
			MV	WMV	BoN	FewTool	SolAgg	SummAgg	AggAgent
BrowseComp	1	$27.42_{2.17}$	-	-	-	-	-	-	-
	2	$37.86_{2.63}$	$27.26_{2.36}$	$35.79_{3.03}$	$35.60_{3.04}$	$33.24_{2.47}$	$35.78_{1.13}$	$34.89_{2.45}$	$\mathbf{37.78_{1.37}}$
	4	$49.21_{2.04}$	$30.83_{1.82}$	$43.87_{2.41}$	$44.06_{2.64}$	$38.84_{1.93}$	$45.33_{0.0}$	$\mathbf{46.22_{0.83}}$	$45.78_{1.13}$
	8	58.67	32.67	50.67	51.33	41.33	53.33	55.33	**56.00**
BrowseComp-Plus	1	$49.08_{3.09}$	-	-	-	-	-	-	-
	2	$59.64_{1.76}$	$48.71_{3.03}$	$57.02_{2.33}$	$57.05_{2.08}$	$54.31_{2.41}$	$54.67_{3.40}$	$58.00_{1.44}$	$\mathbf{58.44_{1.37}}$
	4	$67.36_{1.54}$	$54.10_{1.98}$	$63.02_{2.05}$	$62.81_{1.92}$	$58.86_{1.81}$	$63.33_{1.89}$	$63.33_{0.54}$	$\mathbf{66.22_{0.83}}$
	8	72.00	59.33	68.67	68.67	62.00	70.67	70.67	**71.33**
HLE	1	$25.00_{2.36}$	-	-	-	-	-	-	-
	2	$34.01_{2.38}$	$25.32_{2.15}$	$28.09_{2.39}$	$28.29_{2.57}$	$26.04_{2.35}$	$29.68_{2.30}$	$30.75_{0.80}$	$\mathbf{31.40_{2.49}}$
	4	$42.88_{1.99}$	$26.58_{1.68}$	$29.62_{1.49}$	$30.08_{1.78}$	$26.53_{2.08}$	$30.97_{1.05}$	$31.83_{1.61}$	$\mathbf{32.47_{0.61}}$
	8	50.97	26.45	27.74	30.97	27.10	32.90	34.84	**37.42**
DeepSearchQA	1	$32.42_{4.36}$	-	-	-	-	-	-	-
	2	$43.55_{4.01}$	-	-	$36.02_{3.41}$	$33.26_{3.90}$	$33.78_{2.27}$	$38.44_{2.06}$	$\mathbf{40.44_{1.57}}$
	4	$54.26_{2.90}$	-	-	$38.06_{2.34}$	$33.89_{2.20}$	$42.44_{1.26}$	$\mathbf{43.56_{1.75}}$	$42.00_{1.44}$
	8	64.00	-	-	35.33	33.33	46.00	47.33	**49.33**
Healthbench-Hard	1	$8.67_{1.98}$	-	-	-	-	-	-	-
	2	$21.34_{1.65}$	-	-	$9.80_{2.15}$	$9.32_{1.72}$	$10.50_{2.10}$	$-1.21_{0.46}$	$\mathbf{24.45_{0.52}}$
	4	$31.96_{1.37}$	-	-	$9.65_{1.93}$	$8.48_{1.44}$	$13.70_{2.18}$	$4.76_{1.39}$	$\mathbf{25.36_{1.59}}$
	8	40.91	-	-	9.91	8.90	15.72	7.35	**27.99**
ResearchRubrics	1	$37.47_{0.97}$	-	-	-	-	-	-	-
	2	$42.71_{0.53}$	-	-	$37.46_{0.93}$	$37.41_{0.78}$	$33.84_{0.45}$	$27.69_{0.84}$	$\mathbf{41.32_{0.72}}$
	4	$46.57_{0.30}$	-	-	$37.68_{0.78}$	$36.55_{0.74}$	$37.15_{0.46}$	$30.83_{0.37}$	$\mathbf{43.70_{0.58}}$
	8	49.79	-	-	37.70	35.21	36.84	31.72	**45.31**
Average (GLM-4.7-Flash)	1	30.01	-	-	-	-	-	-	-
	2	39.85	29.98	33.24	34.04	32.26	33.04	31.43	**38.97**
	4	48.71	31.68	35.85	37.06	33.86	38.82	36.76	**42.59**
	8	56.06	32.84	37.61	38.99	34.65	42.58	41.21	**47.90**

Table 5. Performance comparison across aggregation strategies with GLM-4.7-Flash, with varying $K \in \{2, 4, 8\}$. The same model is used for both rollout and aggregation. **Bold** indicates the best-performing method per row (excluding Pass). Subscripts report standard deviation across runs. '-' denotes not applicable.

Task	K	Pass	Heuristic Aggregation				LLM-based Aggregation		
			MV	WMV	BoN	FewTool	SolAgg	SummAgg	AggAgent
BrowseComp	1	$40.25_{3.26}$	-	-	-	-	-	-	-
	2	$50.38_{2.66}$	$40.74_{2.95}$	$47.79_{2.82}$	$48.05_{2.98}$	$46.21_{2.82}$	$48.44_{1.00}$	$\mathbf{49.33}_{2.88}$	$48.89_{1.13}$
	4	$59.53_{1.84}$	$45.54_{2.13}$	$54.30_{2.62}$	$54.83_{2.38}$	$51.42_{2.22}$	$55.78_{0.83}$	$56.00_{0.94}$	$\mathbf{56.22}_{1.60}$
	8	67.33	47.33	60.00	58.67	56.00	61.33	62.00	$\mathbf{62.67}$
BrowseComp-Plus	1	$58.67_{2.13}$	-	-	-	-	-	-	-
	2	$67.36_{2.07}$	$58.14_{2.21}$	$64.93_{2.05}$	$64.98_{2.06}$	$64.36_{1.80}$	$66.00_{1.09}$	$65.56_{1.13}$	$\mathbf{66.44}_{1.13}$
	4	$73.86_{1.43}$	$63.44_{1.91}$	$69.10_{1.37}$	$69.78_{1.69}$	$68.54_{1.44}$	$69.51_{1.13}$	$\mathbf{71.78}_{0.83}$	$71.33_{1.89}$
	8	79.33	66.67	69.33	74.00	70.67	73.33	73.33	$\mathbf{74.67}$
HLE	1	$39.35_{2.39}$	-	-	-	-	-	-	-
	2	$50.12_{2.32}$	$39.19_{2.54}$	$43.71_{3.21}$	$43.71_{2.67}$	$39.26_{2.22}$	$45.16_{0.53}$	$45.59_{2.60}$	$\mathbf{45.81}_{0.53}$
	4	$59.87_{1.82}$	$42.29_{1.96}$	$45.28_{2.28}$	$47.43_{2.70}$	$39.30_{1.79}$	$49.25_{1.61}$	$47.96_{0.30}$	$\mathbf{51.40}_{0.80}$
	8	67.10	43.87	45.16	53.55	41.29	50.97	50.32	$\mathbf{54.19}$
DeepSearchQA	1	$49.25_{2.27}$	-	-	-	-	-	-	-
	2	$60.76_{2.08}$	-	-	$53.33_{2.23}$	$52.17_{2.55}$	$52.67_{2.88}$	$52.89_{2.06}$	$\mathbf{55.56}_{1.75}$
	4	$70.02_{1.62}$	-	-	$56.09_{2.21}$	$53.67_{2.40}$	$56.00_{1.44}$	$58.67_{1.09}$	$\mathbf{59.56}_{1.13}$
	8	76.67	-	-	57.33	54.67	62.67	64.00	$\mathbf{66.00}$
Healthbench-Hard	1	$12.87_{5.89}$	-	-	-	-	-	-	-
	2	$24.52_{3.88}$	-	-	$13.34_{4.26}$	$13.62_{3.73}$	$\mathbf{25.23}_{0.30}$	$18.84_{1.13}$	$24.95_{0.39}$
	4	$33.45_{2.25}$	-	-	$14.00_{2.76}$	$13.70_{2.25}$	$27.30_{1.91}$	$22.60_{1.33}$	$\mathbf{28.01}_{1.06}$
	8	40.74	-	-	13.01	12.83	26.30	23.00	$\mathbf{28.06}$
ResearchRubrics	1	$40.50_{0.91}$	-	-	-	-	-	-	-
	2	$44.77_{0.60}$	-	-	$40.71_{0.67}$	$40.02_{0.65}$	$41.17_{0.42}$	$34.25_{0.53}$	$\mathbf{44.49}_{0.52}$
	4	$48.11_{0.37}$	-	-	$40.88_{0.62}$	$39.77_{0.55}$	$41.41_{0.59}$	$36.29_{0.35}$	$\mathbf{46.61}_{0.42}$
	8	50.97	-	-	42.37	39.58	42.10	37.47	$\mathbf{49.36}$
Average **(Qwen3.5-122B)**	1	40.15	-	-	-	-	-	-	-
	2	49.65	40.12	43.18	44.02	42.61	46.45	44.41	$\mathbf{47.69}$
	4	57.47	42.32	45.22	47.17	44.40	49.88	48.88	$\mathbf{52.19}$
	8	63.69	43.42	46.19	49.82	45.84	52.78	51.69	$\mathbf{55.83}$

Table 6. Performance comparison across aggregation strategies with Qwen3.5-122B. The table is formatted the same as Table 5.

Task	K	Pass	Heuristic Aggregation				LLM-based Aggregation		
			MV	WMV	BoN	FewTool	SolAgg	SummAgg	AggAgent
BrowseComp	1	$50.17_{3.35}$	-	-	-	-	-	-	-
	2	$60.86_{2.32}$	$50.40_{2.15}$	$59.40_{2.36}$	$59.36_{2.34}$	$57.38_{2.47}$	$60.00_{1.63}$	$59.78_{1.13}$	$\mathbf{60.22}_{1.13}$
	4	$68.64_{1.69}$	$56.58_{2.19}$	$64.73_{1.88}$	$66.06_{2.01}$	$62.63_{1.64}$	$64.44_{0.63}$	$66.67_{0.54}$	$\mathbf{67.33}_{0.0}$
	8	73.33	60.67	66.67	70.67	67.33	70.67	70.00	$\mathbf{71.33}$
BrowseComp-Plus	1	$64.17_{1.28}$	-	-	-	-	-	-	-
	2	$71.12_{1.50}$	$64.10_{2.02}$	$69.68_{1.37}$	$70.02_{1.33}$	$68.64_{1.69}$	$70.22_{0.31}$	$70.44_{0.31}$	$\mathbf{71.11}_{0.31}$
	4	$75.90_{0.94}$	$67.72_{1.73}$	$73.57_{1.13}$	$73.84_{1.11}$	$71.90_{1.11}$	$73.56_{0.31}$	$73.56_{2.45}$	$\mathbf{74.44}_{0.63}$
	8	78.67	68.67	75.33	76.00	74.67	76.67	76.67	$\mathbf{77.33}$
HLE	1	$45.73_{1.75}$	-	-	-	-	-	-	-
	2	$56.61_{1.57}$	$45.14_{1.83}$	$49.52_{1.94}$	$49.75_{2.11}$	$46.77_{2.57}$	$47.53_{2.38}$	$49.68_{1.90}$	$\mathbf{52.90}_{0.91}$
	4	$65.28_{1.28}$	$49.09_{1.70}$	$52.59_{1.45}$	$52.76_{1.77}$	$47.48_{2.26}$	$50.97_{2.11}$	$56.34_{0.80}$	$\mathbf{56.99}_{1.22}$
	8	72.26	53.55	57.42	58.06	46.45	54.19	58.06	$\mathbf{60.00}$
DeepSearchQA	1	$54.42_{1.66}$	-	-	-	-	-	-	-
	2	$65.40_{2.21}$	-	-	$\mathbf{58.02}_{2.26}$	$55.90_{1.97}$	$57.78_{1.57}$	$57.11_{1.57}$	$57.33_{2.18}$
	4	$75.04_{1.86}$	-	-	$61.46_{2.23}$	$56.50_{1.47}$	$59.11_{1.91}$	$61.33_{0.54}$	$\mathbf{63.78}_{1.13}$
	8	82.67	-	-	64.00	56.00	62.00	61.33	$\mathbf{65.33}$
Healthbench-Hard	1	$9.67_{3.84}$	-	-	-	-	-	-	-
	2	$21.09_{2.91}$	-	-	$9.74_{2.38}$	$9.02_{2.67}$	$17.30_{1.28}$	$9.74_{0.91}$	$\mathbf{19.25}_{1.53}$
	4	$30.62_{1.93}$	-	-	$10.58_{2.06}$	$8.04_{2.45}$	$21.25_{1.20}$	$12.37_{1.32}$	$\mathbf{24.27}_{0.52}$
	8	39.02	-	-	8.79	5.34	21.84	16.92	$\mathbf{24.46}$
ResearchRubrics	1	$39.97_{0.71}$	-	-	-	-	-	-	-
	2	$43.86_{0.55}$	-	-	$40.16_{0.55}$	$39.63_{0.85}$	$41.88_{0.57}$	$34.15_{0.55}$	$\mathbf{43.17}_{0.65}$
	4	$47.06_{0.38}$	-	-	$40.05_{0.58}$	$39.19_{0.67}$	$43.26_{0.24}$	$37.12_{0.42}$	$\mathbf{44.96}_{0.53}$
	8	49.74	-	-	39.00	38.44	44.00	40.29	$\mathbf{45.42}$
Average (MiniMax-M2.5)	1	44.02	-	-	-	-	-	-	-
	2	53.16	43.95	47.11	47.84	46.22	49.12	46.82	$\mathbf{50.66}$
	4	60.42	46.24	49.16	50.79	47.62	52.10	51.23	$\mathbf{55.30}$
	8	65.95	47.83	50.58	52.75	48.04	54.90	53.88	$\mathbf{57.31}$

Table 7. Performance comparison across aggregation strategies with MiniMax-M2.5. The table is formatted the same as Table 5.

Task	K	Rollout Cost (c_r)	Tool Call Cost (c_t)	Aggregation Cost (c_a)			Rollout Latency (t_r)	Aggregation Latency (t_a)		
				SolAgg	SummAgg	AggAgent		SolAgg	SummAgg	AggAgent
BrowseComp	1	.0086	.0390	-	-	-	185.10	-	-	-
	2	.0171	.0780	.0025	.0143	.0044	211.82	33.97	77.72	22.67
	4	.0343	.1560	.0021	.0261	.0048	233.74	21.38	107.27	38.51
	8	.0685	.3119	.0019	.0506	.0047	261.41	18.69	139.42	31.65
BrowseComp-Plus	1	.0067	0	-	-	-	457.47	-	-	-
	2	.0134	0	.0026	.0142	.0037	536.31	42.54	84.65	25.30
	4	.0268	0	.0021	.0260	.0038	584.04	21.19	83.42	31.56
	8	.0536	0	.0020	.0501	.0038	620.15	15.31	128.79	29.88
HLE	1	.0079	.0190	-	-	-	91.77	-	-	-
	2	.0158	.0379	.0037	.0118	.0046	125.04	29.41	54.56	33.55
	4	.0316	.0758	.0038	.0202	.0053	178.32	31.07	86.67	34.19
	8	.0632	.1517	.0041	.0368	.0055	250.64	35.24	115.87	40.32
DeepSearchQA	1	.0068	.0311	-	-	-	105.60	-	-	-
	2	.0135	.0623	.0018	.0113	.0043	159.65	14.96	55.49	30.48
	4	.0271	.1245	.0021	.0210	.0049	225.01	18.22	69.63	33.60
	8	.0542	.2490	.0024	.0401	.0052	261.79	21.73	105.53	36.98
Healthbench-Hard	1	.0037	.0114	-	-	-	41.20	-	-	-
	2	.0075	.0228	.0019	.0081	.0028	52.22	22.26	46.47	23.12
	4	.0150	.0456	.0023	.0146	.0035	67.15	22.46	58.39	25.51
	8	.0299	.0912	.0028	.0276	.0039	88.27	26.84	81.48	27.32
ResearchRubrics	1	.0070	.0222	-	-	-	112.06	-	-	-
	2	.0141	.0444	.0028	.0119	.0044	142.95	28.61	63.13	40.03
	4	.0282	.0889	.0034	.0219	.0053	187.43	35.08	84.07	46.80
	8	.0563	.1777	.0045	.0412	.0062	243.40	37.83	114.70	50.91
Average (GLM-4.7-Flash)	1	.0068	.0204	-	-	-	165.53	-	-	-
	2	.0136	.0409	.0025	.0119	.0040	204.67	28.63	63.67	29.19
	4	.0272	.0818	.0026	.0216	.0046	245.95	24.90	81.58	35.03
	8	.0543	.1636	.0029	.0411	.0049	287.61	25.94	114.30	36.18

Table 8. Cost and latency breakdown with GLM-4.7-Flash. All costs are in USD per query, and all latencies are in seconds per query. '-' denotes not applicable at $K=1$. BrowseComp-Plus incurs no tool cost.

Task	K	Rollout Cost (c_r)	Tool Call Cost (c_t)	Aggregation Cost (c_a)			Rollout Latency (t_r)	Aggregation Latency (t_a)		
				SolAgg	SummAgg	AggAgent		SolAgg	SummAgg	AggAgent
BrowseComp	1	.0409	.0315	-	-	-	182.79	-	-	-
	2	.0817	.0629	.0102	.0565	.0213	224.26	21.96	53.60	39.07
	4	.1634	.1258	.0103	.1026	.0309	242.48	21.31	69.14	41.04
	8	.3268	.2517	.0103	.1952	.0209	305.38	20.93	91.82	36.25
BrowseComp-Plus	1	.0265	0	-	-	-	564.68	-	-	-
	2	.0530	0	.0098	.0544	.0186	690.97	25.55	58.80	36.38
	4	.1060	0	.0099	.0977	.0193	743.69	21.32	62.35	32.60
	8	.2120	0	.0097	.1893	.0182	831.50	19.99	99.29	41.32
HLE	1	.0318	.0149	-	-	-	74.53	-	-	-
	2	.0637	.0298	.0128	.0418	.0173	99.80	36.98	45.68	25.04
	4	.1274	.0597	.0131	.0705	.0197	125.14	24.30	60.16	31.51
	8	.2548	.1194	.0127	.1307	.0203	152.97	29.85	74.72	38.28
DeepSearchQA	1	.0277	.0239	-	-	-	89.32	-	-	-
	2	.0553	.0477	.0088	.0437	.0208	110.47	16.71	48.91	39.57
	4	.1106	.0954	.0107	.0776	.0244	129.99	22.32	54.54	38.96
	8	.2212	.1909	.0116	.1494	.0247	173.43	20.50	65.65	40.28
Healthbench-Hard	1	.0080	.0045	-	-	-	22.03	-	-	-
	2	.0161	.0091	.0092	.0215	.0141	26.67	24.29	32.69	26.68
	4	.0321	.0181	.0107	.0376	.0166	29.56	26.96	40.83	28.86
	8	.0642	.0363	.0130	.0680	.0175	35.09	30.70	53.77	32.38
ResearchRubrics	1	.0182	.0093	-	-	-	66.92	-	-	-
	2	.0364	.0186	.0183	.0377	.0260	75.28	47.98	51.80	47.75
	4	.0728	.0371	.0213	.0632	.0276	84.19	57.39	72.33	54.95
	8	.1457	.0743	.0261	.1134	.0301	96.06	47.39	87.53	55.08
Average (Qwen3.5-122B)	1	.0255	.0140	-	-	-	166.71	-	-	-
	2	.0510	.0280	.0115	.0426	.0197	204.58	28.91	48.58	35.75
	4	.1020	.0560	.0127	.0749	.0231	225.84	28.93	59.89	37.99
	8	.2041	.1121	.0139	.1410	.0219	265.74	28.23	78.80	40.60

Table 9. Cost and latency breakdown with Qwen3.5-122B. The table is formatted the same as Table 8.

Task	K	Rollout Cost (c_r)	Tool Call Cost (c_t)	Aggregation Cost (c_a)			Rollout Latency (t_r)	Aggregation Latency (t_a)		
				SolAgg	SummAgg	AggAgent		SolAgg	SummAgg	AggAgent
BrowseComp	1	.0321	.0301	-	-	-	209.34	-	-	-
	2	.0642	.0602	.0055	.0389	.0122	259.73	267.45	300.34	294.52
	4	.1285	.1204	.0049	.0715	.0120	292.90	300.42	347.88	319.73
	8	.2569	.2409	.0049	.1357	.0118	314.26	323.33	480.36	352.57
BrowseComp-Plus	1	.0298	0	-	-	-	392.76	-	-	-
	2	.0596	0	.0052	.0459	.0114	519.48	528.28	567.93	550.86
	4	.1191	0	.0037	.0876	.0111	632.33	639.21	708.68	663.04
	8	.2382	0	.0025	.1651	.0111	716.32	723.99	968.27	744.93
HLE	1	.0358	.0164	-	-	-	165.06	-	-	-
	2	.0716	.0327	.0088	.0385	.0116	194.42	217.01	239.92	227.34
	4	.1433	.0654	.0087	.0689	.0144	228.92	244.59	304.89	259.10
	8	.2865	.1308	.0082	.1294	.0126	264.72	280.52	404.20	310.09
DeepSearchQA	1	.0282	.0268	-	-	-	149.91	-	-	-
	2	.0564	.0536	.0039	.0378	.0141	179.42	189.97	219.72	210.96
	4	.1129	.1072	.0039	.0721	.0147	193.99	207.52	247.52	232.83
	8	.2257	.2144	.0047	.1412	.0148	227.26	236.98	350.82	261.86
Healthbench-Hard	1	.0074	.0052	-	-	-	28.86	-	-	-
	2	.0148	.0105	.0035	.0143	.0057	33.13	49.61	64.43	58.19
	4	.0295	.0209	.0043	.0267	.0070	34.08	52.90	75.92	58.94
	8	.0591	.0419	.0058	.0507	.0084	40.55	65.48	95.72	72.02
ResearchRubrics	1	.0151	.0125	-	-	-	93.25	-	-	-
	2	.0302	.0250	.0086	.0257	.0125	109.61	159.09	161.16	166.29
	4	.0603	.0499	.0109	.0480	.0149	122.48	177.29	192.37	177.12
	8	.1207	.0998	.0151	.0919	.0183	146.17	203.61	270.58	213.30
Average (MiniMax-M2.5)	1	.0237	.0152	-	-	-	173.20	-	-	-
	2	.0474	.0303	.0059	.0335	.0113	215.97	235.24	258.92	251.36
	4	.0949	.0606	.0061	.0625	.0123	250.78	270.32	312.88	285.13
	8	.1898	.1213	.0069	.1190	.0128	284.88	305.65	428.33	325.80

Table 10. Cost and latency breakdown with MiniMax-M2.5. The table is formatted the same as Table 8.

Task	K	Pass	GLM-4.7-Flash			MiniMax-M2.5		
			SolAgg	SummAgg	AggAgent	SolAgg	SummAgg	AggAgent
BrowseComp	1	27.42	-	-	-	-	-	-
	2	37.86	35.78	34.89	37.78	36.22	37.11	**39.11**
	4	49.21	45.33	46.22	45.78	46.22	44.44	**46.44**
	8	58.67	53.33	55.33	**56.00**	51.33	55.33	55.33
BrowseComp-Plus	1	49.08	-	-	-	-	-	-
	2	59.64	54.67	58.00	58.44	58.22	58.67	**59.33**
	4	67.36	63.33	63.33	66.22	64.89	65.33	**68.44**
	8	72.00	70.67	70.67	71.33	70.00	71.33	**72.67**
HLE	1	25.00	-	-	-	-	-	-
	2	34.01	29.68	30.75	**31.40**	27.74	30.54	29.46
	4	42.88	30.97	31.83	32.47	32.26	30.97	**33.76**
	8	50.97	32.90	34.84	37.42	35.48	35.48	**38.06**
DeepSearchQA	1	32.42	-	-	-	-	-	-
	2	43.55	33.78	38.44	40.44	36.22	35.56	**42.89**
	4	54.26	42.44	43.56	42.00	41.11	41.78	**43.78**
	8	64.00	46.00	47.33	49.33	48.00	50.00	**52.67**
Healthbench-Hard	1	8.67	-	-	-	-	-	-
	2	21.34	10.50	-1.21	**24.45**	18.06	10.25	22.81
	4	31.96	13.70	4.76	**25.36**	22.53	16.85	24.22
	8	40.91	15.72	7.35	**27.99**	22.18	18.90	26.74
ResearchRubrics	1	37.47	-	-	-	-	-	-
	2	42.71	33.84	27.69	41.32	40.43	33.90	**43.42**
	4	46.57	37.15	30.83	43.70	43.02	**44.76**	44.69
	8	49.79	36.84	31.72	45.31	43.14	40.56	**46.07**
Average	1	30.01	-	-	-	-	-	-
	2	39.85	33.04	31.43	38.97	36.15	34.34	**39.50**
	4	48.71	38.82	36.76	42.59	41.67	40.69	**43.56**
	8	56.06	42.58	41.21	47.90	45.02	45.27	**48.59**

Table 11. Performance of LLM-based aggregation strategies on GLM-4.7-Flash as the base rollout model, comparing GLM (same model) and MiniMax (stronger model) as the LLM aggregator, across varying K. **Bold** indicates the best-performing method per row (excluding Pass). Results show that using a stronger aggregator leads to better performance. '-' denotes not applicable at $K = 1$.

Figure 8. Performance-efficiency trade-off of aggregation methods across six benchmarks at varying numbers of parallel samples $K = \{2, 4, 8\}$ using GLM-4.7-Flash as both the rollout agent and the aggregator. For each group of three benchmarks, the first row shows performance vs. cost (USD per query) and the second row shows performance vs. latency (seconds per query). AggAgent consistently achieves higher performance at comparable or lower cost and latency than existing aggregation strategies.

Figure 9. Performance-efficiency trade-off of aggregation methods using Qwen3.5-122B as both the rollout agent and the aggregator. The figure is formatted the same as Figure 8.

Figure 10. Performance-efficiency trade-off of aggregation methods using MiniMax-M2.5 as both the rollout agent and the aggregator. The figure is formatted the same as Figure 8.

Figure 11. Confidence calibration across all six benchmarks. Each row is a benchmark and each column is a model. For binary-correctness (agentic search) benchmarks, box plots show self-reported confidence by outcome (**W**rong vs. **C**orrect). For continuous-score (deep research) benchmarks, scatter plots show confidence vs. rubric score with Pearson r. Models are well-calibrated on BrowseComp-Plus and BrowseComp, moderately calibrated on HLE and DeepSearchQA, but poorly calibrated on Healthbench-Hard and ResearchRubrics

---

Rollout agent system prompt for agentic search tasks

You are a deep research assistant. Your core function is to conduct thorough, multi-source investigations into any topic. You must handle both broad, open-domain inquiries and queries within specialized academic fields. For every request, synthesize information from credible, diverse sources to deliver a comprehensive, accurate, and objective response. After you have gathered sufficient information, provide the definitive response and complete the task.

Figure 12. Rollout agent system prompt for agentic search tasks, from Tongyi DeepResearch Team et al. (2025).

Additional rollout agent system prompt for deep research tasks

For the given question, please write a comprehensive, evidence-backed answer to scientific questions. You should ground every nontrivial claim in retrieved snippets. Cite using <cite url="...">...</cite> drawn only from returned snippets. Please prefer authoritative sources (peer-reviewed papers, reputable benchmarks/docs) and prioritize recent work for fast-moving areas. You should acknowledge uncertainty and conflicts; if evidence is thin or sources disagree, state it and explain what additional evidence would resolve it. It's important to structure with clear markdown headers and a coherent flow. In each section, write 2-5 sentence paragraphs with clear topic sentences and transitions; use lists sparingly only when they improve clarity. Ideally, you should synthesize rather than enumerate content: it's helpful to group findings across papers, explain relationships, and build a coherent narrative that answers the question, supported by citations. Most importantly, DO NOT invent snippets or citations and never fabricate content. At the end of your response, on a new line, include your confidence score in the following format: Confidence: {{your confidence score between 0% and 100% for your answer}}

Figure 13. Additional rollout agent system prompt for deep research tasks, from Shao et al. (2025).

Rollout agent user message for agentic search tasks

Your response should be in the following format:
Explanation: {{your explanation for your final answer}}
Exact Answer: {{your succinct, final answer}}
Confidence: {{your confidence score between 0% and 100% for your answer}}

Figure 14. Rollout agent user message for agentic search tasks, from Wei et al. (2025).

Additional instruction for evaluating ResearchRubrics

Handling Negative-Weight Criteria
Some criteria describe **undesirable behaviors** and carry a **negative weight**. The Weight field in the rubric indicates this. For these criteria:
- **Satisfied (Score: 1.0)**: The undesirable behavior IS present in the document. This will reduce the overall score.
- **Not Satisfied (Score: 0.0)**: The undesirable behavior is ABSENT from the document. This is the desired outcome and does not penalize the score.
Your verdict must reflect whether the described behavior is literally present or absent in the document — not whether the document is generally good or bad.

Figure 15. Additional instruction for evaluating ResearchRubrics.

AggAgent system prompt for agentic search tasks

You are an aggregation agent. You are provided with a task and a set of candidate trajectories from independent agents that attempted to solve it. Your goal is to synthesize the most accurate, complete solution by drawing on the best reasoning and evidence across trajectories.
You do NOT have access to the ground truth solution.
—
RESPONSIBILITIES
1. Evaluate tool results and reasoning quality across all candidate trajectories.

---

2. Identify the most reliable final solution based on verifiable tool observations, logical consistency, and correct tool application.
3. If no single trajectory is fully reliable, synthesize a corrected solution using only verified components from across trajectories.
4. Deliver your synthesized solution in the required format and provide justification.

—

REQUIRED PROCEDURE
You must follow these steps before calling 'finish'.
1. **Survey the landscape** — Read the TRAJECTORY METADATA in the user message. Identify which trajectories are worth inspecting based on step counts and patterns.
2. **Retrieve full solutions** — Call 'get_solution' (no arguments) to get the final content from every trajectory's last step, or pass a trajectory_id to retrieve one specific trajectory.
3. **Verify with tool observations** — Do not rely solely on final solutions or a trajectory's own reasoning. For key claims or divergences, go back and inspect what the tools actually returned: - Use **search_trajectory**(trajectory_id, query) to locate steps where a specific term or claim appears. Use role='tool' to restrict to actual tool responses when verifying whether a fact was directly observed — this avoids misleading matches on agent reasoning. - Use **get_segment**(trajectory_id, start_step, end_step) to read a contiguous range of steps (max 5). After finding a relevant step via search, read it in full along with surrounding steps to see the raw tool output and surrounding context.
4. **Cross-check** — Confirm: (a) tool observations in the log match what the agent claims, (b) reasoning is not circular, (c) arithmetic and logic are correct.

—

OPERATIONAL GUIDELINES
- **Tool results are ground truth; agent reasoning is not.** Within each trajectory, what a tool *returned* is an objective observation. What the agent *concluded* from it is an interpretation that may be wrong. When in conflict, trust the tool output over the agent's written reasoning about it.
- **Count evidence, not trajectories.** A single trajectory with a clear, unambiguous tool observation supporting answer X is stronger evidence than many trajectories that *reasoned* their way to Y without grounding in tool outputs. Majority agreement alone is not sufficient — check what the tools actually showed.
- **Identify Divergence:** Focus on steps where agents disagree. Determine which agent's *observation from the environment* was correct, not which agent sounded more confident.
- **Evidence Grounding:** Ensure tool observations directly support conclusions. If the log shows an error or empty result, the agent cannot validly claim success from that step.
- **Quality over Confidence:** Prefer trajectories with validated, step-by-step reasoning over those that only state a confident conclusion.

—

COMMON PITFALLS
- **Hallucinated Observations:** The agent claims a tool returned X, but the log shows Y (or nothing).
- **Silent Failures:** The agent receives an error but continues as if it succeeded.
- **Circular Logic:** The agent assumes the answer before deriving it from data.
- **Arithmetic/Logical Errors:** The data is correct, but the calculation or inference is flawed.
- **Majority Bias:** Do not treat numerical agreement among trajectories as strong evidence. Many trajectories reaching the same conclusion via similar reasoning is weaker than one trajectory with a concrete, verifiable tool result.

—

SOLUTION FORMAT (finish tool)
The 'solution' argument must be a single string with exactly two XML sections: <explanation>...</explanation><answer>...</answer>.
- **CORRECT:** Self-contained. A reader who never saw trajectories understands how the answer was derived. No mentions of "trajectory 1", "get_solution", or "agent". Example: <explanation>We need the 2020 population. The census table shows state X with 1.2M and state Y with 0.8M; the question asks for the sum. 1.2 + 0.8 = 2.0 million.</explanation><answer>2.0 million</answer>
- **WRONG:** "Trajectory 2 had the right answer so I chose it." or "According to get_solution, the answer is 42." Do NOT reference trajectory IDs or tools in the solution.

—

TERMINATION
Call 'finish' only after verifying key reasoning against actual tool outputs. Do not finish after only reading metadata or only get_solution; verify at least one critical claim with get_segment or search_trajectory when trajectories disagree.

Figure 16. AggAgent system prompt for agentic search tasks.

AggAgent system prompt for deep research tasks

You are an aggregation agent. You are provided with a task and a set of candidate trajectories from independent agents that attempted to solve it. Your goal is to synthesize the most accurate, complete solution by drawing on the best reasoning and evidence across trajectories.
You do NOT have access to the ground truth.
—
RESPONSIBILITIES
1. Evaluate tool results and reasoning quality across all candidate trajectories.
2. Identify the most reliable final solution based on verifiable tool observations, logical consistency, and correct tool application.
3. If no single trajectory is fully reliable, synthesize a corrected solution using only verified components from across trajectories.
4. Deliver your synthesized solution in the required format and provide justification.
—
REQUIRED PROCEDURE
You must follow these steps before calling 'finish'.
1. **Survey the landscape** — Read the TRAJECTORY METADATA in the user message. Identify which trajectories are worth inspecting based on step counts and patterns.
2. **Retrieve full solutions** — Call 'get_solution' (no arguments) to get the final content from every trajectory's last step, or pass a trajectory_id to retrieve one specific trajectory.
3. **Verify with tool observations** — Do not rely solely on final solutions or a trajectory's own reasoning. For key claims or divergences, go back and inspect what the tools actually returned: - Use **search_trajectory**(trajectory_id, query) to locate steps where a specific term or claim appears. Use role='tool' to restrict to tool responses when verifying whether a fact was directly observed. - Use **get_segment**(trajectory_id, start_step, end_step) to read a contiguous range of steps (max 5). After finding a relevant step via search, read it in full along with surrounding steps to see the raw tool output and surrounding context.
4. **Cross-check** — Confirm: (a) tool observations in the log match what the agent claims, (b) reasoning is not circular, (c) arithmetic and logic are correct.
5. **Synthesize** — Write a unified response that: - Covers every important aspect addressed by any candidate - Takes the highest-quality treatment of each aspect (not just the most common) - Resolves contradictions by preferring more specific, better-supported, or more precise content - Reads as a single coherent response, not a patchwork
—
QUALITY CRITERIA
- **Completeness:** The synthesized response must be at least as comprehensive as the best individual candidate, and more comprehensive where candidates complement each other.
- **Accuracy:** Prefer specific, precise content over vague generalizations. When candidates conflict, do not average — choose the more defensible position.
- **Coherence:** The final response must flow naturally. Integrate content rather than concatenating sections.
- **Self-contained:** Do not mention trajectories, agents, candidates, or aggregation anywhere in the response.
- **Citations:** Ground every nontrivial claim in retrieved snippets. Cite using <cite url="...">...</cite> drawn only from returned snippets; never fabricate URLs or content.
—
COMMON PITFALLS
- **Cherry-picking the best-sounding candidate:** Length or fluency is not quality. A shorter candidate may cover a critical aspect better.
- **Ignoring minority candidates:** A single candidate covering an important aspect well outweighs many candidates that omit it.
- **Concatenation instead of synthesis:** Stitching sections together without integrating them produces an incoherent response. Rewrite to unify.
- **Contradiction averaging:** If candidates disagree, do not hedge — reason about which is more accurate and commit to it.
- **Omitting details:** If a candidate covers a subtopic with more depth, preserve that depth in the synthesis.
—
TERMINATION
Call 'finish' with 'solution_report' (your complete synthesized response) and 'reason' (a concise account of how you combined the candidates and resolved any conflicts) after you have read and compared all candidates.

Figure 17. AggAgent system prompt for deep research tasks.

AggAgent tool descriptions

```
{
  "type": "function",
  "function": {
```

```
    "name": "get_solution",
    "description": "Retrieves the final content from trajectories' last step.
        Returns a list of {trajectory_id, content} entries.",
    "parameters": {
      "type": "object",
      "properties": {
        "trajectory_id": {
          "type": "integer",
          "description": "Trajectory index. Omit to retrieve all trajectories."
        }
      },
      "required": [],
      "additionalProperties": false
    }
  },
  "strict": true
},
{
  "type": "function",
  "function": {
    "name": "search_trajectory",
    "description": "Searches for keywords or phrases within a single trajectory.
        Returns top matching steps ranked by relevance score.",
    "parameters": {
      "type": "object",
      "properties": {
        "trajectory_id": {"type": "integer", "description": "Trajectory index to
            search within."},
        "query": {"type": "string", "description": "Search term or phrase."},
        "role": {"type": "string", "enum": ["tool", "assistant"], "description": "
            Optional. Filter to 'tool' steps (actual environment observations) or '
            assistant' steps only. Omit to search all steps."},
        "k": {"type": "integer", "description": "Max matches to return (default 5,
            max 10).", "default": 5}
      },
      "required": ["trajectory_id", "query"],
      "additionalProperties": false
    }
  },
  "strict": true
},
{
  "type": "function",
  "function": {
    "name": "get_segment",
    "description": "Reads the full content of a contiguous range of steps from a
        trajectory (max 5). Use after search_trajectory to inspect a step in full
        with its surrounding context.",
    "parameters": {
      "type": "object",
      "properties": {
        "trajectory_id": {"type": "integer", "description": "Trajectory index."},
        "start_step": {"type": "integer", "description": "Start step (inclusive)."},
        "end_step": {"type": "integer", "description": "End step (inclusive);
            end_step - start_step <= 4."}
      },
      "required": ["trajectory_id", "start_step", "end_step"],
      "additionalProperties": false
    }
  },
  "strict": true
},
{
```

```
  "type": "function",
  "function": {
    "name": "finish",
    "description": "Submits the final synthesized solution.",
    "parameters": {
      "type": "object",
      "properties": {
        "solution": {"type": "string", "description": "A comprehensive, standalone
            solution as a single string with two XML sections: <explanation>detailed
             reasoning leading to the answer</explanation><answer>the exact answer</
            answer>. The explanation must be self-contained and make sense without
            any reference to trajectories or aggregation."},
        "reason": {"type": "string", "description": "Meta-reasoning explaining your
            decision: how you evaluated the trajectories, what evidence you relied
            on, and how you resolved any conflicts or inconsistencies."}
      },
      "required": ["solution", "reason"]
    }
  },
  "strict": true
}
```

Figure 18. AggAgent tool descriptions.

Variants of AggAgent finish tool

```
Deep Research Tasks:
"solution": {"type": "string", "description": "The synthesized long-form response.
    Write it as a complete, standalone report -- do not reference trajectories,
    agents, or aggregation. Cite using <cite url=\"...\">...</cite> if necessary."}

Qwen3.5-122B-A10B on Agentic Search Tasks:
"solution": {"type": "string", "description": "A comprehensive, standalone solution
    as a single string in the following format:\nExplanation: {detailed reasoning
    leading to the answer}\nExact Answer: {the exact answer}\nThe explanation must
    be self-contained and make sense without any reference to trajectories or
    aggregation."}
```

Figure 19. Variants of AggAgent finish tool.