DEEP ENSEMBLES FOR GRAPHS WITH HIGHER-ORDER DEPENDENCIES

ABSTRACT

Graph neural networks (GNNs) continue to achieve state-of-the-art performance on many graph learning tasks, but rely on the assumption that a given graph is a sufficient approximation of the true neighborhood structure. When a system contains higher-order sequential dependencies, we show that the tendency of traditional graph representations to underfit each node's neighborhood causes existing GNNs to generalize poorly. To address this, we propose a novel **Deep Graph Ensemble** (DGE), which captures neighborhood variance by training an ensemble of GNNs on different neighborhood subspaces of the same node within a higher-order network structure. We show that DGE consistently outperforms existing GNNs on semisupervised and supervised tasks on six real-world data sets with known higher-order dependencies, even under a similar parameter budget. We demonstrate that learning diverse and accurate base classifiers is central to DGE's success, and discuss the implications of these findings for future work on ensembles of GNNs.

1 INTRODUCTION

Graph neural networks (GNNs) solve learning tasks by propagating information through each node's neighborhood in a graph (Zhou et al., 2020; Wu et al., 2020). Most present work on GNNs assumes that a given graph is a sufficient approximation of the underlying neighborhood structure. But a growing body of work has challenged this assumption by showing that traditional graphs often cannot capture the higher-order structure and dynamics that govern many real-world systems (Lambiotte et al., 2019; Battiston et al., 2020; Porter, 2020; Torres et al., 2021; Battiston et al., 2021). In the present work, we couple GNNs with a specific family of graphs, **higher-order networks** (HONs), which encode sequential **higher-order dependencies** (i.e., conditional probabilities that cannot be explained by a first-order Markov model) in a graph structure. A traditional graph, which we call a **first-order network** (FON), represents a system by decomposing it into a set of pairwise edges, so the only way to infer polyadic interactions is via transitive paths over adjacent nodes. When higher-order dependencies are present, these Markovian paths underfit the true neighborhood (Scholtes, 2017) and can thus produce many false positive interactions between nodes (Lambiotte et al., 2019). To address this limitation, Xu et al. (2016) proposed a HON that creates conditional nodes to more accurately encode the observed higher-order interactions. By preserving this additional information in the graph structure, HONs have produced new insights in studies of user behavior (Chierichetti et al., 2012), citation networks (Rosvall et al., 2014), human mobility and navigation patterns (Scholtes et al., 2014; Peixoto & Rosvall, 2017), the spread of invasive species Saebi et al. (2020b), anomaly detection (Saebi et al., 2020d), disease progression (Krieg et al., 2020b), and more (Koher et al., 2016; Peixoto & Rosvall, 2017; Scholtes, 2017; Lambiotte et al., 2019; Saebi et al., 2020a). However, to our knowledge, they have not been studied with GNNs.

As Figure 1 illustrates, the tendency of FONs to underfit has consequences for GNNs, which typically compute representations by recursively pooling features from each node's neighbors. In order to maximize GNN performance, we must ensure that local neighborhoods capture the true distribution of interactions in the system. To enable GNNs to utilize the additional information encoded in HONs, we propose a novel **Deep Graph Ensemble** (DGE), which uses independent GNNs to exploit variance in higher-order node neighborhoods and learn effective representations in graphs with higher-order dependencies. The **key contributions** of our work include:

Figure 1: A toy example of challenges faced by GNNs in modeling systems with higher-order dependencies. A FON ($\mathcal{G}_1$) underfits the higher-order dependencies in the observed paths. Consequently, a GNN will learn similar representations for A and B, since they share the same 2-hop neighborhood in $\mathcal{G}_1$. A HON ($\mathcal{G}_k$, with $k = 2$ in this example) uses conditional nodes to encode higher-order dependencies. For example, node C|A, read as C *given* A, represents the observed dependency that C only interacts with D when it also interacts with A (note that in real-world systems, $\mathcal{G}_k$ rarely breaks the graph into multiple components). However, computing a representation for C then requires a GNN to aggregate multiple local neighborhoods. Colors depict node features.

1. We analyze the challenges that fundamentally limit the ability of existing GNNs to learn effective representations in systems with higher-order dependencies.
2. We introduce the notion of neighborhood subspaces by showing that neighborhoods in a HON are analogous to feature subspaces of first-order neighborhoods. Borrowing from ensemble methods, we then propose DGE to exploit the variance in these subspaces.
3. We experimentally evaluate DGE against eight state-of-the-art baselines on six real-world data sets with known higher-order dependencies, and show that, even with similar parameter budgets, DGE consistently outperforms baselines on semisupervised (node classification) and supervised (link prediction) tasks.[1]
4. We demonstrate that DGE's ability to train accurate and diverse classifiers is central to strong performance, and show that ensembling multiple GNNs with separate parameters is a consistent way to maximize the trade-off between accuracy and diversity.

2 BACKGROUND AND PRELIMINARIES

2.1 HIGHER-ORDER NETWORKS

Let $\mathcal{S} = \{S_1, S_2, ..., S_n\}$ be a set of **observed paths** (e.g., flight itineraries, disease trajectories, or user clickstreams), where each $S_i = \langle s_1, s_2, ..., s_m \rangle$ is a sequence of **entities** (e.g., airports, diagnosis codes, or web pages). Let $\mathcal{A} = \bigcup \mathcal{S}$ denote the set of entities across all sequences. By using a graph to summarize $\mathcal{S}$, we can model the global function of each entity in the system and solve a number of useful learning problems. For example, we can predict disease function via node classification or interactions between airports using link prediction.[2] However, there is a large space of possible graphs that can represent $\mathcal{S}$. We consider two: a FON and the HON introduced by Xu et al. (2016). In a FON $\mathcal{G}_1 = (\mathcal{V}_1, \mathcal{E}_1)$, the node set $\mathcal{V}_1 = \mathcal{A}$ (or, more generally, the mapping $f : \mathcal{V}_1 \to \mathcal{A}$ is bijective), and the edge set $\mathcal{E}_1$ is the set of node pairs $(u, v) \in \mathcal{V}_1 \times \mathcal{V}_1$ that are adjacent elements in at least one S_i.

In a HON $\mathcal{G}_k = (\mathcal{V}_k, \mathcal{E}_k)$ with order $k > 1$, each node is a sequence of entities $u' = \langle a'_1, ..., a'_{m-1}, a'_m \rangle$, where each $a'_i \in \mathcal{V}_1$ and $m \leq k$. We define a'_m as the **base node**, and in practice use the notation $u' = a'_m | a'_1, ..., a'_{m-1}$ to emphasize that each $u' \in \mathcal{V}_k$ represents a base node whose current state is conditioned on a set of predecessors. Each node can have a different

---

[1]Code and 3 data sets are available as supplementary material, and will be published on manuscript acceptance.

[2]This is distinct from sequence models like transformers, which typically predict an entity's local function within a single sequence.

number of predecessors, and a conditional node with $m > 1$ is only created if the conditional distribution of paths it encodes sufficiently reduces the entropy of the graph (Saebi et al., 2020d). This means that $\mathcal{V}_k \subseteq \mathcal{A}^k$; or, more generally, the mapping $f : \mathcal{V}_k \to \mathcal{A}^k$ is injective but not necessarily bijective. We define $\Omega_u^k = \{u' \in \mathcal{V}_k, a'_m = u\}$ as the **higher-order family** of u (including u itself), and call each $u' \in \Omega_u^k$ a **relative** of u (in Figure 1, for example, C|A and C|B are the relatives of C). Like $\mathcal{E}_1$, the edge set $\mathcal{E}_k$ is the set of node pairs $(u, v) \in \mathcal{V}_k \times \mathcal{V}_k$ that are adjacent in at least one S_i. In both HONs and FONs, edges are directed such that $(u, v) \neq (v, u)$ and weighted via $w_k : \mathcal{E}_k \to \mathbb{R}_{\geq 0}$, where 0 indicates a missing edge. By creating conditional nodes, a HON can express higher-order interactions while remaining a graph, since each edge is still a 2-tuple. For example, consider that passengers who fly from Atlanta to Chicago are much more likely to fly back to Atlanta than to New York, and vice versa. A HON can encode this dependency—which cannot be represented in a FON—by creating the conditional nodes "Chicago|Atlanta" and "Chicago|New York", which changes the topology and flow of information within local neighborhoods (Rosvall et al., 2014). Choosing which conditional nodes and edges to create and is a non-trivial problem; readers interested in more details can refer to Krieg et al. (2020a), who proposed the procedure that we used in this study.

The term "higher-order" is also used in the literature to refer to the analysis of polyadic structures within graphs (Benson et al., 2016), as well GNNs that are able to distinguish these structures (Morris et al., 2019; Schnake et al., 2021). These studies rely on the same assumptions as other GNNs, i.e. that a graph is a sufficient approximation of the neighborhood structure. Despite similarities in terminology, HONs are primarily concerned with the question of initial representation (i.e., how should the graph be constructed?) rather than downstream analysis of an existing graph, and thus address a fundamentally different problem (Lambiotte et al., 2019). HONs are also distinct from other formalisms like hypergraphs and simplicial complexes in that they encode sequential paths (via edge direction) and probability distributions (via edge weights), and therefore represent different kinds of systems (Battiston et al., 2020; Porter, 2020; Torres et al., 2021; Battiston et al., 2021).

2.2 GRAPH NEURAL NETWORKS

A generic GNN computes a hidden vector representation for a node u at timestamp t according to:

$$\mathbf{h}_u^{(t)} = \text{COMBINE}\Big(\mathbf{h}_u^{(t-1)}, \text{AGGREGATE}\big(\{\mathbf{h}_v^{(t-1)}, v \in \mathcal{N}(u)\}\big)\Big), \tag{1}$$

where $\mathcal{N}(u)$ is the neighborhood of u in a graph $\mathcal{G}$. What typically distinguishes GNNs is how they define COMBINE and AGGREGATE, and how they represent $\mathcal{N}(u)$ (Xu et al., 2019; Zhou et al., 2020; Wu et al., 2020). By recursively pooling features via Eq. 1, GNNs implicitly construct higher-order neighborhoods across transitive paths. This assumption of transitivity is essential, since it allows nonadjacent nodes to share information if they are close in the graph (Li et al., 2018; Chen et al., 2020). However, as we will demonstrate, when higher-order dependencies are present, this assumption leads GNNs that are trained on FONs to generalize poorly.

In this work, we do not reformulate Eq. 1 and are agnostic toward its particular implementation. We instead abstract GNN as a function that takes a single node u as input and returns either the final hidden representation $\mathbf{h}_u^{(t)}$, or, in a supervised setting, a vector of predicted label probabilities $\hat{\mathbf{y}}_u$:

$$\text{GNN}(u) = \mathbf{h}_u^{(t)} \quad \text{or} \quad \text{GNN}(u) = \hat{\mathbf{y}}_u. \tag{2}$$

We always assume that $\mathcal{G}$ contains initial node features $\{\mathbf{x}_u, \forall u \in \mathcal{V}\}$ and that $\text{GNN}(\cdot)$ is parameterized by weights θ, but for simplicity we omit them from our notation.

2.3 GNN ENSEMBLES

Ho (1998) and Breiman (2001) showed that training an ensemble of shallow learners on random subspaces could exploit variance in the feature space and improve performance, and Dietterich (2000) demonstrated that these ensembles are most potent when the predictions of their base classifiers are accurate and diverse. Deep ensembles have typically been used with random weight initializations to improve uncertainty estimation and robustness (Lakshminarayanan et al., 2017; Fort et al., 2019; Wasay & Idreos, 2020), but very few works have studied ensembles of GNNs. Some recent exceptions have suggested that ensembling subgraphs could benefit GNNs (Zeng et al., 2021; Tang

Figure 2: Overview of DGE. Given a HON $\mathcal{G}_k$, DGE computes outputs for each base node u by a) resampling relatives from u's higher-order family Ω_u^k via a sampling distribution P_u^k, b) computing outputs for each sampled relative using independent GNN modules, and c) pooling the outputs.

et al., 2021; Lin et al., 2022). Some other work on GNNs is conceptually related to ensembles; for example, multi-head attention (Veličković et al., 2018; Brody et al., 2022; Hou et al., 2021) can be understood as a type of ensemble.

3 DEEP GRAPH ENSEMBLES FOR HIGHER-ORDER NETWORKS

3.1 WHY ENSEMBLES?

There are a number of design challenges (**CHs**) we must address in order to realize the joint potential of GNNs and HONs. In a HON, entities are represented by a non-fixed number of conditional nodes (**CH1**); for example, in Figure 1, C is represented by two nodes but A, B, D, and E are each only represented by one node. Conditional nodes typically have different neighborhoods (**CH2**); for example, in Figure 1, C|A and C|B have different neighbors. Further, they may vary in importance (i.e., have lower degree) in the graph (**CH3**) (Xu et al., 2016; Saebi et al., 2020d). To address these challenges, one intuitive idea is to reformulate Eq. 2 so that it computes a representation for u by sampling neighbors from any of u's relatives. However, this fails to address CH2 because a GNN would aggregate the samples without considering differences between relatives. Another idea is to compute representations for each relative separately, then pool them via a permutation-invariant function like an elementwise MEAN. But this does not address CH3, since all relatives would contribute equally to the final representation. Moreover, if we assume that all relatives in a higher-order family share the same (or similar) features, this solution will overrepresent features associated with larger higher-order families. To comprehensively address these challenges, we first consider the relationship of u's neighborhood to the neighborhoods of its relatives.

Theorem 1. *Let $\mathcal{G}_1$ and $\mathcal{G}_k$ be a FON and HON, respectively, both constructed from the same input $\mathcal{S}$. Let $\mathcal{N}_1(u)$ and $\mathcal{N}_k(u)$ denote the neighborhoods of any node u in $\mathcal{G}_1$ and $\mathcal{G}_k$, respectively. Let $\mathrm{AGGREGATE}(\cdot)$ represent any symmetric neighborhood aggregation function. If $u \in \mathcal{V}_1$ and $u' \in \Omega_u^k$, then $\mathrm{AGGREGATE}(\mathcal{N}_k(u'))$ is a biased estimator of $\mathrm{AGGREGATE}(\mathcal{N}_1(u))$.*

We prove Theorem 1 in Appendix A. Intuitively, HONs are constructed such that $\mathcal{N}_k(u') \subseteq \mathcal{N}_1(u)$, and u' only exists in $\mathcal{G}_k$ if the expectation of a random walker differs substantially (measured via KL-divergence) from u in $\mathcal{G}_1$ (Saebi et al., 2020d; Krieg et al., 2020a). Consequently, these differences in neighborhood structure will shift the expectation of the features gathered by $\mathrm{AGGREGATE}(\mathcal{N}_k(u'))$. A typical strategy for training a single GNN would involve attempting to eliminate this variance via some sampling method on the graph. But we could also take an ensemble approach, and instead regularize a model via multiple GNNs that err in different ways. Toward this end, and inspired by the success of feature subspace methods (Ho, 1998; Breiman, 2001), we call $\mathcal{N}_k(u')$ a **neighborhood subspace** of $\mathcal{N}_1(u)$.

To address the CHs outlined above, we propose to train an ensemble of GNNs $\{\mathrm{GNN}_1, \mathrm{GNN}_2, ..., \mathrm{GNN}_\ell\}$. Given a set of training nodes $D \subseteq \mathcal{V}_1$, we generate bootstraps $\{D^{(1)}, D^{(2)}, ..., D^{(\ell)}\}$ subject to the constraint that $|D^{(i)} \bigcap \Omega_u^k| = 1$ for all $u \in D$ and $i \leq \ell$

(i.e., each bootstrap contains exactly one relative of each training node). This constraint allows us to avoid the feature overrepresentation problem, address CH1 by sampling with replacement, and address CH2 by training each GNN_i on different neighborhood subspaces as represented in $D^{(i)}$. To solve CH3, we weight the sampling probability for each relative u' according to the normalized out-degree of its higher-order family:

$$P_u^k(u') = \frac{\text{OUTDEG}_k(u')}{\sum_{v' \in \Omega_u^k} \text{OUTDEG}_k(v')}, \tag{3}$$

where $u \in D$ and $\text{OUTDEG}_k(u')$ is the weighted out-degree of u' in $\mathcal{G}_k$. Because weighted out-degree in $\mathcal{G}_k$ is the frequency with which u' appears in $\mathcal{S}$ (Krieg et al., 2020a), it is a natural measure of the importance of u' with respect to the rest of the higher-order family Ω_u^k.

When $D \subseteq \mathcal{E}_1$ consists of node pairs for an edge task, we modify Eq. 3 slightly. For each edge $(u, v) \in D$, we resample a single pair of relatives (u', v') with probability according to the normalized weights of all edges between relatives of u and v:

$$P_{u,v}^k(u', v') = \frac{w_k(u', v')}{\sum_{(u'', v'') \in \Omega_u^k \times \Omega_v^k} \left(w_k(u'', v'') \right)}. \tag{4}$$

3.2 TRAINING AND INFERENCE

Let $D_u^{(i)}$ denote the relative of u that was sampled for the i^{th} bootstrap. We specifically consider a supervised or semisupervised setting, in which our goal is to predict class probabilities $\hat{\mathbf{y}}_u$ for each $u \in D$ such that some loss is minimized w.r.t. ground truth $\mathbf{y}_u$. We propose three methods for computing $\hat{\mathbf{y}}_u$:

$$\hat{\mathbf{y}}_u = \sigma\Big(\text{CONCAT}\big(\{ \text{GNN}_i\,(D_u^{(i)}), \forall i \leq \ell \} \big)^\top \cdot \mathbf{W} \Big) \quad \text{and} \quad \text{GNN}_i(u') = \mathbf{h}_{u'}^{(i,t)}, \tag{5a}$$

or

$$\hat{\mathbf{y}}_u = \sigma\Big(\text{MEAN}\big(\{ \text{GNN}_i(D_u^{(i)}), \forall i \leq \ell \} \big)^\top \cdot \mathbf{W} \Big) \quad \text{and} \quad \text{GNN}_i(u') = \mathbf{h}_{u'}^{(i,t)}, \tag{5b}$$

or

$$\hat{\mathbf{y}}_u = \text{MEAN}\Big(\{ \text{GNN}_i(D_u^{(i)}), \forall i \leq \ell \} \Big) \quad \text{and} \quad \text{GNN}_i(u') = \hat{\mathbf{y}}_{u'}^{(i)}, \tag{5c}$$

where σ is a non-linear activation, CONCAT is vector concatenation, MEAN is elementwise mean, $\mathbf{x}^\top$ is the transpose of $\mathbf{x}$, $\mathbf{h}_{u'}^{(i,t)} \in \mathbb{R}^d$ represents the hidden state of node u' in the t^{th} (final) layer of GNN_i, and d is the number of hidden units (we assume d is fixed for all GNN_i). Using c to denote the number of classes, for Eq. 5a we have $\mathbf{W} \in \mathbb{R}^{d\ell \times c}$, and for Eq. 5b we have $\mathbf{W} \in \mathbb{R}^{d \times c}$. We refer to Eq. 5a as **DGE-concat**, Eq. 5b as **DGE-pool**, and Eq. 5c as **DGE-bag**.

In DGE-concat and DGE-pool each GNN outputs hidden representations, which are concatenated or pooled, respectively, before computing the logits. This means that they can be trained in end-to-end fashion as a single neural network with parallel but independent GNN modules. During a forward pass, each GNN_i only computes representations for the nodes in $D^{(i)}$. In DGE-bag, on the other hand, each GNN outputs class probabilities, which means that each GNN is trained independently and their predictions are simply averaged to compute the final probabilities. We also designed an attention-based pooling method, but found that it did not generalize well (Appendix D).

One important question is whether all GNN_i should share parameters. In other words, is an ensemble necessary, or is it sufficient to use single, more complex model (Abe et al., 2022)? We evaluated this question experimentally, and use **DGE-concat***, **DGE-pool***, and **DGE-bag*** to denote shared-parameter variants of Eqs. 5a, 5b, and 5c, respectively. For DGE-concat* and DGE-pool*, we adjusted our training procedure so that, during backpropagation, each parameter was updated once according to its contribution to the summed loss across all $D^{(i)}$. For DGE-bag*, this meant that each GNN_i was essentially pretrained on $D^{(i-1)}$. Since each GNN_i shares parameters, none of these variants are true ensembles. Instead, they are single models that synthesize representations for conditional nodes (i.e., address CH1, CH2, and CH3) via a READOUT function (Wu et al., 2020) on each higher-order family. We also considered one final variant, **DGE-batch***, which does not use a

Table 1: Summary of graphs used in node classification and link prediction experiments.

Name	$|S|$	$|\mathcal{V}_1|$	$|\mathcal{E}_1|$	$|\mathcal{V}_2|$	$|\mathcal{E}_2|$	# classes	$\mathcal{H}(\mathcal{G}_1)$	$\mathcal{H}(\mathcal{G}_2)$
Air	17.1m	416	13,735	7,461	236,806	10	0.351	0.288
T2D	0.8m	908	314,352	5,462	367,530	16	0.099	0.099
Wiki	76.2k	4,179	70,662	5,584	84,806	10	0.366	0.375
Mag	3.8m	4,079	1,873,279	9,568	1,957,602	4	0.323	0.336
Mag+	8.1m	17,428	5,098,787	192,204	7,980,026	6	0.292	0.310
Ship	54.9k	5,586	369,952	8,586	422,426	38	0.477	0.489

fixed set of bootstraps for training. Instead, it uses Eq. 3 to sample a new set of relatives for each batch. Then, during inference, we use the same procedure as DGE-bag: resample ℓ relatives for each node and compute their outputs via Eq. 5c. We considered DGE-batch* an important variant to evaluate because it drops any resemblance to an ensemble, instead addressing CH1, CH2, and CH3 entirely via batch sampling.

Figure 2 summarizes the components of DGE: resampling ℓ relatives for each entity via Eq. 3, computing a node representation for each sampled relative via Eq. 2, and pooling the computed representations via Eq. 5a, 5b, or 5c. In general, DGE's computational cost is linear with the cost of the base GNN and the ensemble size ℓ, since we are essentially constructing ℓ copies of that GNN (or, in the case of shared parameters, repeating ℓ forward passes per example). For a given node u, the additional cost of sampling and pooling ℓ relatives is $O(\ell\,|\Omega_u^k|)$ and $O(\ell)$, respectively, which are trivial compared to the costs of Eq. 2 (Wu et al., 2020). Additionally, the one-time cost of constructing $\mathcal{G}_k$ increases linearly with k (Krieg et al., 2020a). Since we used $\mathcal{G}_2$ in our experiments, there was marginal overhead for graph construction as compared to $\mathcal{G}_1$.

4 EXPERIMENTAL RESULTS AND DISCUSSION

4.1 EXPERIMENTAL SETUP

Data We used GROWHON (Krieg et al., 2020a) to construct FONs ($\mathcal{G}_1$) and HONs with $k = 2$ ($\mathcal{G}_2$) for six real-world data sets with known higher-order dependencies: flight itineraries for airline passengers in the United States (**Air**) (Rosvall et al., 2014), disease trajectories for type 2 diabetes patients in Indiana (**T2D**) (Krieg et al., 2020b), clickstreams of users playing the Wikispeedia game (**Wiki**) (West et al., 2009), readership trajectories for a large online magazine (**Mag** and a larger version, **Mag+**, for node classification only) (Wang et al., 2020), and global shipping routes (**Ship**) (Saebi et al., 2020c). Table 1 their key characteristics, including average homophily $\mathcal{H}$ (defined by Zhu et al. (2020) as the fraction of edges that connect nodes of the same class). Additional details on each data set are available in Appendix B.

Tasks We tested DGE on node classification (semisupervised) and link prediction (supervised). For node classification, we used stratified 5-fold cross validation (Shchur et al., 2018) and reported the mean micro F1-score. For link prediction, we generated training and testing sets by randomly sampling 10% of positive node pairs and an equal number of negative node pairs. In addition to hiding all edges (in both directions) between testing pairs, for experiments using $\mathcal{G}_2$ we also hid all edges between any pair of nodes in the same higher-order families as each testing pair. We repeated each experiment five times and reported the mean area under the precision-recall curve (AUPRC) (Yang et al., 2015). All experiments utilized the same training and testing splits.

Baselines We evaluated several baselines, including GCN (Kipf & Welling, 2017), GAT (Veličković et al., 2018), GraphSAGE (Hamilton et al., 2017), GIN (Xu et al., 2019) and GATv2 (Brody et al., 2022). Two particularly relevant baselines are GraphSAINT (Zeng et al., 2020), which samples a different subgraph for each training iteration and has outperformed other GNNs on a number of tasks (Hu et al., 2020), and GCNII (Chen et al., 2020), which uses residual connections to address over-smoothing and enable deeper GNNs. We also evaluated HONEM, a matrix factorization method that is, to the best of our knowledge, the only learning algorithm that has been designed specifically for HONs (Saebi et al., 2020a).

Table 2: Node classification results (micro F1). Bold font indicates the best result for each data set.

Model	Air	T2D	Wiki	Mag	Mag+	Ship
GCN	0.818 ± 0.03	0.480 ± 0.02	0.643 ± 0.01	0.796 ± 0.01	0.710 ± 0.01	0.746 ± 0.01
GCNII	0.839 ± 0.05	0.511 ± 0.02	0.654 ± 0.02	0.801 ± 0.01	0.712 ± 0.01	0.770 ± 0.01
GAT	0.804 ± 0.03	0.282 ± 0.10	0.639 ± 0.02	0.487 ± 0.06	0.511 ± 0.02	0.745 ± 0.02
GATv2	0.838 ± 0.03	0.292 ± 0.07	0.643 ± 0.03	0.495 ± 0.05	0.527 ± 0.02	0.747 ± 0.01
GraphSAGE	0.781 ± 0.04	0.654 ± 0.04	0.625 ± 0.02	0.808 ± 0.02	0.689 ± 0.01	0.796 ± 0.01
GIN	0.745 ± 0.02	0.673 ± 0.04	0.636 ± 0.02	0.826 ± 0.02	0.722 ± 0.00	0.801 ± 0.01
GraphSAINT	0.802 ± 0.02	0.600 ± 0.07	0.664 ± 0.01	0.821 ± 0.02	0.719 ± 0.01	0.803 ± 0.01
HONEM	0.805 ± 0.04	0.566 ± 0.02	0.588 ± 0.01	0.728 ± 0.02	0.620 ± 0.01	0.750 ± 0.01
DGE-concat	0.825 ± 0.04	0.501 ± 0.06	0.615 ± 0.02	0.790 ± 0.02	0.681 ± 0.04	0.828 ± 0.01
DGE-concat*	0.810 ± 0.04	0.439 ± 0.03	0.577 ± 0.02	0.761 ± 0.02	0.642 ± 0.01	0.809 ± 0.01
DGE-pool	0.839 ± 0.03	0.735 ± 0.03	0.671 ± 0.01	0.860 ± 0.01	0.722 ± 0.01	0.808 ± 0.01
DGE-pool*	$\mathbf{0.865} \pm 0.02$	0.555 ± 0.07	0.599 ± 0.04	0.775 ± 0.01	0.671 ± 0.01	0.767 ± 0.02
DGE-bag	0.856 ± 0.02	$\mathbf{0.770} \pm 0.04$	$\mathbf{0.681} \pm 0.00$	$\mathbf{0.871} \pm 0.01$	$\mathbf{0.769} \pm 0.01$	$\mathbf{0.840} \pm 0.01$
DGE-bag*	0.766 ± 0.04	0.719 ± 0.04	0.644 ± 0.02	0.841 ± 0.02	0.739 ± 0.01	0.825 ± 0.01
DGE-batch*	0.764 ± 0.03	0.646 ± 0.01	0.623 ± 0.01	0.818 ± 0.01	0.742 ± 0.00	0.812 ± 0.01

* shared parameters

Table 3: Link prediction results (AUPRC). Bold font indicates the best result for each data set. Full baseline results are available in Appendix E.

Model	Air	T2D	Wiki	Mag	Ship
Best baseline	0.806 ± 0.01 (GCNII)	0.818 ± 0.00 (HONEM)	0.797 ± 0.01 (GATv2)	0.769 ± 0.00 (HONEM)	0.862 ± 0.01 (GraphSAINT)
DGE-concat	$\mathbf{0.886} \pm 0.01$	0.815 ± 0.01	0.774 ± 0.01	0.802 ± 0.00	$\mathbf{0.910} \pm 0.00$
DGE-concat*	0.856 ± 0.01	0.779 ± 0.01	0.712 ± 0.02	0.769 ± 0.01	0.904 ± 0.00
DGE-pool	0.851 ± 0.02	$\mathbf{0.920} \pm 0.00$	0.838 ± 0.03	0.913 ± 0.00	0.898 ± 0.00
DGE-pool*	0.845 ± 0.01	0.901 ± 0.00	0.802 ± 0.06	0.898 ± 0.00	0.815 ± 0.00
DGE-bag	$\mathbf{0.887} \pm 0.00$	0.907 ± 0.00	$\mathbf{0.876} \pm 0.01$	$\mathbf{0.921} \pm 0.00$	0.895 ± 0.00
DGE-bag*	0.862 ± 0.02	0.894 ± 0.00	0.856 ± 0.00	0.916 ± 0.00	0.891 ± 0.00
DGE-batch*	0.853 ± 0.03	0.871 ± 0.01	0.830 ± 0.01	0.887 ± 0.00	0.865 ± 0.00

* shared parameters

Implementation details   All baselines used $\mathcal{G}_1$ as input (we also evaluated each baseline using $\mathcal{G}_2$ as input, details are in Appendix E). We manually tuned each model (details in Appendix C). For DGE, unless noted otherwise, we fixed $\ell = 16$ and used the mean-pooling variant of GraphSAGE as the base GNN, since a) it performed reasonably well as a baseline on all six data sets, and b) its sample-and-aggregate procedure intuitively complements the relative sampling and pooling used by DGE. We used Python 3.7.3 and Tensorfow 2.4.1 for all experiments, and utilized Stellargraph 1.2.1 (Data61, 2018) for all neighborhood sampling functions and the implementation of DGE.

4.2   EXPERIMENTAL RESULTS

Node classification and link prediction   On the node classification task, DGE-bag outperformed all other methods on five data sets (Table 2) and was closely behind DGE-pool* on Air. DGE-pool performed marginally worse than DGE-bag in all cases, but DGE-concat did not generalize well and performed poorly in all cases except Ship. Sharing parameters typically reduced performance for each DGE variant, excepting DGE-pool* on Air. We discuss this observation in Section 4.3. Some baselines were competitive in a couple of cases: GCNII and GATv2 performed relatively well on Air, and GCNII and GraphSAINT performed relatively well on Wiki. However, on Mag and especially T2D, DGE-bag outperformed all baselines by a significant margin. The full-batch models struggled on T2D, perhaps due to its combination of high density (meaning that there are many transitive paths) and low homophily, which is a known obstacle for many GNNs (Zhu et al.,

Figure 3: Node classification loss as a function of model depth. Error bars represent standard deviation.

(a) Air results.   (b) T2D results.   (c) Wiki results.   (d) Mag results.

Figure 4: Node classification results as a function of total model parameters (log scale). GATv2 performed poorly on T2D and Mag and is not pictured in order to preserve figure scale.

2020) (see discussion in Appendix G). GAT and GATv2 performed especially poorly on the dense graphs (T2D and Mag), likely because they compute attention weights (instead of using the edge weights) and were thus more susceptible to overfitting. The link prediction results tell a similar story (Table 3), but the margin by which DGE outperformed baselines was even more significant. Additionally, the shared parameter variants of DGE were consistently worse than their counterparts. Because of its strong performance across all experiments, we focus the remainder of our analysis on DGE-bag. For details on training time and convergence for all models, please see Appendix F.

Model depth For all baselines, increasing the number of GNN layers typically increased generalization error (Figure 3). This was especially true for GAT and GATv2, which produced extremely high test error on T2D, Mag, Mag+, and Ship, especially when using more than one layer, and are not shown in Figure 3 in order to preserve scale. For DGE-bag, the test loss decreased with increased model depth in all but one case (layer 3 on T2D). These results support the findings of Lambiotte et al. (2019) that transitively inferring paths in a FON cannot account for higher-order dependencies, and our hypothesis that GNNs trained on $\mathcal{G}_1$ will overfit on non-existent paths. The exception to this pattern was Wiki, on which almost all models performed best with 3 layers (GCNII was the only model we tested with more than 3 layers, but it performed best with only a single layer). This difference is perhaps because Wiki was the sparsest graph, meaning that the likelihood of sampling a false positive path is relatively low due to smaller average neighborhood sizes. However, DGE-bag still produced the lowest test error at all depths.

Total model size In order to ensure that DGE's performance was not simply due to using a more expensive model, we also evaluated the impact of the total number of parameters on node classification performance for the strongest baselines and DGE-bag (Figure 4). Here we fixed the number of GNN layers to 2 and varied the size of the hidden layers from 4 to 4,096 units, as well as the ensemble size ℓ (for DGE-bag only). For example, with a budget of 7k parameters on Air, GCNII was allotted 16 hidden units per layer, while DGE-bag (ℓ=4) was allotted 4 hidden units per layer for each of the 4 base learners. DGE-bag underperformed with the smallest parameter budgets, since each base learner was too weak. We found that sharing parameters (DGE-bag*) resolved this issue and produced strong results on T2D, Wiki, and Mag. However, with a moderate parameter budget, DGE-bag (ℓ=4) consistently outperformed other models. As we increased the total budget such

Figure 5: Mean node classification loss for all pairs of the $\ell = 16$ base GNNs within each testing fold on T2D, plotted as a function of Cohen's kappa (lower values indicate lower agreement). Each point represents one pair of GNNs in the ensemble. All plots contain the same number of points.

that each base learner cointained at least 16 units per layer, DGE-bag consistently outperformed other models. After a certain point, further increasing the size of the hidden layers had a small (or even negative) impact on most models. Instead, increasing the ensemble size ℓ and allocating these parameters to additional base GNNs produced the best performance.

4.3 ENSEMBLE DIVERSITY AND PARAMETER SHARING

The variants of DGE that used separate parameters generally performed best. To understand this observation, we draw from prior work on ensembles, which has established that ensembles most potent when the individual classifiers have low error and high disagreement (Dietterich, 2000). As Figure 5 shows, DGE-bag consistently produced classifiers that both diverse and accurate. The shared-parameter variants often produced classifiers that were either diverse or accurate, but not both. We observed similar results for Air, Wiki, and Mag (Appendix E). These results reflect overall node classification performance (Table 2) and support a number of important conclusions. First, the high disagreement in DGE-bag demonstrates that our notion of neighborhood subspaces successfully introduced variance into the model. Second, the low mean error for DGE-bag demonstrates that ensembling GNNs with separate parameters effectively captured and exploited this variance. Third, sharing parameters (i.e., using a single, more complex model) did not achieve the same effect. DGE-pool* outperformed DGE-bag on Air because the classifiers were accurate enough to make up for the lack of disagreement. This may be because Air had large higher-order families than other data sets, so each bootstrap was less representative of the true neighborhood. However, using a true ensemble approach, where each GNN uses separate parameters, was the most consistently effective way to balance the trade-off between accuracy and diversity. If this trade-off can be addressed for other types of graphs, they may also benefit from ensembling GNNs.

5 LIMITATIONS, OTHER RELATED WORK, AND FUTURE DIRECTIONS

DGE's empirical success has implications for multiple research areas. Most broadly, we suggest that ensembling techniques for GNNs have been underexplored. However, generalizing our findings is complicated by the fact that DGE relies on the HON to supply the neighborhood variance, which is in turn limited to representing sequential data. Our results also suggest that the task of designing informed graph representations like HONs is essential and has been previously overshadowed by downstream learning algorithms. Other research on higher-order models has made progress toward this end, but much work remains to generalize these models and the types of dependencies they can represent. One area we consider promising for future work is graph structure learning. At present, HONs are constructed in unsupervised fashion, but future work could overcome this limitation by inferring the graph structure that best solves the given task (Brugere & Berger-Wolf, 2020; Chen & Wu, 2022). Unfortunately, most standard data sets for GNN tasks are pre-constructed graphs, meaning that any higher-order dependencies (sequential or otherwise) have already been lost before learning begins. By integrating graph construction into the learning process and continuing to develop more powerful GNNs, we will increase our capacity to model higher-order relationships and expand the frontier of machine learning on graphs.

REFERENCES

Taiga Abe, E Kelly Buchanan, Geoff Pleiss, Richard Zemel, and John P Cunningham. Deep ensembles work, but are they necessary? *arXiv preprint arXiv:2202.06985*, 2022.

Federico Battiston, Giulia Cencetti, Iacopo Iacopini, Vito Latora, Maxime Lucas, Alice Patania, Jean-Gabriel Young, and Giovanni Petri. Networks beyond pairwise interactions: structure and dynamics. *Physics Reports*, 874:1–92, 2020.

Federico Battiston, Enrico Amico, Alain Barrat, Ginestra Bianconi, Guilherme Ferraz de Arruda, Benedetta Franceschiello, Iacopo Iacopini, Sonia Kéfi, Vito Latora, Yamir Moreno, et al. The physics of higher-order interactions in complex systems. *Nature Physics*, 17(10):1093–1098, 2021.

Austin R Benson, David F Gleich, and Jure Leskovec. Higher-order organization of complex networks. *Science*, 353(6295):163–166, 2016.

Leo Breiman. Random forests. *Machine learning*, 45(1):5–32, 2001.

Shaked Brody, Uri Alon, and Eran Yahav. How attentive are graph attention networks? *International Conference on Learning Representations*, 2022.

Ivan Brugere and Tanya Y Berger-Wolf. Inferring network structure from data. *arXiv preprint arXiv:2004.02046*, 2020.

Ming Chen, Zhewei Wei, Zengfeng Huang, Bolin Ding, and Yaliang Li. Simple and deep graph convolutional networks. In *International Conference on Machine Learning*, pp. 1725–1735. PMLR, 2020.

Yu Chen and Lingfei Wu. Graph neural networks: Graph structure learning. In *Graph Neural Networks: Foundations, Frontiers, and Applications*, pp. 297–321. Springer, 2022.

Flavio Chierichetti, Ravi Kumar, Prabhakar Raghavan, and Tamas Sarlos. Are web users really markovian? In *Proceedings of the 21st international conference on World Wide Web*, pp. 609–618, 2012.

CSIRO's Data61. Stellargraph machine learning library. `https://github.com/stellargraph/stellargraph`, 2018.

Thomas G Dietterich. Ensemble methods in machine learning. In *International workshop on multiple classifier systems*, pp. 1–15. Springer, 2000.

Stanislav Fort, Huiyi Hu, and Balaji Lakshminarayanan. Deep ensembles: A loss landscape perspective. *arXiv preprint arXiv:1912.02757*, 2019.

Will Hamilton, Zhitao Ying, and Jure Leskovec. Inductive representation learning on large graphs. *Advances in neural information processing systems*, 30, 2017.

Tin Kam Ho. The random subspace method for constructing decision forests. *IEEE transactions on pattern analysis and machine intelligence*, 20(8):832–844, 1998.

Xiaochen Hou, Peng Qi, Guangtao Wang, Rex Ying, Jing Huang, Xiaodong He, and Bowen Zhou. Graph ensemble learning over multiple dependency trees for aspect-level sentiment classification. *arXiv preprint arXiv:2103.11794*, 2021.

Weihua Hu, Matthias Fey, Marinka Zitnik, Yuxiao Dong, Hongyu Ren, Bowen Liu, Michele Catasta, and Jure Leskovec. Open graph benchmark: Datasets for machine learning on graphs. *Advances in neural information processing systems*, 33:22118–22133, 2020.

Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *International Conference on Learning Representations (ICLR)*, 2017.

Andreas Koher, Hartmut HK Lentz, Philipp Hövel, and Igor M Sokolov. Infections on temporal networks—a matrix-based approach. *PloS one*, 11(4):e0151209, 2016.

Steven J Krieg, Peter M Kogge, and Nitesh V Chawla. Growhon: A scalable algorithm for growing higher-order networks of sequences. In *International Conference on Complex Networks and Their Applications*, pp. 485–496. Springer, 2020a.

Steven J Krieg, Daniel H Robertson, Meeta P Pradhan, and Nitesh V Chawla. Higher-order networks of diabetes comorbidities: Disease trajectories that matter. In *2020 IEEE International Conference on Healthcare Informatics (ICHI)*, pp. 1–11. IEEE, 2020b.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. *Advances in neural information processing systems*, 30, 2017.

Renaud Lambiotte, Martin Rosvall, and Ingo Scholtes. From networks to optimal higher-order models of complex systems. *Nature physics*, 15(4):313–320, 2019.

Qimai Li, Zhichao Han, and Xiao-Ming Wu. Deeper insights into graph convolutional networks for semi-supervised learning. In *Thirty-Second AAAI conference on artificial intelligence*, 2018.

Qi Lin, Shuo Yu, Ke Sun, Wenhong Zhao, Osama Alfarraj, Amr Tolba, and Feng Xia. Robust graph neural networks via ensemble learning. *Mathematics*, 10(8):1300, 2022.

Christopher Morris, Martin Ritzert, Matthias Fey, William L Hamilton, Jan Eric Lenssen, Gaurav Rattan, and Martin Grohe. Weisfeiler and leman go neural: Higher-order graph neural networks. In *Proceedings of the AAAI conference on artificial intelligence*, volume 33, pp. 4602–4609, 2019.

Tiago P Peixoto and Martin Rosvall. Modelling sequences and temporal networks with dynamic community structures. *Nature communications*, 8(1):582, 2017.

Mason A Porter. Nonlinearity+ networks: A 2020 vision. In *Emerging Frontiers in Nonlinear Science*, pp. 131–159. Springer, 2020.

Martin Rosvall, Alcides V Esquivel, Andrea Lancichinetti, Jevin D West, and Renaud Lambiotte. Memory in network flows and its effects on spreading dynamics and community detection. *Nature communications*, 5:4630, 2014.

Mandana Saebi, Giovanni Luca Ciampaglia, Lance M Kaplan, and Nitesh V Chawla. Honem: learning embedding for higher order networks. *Big Data*, 8(4):255–269, 2020a.

Mandana Saebi, Jian Xu, Salvatore R Curasi, Erin K Grey, Nitesh V Chawla, and David M Lodge. Network analysis of ballast-mediated species transfer reveals important introduction and dispersal patterns in the arctic. *Scientific reports*, 10(1):1–15, 2020b.

Mandana Saebi, Jian Xu, Erin K Grey, David M Lodge, James J Corbett, and Nitesh Chawla. Higher-order patterns of aquatic species spread through the global shipping network. *Plos one*, 15(7): e0220353, 2020c.

Mandana Saebi, Jian Xu, Lance M Kaplan, Bruno Ribeiro, and Nitesh V Chawla. Efficient modeling of higher-order dependencies in networks: from algorithm to application for anomaly detection. *EPJ Data Science*, 9(1):15, 2020d.

Thomas Schnake, Oliver Eberle, Jonas Lederer, Shinichi Nakajima, Kristof T Schutt, Klaus-Robert Mueller, and Gregoire Montavon. Higher-order explanations of graph neural networks via relevant walks. *IEEE Transactions on Pattern Analysis & Machine Intelligence*, pp. 1–1, 2021.

Ingo Scholtes. When is a network a network? In *Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 1037–1046. ACM, 2017.

Ingo Scholtes et al. Causality-driven slow-down and speed-up of diffusion in non-markovian temporal networks. *Nature communications*, 5:5024, 2014.

Oleksandr Shchur, Maximilian Mumme, Aleksandar Bojchevski, and Stephan Günnemann. Pitfalls of graph neural network evaluation. *arXiv preprint arXiv:1811.05868*, 2018.

Mark D Spalding, Helen E Fox, Gerald R Allen, Nick Davidson, Zach A Ferdaña, MAX Finlayson, Benjamin S Halpern, Miguel A Jorge, AL Lombana, Sara A Lourie, et al. Marine ecoregions of the world: a bioregionalization of coastal and shelf areas. *BioScience*, 57(7):573–583, 2007.

Hui Tang, Xun Liang, Bo Wu, Zhenyu Guan, Yuhui Guo, and Xiangping Zheng. Graph ensemble networks for semi-supervised embedding learning. In *International Conference on Knowledge Science, Engineering and Management*, pp. 408–420. Springer, 2021.

Leo Torres, Ann S Blevins, Danielle Bassett, and Tina Eliassi-Rad. The why, how, and when of representations for complex systems. *SIAM Review*, 63(3):435–485, 2021.

Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua Bengio. Graph attention networks. *International Conference on Learning Representations*, 2018.

Daheng Wang, Meng Jiang, Munira Syed, Oliver Conway, Vishal Juneja, Sriram Subramanian, and Nitesh V Chawla. Calendar graph neural networks for modeling time structures in spatiotemporal user behaviors. In *Proceedings of the 26th ACM SIGKDD international conference on knowledge discovery & data mining*, pp. 2581–2589, 2020.

Abdul Wasay and Stratos Idreos. More or less: When and how to build convolutional neural network ensembles. In *International Conference on Learning Representations*, 2020.

Robert West, Joelle Pineau, and Doina Precup. Wikispeedia: An online game for inferring semantic distances between concepts. In *Twenty-First International Joint Conference on Artificial Intelligence*, 2009.

Zonghan Wu, Shirui Pan, Fengwen Chen, Guodong Long, Chengqi Zhang, and S Yu Philip. A comprehensive survey on graph neural networks. *IEEE transactions on neural networks and learning systems*, 32(1):4–24, 2020.

Jian Xu, Thanuka L Wickramarathne, and Nitesh V Chawla. Representing higher-order dependencies in networks. *Science advances*, 2(5):e1600028, 2016.

Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=ryGs6iA5Km.

Yang Yang, Ryan N Lichtenwalter, and Nitesh V Chawla. Evaluating link prediction methods. *Knowledge and Information Systems*, 45(3):751–782, 2015.

Hanqing Zeng, Hongkuan Zhou, Ajitesh Srivastava, Rajgopal Kannan, and Viktor Prasanna. Graphsaint: Graph sampling based inductive learning method. *International Conference on Learning Representations*, 2020.

Hanqing Zeng, Muhan Zhang, Yinglong Xia, Ajitesh Srivastava, Andrey Malevich, Rajgopal Kannan, Viktor Prasanna, Long Jin, and Ren Chen. Decoupling the depth and scope of graph neural networks. *Advances in Neural Information Processing Systems*, 34:19665–19679, 2021.

Jie Zhou, Ganqu Cui, Shengding Hu, Zhengyan Zhang, Cheng Yang, Zhiyuan Liu, Lifeng Wang, Changcheng Li, and Maosong Sun. Graph neural networks: A review of methods and applications. *AI Open*, 1:57–81, 2020.

Jiong Zhu, Yujun Yan, Lingxiao Zhao, Mark Heimann, Leman Akoglu, and Danai Koutra. Beyond homophily in graph neural networks: Current limitations and effective designs. *Advances in Neural Information Processing Systems*, 33:7793–7804, 2020.