DISSECTING ADAPTIVE METHODS IN GANS

ABSTRACT

Adaptive methods are a crucial component widely used for training generative adversarial networks (GANs). While there has been some work to pinpoint the "marginal value of adaptive methods" in standard tasks, it remains unclear why they are still critical for GAN training. In this paper, we formally study how adaptive methods help train GANs; inspired by the grafting method proposed in Agarwal et al. (2020), we separate the magnitude and direction components of the Adam updates, and graft them to the direction and magnitude of SGDA updates respectively. By considering an update rule with the magnitude of the Adam update and the normalized direction of SGD, we empirically show that the adaptive magnitude of Adam is key for GAN training. This motivates us to have a closer look at the class of normalized stochastic gradient descent ascent (nSGDA) methods in the context of GAN training. We propose a synthetic theoretical framework to compare the performance of nSGDA and SGDA for GAN training with neural networks. We prove that in that setting, GANs trained with nSGDA recover all the modes of the true distribution, whereas the same networks trained with SGDA (and any learning rate configuration) suffer from mode collapse. The critical insight in our analysis is that normalizing the gradients forces the discriminator and generator to be updated at the same pace. We also experimentally show that for several datasets, Adam's performance can be recovered with nSGDA methods.

1 INTRODUCTION

Adaptive algorithms have become a key component in training modern neural network architectures in various deep learning tasks. Minimization problems that arise in natural language processing (Vaswani et al., 2017), fMRI (Zbontar et al., 2018), or min-max problems such as generative adversarial networks (GANs) (Goodfellow et al., 2014) almost exclusively use adaptive methods, and it has been empirically observed that Adam (Kingma & Ba, 2014) yields a solution with better generalization than stochastic gradient descent (SGD) in such problems (Choi et al., 2019). Several works have attempted to explain this phenomenon in the minimization setting. Common explanations are that adaptive methods train faster (Zhou et al., 2018), escape flat "saddle-point"–like plateaus faster (Orvieto et al., 2021), or handle heavy-tailed stochastic gradients better (Zhang et al., 2019; Gorbunov et al., 2022). However, much less is known about why adaptive methods are so critical for solving min-max problems such as GANs.

Several previous works attribute this performance to the superior convergence speed of adaptive methods. For instance, Liu et al. (2019) show that an adaptive variant of Optimistic Gradient Descent (Daskalakis et al., 2017) converges faster than SGDA for a class of non-convex, non-concave min-max problems. However, contrary to the minimization setting, convergence to a stationary point is not guaranteed, nor is it even a requirement to ensure a satisfactory GAN performance. Mescheder et al. (2018) empirically shows that popular architectures such as Wasserstein GANs (WGANs) (Arjovsky et al., 2017) do not always converge, and yet they produce realistic images. We support this observation with our own experiments in Section 2 (see Fig. 1b.) This finding motivates the central question in this paper: *what factors of Adam contribute to better quality solutions than SGDA when training GANs?*

In this paper, we investigate why GANs trained with adaptive methods outperform those trained using stochastic gradient descent ascent (SGDA). Directly analyzing Adam is challenging due to the highly non-linear nature of its gradient oracle and its path-dependent update rule. Inspired by the grafting approach in (Agarwal et al., 2020), we disentangle the adaptive magnitude and direction of Adam and show evidence that an algorithm made of the adaptive magnitude of Adam and the direction of

SGDA (Ada-nSGDA) recovers the performance of Adam in GANs. The adaptive magnitude in Adam is thus key for the performance, and the standard nSGDA direction . Our contributions are as follows:

- In Section 2, we present the Ada-nSGDA algorithm and the standard normalized SGDA (nSGDA). We further show that for some architectures and datasets, nSGDA can be used to model the dynamics of the performance of Adam in GAN training.
- In Section 3, we prove that for a synthetic dataset consisting of two modes, a model trained with SGDA suffers from *mode collapse* (producing only a single type of output), while a model trained with nSGDA does not. This provides an explanation for why GANs trained with nSGDA outperform those trained with SGDA.
- In Section 4, we empirically confirm that Ada-nSDGA recovers the performance of Adam when using different GAN architectures on a wide range of datasets.

Our key theoretical insight is that when using SGDA and any step-size configuration, either the generator G or discriminator D updates much faster than its counterpart. By normalizing the gradients as done in nSGDA, D and G are forced to update at the same speed throughout training. The consequence is that whenever D learns a mode of the distribution, G learns it right after, which makes both of them learn all the modes of the distribution separately.

1.1 RELATED WORK

Adaptive methods in games optimization. Several works designed adaptive algorithms and analyzed their convergence to show their benefits relative to SGDA e.g. in variational inequality problems, Gasnikov et al. (2019); Antonakopoulos et al. (2019); Bach & Levy (2019); Antonakopoulos et al. (2020); Liu et al. (2019); Barazandeh et al. (2021). Heusel et al. (2017) show that Adam locally converges to a Nash equilibrium in the regime where the step-size of the discriminator is much larger than the one of the generator. Our work differs as we do not focus on the convergence properties of Adam, but rather on the fit of the trained model to the *true* (and not empirical) data distribution.

Statistical results in GANs. Early works studied whether GANs memorize the training data or actually learn the distribution (Arora et al., 2017; Liang, 2017; Feizi et al., 2017; Zhang et al., 2017; Arora et al., 2018; Bai et al., 2018; Dumoulin et al., 2016). Some works explained GAN performance through the lens of optimization. Lei et al. (2020); Balaji et al. (2021) show that GANs trained with SGDA converge to a global saddle point when the generator is one-layer neural network and the discriminator is a specific quadratic/linear function. Our contribution differs as i) we construct a setting where SGDA converges to a locally optimal min-max equilibrium but still suffers from mode collapse, and ii) we have a more challenging setting since we need at least a degree-3 discriminator to learn the distribution, which is discussed in Section 3.

Normalized gradient descent. Introduced by Nesterov (1984), normalized gradient descent has been widely used in minimization problems. Normalizing the gradient remedies the issue of iterates being stuck in flat regions such as spurious local minima or saddle points (Hazan et al., 2015; Levy, 2016). Normalized gradient descent methods outperforms their non-normalized counterparts in multi-agent coordination (Cortés, 2006) and deep learning tasks (Cutkosky & Mehta, 2020). Our work considers the min-max setting and shows that nSGDA outperforms SGDA as it forces discriminator and generator to update at same rate.

1.2 BACKGROUND

Generative adversarial networks. Given a training set sampled from some target distribution $\mathcal{D}$, a GAN learns to generate new data from this distribution. The architecture is comprised of two networks: a generator that maps points in the latent space $\mathcal{D}_z$ to samples of the desired distribution, and a discriminator which evaluates these samples by comparing them to samples from $\mathcal{D}$. More formally, the generator is a mapping $G_\mathcal{V} \colon \mathbb{R}^k \to \mathbb{R}^d$ and the discriminator is a mapping $D_\mathcal{W} \colon \mathbb{R}^d \to \mathbb{R}$, where $\mathcal{V}$ and $\mathcal{W}$ are their corresponding parameter sets. To find the optimal parameters of these two networks, one must solve a min-max optimization problem of the form

$$\min_\mathcal{V} \max_\mathcal{W} \mathbb{E}_{X \sim p_{data}}[\log(D_\mathcal{W}(X))] + \mathbb{E}_{z \sim p_z}[\log(1 - D_\mathcal{W}(G_\mathcal{V}(z)))] := f(\mathcal{V}, \mathcal{W}), \quad \text{(GAN)}$$

where p_{data} is the distribution of the training set, p_z the latent distribution, $G_\mathcal{V}$ the generator and $D_\mathcal{W}$ the discriminator. Contrary to minimization problems where convergence to a local minimum is *required* for high generalization, we empirically verify that most of the well-performing GANs do not converge to a stationary point.

(a) Each circle corresponds to a specific step-size configuration η_D/η_G. The best-performing models have step-size ratios between 10^{-1} and 1, and do not converge. As η_D/η_G increases, the models perform worse but get closer to an equilibrium.

(b) shows that during training, the gradient ratio of a well-performing GAN approximately stays constant to 1. We also display the images produced by the model during training.

Figure 1: Gradient ratio against FID score (a) and number of epochs (b) obtained with DCGAN on CIFAR-10. This ratio is equal to $\|\text{grad}_G^{(t)}\|_2/\|\text{grad}_G^{(0)}\|_2 + \|\text{grad}_D^{(t)}\|_2/\|\text{grad}_D^{(0)}\|_2$, where $\text{grad}_G^{(t)}$ (resp. $\text{grad}_D^{(t)}$) and $\text{grad}_G^{(0)}$ (resp. $\text{grad}_D^{(0)}$) are the current and initial gradients of G (resp. D). Note that $\|\cdot\|_2$ refers to the sum of all the parameters norm in a network. For all the plots, the models are trained for 100 epochs using a batch-size 64. For (b), the results are averaged over 5 seeds.

Convergence and performance are decorrelated in GANs. We support this observation through the following experiment. We train a DCGAN (Radford et al., 2015) using Adam and set up the step-sizes for G and D as η_D, η_G, respectively. Note that D is usually trained faster than G i.e. $\eta_D \geq \eta_G$. Figure 1a displays the GAN convergence measured by the ratio of gradient norms and the GAN's performance measured in FID score (Heusel et al., 2017). We observe that when η_D/η_G is close to 1, the algorithm does not converge, and yet, the model produces high-quality solutions. On the other hand, when $\eta_D/\eta_G \gg 1$, the model converges to an equilibrium; a similar statement has been proved by Jin et al. (2020) and Fiez & Ratliff (2020) in the case of SGDA. However, the trained GAN produces low-quality solutions at this equilibrium, so simply comparing the convergence speed of adaptive methods and SGDA cannot explain the performance obtained with adaptive methods.

SGDA and adaptive methods. The most simple algorithm to solve the min-max (GAN) is SGDA, which is defined as follows:

$$\mathcal{W}^{(t+1)} = \mathcal{W}^{(t)} + \eta_D \mathbf{M}_{\mathcal{W},1}^{(t)}, \quad \mathcal{V}^{(t+1)} = \mathcal{V}^{(t)} - \eta_G \mathbf{M}_{\mathcal{V},1}^{(t)}, \tag{1}$$

where $\mathbf{M}_{\mathcal{W},1}^{(t)}, \mathbf{M}_{\mathcal{V},1}^{(t)}$ are the first-order momentum gradients as defined in Algorithm 1. While this method has been used in the first GANs (Radford et al., 2015), most modern GANs are trained with adaptive methods such as Adam (Kingma & Ba, 2014).

The definition of this algorithm for game optimizations is given in Algorithm 1. The hyperparameters $\beta_1, \beta_2 \in [0, 1)$ control the weighting of the exponential moving average of the first and second-order moments. In many deep-learning tasks, practitioners have found that setting $\beta_2 = 0.9$ works for most problem settings. It has been empirically observed that having no momentum (i.e., $\beta_1 \approx 0$) is optimal for many popular architectures (Karras et al., 2020; Brock et al., 2018). Thus, in what follows, we only consider the case where $\beta_1 = 0$.

Optimizers such as Adam (Algorithm 1) are *adaptive* because they keep updating step-sizes while training the model. There are two components that contribute to the update step: the adaptive magnitude $\|\mathbf{A}_{\mathcal{Y}}^{(t)}\|_2$ and the adaptive direction $\mathbf{A}_{\mathcal{Y}}^{(t)}/\|\mathbf{A}_{\mathcal{Y}}^{(t)}\|_2$. The two components are entangled and it remains unclear how they contribute to the superior performance of adaptive methods relative to SGDA in GANs.

2 NSGDA AS A MODEL TO ANALYZE ADAM IN GANS

In this section, we show that normalized stochastic gradient descent-ascent (nSGDA) is a suitable proxy to study the learning dynamics of Adam.

Algorithm 1 Adam (Kingma & Ba, 2014) for games. All operations on vectors are element-wise.

Input: initial points $\mathcal{W}^{(0)}, \mathcal{V}^{(0)}$, step-size schedules $\{(\eta_G^{(t)}, \eta_D^{(t)})\}$, hyperparameters $\{\beta_1, \beta_2, \varepsilon\}$.

Initialize $\mathbf{M}_{\mathcal{W},1}^{(0)}, \mathbf{M}_{\mathcal{W},2}^{(0)}, \mathbf{M}_{\mathcal{V},1}^{(0)}$ and $\mathbf{M}_{\mathcal{V},2}^{(0)}$ to zero.

for $t = 0 \ldots T - 1$ **do**

    Receive stochastic gradients $\mathbf{g}_{\mathcal{W}}^{(t)}, \mathbf{g}_{\mathcal{V}}^{(t)}$ evaluated at $\mathcal{W}^{(t)}$ and $\mathcal{V}^{(t)}$.

    Update for $\mathcal{Y} \in \{\mathcal{W}, \mathcal{V}\}$: $\mathbf{M}_{\mathcal{Y},1}^{(t+1)} = \beta_1 \mathbf{M}_{\mathcal{Y},1}^{(t)} + \mathbf{g}_{\mathcal{Y}}^{(t)}$ and $\mathbf{M}_{\mathcal{Y},2}^{(t+1)} = \beta_2 \mathbf{M}_{\mathcal{Y},2}^{(t)} + \mathbf{g}_{\mathcal{Y}}^{(t)2}$.

    Compute gradient oracles for $Y \in \{V, W\}$: $\mathbf{A}_{\mathcal{Y}}^{(t+1)} = \mathbf{M}_{\mathcal{Y},1}^{(t+1)} / \sqrt{\mathbf{M}_{\mathcal{Y},2}^{(t+1)} + \varepsilon}$.

    Update: $\mathcal{W}^{(t+1)} = \mathcal{W}^{(t)} + \eta_D^{(t)} \mathbf{A}_{\mathcal{W}}^{(t+1)}, \qquad \mathcal{V}^{(t+1)} = \mathcal{V}^{(t)} - \eta_G^{(t)} \mathbf{A}_{\mathcal{V}}^{(t+1)}$.

(a)	(b)	(c)

Figure 2: (a) shows the FID training curve for a WGAN-GP ResNet, averaged over 5 seeds. We see that Ada-nSGDA and nSGDA have very similar performance to Adam for a WGAN-GP. (b, c) displays the fluctuations of Ada-nSGDA adaptive magnitude. We plot the ratio $\|\mathbf{A}_{\mathcal{Y}}^{(t)}\|_2 / \|\mathbf{A}_{\mathcal{Y}}^{(0)}\|_2$ for each discriminator's (b) and generator's (c) layers. At early stages, this ratio barely increases and remains constant after 10 steps.

To decouple the adaptive magnitude and direction in Adam, we adopt the step-size grafting approach proposed by Agarwal et al. (2020). At each iteration, we compute stochastic gradients, pass them to two optimizers $\mathcal{A}_1, \mathcal{A}_2$ and make a grafted step that combines the *magnitude* of $\mathcal{A}_1$'s step and *direction* of $\mathcal{A}_2$'s step. We focus on the optimizer defined by grafting the Adam magnitude onto the SGDA direction, i.e:

$$\mathcal{W}^{(t+1)} = \mathcal{W}^{(t)} + \eta_D^{(t)} \|\mathbf{A}_{\mathcal{W}}^{(t)}\|_2 \frac{\mathbf{g}_{\mathcal{W}}^{(t)}}{\|\mathbf{g}_{\mathcal{W}}^{(t)}\|_2 + \varepsilon}, \quad \mathcal{V}^{(t+1)} = \mathcal{V}^{(t)} - \eta_G^{(t)} \|\mathbf{A}_{\mathcal{V}}^{(t)}\|_2 \frac{\mathbf{g}_{\mathcal{V}}^{(t)}}{\|\mathbf{g}_{\mathcal{V}}^{(t)}\|_2 + \varepsilon}, \quad (2)$$

where $\mathbf{A}_{\mathcal{V}}^{(t)}, \mathbf{A}_{\mathcal{W}}^{(t)}$ are the Adam gradient oracles as in Algorithm 1 and $\boldsymbol{g}_{\mathcal{V}}^{(t)}, \boldsymbol{g}_{\mathcal{W}}^{(t)}$ the stochastic gradients. We refer to this algorithm as *Ada-nSGDA* (combining the Adam magnitude and SGDA direction). There are two natural implementations for nSDGA. In the *layer-wise* version, $\mathcal{Y}^{(t)}$ is a single parameter group (typically a layer in a neural network), and the updates are applied to each group. In the *global* version, $\mathcal{Y}^{(t)}$ contains all of the model's weights.

In Fig. 2, we show that Ada-nSGDA and Adam appear to have similar learning dynamics in terms of the FID score. Both Adam and Ada-nSGDA significantly outperform SGDA as well as AdaDir, which is the alternate case of (2) where we instead graft the magnitude of the SGDA update to the direction of the Adam update. AdaDir diverged after a single step so we omit it in Fig. 2. This confirms that the critical component of Adam is the *adaptive magnitude*, and that the standard update direction recovered by SGDA is sufficient to recover a good solution. However, from a theoretical perspective, directly analyzing Ada-nSGDA is difficult due to the adaptive magnitudes $\|\mathbf{A}_{\mathcal{V}}^{(t)}\|_2, \|\mathbf{A}_{\mathcal{W}}^{(t)}\|_2$. Therefore, in Section 3, we analyze normalized SGDA (nSGDA) which is Ada-nSGDA (2) where we omit the adaptive magnitudes. Although nSGDA does not consider the adaptive magnitude, it still recovers the performance of Adam for some architectures such as WGAN-GP (Arjovsky et al., 2017) as we show in Fig. 2. This may come from the fact that the adaptive magnitudes stay within a constant range and do not fluctuate across time, as shown in Figs. 2b and 2c.

3 WHY DOES NSGDA PERFORM BETTER THAN SGDA IN GANS?

In Section 2, we numerically showed that nSGDA recovers the performance Adam. Similar to other optimization works in minimization, we use nSGDA as a model to understand Adam in GANs. Our goal is to construct a dataset and model where we can prove that a model trained with nSGDA generates samples from the true training distribution while SGDA fails. To this end, we consider a dataset where the underlying distribution consists of two modes, defined as vectors u_1, u_2, that are slightly correlated (See Assumption 1) and consider the standard GANs' training objective. We show that a GAN trained with SGDA using any reasonable[1] step-size configuration suffers from *mode collapse* (Theorem 3.1); it only outputs samples from a single mode which is a weighted average of u_1 and u_2. Conversely, nSGDA-trained GANs learn the two modes separately (Theorem 3.2).

Notation We set the GAN 1-sample loss $L_{\mathcal{V},\mathcal{W}}^{(t)}(X, z) = \log(D_{\mathcal{W}}^{(t)}(X)) + \log(1 - D_{\mathcal{W}}^{(t)}(G_{\mathcal{V}}^{(t)}(z)))$. We denote $\mathbf{g}_{\mathcal{Y}}^{(t)} = \nabla_{\mathcal{Y}} L_{\mathcal{V},\mathcal{W}}^{(t)}(X, z)$ as the 1-sample stochastic gradient. We use the asymptotic complexity notations when defining the different constants e.g. $\text{poly}(d)$ refers to any polynomial in the dimension d, $\text{polylog}(d)$ to any polynomial in $\log(d)$, and $o(1)$ to a constant $\ll d$. We denote $a \propto b$ for vectors a and b in $\mathbb{R}^d$ if there is a positive scaling factor $c > 0$ such that $\|a - cb\|_2 = o(\|b\|_2)$.

3.1 SETTING

In this section, we present the setting to sketch our main results in Theorem 3.1 and Theorem 3.2. We first define the distributions for the training set and latent samples, and specify our GAN model and the algorithms we analyze to solve (GAN). Note that for many assumptions and theorems below, we present informal statements which are sufficient to capture the main insights. The precise statements can be found in Appendix B.

Our synthetic theoretical framework considers a bimodal data distribution with two correlated modes:

Assumption 1 (p_{data} structure). *Let $\gamma = \frac{1}{\text{polylog}(d)}$. We assume that the modes are correlated. This means that $\langle u_1, u_2 \rangle = \gamma > 0$ and the generated data point X is either $X = u_1$ or $X = u_2$.*

Next, we define the latent distribution p_z that $G_{\mathcal{V}}$ samples from and maps to p_{data}. Each sample from p_z consists of a data-point z that is a binary-valued vector $z \in \{0, 1\}^{m_G}$, where m_G is the number of neurons in $G_{\mathcal{V}}$, and has non-zero support, i.e. $\|z\|_0 \geq 1$. Although the typical choice of a latent distributions in GANs is either Gaussian or uniform, we choose p_z to be a binary distribution because it models the weights' distribution of a hidden layer of a deep generator; Allen-Zhu & Li (2021) argue that the distributions of these hidden layers are sparse, non-negative, and non-positively correlated. We now make the following assumptions on the coefficients of z:

Assumption 2 (p_z structure). *Let $z \sim p_z$. We assume that with probability $1 - o(1)$, there is only one non-zero entry in z. The probability that the entry $i \in [m_G]$ is non-zero is $\Pr[z_i = 1] = \Theta(1/m_G)$.*

In Assumption 2, the output of $G_{\mathcal{V}}$ is only made of one mode with probability $1 - o(1)$. This avoids summing two of the generator's neurons, which may cause mode collapse.

To learn the target distribution p_{data}, we use a linear generator $G_{\mathcal{V}}$ with m_G neurons and a non-linear neural network with m_D neurons:

$$G_{\mathcal{V}}(z) = Vz = \sum_{i=1}^{m_G} v_i z_i, \qquad D_{\mathcal{W}}(X) = \text{sigmoid}\Big(a \sum_{i=1}^{m_D} \langle w_i, X \rangle^3 + \frac{b}{\sqrt{d}}\Big). \qquad (3)$$

where $V = [v_1^\top, v_2^\top, \cdots, v_{m_G}^\top] \in \mathbb{R}^{m_G \times d}$, $z \in \{0, 1\}^{m_G}$, $W = [w_1^\top, \ldots, w_{m_D}^\top] \in \mathbb{R}^{m_D \times d}$, and $a, b \in \mathbb{R}$. Intuitively, $G_{\mathcal{V}}$ outputs linear combinations of the modes v_i. We choose a cubic activation as it is the smallest monomial degree for the discriminator's non-linearity that is sufficient for the generator to recover the modes u_1, u_2.[2]

---

[1]Reasonable simply means that the learning rates are bounded to prevent the training from diverging.

[2]Li & Dou (2020) show that when using linear or quadratic activations, the generator can fool the discriminator by only matching the first and second moments of p_{data}.

We now state the SGDA and nSGDA algorithms used to solve the GAN training problem (GAN). For simplicity, we set the batch-size to 1. The resultant update rules for SGDA and nSGDA are:[3]

SGDA: at each step $t > 0$, sample $X \sim p_{data}$ and $z \sim p_z$ and update as

$$\mathcal{W}^{(t+1)} = \mathcal{W}^{(t)} + \eta_D \mathbf{g}_{\mathcal{W}}^{(t)}, \quad \mathcal{V}^{(t+1)} = \mathcal{V}^{(t)} - \eta_G \mathbf{g}_{\mathcal{V}}^{(t)}, \tag{4}$$

nSGDA: at each step $t > 0$, sample $X \sim p_{data}$ and $z \sim p_z$ and update as

$$\mathcal{W}^{(t+1)} = \mathcal{W}^{(t)} + \eta_D \frac{\mathbf{g}_{\mathcal{W}}^{(t)}}{\|\mathbf{g}_{\mathcal{W}}^{(t)}\|_2}, \quad \mathcal{V}^{(t+1)} = \mathcal{V}^{(t)} - \eta_G \frac{\mathbf{g}_{\mathcal{V}}^{(t)}}{\|\mathbf{g}_{\mathcal{V}}^{(t)}\|_2}. \tag{5}$$

Compared to the versions of SGDA and Ada-nSGDA that we introduced in Section 2, we have the same algorithms except that we set $\beta_1 = 0$ and omit ε in (4) and (5). Lastly, we detail how to set the optimization parameters for SGDA and nSGDA in (4) and (5).

Parametrization 3.1 (Informal). *When running SGDA and nSGDA on (GAN), we set:*

*– **Initialization**: $b^{(0)} = 0$, and $a^{(0)}$, $w_i^{(0)}(i \in [m_D])$, $v_j^{(0)}(j \in [m_G])$ are initialized with a Gaussian with small variance.*

*– **Number of iterations**: we run SGDA for $t \leq T_0$ iterations where T_0 is the first iteration such that the algorithm converges to an approximate first order local minimum. For nSGDA, we run for $T_1 = \tilde{\Theta}(1/\eta_D)$ iterations.*

*– **Step-sizes**: For SGDA, $\eta_D, \eta_G \in (0, \frac{1}{\text{poly}(d)})$ can be arbitrary. For nSGDA, $\eta_D \in (0, \frac{1}{\text{poly}(d)}]$, and η_G is slightly smaller than η_D.*

*– **Over-parametrization**: For SGDA, $m_D, m_G = \text{polylog}(d)$ are arbitrarily chosen i.e. m_D may be larger than m_G or the opposite. For nSGDA, we set $m_D = \log(d)$ and $m_G = 2\log(d)$.*

Our theorem holds when running SGDA for any (polynomially) possible number of iterations; after T_0 steps, the gradient becomes inverse polynomially small and SGDA essentially stops updating the parameters. Additionally, our setting allows any step-size configuration for SGDA i.e. larger, smaller, or equal step-size for D compared to G. Note that our choice of step-sizes for nSGDA is the one used in practice, i.e. η_D slightly larger than η_G.

3.2 MAIN RESULTS

We state our main results on the performance of models trained using SGDA (4) and nSGDA (5). We show that nSGDA learns the modes of the distribution p_{data} while SGDA does not.

Theorem 3.1 (Informal). *Consider a training dataset and a latent distribution as described above and let Assumption 1 and Assumption 2 hold. Let T_0, η_G, η_D and the initialization be as defined in Parametrization 3.1. Let t be such that $t \leq T_0$. Run SGDA on the GAN problem defined in (GAN) for t iterations with step-sizes η_G, η_D. Then, with probability at least $1 - o(1)$, the generator outputs for all $z \in \{0,1\}^{m_G}$:*

$$G_{\mathcal{V}}^{(t)}(z) \propto \begin{cases} u_1 + u_2 & \text{if } \eta_D \geq \eta_G \\ \xi^{(t)}(z) & \text{otherwise} \end{cases}, \tag{6}$$

where $\xi^{(t)}(z) \in \mathbb{R}^d$ is some vector that is not correlated to any of the modes. Formally, $\forall \ell \in [2]$, $\cos(\xi^{(t)}(z), u_\ell) = o(1)$ for all $z \in \{0,1\}^{m_G}$.

A formal proof can be found in Appendix G. Theorem 3.1 indicates that when training with SGDA and any step-size configuration, the generator either does not learn the modes at all ($G_{\mathcal{V}}^{(t)}(z) = \xi^{(t)}(z)$) or learns an average of the modes ($G_{\mathcal{V}}^{(t)}(z) \propto u_1 + u_2$). The theorem holds *for any* time $t \leq T_0$ which is the iteration where SGDA converges to an approximate first-order locally optimal min-max equilibrium. Conversely, nSGDA succeeds in learning the two modes separately:

---

[3]In the nSGDA algorithm defined in (2), the step-sizes were time-dependent. Here, we assume for simplicity that the step-sizes $\eta_D, \eta_G > 0$ are *constant*.

(a) Relative gradients   (b) D weight correlation   (c) $\mathcal{V}$ learned via SGDA   (d) $\mathcal{V}$ learned via nSGDA

Figure 3: (a) shows the relative gradient updates for SGDA. D first updates its weights while G does not move until iteration 20, then G moves its weights. (b) shows the correlation for one neuron of D (with maximal correlation to u_2 at initialization) with the modes u_1, u_2 during the learning process of SGDA. (c, d) shows the correlations of the neurons of G with the modes when trained with SGDA and nSGDA respectively. This shows that for SGDA (c), the model ultimately learns the weighted average $u_1 + u_2$. For nSGDA, we see from (d) that one of the neurons (V_4) is highly correlated with u_1 and another one (V_3) is correlated with u_2.

Theorem 3.2 (Informal). *Consider a training dataset and a latent distribution as described above and let Assumption 1 and Assumption 2 hold. Let T_1, η_G, η_D and the initialization as defined in Parametrization 3.1. Run nSGDA on (GAN) for T_1 iterations with step-sizes η_G, η_D. Then, the generator learns both modes u_1, u_2 i.e., for $\ell \in \{1, 2\}$,*

$$\Pr_{z \sim p_z}[G_{\mathcal{V}}^{(T_1)}(z) \propto u_\ell] \quad \text{is non-negligible.} \tag{7}$$

A formal proof can be found in Appendix I. Theorem 3.2 indicates that when we train a GAN with nSGDA in the regime where the discriminator updates slightly faster than the generator (as done in practice), the generator successfully learns the distribution containing the direction of both modes.

We implement the setting introduced in Subsection 3.1 and validate Theorem 3.1 and Theorem 3.2 in Fig. 3. Fig. 3a displays the relative update speed $\eta \|\mathbf{g}_{\mathcal{Y}}^{(t)}\|_2 / \|\mathcal{Y}^{(t)}\|_2$, where $\mathcal{Y}$ corresponds to the parameters of either D or G. Fig. 3b shows the correlation $\langle w_i^{(t)}, u_\ell \rangle / \|w_i^{(t)}\|_2$ between *one* of D's neurons and a mode u_ℓ and Fig. 3c the correlation $\langle v_j^{(t)}, u_\ell \rangle / \|v_j^{(t)}\|_2$ between G's neurons and u_ℓ. We discuss the interpretation of these plots to the next section.

WHY DOES SGDA SUFFER FROM MODE COLLAPSE AND NSGDA LEARN THE MODES?

We now explain why SGDA suffers from mode collapse, which corresponds to the case where $\eta_D \geq \eta_G$. Our explanation relies on the interpretation of Figs. 3a, 3b, and 3c, and on the updates around initialization that are defined as followed. There exists $i \in [m_D]$ such that D's update is with high probability

$$\mathbb{E}[w_i^{(t+1)}|w_i^{(t)}] \approx w_i^{(t)} + \eta_D \sum_{l=1}^{2} \mathbb{E}[\langle w_i^{(t)}, u_l \rangle^2] u_l. \tag{8}$$

Thus, the weights of D receive gradients directed by u_1 and u_2. On the other hand, the weights of G at early stages receive gradients directed by $w_j^{(t)}$:

$$v_i^{(t+1)} \approx v_i^{(t)} + \eta_G \sum_j \langle v_i^{(t)}, w_j^{(t)} \rangle^2 w_j^{(t)}. \tag{9}$$

We observe that the learning process in Figs. 3a & 3b has three distinct phases. In the first phase (iterations 1-20), D learns one of the modes (u_1 or u_2) of p_{data} (Fig. 3b) and G barely updates its weights (Fig. 3a). In the second phase (iterations 20-40), D learns the weighted average $u_1 + u_2$ (Fig. 3b) while G starts moving its weights (Fig. 3a). In the final phase (iterations 40+), G learns $u_1 + u_2$ (Fig. 3c) from D. In more detail, the learning process is described as follows:

Phase 1 : At initialization, $w_j^{(0)}$ and $v_j^{(0)}$ are small. Assume w.l.o.g. that $\langle w_i^{(0)}, u_2 \rangle > \langle w_i^{(0)}, u_1 \rangle$. Because of the $\langle w_i^{(t)}, u_l \rangle^2$ in front of u_2 in (8), the parameter $w_i^{(t)}$ gradually grows its correlation with u_2 (Fig. 3b) and D's gradient norm thus increases (Fig. 3a). While $\|w_j^{(t)}\| \ll 1 \, \forall j$, we have that $v_i^{(t)} \approx v_i^{(0)}$ (Fig. 3a).

Phase 2: D has learned u_2. Because of the sigmoid in the gradient of $w_i^{(t)}$ (that was negligible during Phase 1) and $\langle u_1, u_2 \rangle = \gamma > 0$, $w_i^{(t)}$ now mainly receives updates with direction u_2. Since G did not update its weights yet, the min-max problem (GAN) is approximately just a minimization problem with respect to D's parameters. Since the optimum of such a problem is the weighted average $u_1 + u_2$, $w_j^{(t)}$ slowly converges to this optimum. Meanwhile, $v_i^{(t)}$ start to receive some significant signal (Fig. 3a) but mainly learn the direction $u_1 + u_2$ (Fig. 3c), because $w_j^{(t)}$ is aligning with this direction.

Phase 3: The parameters of G only receive gradient directed by $u_1 + u_2$. The norm of its relative updates stay large and D only changes its last layer terms (slope a and bias b).

In contrast to SGDA, nSGDA ensures that G and D always learn at the same speed with the updates:

$$w_i^{(t+1)} \approx w_i^{(t)} + \eta_D \frac{\langle w_i^{(t)}, X \rangle^2 X}{\| \langle w_i^{(t)}, X \rangle^2 X \|_2}, \text{ and } v_i^{(t+1)} \approx v_i^{(t)} + \eta_G \frac{\sum_j \langle w_j^{(t)}, v_i^{(t)} \rangle^2 w_j^{(t)}}{\| \sum_j \langle w_j^{(t)}, v_i^{(t)} \rangle^2 w_j^{(t)} \|_2} \quad (10)$$

No matter how large $\langle w_i^{(t)}, X \rangle$ is, G still learns at the same speed with D. There is a tight window (iteration 25, Fig. 3b) where only one neuron of D is aligned with u_1. This is when G can also learn to generate u_1 by "catching up" to D at that point, which avoids mode collapse.

4 NUMERICAL PERFORMANCE OF NSGDA

In Section 2, we present the Ada-nSGDA algorithm (2) which corresponds to "grafting" the Adam magnitude onto the SGDA direction. In Section 3, we construct a dataset and GAN model where we prove that a GAN trained with nSGDA can generate examples from the true training distribution, while a GAN trained with SGDA fails due to mode collapse. We now provide more experiments comparing nSGDA and Ada-nSGDA with Adam on real GANs and datasets.

We train a ResNet WGAN with gradient penalty on CIFAR-10 (Krizhevsky et al., 2009) and STL-10 (Coates et al., 2011) with Adam, Ada-nSDGA, SGDA, as well as nSGDA with a fixed learning rate as done in Section 3. We use the default architectures and training parameters specified in Gulrajani et al. (2017) ($\lambda_{GP} = 10$, $n_{dis} = 5$, learning rate decayed linearly to 0 over 100k steps). We also train a StyleGAN2 model (Karras et al., 2020) on FFHQ (Karras et al., 2019) and LSUN Churches (Yu et al., 2016) (both resized to 128×128 pixels) with Adam, Ada-nSGDA, and SGDA. We use the recommended StyleGAN2 hyperparameter configuration for this resolution (batch size = 32, $\gamma = 0.1024$, map depth = 2, channel multiplier = 16384). We use the Fréchet Inception distance (FID) (Heusel et al., 2017) to quantitatively assess the performance of the model. For each optimizer, we conduct a coarse log-space sweep over step sizes and optimize for FID. We train the WGAN-GP models for 2880 thousand images (kimgs) on CIFAR-10 and STL-10 (45k steps with a batch size of 64), and the StyleGAN2 models for 2600 kimgs on FFHQ and LSUN Churches. We average our results over 5 seeds for the WGAN-GP ResNets, and over 3 seeds for the StyleGAN2 models due to the computational cost associated with training GANs.

WGAN-GP Figures 4a and 4b show the FID curves during training for the WGAN-GP model. We test Adam, Ada-nSGDA, AdaDir (that contains the adaptive direction), nSGDA and SGDA. The first remark is that Ada-nSGDA recovers the performance of Adam while AdaDir diverges (NaN loss) for these experiments and is hence omitted. This means that the adaptive magnitude is key to the performance of adaptive methods. Additionally, nSGDA not only recovers the performance of Adam but obtains a final FID of $\sim$2-3 points lower than Ada-nSGDA. Such performance is possible because the adaptive magnitude $\|A_{\mathcal{Y}}^{(t)}\|_2$ stays within a constant range and does not fluctuate much (Figs. 2b, 2c) and a constant learning rate as in nSGDA is enough to recover Adam's performance. Thus, nSGDA is a valid model for Adam in the case of WGAN-GP. In contrast, models trained with SGDA consistently perform significantly worse, with final FID scores $4\times$ larger than Adam.

StyleGAN2 Figures 4c and 4d show the FID curves during training for StyleGAN2. Similar to WGAN-GP, we observe that Ada-nSGDA recovers the Adam performance while SGDA performs much worse. However, nSGDA was not able to recover the performance of Adam in this setting. There are several hypotheses to explain this:

Figure 4: (a, b) are the final FID scores for a ResNet WGAN-GP model trained for 45k steps on CIFAR-10 and STL-10 respectively. (c, d) are the final FID scores for a StyleGAN2 model trained for 2600kimgs on FFHQ and LSUN Churches respectively. WGAN-GP results are obtained over 5 seeds, and StyleGAN2 results over 3 seeds.

Figure 5: (a) shows the FID curve for the StyleGAN2 model trained for 2600 kimgs on FFHQ. (b, c) shows the fluctuations of the Ada-nSGDA adaptive magnitude. Like Fig. 2, we plot the ratio $\|\mathbf{A}_{\mathcal{Y}}^{(t)}\|_2 / \|\mathbf{A}_{\mathcal{Y}}^{(0)}\|_2$ for each of the discriminator's (b) and generator's (c) layers. This ratio stays in a stable range but fluctuates a lot.

- We observe in Figs. 5b, 5c that the adaptive magnitude the ratio $\|\mathbf{A}_{\mathcal{Y}}^{(t)}\|_2$ stays within a constant range but varies significantly across time. This violates our theoretical setting of assuming a constant adaptive magnitude. In contrast, $\|\mathbf{A}_{\mathcal{Y}}^{(t)}\|_2$ stays within a constant range and does not fluctuate across time in the WGAN-GP experiment (Figs. 2b, 2c).
- The GAN problem formulation in the case of StyleGAN2 is very different from the one in WGAN-GP. Specifically, StyleGAN2 has a drastically different generator architecture than the ResNet generator used in the WGAN-GP experiments (utilizing weight demodulation), as well as using adaptive data augmentation and additional regularizers (such as a path-length regularization).

Because our theoretical setting does not capture these observations, we do not expect nSGDA to work in this setting. However in spite of these differences, Ada-nSGDA performed similarly to Adam indicating that the nSGDA direction that we theoretically study is still valid in modern real-world GAN architectures. We further validate our theory with additional experiments on DCGAN (Radford et al., 2015) which more closely matches our theoretical setting in Appendix A, and find that nSGDA recovers the performance of Adam as in WGAN-GP.

5   CONCLUSION

Our work addresses the question of how adaptive methods improve the GAN performance. We empirically showed that the adaptive magnitude of Adam is responsible for the high performance of adaptive methods in GANs. We further show that the adaptive magnitude is almost constant in some settings (for instance in the case of WGAN-GP), and nSGDA is able to recover the learning dynamics of Adam. We constructed a setting where we proved that nSGDA –thanks to its balanced updates– recovers the modes of the true distribution while SGDA fails to do it. Our theory provides insights on the effectiveness of adaptive methods in architectures such as DCGAN or WGAN-GP, however the limitation of our work is that we do not fully capture all of the components in modern architectures such as StyleGAN2. An exciting direction would be to find an optimization model that recovers the same perform for Adam on these modern GAN architectures.

REFERENCES

Naman Agarwal, Rohan Anil, Elad Hazan, Tomer Koren, and Cyril Zhang. Disentangling adaptive gradient methods from learning rates. *arXiv preprint arXiv:2002.11803*, 2020.

Zeyuan Allen-Zhu and Yuanzhi Li. Towards understanding ensemble, knowledge distillation and self-distillation in deep learning. *CoRR*, abs/2012.09816, 2020. URL https://arxiv.org/abs/2012.09816.

Zeyuan Allen-Zhu and Yuanzhi Li. Forward super-resolution: How can gans learn hierarchical generative models for real-world distributions. *arXiv preprint arXiv:2106.02619*, 2021.

Kimon Antonakopoulos, Veronica Belmega, and Panayotis Mertikopoulos. An adaptive mirror-prox method for variational inequalities with singular operators. *Advances in Neural Information Processing Systems*, 32:8455–8465, 2019.

Kimon Antonakopoulos, E Veronica Belmega, and Panayotis Mertikopoulos. Adaptive extra-gradient methods for min-max optimization and games. *arXiv preprint arXiv:2010.12100*, 2020.

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein generative adversarial networks. In *International conference on machine learning*, pp. 214–223. PMLR, 2017.

Sanjeev Arora, Rong Ge, Yingyu Liang, Tengyu Ma, and Yi Zhang. Generalization and equilibrium in generative adversarial nets (gans). In *International Conference on Machine Learning*, pp. 224–232. PMLR, 2017.

Sanjeev Arora, Andrej Risteski, and Yi Zhang. Do gans learn the distribution? some theory and empirics. In *International Conference on Learning Representations*, 2018.

Francis Bach and Kfir Y Levy. A universal algorithm for variational inequalities adaptive to smoothness and noise. In *Conference on Learning Theory*, pp. 164–194. PMLR, 2019.

Yu Bai, Tengyu Ma, and Andrej Risteski. Approximability of discriminators implies diversity in gans. *arXiv preprint arXiv:1806.10586*, 2018.

Yogesh Balaji, Mohammadmahdi Sajedi, Neha Mukund Kalibhat, Mucong Ding, Dominik Stöger, Mahdi Soltanolkotabi, and Soheil Feizi. Understanding overparameterization in generative adversarial networks. *arXiv preprint arXiv:2104.05605*, 2021.

Babak Barazandeh, Davoud Ataee Tarzanagh, and George Michailidis. Solving a class of non-convex min-max games using adaptive momentum methods. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 3625–3629. IEEE, 2021.

Andrew Brock, Jeff Donahue, and Karen Simonyan. Large scale gan training for high fidelity natural image synthesis. *arXiv preprint arXiv:1809.11096*, 2018.

Dami Choi, Christopher J Shallue, Zachary Nado, Jaehoon Lee, Chris J Maddison, and George E Dahl. On empirical comparisons of optimizers for deep learning. *arXiv preprint arXiv:1910.05446*, 2019.

Adam Coates, Andrew Ng, and Honglak Lee. An analysis of single-layer networks in unsupervised feature learning. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pp. 215–223. JMLR Workshop and Conference Proceedings, 2011.

Jorge Cortés. Finite-time convergent gradient flows with applications to network consensus. *Automatica*, 42(11):1993–2000, 2006.

Ashok Cutkosky and Harsh Mehta. Momentum improves normalized sgd. In *International Conference on Machine Learning*, pp. 2260–2268. PMLR, 2020.

Constantinos Daskalakis, Andrew Ilyas, Vasilis Syrgkanis, and Haoyang Zeng. Training gans with optimism. *arXiv preprint arXiv:1711.00141*, 2017.

Vincent Dumoulin, Ishmael Belghazi, Ben Poole, Olivier Mastropietro, Alex Lamb, Martin Arjovsky, and Aaron Courville. Adversarially learned inference. *arXiv preprint arXiv:1606.00704*, 2016.

Soheil Feizi, Farzan Farnia, Tony Ginart, and David Tse. Understanding gans: the lqg setting. *arXiv preprint arXiv:1710.10793*, 2017.

Tanner Fiez and Lillian Ratliff. Gradient descent-ascent provably converges to strict local minmax equilibria with a finite timescale separation. *arXiv preprint arXiv:2009.14820*, 2020.

AV Gasnikov, PE Dvurechensky, FS Stonyakin, and AA Titov. An adaptive proximal method for variational inequalities. *Computational Mathematics and Mathematical Physics*, 59(5):836–841, 2019.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. *Advances in neural information processing systems*, 27, 2014.

Eduard Gorbunov, Marina Danilova, David Dobre, Pavel Dvurechensky, Alexander Gasnikov, and Gauthier Gidel. Clipped stochastic methods for variational inequalities with heavy-tailed noise. *arXiv preprint arXiv:2206.01095*, 2022.

Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron Courville. Improved training of wasserstein gans. *arXiv preprint arXiv:1704.00028*, 2017.

Elad Hazan, Kfir Y Levy, and Shai Shalev-Shwartz. Beyond convexity: Stochastic quasi-convex optimization. *arXiv preprint arXiv:1507.02030*, 2015.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. *Advances in neural information processing systems*, 30, 2017.

Chi Jin, Praneeth Netrapalli, and Michael Jordan. What is local optimality in nonconvex-nonconcave minimax optimization? In *International Conference on Machine Learning*, pp. 4880–4889. PMLR, 2020.

Tero Karras, Samuli Laine, and Timo Aila. A style-based generator architecture for generative adversarial networks. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 4401–4410, 2019.

Tero Karras, Samuli Laine, Miika Aittala, Janne Hellsten, Jaakko Lehtinen, and Timo Aila. Analyzing and improving the image quality of stylegan. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 8110–8119, 2020.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Qi Lei, Jason Lee, Alex Dimakis, and Constantinos Daskalakis. Sgd learns one-layer networks in wgans. In *International Conference on Machine Learning*, pp. 5799–5808. PMLR, 2020.

Kfir Y Levy. The power of normalization: Faster evasion of saddle points. *arXiv preprint arXiv:1611.04831*, 2016.

Yuanzhi Li and Zehao Dou. Making method of moments great again?–how can gans learn distributions. *arXiv preprint arXiv:2003.04033*, 2020.

Tengyuan Liang. How well can generative adversarial networks learn densities: A nonparametric view. *arXiv preprint arXiv:1712.08244*, 2017.

Mingrui Liu, Youssef Mroueh, Jerret Ross, Wei Zhang, Xiaodong Cui, Payel Das, and Tianbao Yang. Towards better understanding of adaptive gradient algorithms in generative adversarial nets. *arXiv preprint arXiv:1912.11940*, 2019.

Lars Mescheder, Andreas Geiger, and Sebastian Nowozin. Which training methods for gans do actually converge? In *International conference on machine learning*, pp. 3481–3490. PMLR, 2018.

Y.E. Nesterov. Minimization methods for nonsmooth convex and quasiconvex functions. *Econ. Mat. Met.*, 20:519–531, 01 1984.

Antonio Orvieto, Jonas Kohler, Dario Pavllo, Thomas Hofmann, and Aurelien Lucchi. Vanishing curvature and the power of adaptive methods in randomly initialized deep networks, 2021.

Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. *arXiv preprint arXiv:1511.06434*, 2015.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Fisher Yu, Ari Seff, Yinda Zhang, Shuran Song, Thomas Funkhouser, and Jianxiong Xiao. Lsun: Construction of a large-scale image dataset using deep learning with humans in the loop, 2016.

Jure Zbontar, Florian Knoll, Anuroop Sriram, Tullie Murrell, Zhengnan Huang, Matthew J Muckley, Aaron Defazio, Ruben Stern, Patricia Johnson, Mary Bruno, et al. fastmri: An open dataset and benchmarks for accelerated mri. *arXiv preprint arXiv:1811.08839*, 2018.

Jingzhao Zhang, Sai Praneeth Karimireddy, Andreas Veit, Seungyeon Kim, Sashank J Reddi, Sanjiv Kumar, and Suvrit Sra. Why are adaptive methods good for attention models? *arXiv preprint arXiv:1912.03194*, 2019.

Pengchuan Zhang, Qiang Liu, Dengyong Zhou, Tao Xu, and Xiaodong He. On the discrimination-generalization tradeoff in gans. *arXiv preprint arXiv:1711.02771*, 2017.

Dongruo Zhou, Jinghui Chen, Yuan Cao, Yiqi Tang, Ziyan Yang, and Quanquan Gu. On the convergence of adaptive gradient methods for nonconvex optimization. *arXiv preprint arXiv:1808.05671*, 2018.