Graph Neural Networks with Adaptive Residual

Abstract

Graph neural networks (GNNs) have shown the power in graph representation learning for numerous tasks. In this work, we discover an interesting phenomenon that although residual connections in the message passing of GNNs help boost the performance, they immensely amplify GNNs' vulnerability against abnormal node features. This is undesirable because in real-world applications, node features in graphs could often be abnormal such as being naturally noisy or adversarially manipulated. We analyze possible reasons to understand this phenomenon, and aim to design GNNs with stronger resilience to abnormal features. Our understandings motivate us to propose and derive a simple, efficient, principled, and interpretable message passing scheme, leading to a novel GNN with Adaptive residual, AirGNN. Extensive experiments under various abnormal feature scenarios demonstrate the effectiveness of the proposed algorithm.

1 Introduction

Recent years have witnessed the great success of graph neural networks (GNNs) in representation learning for graph structure data. Essentially, GNNs generalize deep neural networks (DNNs) from regular grids, such as image, video and text, to irregular data such as social, energy, transportation, citation, and biological networks. Such data can be naturally represented as graphs with nodes and edges. The key building block for such generalization is the neural message passing framework [1]:

$$\mathbf{x}_u^{(k+1)} = \text{UPDATE}^{(k)}\big(\mathbf{x}_u^{(k)}, \mathbf{m}_{\mathcal{N}(u)}^{(k)}\big) \tag{1}$$

where $\mathbf{x}_u^{(k)} \in \mathbb{R}^d$ denotes the feature vector of node u in the k-th iteration of message passing, and $\mathbf{m}_{\mathcal{N}(u)}^{(k)}$ is the message aggregated from u's neighborhood $\mathcal{N}(u)$. The specific design of message passing scheme can be motivated from spectral domain [2, 3] or spatial domain [4, 5, 6, 1]. It usually linearly smooths the features in a local neighborhood on the graph.

GNNs have achieved superior performance in a large number of benchmark datasets [7] where the node features are assumed to be complete and informative. However, in real-world applications, some node features could be abnormal from various aspects. For instance, in social networks, new users might not have complete profile before they make connections with others, leading to missing user features. In transportation networks, node features can be noisy since there exist certain uncertainty and dynamics in the observation of the traffic information. What is worse, node features can be adversarially chosen by the attacker to maliciously manipulate the prediction made by GNNs. Therefore, it is greatly desired to design GNN models with stronger resilience to abnormal node features.

In this work, we first perform empirical investigations on how representative GNN models behave on graphs with abnormal features. Specifically, based upon standard benchmark datasets, we simulate the abnormal features by replacing the features of randomly selected nodes with random Gaussian

noise. Then the performance of node classification on abnormal features and normal features are examined separately. From our preliminary study in Section 2, we reveal two interesting observations: (1) Feature aggregation can boost the resilience to abnormal features, but too many aggregations could hurt the performance on both normal and abnormal features; and (2) Residual connection helps GNNs benefit from more layers for normal features, while making GNNs more fragile to abnormal features. We then provide possible explanations to understand these observed phenomena from the perspective of graph Laplacian smoothing. Our analyses imply that there might exist an intrinsic tension between feature aggregation and residual connection, which results in a performance tradeoff between normal features and abnormal features.

Motivated by these findings and understandings, we aim to design new GNNs with stronger resilience to abnormal features while largely maintaining the performance on normal features. Our contributions can be summarized as follows:

- We discover an intrinsic tension between feature aggregation and residual connection in GNNs, and the corresponding performance tradeoff between abnormal and normal features. We also analyze possible reasons to explain and understand these findings.
- We propose a simple, efficient, principled, and interpretable message passing scheme, which leads to a novel GNN model with adaptive residual, named as AirGNN.
- Extensive experiments under various abnormal feature scenarios demonstrate the superiority of the proposed algorithm.

2 Preliminary

Before introducing the preliminary study, we first define the notations used throughout the paper.

Notations. We use bold upper-case letters such as $\mathbf{X}$ to denote matrices. Given a matrix $\mathbf{X} \in \mathbb{R}^{n \times d}$, we use $\mathbf{X}_i$ to denote its i-th row and $\mathbf{X}_{ij}$ to denote its element in i-th row and j-th column. The Frobenius norm and ℓ_{21} norm of a matrix $\mathbf{X}$ are defined as $\|\mathbf{X}\|_F = \sqrt{\sum_{ij} \mathbf{X}_{ij}^2}$ and $\|\mathbf{X}\|_{21} = \sum_i \|\mathbf{X}_i\|_2 = \sum_i \sqrt{\sum_j \mathbf{X}_{ij}^2}$, respectively. We define $\|\mathbf{X}\|_2 = \sigma_{\max}(\mathbf{X})$ where $\sigma_{\max}(\mathbf{X})$ is the largest singular value of $\mathbf{X}$.

Let $\mathcal{G} = \{\mathcal{V}, \mathcal{E}\}$ be a graph with the node set $\mathcal{V} = \{v_1, \ldots, v_n\}$ and the undirected edge set $\mathcal{E} = \{e_1, \ldots, e_m\}$. We use $\mathcal{N}(v_i)$ to denote the neighboring nodes of node v_i, including v_i itself. Suppose that each node is associated with a d-dimensional feature vector, and the features for all nodes are denoted as $\mathbf{X}_{\text{fea}} \in \mathbb{R}^{n \times d}$. The graph structure $\mathcal{G}$ can be represented as an adjacent matrix $\mathbf{A} \in \mathbb{R}^{n \times n}$, where $\mathbf{A}_{ij} = 1$ when there exists an edge between nodes v_i and v_j, and $\mathbf{A}_{ij} = 0$ otherwise. The graph Laplacian matrix is defined as $\mathbf{L} = \mathbf{D} - \mathbf{A}$, where $\mathbf{D}$ is the diagonal degree matrix. Let us denote the commonly used feature aggregation matrix in GNNs [2] as $\tilde{\mathbf{A}} = \hat{\mathbf{D}}^{-\frac{1}{2}} \hat{\mathbf{A}} \hat{\mathbf{D}}^{-\frac{1}{2}}$ where $\hat{\mathbf{A}} = \mathbf{A} + \mathbf{I}$ is the adjacent matrix with self-loop and its degree matrix is $\hat{\mathbf{D}}$. The corresponding Laplacian matrix is defined as $\tilde{\mathbf{L}} = \mathbf{I} - \tilde{\mathbf{A}}$.

In this work, we focus on the setting where a subset of nodes in the graph contain abnormal features, while the remaining nodes have normal features. In the remaining of this paper, we use *abnormal/normal features* to denote *nodes with abnormal/normal features*, for simplicity.

2.1 Preliminary Study

Experimental setup. To investigate how GNNs behave on abnormal and normal node features, we design semi-supervised node classification experiments on three common datasets (i.e., Cora, CiteSeer and PubMed), following the data splits in the work [2]. Moreover, we simulate the abnormal features by assigning 10% of the nodes with random features sampled from a standard Gaussian distribution. The experiments are performed on representative GNN models covering coupled and decoupled architectures, including GCN [2], GCNII [8], APPNP [9], and their variants with or without residual connections, denoted as w/Res and wo/Res. All methods follow the hyperparameter settings in their original papers. We examine how these models perform when the number of layers increases. Note that for the decoupled architectures such as APPNP, we fix the 2-layer MLP and increase the number of propagation layers. While for the coupled architectures such as GCN and

84 GCNII, we increase the number of feature transformation and propagation layers simultaneously. The
85 node classification accuracy on abnormal and normal features is illustrated in Figure 1 and Figure. 2,
86 separately.

(a) APPNP   (b) GCNII   (c) GCN

Figure 1: Node classification accuracy on abnormal features (Cora)

(a) APPNP   (b) GCNII   (c) GCN

Figure 2: Node classification accuracy on normal features (Cora)

87 **Observations.** From Figure 1 and Figure 2, we can make the following observations: (1) Without
88 residual connection, more layers (e.g., > 2 for GCN and GCNII, > 10 for APPNP) hurt the accuracy
89 on normal features. However, more layers boost the accuracy on abnormal features significantly,
90 before finally starting to decrease; (2) With residual connection, the accuracy on normal features keeps
91 increasing with more layers[1]. However, the accuracy on abnormal features only increases marginally
92 when stacking more layers, and then starts to decrease. While we only present the experiments on
93 Cora, we defer the results on other datasets to Appendix C, which provide similar observations. To
94 conclude, we can summarize these observations into two major findings:

95 • *Finding I:* Feature aggregation can boost the resilience to abnormal features, but too many
96   aggregations could hurt the performance on both normal and abnormal features;

97 • *Finding II:* Residual connection helps GNNs benefit from more layers for normal features,
98   while making GNNs more fragile to abnormal features.

99 ## 2.2 Understandings

100 In this subsection, we provide the understanding and explanation for aforementioned findings, from
101 the perspective of graph Laplacian smoothing.

102 **Understanding Finding I: Feature aggregation as Laplacian smoothing**

103 The message passing in GCN [2], GCNII wo/ residual and APPNP wo/ residual (as well as many
104 popular GNN models), follows the feature aggregation

$$\mathbf{X}_{\text{out}} = \tilde{\mathbf{A}}\mathbf{X}_{\text{in}}, \tag{2}$$

105 where $\mathbf{X}_{\text{in}}$ and $\mathbf{X}_{\text{out}}$ represent the features before and after message passing layer, respectively. It can
106 be interpreted as one gradient descent step for the Laplacian smoothing problem

$$\underset{\mathbf{X}\in\mathbb{R}^{n\times d}}{\arg\min}\ \mathcal{L}_1(\mathbf{X}) \coloneqq \frac{1}{2}\text{tr}\Big(\mathbf{X}^\top(\mathbf{I}-\tilde{\mathbf{A}})\mathbf{X}\Big) = \frac{1}{2}\sum_{(v_i,v_j)\in\mathcal{E}} \|\frac{\mathbf{X}_i}{\sqrt{d_i+1}} - \frac{\mathbf{X}_j}{\sqrt{d_j+1}}\|_2^2, \tag{3}$$

---

[1]GCN w/Res is an exception because its residual is not appropriate, which is consistent with the experiments
in the work [2].

where d_i is the node degree of node v_i. Eq. (2) can be derived from $\mathbf{X}_{\text{out}} = \mathbf{X}_{\text{in}} - (\mathbf{I} - \tilde{\mathbf{A}})\mathbf{X}_{\text{in}} = \tilde{\mathbf{A}}\mathbf{X}_{\text{in}}$, with the initialization $\mathbf{X} = \mathbf{X}_{\text{in}}$ and stepsize $\gamma = 1$. The Laplacian smoothing problem penalizes the feature difference between neighboring nodes. To reduce this penalty, the feature aggregation in Eq. (2) smooths the node features by taking the average of local neighbors, and thus can be considered as low-pass filter which gradually filters out high-frequency signals [10, 11]. Therefore, it increases the resilience to abnormal features which are likely to be high-frequency signals. In other words, the local neighboring nodes help to correct the abnormal features. Unfortunately, if applied too many times, these low-pass filters could overly smooth the features (well-known as oversmoothing [12, 13]) such that nodes are not distinguishable enough, providing an explanation to the degraded performance on both abnormal and normal features when stacking too many layers.

Understanding Finding II: Residual connection maintains feature proximity

To adjust the feature smoothness for better performance, APPNP [9] utilizes residual connections in message passing as follows

$$\mathbf{X}^{k+1} = (1 - \alpha)\tilde{\mathbf{A}}\mathbf{X}^k + \alpha\mathbf{X}_{\text{in}}, \tag{4}$$

where $\mathbf{X}^0 = \mathbf{X}_{\text{in}}$. It can be considered as an iterative solution for the regularized Laplacian smoothing problem

$$\underset{\mathbf{X} \in \mathbb{R}^{n \times d}}{\arg\min} \ \mathcal{L}_2(\mathbf{X}) \coloneqq \frac{\alpha}{2(1-\alpha)}\|\mathbf{X} - \mathbf{X}_{\text{in}}\|_F^2 + \frac{1}{2}\text{tr}\Big(\mathbf{X}^\top(\mathbf{I} - \tilde{\mathbf{A}})\mathbf{X}\Big), \tag{5}$$

with initialization $\mathbf{X} = \mathbf{X}_{\text{in}}$ and stepsize $\gamma = 1 - \alpha$ due to

$$\mathbf{X}^{k+1} = \mathbf{X}^k - (1-\alpha)\Big(\frac{\alpha}{1-\alpha}(\mathbf{X}^k - \mathbf{X}_{\text{in}}) + (\mathbf{I} - \tilde{\mathbf{A}})\mathbf{X}^k\Big) = (1-\alpha)\tilde{\mathbf{A}}\mathbf{X}^k + \alpha\mathbf{X}_{\text{in}}.$$

GCNII [8] adopts a similar message passing but further combines a feature transformation layer in each message passing step, which leads to a coupled architecture, as contrast to the decoupled architecture of APPNP. The residual connection naturally arises when regularizing the proximity between input and output features, as showed in the first term of $\mathcal{L}_2(\mathbf{X})$. Such proximity can help avoid the trivial solution for the problem in Eq. (3), i.e., totally oversmoothed features only depending on node degrees, and consequently mitigates the oversmoothing issue. More intuitively, residual connections in GNNs provide direct information flows between layers that can preserve some necessary high-frequency signals for better discrimination between classes. More layers with residual provide a more accurate solution to Eq. (5), which explains the performance gain from deeper GNNs. Unfortunately, these residual connections also undesirably carry on abnormal features which are detrimental, leading to the inferior performance on abnormal features.

3 The Proposed Framework

In this section, we first motivate the proposed adaptive message passing scheme (AMP) with further discussions on our preliminary study. We then introduce more details about AMP, its interpretations, convergence guarantee and computation complexity, as well as the model architecture of AirGNN.

3.1 Design Motivation

Our preliminary study in Section 2 reveals an intrinsic tension between feature aggregation and residual connection: (1) feature aggregation helps smooth out abnormal features, while it could cause inappropriate smoothing for normal features; (2) residual connection is essential for adjusting the feature smoothness, but it could be detrimental for abnormal features. Although this conflict can be partially mitigated by adjusting the residual connection such as the residual weight α in GCNII [8] and APPNP [9], such global adjustment cannot be adaptive to a subset of the nodes, e.g., the nodes with abnormal features. This is crucial because in practice we often encounter the scenario where only a subset of nodes contain abnormal features. Therefore, how to reconcile this dilemma still desires dedicated efforts. We then naturally ask a question: *Can we design a better message passing scheme with node-wise adaptive feature aggregation and residual connection?*

The motivation of the proposed idea builds upon the following intuition: while it is important to maintain the proximity between input and output features as in Eq. (5), it could be over aggressive to

penalize their deviations by the Frobenius norm, i.e., $\|\mathbf{X} - \mathbf{X}_{\text{in}}\|_F^2 = \sum_{i=1}^n \|\mathbf{X}_i - (\mathbf{X}_{\text{in}})_i\|_2^2$. The fact that this penalty does not tolerate large deviations weakens the capability to remove abnormal features through Laplacian smoothing. This motivates us to consider an alternative proximity penalty

$$\|\mathbf{X} - \mathbf{X}_{\text{in}}\|_{21} := \sum_{i=1}^n \|\mathbf{X}_i - (\mathbf{X}_{\text{in}})_i\|_2, \tag{6}$$

which instead penalizes the deviations by the ℓ_1 norm of row-wise ℓ_2 norms, namely ℓ_{21} norm. The ℓ_{21} norm promotes row sparsity in $\mathbf{X} - \mathbf{X}_{\text{in}}$, and it also allows large deviations because the penalty on large values is less aggressive, leading to the potential removal of abnormal features. Therefore, we propose the following Laplacian smoothing problem regularized by ℓ_{21} norm proximity control:

$$\underset{\mathbf{X} \in \mathbb{R}^{n \times d}}{\arg\min} \ \mathcal{L}(\mathbf{X}) := \lambda\|\mathbf{X} - \mathbf{X}_{\text{in}}\|_{21} + \frac{1}{2}\text{tr}(\mathbf{X}^\top(\mathbf{I} - \tilde{\mathbf{A}})\mathbf{X}), \tag{7}$$

where λ is a parameter to adjust the balance between proximity and Laplacian smoothing.

3.2 Adaptive Message Passing

Figure 3: Diagram of Adaptive Message Passing

$\mathcal{L}(\mathbf{X})$ is a composite objective with non-smooth and smooth components. To optimize it by proximal gradient descent [14], we obtain the following iterations as the adaptive message passing scheme:

$$\mathbf{Y}^k = \mathbf{X}^k - \gamma(\mathbf{I} - \tilde{\mathbf{A}})\mathbf{X}^k = (1 - \gamma)\mathbf{X}^k + \gamma\tilde{\mathbf{A}}\mathbf{X}^k \tag{8}$$

$$\mathbf{X}^{k+1} = \underset{\mathbf{X}}{\arg\min} \left\{ \lambda\|\mathbf{X} - \mathbf{X}_{\text{in}}\|_{21} + \frac{1}{2\gamma}\|\mathbf{X} - \mathbf{Y}^k\|_F^2 \right\} \tag{9}$$

where $\mathbf{X}^0 = \mathbf{X}_{\text{in}}$ and γ is the stepsize to be specified later. Let $\mathbf{Z} = \mathbf{X} - \mathbf{X}_{\text{in}}$, and Eq. (9) can be rewritten as:

$$\mathbf{Z}^{k+1} = \underset{\mathbf{Z}}{\arg\min} \left\{ \lambda\|\mathbf{Z}\|_{21} + \frac{1}{2\gamma}\|\mathbf{Z} - (\mathbf{Y}^k - \mathbf{X}_{\text{in}})\|_F^2 \right\}$$

$$= \mathbf{prox}_{\gamma\lambda\|\cdot\|_{21}}(\mathbf{Y}^k - \mathbf{X}_{\text{in}}) \tag{10}$$

$$\mathbf{X}^{k+1} = \mathbf{X}_{\text{in}} + \mathbf{Z}^{k+1}. \tag{11}$$

The i-th row of the proximal operator in Eq. (10) can be computed analytically

$$\left(\mathbf{prox}_{\gamma\lambda\|\cdot\|_{21}}(\mathbf{X})\right)_i = \frac{\mathbf{X}_i}{\|\mathbf{X}_i\|_2}\max(\|\mathbf{X}_i\|_2 - \gamma\lambda, 0) = \max(1 - \frac{\gamma\lambda}{\|\mathbf{X}_i\|_2}, 0) \cdot \mathbf{X}_i. \tag{12}$$

Note that the proximal operator returns $\mathbf{0}$ if the input vector is $\mathbf{0}$. Substituting $\mathbf{X}$ in Eq. (12) with $\mathbf{Y}^k - \mathbf{X}_{\text{in}}$ and combining Eq. (10) and Eq. (11), then Eq. (11) becomes

$$\mathbf{X}_i^{k+1} = (\mathbf{X}_{\text{in}})_i + \beta_i(\mathbf{Y}_i^k - (\mathbf{X}_{\text{in}})_i) = (1 - \beta_i)(\mathbf{X}_{\text{in}})_i + \beta_i\mathbf{Y}_i^k, \quad \forall i \in [n], \tag{13}$$

where $\beta_i := \max(1 - \frac{\gamma\lambda}{\|\mathbf{Y}_i^k - (\mathbf{X}_{\text{in}})_i\|_2}, 0)$. To summarize, the proposed adaptive message passing (AMP) scheme is showed in Figure 4, and a diagram is showed in Figure 3. In detail, AMP works as follows:

- The first step takes a *feature aggregation* within the local neighbors with a self-loop weighted by $1 - \gamma$;
- The second step computes a weight $\beta_i \in [0, 1]$ for each node v_i depending on the local deviation $\|\mathbf{Y}_i^k - (\mathbf{X}_{\text{in}})_i\|_2$.

$$\begin{cases} \mathbf{Y}^k = (1-\gamma)\mathbf{X}^k + \gamma\tilde{\mathbf{A}}\mathbf{X}^k \\ \beta_i = \max(1 - \dfrac{\gamma\lambda}{\|\mathbf{Y}_i^k - (\mathbf{X}_{\text{in}})_i\|_2}, 0) \quad \forall i \in [n] \\ \mathbf{X}_i^{k+1} = (1-\beta_i)(\mathbf{X}_{\text{in}})_i + \beta_i\mathbf{Y}_i^k \qquad \forall i \in [n] \end{cases}$$

Figure 4: Adaptive Message Passing (AMP).

- The final step takes a *linear combination* of input features $\mathbf{X}_{\text{in}}$ and the aggregated features $\mathbf{Y}^k$, where the node-wise residual is adaptively weighted by $1 - \beta_i$ for each node v_i.

The convergence guarantee of AMP and parameter setting for the stepsize γ are illustrated in Theorem 1, proved in Appendix A. We discuss the computation complexity of AMP in Remark 1.

Theorem 1 (Convergence of AMP). *Under the stepsize setting $\gamma < \frac{2}{\|\tilde{\mathbf{L}}\|_2}$, the adaptive message passing scheme (AMP) in Figure 4 converges to the optimal solution of the problem in Eq. (7). In practice, it is sufficient to choose any $\gamma < 1$ since $\|\tilde{\mathbf{L}}\|_2 \leq 2$.*

Remark 1 (Computation complexity). *AMP is as efficient as simple feature aggregation $\mathbf{X}_{out} = \tilde{\mathbf{A}}\mathbf{X}_{in}$ because the additional computation cost from the second and third steps in Figure 4 is in the order $\mathcal{O}(nd)$, where n is the number of nodes and d is the feature dimension. This is negligible compared with the computation cost $\mathcal{O}(md)$ in feature aggregation, where m is the number of edges, due to the fact that usually there are many more edges than nodes in real-world graphs, i.e., $m \gg n$.*

3.3 Interpretation of AMP

Interestingly, the proposed AMP has a simple and intuitive interpretation as adaptive residual connection, which aligns well with our design motivation:

- If the feature of node v_i, i.e., $(\mathbf{X}_{\text{in}})_i$, is significantly inconsistent with its local neighbors, i.e., the aggregated feature $\mathbf{Y}_i^k$, then the local deviation $\|\mathbf{Y}_i^k - (\mathbf{X}_{\text{in}})_i\|_2$ will be large, which leads to a β_i close to 1. Therefore, the final step will assign a small weight to the residual, i.e., $(1 - \beta_i)(\mathbf{X}_{\text{in}})_i$, and the aggregated feature $\mathbf{Y}_i^k$ will dominate.

- On the contrary, if $(\mathbf{X}_{\text{in}})_i$ is already consistent with its local neighbors, $\|\mathbf{Y}_i^k - (\mathbf{X}_{\text{in}})_i\|_2$ will be small, which leads to a β_i close to 0. Thus, the residual will dominate, which is reasonable since there is less need to aggregate features in this case.

- To summarize, the local deviation $\|\mathbf{Y}_i^k - (\mathbf{X}_{\text{in}})_i\|_2$ provides a natural transition from $\beta_i \to 1$ to $\beta_i \to 0$, and the transition can be modulated by λ which can be either learned or tuned as a hyperparameter through cross-validation. This transition provides an node-wise adaptive residual connection for the message passing scheme.

Adaptivity for abnormal & normal features. According to the homophily assumption on graph structure data [15, 16, 17, 2], the feature representations of normal features should be more consistent with local neighbors than abnormal features. As a result, AMP will assign more residual (i.e., smaller β) to normal features but less residual (i.e., larger β) to abnormal features, providing a customized tradeoff between feature aggregation and residual connection. Consequently, it can promote both the resilience to abnormal features and the performance on normal features. Above discussion also implies a clear physical meaning for β in AMP, and we formally define it as the adaptive score.

Definition 1 (Adaptive score). *The variables $\{\beta_1, \cdots, \beta_n\}$ in the adaptive message passing scheme (AMP) are defined as the adaptive scores for nodes $\{v_1, \cdots, v_n\}$ respectively in graph $\mathcal{G}$. In particular, the larger β_i is, the more likely the feature of node v_i is abnormal.*

Remark 2 (Nonlinear smoother). *Different from most existing message passing scheme which are linear smoothers, AMP is a nonlinear smoother because the weights $\{\beta_i\}$ are computed from $\mathbf{Y}^k$ and $\mathbf{X}_{in}$. This nonlinearity is the key to achieve adaptive residual connection for different nodes.*

3.4 The Model Architecture

We incorporate AMP into deep neural networks following the decoupled structure [9, 18], which leads to the proposed Adaptive residual GNN (AirGNN):

$$\mathbf{X}_{\text{in}} = h_\theta(\mathbf{X}_{\text{fea}}) \tag{14}$$

$$\mathbf{Y}_{\text{pre}} = \textbf{AMP}\,(\mathbf{X}_{\text{in}}, K, \lambda). \tag{15}$$

$h_\theta(\cdot)$ is any machine learning model parameterized by learnable parameters θ, such as multilayer perceptrons (MLPs). $\mathbf{X}_{\text{fea}} \in \mathbb{R}^{n \times d}$ denotes the initial node features. AMP takes $h_\theta(\mathbf{X}_{\text{fea}})$ as input, and carrys out the message passing for K steps with hyperparameter λ. Note that AirGNN is very efficient as explained in Remark 1, and it only requires two hyperparameters K and λ without introducing additional parameters to learn, which could reduce the risk of overfitting.

4 Experiment

In this section, we aim to verify the effective of the proposed adaptive message passing scheme (AMP) and the AirGNN model through the semi-supervised node classification tasks. Specifically, we try to answer the following questions: (1) How does AirGNN perform on abnormal and normal features? (Section 4.2 and 4.3) and (2) How does AirGNN work by adjusting the adaptive residual? (Section 4.4)

4.1 Experimental Settings

Datasets and baselines. We conduct experiments on 8 real-world datasets including three citation graphs, i.e., Cora, Citeseer, Pubmed [19], two co-authorship graphs, i.e., Coauthor CS and Coauthor Physics [20], two co-purchase graphs, i.e., Amazon Computers and Amazon Photo [20], and one OGB dataset, i.e., ogbn-arxiv [21]. Due to the space limit, we only present the results on Cora, Citeseer, and Pubmed in this section, but defer the results on other datasets to Appendix D. More details about the data statistics and data splits are summarized in Appendix B. The proposed AirGNN is compared with representative GNNs, including GCN [2], GAT [5], APPNP [9] and GCNII [8].

Parameter settings. For all baselines, we follow the best hyperparameter settings in their original papers. Additionally, we tune a best residual weight α for APPNP and GCNII from the search space $\{0, 0.1, 0.2, 0.3, 0.4\}$. For AirGNN, we use a two-layer MLP as the base model $h_\theta(\cdot)$, following APPNP. We fix the learning rate 0.01, dropout 0.8, and weight decay 0.0005. Moreover, we set $\gamma = 0.5$ as suggested by Theorem 1. We choose $K = 10$ and tune λ from the search space $\{0, 0.1, 0.2, 0.3, 0.4\}$. Adam optimizer [22] is used in all experiments. All hyperparameters are tuned according to the performance on validation sets.

Evaluation setting. We assess the performance of all models under two types of abnormal feature scenarios, including noisy features and adversarial features. The abnormal features are injected to randomly selected test nodes after model training. We run all experiments by 10 times, and report the mean and variance in the figures.

4.2 Performance Comparison with Noisy Features

In this subsection, we consider the abnormal features in the noisy feature scenario. Specifically, we simulate the noisy features by assigning a subset of the nodes with random features sampled from a multivariate standard Gaussian distribution, similar to the settings in the preliminary study. We report the node classification test accuracy on abnormal (noisy) features and normal features in Figure 5 and Figure 6, separately, under varying noisy ratio. From these figures, we can observe:

- Figure 5 shows that AirGNN significantly outperforms all baselines on all datasets in terms of the performance on noisy features. This verifies that AMP is able to boost the resilience to noisy features, aligning well with the design motivation.
- Figure 6 shows that AirGNN promotes the performance on normal features when abnormal features exist. This is because AMP can remove some abnormal features which are detrimental to normal features.

Figure 5: Node classification accuracy on abnormal (noisy) features

Figure 6: Node classification accuracy on normal features

4.3 Performance Comparison with Adversarial Features

In this subsection, we consider the abnormal feature scenario when the node features are maliciously attacked by the attacker to manipulate the prediction of GNNs. We use the Nettack [23] implemented in DeepRobust [24], a PyTorch library for adversarial attacks and defenses, to generate the adversarial features. We randomly choose 40 test nodes as the targeted nodes, and assess the performance under increasing perturbation budgets $\{0, 5, 10, 20, 50, 80\}$, where the perturbation numbers denote the number of feature dimensions can be manipulated. The node classification accuracy on these attacked nodes are showed in Figure 7. From these figures, we can make the following observations:

- AirGNN is significantly more robust against adversarially attacked features than all baselines.

- The advantages of AirGNN over the baselines become much stronger with increasing perturbation budgets. This again suggests that AMP can boost the resilience to abnormal features.

Figure 7: Node classification accuracy on adversarial features

4.4 Adaptive Residual for Abnormal & Normal Nodes

To further understand and verify how AMP and AirGNN work, we investigate the adaptive score β_i for each node v_i. Specifically, the average adaptive scores for abnormal nodes and normal nodes in

the last layer of AMP are computed separately. In the noisy feature scenario, we fix ratio of noisy nodes as 10%. In the adversarial feature scenario, we choose 40 target nodes and fix the perturbation number as 80. The results in noisy and adversarial feature scenarios are showed in Table 1 and Table 2, respectively. From these tables, we can observe:

- On the one hand, it can be clearly observed that in both scenarios, the average adaptive scores for abnormal nodes are significantly higher than those for normal nodes. Therefore, it verifies our intuition that large adaptive scores are strongly related to abnormal features.

- On the other hand, it also implies that the residual weights (i.e., $1 - \beta_i$ for abnormal nodes) are much lower than those of normal nodes. This perfectly aligns with our expectation that we desire to get rid of residual connections for abnormal features.

To conclusion, the study on adaptive scores verifies that AMP and AirGNN work via adaptive residual as designed.

Table 1: Average adaptive score (β) and residual weight ($1 - \beta$) in the noisy feature scenario.

Measure	Cora	CiteSeer	PubMed
Average adaptive score for abnormal nodes	0.998 ± 0.000	0.988 ± 0.000	0.996 ± 0.000
Average adaptive score for normal nodes	0.924 ± 0.002	0.807 ± 0.005	0.869 ± 0.006
Average residual weight for abnormal nodes	0.002 ± 0.000	0.012 ± 0.000	0.004 ± 0.000
Average residual weight for normal nodes	0.076 ± 0.002	0.193 ± 0.005	0.131 ± 0.006

Table 2: Average adaptive score (β) and residual weight ($1 - \beta$) in the adversarial feature scenario.

Measure	Cora	CiteSeer	PubMed
Average adaptive score for abnormal nodes	0.987 ± 0.000	0.930 ± 0.007	0.959 ± 0.005
Average adaptive score for normal nodes	0.922 ± 0.004	0.689 ± 0.024	0.826 ± 0.016
Average residual weight for abnormal nodes	0.013 ± 0.000	0.070 ± 0.007	0.041 ± 0.005
Average residual weight for normal nodes	0.078 ± 0.004	0.311 ± 0.024	0.174 ± 0.016

5 Related Work

GNNs generalize convolutional neural networks (CNN) to graph structure data through the message passing framework [1, 6]. The design of message passing and GNN architectures are majorly motivated in spectral domain [2, 3] and spatial domain [4, 5, 6, 1]. Recent works have shown that the message passing in GNNs can be regarded as low-pass graph filters [10, 11]. More generally, it has been proven that message passing in many GNNs can be uniformly derived from graph signal denoising [25, 26, 27, 28].

Classic GNNs such as GCN [2] and GAT [5] achieve their best performance with shallow models, but their performance degrades when stacking more layers, which can be partially explained through oversmoothing analyses [12, 13]. Recent works propose to use residual connections or skip connections to mitigate the oversmoothing issues, and they demonstrate the potential benefits from more feature aggregations. Examples include but not limited to DeepGCNs [29], JKNet [30], GCNII [8], APPNP [9] and DeeperGNN [18]. These models use global residual connection which can't be adaptive for each node, which significantly differ from the proposed AirGNN.

6 Conclusion

In this work, we discover an intrinsic tension between feature aggregation and residual connection in the message passing scheme of GNNs, as well as the corresponding performance tradeoff between abnormal and normal features. We analyze possible reasons to explain these findings from the perspective of graph Laplacian smoothing. Our understandings further motivate us to propose a simple, novel, efficient, and interpretable message passing scheme as well as a new GNN model with adaptive residual, named AirGNN. AirGNN provides a node-wise adaptive transition between feature aggregation and residual connection, and the significant advantages of AirGNN are demonstrated through extensive experiments.

References

[1] Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. In *International Conference on Machine Learning*, pages 1263–1272. PMLR, 2017.

[2] Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

[3] Michaël Defferrard, Xavier Bresson, and Pierre Vandergheynst. Convolutional neural networks on graphs with fast localized spectral filtering. In *Proceedings of the 30th International Conference on Neural Information Processing Systems*, pages 3844–3852, 2016.

[4] William L Hamilton, Rex Ying, and Jure Leskovec. Inductive representation learning on large graphs. *arXiv preprint arXiv:1706.02216*, 2017.

[5] Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua Bengio. Graph attention networks. *arXiv preprint arXiv:1710.10903*, 2017.

[6] Franco Scarselli, Marco Gori, Ah Chung Tsoi, Markus Hagenbuchner, and Gabriele Monfardini. The graph neural network model. *IEEE transactions on neural networks*, 20(1):61–80, 2008.

[7] Zonghan Wu, Shirui Pan, Fengwen Chen, Guodong Long, Chengqi Zhang, and S Yu Philip. A comprehensive survey on graph neural networks. *IEEE transactions on neural networks and learning systems*, 2020.

[8] Ming Chen, Zhewei Wei, Zengfeng Huang, Bolin Ding, and Yaliang Li. Simple and deep graph convolutional networks. In Hal Daumé III and Aarti Singh, editors, *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 1725–1735. PMLR, 13–18 Jul 2020.

[9] Johannes Klicpera, Aleksandar Bojchevski, and Stephan Günnemann. Predict then propagate: Graph neural networks meet personalized pagerank. *arXiv preprint arXiv:1810.05997*, 2018.

[10] Hoang Nt and Takanori Maehara. Revisiting graph neural networks: All we have is low-pass filters. *arXiv preprint arXiv:1905.09550*, 2019.

[11] Lingxiao Zhao and Leman Akoglu. Pairnorm: Tackling oversmoothing in gnns. In *International Conference on Learning Representations*, 2019.

[12] Qimai Li, Zhichao Han, and Xiao-Ming Wu. Deeper insights into graph convolutional networks for semi-supervised learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

[13] Kenta Oono and Taiji Suzuki. Graph neural networks exponentially lose expressive power for node classification. In *International Conference on Learning Representations*, 2020.

[14] Stephen Boyd and Lieven Vandenberghe. *Convex optimization*. Cambridge university press, 2004.

[15] Miller McPherson, Lynn Smith-Lovin, and James M Cook. Birds of a feather: Homophily in social networks. *Annual review of sociology*, 27(1):415–444, 2001.

[16] Xiaojin Zhu and Zoubin Ghahramani. Learning from labeled and unlabeled data with label propagation.

[17] Dengyong Zhou, Olivier Bousquet, Thomas Navin Lal, Jason Weston, and Bernhard Schölkopf. Learning with local and global consistency. 2004.

[18] Meng Liu, Hongyang Gao, and Shuiwang Ji. Towards deeper graph neural networks. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*. ACM, 2020.

[19] Prithviraj Sen, Galileo Namata, Mustafa Bilgic, Lise Getoor, Brian Galligher, and Tina Eliassi-Rad. Collective classification in network data. *AI magazine*, 29(3):93–93, 2008.

[20] Oleksandr Shchur, Maximilian Mumme, Aleksandar Bojchevski, and Stephan Günnemann. Pitfalls of graph neural network evaluation. *arXiv preprint arXiv:1811.05868*, 2018.

[21] Marinka Zitnik Yuxiao Dong Hongyu Ren Bowen Liu Michele Catasta Jure Leskovec Weihua Hu, Matthias Fey. Open graph benchmark: Datasets for machine learning on graphs. *arXiv preprint arXiv:2005.00687*, 2020.

[22] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

[23] Daniel Zügner, Amir Akbarnejad, and Stephan Günnemann. Adversarial attacks on neural networks for graph data. In *KDD*. ACM, 2018.

[24] Yaxin Li, Wei Jin, Han Xu, and Jiliang Tang. Deeprobust: A pytorch library for adversarial attacks and defenses, 2020.

[25] Yao Ma, Xiaorui Liu, Tong Zhao, Yozen Liu, Jiliang Tang, and Neil Shah. A unified view on graph neural networks as graph signal denoising. *arXiv preprint arXiv:2010.01777*, 2020.

[26] Xuran Pan, Song Shiji, and Huang Gao. A unified framework for convolution-based graph neural networks. *https://openreview.net/forum?id=zUMD–Fb9Bt*, 2020.

[27] Meiqi Zhu, Xiao Wang, Chuan Shi, Houye Ji, and Peng Cui. Interpreting and unifying graph neural networks with an optimization framework, 2021.

[28] Siheng Chen, Yonina C. Eldar, and Lingxiao Zhao. Graph unrolling networks: Interpretable neural networks for graph signal denoising, 2020.

[29] Guohao Li, Matthias Müller, Ali Thabet, and Bernard Ghanem. Deepgcns: Can gcns go as deep as cnns? In *The IEEE International Conference on Computer Vision (ICCV)*, 2019.

[30] Keyulu Xu, Chengtao Li, Yonglong Tian, Tomohiro Sonobe, Ken-ichi Kawarabayashi, and Stefanie Jegelka. Representation learning on graphs with jumping knowledge networks. In Jennifer Dy and Andreas Krause, editors, *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pages 5453–5462. PMLR, 10–15 Jul 2018.

[31] Laurent Condat. A primal–dual splitting method for convex optimization involving lipschitzian, proximable and linear composite terms. *Journal of optimization theory and applications*, 158(2):460–479, 2013.

[32] Fan RK Chung and Fan Chung Graham. *Spectral graph theory*. Number 92. American Mathematical Soc., 1997.