CoNSoLe: Convex Neural Symbolic Learning

Abstract

Learning the underlying equation from data is a fundamental problem in many disciplines. Recent advances rely on Neural Networks (NNs) but do not provide theoretical guarantees in obtaining the exact equations owing to the non-convexity of NNs. In this paper, we propose Convex Neural Symbolic Learning (CoNSoLe) to seek convexity under mild conditions. The main idea is to decompose the recovering process into two steps and convexify each step. In the first step of searching for right symbols, we convexify the deep Q-learning. The key is to maintain double convexity for both the negative Q-function and the negative reward function in each iteration, leading to provable convexity of the negative optimal Q function to learn the true symbol connections. Conditioned on the exact searching result, we construct a Locally-Convex equation Learner (LoCaL) neural network to convexify the estimation of symbol coefficients. With such a design, we quantify a large region with strict convexity in the loss surface of LoCaL for commonly used physical functions. Finally, we demonstrate the superior performance of the CoNSoLe framework over the state-of-the-art on a diverse set of datasets.

1 Introduction

Identifying the underlying mathematical expressions from data plays a key role in multiple domains. For example, scientific discovery naturally requires learning analytical solutions to fit data. Engineering systems also need to frequently re-estimate system equations due to events, maintenance, upgrading, and new constructions [1], etc. In general, the problem, known as Symbolic Regression (SR) [2], learns the underlying equations $y = g(x)$ constructed via certain symbols, where x and y represent the input/output vector of the equations. If successfully learned, the equation can enjoy many important properties like high interpretability and generalizability, which will in turn significantly benefit scientific understanding and engineering planning, monitoring, and control.

Promising as it might be, SR is NP-hard [3, 4]. Mathematically, one can cast SR as an optimization problem over both discrete variables to select symbols and continuous variables to represent the symbol coefficients. Traditional solutions employ evolutionary algorithms like Genetic Programming (GP) [5]. These methods start from an initial set of expressions and continue evolving via operations like crossover or mutation. With fitness measures, GP-based algorithms can evaluate and select the best equations. However, these methods have poor scalability and limited theoretical guarantees [3].

More recent SR studies leverage Neural Networks (NNs) with high representational power. For the NN-based SR, we mainly categorize them into two groups based on the roles of the NNs. The first group employs NNs to directly model the equations, where sparsity of the NN weights is enforced to select symbols [6–10]. Thus, the problem is transformed into training the designed NN with sparsity regularization. However, due to the non-convexity of NNs, the weight selection and updating can be easily stuck in local optima, failing to find the exact equations.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

The second group employs NNs to search the symbol connections, and non-linear optimizations like BFGS [11] can be employed to estimate symbol coefficients. For the searching procedure, [3, 12–14] leverage a Recursive Neural Network (RNN) as a policy network to iteratively generate optimal actions that can select and connect symbols. [15] employs large-scale pre-training to directly map from data to the symbolic equations. While these methods restrict the utilization of NNs in the search phase, the non-convexity of NNs can still suffer the risk of sub-optimal decisions to formulate equations. To mitigate this issue, some efforts have been made such as risk-seeking policy gradient to find the best equations [3], restricting the searching space via domain knowledge [16] and entropy regularization [13], and re-initialization [13], etc. However, they have limited theoretical guarantees.

In this paper, we propose Convex Neural Symbolic Learning (CoNSoLe) with convexity under moderate conditions. To our best knowledge, we are the first to provide provable guarantees to learn the exact equations. In general, we decompose the SR problem into two sub-problems and seek convexity, respectively. In the first problem of searching symbols, we propose a double-convexified deep Q-learning to maintain the convexity of negative Q-function and negative reward functions with continuous action variables. Specifically, we use the Input Convex Neural Network (ICNN) [17] to represent both the negative Q-function and the negative reward function in each iteration. Subsequently, we prove that such a design (1) guarantees an optimal action selection at each step and (2) ensures the negative optimal Q-function, if successfully found, to be convex. Therefore, the convex negative optimal Q-function can yield global optimal decisions of equation constructions.

In the second problem of coefficient estimation, we use the search result to build a Locally-Convex Equation Learner (LoCaL) neural network. The key insight is that if the search result is correct, the loss surface of LoCaL has local regions that contain the global optima and has strict convexity. Moreover, we quantify the local regions and show the range of the region is large under mild assumptions. Therefore, initializations based on prior knowledge can often lie in the convex region, bringing the accurate coefficient estimation. Finally, we demonstrate that our CoNSoLe outperforms state-of-the-art methods on a diverse set of datasets.

2 Related Work

Symbolic regression using neural networks. As discussed in Section 1, the high approximation capacity of NNs can facilitate SR in both the symbol search [3, 12–15] and the expression representation [6–10]. In addition, there are studies to indirectly help SR with NNs. They typically treat NNs as a data augmentation tool to create high-quality data for learning or evaluation [18, 2].

Neural architecture search. Searching the connections of LoCaL falls into the area of Neural Architecture Search (NAS). NAS tries to find an optimal architecture of a target NN with the best performance [19]. The searching algorithms can be divided into RL-based, evolutionary algorithm-based, sequential optimization-based, and gradient descent-based methods. For RL-based methods, [20] employs an RNN model to sample the architecture and utilizes the accuracy of the sampled network as the reward. [21] uses Q-learning to find the connections of a target NN. However, Q-learning can hardly be applicable when the state and action spaces are large, e.g., SR problem. The evolutionary algorithm employs methods such as GP [22] and tournament selection [23]. However, these methods may lack the scalability for SR problem [3]. The sequential optimization-based method is more scalable as the model complexity increases in a sequential manner [24]. Finally, the gradient descent-based method [25] builds a large and over-parameterized network to search and train. Then, regularizations like dropout are added to find the best connections. However, for these methods, the theoretical guarantees remain opaque for SR problem.

Global optimum in neural networks. Many studies have been conducted to seek global optimality in NNs, and they can be categorized into finding global optima for weights or input variables. The weight optimization is directly linked to finding symbol coefficients in LoCaL. Specifically, [26] establishes a strong result that every local optimum is a global optimum for deep non-linear networks under several assumptions. [27] eliminates these assumptions and finds that with weight decay regularization (e.g., l_2 norm), the loss function of NN with ReLU activations is piece-wise strongly convex in local regions. However, LoCaL doesn't fit the above conditions. The second group of input variable optimization can help search for optimal inputs. [17] proposes ICNN such that the output of ICNN is convex in input variables. The key of ICNN is to restrict some weights and activation functions to preserve convexity. ICNN facilitates to design a convexified search algorithm.

3 Convex Neural Symbolic Learning

3.1 LOCAL to Hierarchically Represent the Equations and Learn Symbol Coefficients

We utilize a neural network to represent the multi-input multi-output equations due to the efficiency [6]. We prove in Theorem 3 that under certain conditions, there are local regions in the loss surface with strict convexity. Thus, we name our NN as Locally Convex Equation Learner (LOCAL).

Figure 1: An example of LOCAL structure and the state transition calculation.

We assume the underlying equation $y = g(x)$ follows compositionality and smoothness assumptions in [2], which are often the case in physics and many other scientific applications. Then, we can build LOCAL that can be trained via input/output pairs $\{x_i, y_i\}_{i=1}^N$, where $x_i \in \mathcal{X}$ and $y_i \in \mathcal{Y}$ are the i^{th} samples and N is the number of data. $\mathcal{X}$ and $\mathcal{Y}$ are the input and output data spaces, respectively. By the compositionality, we propose to hierarchically map x to y with correct symbols. Fig. 1 shows an example of the LOCAL structure. Specifically, each input entry first goes through the activation functions from a symbol library Φ. For example, in Fig. 1, we denote $\Phi = \{x, x^2, \cos(wx)\}$ to correspond with three neurons from top to bottom in the dotted black box, where w is a learnable weight. As for weights of x and x^2, they only need to appear in the later summation layer. Then, some activation outputs will be selected as multipliers for the multiplication. Subsequently, the multiplied outputs are selected and summed together. The repetition of symbolic activation, multiplication, and summation formulates final equations. For instance, the LOCAL structure in Fig. 1 can correctly represents y_1 and y_2 shown on the top right of Fig. 1.

Mathematically, we denote $Z_k \in \{0, 1\}^{n_k \times n_{k+1}}$ and $W_k \in \mathbb{R}^{n_k \times n_{k+1}}$ as the indicator and weight matrix between the k^{th} and the $(k + 1)^{th}$ layer of the LOCAL, respectively. n_k is the number of neurons for the k^{th} layers. $Z_k[i, j] = 1$ indicates that the connection exists between the i^{th} neuron in the k^{th} layer and the j^{th} neuron in the $(k + 1)^{th}$ layer, where $Z_k[i, j]$ is the $(i, j)^{th}$ entry of Z_k. We assume there are $(K + 1)$ layers in LOCAL and denote $h_k \in \mathbb{R}^{n_k}$ to be the output of the k^{th} layer. Naturally, we have $h_0 = x$ and $h_K = y$. For the symbolic activation or summation layer, we have $h_{k+1} = Z_k^T \circ W_k^T h_k$, where $\circ$ represents the Hadamard product and helps to zero out some connections. For the multiplication layer, we have $h_{k+1}[j] = \prod_{Z_k[i,j]=1} h_k[i]$. In general, we denote LOCAL as $f(x; \{Z_k\}_{k=0}^{K-1}, \{W_k\}_{k=0}^{K-1})$. The search algorithm identifies the locations of the entry 1 in $\{Z_k\}_{k=0}^{K-1}$ and the estimation process learns the corresponding weights in $\{W_k\}_{k=0}^{K-1}$ using $\{x_i, y_i\}_{i=1}^N$.

3.2 Search LOCAL Structures with Double Convex Deep Q-Learning

The high dimensionality of the search space is a general problem for LOCAL and other SR models. For an efficient search, NN-based RL methods are often utilized, e.g., deep Q-learning [28]. In this subsection, we employ the Input Convex Neural Network (ICNN) [17] to design a double convex deep Q-learning with provable performance guarantees.

Markov Decision Process (MDP) to search the structure of LoCaL. The search procedure is an MDP where each layer of LoCaL can be treated as a state and the connections between layers are actions. At each state, the deep Q-learning agent aims to find the optimal policy to decide the next action [21]. Therefore, we denote $\boldsymbol{a}_k \in \{0,1\}^{n_a}$ as the k^{th} action vector where $\boldsymbol{a}_k[(i-1)n_k+j] = 1$ implies that the connection ij exists for the i^{th} neuron in the k^{th} layer and the j^{th} neuron in the $(k+1)^{th}$ layer. $n_a = \max\{n_k n_{k+1}\}_{k=0}^{K-1}$ is the dimensionality of the action space. Also, we denote $\boldsymbol{s}_k \in \mathbb{Z}^{n_s}$ as the state vector to represent the current state for the k^{th} layers, where $n_s = \max\{n_k\}_{k=0}^{K}$ is the dimensionality of the state space. For a known state and a fixed action, the next state is exactly known due to the exact neuron connections, which implies a deterministic state transition. Thus, we utilize a linear transformation to represent the state transition process. $\forall 0 \leq k \leq K-1$, we define

$$\boldsymbol{s}_0 = [\boldsymbol{1}, \boldsymbol{0}]^T, \boldsymbol{s}_{k+1} = (\boldsymbol{Z}_k^{'})^T \boldsymbol{s}_k = [\mathrm{Mat}(\boldsymbol{a}_k); \boldsymbol{0}]^T \boldsymbol{s}_k, \tag{1}$$

where $\mathrm{Mat}(\cdot)$ is the operation to convert a vector to a matrix and we fill 0s to some $\boldsymbol{s}_k$, $\boldsymbol{a}_k$, and $\boldsymbol{Z}_k^{'}$ to maintain the fixed size. $[\cdot; \cdot]$ is the row concatenation process. We show this linear state transition is essential to guarantee the convexity of negative optimal Q-function in Theorem 1. For the calculation example of state transition, one can refer to Fig. 1. Finally, we can obtain $\boldsymbol{Z}_k$ from $\mathrm{Mat}(\boldsymbol{a}_k)$ by deleting the filled 0s. By the designed states and actions, the search will always start at $\boldsymbol{s}_0$ and end at $\boldsymbol{s}_K$ in one episode, thus formulating the LoCaL function $f(\boldsymbol{x}; \{\boldsymbol{Z}_k\}_{k=0}^{K-1}, \{\boldsymbol{W}_k\}_{k=0}^{K-1})$.

Double convexity for the negative reward and Q-function in the search model. Training LoCaL can bring a terminal reward [3] to evaluate the episode. However, this reward is insufficient to enable a convex evaluation for instant state-action pairs. Thus, we propose to restrict the negative reward function to be convex. Based on Bellman equations [29], this design will ensure the convexity of the negative optimal Q-function. More proof details can be referred to Theorem 1 and Appendix A.2.

Specifically, we utilize an ICNN to model the reward function $-R(\boldsymbol{s}_k, \boldsymbol{a}_k)$ such that $-R(\boldsymbol{s}_k, \boldsymbol{a}_k)$ is convex in states and actions in continuous spaces. $-R(\boldsymbol{s}_k, \boldsymbol{a}_k)$ requires proper training to do the correct evaluation. In the t^{th} episode, we collect the training input of state-action pairs $\{\boldsymbol{s}_k^t, \boldsymbol{a}_k^t\}_{k=0}^{K-1}$. Then, the output can be defined as the terminal reward to evaluate the obtained LoCaL which is denoted as $f_t(\cdot)$. Basically, we calculate the Normalized Root-Mean-Square Error (NRMSE) [3] of the trained $f_t(\cdot)$ function such that $\mathrm{NRMSE}_t = \frac{1}{\sigma_y}\sqrt{\frac{1}{N}\sum_{i=1}^{N}(\boldsymbol{y}_i - f_t(\boldsymbol{x}_i))^2}$, where σ_y is the standard deviation of the outputs. Then, the output of the reward can be calculated as $R_t = \frac{1}{1+\mathrm{NRMSE}_t}$. Therefore, we can train $-R(\cdot)$ using $\{\{\boldsymbol{s}_k^t, \boldsymbol{a}_k^t\}_{k=0}^{K-1}, -R_t\}$.

It's important to note that building this convex function $-R(\cdot)$ is better than directly leveraging the terminal reward for evaluations. The reason is that the former process not only provides theoretical guarantees in Theorem 1 but also evaluates the actions in a continuous space with convexity. Namely, one can utilize $R(\boldsymbol{s}_k, \tilde{\boldsymbol{a}}_k)$ to evaluate a continuous action $\tilde{\boldsymbol{a}}_k$, given that there is a much higher probability to obtain $\tilde{\boldsymbol{a}}_k$ rather than the discrete action $\boldsymbol{a}_k$ in the deep Q-learning. Then, to update Q values, we have the following iterative computations based on the temporal difference [21]:

$$Q_{t+1}(\boldsymbol{s}_k, \tilde{\boldsymbol{a}}_k) = Q_t(\boldsymbol{s}_k, \tilde{\boldsymbol{a}}_k) + \alpha\big(R(\boldsymbol{s}_k, \tilde{\boldsymbol{a}}_k) + \gamma \max_{\boldsymbol{a}} Q_t(\boldsymbol{s}_{k+1}, \tilde{\boldsymbol{a}}) - Q_t(\boldsymbol{s}_k, \tilde{\boldsymbol{a}}_k)\big), \tag{2}$$

where $Q_t(\boldsymbol{s}_k, \tilde{\boldsymbol{a}}_k)$ is the Q value at the t^{th} episode for state $\boldsymbol{s}_k$ and action $\tilde{\boldsymbol{a}}_k$. α and γ are pre-defined learning rate and discount factor, respectively. Similarly, we utilize another ICNN to represent $-Q(\boldsymbol{s}_k, \tilde{\boldsymbol{a}}_k)$ such that $-Q(\boldsymbol{s}_k, \tilde{\boldsymbol{a}}_k)$ is convex in $\tilde{\boldsymbol{a}}_k$ given fixed $\boldsymbol{s}_k$. Therefore, one can solve a convex optimization problem $\max_{\boldsymbol{a}} Q_t(\boldsymbol{s}_{k+1}, \tilde{\boldsymbol{a}})$ to obtain the (approximately) global optimal action for Equation (2) in each iteration. By definitions of the discrete actions, we can restrict the continuous action space in a hypercube $\mathrm{conv}(\{0,1\}^{n_a})$, i.e., a convex hull of the discrete actions. Thus, the optimization problem is:

$$\tilde{\boldsymbol{a}}^* = \arg\min_{\tilde{\boldsymbol{a}}} -Q(\boldsymbol{s}, \tilde{\boldsymbol{a}}), \tilde{\boldsymbol{a}} \in \mathrm{conv}(\{0,1\}^{n_a}). \tag{3}$$

Based on [17], this convex optimization problem can be solved via a bundle entropy method. After obtaining a continuous solution $\tilde{\boldsymbol{a}}^*$, we discretize it to a discrete vector $\boldsymbol{a}^*$ to build LoCaL. One simple method is to enforce $\boldsymbol{a}^*[i] = 1$ if $\tilde{\boldsymbol{a}}^*[i] \geq 0.5$, and otherwise $\boldsymbol{a}^*[i] = 0$. Thus, both $Q(\boldsymbol{s}_k, \tilde{\boldsymbol{a}}_k)$ and $Q(\boldsymbol{s}_k, \boldsymbol{a}_k)$ can be trained using Equation (2). Practically, we introduce ϵ-greedy strategy [30], experience replay [31] and a target Q-network [28] to update Q-function, thus boosting the convergence to the optimal Q-function. The specific algorithm can be seen in Algorithm 1. Finally,

173 based on Theorems 1-2, if the optimal Q-function is found, solving the convex optimization via the
174 optimal Q-function can generate the correct structures of LoCAL and exact equations.

175 **Symbolic static and dynamic constraints.** Constraints can be added to accelerate the search process
176 [3, 2]. For example, in Algorithm 1, we propose a constraint checking program for the state-action
177 pairs to avoid the invalid search, suitable for arbitrary restrictions. Then, we emphasize a general
178 type of constraint, symbolic constraint, for the SR problem. The symbolic static constraint requires
179 that each equation contains only a subset of symbols. For example, the equation $y_1 = x_1 x_2 \cdots x_{100}$
180 shouldn't exist since it is too complicated for real-world systems. This constraint eliminates part of
181 the action space and can be checked by counting the number of 1s in the action vector. The symbolic
182 dynamic constraint can gradually reduce the search space based on symbol correlations. Specifically,
183 we investigate the $(K-1)^{th}$ layer's neurons that are linearly summed to form the equation. If
184 some of these neurons have strong linear correlations to the output neuron (e.g., Pearson correlation
185 coefficient larger than 0.99), they should be kept subsequently. Namely, we can maintain the path
186 from input neurons to the neurons to be kept and reduce the search space.

4 Theoretical Analysis

188 We employ explorations, experience replay, and a target Q-network to boost the convergence to the
189 optimal Q function. However, our extra requirement of the convex shape for the negative Q-function
190 may deteriorate the convergence performance. Thus, we first prove that in CONSoLE, the negative
191 optimal Q-function is also convex so that the convex design doesn't affect the convergence. Then, we
192 prove that the convexity of the negative optimal Q-function eventually yields the exact equations.

193 **Theorem 1.** $\forall 0 \leq k \leq K-1$, the negative optimal Q-function $-Q^*(s_k, \tilde{a}_k)$ in the proposed
194 CONSoLE *framework is convex in* s_k *and* $\tilde{a}_k$, *where* s_k *is the discrete state and* $\tilde{a}_k$ *is the continuous*
195 *action at the* k^{th} *stage.*

196 The proof can be seen in Appendix A.2. Based on the convexity of negative optimal Q-function,
197 the optimal sequence of states $(s_0, s_1^*, \cdots, s_K^*)$ and actions $(a_0^*, a_1^*, \cdots, a_{K-1}^*)$ can be found via
198 solving the convex optimization problem. Then, we have the following theorem.

199 **Theorem 2.** *Let* $f^*(\cdot; W)$ *denote the* LoCAL *constructed by the optimal sequences of states*
200 $(s_0, s_1^*, \cdots, s_K^*)$ *and actions* $(a_0^*, a_1^*, \cdots, a_{K-1}^*)$ *from* $-Q^*(\cdot)$, *where* W *is the set of weights*
201 *of* $f^*(\cdot; W)$. *If* $f^*(\cdot; W)$ *can be trained with noiseless datasets and the training can achieve the*
202 *global optimal weights* W^*, $f^*(\cdot; W^*)$ *represents the exact equations.*

203 The proof can be seen in Appendix A.3. Theorem 2 requires that LoCAL can learn the global optimal
204 weights. The requirement is generally hard to achieve due to the non-linearity and non-convexity
205 of LoCAL. However, we show that with mild assumptions, there are local regions in the LoCAL
206 loss surface with strict convexity. Then, if we have proper initializations, the gradient-based weight
207 updating can find the global optimum. Specifically, we have the following theorem.

208 **Theorem 3.** *Assume the following conditions hold:* (1) *the equation* $g(x)$ *is* C^2 *smooth and has*
209 *bounded second derivatives with respect to weights,* (2) $\exists x \in \mathcal{X}$, $g(x)$ *has non-zero gradients with*
210 *respect to weights,* (3) *the structure of* LoCAL *is correctly searched to exactly represent symbols*
211 *and symbol connections in* $g(x)$, *and* (4) *the training dataset of* LoCAL *is noiseless. Then, for the*
212 *MSE loss surface of* LoCAL, *each global optimal point has a strictly convex local region.*

213 The proofs can be seen in Appendix A.4. Note that Assumptions 1-2 easily hold for common physical
214 equations in nature [2]. Assumption 3 relies on the search algorithm, and we show, both theoretically
215 and numerically, that our double convex deep Q-learning has good performances. Assumption 4
216 relies on the quality of data and we focus on the noiseless data in this paper. What's more, Equation
217 (6) in the proof suggests that if the absolute noise values are small, the locally convex region still
218 exists. We also numerically prove CONSoLE is robust under certain noise levels in Section 5.5. To
219 summarize, these assumptions are acceptable. To quantify the range of the local region for a LoCAL
220 with a certain complexity, we have the following theorem.

221 **Theorem 4.** *Suppose Assumptions 1-4 in Theorem 3 hold. For a* LoCAL *with one symbolic*
222 *activation, multiplication, and summation layer, the set of local convex regions with global optima is*

223 $$U = \left\{ W \Big| \frac{\left| \frac{d}{dt} \big|_{t=0} \hat{y}(x_i, W+tX) \right|^2}{\eta \left| \frac{d}{dt} \big|_{t=0} \hat{y}(x_j, W+tX) \right|} > |\hat{y}(x_k, W) - y_k| \right\}, \text{ where notations are defined in the proof.}$$

224 The proofs can be seen in Appendix A.5. We explain the region range is large for a stable system that
225 satisfies all assumptions in Theorem 4.

226 **Physical interpretations of the convex region size.** Physical systems in scientific and engineering
227 domains have certain stability that can withstand parameter changes to some extent. Further, this
228 ability should hold for arbitrary $\boldsymbol{x} \in \mathcal{X}$ and $\boldsymbol{y} \in \mathcal{Y}$. Thus, we can assume $\frac{d}{dt}\big|_{t=0}\hat{y}(\boldsymbol{x}_i, W + tX) \approx$
229 $\frac{d}{dt}\big|_{t=0}\hat{y}(\boldsymbol{x}_j, W + tX) \approx \frac{d}{dt}\big|_{t=0}\hat{y}(\boldsymbol{x}_k, W + tX)$ for $\boldsymbol{x}_i, \boldsymbol{x}_j, \boldsymbol{x}_k \in \mathcal{X}$. Then, the inequality in set U
230 can be approximately rewritten as $\frac{1}{\eta} > ||\boldsymbol{w} - \boldsymbol{w}^*||_2$, where $\boldsymbol{w}$ and $\boldsymbol{w}^*$ are the vectorized W and W^*,
231 respectively. Namely, the distance between any point W in the region to the global optimal point
232 W^* in the region is bounded by $\frac{1}{\eta}$. Based on Equation (19), η is the bound of the ratio of second
233 derivative to the first derivative. For a stable system, this ratio should be small. Otherwise, the system
234 can easily crash with a small parameter disturbance. Thus, $\frac{1}{\eta}$ is relatively large and so is the region
235 of U. An example of the range is displayed in Section 5.2. Finally, the above analysis also holds
236 when the LOCAL of the system equation has more than one symbolic activation, multiplication, and
237 summation layers. This is because Equations (20) always hold as long as we can find a η to bound
238 the ratio of second derivative to the first derivative, which is irrelevant to the structure of LOCAL.

5 Experiments

5.1 Settings

241 **Datasets.** We use the following datasets for testing. (1) **Synthetic datasets**. We create two datasets,
242 Syn_1 and Syn_2, for testing. Syn_1 has the following equations: $y_1 = 3x_1^2 \cos(2.5x_2)$, $y_2 = 4x_1x_3$,
243 and $y_3 = 3x_3^2$. Syn_2 is more complex with the following equations $y_1 = \sqrt{2.2x_1}x_2 + x_1x_2^2$,
244 $y_2 = \sin(1.8x_1)\big(\log(3x_2) + \sqrt{x_3}\big)$, $y_3 = \sqrt{3.7x_3}\log(1.6x_1) + x_1^2$. For the training data, each input
245 variable is randomly sampled from a uniform distribution of $U(1, 2)$ to avoid invalid values like
246 $\log(0)$. Totally, we create $2,000$ samples for training. Then, in the test phase, we utilize another
247 $2,000$ samples whose input variables are sampled from $U(3, 4)$. The symbolic activation pools are
248 $\{x, x^2, \cos(x)\}$ and $\{\sqrt{x}, x, x^2, \log(x), \sin(x)\}$ for Syn_1 and Syn_2, respectively.

249 (2) **Power system dataset.** Power flow equation determines the operations of electric systems [32].
250 For node i in an M-node system, the equation can be written as $p_i = \sum_{m=1}^{|M|} G_{im}(u_i u_m + v_i v_m) +$
251 $B_{im}(v_i u_m - u_i v_m)$ and $q_i = \sum_{m=1}^{M} G_{im}(v_i u_m - u_i v_m) - B_{im}(v_i u_m - u_i v_m)$, where u_i and v_i
252 are the real and imaginary components of the voltage phasor at node i. p_i and q_i are the active
253 and reactive power at node i. G_{im} and B_{im} represent the physical parameters of line im. If line
254 im does not exist, $G_{im} = B_{im} = 0$. Therefore, we can treat $\boldsymbol{x} = [u_1, v_1, \cdots, u_M, v_M]^T$ and
255 $\boldsymbol{y} = [p_1, q_1, \cdots, p_M, q_M]^T$. The target is to learn the underlying system topology and parameters,
256 which has broad impacts on the power domains [33]. In this experiment, we implement simulation
257 from a 5-node system using MATPOWER [34] and two year's hourly data. The first $8,760$ points are
258 used for training while the remaining samples are used for testing. The symbolic activation pool is
259 $\{x\}$. We denote this dataset as Pow.

260 (3) **Mass-damper system dataset.** Equations of the mass-damper system can be approximately
261 written as: $\dot{\boldsymbol{q}} = -\boldsymbol{DRD}^\top \boldsymbol{M}^{-1}\boldsymbol{q}$, where $\dot{\boldsymbol{q}}$ is a vector of momenta, $\boldsymbol{D}$ is the incidence matrix of
262 the system, $\boldsymbol{R}$ is the diagonal matrix of the damping coefficients for each line of the system, and
263 $\boldsymbol{M}$ is the diagonal matrix of each node mass of the system. Thus, we can set $\boldsymbol{y} = \dot{\boldsymbol{q}}$ and $\boldsymbol{x} = \boldsymbol{q}$ and
264 the goal is to learn the parameter matrix $-\boldsymbol{DRD}^\top \boldsymbol{M}^{-1}$. We conduct the simulation via MATLAB
265 for a 10-node system and obtain $6,000$ points for 1min simulation with a step size to be 0.01s. The
266 first $3,000$ samples are used for training while the rest samples are used for testing. The symbolic
267 activation pool is $\{x\}$. Then, we denote the dataset as Mas.

268 **Benchmark methods**. The following benchmark methods are utilized. (1) Deep Symbolic Regression
269 (**DSR**) [3]. DSR develops an RNN-based framework to search the expression tree. Especially, the
270 risk-seeking policy gradient is utilized to seek the best performance. Then, BFGS [11] can solve the
271 non-linear optimization and estimate the symbol coefficients. (2) Vanilla Policy Gradient (**VPG**) [3].
272 VPG is a vanilla version of DSR with a normal policy gradient rather than the risk-seeking method.
273 (3) Equation Learner (**EQL**) [6, 7]. EQL creates an end-to-end NN to select symbols and estimate
274 the coefficients. The sparse regularization is enforced for the NN weights to search symbols. (4)

275 Multilayer Perceptron (**MLP**). We also employ a standard MLP to learn the regression from $\boldsymbol{x}$ to $\boldsymbol{y}$.
276 We only evaluate the extrapolation capacity of MLP in the test dataset.

277 For DSR, VPG, and EQL methods, based on the input datasets, we adjust the symbol and operator
278 library to enable the same searching space as CONSOLE for fair comparisons. We run the benchmark
279 methods 5 times with different random seeds and present their best results. As for our method, we
280 only run 1 time and obtain good results due to the convex design and the ϵ-greedy strategy.

281 **Metrics for evaluation.** We employ the following metrics. (1) Average coefficient estimation percent-
282 age error E_c. For an equation with H symbols, We calculate the error as $E_c = \frac{1}{H} \sum_h \mathrm{PE}(w_h, \hat{w}_h)$,
283 where w_h and $\hat{w}_h$ represents the true and the estimated coefficients for the h^{th} symbol, respectively.
284 PE is the operation to calculate the percentage error. If there is no matched symbol for the h^{th} true
285 symbol, we denote $\mathrm{PE}(w_h, \hat{w}_h) = 100\%$. Note that when calculating E_c, proper simplifications may
286 be needed. For example, $\cos\big(2.5(\sqrt{x})^2\big) = \cos(2.5x)$. (2) NRMSE in the test dataset. We measure
287 the extrapolation capacity in the test dataset and utilize NRMSE employed in Section 3.2.

288 **Implementing details of CONSOLE.** Hyper-parameters of CONSOLE exist for both the double
289 convex deep Q-learning and the LOCAL. In the deep Q-learning, we set $\gamma = 0.2$, $\epsilon = 0.4$, $T = 600$,
290 $\lambda = 10^{-2}$, $T_0 = 10$ for Algorithm 1. Furthermore, to train the negative Q-function and the reward
291 function, we set the learning rate to be 5×10^{-3} and the number of epochs for training to be 50.
292 Then, we set the batch size for the negative Q-function to be 100. If the number of data in the replay
293 buffer is less than 100, no training happens for the negative Q-function. Additionally, all the data
294 gathered in one episode are used to train the negative reward function. As for the LOCAL, we set
295 $K = 3$, the learning rate to be 1×10^{-2} and the number of training epochs to be 8. We make these
296 training epochs to be small since training the LOCAL is the most time-consuming part of CONSOLE.
297 Furthermore, if the structure of LOCAL is correctly searched, a small number of iterations can help
298 LOCAL to gain the global optimal weights. Finally, we initialize all trainable weights in LOCAL to
299 be 1. The following results show that a relatively large area is suitable for an initial guess of LOCAL.

(a) LoCal for the Toy example. (b) Updating of convex $-Q$.

(c) Loss surface with local convexity. (d) Training loss for different initializations.

Figure 2: Illustrations of convex mechanisms using a toy example.

5.2 Verification and 3-D Visualization of Convex Mechanisms

301 We first utilize a toy example to verify the benefits of convex designs for two sub problems.
302 Specifically, we consider to learn $y_1 = 3x_1^2 \cos(2.5x_2)$ with the loss function $L = \sum_i^N (\boldsymbol{y}_i[1] -$
303 $w_1 \boldsymbol{x}_i[1]^2 \cos(w_2 \boldsymbol{x}_i[2]))^2$, where the data sample notations are defined in Section 3.1. As shown in
304 Fig. 2a, we design a 4-layer LOCAL with two learnable parameters w_1 and w_2 to represent the
305 coefficients. Thus, in the search phase, the goal is to identify the action $\boldsymbol{a}_1$. We plot $-Q_t(\cdot)$ when
306 $t = 1, 5, 10$ in Fig. 2b. The convexity always exists so that the algorithm can quickly find the global
307 optimal solutions in red dots. Next, as the agent update Q values with true rewards, the Q-function
308 converges to the optimal function within 10 episodes. Finally, the convex $-Q^*(\cdot)$ remains unchanged
309 and can bring the optimal action and the true equation, which supports Theorem 2.

Subsequently, we plot the loss surface of L in Fig. 2c. We find that around the two global optima $(3, 2.5)$ and $(3, -2.5)$, there are convex regions that have an approximate quadratic shape. To further quantify the range for proper initialization, we vary the initial weight $w_0 \in \{-10, -9, \cdots, 10\}$ for w_1 and w_2 in LoCAL. Fig. 2 reports the final training loss with respect to different w_0, and we find the safe range for initialization is $[-3, 7] \setminus \{0\}$. This range is relatively large when compared to the optimal values. These observations support our Theorems 3 and 4. Finally, $w_0 = 0$ does not work since $\frac{\partial L}{\partial w_2}\big|_{w_2=0} = 0$ always holds, which prevents the weight updating using gradient methods.

Table 1: The learned equations for Syn_1 and Syn_2.

	CONSOLE	DSR
SYN_1	$y_1 = 3x_1^2 \cos(2.5x_2)$
$y_2 = 3.999x_1x_3$
$y_3 = 3x_3^2 \cos(0.005x_1)$	$y_1 = 0.905x_2 + 3.88\cos(2.48x_2) + 1.74x_1^2\cos(1.98x_1)$
$y_2 = 4.02x_1x_3$
$y_3 = 3x_3^2$
SYN_2	$y_1 = 1.47\sqrt{x_1}x_2 + 1.001x_1x_2^2$
$y_2 = \sin(1.8x_1)\big(\log(2.998x_2) + 0.998\sqrt{x_3}\big)$
$y_3 = 1.931\sqrt{x_3}\log(1.594x_1) + 1.007x_1^2$	$y_1 = 1.223\sqrt{x_1}x_2 + 0.181x_1\log(x_3) + 0.925x_1x_2^2$
$y_2 = \sin(1.633x_1)\log(2.965x_2)$
$+0.874\sin(1.723x_1)\sqrt{x_3}$
$y_3 = 2.081\sqrt{x_3}x_2 + 1.045x_1^2$
	VPG	EQL
SYN_1	$y_1 = -0.364x_1^2\cos(1.56x_3)$
$+4.707x_2 + 0.854x_2^2\cos(1.98x_1)$
$y_2 = 3.293x_2 + 0.554\cos(2.82x_2)$
$y_3 = 3x_3^3$	$y_1 = 0.23x_1 + 0.021x_3^2 + 0.283x_3$
$y_2 = 0.03x_1x_3 + 0.488x_1$
$+0.045x_3^2 + 0.6x_3$
$y_3 = 0.366x_1 + 0.03x_3^2 + 0.45x_3$
SYN_2	$y_1 = 1.462\log(x_1)x_2 + 0.830x_1x_2^2$
$y_2 = \sin(1.220x_1)\log(3.024x_2)$
$+0.248\sin(1.454x_1)x_2^2 + 0.567\sin(1.56x_3)$
$y_3 = 2.081\sqrt{x_3}x_2 + 1.045x_1^2$	$y_1 = 0.44x_2 + 0.2x_1^2 + 0.14x_1x_2^2 + 0.45x_1x_2$
$+0.51x_1 + 0.24x_2^2 + 0.55x_2 + 0.705$
$y_2 = 0.018x_1^2 + 0.012x_1x_2^2 + 0.0636$
$y_3 = 0.383x_2 + 0.357x_3 + 0.31x_1x_2 + 0.487$

5.3 Convexity Guarantees of CONSOLE to Learn Correct Equations

In this subsection, we report the results of the equation learning. First, we list the learned equations for Syn_1 and Syn_2 in Table 1. Table 1 presents that CONSOLE has the best performance in most of the equations while DSR ranks second. In particular, CONSOLE can accurately learn all equations in Syn_1 and Syn_2. The superior performance is mostly due to the convex design of the search and the coefficient estimation process with provable guarantees. In addition, we observe that for the result of CONSOLE in learning y_3 of Syn_1, we have $3x_3^2\cos(0.005x_1) \approx 3x_3^2$. This shows that there is a possibility that the search result of CONSOLE might not be optimal (i.e., an extra consine term exists but is close to 1), but the learned equation is still highly accurate. Such an observation nonetheless guides further study of the coupling relationship between the search and the estimation procedures.

(a) The average percentage error $E_c(\%)$ of coefficients. (b) NRMSE of test datasets.

Figure 3: Results of equation learning for different methods and datasets.

DSR doesn't perform well when the underlying equation is relatively complex, e.g., y_1 in Syn_1 and y_1 and y_2 in Syn_2. This is because DSR may still fall into a local optimal solution despite risk-seeking policy design. VPG method performs worse than DSR since VPG considers an expected reward [3]. Finally, EQL performs the worst as it merges the symbol search and the coefficient estimation in one NN model, which provides few guarantees of accurate learning. The above observations and analyses

are consistent with the result of coefficient estimation errors and prediction errors in Fig. 3a and 3b. For the Pow and Mas, CONSOLE doesn't learn completely exact equations within $T = 600$ episodes. This is because they have a large number of variables to be considered. However, CONSOLE is still better than other methods.

5.4   Ablation Study: Exploration and Convex Search are Essential

We conduct an ablation study to further understand what factors are important in the CONSOLE. We test the result with Syn_1 and Syn_1 and report the $E_c(\%)$ values. Specifically, we investigate the following cases. (1) No ablation. (2) Drop exploration in deep Q-learning. We delete the ϵ-greedy strategy. (3) Drop double-convex deep-Q learning. We replace this design with a traditional deep-Q learning. (4) Drop coefficient estimation using LOCAL. After learning the structure of LOCAL, we reformulate a non-linear optimization and utilize BFGS [11] in DSR, instead of gradient descent in LOCAL, to estimate the coefficient. (5) Drop static symbolic constraint. (6) Drop dynamic symbolic constraint. These two constraints are mentioned in Section 3.2. Then, Fig. 4 shows that cases (2) and (3) cause large errors. For case (2), if no exploration strategy is added, the updating of the Q-function and the reward function is slow. For case (3), the non-convex search induces many sub-optimal actions in the search process. Thus, these two cases cause a slow search process and significant errors after $T = 600$ episodes. For symbolic constraints in (5) and (6), removing them slightly increases the error for Syn_1. This shows these constraints are beneficial to the search process. Finally, we find that utilizing BFGS in (4) can bring good results with initialization in the locally convex region. Since the non-linear optimization has the same loss surface as LOCAL, the locally convex region in Theorems 3 and 4 can prove the good performance of BFGS.

Figure 4: $E_c(\%)$ of ablation study.

(a) $E_c(\%)$ w.r.t. SNRs.

(b) $E_c(\%)$ w.r.t. data volumes.

Figure 5: $E_c(\%)$ of sensitivity analysis.

5.5   CONSOLE is Robust with Changing Noise Levels and Data Volume

We utilize Syn_1 and Syn_2 to examine the robustness of the framework with changing noise levels and data volumes. For the noise level, we consider the Signal-to-Noise Ratio (SNR) such that $SNR \in \{80, 90, 100, 110, 120\}$. For the data volume, we fix $SNR = 100$ and vary $N \in \{500, 1000, 1500, 2000, 2500\}$. Fig. 5a and 5b demonstrate the results. We find that when $SNR \geq 100$, the error can be less than 1%. This noise level is suitable to real-word systems. For example, $SNR = 125$ for electric measurements [33]. For the data volume, the overall error is less than 2% when $N \geq 500$, which shows a robust performance of CONSOLE.

6   Conclusions and Future Work

In this paper, we propose CONSOLE, a novel Convex Neural Symbolic Learning method, which enjoys convexity with certain conditions to tackle Symbolic Regression with guaranteed performances. Specifically, we convexify the search problem by proposing a double convex deep-Q learning. In the meantime, we prove the local and strict convexity of the coefficient estimation in our Locally-Convex equation Learner (LOCAL). To our best knowledge, CONSOLE is the first method that provides guarantees with reasonable assumptions to learn exact equations. Besides, CONSOLE has, at a minimum, a broader impact on the following domains. (1) Convex control for physical systems using Reinforcement Learning. (2) Neural networks in engineering applications with local convexity.

References

[1] J. V. Beck and K. J. Arnold, *Parameter estimation in engineering and science*. James Beck, 1977.

[2] S.-M. Udrescu and M. Tegmark, "Ai feynman: A physics-inspired method for symbolic regression," *Science Advances*, vol. 6, no. 16, p. eaay2631, 2020.

[3] B. K. Petersen, M. L. Larma, T. N. Mundhenk, C. P. Santiago, S. K. Kim, and J. T. Kim, "Deep symbolic regression: Recovering mathematical expressions from data via risk-seeking policy gradients," in *International Conference on Learning Representations*, 2021. [Online]. Available: https://openreview.net/forum?id=m5Qsh0kBQG

[4] Q. Lu, J. Ren, and Z. Wang, "Using genetic programming with prior formula knowledge to solve symbolic regression problem," *Computational intelligence and neuroscience*, vol. 2016, 2016.

[5] P. Orzechowski, W. La Cava, and J. H. Moore, "Where are we now? a large benchmark study of recent symbolic regression methods," in *Proceedings of the Genetic and Evolutionary Computation Conference*, 2018, pp. 1183–1190.

[6] S. Sahoo, C. Lampert, and G. Martius, "Learning equations for extrapolation and control," in *Proceedings of the 35th International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, J. Dy and A. Krause, Eds., vol. 80. PMLR, 10–15 Jul 2018, pp. 4442–4450. [Online]. Available: https://proceedings.mlr.press/v80/sahoo18a.html

[7] G. Martius and C. H. Lampert, "Extrapolation and learning equations," *arXiv preprint arXiv:1610.02995*, 2016.

[8] M. Werner, A. Junginger, P. Hennig, and G. Martius, "Informed equation learning," *arXiv preprint arXiv:2105.06331*, 2021.

[9] H. Li and Y. Weng, "Physical equation discovery using physics-consistent neural network (pcnn) under incomplete observability," in *Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery & Data Mining*, 2021, pp. 925–933.

[10] Z. Chen, Y. Liu, and H. Sun, "Physics-informed learning of governing equations from scarce data," *Nature communications*, vol. 12, no. 1, pp. 1–13, 2021.

[11] R. Fletcher, *Practical methods of optimization*. John Wiley & Sons, 2013.

[12] T. N. Mundhenk, M. Landajuela, R. Glatt, C. P. Santiago, D. M. Faissol, and B. K. Petersen, "Symbolic regression via neural-guided genetic programming population seeding," *arXiv preprint arXiv:2111.00053*, 2021.

[13] M. L. Larma, B. K. Petersen, S. K. Kim, C. P. Santiago, R. Glatt, T. N. Mundhenk, J. F. Pettit, and D. M. Faissol, "Improving exploration in policy gradient search: Application to symbolic optimization," *arXiv preprint arXiv:2107.09158*, 2021.

[14] J. T. Kim, M. L. Larma, and B. K. Petersen, "Distilling wikipedia mathematical knowledge into neural network models," *arXiv preprint arXiv:2104.05930*, 2021.

[15] L. Biggio, T. Bendinelli, A. Neitz, A. Lucchi, and G. Parascandolo, "Neural symbolic regression that scales," in *International Conference on Machine Learning*. PMLR, 2021, pp. 936–945.

[16] B. K. Petersen, C. Santiago, and M. Landajuela, "Incorporating domain knowledge into neural-guided search via in situ priors and constraints," in *8th ICML Workshop on Automated Machine Learning (AutoML)*, 2021.

[17] B. Amos, L. Xu, and J. Z. Kolter, "Input convex neural networks," in *International Conference on Machine Learning*. PMLR, 2017, pp. 146–155.

[18] C. Rao, P. Ren, Y. Liu, and H. Sun, "Discovering nonlinear pdes from scarce data with physics-encoded learning," *arXiv preprint arXiv:2201.12354*, 2022.

[19] T. Elsken, J. H. Metzen, and F. Hutter, "Neural architecture search: A survey," *The Journal of Machine Learning Research*, vol. 20, no. 1, pp. 1997–2017, 2019.

[20] B. Zoph and Q. V. Le, "Neural architecture search with reinforcement learning," *arXiv preprint arXiv:1611.01578*, 2016.

[21] B. Baker, O. Gupta, N. Naik, and R. Raskar, "Designing neural network architectures using reinforcement learning," *arXiv preprint arXiv:1611.02167*, 2016.

[22] K. O. Stanley, J. Clune, J. Lehman, and R. Miikkulainen, "Designing neural networks through neuroevolution," *Nature Machine Intelligence*, vol. 1, no. 1, pp. 24–35, 2019.

[23] E. Real, A. Aggarwal, Y. Huang, and Q. V. Le, "Regularized evolution for image classifier architecture search," in *Proceedings of the aaai conference on artificial intelligence*, vol. 33, no. 01, 2019, pp. 4780–4789.

[24] C. Liu, B. Zoph, M. Neumann, J. Shlens, W. Hua, L.-J. Li, L. Fei-Fei, A. Yuille, J. Huang, and K. Murphy, "Progressive neural architecture search," in *Proceedings of the European conference on computer vision (ECCV)*, 2018, pp. 19–34.

[25] G. Bender, P.-J. Kindermans, B. Zoph, V. Vasudevan, and Q. Le, "Understanding and simplifying one-shot architecture search," in *International Conference on Machine Learning*. PMLR, 2018, pp. 550–559.

[26] K. Kawaguchi, "Deep learning without poor local minima," in *Advances in Neural Information Processing Systems*, D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett, Eds., vol. 29. Curran Associates, Inc., 2016. [Online]. Available: https://proceedings.neurips.cc/paper/2016/file/f2fc990265c712c49d51a18a32b39f0c-Paper.pdf

[27] T. Milne, "Piecewise strong convexity of neural networks," in *Advances in Neural Information Processing Systems*, H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, Eds., vol. 32. Curran Associates, Inc., 2019. [Online]. Available: https://proceedings.neurips.cc/paper/2019/file/b33128cb0089003ddfb5199e1b679652-Paper.pdf

[28] J. Fan, Z. Wang, Y. Xie, and Z. Yang, "A theoretical analysis of deep q-learning," in *Learning for Dynamics and Control*. PMLR, 2020, pp. 486–489.

[29] D. Bertsekas, *Convex optimization algorithms*. Athena Scientific, 2015.

[30] T. Hester, M. Vecerik, O. Pietquin, M. Lanctot, T. Schaul, B. Piot, D. Horgan, J. Quan, A. Sendonaris, I. Osband *et al.*, "Deep q-learning from demonstrations," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 32, no. 1, 2018.

[31] V. Mnih, K. Kavukcuoglu, D. Silver, A. A. Rusu, J. Veness, M. G. Bellemare, A. Graves, M. Riedmiller, A. K. Fidjeland, G. Ostrovski *et al.*, "Human-level control through deep reinforcement learning," *nature*, vol. 518, no. 7540, pp. 529–533, 2015.

[32] J. Yu, Y. Weng, and R. Rajagopal, "Mapping rule estimation for power flow analysis in distribution grids," *arXiv preprint arXiv:1702.07948*, 2017.

[33] H. Li, Y. Weng, Y. Liao, B. Keel, and K. E. Brown, "Distribution grid impedance & topology estimation with limited or no micro-pmus," *International Journal of Electrical Power & Energy Systems*, vol. 129, p. 106794, 2021.

[34] MATPOWER community, "MATPOWER," 2020, https://matpower.org/.