COMPUTATIONAL SEPARATION BETWEEN CONVOLUTIONAL AND FULLY-CONNECTED NETWORKS

ABSTRACT

Convolutional neural networks (CNN) exhibit unmatched performance in a multitude of computer vision tasks. However, the advantage of using convolutional networks over fully-connected networks is not understood from a theoretical perspective. In this work, we show how convolutional networks can leverage locality in the data, and thus achieve a computational advantage over fully-connected networks. Specifically, we show a class of problems that can be efficiently solved using convolutional networks trained with gradient-descent, but at the same time is hard to learn using a polynomial-size fully-connected network.

1 INTRODUCTION

Convolutional neural networks (LeCun et al., 1998; Krizhevsky et al., 2012) achieve state-of-the-art performance on every possible task in computer vision. However, while the empirical success of convolutional networks is indisputable, the advantage of using them is not well understood from a theoretical perspective. Specifically, we consider the following fundamental question:

Why do convolutional networks (CNNs) perform better than fully-connected networks (FCNs)?

Clearly, when considering expressive power, FCNs have a big advantage. Since convolution is a linear operation, any CNN can be expressed using a FCN, whereas FCNs can express a strictly larger family of functions. So, any advantage of CNNs due to expressivity can be leveraged by FCNs as well. Therefore, *expressive power does not explain the superiority of CNNs over FCNs*.

There are several possible explanations to the superiority of CNNs over FCNs: parameter efficiency (and hence lower sample complexity), weight sharing, and locality prior. The main result of this paper is arguing that locality is a key factor by proving a computational separation between CNNs and FCNs based on locality. But, before that, let's discuss the other possible explanations.

First, we observe that CNNs seem to be much more efficient in utilizing their parameters. A FCN needs to use a greater number of parameters compared to an equivalent CNN: each neuron of a CNN is limited to a small receptive field, and moreover, many of the parameters of the CNN are shared. From classical results in learning theory, using a large number of parameters may result in inferior generalization. So, can the advantage of CNNs be explained simply by counting parameters?

To answer this question, we observe the performance of CNN and FCN based architecture of various widths and depths trained on the CIFAR-10 dataset. For each architecture, we observe the final test accuracy versus the number of trainable parameters. The results are shown in Figure 1. As can be seen, CNNs have a clear advantage over FCNs, regardless of the number of parameters used. As is often observed,

Figure 1: Comparison between CNN and FCN of various depths (2/4/6) and widths, trained for 125 epochs with RMSprop optimizer.

a large number of parameters does not hurt the performance of neural networks, and so *parameter efficiency cannot explain the advantage of CNNs*. This is in line with various theoretical works on optimization of neural networks, which show that over-parameterization is beneficial for convergence of gradient-descent (e.g., Du et al. (2018); Soltanolkotabi et al. (2018); Li & Liang (2018)).

The superiority of CNNs can be also attributed to the extensive *weight sharing* between the different convolutional filters. Indeed, it has been previously shown that weight sharing is important for the optimization of neural networks (Shalev-Shwartz et al., 2017b). Moreover, the translation-invariant nature of CNNs, which relies on weight sharing, is often observed to be beneficial in various signal processing tasks (Kauderer-Abrams, 2017; Kayhan & Gemert, 2020). So, how much does the weight sharing contribute to the superiority of CNNs over FCNs?

To understand the effect of weight sharing on the behavior of CNNs, it is useful to study **locally-connected network** (LCN) architectures, which are similar to CNNs, but have no weight sharing between the kernels of the network. While CNNs are far more popular in practice (also due to the fact that they are much more efficient in terms of model size), LCNs have also been used in different contexts (e.g., Bruna et al. (2013); Chen et al. (2015); Liu et al. (2020)). It has been recently observed that in some cases, the performance of LCNs is on par with CNNs (Neyshabur, 2020). So, even if weight sharing explains some of the advantage of CNNs, it clearly doesn't tell the whole story.

Finally, a key property of CNN architectures is their strong utilization of **locality** in the data. Each neuron in a CNN is limited to a local receptive field of the input, hence encoding a strong locality bias. In this work we demonstrate how CNNs can leverage the local structure of the input, giving them a clear advantage in terms of *computational complexity*. Our results hint that **locality** is the principal property that explains the advantage of using CNNs.

Our main result is a computational separation result between CNNs and FCNs. To show this result, we introduce a family of functions that have a very strong local structure, which we call k-**patterns**. A k-**pattern** is a function that is determined by k *consecutive* bits of the input. We show that for inputs of n bits, when the target function is a $(\log n)$-pattern, training a CNN of polynomial size with gradient-descent achieves small error in polynomial time. However, gradient-descent will fail to learn $(\log n)$-patterns, when training a FCN of polynomial-size.

1.1 RELATED WORK

It has been empirically observed that CNN architectures perform much better than FCNs on computer vision tasks, such as digit recognition and image classification (e.g., Urban et al. (2017); Driss et al. (2017)). While some works have applied various techniques to improve the performance of FCNs (Lin et al. (2015); Fernando et al. (2016); Neyshabur (2020)), there is still a gap between performance of CNNs and FCNs, where the former give very good performance "out-of-the-box". The focus of this work is to understand, from a theoretical perspective, why CNNs give superior performance when trained on input with strong local structure.

Various theoretical works show the advantage of architectures that leverage local and hierarchical structure. The work of Poggio et al. (2015) shows the advantage of using deep hierarchical models over wide and shallow functions. These results are extended in Poggio et al. (2017), showing an exponential gap between deep and shallow networks, when approximating locally compositional functions. The works of Mossel (2016); Malach & Shalev-Shwartz (2018) study learnability of deep hierarchical models. The work of Cohen et al. (2017) analyzes the expressive efficiency of convolutional networks via hierarchical tensor decomposition. While all these works show that indeed CNNs powerful due to their hierarchical nature and the efficiency of utilizing local structure, they do not explain why these models are superior to fully-connected models.

There are a few works that provide a theoretical analysis of CNN optimization. The works of Brutzkus & Globerson (2017); Du et al. (2018) show that gradient-descent can learn a shallow CNN with a single filter, under various distributional assumptions. The work of Zhang et al. (2017) shows learnability of a convex relaxation of convolutional networks. While these works focus on computational properties of learning CNNs, as we do in this work, they do not compare CNNs to FCNs, but focus only on the behavior of CNNs. The works of Cohen & Shashua (2016); Novak et al. (2018) study the implicit bias of simplified CNN models. However, these result are focused on generalization properties of CNNs, and not on computational efficiency of the optimization.

Figure 2: Example of a k-pattern with $k = 5$.

2 DEFINITIONS AND NOTATIONS

Let $\mathcal{X} = \{\pm 1\}^n$ be our instance space, and let $\mathcal{Y} = \{\pm 1\}$ be the label space. Throughout the paper, we focus on learning a binary classification problem using the hinge-loss: $\ell(\hat{y}, y) = \max\{1 - y\hat{y}, 0\}$. Given some distribution $\mathcal{D}$ over $\mathcal{X}$, some target function $f : \mathcal{X} \to \mathcal{Y}$ and some hypothesis $h : \mathcal{X} \to \mathcal{Y}$, we define the loss of h with respect to f on the distribution $\mathcal{D}$ by:

$$L_{f,\mathcal{D}}(h) = \mathbb{E}_{\mathbf{x} \sim \mathcal{D}} [\ell(h(\mathbf{x}), f(\mathbf{x}))]$$

The goal of a supervised learning algorithm is, given access to examples sampled from $\mathcal{D}$ and labeled by f, to find a hypothesis h that minimizes $L_{f,\mathcal{D}}(h)$. We focus on the gradient-descent (GD) algorithm: given some parametric hypothesis class $\mathcal{H} = \{h_{\mathbf{w}} \ : \ \mathbf{w} \in \mathbb{R}^q\}$, gradient-descent starts with some (randomly initialized) hypothesis $h_{\mathbf{w}^{(0)}}$ and, for some learning rate $\eta > 0$, updates:

$$\mathbf{w}^{(t)} = \mathbf{w}^{(t-1)} - \eta \nabla_{\mathbf{w}} L_{f,\mathcal{D}}(h_{\mathbf{w}^{(t-1)}})$$

We compare the behavior of gradient-descent, when learning two possible neural network architectures: a **convolutional network** (CNN) and a **fully-connected network** (FCN).

Definition 1. *A **convolutional network** $h_{\mathbf{u},W,\mathbf{b}}$ is defined as follows:*

$$h_{\mathbf{u},W,b}(\mathbf{x}) = \sum_{j=1}^{n-k} \left\langle \mathbf{u}^{(j)}, \sigma(W\mathbf{x}_{j\dots j+k} + \mathbf{b}) \right\rangle$$

for activation function σ, with kernel $W \in \mathbb{R}^{q \times k}$, bias $\mathbf{b} \in \mathbb{R}^q$ and readout layer $\mathbf{u}^{(1)}, \dots, \mathbf{u}^{(n)} \in \mathbb{R}^q$. Note that this is a standard depth-2 CNN with kernel k, stride 1 and q filters.

Definition 2. *A **fully-connected network** $h_{\mathbf{u},\mathbf{w},\mathbf{b}}$ is defined as follows:*

$$h_{\mathbf{u},\mathbf{w},\mathbf{b}}(\mathbf{x}) = \sum_{i=1}^{q} u_i \sigma \left(\left\langle \mathbf{w}^{(i)}, \mathbf{x} \right\rangle + b_i \right)$$

for activation function σ, first layer $\mathbf{w}^{(1)}, \dots, \mathbf{w}^{(q)} \in \mathbb{R}^n$, bias $\mathbf{b} \in \mathbb{R}^q$ and second layer $\mathbf{u} \in \mathbb{R}^q$.

We demonstrate the advantage of CNNs over FCNs by observing a problem that can be learned using CNNs, but is hard to learn using FCNs. We call this problem the k-**pattern** problem:

Definition 3. *A function $f : \mathcal{X} \to \mathcal{Y}$ is a k-**pattern**, if for some $g : \{\pm 1\}^k \to \mathcal{Y}$ and index j^*:*

$$f(\mathbf{x}) = g(x_{j^* \dots j^*+k})$$

Namely, a k-**pattern** is a function that depends only on a small pattern of *consecutive* bits of the input. The k-**pattern problem** is the problem of learning k-patterns: for some k-pattern f and some distribution $\mathcal{D}$ over $\mathcal{X}$, given access to $\mathcal{D}$ labeled by f, find a hypothesis h with $L_{f,\mathcal{D}}(h) \le \epsilon$.

3 CNNs EFFICIENTLY LEARN $(\log n)$-PATTERNS

The main result in this section shows that gradient-descent can learn k-patterns when training convolutional networks for $poly(2^k, n)$ iterations, and when the network has $poly(2^k, n)$ neurons:

Theorem 4. *Assume we uniformly initialize $W^{(0)} \sim \{\pm 1/k\}^{q \times k}$, $b_i = 1/k - 1$ and $\mathbf{u}^{(0,j)} = 0$ for every j. Assume the activation σ satisfies $|\sigma| \le c, |\sigma'| \le 1$, for some constant c. Fix some $\delta > 0$, some k-pattern f and some distribution $\mathcal{D}$ over $\mathcal{X}$. Then, if $q > 2^{k+3} \log(2^k/\delta)$, with probability at least $1 - \delta$ over the initialization, when training a convolutional network $h_{\mathbf{u},W,\mathbf{b}}$ using gradient descent with $\eta = \frac{\sqrt{n}}{\sqrt{qT}}$ we have:*

$$\frac{1}{T} \sum_{t=1}^{T} L_{f,\mathcal{D}}(h_{\mathbf{u}^{(t)}, W^{(t)}, b}) \le \frac{2cn^2 k^2 2^k}{q} + \frac{2(2^k k)^2}{\sqrt{qn}} + \frac{c^2 n^{1.5} \sqrt{q}}{T}$$

Before we prove the theorem, observe that the above immediately implies that when $k = O(\log n)$, gradient-descent can **efficiently** learn to solve the k-pattern problem, when training a CNN:

Corollary 5. *Let $k = O(\log n)$. Then, running GD on a CNN with $q = O(\epsilon^{-2}n^3 \log^2 n)$ neurons for $T = O(\epsilon^{-2}n^3 \log n)$ iterations, using a sample $S \sim \mathcal{D}$ of size $O(\epsilon^{-2}nkq \log(nkq/\delta))$, learns the k-pattern problem up to accuracy ϵ w.p. $\geq 1 - \delta$.*

Proof. Sample $S \sim \mathcal{D}$, and let $\widehat{\mathcal{D}}$ be the uniform distribution over S. Then, from Theorem 4 and the choice of q and T there exists $t \in [T]$ with $L_{f,\widehat{\mathcal{D}}}(h_{\mathbf{u}^{(t)}, W^{(t)}, b}) \leq \epsilon/2$, i.e. GD finds a hypothesis with train loss at most $\epsilon/2$. Now, using the fact the VC dimension of depth-2 ReLU networks with W weights is $O(W \log W)$ (see Bartlett et al. (2019)), we can bound the generalization gap by $\epsilon/2$. $\square$

To prove Theorem 4, we show that, for a large enough CNN, the k-pattern problem becomes linearly separable, after applying the first layer of the randomly initialized CNN:

Lemma 6. *Assume we uniformly initialize $W \sim \{\pm 1/k\}^{q \times k}$ and $b_i = 1/k - 1$. Fix some $\delta > 0$. Then if $q > 2^{k+3} \log(2^k/\delta)$, w.p. $\geq 1 - \delta$ over the choice of W, for every k-pattern f there exist $\mathbf{u}^{*(1)}, \ldots, \mathbf{u}^{*(n-k)} \in \mathbb{R}^q$ with $\left\| \mathbf{u}^{*(j^*)} \right\| \leq \frac{2^{k+1}k}{\sqrt{q}}$ and $\left\| \mathbf{u}^{*(j)} \right\| = 0$ for $j \neq j^*$, s.t. $h_{\mathbf{u}^*, W, b} = f(\mathbf{x})$.*

Proof. Fix some $\mathbf{z} \in \{\pm 1\}^k$, then for every $\mathbf{w}^{(i)} \sim \{\pm 1/k\}^k$, we have: $\mathbb{P}\left[\text{sign } \mathbf{w}^{(i)} = \mathbf{z}\right] = 2^{-k}$. Denote by $J_{\mathbf{z}} \subseteq [q]$ the subset of indexes satisfying $\text{sign } \mathbf{w}^{(i)} = \mathbf{z}$, for every $i \in J_{\mathbf{z}}$, and note that $\mathbb{E}_W |J_{\mathbf{z}}| = q2^{-k}$. From Chernoff bound:

$$\mathbb{P}\left[|J_{\mathbf{z}}| \leq q2^{-k}/2\right] \leq e^{-q2^{-k}/8} \leq \delta 2^{-k}$$

by choosing $q > 2^{k+3} \log(2^k/\delta)$. So, using the union bound, w.p. at least $1 - \delta$, for every $\mathbf{z} \in \{\pm 1\}^k$ we have $|J_{\mathbf{z}}| \geq q2^{-k-1}$. By the choice of b_i we have $\sigma(\langle \mathbf{w}^{(i)}, \mathbf{z} \rangle + b_i) = (1/k)\mathbf{1}\{\text{sign } \mathbf{w}^{(i)} = \mathbf{z}\}$.

Now, fix some k-pattern f, where $f(\mathbf{x}) = g(\mathbf{x}_{j^*, \ldots, j^*+k})$. For every $i \in J_{\mathbf{z}}$ we choose $\mathbf{u}_i^{*(j^*)} = \frac{k}{|J_{\mathbf{z}}|}g(\mathbf{z})$ and $\mathbf{u}^{*(j)} = 0$ for every $j \neq j^*$. Therefore, we get:

$$h_{\mathbf{u}^*, W, b}(\mathbf{x}) = \sum_{j=1}^{n-k} \left\langle \mathbf{u}^{*(j)}, \sigma(W\mathbf{x}_{j\ldots j+k} + \mathbf{b}) \right\rangle = \sum_{\mathbf{z} \in \{\pm 1\}^k} \sum_{i \in J_{\mathbf{z}}} \mathbf{u}_i^{*(j^*)} \sigma\left(\left\langle \mathbf{w}^{(i)}, \mathbf{x}_{j^*\ldots j^*+k} \right\rangle + b_i\right)$$

$$= \sum_{\mathbf{z} \in \{\pm 1\}^k} \mathbf{1}\{\mathbf{z} = \mathbf{x}_{j^*\ldots j^*+k}\}g(\mathbf{z}) = g(x_{j^*\ldots j^*+k}) = f(\mathbf{x})$$

Note that by definition of $\mathbf{u}^{*(j^*)}$ we have $\left\| \mathbf{u}^{*(j^*)} \right\|^2 = \sum_{\mathbf{z} \in \{\pm 1\}^k} \sum_{i \in J_{\mathbf{z}}} \frac{k^2}{|J_{\mathbf{z}}|^2} \leq 4\frac{(2^k k)^2}{q}$. $\square$

Comment 7. Admittedly, the initialization assumed above is non-standard, but is favorable for the analysis. A similar result can be shown for more natural initialization (e.g., normal distribution), using known results from random features analysis (for example, Bresler & Nagaraj (2020)).

From Lemma 6 and known results on learning linear classifiers with gradient-descent, solving the k-pattern problem can be achieved by optimizing the second layer of a randomly initialized CNN. However, since in gradient-descent we optimize both layers of the network, we need a more refined analysis to show that full gradient-descent learns to solve the problem. We follow the scheme introduced in Daniely (2017), adapting it our setting.

We start by showing that the first layer of the network does not deviate from the initialization during the training:

Lemma 8. *We have $\left\| \mathbf{u}^{(j,T)} \right\| \leq \eta T\sqrt{q}$ for all $j \in [n-k]$, and $\left\| W^{(0)} - W^{(T)} \right\| \leq c\eta^2 T^2 n\sqrt{qk}$*

We can now bound the difference in the loss when the weights of the first layer change during the training process:

Lemma 9. *For every $\mathbf{u}^*$ we have:*

$$\left| L_{f,\mathcal{D}}(h_{\mathbf{u}^*, W^{(T)}, b}) - L_{f,\mathcal{D}}(h_{\mathbf{u}^*, W^{(0)}, b}) \right| \leq c\eta^2 T^2 nk\sqrt{q} \sum_{j=1}^{n-k} \left\| \mathbf{u}^{*(j)} \right\|$$

The proofs of Lemma 8 and Lemma 9 are shown in the appendix.

Finally, we use the following result on the convergence of online gradient-descent to show that gradient-descent converges to a good solution. The proof of the Theorem is given in Shalev-Shwartz et al. (2011), with an adaptation to a similar setting in Daniely & Malach (2020).

Theorem 10. *(Online Gradient Descent) Fix some η, and let $f_1, \ldots, f_T$ be some sequence of convex functions. Fix some θ_1, and update $\theta_{t+1} = \theta_t - \eta \nabla f_t(\theta_t)$. Then for every θ^* the following holds:*

$$\frac{1}{T} \sum_{t=1}^{T} f_t(\theta_t) \leq \frac{1}{T} \sum_{t=1}^{T} f_t(\theta^*) + \frac{1}{2\eta T} \|\theta^*\|^2 + \|\theta_1\| \frac{1}{T} \sum_{t=1}^{T} \|\nabla f_t(\theta_t)\| + \eta \frac{1}{T} \sum_{t=1}^{T} \|\nabla f_t(\theta_t)\|^2$$

Proof. of Theorem 4. From Lemma 6, with probability at least $1 - \delta$ over the initialization, there exist $\mathbf{u}^{*(1)}, \ldots, \mathbf{u}^{*(n-k)} \in \mathbb{R}^q$ with $\|\mathbf{u}^{*(1)}\| \leq \frac{2^{k+1} k}{\sqrt{q}}$ and $\|\mathbf{u}^{*(j)}\| = 0$ for $j > 1$ such that $h_{\mathbf{u}^*, W^{(0)}, b}(\mathbf{x}) = f(\mathbf{x})$, and so $L_{f,\mathcal{D}}(h_{\mathbf{u}^*, W^{(0)}, b}) = 0$. Using Theorem 10, since $L_{f,\mathcal{D}}(h_{\mathbf{u}, W, b})$ is convex with respect to $\mathbf{u}$, we have:

$$\frac{1}{T} \sum_{t=1}^{T} L_{f,\mathcal{D}}(h_{\mathbf{u}^{(t)}, W^{(t)}, b})$$

$$\leq \frac{1}{T} \sum_{t=1}^{T} L_{f,\mathcal{D}}(h_{\mathbf{u}^*, W^{(t)}, b}) + \frac{1}{2\eta T} \sum_{j=1}^{n-k} \|\mathbf{u}^{*(j)}\|^2 + \eta \frac{1}{T} \sum_{t=1}^{T} \left\| \frac{\partial}{\partial \mathbf{u}} L_{f,\mathcal{D}}(f_{\mathbf{u}^{(t)}, W^{(t)}, b}) \right\|^2$$

$$\leq \frac{1}{T} \sum_{t=1}^{T} L_{f,\mathcal{D}}(h_{\mathbf{u}^*, W^{(t)}, b}) + \frac{2(2^k k)^2}{q\eta T} + c^2 \eta n q = (*)$$

Using Lemma 9 we have:

$$(*) \leq \frac{1}{T} \sum_{t=1}^{T} L_{f,\mathcal{D}}(h_{\mathbf{u}^*, W^{(0)}, b}) + c\eta^2 T^2 n k \sqrt{q} \sum_{j=1}^{n-k} \|\mathbf{u}^{*(j)}\| + \frac{2(2^k k)^2}{q\eta T} + c^2 \eta n q$$

$$\leq 2c\eta^2 T^2 n k^2 2^k + \frac{2(2^k k)^2}{q\eta T} + c^2 \eta n q$$

Now, choosing $\eta = \frac{\sqrt{n}}{\sqrt{qT}}$ we get the required. $\square$

3.1 ANALYSIS OF LOCALLY-CONNECTED NETWORKS

The above result shows that polynomial-size CNNs can learn $(\log n)$-patterns in polynomial time. As discussed in the introduction, the success of CNNs can be attributed to either the weight sharing or the locality-bias of the architecture. While weight sharing may contribute to the success of CNNs in some cases, we note that it gives no benefit when learning k-patterns. Indeed, we can show a similar positive result for locally-connected networks (LCN), which have no weight sharing.

Observe the following definition of a LCN with one hidden-layer:

Definition 11. *A **locally-connected network** $h_{\mathbf{u}, \mathbf{w}, \mathbf{b}}$ is defined as follows:*

$$h_{\mathbf{u}, W, \mathbf{b}}(\mathbf{x}) = \sum_{j=1}^{n-k} \left\langle \mathbf{u}^{(j)}, \sigma(W^{(j)} \mathbf{x}_{j \ldots j+k} + \mathbf{b}^{(j)}) \right\rangle$$

for some activation function σ, with $W^{(1)}, \ldots, W^{(q)} \in \mathbb{R}^{q \times k}$, bias $\mathbf{b}^{(1)}, \ldots, \mathbf{b}^{(q)} \in \mathbb{R}^q$ and readout layer $\mathbf{u}^{(1)}, \ldots, \mathbf{u}^{(n)} \in \mathbb{R}^q$.

Note that the only difference from Definition 1 is the fact that the weights of the first layer are not shared. It is easy to verify that Theorem 4 can be modified in order to show a similar positive result for LCN architectures. Specifically, we note that in Lemma 6, which is the core of the Theorem, we do not use the fact that the weights in the first layer are shared. So, LCNs are "as good as" CNNs for solving the k-pattern problem. This of course does not resolve the question of comparing between LCN and CNN architectures, which we leave for future work.

4   LEARNING $(\log n)$-PATTERNS WITH FCN

In the previous section we showed that patterns of size $\log n$ are efficiently learnable, when using CNNs trained with gradient-descent. In this section we show that, in contrast, gradient-descent fails to learn $(\log n)$-patterns using fully-connected networks, unless the size of the network is super-polynomial (namely, unless the network is of size $n^{\Omega(\log n)}$). For this, we will show an instance of the k-pattern problem that is hard for fully connected networks.

We take $\mathcal{D}$ to be the uniform distribution over $\mathcal{X}$, and let $f(\mathbf{x}) = \prod_{i \in I} x_i$, where I is some set of k consecutive bits. Specifically, we take $I = \{1, \ldots, k\}$, although the same proof holds for any choice of I. In this case, we show that the initial gradient of the network is very small, when a fully-connected network is initialized from a permutation invariant distribution.

Theorem 12. *Assume $|\sigma| \le c, |\sigma'| \le 1$. Let $\mathcal{W}$ be some permutation invariant distribution over $\mathbb{R}^n$, and assume we initialize $\mathbf{w}^{(1)}, \ldots, \mathbf{w}^{(q)} \sim \mathcal{W}$ and initialize $\mathbf{u}$ such that $|u_i| \le 1$ and for all $\mathbf{x}$ we have $h_{\mathbf{u},\mathbf{w}}(\mathbf{x}) \in [-1, 1]$. Then, the following holds:*

- $\mathbb{E}_{\mathbf{w} \sim \mathcal{W}} \left\| \frac{\partial}{\partial W} L_{f,\mathcal{D}}(h_{\mathbf{u},\mathbf{w},\mathbf{b}}) \right\|_2^2 \le qn \cdot \min \left\{ \binom{n-1}{k}^{-1}, \binom{n-1}{k-1}^{-1} \right\}$

- $\mathbb{E}_{\mathbf{w} \sim \mathcal{W}} \left\| \frac{\partial}{\partial \mathbf{u}} L_{f,\mathcal{D}}(h_{\mathbf{u},\mathbf{w},\mathbf{b}}) \right\|_2^2 \le c^2 q \binom{n}{k}^{-1}$

From the above result, if $k = \Omega(\log n)$ then the norm of initial gradient is $qn^{-\Omega(\log n)}$. Therefore, unless $q = n^{\Omega(\log n)}$, GD will be "stuck" upon initialization, and will fail on the k-pattern problem.

The key for proving Theorem 12 is the following observation: since the first layer of the FCN is initialized from a symmetric distribution, we observe that if learning *some* function that relies on k bits of the input is hard, then learning *any* function that relies on k bits is hard. Using Fourier analysis (e.g., Blum et al. (1994); Kearns (1998); Shalev-Shwartz et al. (2017a)), we can show that learning k-parities (functions of the form $\mathbf{x} \mapsto \prod_{i \in I} x_i$) using gradient-descent is hard. Since an arbitrary k-parity is hard, then any k-parity, and specifically a parity of k consecutive bits, is also hard. That is, since the first layer is initialized symmetrically, training a FCN on the original input is equivalent to training a FCN on an input where all the input bits are randomly permuted. So, for a FCN, learning a function that depends on consecutive bits is just as hard as learning a function that depends on arbitrary bits (a task that is known to be hard).

Proof. of Theorem 12. Denote $\chi_{I'} = \prod_{i \in I'} x_i$, so $f(\mathbf{x}) = \chi_I$ with $I = \{1, \ldots, k\}$. We begin by calculating the gradient w.r.p. to $\mathbf{w}_j^{(i)}$:

$$\frac{\partial}{\partial \mathbf{w}_j^{(i)}} L_{f,\mathcal{D}}(h_{\mathbf{u},\mathbf{w},\mathbf{b}}) = \mathbb{E}_{\mathcal{D}} \left[\frac{\partial}{\partial \mathbf{w}_j^{(i)}} \ell(h_{\mathbf{u},\mathbf{w},\mathbf{b}}(\mathbf{x}), f(\mathbf{x})) \right] = -\mathbb{E}_{\mathcal{D}} \left[x_j u_i \sigma' \left(\left\langle \mathbf{w}^{(i)}, \mathbf{x} \right\rangle + b_i \right) \chi_I(\mathbf{x}) \right]$$

Fix some permutation $\pi : [n] \to [n]$. For some vector $\mathbf{x} \in \mathbb{R}^n$ we denote $\pi(\mathbf{x}) = (x_{\pi(1)}, \ldots, x_{\pi(n)})$, for some subset $I \subseteq [n]$ we denote $\pi(I) = \cup_{j \in I} \{\pi(j)\}$. Notice that we have for all $\mathbf{x}, \mathbf{z} \in \mathbb{R}^n$: $\chi_I(\pi(\mathbf{x})) = \chi_{\pi(I)}$ and $\langle \pi(\mathbf{x}), \mathbf{z} \rangle = \langle \mathbf{x}, \pi^{-1}(\mathbf{z}) \rangle$. Denote $\pi(h_{\mathbf{u},\mathbf{w},\mathbf{b}})(\mathbf{x}) = \sum_{i=1}^k u_i \sigma(\langle \pi(\mathbf{w}^{(i)}), \mathbf{x} \rangle + b_i)$. Denote $\pi(\mathcal{D})$ the distribution of $\pi(\mathbf{x})$ where $\mathbf{x} \sim \mathcal{D}$. Notice that since $\mathcal{D}$ is the uniform distribution, we have $\pi(\mathcal{D}) = \mathcal{D}$. From all the above, for every permutation π with $\pi(j) = j$ we have:

$$-\frac{\partial}{\partial \mathbf{w}_j^{(i)}} L_{\chi_{\pi(I)},\mathcal{D}}(h_{\mathbf{u},\mathbf{w},\mathbf{b}}) = \mathbb{E}_{\mathbf{x} \sim \mathcal{D}} \left[x_j u_i \sigma' \left(\left\langle \mathbf{w}^{(i)}, \mathbf{x} \right\rangle + b_i \right) \chi_{\pi(I)}(\mathbf{x}) \right]$$

$$= \mathbb{E}_{\mathbf{x} \sim \pi(\mathcal{D})} \left[x_j u_i \sigma' \left(\left\langle \mathbf{w}^{(i)}, \pi^{-1}(\mathbf{x}) \right\rangle + b_i \right) \chi_I(\mathbf{x}) \right]$$

$$= \mathbb{E}_{\mathbf{x} \sim \mathcal{D}} \left[x_j u_i \sigma' \left(\left\langle \pi(\mathbf{w}^{(i)}), \mathbf{x} \right\rangle + b_i \right) \chi_I(\mathbf{x}) \right] = -\frac{\partial}{\partial \mathbf{w}_j^{(i)}} L_{\chi_I,\mathcal{D}}(\pi(h_{\mathbf{u},\mathbf{w},\mathbf{b}}))$$

Fix some $I \subseteq [n]$ with $|I| = k$ and $j \in [n]$. Now, let S_j be a set of permutations satisfying:

1. For all $\pi_1, \pi_2 \in S_j$ with $\pi_1 \neq \pi_2$ we have $\pi_1(I) \neq \pi_2(I)$.

2. For all $\pi \in S_j$ we have $\pi(j) = j$.

Note that if $j \notin I$ then the maximal size of such S_j is $\binom{n-1}{k}$, and if $j \in I$ then the maximal size is $\binom{n-1}{k-1}$. Denote $g_j(\mathbf{x}) = x_j u_i \sigma'(\langle \mathbf{w}^{(i)}, \mathbf{x} \rangle + b_i)$. We denote the inner-product $\langle \psi, \phi \rangle_{\mathcal{D}} = \mathbb{E}_{\mathbf{x} \sim \mathcal{D}}[\psi(\mathbf{x})\phi(\mathbf{x})]$ and the induced norm $\|\psi\|_{\mathcal{D}} = \sqrt{\langle \psi, \psi \rangle_{\mathcal{D}}}$. Since $\{\chi_{I'}\}_{I' \subseteq [n]}$ is an orthonormal basis w.r.p. to $\langle \cdot, \cdot \rangle_{\mathcal{D}}$ from Parseval's equality we have:

$$\sum_{\pi \in S_j} \left(\frac{\partial}{\partial \mathbf{w}_j^{(i)}} L_{\chi_I, \mathcal{D}}(\pi(h_{\mathbf{u},\mathbf{w},\mathbf{b}})) \right)^2 = \sum_{\pi \in S} \left(\frac{\partial}{\partial \mathbf{w}_j^{(i)}} L_{\chi_{\pi(I)}, \mathcal{D}}(h_{\mathbf{u},\mathbf{w},\mathbf{b}}) \right)^2$$
$$= \sum_{\pi \in S} \langle g_j, \chi_{\pi(I)} \rangle_{\mathcal{D}}^2 \leq \sum_{I' \subseteq [n]} \langle g_j, \chi_{I'} \rangle_{\mathcal{D}}^2 = \|g_j\|_{\mathcal{D}}^2 \leq 1$$

So, from the above we get that, taking S_j of maximal size:

$$\mathbb{E}_{\pi \sim S_j} \left(\frac{\partial}{\partial \mathbf{w}_j^{(i)}} L_{\chi_I, \mathcal{D}}(\pi(h_{\mathbf{u},\mathbf{w},\mathbf{b}})) \right)^2 \leq |S_j|^{-1} \leq \min \left\{ \binom{n-1}{k}^{-1}, \binom{n-1}{k-1}^{-1} \right\}$$

Now, for some permutation invariant distribution of weights $\mathcal{W}$ we have:

$$\mathbb{E}_{\mathbf{w} \sim \mathcal{W}} \left(\frac{\partial}{\partial \mathbf{w}_j^{(i)}} L_{\chi_I, \mathcal{D}}(h_{\mathbf{u},\mathbf{w},\mathbf{b}}) \right)^2 = \mathbb{E}_{\mathbf{w} \sim \mathcal{W}} \mathbb{E}_{\pi \sim S_j} \left(\frac{\partial}{\partial \mathbf{w}_j^{(i)}} L_{\chi_I, \mathcal{D}}(\pi(h_{\mathbf{u},\mathbf{w},\mathbf{b}})) \right)^2 \leq |S_j|^{-1}$$

Summing over all neurons we get:

$$\mathbb{E}_{\mathbf{w} \sim \mathcal{W}} \left\| \frac{\partial}{\partial W} L_{\chi_I, \mathcal{D}}(h_{\mathbf{u},\mathbf{w},\mathbf{b}}) \right\|_2^2 \leq qn \cdot \min \left\{ \binom{n-1}{k}^{-1}, \binom{n-1}{k-1}^{-1} \right\}$$

We can use a similar argument to bound the gradient of $\mathbf{u}$. We leave the details to the appendix. $\quad\square$

5 NEURAL ARCHITECTURE SEARCH

So far, we showed that while the $(\log n)$-pattern problem can be solved efficiently using a CNN, this problem is hard for a FCN to solve. Since the CNN architecture is designed for processing consecutive patterns of the inputs, it can easily find the pattern that determines the label. The FCN, however, disregards the order of the input bits, and so it cannot enjoy from the fact that the bits which determine the label are consecutive. In other words, the FCN architecture needs to learn the order of the bits, while the CNN already encodes this order in the architecture.

So, a FCN fails to recover the k-pattern since it does not assume anything about the order of the input bits. But, is it be possible to recover the order of the bits prior to training the network? Can we apply some algorithm that searches for an optimal architecture to solve the k-pattern problem? Such motivation stands behind the thriving research field of Neural Architecture Search algorithms (see Elsken et al. (2018) for a survey).

Unfortunately, we claim that if the order of the bits is not known to the learner, *no architecture search algorithm can help in solving the k-pattern problem*. To see this, it is enough to observe that when the order of the bits is unknown, the k-pattern problem is equivalent to the k-Junta problem: learning a function that depends on an arbitrary (not necessarily consecutive) set of k bits from the input. Learning k-Juntas is a well-studied problem in the literature of learning theory (e.g., Mossel et al. (2003)). The best algorithm for solving the $(\log n)$-Junta problem runs in time $n^{O(\log n)}$, and no poly-time algorithm is known for solving this problem. Moreover, if we consider statistical-query algorithms (a wide family of algorithms, that only have access to estimations of query function on the distribution, e.g. Blum et al. (2003)), then existing lower bounds show that the $(\log n)$-Junta problem **cannot** be solved in polynomial time (Blum et al., 1994).

Figure 3: Top: Performance of different architectures on a size-n MNIST sequences, where the label is determined by the parity of the central 3 digits. Bottom: MNIST sequences of varying length.

6 EXPERIMENTS

In the previous sections we showed a simplistic learning problem that can be solved using CNNs and LCNs, but is hard to solve using FCNs. In this problem, the label is determined by a few *consecutive* bits of the input. In this section we show some experiments that validate our theoretical results. In these experiments, the input to the network is a sequence of n MNIST digits, where each digit is scaled and cropped to a size of 24×8. We then train three different network architectures: FCN, CNN and LCN. The CNN and LCN architectures have kernels of size 24×24, so that 3 MNIST digits fit in a single kernel. In all the architectures we use a single hidden-layer with 1024 neurons, and ReLU activation. The networks are trained with AdaDelta optimizer for 30 epochs [1].

In the first experiment, the label of the example is set to be the parity of the sum of the 3 consecutive digits located in the middle of the sequence. So, as in our theoretical analysis, the label is determined by a small area of consecutive bits of the input. Figure 3 shows the results of this experiment. As can be clearly seen, the CNN and LCN architectures achieve good performance regardless of the choice of n, where the per-formance of the FCN architec-

Figure 4: n-sequence MNIST with non-consecutive parity.

tures critically degrades for larger n, achieving only chance-level performance when $n = 19$. We also observe that LCN has a clear advantage over CNN in this task. As noted, our primary focus is on demonstrating the superiority of locality-based architectures, such as CNN and LCN, and we leave the comparison between the two to future work.

Our second experiment is very similar to the first, but instead of taking the label to be the parity of 3 consecutive digits, we calculate the label based on 3 digits that are far apart. Namely, we take the parity of the first, middle and last digits of the sequence. The results of this experiment are shown in Figure 4. As can be seen, for small n, FCN performs much better than CNN and LCN. This demonstrates that when we break the local structure, the advantage of CNN and LCN disappears, and using FCN becomes a better choice. However, for large n, all architectures perform poorly.

---

[1]In each epoch we randomly shuffle the sequence of the digits.

REFERENCES

Peter L Bartlett, Nick Harvey, Christopher Liaw, and Abbas Mehrabian. Nearly-tight vc-dimension and pseudodimension bounds for piecewise linear neural networks. *J. Mach. Learn. Res.*, 20: 63–1, 2019.

Avrim Blum, Merrick Furst, Jeffrey Jackson, Michael Kearns, Yishay Mansour, and Steven Rudich. Weakly learning dnf and characterizing statistical query learning using fourier analysis. In *Proceedings of the twenty-sixth annual ACM symposium on Theory of computing*, pp. 253–262, 1994.

Avrim Blum, Adam Kalai, and Hal Wasserman. Noise-tolerant learning, the parity problem, and the statistical query model. *Journal of the ACM (JACM)*, 50(4):506–519, 2003.

Guy Bresler and Dheeraj Nagaraj. A corrective view of neural networks: Representation, memorization and learning. *arXiv preprint arXiv:2002.00274*, 2020.

Joan Bruna, Wojciech Zaremba, Arthur Szlam, and Yann LeCun. Spectral networks and locally connected networks on graphs. *arXiv preprint arXiv:1312.6203*, 2013.

Alon Brutzkus and Amir Globerson. Globally optimal gradient descent for a convnet with gaussian inputs. *arXiv preprint arXiv:1702.07966*, 2017.

Yu-hsin Chen, Ignacio Lopez-Moreno, Tara N Sainath, Mirkó Visontai, Raziel Alvarez, and Carolina Parada. Locally-connected and convolutional neural networks for small footprint speaker recognition. In *Sixteenth Annual Conference of the International Speech Communication Association*, 2015.

Nadav Cohen and Amnon Shashua. Inductive bias of deep convolutional networks through pooling geometry. *arXiv preprint arXiv:1605.06743*, 2016.

Nadav Cohen, Or Sharir, Yoav Levine, Ronen Tamari, David Yakira, and Amnon Shashua. Analysis and design of convolutional networks via hierarchical tensor decompositions. *arXiv preprint arXiv:1705.02302*, 2017.

Amit Daniely. Sgd learns the conjugate kernel class of the network. In *Advances in Neural Information Processing Systems*, pp. 2422–2430, 2017.

Amit Daniely and Eran Malach. Learning parities with neural networks. *arXiv preprint arXiv:2002.07400*, 2020.

S Ben Driss, Mahmoud Soua, Rostom Kachouri, and Mohamed Akil. A comparison study between mlp and convolutional neural network models for character recognition. In *Real-Time Image and Video Processing 2017*, volume 10223, pp. 1022306. International Society for Optics and Photonics, 2017.

Simon S Du, Xiyu Zhai, Barnabas Poczos, and Aarti Singh. Gradient descent provably optimizes over-parameterized neural networks. *arXiv preprint arXiv:1810.02054*, 2018.

Thomas Elsken, Jan Hendrik Metzen, and Frank Hutter. Neural architecture search: A survey. *arXiv preprint arXiv:1808.05377*, 2018.

Chrisantha Fernando, Dylan Banarse, Malcolm Reynolds, Frederic Besse, David Pfau, Max Jaderberg, Marc Lanctot, and Daan Wierstra. Convolution by evolution: Differentiable pattern producing networks. In *Proceedings of the Genetic and Evolutionary Computation Conference 2016*, pp. 109–116, 2016.

Eric Kauderer-Abrams. Quantifying translation-invariance in convolutional neural networks. *arXiv preprint arXiv:1801.01450*, 2017.

Osman Semih Kayhan and Jan C van Gemert. On translation invariance in cnns: Convolutional layers can exploit absolute spatial location. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14274–14285, 2020.

Michael Kearns. Efficient noise-tolerant learning from statistical queries. *Journal of the ACM (JACM)*, 45(6):983–1006, 1998.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pp. 1097–1105, 2012.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Yuanzhi Li and Yingyu Liang. Learning overparameterized neural networks via stochastic gradient descent on structured data. In *Advances in Neural Information Processing Systems*, pp. 8157–8166, 2018.

Zhouhan Lin, Roland Memisevic, and Kishore Konda. How far can we go without convolution: Improving fully-connected networks. *arXiv preprint arXiv:1511.02580*, 2015.

Wen Liu, Hong Chen, Zhongliang Deng, Xinyu Zheng, Xiao Fu, and Qianqian Cheng. Lc-dnn: Local connection based deep neural network for indoor localization with csi. *IEEE Access*, 8: 108720–108730, 2020.

Eran Malach and Shai Shalev-Shwartz. A provably correct algorithm for deep learning that actually works. *arXiv preprint arXiv:1803.09522*, 2018.

Elchanan Mossel. Deep learning and hierarchal generative models. *arXiv preprint arXiv:1612.09057*, 2016.

Elchanan Mossel, Ryan O'Donnell, and Rocco P Servedio. Learning juntas. In *Proceedings of the thirty-fifth annual ACM symposium on Theory of computing*, pp. 206–212, 2003.

Behnam Neyshabur. Towards learning convolutions from scratch. *arXiv preprint arXiv:2007.13657*, 2020.

Roman Novak, Lechao Xiao, Jaehoon Lee, Yasaman Bahri, Greg Yang, Jiri Hron, Daniel A Abolafia, Jeffrey Pennington, and Jascha Sohl-Dickstein. Bayesian deep convolutional networks with many channels are gaussian processes. *arXiv preprint arXiv:1810.05148*, 2018.

Tomaso Poggio, Fabio Anselmi, and Lorenzo Rosasco. I-theory on depth vs width: hierarchical function composition. Technical report, Center for Brains, Minds and Machines (CBMM), 2015.

Tomaso Poggio, Hrushikesh Mhaskar, Lorenzo Rosasco, Brando Miranda, and Qianli Liao. Why and when can deep-but not shallow-networks avoid the curse of dimensionality: a review. *International Journal of Automation and Computing*, 14(5):503–519, 2017.

Shai Shalev-Shwartz, Ohad Shamir, and Shaked Shammah. Failures of gradient-based deep learning. *arXiv preprint arXiv:1703.07950*, 2017a.

Shai Shalev-Shwartz, Ohad Shamir, and Shaked Shammah. Weight sharing is crucial to succesful optimization. *arXiv preprint arXiv:1706.00687*, 2017b.

Shai Shalev-Shwartz et al. Online learning and online convex optimization. *Foundations and trends in Machine Learning*, 4(2):107–194, 2011.

Mahdi Soltanolkotabi, Adel Javanmard, and Jason D Lee. Theoretical insights into the optimization landscape of over-parameterized shallow neural networks. *IEEE Transactions on Information Theory*, 65(2):742–769, 2018.

Gregor Urban, Krzysztof J Geras, Samira Ebrahimi Kahou, Ozlem Aslan, Shengjie Wang, Rich Caruana, Abdelrahman Mohamed, Matthai Philipose, and Matt Richardson. Do deep convolutional nets really need to be deep and convolutional? *International Conference on Learning Representations*, 2017.

Yuchen Zhang, Percy Liang, and Martin J Wainwright. Convexified convolutional neural networks. In *International Conference on Machine Learning*, pp. 4044–4053. PMLR, 2017.

A ADDITIONAL PROOFS

Proof. of Lemma 8.

We denote $h^{(t)} := h_{\mathbf{u}^{(t)},W^{(t)},b}$. For every j we have:

$$\frac{\partial}{\partial \mathbf{u}^{(j)}} L_{f,\mathcal{D}}(h^{(t)}) = \mathop{\mathbb{E}}_{\mathbf{x}\sim\mathcal{D}}\left[\frac{\partial}{\partial \mathbf{u}^{(j)}}\ell(h^{(t)}(\mathbf{x}),f(\mathbf{x}))\right] = \mathop{\mathbb{E}}_{\mathbf{x}\sim\mathcal{D}}\left[\sigma(W^{(t)}x_{j\ldots j+k})\ell'(h^{(t)}(\mathbf{x}),f(\mathbf{x}))\right]$$

Therefore:

$$\left\|\frac{\partial}{\partial \mathbf{u}^{(j)}} L_{f,\mathcal{D}}(h^{(t)})\right\| \le \mathop{\mathbb{E}}_{\mathbf{x}\sim\mathcal{D}}\left[\left\|\sigma(W^{(t)}x_{j\ldots j+k})\right\|\right] \le c\sqrt{q}$$

And from the updates of gradient-descent we have:

$$\left\|\mathbf{u}^{(j,t)}\right\| = \left\|\eta\sum_{t=1}^{T}\frac{\partial}{\partial \mathbf{u}^{(j)}} L_{f,\mathcal{D}}(h^{(t)})\right\| \le \eta\sum_{t=1}^{T}\left\|\frac{\partial}{\partial \mathbf{u}^{(j)}} L_{f,\mathcal{D}}(h^{(t)})\right\| \le c\eta T\sqrt{q}$$

Now, we have that:

$$\frac{\partial}{\partial W} L_{f,\mathcal{D}}(h^{(t)}) = \mathop{\mathbb{E}}_{\mathbf{x}\sim\mathcal{D}}\left[\sum_{j=1}^{n-k}\mathbf{u}^{(j,t)}\mathbf{x}_{j\ldots j+k}^{\top}\sigma'(W^{(t)}\mathbf{x}_{j\ldots j+k}+b)\ell'(h^{(t)}(\mathbf{x}),f(\mathbf{x}))\right]$$

And so:

$$\left\|\frac{\partial}{\partial W} L_{f,\mathcal{D}}(h^{(t)})\right\| \le \mathop{\mathbb{E}}_{\mathbf{x}\sim\mathcal{D}}\left[\sum_{j=1}^{n-k}\left\|\mathbf{u}^{(j,t)}\right\|\|\mathbf{x}_{j\ldots j+k}\|\right] \le c(n-k)\eta T\sqrt{q}\sqrt{k}$$

Again, by the updates of gradient-descent:

$$\left\|W^{(T)}-W^{(0)}\right\| = \left\|\eta\sum_{t=1}^{T}\frac{\partial}{\partial W} L_{f,\mathcal{D}}(h^{(t)})\right\| \le \eta\sum_{t=1}^{T}\left\|\frac{\partial}{\partial W} L_{f,\mathcal{D}}(h^{(t)})\right\| \le c\eta^2 T^2 n\sqrt{qk}$$

$\square$

Proof. of Lemma 9

$$\left|L_{f,\mathcal{D}}(h_{\mathbf{u}^*,W^{(T)},b}) - L_{f,\mathcal{D}}(h_{\mathbf{u}^*,W^{(0)},b})\right|$$

$$= \left|\mathop{\mathbb{E}}_{\mathbf{x}\sim\mathcal{D}}\left[\ell(h_{\mathbf{u}^*,W^{(T)},b}(\mathbf{x}),f(\mathbf{x}))\right] - \mathop{\mathbb{E}}_{\mathbf{x}\sim\mathcal{D}}\left[\ell(h_{\mathbf{u}^*,W^{(0)},b}(\mathbf{x}),f(\mathbf{x}))\right]\right|$$

$$\le \mathop{\mathbb{E}}_{\mathbf{x}\sim\mathcal{D}}\left[\left|\ell(h_{\mathbf{u}^*,W^{(T)},b}(\mathbf{x}),f(\mathbf{x})) - \ell(h_{\mathbf{u}^*,W^{(0)},b}(\mathbf{x}),f(\mathbf{x}))\right|\right]$$

$$\le \mathop{\mathbb{E}}_{\mathbf{x}\sim\mathcal{D}}\left[\left|h_{\mathbf{u}^*,W^{(T)},b}(\mathbf{x}) - h_{\mathbf{u}^*,W^{(0)},b}(\mathbf{x})\right|\right]$$

$$= \mathop{\mathbb{E}}_{\mathbf{x}\sim\mathcal{D}}\left[\left|\sum_{j=1}^{n-k}\left\langle\mathbf{u}^{*(j)},\sigma(W^{(T)}\mathbf{x}_{j\ldots j+k}+\mathbf{b}) - \sigma(W^{(0)}\mathbf{x}_{j\ldots j+k}+\mathbf{b})\right\rangle\right|\right]$$

$$\le \mathop{\mathbb{E}}_{\mathbf{x}\sim\mathcal{D}}\left[\sum_{j=1}^{n-k}\left\|\mathbf{u}^{*(j)}\right\|\left\|\sigma(W^{(T)}\mathbf{x}_{j\ldots j+k}+\mathbf{b}) - \sigma(W^{(0)}\mathbf{x}_{j\ldots j+k}+\mathbf{b})\right\|\right]$$

$$\le \mathop{\mathbb{E}}_{\mathbf{x}\sim\mathcal{D}}\left[\sum_{j=1}^{n-k}\left\|\mathbf{u}^{*(j)}\right\|\left\|W^{(T)}-W^{(0)}\right\|\|\mathbf{x}_{j\ldots j+k}\|\right] \le c\eta^2 T^2 nk\sqrt{q}\sum_{j=1}^{n-k}\left\|\mathbf{u}^{*(j)}\right\|$$

$\square$

Proof. (second part of Theorem 12)

For some π, observe that:

$$\frac{\partial}{\partial u_i} L_{\chi_{\pi(I)}, \mathcal{D}}(h_{\mathbf{u},\mathbf{w},\mathbf{b}}) = -\mathop{\mathbb{E}}_{\mathbf{x} \sim \mathcal{D}} \left[\sigma \left(\left\langle \mathbf{w}^{(i)}, \mathbf{x} \right\rangle + b_i \right) \chi_I(\pi(\mathbf{x})) \right]$$

$$= -\mathop{\mathbb{E}}_{\mathbf{x} \sim \mathcal{D}} \left[\sigma \left(\left\langle \pi(\mathbf{w}^{(i)}), \mathbf{x} \right\rangle + b_i \right) \chi_I(\mathbf{x}) \right] = \frac{\partial}{\partial u_i} L_{\chi_I, \mathcal{D}}(\pi(h_{\mathbf{u},\mathbf{w},\mathbf{b}}))$$

Let S be a maximal set of permutations such that for every $\pi_1 \neq \pi_2 \in S$ we have $\pi_1(I) \neq \pi_2(I)$, and note that $|S| = \binom{n}{k}$. Let $g_i(\mathbf{x}) = \sigma \left(\left\langle \mathbf{w}^{(i)}, \mathbf{x} \right\rangle + b_i \right)$ and note that $\|g_i\|_{\mathcal{D}}^2 \leq c^2$. Therefore:

$$\sum_{\pi \in S_j} \left(\frac{\partial}{\partial u_i} L_{\chi_I, \mathcal{D}}(\pi(h_{\mathbf{u},\mathbf{w},\mathbf{b}})) \right)^2 = \sum_{\pi \in S} \left(\frac{\partial}{\partial u_i} L_{\chi_{\pi(I)}, \mathcal{D}}(h_{\mathbf{u},\mathbf{w},\mathbf{b}}) \right)^2$$

$$= \sum_{\pi \in S} \left\langle g_i, \chi_{\pi(I)} \right\rangle_{\mathcal{D}}^2 \leq \sum_{I' \subseteq [n]} \left\langle g_i, \chi_{I'} \right\rangle_{\mathcal{D}}^2 = \|g_i\|_{\mathcal{D}}^2 \leq c^2$$

And therefore:

$$\mathop{\mathbb{E}}_{\mathbf{w} \sim \mathcal{W}} \left\| \frac{\partial}{\partial \mathbf{u}} L_{\chi_I, \mathcal{D}}(h_{\mathbf{u},\mathbf{w},\mathbf{b}}) \right\|_2^2 = \mathop{\mathbb{E}}_{\mathbf{w} \sim \mathcal{W}} \mathop{\mathbb{E}}_{\pi \sim S} \left\| \frac{\partial}{\partial \mathbf{u}} L_{\chi_I, \mathcal{D}}(\pi(h_{\mathbf{u},\mathbf{w},\mathbf{b}})) \right\|_2^2 \leq c^2 q \binom{n}{k}^{-1}$$

$\square$