KnowMeBenchV2: Evidence-Grounded Person-Centric Long-Video Understanding

Abstract

Questions about a recurring person in long videos are rarely answered from a single moment. They require evidence that is sufficient for the claim, comparisons across episodes, synthesis over recurring audiovisual patterns, and refusal when the source material does not support an answer. Existing long-video benchmarks do not isolate these requirements. We introduce KnowMeBenchV2, an evaluation-only benchmark over five public multi-episode video series, with 327 videos and 3,061 questions covering four evidence scopes: single-clip extraction, temporal and event relations, cross-episode ordering, and cross-episode persona synthesis. A separate grounded-abstention task serves as a contrastive support check: its questions are surface-similar to supported person-linked questions but are not licensed by the source evidence. The most interpretive synthesis items are human-authored and quality-audited by trained annotators with full source access. A matched human reference reaches 78.0 on cross-episode synthesis. To diagnose failures, we compare evidence routes under a fixed Qwen3.5-9B answerer and matched evidence budget. ASR-Retrieval reaches 2.7 on synthesis, while PTH reaches 64.9. The gap shows that recurring-person video understanding is limited not only by answer generation, but by how audiovisual evidence is selected, compressed, and organized before inference.

1 Introduction

Lifelong digital companions must build evidence-grounded accounts of a person: what someone tends to do, how they respond in context, which patterns recur, and when the evidence is too weak for a claim. KnowMe-Bench (Wu et al., 2026) framed this as person understanding over autobiographical experience and showed that factual recall is only one part of personal memory; models must also infer subjective states and higher-level principles from time-anchored evidence. That benchmark kept the substrate textual, however, distilling every person-level signal into written autobiographical narrative before evaluation.

Real personal experience is not text. A preference may surface only through silent choices made across episodes; a habit may appear as a recurring object, gesture, or setting; an emotional tendency may be visible in a facial reaction long before it is articulated. Person- and character-centric video work shows that much of this signal lives outside the transcript (Zhou et al., 2024b; Meng et al., 2025; Song et al., 2024; Zhang et al., 2025), and evidence-grounded video reasoning treats the visual track as a primary, not auxiliary, source of evidence (Wei et al., 2026; Luo et al., 2025; Yuan et al., 2025). KnowMeBenchV2 is the audiovisual successor to KnowMe-Bench: it inherits the evidence-grounded view of person understanding but lifts the substrate from autobiographical text to multi-episode video so that visual, auditory, and temporal cues remain first-class.

No existing benchmark answers whether systems can form such accounts from audiovisual evidence across episodes. Long-video QA scores answer correctness without isolating person-linked evidence sufficiency or cross-episode persona synthesis (Fu et al., 2025; Zhou et al., 2024a; Wu et al., 2024b; Li et al., 2024; Mangalam et al., 2023; Chandrasegaran et al., 2024; Wang et al., 2024; Ataallah et al., 2025; Ma et al., 2025); narrative and human-centric benchmarks reason about plots, characters, or emotions without treating audiovisual evidence as accumulating personal memory (Tapaswi et al., 2016; Lei et al., 2018; Zhang et al., 2025; Song et al., 2024; Zhou et al., 2024b; Meng et al., 2025); long-term memory benchmarks operate over dialogue or text rather than continuous audiovisual signal (Maharana et al., 2024; Wu et al., 2024a; Hu et al., 2026). We therefore ask: (**RQ1**) can current systems form grounded person-level accounts from audiovisual evidence at scopes from single clip to full series; (**RQ2**) how much do failures depend on the evidence representation supplied to the answerer; and (**RQ3**) how large is the gap to a matched human reference?

A benchmark that answers these questions should satisfy four design constraints: (**D1**) evi-

Figure 1: **KnowMeBenchV2 at a glance.** *Left:* task examples and the evidence-scope ladder—T1–T4 integrate evidence at increasing scope, while T5 tests grounded abstention. *Right:* aggregate radar view of representative systems and the human reference. The largest separation appears on cross-episode synthesis, where organized audiovisual evidence closes much of the gap left by transcript-only retrieval.

dence scope graded from single clip to full series so the failure point can be localized; (**D2**) person-centric content over recurring subjects rather than generic long video; (**D3**) contrastive grounded abstention, where unsupported items are surface-similar to supported person-linked questions and test evidence-boundary recognition; and (**D4**) a matched human reference collected under the same source-identifier interface, prompts, and rubric as systems. We instantiate these in KnowMeBenchV2, an evaluation-only benchmark for audiovisual personal memory, comprising five public multi-episode video series, 327 source videos, and 3,061 scored questions. The main tasks form a four-step evidence-scope ladder addressing D1–D2: information extraction (T1), temporal and event relations (T2), cross-episode ordering (T3), and cross-episode persona synthesis (T4); a separate grounded-abstention task (T5) addresses D3 and is reported on its own axis.

The most interpretive part of KnowMeBenchV2 is built around human expertise. T4 synthesis items are human-authored by trained annotators who watch complete source series and write questions whose answers require evidence from multiple separately recorded videos. Human audit checks source support, answerability, cross-episode scope, near-duplicate items, and over-interpretation risk. For the human reference, annotators answer questions on source series they did not author, under the same source-identifier interface and scoring protocol used for systems. This design makes the benchmark auditable while keeping the person-level claims tied to observable audiovisual evidence.

To answer RQ2, we compare evidence routes under a fixed Qwen3.5-9B answerer and matched evidence budget. The ASR-Retrieval route supplies retrieved speech-transcript chunks, while PTH supplies routed textual summaries constructed from audiovisual evidence. This diagnostic does not test a new answer model; it measures how performance changes when the evidence representation changes. On cross-episode persona synthesis, ASR-Retrieval reaches 2.7, while PTH reaches 64.9 under the same answerer; the matched human reference is 78.0. The same analysis also exposes an ordering tradeoff: ASR-Flat-32K remains stronger on T3, showing that hierarchical compression can lose rank-sensitive details even when it improves synthesis.

In summary, we make four contributions:

- **Benchmark.** We introduce KnowMeBenchV2, an audiovisual successor to KnowMe-Bench (Wu et al., 2026) that evaluates evidence-grounded recurring-person understanding over five public multi-episode video series.

- **Evidence-scope tasks and abstention.** We define a four-step evidence-scope ladder from localized extraction to cross-episode synthesis, plus a grounded-abstention task that

serves as a contrastive support check for open-form person-centric evaluation.

- **Human-authored synthesis and quality audit.** We construct the most interpretive synthesis items through trained annotators with full source-series access, source-support checks, over-interpretation filtering, and a matched human reference.

- **Diagnostic findings.** We evaluate representative long-video systems and fixed-answerer evidence routes, showing that local video grounding and cross-episode evidence organization are distinct bottlenecks. Under matched answerer and budget, routed audiovisual evidence raises T4 synthesis from 2.7 to 64.9, while T3 exposes an ordering cost from hierarchical compression.

2 Related Work

Long-video and agentic video benchmarks. Long-video QA benchmarks have expanded from ActivityNet-QA and EgoSchema to broader suites covering diverse domains, durations, and task formats (Yu et al., 2019; Mangalam et al., 2023; Fu et al., 2025; Zhou et al., 2024a; Li et al., 2024; Wu et al., 2024b; Chandrasegaran et al., 2024; Wang et al., 2024; Ataallah et al., 2025). Recent work further moves toward open-ended or agentic evaluation beyond closed-form answering (Ma et al., 2025). These resources stress long-horizon comprehension and realistic evaluation, but do not make cross-episode person-level evidence sufficiency the primary target.

Narrative, character, and human-centric video. MovieQA, TVQA, MovieChat, and SeriesBench evaluate story-level character reasoning in movies, TV, and drama series (Tapaswi et al., 2016; Lei et al., 2018; Song et al., 2024; Zhang et al., 2025). HumanVBench and VideoForest/CrossVideoQA move closer to person-level evaluation through human-centric perception or person-anchored cross-video QA (Zhou et al., 2024b; Meng et al., 2025). KnowMeBenchV2 differs by asking whether systems can synthesize stable behavioral regularities across episodes, including recurring preferences, values, and aversions, under explicit evidence-sufficiency and abstention constraints.

Evidence grounding, temporal localization, and abstention. Temporal localization and moment-retrieval work grounds language queries in video intervals (Gao et al., 2017), while recent long-video reasoning work treats visual evidence as an evaluation or training target (Wei et al., 2026; Luo et al., 2025; Yuan et al., 2025). Separately, abstention and selective prediction improve reliability in language and vision-language QA (Dancette et al., 2023; Srinivasan et al., 2024; Khan and Fu, 2024; Wen et al., 2025), and hallucination evaluation highlights the risk of unsupported visual claims (Li et al., 2023). KnowMeBenchV2 combines these threads: systems must decide whether observable audiovisual evidence is sufficient to support claims about a person across videos, and T5 uses surface-similar unsupported questions as a contrastive support check for open-form evaluation.

Personalized memory and retrieval-based long-video systems. Retrieval-augmented generation, graph/hierarchical retrieval, and agentic memory systems provide mechanisms for organizing external evidence (Lewis et al., 2020; Edge et al., 2024; Zhong et al., 2024; Packer et al., 2024; Park et al., 2023). Long-video systems instantiate these ideas through memory augmentation, retrieval, or navigation (He et al., 2024; Ren et al., 2025; Long et al., 2025; Qiu et al., 2026), while long-term and personalized-memory benchmarks evaluate recall, temporal reasoning, memory updating, and person understanding in dialogue histories or personal traces (Maharana et al., 2024; Wu et al., 2024a, 2026; Hu et al., 2026). KnowMeBenchV2 differs by making audiovisual evidence construction observable in evaluation: the same benchmark separates local grounding, cross-episode ordering, synthesis, and abstention, and the experiments use fixed-answerer route comparisons to analyze where evidence organization matters. Table 1 summarizes this positioning across person-centric evaluation, multimodal evidence, grounding, and cross-episode synthesis.

3 The KnowMeBenchV2 Benchmark

KnowMeBenchV2 evaluates person-centric long-video understanding over recurring subjects in multi-episode audiovisual sources. Each benchmark instance asks whether a system can construct sufficient evidence from a source set and use it to answer, order, synthesize, or reject a person-linked claim. A source set consists of multiple videos drawn from the same public series, where the same people, settings, activities, and interaction contexts

Benchmark / resource	Year	Substrate / scale	P (Pers.)	M (Multi.)	G (Grnd.)	X (Cross.)
Long-video and multimodal video QA						
ActivityNet-QA / EgoSchema	2019–23	Web and egocentric videos	◐	◐	◐	○
Video-MME / MLVU / MVBench	2024–25	Broad video suites	○	◐	○	○
LongVideoBench / LVBench / InfiniBench	2024	Long public videos, movies, TV	◐	◐	◐	○
VideoEval-Pro	2025	Long videos	○	◐	○	○
Narrative, character, and human-centric video						
MovieQA / TVQA	2016–18	Movies and TV episodes	◐	◐	◐	○
MovieChat-1K / SeriesBench	2024–25	Movies and drama series	◐	◐	◐	◐
HumanVBench	2024	Human-centric videos	●	●	◐	○
VideoForest / CrossVideoQA	2025	Distributed video streams	●	◐	◐	●
Longitudinal memory and persona resources						
LoCoMo / LongMemEval	2024	Dialogue histories	●	○	◐	●
KnowMe-Bench	2026	Lifelong digital companion memories	●	○	◐	●
CloneMem	2026	Personal digital traces	●	◐	◐	●
KnowMeBenchV2 (ours)	**2026**	**327 videos / 3,061 Qs**	●	●	●	●

Legend: ● explicit   ◐ limited / implicit   ○ absent

Table 1: Positioning of KnowMeBenchV2 relative to representative long-video, narrative/character, human-centric, and longitudinal-memory resources. P (Pers.) = person-centric evaluation target; M (Multi.) = multimodal or multi-source evidence; G (Grnd.) = items require explicit evidence pointers, such as span anchors or cited evidence, rather than free-form QA only; X (Cross.) = cross-episode or cross-session synthesis.

recur across episodes. This setting changes the evidence substrate of person understanding: the relevant information is no longer confined to written narrative or a single video clip, but distributed across speech, visible behavior, objects, locations, social interactions, and repeated episode-level patterns.

The benchmark contains five public multi-episode video series, covering 327 videos and roughly 125 hours of audiovisual material. From these sources, KnowMeBenchV2 provides 3,061 evidence-grounded questions with gold answers, source identifiers, task labels, and evaluation metadata. The benchmark is organized around observable evidence. Gold answers are supported by what appears, is said, or repeatedly happens in the source videos, including explicit statements, recurring routines, visual actions, interaction roles, and cross-episode changes. This makes the benchmark suitable for evaluating person understanding as grounded inference over audiovisual traces rather than as open-ended profile generation.

3.1 Task Design

KnowMeBenchV2 is structured as an evidence-scope ladder. T1–T4 move from localized evidence recovery to cross-episode synthesis, while T5 is a contrastive support check for evidence boundaries.

T1 focuses on local grounding. These questions require the model to identify a concrete detail from a specified video moment, such as what a person says, holds, does, wears, or encounters. T2 extends this setting to short-range event relations, where the answer depends on connecting neighboring moments within a video rather than copying a single fact. T3 moves beyond single-episode reasoning by asking the model to order evidence instances across videos according to an explicitly stated criterion. These questions test whether the system can preserve provenance and compare events without collapsing them into an unordered set of retrieved clips.

T4 is the main cross-episode synthesis task. It asks questions whose answers are not licensed by any single clip alone. A valid T4 answer must be supported by multiple observations from the same source set and must express a recurring pattern at the level of observable behavior, social role, preference, practice, or interaction style. T5 complements the ladder by testing the boundary of support. Its questions deliberately resemble supported person-centric questions in surface form, but combine valid people, settings, objects, or partial events with an unsupported relation, false temporal setting, or missing causal link. The correct answer is ABSTAIN. T5 therefore tests whether a system distinguishes evidential support from surface familiarity, rather than producing a plausible but unsupported person-level explanation.

3.2 Question Construction

KnowMeBenchV2 uses two construction tracks. For T1–T3 and T5, we first extract candidate moments from each source set using visual signals and ASR transcripts. Candidate moments are short evidence-rich spans containing person-linked ac-

Figure 2: Overview of the KnowMeBenchV2 benchmark and evaluation pipeline. Public multi-episode videos are converted into evidence-indexed candidate moments, used to construct grounded questions, checked for answerability and provenance, supplemented with human-authored cross-episode synthesis items, and evaluated through a shared scoring protocol.

tions, dialogue, objects, settings, or event transitions. Question generation then converts these moments into task-specific items with associated source identifiers and evidence provenance. Quality control checks support, answerability, task fit, abstention polarity, and source traceability. Items that fail these checks are revised, regenerated, or filtered. For T5, construction deliberately combines valid source elements with an unsupported relation or premise, so that familiarity with people, settings, or events is insufficient for answering.

T4 follows a human-authored construction track. Annotators watch the full source series and write cross-episode questions whose answers require evidence distributed across multiple videos. This design aligns the most person-centric task with the natural viewing process: recurring patterns become visible through repeated exposure rather than through isolated retrieval. T4 items are retained only when the answer can be grounded in source evidence from more than one episode and when the

question targets a stable observable pattern rather than a one-off event. Annotators also record evidence notes used for verification and later audit.

3.3 Human-Authored Synthesis and Quality Audit

Human experts are central to the construction of the most interpretive part of KnowMeBenchV2. Five trained graduate-student annotators each watch one complete source series and write candidate T4 questions whose answers require evidence from multiple separately recorded videos. LLM assistance is limited to wording normalization, duplicate detection, and answer-format standardization; the question, cross-video evidence pattern, and gold answer are human-authored.

Human audit then checks source support, answerability, cross-episode scope, near-duplicate items, and over-interpretation risk. Items are revised or rejected when the evidence supports only a single episode or when the answer requires a claim

Task	Evidence Scope	Target Capability	Answer Form
T1: Information Extraction	Local clip or moment	Recover grounded facts about a person, action, object, setting, or spoken detail under explicit source constraints.	Short answer
T2: Temporal and Event Relations	Within-video or local episode context	Relate temporally adjacent or causally connected events, including what happened before/after an action or why a local event relation holds.	Short or structured answer
T3: Cross-Episode Ordering	Multiple episodes	Order person-linked events, activities, or evidence instances under a stated criterion, such as recurrence, progression, or observable change.	Ordered list
T4: Cross-Episode Persona Synthesis	Full source set	Synthesize a recurring person-level pattern supported by multiple episodes, such as routines, preferences, roles, interaction habits, or stable behavioral tendencies.	Free-form answer
T5: Grounded Abstention	Unsupported or mismatched evidence	Reject a person-linked premise that is surface-similar to supported questions but not licensed by the source evidence.	ABSTAIN

Table 2: KnowMeBenchV2 task taxonomy. T1–T4 form an evidence-scope ladder from localized extraction to cross-episode synthesis. T5 is evaluated separately as a contrastive support check for grounded abstention.

beyond the observable audiovisual record. For the human reference, annotators answer questions on source series they did not author, using the same source-identifier interface and task-specific scoring protocol as systems. This separates question construction from human answering while keeping both stages grounded in the same audiovisual evidence.

3.4 Scoring Protocol

We use task-specific scoring. T1 is evaluated with exact or constrained semantic matching, depending on whether the answer is a closed-form entity, phrase, or short description. T2 and T3 are scored for both answer correctness and relation correctness: a response must recover the relevant event relation or ordering criterion, not merely mention plausible evidence. T4 uses semantic grading against the reference answer, emphasizing whether the response captures the recurring pattern and grounds it in source-supported observations.

T5 is strict-scored: full credit is given only to explicit ABSTAIN. We report it separately from the T1–T4 ladder because it measures evidence-boundary recognition rather than additional synthesis depth. Its role is to check whether open-form scores reflect grounded evidence use rather than generic person-level language. This check is important because open-form person-centric questions can otherwise reward plausible but weakly grounded answers. As a no-evidence validity check, Qwen3.5-9B with the evidence route removed scores 1.3/0.0/0.0/0.0 on T1–T4 and 100.0 on T5, indicating that the sup-

ported tasks cannot be solved from question priors alone while T5 preserves its intended unsupported-premise signal. On semantic scoring, a 100-record blind audit by three NLP researchers gives 88.0% exact agreement and Cohen's $\kappa=0.78$ against the GPT-5.2 judge, with full disagreement analysis in Appendix E. Full scoring prompts, audit procedures, agreement analysis, and task examples are provided in the appendix.

4 Experiments

The experiments evaluate how current systems use audiovisual evidence at different scopes. We report end-to-end long-video systems and a fixed-answerer evidence diagnostic. The first view characterizes current system-level behavior on KnowMeBenchV2; the second view isolates how performance changes when the same answerer receives different evidence representations.

4.1 Experimental Setup

Systems. We evaluate representative long-video and multimodal systems, including LongVideo-R1, M3-Agent, VideoRAG, and MA-LMM. These systems differ in their video access mechanisms, retrieval modules, temporal reasoning procedures, and memory designs. Their results characterize current long-video behavior across localized and cross-episode tasks.

Fixed-answerer evidence diagnostic. We additionally run a fixed-answerer diagnostic with Qwen3.5-9B. Qwen3.5-9B is a multimodal-capable

| System | T1
Extract. | T2
Temporal | T3
Ordering | T4
Synthesis | Overall
T1–T4 | Core
T3–T4 | T5
Abstain |
|---|---|---|---|---|---|---|---|
| Qwen3.5-9B ASR-Retrieval | 26.7 | 15.0 | 42.9 | 2.7 | 21.8 | 22.8 | 97.0 |
| Qwen3.5-9B + KnowMe | 34.0 | 47.0 | **49.0** | **64.9** | **48.7** | **57.0** | 100.0 |
| LongVideo-R1 | **44.0** | **52.0** | 32.7 | 56.8 | 46.4 | 44.8 | 76.0 |
| M3-Agent | 17.3 | 39.0 | **49.0** | 18.9 | 31.0 | 34.0 | 45.0 |
| VideoRAG | 3.0 | 17.8 | 24.4 | 2.7 | 12.0 | 13.6 | 67.0 |
| MA-LMM | 4.7 | 29.0 | 22.4 | – | – | – | 12.0 |
| Human reference | 92.0 | 88.0 | 82.0 | 78.0 | 85.0 | 80.0 | 93.0 |

Table 3: Main results on KnowMeBenchV2. Overall is the average over T1–T4. Core is the average over the cross-episode tasks T3–T4. T5 is reported separately because abstention evaluates evidence-boundary recognition rather than synthesis depth. Bold numbers mark the strongest non-human result for each T1–T4 column and aggregate.

answerer; in this diagnostic, we hold the answer model fixed and vary the evidence representation supplied at inference time. ASR-Retrieval provides retrieved speech-transcript chunks. KnowMe provides routed textual evidence summaries constructed from audiovisual source evidence.

KnowMe first builds an offline hierarchy of clip, segment, video-level persona, and series-level trajectory memories. At inference time, the answerer does not receive the full hierarchy. Each question retrieves a task-specific subset: local tasks primarily use clip and segment evidence, while cross-episode tasks additionally route through persona and trajectory memories before returning supporting lower-level evidence.

Metrics. We report T1–T5. T1–T4 form the main person-understanding ladder and are averaged as Overall. We also report Core, the average of T3 and T4, to emphasize cross-episode comparison and synthesis. T5 is reported separately because it measures evidence-boundary recognition: the correct behavior is to abstain when a person-linked premise is unsupported by the source evidence.

4.2 Main Results

Table 3 shows a split between local video grounding and cross-episode evidence organization. Human viewers remain far ahead, reaching 85.0 Overall and 80.0 Core, which shows that the questions are recoverable from the audiovisual source evidence while leaving a substantial gap for current systems.

Among non-human systems, LongVideo-R1 performs best on the localized tasks T1 and T2, with scores of 44.0 and 52.0. This indicates that native video access is most useful when the answer is close to a specific observed moment. In contrast,

Qwen3.5-9B+KnowMe performs best on cross-episode synthesis, reaching 64.9 on T4 and 57.0 Core. The contrast shows that local video grounding and cross-episode evidence organization are distinct capabilities.

T5 provides a separate check on evidence boundaries. Because T5 items are surface-similar to supported person-linked questions but unsupported by source evidence, high T5 performance indicates that a system can reject plausible but unlicensed claims. The two Qwen3.5-9B diagnostic routes score 97.0 and 100.0 on T5, supporting the interpretation that their open-form scores are not produced solely by generic person-level language. We therefore report T5 outside Overall and Core: it supports the reliability of open-form evaluation, but does not measure additional synthesis depth.

4.3 Attribution Diagnostics

Figure 3 separates transcript volume from evidence organization under the same Qwen3.5-9B answerer. ASR-Flat-32K and ASR-Retrieval remain close on Overall, while KnowMe nearly doubles the score. The largest difference appears on T4: ASR-Retrieval reaches 2.7, whereas KnowMe reaches 64.9. Cross-episode synthesis is therefore not recovered by transcript access alone. The answerer needs a representation that links recurring audiovisual evidence across the source set.

Panel (a) also exposes a compression trade-off. ASR-Flat-32K exceeds KnowMe on T3, 53.1 versus 49.0, even though it fails on T4. Ordering can depend on local discriminative cues preserved in a long transcript, while synthesis benefits from higher-level organization. This is why KnowMeBenchV2 separates ordering from synthesis: both are cross-episode tasks, but they reward different evidence structures.

Figure 3: **Attribution diagnostics for the fixed-answerer route comparison.** **(a)** Route lift across T1–T4 under the same Qwen3.5-9B answerer. Gray circles denote ASR-Retrieval, blue circles denote KnowMe, and the brown diamond marks the ASR-Flat-32K boundary condition on T3. KnowMe improves T1, T2, and especially T4, while ASR-Flat-32K remains stronger on T3, revealing an ordering cost of hierarchical compression. **(b)** System ranking on T4 cross-episode synthesis. KnowMe reaches 64.9, exceeding all evaluated systems and approaching the human reference of 78.0. **(c)** Per-series T4 lift across the five source series (S1–S5). The synthesis gain is consistent across all source sets, indicating that the route effect is not driven by a single series.

Panel (c) further shows that the T4 gain is stable across all five source series, ranging from +60.0 to +66.0 points over ASR-Retrieval. Additional route ablations confirm this interpretation. Removing the trajectory/theme layer reduces T4 from 64.9 to 43.8, while leaving lower-level tasks comparatively less affected. This indicates that the synthesis gain comes from cross-episode aggregation rather than from the answerer or retrieval infrastructure alone. KnowMe also uses a smaller per-question inference context than transcript-heavy controls: 1.8K–2.8K retrieved-evidence-plus-prompt tokens versus about 8K–12K for matched ASR retrieval and about 28K for ASR-Flat-32K (Appendix G.1), so the T4 gain is not purchased by a larger answer-time context. Full component ablations, routing budgets, and qualitative examples are reported in Appendix G.

5 Conclusion

We introduced KnowMeBenchV2, an evidence-grounded benchmark for person-centric long-video understanding over recurring subjects in multi-episode audiovisual sources. The benchmark evaluates a ladder of evidence scopes, from localized extraction to cross-episode synthesis, and uses grounded abstention as a contrastive check on evidence-boundary recognition.

The experiments show that current systems fail in task-dependent ways. Native long-video systems are strongest on local grounding, while organized audiovisual evidence is most effective for cross-episode synthesis. Under a fixed Qwen3.5-9B answerer, replacing flat ASR retrieval with the KnowMe evidence route raises T4 from 2.7 to 64.9, approaching the human reference of 78.0. At the same time, ordering tasks reveal a compression cost: summaries help expose recurring patterns but can discard rank-sensitive details.

KnowMeBenchV2 reframes recurring-person video understanding as an evidence-construction problem over audiovisual traces. Progress on this setting requires systems that preserve local visual grounding while organizing evidence across episodes into representations suitable for comparison, synthesis, and abstention.

Limitations

Source breadth and language. The source collections are drawn from five documentary-style public playlists; source speech is primarily English, with a non-English subset, while benchmark questions and gold answers are English throughout. Results on a balanced multilingual or low-resource setting may differ.

Ethical Considerations

KnowMeBenchV2 is intended for evidence-grounded long-video research. The task definitions restrict behavioral claims to observable source evidence and do not support surveillance, identity inference, protected-attribute inference, psychological profiling, or claims about sensitive attributes such as health, religion, sexuality, or political identity. Target subjects are people who are explicitly framed by the public source series as central

documentary subjects; non-target people appearing incidentally in videos are not benchmark subjects and are not used for persona claims. Cross-episode synthesis items ask for recurring evidence patterns within a source series, not stable psychological labels or protected-attribute inferences. The source manifest records source identifiers, platform links, duration, language metadata, access dates, and availability status; if a source is removed or a rights holder requests takedown, affected items are deprecated or removed in the public artifact. The accompanying artifacts provide links, metadata, scoring resources, and limited derived artifacts rather than raw videos.

References

Kirolos Ataallah, Eslam Mohamed Bakr, Mahmoud Ahmed, Chenhui Gou, Khushbu Pahwa, Jian Ding, and Mohamed Elhoseiny. 2025. InfiniBench: A benchmark for large multi-modal models in long-form movies and tv shows. *arXiv preprint arXiv:2406.19875*.

Keshigeyan Chandrasegaran, Agrim Gupta, Lea M. Hadzic, Taran Kota, Jimming He, Cristóbal Eyzaguirre, Zane Durante, Manling Li, Jiajun Wu, and Li Fei-Fei. 2024. HourVideo: 1-hour video-language understanding. In *Advances in Neural Information Processing Systems (Datasets and Benchmarks Track)*.

Corentin Dancette, Spencer Whitehead, Rishabh Maheshwary, Ramakrishna Vedantam, Stefan Scherer, Xinlei Chen, Matthieu Cord, and Marcus Rohrbach. 2023. Improving selective visual question answering by learning from your peers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 24049–24059.

Darren Edge, Ha Trinh, Newman Cheng, Joshua Bradley, Alex Chao, Apurva Mody, Steven Truitt, and Jonathan Larson. 2024. From local to global: A graph RAG approach to query-focused summarization. *arXiv preprint arXiv:2404.16130*.

Chaoyou Fu, Yuhan Dai, Yongdong Luo, Lei Li, Shuhuai Ren, Renrui Zhang, Zihan Wang, Chenyu Zhou, Yunhang Shen, Mengdan Zhang, Peixian Chen, Yanwei Li, Shaohui Lin, Sirui Zhao, Ke Li, Tong Xu, Xiawu Zheng, Enhong Chen, Rongrong Ji, and Xing Sun. 2025. Video-MME: The first-ever comprehensive evaluation benchmark of multi-modal LLMs in video analysis. In *Proceedings of CVPR*.

Jiyang Gao, Chen Sun, Zhenheng Yang, and Ram Nevatia. 2017. TALL: Temporal activity localization via language query. In *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*.

Bo He, Hengduo Li, Young Kyun Jang, Menglin Jia, Xuefei Cao, Ashish Shah, Abhinav Shrivastava, and Ser-Nam Lim. 2024. MA-LMM: Memory-augmented large multimodal model for long-term video understanding. In *Proceedings of CVPR*.

Sen Hu, Zhiyu Zhang, Yuxiang Wei, Xueran Han, Zhenheng Tang, Huacan Wang, and Ronghao Chen. 2026. CloneMem: Benchmarking long-term memory for AI clones. *arXiv preprint arXiv:2601.07023*.

Zaid Khan and Yun Fu. 2024. Consistency and uncertainty: Identifying unreliable responses from black-box vision-language models for selective visual question answering. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 10854–10863.

Jie Lei, Licheng Yu, Mohit Bansal, and Tamara Berg. 2018. TVQA: Localized, compositional video question answering. In *Proceedings of EMNLP*.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. 2020. Retrieval-augmented generation for knowledge-intensive NLP tasks. In *Advances in Neural Information Processing Systems*.

Kunchang Li, Yali Wang, Yinan He, Yizhuo Li, Yi Wang, Yi Liu, Zun Wang, Jilan Xu, Guo Chen, Ping Luo, Limin Wang, and Yu Qiao. 2024. MVBench: A comprehensive multi-modal video understanding benchmark. In *Proceedings of CVPR*.

Yifan Li, Yifan Du, Kun Zhou, Jinpeng Wang, Xin Zhao, and Ji-Rong Wen. 2023. Evaluating object hallucination in large vision-language models. In *Proceedings of EMNLP*.

Lin Long, Yichen He, Wentao Ye, Yiyuan Pan, Yuan Lin, Hang Li, Junbo Zhao, and Wei Li. 2025. Seeing, listening, remembering, and reasoning: A multimodal agent with long-term memory. *arXiv preprint arXiv:2508.09736*.

Mi Luo, Zihui Xue, Alex Dimakis, and Kristen Grauman. 2025. When thinking drifts: Evidential grounding for robust video reasoning. In *Advances in Neural Information Processing Systems*.

Wentao Ma, Weiming Ren, Yiming Jia, Zhuofeng Li, Ping Nie, Ge Zhang, and Wenhu Chen. 2025. VideoEval-Pro: Robust and realistic long video understanding evaluation. *arXiv preprint arXiv:2505.14640*.

Adyasha Maharana, Dong-Ho Lee, Sergey Tulyakov, Mohit Bansal, Francesco Barbieri, and Yuwei Fang. 2024. Evaluating very long-term conversational memory of LLM agents. In *Proceedings of ACL*.

Karttikeya Mangalam, Raiymbek Akshulakov, and Jitendra Malik. 2023. EgoSchema: A diagnostic benchmark for very long-form video language understanding. In *Advances in Neural Information Processing Systems (Datasets and Benchmarks Track)*.

Yiran Meng, Junhong Ye, Wei Zhou, Guanghui Yue, Xudong Mao, Ruomei Wang, and Baoquan Zhao. 2025. VideoForest: Person-anchored hierarchical reasoning for cross-video question answering. *arXiv preprint arXiv:2508.03039*.

Charles Packer, Sarah Wooders, Kevin Lin, Vivian Fang, Shishir G. Patil, Ion Stoica, and Joseph E. Gonzalez. 2024. Memgpt: Towards llms as operating systems. *Preprint*, arXiv:2310.08560.

Joon Sung Park, Joseph C. O'Brien, Carrie J. Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. 2023. Generative agents: Interactive simulacra of human behavior. In *Proceedings of UIST*.

Jihao Qiu, Lingxi Xie, Xinyue Huo, Qi Tian, and Qixiang Ye. 2026. LongVideo-R1: Smart navigation for low-cost long video understanding. *arXiv preprint arXiv:2602.20913*.

Xubin Ren, Lingrui Xu, Long Xia, Shuaiqiang Wang, Dawei Yin, and Chao Huang. 2025. VideoRAG: Retrieval-augmented generation with extreme long-context videos. *arXiv preprint arXiv:2502.01549*.

Enxin Song, Wenhao Chai, Guanhong Wang, Yucheng Zhang, Haoyang Zhou, Feiyang Wu, Haozhe Chi, Xun Guo, Tian Ye, Yan Lu, Jenq-Neng Hwang, Mike Zheng Shou, and Gaoang Wang. 2024. MovieChat: From dense token to sparse memory for long video understanding. In *Proceedings of CVPR*.

Tejas Srinivasan, Jack Hessel, Tanmay Gupta, Bill Yuchen Lin, Yejin Choi, Jesse Thomason, and Khyathi Chandu. 2024. Selective "selective prediction": Reducing unnecessary abstention in vision-language reasoning. In *Findings of the Association for Computational Linguistics: ACL*.

Makarand Tapaswi, Yukun Zhu, Rainer Stiefelhagen, Antonio Torralba, Raquel Urtasun, and Sanja Fidler. 2016. MovieQA: Understanding stories in movies through question-answering. In *Proceedings of CVPR*.

Weihan Wang, Zehai He, Wenyi Hong, Yean Cheng, Xiaohan Zhang, Ji Qi, Xiaotao Gu, Shiyu Huang, Bin Xu, Yuxiao Dong, Ming Ding, and Jie Tang. 2024. LVBench: An extreme long video understanding benchmark. *arXiv preprint arXiv:2406.08035*.

Zhaoyang Wei, Guoliang Wang, Guohua Gao, Yanchao Hao, Mingda Li, Wenchao Ding, Xi Chen, Shizhu He, and Xuehui Yu. 2026. Seeing is believing: Grounding long-video understanding in spatio-temporal visual evidence. In *Proceedings of AAAI*.

Bingbing Wen, Jihan Yao, Shangbin Feng, Chenjun Xu, Yulia Tsvetkov, Bill Howe, and Lucy Lu Wang. 2025. Know your limits: A survey of abstention in large language models. *Transactions of the Association for Computational Linguistics*.

Di Wu, Hongwei Wang, Wenhao Yu, Yuwei Zhang, Kai-Wei Chang, and Dong Yu. 2024a. LongMemEval: Benchmarking chat assistants on long-term interactive memory. *arXiv preprint arXiv:2410.10813*.

Haoning Wu, Dongxu Li, Bei Chen, and Junnan Li. 2024b. LongVideoBench: A benchmark for long-context interleaved video-language understanding. In *Advances in Neural Information Processing Systems (Datasets and Benchmarks Track)*.

Tingyu Wu, Zhisheng Chen, Ziyan Weng, Shuhe Wang, Chenglong Li, Shuo Zhang, Sen Hu, Silin Wu, Qizhen Lan, Huacan Wang, and 1 others. 2026. Knowme-bench: Benchmarking person understanding for lifelong digital companions. *arXiv preprint arXiv:2601.04745*.

Zhou Yu, Dejing Xu, Jun Yu, Ting Yu, Zhou Zhao, Yueting Zhuang, and Dacheng Tao. 2019. ActivityNet-QA: A dataset for understanding complex web videos via question answering. In *Proceedings of AAAI*.

Huaying Yuan, Zheng Liu, Junjie Zhou, Hongjin Qian, Yan Shu, Nicu Sebe, Ji-Rong Wen, and Zhicheng Dou. 2025. VideoExplorer: Think with videos for agentic long-video understanding. *arXiv preprint arXiv:2506.10821*.

Chenkai Zhang, Yiming Lei, Zeming Liu, Haitao Leng, ShaoGuo Liu, Tingting Gao, Qingjie Liu, and Yunhong Wang. 2025. SeriesBench: A benchmark for narrative-driven drama series understanding. In *Proceedings of CVPR*.

Wanjun Zhong, Lianghong Guo, Qiqi Gao, He Ye, and Yanlin Wang. 2024. MemoryBank: Enhancing large language models with long-term memory. In *Proceedings of AAAI*.

Junjie Zhou, Yan Shu, Bo Zhao, Boya Wu, Zhengyang Liang, Shitao Xiao, Minghao Qin, Xi Yang, Yongping Xiong, Bo Zhang, Tiejun Huang, and Zheng Liu. 2024a. MLVU: Benchmarking multi-task long video understanding. *arXiv preprint arXiv:2406.04264*.

Ting Zhou, Daoyuan Chen, Qirui Jiao, Bolin Ding, Yaliang Li, and Ying Shen. 2024b. HumanVBench: Exploring human-centric video understanding capabilities of MLLMs with synthetic benchmark data. *arXiv preprint arXiv:2412.17574*.

Statistic	S1	S2	S3	S4	S5	Total	Scoring
Source videos	50	55	91	75	56	327	–
Main questions	439	513	859	684	566	3,061	–
Video-indexed	402	488	809	654	480	2,833	–
Series synthesis	37	25	50	30	86	228	–
T1 Information extr.	150	165	273	225	168	981	strict
T2 Temp.-event rel.	100	110	182	150	112	654	strict
T3 Ordering	49	49	49	49	49	245	semantic
T4 Persona synth.	37	25	50	30	86	228	semantic
T5 Grounded abst.	100	110	182	150	112	654	strict

Table 4: Benchmark statistics for the released question pool. S1–S5 denote the five source series. Per-task rows correspond to the scored task pools reported in the paper; source manifests retain additional construction and calibration records. T3 is balanced across series, while T4 is human-authored with a series-dependent yield.

A   Dataset Scope and Artifacts

KnowMeBenchV2 uses five public person-centric long-form video series sourced from open video-sharing platforms: 327 source videos across five playlists, totaling roughly 125 hours. Source speech is primarily English, with a subset of videos containing additional non-English speech; benchmark questions and gold answers are in English throughout. Raw videos are not redistributed. The released artifacts include source identifiers, benchmark questions, gold answers, task labels, scoring scripts, prompt templates, model predictions, archived semantic-judge outputs for the reported semantic-scored subsets, model/component metadata, and de-identified semantic-audit records. Derived artifacts such as ASR segments, frame timestamps, visual-extraction fields, generated memories, and retrieval outputs are included when permitted by platform, privacy, and licensing constraints.

Per-video source metadata identify the public source identifiers from which local copies can be reconstructed when permitted by the original platform and license terms. Duration statistics are recorded in the manifest for provenance but are not used as a primary result. Unavailable videos are marked during manifest versioning, and creator removal requests trigger item review and a manifest revision.

ASR-Flat-32K input construction. For single-video tasks (T1–T3 and T5), the ASR-Flat-32K boundary feeds the answerer the full transcript of the target video, capped at 110K characters ($\approx$28K tokens) by head-50% + tail-50% truncation. For T4, per-video ASR is concatenated in episode order across the corresponding series source set and

truncated front-to-back to the same character cap, so only a small fraction of the source set reaches the answerer's context window. Both modes use a 32K context window, no visual input, answerer temperature 0.1, and a 2,048-token output cap.

B   Task Definitions and Examples

T1: Information Extraction. T1 asks for localized facts, entities, attributes, numerical details, or time-anchored observations directly supported by the video or transcript. It is strict-scored.

T2: Temporal and Event Relations. T2 covers before/after relations, local event sequences, short-window reactions, and event-linked social cues within a video. It is strict-scored.

T3: Cross-Episode Ordering. T3 asks the system to rank a small set of people, events, or items from the same source series along a stated criterion such as severity, urgency, escalation, risk, cost, recurrence, or observable change. Each item lists 3–5 candidates and is judged for semantic equivalence to the gold ordering rather than exact string match.

T4: Cross-Episode Persona Synthesis. T4 integrates evidence across multiple videos to identify recurring stated preferences, roles, practices, routines, or observable behavior patterns within the associated source collection. Each item is associated with the series-specific source set and is semantically scored. In the evaluated T4 pool, ABSTAIN is scored incorrect because retained T4 items are answerable from the source set.

T5: Grounded Abstention. T5 is a contrastive support check for open-form person-centric evaluation. Items are surface-similar to supported questions but combine valid people, settings, objects, or partial events with an unsupported relation, false temporal setting, or missing causal link. The gold answer is the fixed token ABSTAIN. T5 is strict-scored and reported separately from T1–T4.

Representative examples. The released artifact includes item-level examples with source identifiers, timestamps, evidence notes, and answers. T1 examples ask for a concrete local detail, T2 examples ask about an event relation, T3 examples ask for a ranked list under a stated criterion, T4 examples ask for a recurring person-level pattern supported by multiple videos, and T5 examples contain an unsupported premise while retaining familiar entities or settings.

C Annotation and Human Materials

Gold answers were constructed with access to full video context and localized evidence. Per-series construction records contain video-indexed main-task records and cross-episode synthesis records, each with question id, task type, video id (or video-set id for T4), localized time range (or per-video evidence anchors for T4), question, answer, and annotator metadata. These records support provenance for gold-answer construction but are not used as model inputs.

The cross-episode synthesis construction material comes from five trained graduate-student annotators, with one annotator assigned to each source series. After calibration, each annotator watched the full source set for the assigned series and wrote candidate questions whose answers require evidence from multiple separately recorded videos. LLM assistance was limited to wording normalization, duplicate detection, and answer-format standardization; the question, cited cross-video evidence pattern, and gold answer were human-authored. Human evidence checks merged candidates, removed near-duplicates, checked source support, answerability, cross-episode scope, and over-interpretation risk, and rejected single-video items, retaining 228 final items with provenance links to supporting source videos.

Construction-stage agreement on a separate 60-item stratified double-annotated subset (12 items per task) gives per-task Cohen's κ of 0.78 (T1), 0.71 (T2), 0.66 (T3), 0.61 (T4), and 0.74 (T5), with aggregate $\kappa = 0.70$. T3 and T4 show lower agreement than the strict-scored tasks, consistent with semantic-scoring tasks being harder to standardize at the gold level.

D Question Construction Prompts and QC Gates

The construction pipeline uses prompt cards rather than unconstrained generation. Each card defines the role, input fields, output schema, rejection gate, and hard constraints. This appendix summarizes the contracts needed to reproduce the paper-level items.

Candidate-moment extraction. The candidate-moment prompt watches one full video and returns 5–15 evidence-rich windows with `video_id`, start time, end time, and a short factual reason. Candidate moments are selected for clear speech content, visible action changes, environmental changes, reactions, anomalies, contrasts, or causal structure. The prompt requires JSON-only output and forbids invented events, motives, or background facts.

Supported video-indexed item generation. For T1 and T2, the item-generation prompt conditions on candidate moments and ASR/visual notes. It requires a uniquely answerable question, a concise answer, task label, source video id, timestamp span, and evidence note. The QC prompt rejects items whose answer is not supported by the cited span, whose wording leaks the answer, whose answer is not unique, or whose task label does not match the intended capability.

Cross-episode ordering construction. T3 construction aggregates candidate events within the same source series and asks for a ranked list under an explicitly stated observable criterion. The prompt requires discrete evidence instances, a non-trivial ranking dimension, and evidence closure: the cited evidence must be sufficient to recover both the candidates and the ordering rationale.

Grounded abstention construction. T5 construction deliberately combines true fragments into a false or unsupported premise. Entities, people, settings, or partial events are valid, but the relation is invalid. Trap strategies include entity swapping, spatiotemporal distortion, and false causality via unrelated true anchors. The answer must be exactly `ABSTAIN`.

Quality-control gates. The shared QC pass checks support, answerability, task fit, abstention polarity, observable grounding, provenance completeness, and over-interpretation risk. Items that fail are revised, regenerated, or filtered. T4 additionally requires multi-episode support and human evidence notes; T5 additionally requires that the unsupported premise be surface-similar to supported items while still unanswerable from the source.

A. Candidate-Moment Extraction

Role	Identify candidate moments from one full source video that are suitable for downstream question generation.
Inputs	Uploaded source video and source-level `video_id`.
Output Contract	A JSON list of 5–15 candidate moments. Each record contains `video_id`, `start_time`, `end_time`, and a short factual `reason`.
Gate	If no valid candidate moment can be generated, return an empty list. Do not output fields beyond the specified schema.

Hard Constraints.

- **Source faithfulness**: use only content actually present in the video; do not invent events, motives, or background facts.
- **Moment quality**: prefer concrete and visually/verbal clear moments.
- **Selection criteria**: select moments with clear speech content, visible action change, environmental change, reaction, anomaly, contrast, causal structure, or evidence likely to support a unique-answer or stable-ordering question.
- **Reason format**: keep the `reason` short and factual.
- **Schema-only output**: return JSON only.

Skeleton.

```
Input: uploaded video + video_id.
Operation: extract 5--15 evidence-rich candidate moments.
Output(JSON): [{video_id, start_time, end_time, reason}, ...]
```

B. Per-Video Drafting: code-T1 / code-T2 / code-T3

Role	Generate per-video benchmark QA drafts from the uploaded video and the provided candidate moments.
Inputs	Uploaded source video and `candidate_moments_json`.
Output Contract	A JSON list containing 3 code-T1 items, 2 code-T2 items, and 2 code-T3 items. Each record contains `question_id`, `task_type`, `question`, `answer`, `video_id`, and `time_range`.
Gate	If no valid item can be generated, return an empty list. Do not output fields beyond the specified schema. Retention is decided by downstream evidence and audit checks.

Task Mapping.

- **code-T1**: fact extraction with a unique verifiable answer; this corresponds to paper-T1 information extraction.
- **code-T2**: adversarial abstention by combining real elements into a false scenario; this corresponds to paper-T5 grounded abstention.
- **code-T3**: temporal reasoning such as duration, order, before/after relations, or event sequence; this corresponds to paper-T2 temporal/event relations.

Hard Constraints.

- **Source faithfulness**: use only information actually present in the video; do not invent unseen events or unsupported causal relations.
- **code-T1 uniqueness**: answers must be unique and factual.
- **code-T2 abstention**: answers must be exactly ABSTAIN.
- **code-T3 temporal dependence**: questions must depend on temporal reasoning, not only surface lookup.
- **Quality control**: prefer clear, high-confidence questions and avoid duplicates.
- **Schema-only output**: return JSON only.

Skeleton.

```
Inputs: uploaded video + candidate_moments_json.
Generate: 3 code-T1 + 2 code-T2 + 2 code-T3 draft items.
Output(JSON): [{question_id, task_type, question, answer, video_id, time_range}, ...]
Constraint: code-T2 answer = ABSTAIN.
```

C. Per-Video Drafting: code-T4 Logical Ordering

Role	Generate one logical-ordering draft item from the uploaded video and the provided candidate moments.
Inputs	Uploaded source video and `candidate_moments_json`.
Output Contract	A JSON list containing one code-T4 item. Each record contains `question_id`, `task_type`, `question`, `answer`, `video_id`, and `time_range`. The answer is a comma-separated string representing the ordered events.
Gate	If no valid item can be generated, return an empty list. Do not output fields beyond the specified schema. These per-video drafts feed the cross-episode aggregation that produces the released paper-T3 ordering probe.

Hard Constraints.

- **Source faithfulness**: use only events actually present in the video.
- **Comparable events**: select 3–4 comparable events.
- **Non-temporal ordering**: the ordering must not be based on time.
- **Explicit semantic dimension**: rank events by a stated dimension such as risk, physical effort, environmental harshness, emotional intensity, or equipment difficulty.
- **Objectivity**: the ranking dimension should be as objective as possible; avoid highly subjective or ambiguous criteria.
- **Answer format**: return a comma-separated string representing the ordered events.
- **Schema-only output**: return JSON only.

Skeleton.

```
Inputs: uploaded video + candidate_moments_json.
Generate: 1 code-T4 logical-ordering draft item.
Choose: 3--4 comparable events + explicit non-temporal semantic dimension.
Output(JSON): [{question_id, task_type, question, answer, video_id, time_range}]
Use: per-video code-T4 draft -> cross-episode aggregation -> paper-T3 ordering probe.
```

932

Subset	N	Correct	Acc.	Conf.
T3 ordering	245	120	49.0	0.84
T4 synthesis	185	120	64.9	0.78
Audit subset	100	88	88.0	–

Table 5: Semantic scorer validation summary for the reported Qwen3.5-9B + KnowMe semantic-scored subsets and the blind human audit subset.

E   Scoring and Semantic-Judge Audit

T1, T2, and T5 use strict or constrained matching. T3 and T4 use semantic scoring because valid answers are often paraphrastic: T3 admits any ordering that preserves the gold ranking on the named criterion, and T4 admits any synthesis that names the same recurring pattern using source-equivalent observable evidence. A fixed GPT-5.2 judge at temperature 0.0 takes the question, gold answer, and prediction and returns JSON fields for equivalence, confidence, and rationale. Core claim, stance, implication, and yes/no polarity must match; factual contradictions are marked incorrect.

For the 100-record audit subset, three blind NLP researchers label each model prediction by majority vote. The GPT-5.2 judge matches the human majority with 88.0% exact agreement and Cohen's $\kappa = 0.78$, against a mean pairwise human ceiling of $\kappa = 0.82$. The record-level Pearson correlation between judge and human labels is $r = 0.86$ ($p < 0.001$). A third-party Claude Opus 4.7 cross-judge audit on the same records preserves the ASR-Flat-32K versus KnowMe ordering on T3 and T4, ruling out a scorer-family-specific artifact.

No-evidence validity check.   With no evidence route attached, the Qwen3.5-9B answerer scores 1.3/0.0/0.0/0.0 on T1–T4 and 100.0 on T5. This validates two intended properties of the benchmark: supported questions require source evidence rather than question priors, and T5 retains its unsupported-premise signal even without evidence.

F   Fixed-Answerer Evidence Routes

F.1   Protocol

KnowMe is contributed as a reproducible reference evidence route for the fixed-answerer diagnostic. ASR-Retrieval and KnowMe share the same question, source identifiers, answerer, prompt family, and scoring protocol; only the context-construction route differs. The diagnostic compares evidence representations supplied to the same multimodal-capable Qwen3.5-9B answerer, not the native modality capacity of the backbone.

KnowMe segments each video into 30-second clip units with ASR text, sampled keyframes, and vision-language-model-derived visual fields. It then groups clips into segment memories, summarizes video-level persona cues, and builds series-level trajectory/theme memories. At query time, T1 retrieves local clip and segment evidence, T2 emphasizes event sequences, T3 traverses persona-level cues plus cross-episode segment evidence for the ordering criterion, T4 starts from trajectory and theme nodes before retrieving supporting evidence, and T5 reuses the local evidence route while checking premise support.

F.2   Engineering Stack

ASR is stored as transcript JSON with segment-level timing. Video is partitioned into 30-second non-overlapping clips with three keyframes per clip at offsets 0.2, 0.5, and 0.8. Visual extraction uses Qwen3.5-9B as the primary extractor and MiniCPM-V-2.6-int4 as fallback, producing scene, visible text, people, objects, actions, alignment cues, uncertainty, and summary fields. Segments group four clips with stride two. Segment, persona, and trajectory summaries are generated by Qwen3.5-9B at temperature 0.0 under schema-constrained output.

Embeddings come from BGE-Multilingual-Gemma2 via SentenceTransformers with normalized vectors. Indexing uses FAISS IndexFlatIP for dense retrieval and BM25Okapi for sparse retrieval, fused into a hybrid BM25+dense pipeline that feeds task-aware hierarchical retrieval over clip, segment, persona, and theme memories. The answerer is Qwen3.5-9B at temperature 0.1 with evidence-first formatting and explicit `ABSTAIN` support.

F.3   Route–Task Compatibility

A context-construction route is task-compatible with a task when its input-construction policy can in principle deliver evidence from anywhere in the source set at the coverage required by that task. When a route is not task-compatible, its cell is reported as "–" and excluded from paired diagnostic aggregates for that task. This convention applies to MA-LMM's T4 cell because its input regime does not support the series-level T4 setting.

ASR-Flat-32K is treated as a boundary transcript condition rather than the primary matched-budget route. It can be informative on local and order-

Route	Evidence source	Retrieval	Budget	Cross-video access
ASR-Flat-32K	Full ASR transcript, truncated	None	110K chars	Truncated series window
ASR-Retrieval	Retrieved ASR chunks	BM25+dense	8.5K–16K chars	T4 series-level retrieval
KnowMe full	Clip, segment, persona, trajectory memories	BM25+dense+Iteration	18K–40K chars	Persona/theme routing

Table 6: Evidence-source design for attribution controls. Budgets refer to routed character budgets before answerer tokenization; token-level bookkeeping is in Appendix G.1.

Route	T1	T2	T3	T4	Overall	T5
ASR-Flat-32K	28.0	17.0	**53.1**	0.0	24.5	97.0
ASR-Retrieval	26.7	15.0	42.9	2.7	21.8	97.0
KnowMe full	**34.0**	**47.0**	49.0	**64.9**	**48.7**	**100.0**

Table 7: Matched-answerer attribution results under Qwen3.5-9B. The table separates transcript volume from organized audiovisual evidence.

Setting	T2	T3	T4
Full KnowMe	**47.0**	**49.0**	**64.9**
w/o trajectory/theme	45.6	47.6	43.8
w/o segment summaries	42.9	46.2	47.0
Clip-only	41.6	44.9	33.0
Transcript-only	41.3	44.5	51.9

Table 8: Component ablations under the Qwen3.5-9B answerer and summarizer. T1 and T5 are omitted because they are less sensitive to the hierarchy components.

ing tasks, where relevant evidence may fall inside the retained transcript window, but it is not a sufficient route for full-series persona synthesis because T4 evidence patterns can be distributed across the source set beyond the truncation window.

G Matched-Budget Attribution and Route Ablations

The attribution controls show that transcript volume and evidence organization have different effects. ASR-Flat-32K is strongest on T3 but fails on T4, indicating that long transcripts can preserve ordering-relevant details while still failing to expose recurring cross-episode patterns. Removing trajectory/theme memory roughly halves T4, showing that the synthesis gain comes from cross-episode aggregation rather than from the answerer alone.

G.1 Token Budget and Memory Corpus

KnowMe trades a single long-context transcript pass for a structured, retrieved-evidence pass. The offline memory corpus indexes 327 source videos as 2,348 clip units and totals 549,680 tokens across clip, segment, persona, and trajectory layers. Per-unit token cost averages 168 tokens for clip evidence, 49 tokens for segment summaries, and 51 tokens for theme nodes. After hierarchical retrieval, per-question retrieved-evidence budgets are 2,212 (T1), 1,777 (T2), 2,646 (T3), 2,745 (T4), and 2,173 (T5) tokens; adding prompt and instruction overhead puts total per-question KnowMe input at 1,817–2,793 tokens. This is 3–5× smaller than a hybrid transcript-retrieval baseline at matched evidence budgets (≈8,000–12,000 tokens per question), and roughly an order of magnitude smaller than the truncated ASR-Flat-32K transcript (≈28,000 tokens).

H Human Performance Reference

The human-reference row in Table 3 is collected under the same prompts, source-identifier interface, and scoring protocol used by the evaluated systems. The annotator pool is the same five graduate-student question-authors used for T4 construction, one per source series. Each annotator wrote questions for their assigned series and answered questions on a series they did not author. For each series, the answered set is stratified by task: 20 items for each of T1, T2, and T5 and 30 items for each of T3 and T4, giving aggregate denominators of 100/100/150/150/100 across T1–T5. Aggregate human-reference scores are 92.0 / 88.0 / 82.0 / 78.0 / 93.0 on T1–T5.

I Artifact Matrix

The release is organized into three tiers. **Fully included**: benchmark JSON, questions, task labels, gold answers, split metadata, scoring scripts and rubrics, prompt templates, model/component metadata, model predictions for reported runs, semantic-judge outputs for reported runs, and de-identified semantic-scorer audit labels. **Link- or cache-based**: source manifest, ASR segments, frame timestamps, visual-extraction fields, generated memories, and retrieval outputs for reported runs. **Excluded**: raw videos, raw internal evidence logs, private workpapers, credentials, service endpoints, and local paths.

J   Additional Qualitative Diagnostics

Qualitative inspection focuses on two representative failure modes. On T4, transcript retrieval often surfaces one explicit mention and produces a narrow answer, while KnowMe combines repeated evidence across videos into a stable pattern. On T3, failures often arise when summaries preserve the broad topic but remove the local contrast needed for the correct ordering. These cases motivate the separation between ordering and synthesis in the main benchmark taxonomy.