Algorithmic stability and generalization of an unsupervised feature selection algorithm

Abstract

Feature selection, as an important dimension reduction technique, reduces data dimension by identifying an essential subset of input features, which can facilitate interpretable insights into learning and inference processes. Algorithmic stability is a key characteristic of an algorithm regarding its sensitivity to perturbations of input samples. In this paper, we propose an innovative unsupervised feature selection algorithm attaining this stability with provable guarantees. The architecture of our algorithm consists of a feature scorer and a feature selector. The scorer trains a neural network (NN) to score all the features globally, and the selector comprises a dependent sub-NN that locally evaluates the representation abilities to select features. Further, we present algorithmic stability analysis and show our algorithm has a performance guarantee via a generalization error bound. Extensive experimental results on real-world datasets demonstrate superior generalization performance of the proposed algorithm to strong baseline methods. Also, we empirically confirm the properties revealed by the theoretical analysis and the stability of the selected features.

1   Introduction

High-dimensional data is challenging due to the curse of dimensionality [7]. Dimensionality reduction is an important technique for dealing with such data, comprising two typical approaches: feature extraction and feature selection. The former, including principal component analysis (PCA) [34] and autoencoder (AE) [37, 5], is widely used in various fields such as biology [3] and computer vision [43, 17]. Nonetheless, new features produced by feature extraction form a new space and, in general, do not have direct correspondence to original features, leading to a difficulty in deriving interpretable insights for the domain problems, such as biomarker identification and drug discovery. Alternatively, feature selection identifies essential features from the original feature space, providing critical interpretations and insights in many tasks, e.g., gene functional enrichment analysis, cancer biomarker detection, and high-throughput screening for drug discovery [22, 27].

Stability is an important characteristic of an algorithm, which quantifies the sensitivity of the output to the perturbation of its training samples [11, 18]. The current stability analyses of feature selection algorithms focus on similarity-based and frequency-based stability measures for practical assessment, e.g., [15, 21, 33], rather than the algorithms themselves, leaving feature selection with proper algorithmic stability [8] an unmet need. Especially, existing unsupervised feature selection algorithms use the empirical error, or its proxy, to represent the generalization error but provide none theoretical guarantee of such a use, leaving their ability to generalize to new data unclear.

To address these issues, we propose a novel unsupervised feature selection algorithm with a proven algorithmic stability guarantee in this paper. Our approach trains a neural network (NN) to score all features globally and a dependent sub-NN to select the features with the highest scores to reconstruct

the original data. Mathematically, we analyze the algorithm and provide a generalization error upper bound, ensuring its algorithmic stability for guaranteed learning performance. Our contributions are summarized in the following:

- We establish an innovative approach for feature selection. It comprises a NN as a feature scorer to globally score all the features and a dependent sub-NN as a feature selector to evaluate the representation ability of the highly scored features locally. Thus, our algorithm is capable of both globally exploring and locally excavating essential features.

- We establish performance guarantees for our algorithm. It has a proven convergence rate $\mathcal{O}\left(1/\left(n\min\{\sqrt{\lambda_1},\lambda_1\}\right)\right)$ for ensuring its uniform stability and a rate $\mathcal{O}\left(1/\left(\sqrt{n}\min\{\sqrt{\lambda_1},\lambda_1\}\right)\right)$ for its generalization error bound. Here, n is the number of training samples, and λ_1 is a regularization parameter.

- We confirm the effectiveness of our algorithm with extensive experiments on real datasets. It achieves more competitive performance for data reconstruction and downstream classification tasks than state-of-the-art methods. Notably, the features selected by it have performance comparable to the original features. Further, we empirically confirm the properties revealed by theoretical analysis and the stability of the selected features by our algorithm.

2 Related work

In the literature, the approaches for bounding the generalization error can be generally grouped into two categories: 1) Controlling the complexity of hypothesis spaces. They usually need to define an additional complexity measure on the hypothesis space, such as the Vapnik-Chervonenkis dimension [40] and the Rademacher complexity [6]. 2) Focusing on the property of learning algorithms. This category of techniques includes algorithmic stability [8] and robustness-based analysis [44]. In this paper, we focus on algorithmic stability to analyze the stability and generalization of our proposed new algorithm.

Algorithmic stability in learning theory. Algorithmic stability is an important tool for analyzing the generalization of algorithms in learning theory, and it characterizes the sensitivity of the loss when the inputs to an algorithm are changed. Simply speaking, if an algorithm is stable, then its loss does not change significantly when the training samples are modified slightly, such as deleting and replacing a sample. Since the inception of the notion [38, 39], the concepts and properties of stability have become a significant learning theory topic. Bousquet and Elisseeff [8] have shown that stability has a direct connection with the generalization in that the uniform stability of a learning algorithm implies a tight generalization error bound. Thanks to this connection, algorithmic stability has been used for the generalization analysis of learning algorithms, for example, regularized least squares regression [8], multi-class support-vector-machine classification [35], multi-task learning [28], supervised autoencoders [23], and distributed learning [41]. Especially in [28], the auxiliary tasks are used for regularization, and so is the reconstruction in [23]. It is noted that all these studies are on supervised learning; for unsupervised learning, stability analysis of algorithms is yet to be developed; particularly, the role of the regularization in the stability bound remains elusive.

Stability studies of feature selection algorithms. A few existing studies about the stability of feature selection algorithms are mainly on stability measures for quantifying the sensitivity to input changes. In [21] a Shannon entropy-based stability measure is proposed for evaluating the stability of selected features. In [15] the stability of a feature selection algorithm is assessed by comparing the average pairwise similarity of all feature subsets obtained from different subsamples by the algorithm. The recent work [33] generalizes the requirements of stability measures into five properties and proposes a statistical estimator for stability to satisfy these properties. Although able to provide relevant assessment information about the selected features to some extent, most stability measures have no essential connection with the corresponding feature selection algorithms. In addition, they are demonstrated empirically in general, without theoretical insights and generalization guarantees. The only exception appears to be the theoretical proof for uniform weighting stability [25]. This work builds an algorithm called feature weighting as regularized energy-based learning (FREL), proves the stability, and extends to a further ensemble version. FREL is for supervised feature selection, and the uniform weighting stability does not appear to be linked with the generalization. In brief, despite

the wide use of algorithmic stability in analyzing many learning algorithms, its use and analysis for unsupervised feature selection algorithms are still unmet needs.

Unsupervised feature selection algorithms. Many unsupervised feature selection algorithms have been proposed in recent years to meet the demand for effectively handling large-scale and high-dimensional data. They can be generally classified into four categories including the filter, wrapper, embedder, and hybrid approaches [2, 24]. In this paper, we will mainly compare our algorithm with 10 typical unsupervised feature selection algorithms, including Laplacian score (LS) [16], principal feature analysis (PFA) [30], SPEC [46], multi-cluster feature selection (MCFS) [9], unsupervised discriminative feature selection (UDFS) [45], Nonnegative discriminative feature selection (NDFS) [26], Autoencoder feature selector (AEFS) [14], Agnostic feature selection with slack variables (AgnoS-S) [10],[1] graph-based infinite feature selection (Inf-FS) [36], and concrete autoencoders (CAE) [1]. LS, SPEC, and Inf-FS are filter approaches; PFA can be classified as a wrapper approach; and the other six are embedded algorithms. While frequently used, these methods have no theoretical analysis of their algorithmic stability and leave their generalization abilities to new data unclear. Indeed, they generally lack such needed abilities as manifested in our experiments.

3 Notations and preliminary

Let n, m, k, and d be the numbers of training samples, features, selected features, and reduced dimensions. Let $X \in \mathbb{R}^{n \times m}$ be a sample matrix, and X' be its transposition. A lowercase capital letter like w_m denotes a vector; $\text{Diag}(w_m)$ represents a diagonal matrix with the diagonal w_m. $w_m^{\max_k}$ stands for the operation to keep the k largest entries of w_m while making the other entries 0. Let $\phi : \mathbb{R}^m \to \mathbb{R}^m$ be an element-wise squaring operation. $\|\cdot\|_{\mathrm{F}}, \|\cdot\|_2, \|\cdot\|_1$, and $\|\cdot\|_\infty$ respectively denote the Frobenius, ℓ_2, ℓ_1, and infinity norms. The sample space of data is denoted as $\mathcal{X}$. We assume all samples are bounded, i.e., $\forall x \in \mathcal{X}, \exists \kappa_1 > 0$, such that $\|x\|_2 \leqslant \kappa_1$. Besides, $\forall x, x' \in [0, \infty)$, for a function f, $\Delta^t(f(x), x') \triangleq f(x) - f(x + t\Delta x)$, where $\Delta x = x' - x$ and $t \in [0, 1]$.

Let $S \triangleq \{x_i \in \mathcal{X}, i = 1, 2, \ldots, n\}$ be a finite set of training samples which are independently and identically distributed according to an unknown distribution P. We denote the sets after removing and replacing the i-th element from S by $S^{\backslash i} \triangleq \{x_1, \ldots, x_{i-1}, x_{i+1}, \ldots, x_n\}$ and $S^i \triangleq \{x_1, \ldots, x_{i-1}, x_i', x_{i+1}, \ldots, x_n\}$, respectively. Let $\boldsymbol{A}$ be an algorithm, and $\boldsymbol{A}_S$ be a function picked by $\boldsymbol{A}$ from the hypothesis space $\mathcal{H}$ based on S. $\boldsymbol{A}$ is assumed to be deterministic and symmetric with respect to S. Let $\ell : \mathcal{X} \times \mathcal{X} \to [0, +\infty)$ be a loss function. The generalization error is $L(\boldsymbol{A}, S) \triangleq \mathbb{E}_x[\ell(\boldsymbol{A}_S, x)] = \int_{\mathcal{X}} \ell(\boldsymbol{A}_S, x)dP$, and the empirical error is $L_{emp}(\boldsymbol{A}, S) \triangleq (1/n)\sum_{i=1}^n \ell(\boldsymbol{A}_S, x_i)$, where $x_i \in \mathcal{S}$. To study the stability of $\boldsymbol{A}$, the leave-one-out error is used, $L_{loo}(\boldsymbol{A}, S) \triangleq (1/n)\sum_{i=1}^n \ell(\boldsymbol{A}_{S^{\backslash i}}, x_i)$.

By the empirical and leave-one-out errors, uniform stability is defined as follows:

Definition 1 (Uniform Stability [8]). *An algorithm $\boldsymbol{A}$ has uniform stability β with respect to ℓ if $\forall S \in \mathcal{X}^n, i = 1, 2, \ldots, n, \|\ell(\boldsymbol{A}_S, \cdot) - \ell(\boldsymbol{A}_{S^{\backslash i}}, \cdot)\|_\infty \leqslant \beta$, where β is a function of n. Generally, for a uniformly stable algorithm, β decreases as $\mathcal{O}(1/n)$.*

4 Method

Now we will present our novel AE-based feature selection algorithm.

Revisit of AE. For AE, we formalize it as $\min_{f,g} \|X - f(g(X))\|_{\mathrm{F}}^2$, where g is an encoder, and f is a decoder. $g(\mathbf{X})$ embeds the input data into a latent space $\mathbb{R}^{n \times d}$, where d denotes the dimension of the bottleneck layer.

Formalization of unsupervised feature selection. Feature selection is to identify a subset of important features in the original feature space, and it can be formalized as follows:

$$\min_{S(k), H} \|H(X_{S(k)}) - X\|_{\mathrm{F}}^2, \tag{1}$$

---

[1]In [10], three variants of AE-based agnostic feature selection algorithms are proposed. AgnoS-S is the best among the three; thus, in this paper we will compare our algorithm with AgnoS-S.

where $S(k)$ denotes a subset of k features of X with $k < m$, $\text{X}_{S(k)}$ is the resulting dataset by restricting X to the selected subset. H is a mapping on the k-dimensional space, and it selects a subset of the features of X to preserve the information of X as much as possible. The optimization problem of evaluating the subset of features is typically NP-hard [31, 13]. This paper will develop an efficient algorithm to approximate the solution of (1) effectively.

AE-based new algorithm for feature selection. Our model is constructed as follows:

$$\min_{\text{W}_\text{I},f,g} \quad \|\text{X} - f(g(\text{X}(\Phi(\text{W}_\text{I})^{\max_k})))\|_\text{F}^2 + \lambda_1\|\text{X} - f(g(\text{X}\Phi(\text{W}_\text{I})))\|_\text{F}^2, \tag{2}$$

where $\Phi(\text{W}_\text{I}) \triangleq \text{Diag}(\phi(\text{w}_m))$, $\Phi(\text{W}_\text{I})^{\max_k} \triangleq \text{Diag}((\phi(\text{w}_m))^{\max_k})$, and λ_1 is a regularization parameter. Our new algorithm is to use NN for the optimization of (2), and the network architecture is shown in the Supplementary Material. For the convenience of later discussions, $\forall \text{x} \in \mathcal{X}$, let $\ell^{\text{selec}}(\Phi(\text{W}_\text{I})^{\max_k}, \text{x}) \triangleq \|\text{x} - f(g(\text{x}(\Phi(\text{W}_\text{I})^{\max_k})))\|_2^2$, and $\ell^{\text{score}}(\Phi(\text{W}_\text{I}), \text{x}) \triangleq \|\text{x} - f(g(\text{x}\Phi(\text{W}_\text{I})))\|_2^2$.

We respectively call $\Phi(\text{W}_\text{I})$ and $\Phi(\text{W}_\text{I})^{\max_k}$ feature scorer and feature selector.[2] After training our model, we obtain the feature selector and use it to make feature selection on new samples during testing. Taking MNIST-Fashion, COIL-20, and USPS as examples, for $k = 50$ and $\Phi^{\max_k} = (\text{W}_\text{I}^2)^{\max_k}$, we visualize the feature selection and reconstruction results demonstrated in Figure 1; we present more results on USPS in Figure 2 of the Supplementary Material.

Figure 1: Original testing samples (row 1), 50 selected features (row 2), and reconstruction based on the 50 selected features (row 3) for MNIST-Fashion (left panel) and COIL-20 (right panel). More results are illustrated in the Supplementary Material.

5 Algorithmic stability and generalization

As previously reviewed, existing feature selection methods have not considered algorithmic stability. Generally, they lack this property or generalization ability as manifested in our experiments. There has been neither a clue about the role of the regulation in the uniform stability. Our algorithm is built to address these issues and, here, it will be shown to have these desirable properties. For (2), the first term implies that the original samples are to be well represented by the selected k features. The second term scores all the features by their reconstruction ability and ensures that the selected features have high scores among all features. It will be used as a regularizer to promote the stability for the feature selection, and it requires that all features be explored globally for high representation ability before being further excavated locally by the selector. The role of the scorer will be demonstrated in the experiments (see Figure 2 (b)).

It is worth noting that, in contrast to existing models such as NNs that require nonlinear activation functions to capture the nonlinearity, the first term in our algorithm (2) naturally facilitates a nonlinear model even when the scorer is a linear model. Such a nonlinearity intrinsically comes from the feature weight ranking and selecting the k informative features during the iterative optimization. For simplicity, in the following discussion, we only consider the linear version of f and g in (2), that is, $g(\mathbf{X}) = \mathbf{X}\mathbf{W}_\text{E}$, $\mathbf{W}_\text{E} \in \mathbb{R}^{m \times d}$, and $f(g(\mathbf{X})) = (g(\mathbf{X}))\mathbf{W}_\text{D}$, $\mathbf{W}_\text{D} \in \mathbb{R}^{d \times m}$. In the experimental section, it will be evident that such a concise version already achieves superior performance.

Formalization of stability and generalization. Let $(\Phi_*^{\max_k}, \Phi_*)$ and $((\Phi_*^{\setminus j})^{\max_k}, \Phi_*^{\setminus j})$ correspond to the optimal feature selectors and feature scorers for the errors

---

[2]For simplicity, we will use the shorthand notations Φ and $\Phi^{\max_k}$ to denote $\Phi(\text{W}_\text{I})$ and $\Phi(\text{W}_\text{I})^{\max_k}$.

$RL_{emp}(\Phi, S) \triangleq (1/n) \sum_{i=1}^{n} \ell^{\text{selec}}(\Phi^{\max_k}, \mathrm{x}_i) + \lambda_1 \ell^{\text{score}}(\Phi, \mathrm{x}_i)$ and $RL_{emp}^{\backslash j}(\Phi, S) \triangleq$ $(1/n) \sum_{i=1, i \neq j}^{n} \ell^{\text{selec}}(\Phi^{\max_k}, \mathrm{x}_i) + \lambda_1 \ell^{\text{score}}(\Phi, \mathrm{x}_i)$, where $j \in \{1, \ldots, n\}$. Our goal is to bound $\ell^{\text{selec}}(\Phi_*^{\max_k}, \cdot) - \ell^{\text{selec}}((\Phi_*^{\backslash j})^{\max_k}, \cdot)$, which will be used for the analysis of uniform stability. Further, we intend to bound $L^{\text{selec}}(\Phi_*^{\max_k}, S) - L_{emp}^{\text{selec}}(\Phi_*^{\max_k}, S)$, or $L^{\text{selec}}(\Phi_*^{\max_k}, S) - L_{loo}^{\text{selec}}(\Phi_*^{\max_k}, S)$, to be used in the analysis of generalization errors.

Assumptions. To determine the stability and generalization bounds, the following assumptions will be needed:

Assumption 1. $\forall \mathrm{x} \in \mathcal{X}$, $\exists \kappa_2 > 0$, *such that* $\|(\mathrm{x}(\Phi_*^{\max_k} - (\Phi_*^{\backslash j})^{\max_k})\mathrm{W_E})\mathrm{W_D}\|_2 \leqslant \kappa_2 \|(\mathrm{x}(\Phi_* - \Phi_*^{\backslash j})\mathrm{W_E})\mathrm{W_D}\|_2$.

This assumption is reasonable, because the null space of $\Phi_* - \Phi_*^{\backslash j}$ is smaller than $\Phi_*^{\max_k} - \Phi^{\backslash j}$; that is, we generally have $r((((\Phi_*^{\max_k} - (\Phi_*^{\backslash j})^{\max_k})\mathrm{W_E})\mathrm{W_D})') \leqslant r(((\Phi_* - \Phi_*^{\backslash j})\mathrm{W_E}\mathrm{W_D})')$, where $r(\cdot)$ denotes the rank of a matrix, and A' denotes the transposition of A. So, it is more likely that the column vector $((\Phi_* - \Phi_*^{\backslash j})\mathrm{W_E}\mathrm{W_D})'x'$ will have m non-zero elements. Consequently, it is more likely that the row vector $(\mathrm{x}(\Phi_* - \Phi_*^{\backslash j})\mathrm{W_E})\mathrm{W_D}$ will have m non-zero elements.

Assumption 2. $\forall \mathrm{x} \in \mathcal{X}$, $\exists \mathrm{Z} = \{\mathrm{z}_1, \mathrm{z}_2, \ldots, \mathrm{z}_u\} \subset S$, *such that* x *can be reconstructed by* Z, *i.e.,* $\mathrm{x} = \sum_{i=1}^{u} \alpha_i \mathrm{z}_i + \eta$, *where* η *is a small reconstruction error that satisfies* $\|\eta\|_2 \leqslant \kappa_3/n$, *and* α_i *is a scalar that satisfies* $\sqrt{\sum_{i=1}^{u} \alpha_i^2} \leqslant \kappa_4$, *with* κ_3 *and* κ_4 *being positive constants.*

This assumption is mild and implies that any sample x can be reconstructed by Z with a small construction error that decreases with n.[3] Theoretically speaking, when the samples all reside on a manifold, it obviously holds. Practically, it is related to the self expressiveness of samples exploited in many subspace learning algorithms, e.g., [29, 19].

Assumption 3. *Let* $L_{emp}^{\text{score}, \backslash j}(\Phi) \triangleq (1/n) \sum_{i=1, i \neq j}^{n} \ell^{\text{score}}(\Phi, \mathrm{x}_i)$ *and* $L_{emp,\mathrm{z}}^{\text{score}}(\Phi) \triangleq$ $(1/u) \sum_{i=1}^{u} \ell^{\text{score}}(\Phi, \mathrm{z}_i)$. $\forall t \in [0, 1]$,

$$\Delta^t(L_{emp,\mathrm{z}}^{\text{score}}(\Phi_*), \Phi_*^{\backslash j}) + \Delta^t(L_{emp,\mathrm{z}}^{\text{score}}(\Phi_*^{\backslash j}), \Phi_*) \leqslant \frac{\Delta^t(L_{emp}^{\text{score}, \backslash j}(\Phi_*), \Phi_*^{\backslash j}) + \Delta^t(L_{emp}^{\text{score}, \backslash j}(\Phi_*^{\backslash j}), \Phi_*)}{(n-1)/n}. \tag{3}$$

The implication of this assumption is clear: it requires that, at Φ_* and $\Phi_*^{\backslash j}$, the perturbations of $L_{emp,\mathrm{z}}^{\text{score}}$ can be controlled by those of L_{emp}^{score}, and the left-hand-side of (3) is related to Z in Assumption 2. [23] makes a similar assumption; however, we enhance the factor t into $n/(n-1)$ on the right-hand-side of (3), which makes Assumption 3 much weaker and more reasonable than that in [23], since $L_{emp,\mathrm{z}}^{\text{score}}(\Phi) = (n/(n-1))L_{emp}^{\text{score}, \backslash j}(\Phi)$ when $\mathcal{Z} = S^{\backslash j}$. Further, the perturbations of $L_{emp}^{\text{score}}(\Phi_*, S)$ and $L_{emp}^{\text{score}, \backslash j}(\Phi_*)$ are implicitly related to λ_1 (see Proposition 1 below).

Proposition 1. *Let* $\Delta\Phi^{\max_k} \triangleq (\Phi_*^{\backslash j})^{\max_k} - \Phi_*^{\max_k}$. $\forall t \in [0, 1]$, *the following inequality holds:*

$$\Delta^t(L_{emp}^{\text{score}}(\Phi_*), \Phi_*^{\backslash j}) + \Delta^t(L_{emp}^{\text{score}, \backslash j}(\Phi_*), \Phi_*^{\backslash j})$$
$$\leqslant \frac{\left(t\kappa_1^2 \left(\left\| \left(2\left(\Phi_*^{\backslash j}\right)^{\max_k} - t\Delta\Phi^{\max_k} \right) \mathrm{W_E}\mathrm{W_D} \right\|_2 + 2 \right) \|((\Delta\Phi^{\max_k})\mathrm{W_E})\mathrm{W_D}\|_2 \right)}{\lambda_1}.$$

Proposition 1 reveals the relationship of the regularization represented by λ_1 with the perturbation of $L_{emp}^{\text{score}}(\Phi_*, S)$ and $L_{emp}^{\text{score}, \backslash j}(\Phi_*, S)$.

As discussed above, we will mainly verify Assumption 2. For this purpose, we develop a core-subspace learning procedure. More details about the verification are given in the Supplementary Material.

Uniform stability. We establish a bound on the uniform stability of our algorithm for (2).

---

[3]Liu et al [28] and Le et al [23] have made a similar assumption.

Theorem 1 (Uniform Stability). *Under Assumptions 1, 2, and 3, we have, $\forall n \geqslant 2$,*

$$\left\| \ell^{\mathrm{selec}}\left(\Phi_*^{\max_k}, \cdot\right) - \ell^{\mathrm{selec}}\left(\left(\Phi_*^{\backslash j}\right)^{\max_k}, \cdot\right) \right\|_\infty$$
$$\leqslant \frac{\sigma^{\mathrm{selec}}\sigma^{\mathrm{score}}\kappa_2\kappa_4^2\Delta_1\Delta_2 + u\sigma^{\mathrm{selec}}\sigma^{\mathrm{score}}\kappa_2\kappa_4^2(\kappa_2+\lambda_1)}{4\lambda_1(n-1)} + \frac{\sigma^{\mathrm{selec}}\kappa_2\kappa_3\kappa_5}{(n-1)}, \quad (4)$$

where $\Delta_1 = \sqrt{u(\kappa_2+\lambda_1) + 8\lambda_1\kappa_3\kappa_5}$, $\Delta_2 = \sqrt{u(\kappa_2+\lambda_1)}$, $\kappa_5 = \|((\Phi_* - \Phi_*^{\backslash j})W_E)W_D\|_2$, $\sigma^{\mathrm{selec}} = \kappa_1\|(\Phi_*^{\max_k} + (\Phi_*^{\backslash j})^{\max_k})W_EW_D\|_2 + 2\kappa_1$, and $\sigma^{\mathrm{score}} = \kappa_1\|(\Phi_* + \Phi_*^{\backslash j})W_EW_D\|_2 + 2\kappa_1$.

This theorem quantifies the insensitivity of our algorithm to the perturbation of its input, and the optimal feature selector $\Phi_*^{\max_k}$ would not change significantly with the change of one sample. Further, it reveals that the convergence rate of the uniform stability bound in n and λ_1 is $\mathcal{O}\left(1/\left(n\min\{\sqrt{\lambda_1}, \lambda_1\}\right)\right)$. The upper bound in (4) is theoretically more meaningful when λ_1 is much larger than $1/n$.

Generalization error bound. Now we will bound $L_{emp}^{\mathrm{selec}}(\Phi_*^{\max_k}, S) - L^{\mathrm{selec}}(\Phi_*^{\max_k}, S)$.

Theorem 2 (Generalization Error). *Given $\mathbf{x} \in \mathcal{X}$, S, $\ell(\mathbf{A}_S, \mathbf{x}) \leqslant \kappa_5$, and $\delta \in (0, 1)$, the following inequality holds with probability at least $1 - \delta$,*

$$L^{\mathrm{selec}}(\Phi_*^{\max_k}, S) - L_{emp}^{\mathrm{selec}}(\Phi_*^{\max_k}, S)$$
$$\leqslant \frac{\sigma^{\mathrm{selec}}\sigma^{\mathrm{score}}\kappa_2\kappa_4^2\left(1 + \sqrt{2n\ln\left(\frac{1}{\delta}\right)}\right)\Delta_1\Delta_2}{2\lambda_1(n-1)} + \kappa_5\sqrt{\frac{\ln\left(\frac{1}{\delta}\right)}{2n}} + \frac{\left(1 + \sqrt{2n\ln\left(\frac{1}{\delta}\right)}\right)\Delta_3}{2\lambda_1(n-1)}, \quad (5)$$

where $\Delta_3 = u\sigma^{\mathrm{selec}}\sigma^{\mathrm{score}}\kappa_2\kappa_4^2(\kappa_2+\lambda_1) + 4\lambda_1\sigma^{\mathrm{selec}}\kappa_2\kappa_3\kappa_5$.

This theorem shows that, aside with the uniform stability bound in Theorem 1, there is an upper bound for the generalization error of our algorithm. The convergence rate of the generalization error bound is $\mathcal{O}\left(1/\left(\sqrt{n}\min\{\sqrt{\lambda_1}, \lambda_1\}\right)\right)$. It is noted that, when $\lambda_1 > 1$, the convergence rate is $\mathcal{O}\left(1/\left(\sqrt{n\lambda_1}\right)\right)$, which is different from the rate under the ℓ_2 regularization; when $\lambda_1 \leqslant 1$, it has the convergence rate $\mathcal{O}\left(1/\left(\sqrt{n}\lambda_1\right)\right)$, the same as that under the ℓ_2 regularization [8]. This "phase transition" with λ_1 may be because, when the reconstruction error from the feature scorer is made small with a large $\lambda_1 > 1$, the selected model might be underfitted (see Figure 2 (b) for $\lambda_1 > 1$), then the reconstruction error from the feature selector would become more perturbable than $\lambda_1 \leqslant 1$; and vice versa for $\lambda_1 \leqslant 1$. By this theorem, as long as our feature selection algorithm is stable, the empirical error has a proven guarantee to approximate the generalization error. Additionally, if we fix λ_1, the bound will reduce to $\mathcal{O}(1/\sqrt{n})$, which decays similarly to the bound under the ℓ_2 regularization [8].

The proofs of Proposition 1, Theorems 1 and 2, the bound of $L^{\mathrm{selec}}(\Phi_*^{\max_k}, S) - L_{loo}^{\mathrm{selec}}(\Phi_*^{\max_k}, S)$, and more discussions are provided in the Supplementary Material.

6 Experiments

In this section, we will perform extensive experiments to validate our new algorithm.

Table 1: Statistics of datasets.

No.	Dataset	#Samples	#Features	#Classes	No.	Dataset	#Samples	#Features	#Classes
1	Mice Protein	1,080	77	8	6	USPS	9,298	256	10
2	COIL-20 [32]	1,440	400	20	7	GLIOMA	50	4,434	4
3	Activity [4]	5,744	561	6	8	Prostate_GE	102	5,966	2
4	ISOLET	7,797	617	26	9	SMK_CAN_187	187	19,993	2
5	MNIST-Fashion [42]	10,000	784	10	10	arcene	200	10,000	2

Datasets to be used. The benchmarking datasets and their statistics are summarized in Table 1.[4] Following CAE [1] and considering the long runtime of UDFS, for dataset 5, we randomly choose

---

[4]Datasets 1 and 4 are downloaded from http://archive.ics.uci.edu/ml/datasets/. Datasets 6-10 are from the scikit-feature feature selection repository [24].

6,000 samples from the training set to train and validate and 4,000 samples from the test set for testing. We then randomly split 6,000 samples into training and validation sets by a ratio of 90 : 10. For other datasets, we randomly split the samples into training, validation, and test sets by a ratio of 72 : 8 : 20, and we tune hyper-parameters on the validation set.

Design of experiments. In all experiments, for our model, we set the maximum number of epochs to be 200. We initialize the weights of feature selection layer by sampling uniformly from $U[0.999999, 0.9999999]$ and the other layers with the Xavier normal initializer.[5] We adopt the Adam optimizer [20] with a learning rate of 0.001. We set λ_1 to be $1/2^7$.[6] We take $k = 10$ for dataset 1 and $k = 50$ for datasets 2-6 following CAE [1], and $k = 64$ for high-dimensional datasets 7-10. The dimension of the latent space is consistently set to k. The implementation details of baseline algorithms are provided in the Supplementary Material.

Two metrics are used for evaluating the performance of algorithms: 1) reconstruction error, which is measured in mean squared error (MSE); 2) accuracy, which is measured by passing the selected features to a downstream classifier as a viable means to benchmark the quality of selected features. For a fair comparison, following CAE [1], after selecting the features, we train an ordinary linear regression model to reconstruct the original features, and the resulting linear reconstruction error is used as metric 1);[7] for metric 2) we use extremely randomized trees [12] as the classifier.

Results on 10 datasets. Our experimental results on reconstruction and classification with the selected features are displayed in Tables 2 and 3,[8] and $|W_I|$ and W_I^2 are shorthands for feature selectors $\Phi^{\max_k} = |W_I|^{\max_k}$ and $\Phi^{\max_k} = (W_I^2)^{\max_k}$. We followed the way of CAE [1] to split samples and to report the final results on the hold-out test set. For a fair comparison, we directly adopt the published results for reconstruction and classification by LS, AEFS, UDFS, MCFS, PFA, and CAE on datasets 1-5 from [1]. From Table 2, it is seen that our algorithm gives smaller linear reconstruction errors than baseline methods on majority datasets, indicating a stronger ability to select a subset of representative features. From Table 3, it is evident that our algorithm exhibits almost consistently superior performance in the downstream classification task on diverse datasets.

Table 2: Linear reconstruction error with selected features by different algorithms.

Dataset No.	LS	SPEC	NDFS	AEFS	UDFS	MCFS	PFA	Inf-FS	AgnoS-S	CAE	Ours $|W_I|$	Ours W_I^2
1	0.603	0.051	0.041	0.783	0.867	0.695	0.871	0.601	0.013	0.372	0.009	**0.008**
2	0.126	0.413	0.134	0.061	0.116	0.085	0.061	0.130	0.038	0.093	**0.015**	0.016
3	0.139	0.127	144.353	0.112	0.173	0.170	0.010	0.282	0.010	0.108	**0.005**	**0.005**
4	0.344	0.119	0.129	0.301	0.375	0.471	0.316	0.098	0.042	0.299	**0.016**	0.018
5	0.128	0.107	0.127	0.047	0.133	0.096	0.043	0.094	0.024	0.041	**0.022**	0.023
6	3.528	1.120	0.918	0.025	0.034	1.050	0.022	5.245	0.017	**0.010**	0.018	0.018
7	0.140	0.210	0.404	0.060	0.060	0.173	0.055	0.163	**0.054**	0.063	0.067	0.070
8	1.694	0.605	4.506	0.280	0.228	1.929	0.180	0.187	0.387	**0.048**	0.172	0.144
9	7.344	0.118	3.005	0.102	\	5.492	0.089	8.725	0.096	**0.077**	0.093	0.100
10	0.328	0.045	1335.029	0.025	\	4.826	0.042	329.507	0.031	0.029	0.025	**0.024**

Further, we compare the behavior of our algorithm with contemporary algorithms over different k. By varying k on ISOLET we obtain the corresponding linear reconstruction errors and classification accuracy rates as the outputs from different algorithms. We plot the linear reconstruction errors in MSE and classification accuracy rates in Figure 9 in the Supplementary Material. It can be observed that our algorithm demonstrates almost consistently better and more stable performance than feature selection algorithms in comparison.

Also, we take $\Phi^{\max_k} = |W_I|^{\max_k}$, and we compare the variation of classification accuracy with the reduction of original features. The results are shown in Table 1 and Figure 10 in the Supplementary Material. It is observed that all the reduction in the number of features is more than 80%, while the corresponding reduction in classification accuracy is less than 10% with the exception of ISOLET.

---

[5]This distribution makes initial values of the weights in the selection layer close to 1 but still different.

[6]We tune λ_1 by searching in $\{2, 1/2^0, \ldots, 1/2^{10}\}$ on the validation set, then we choose the optimal one.

[7]Here, the reconstruction error denotes the error from the first term of (2).

[8]The "\" mark denotes the case with prohibitive running time, where the algorithm ran for more than a week without getting a result and thus was stopped.

Table 3: Classification accuracy (%) with selected features by different algorithms.

Dataset No.	LS	SPEC	NDFS	AEFS	UDFS	MCFS	PFA	Inf-FS	AgnoS-S	CAE	Ours	
											$\lvert W_I \rvert$	W_I^2
1	13.4	24.5	8.3	12.5	13.9	13.9	13.0	42.6	51.9	13.4	97.2	**99.1**
2	38.9	14.9	21.2	58.0	55.6	63.5	64.2	37.8	89.2	58.6	96.9	**97.9**
3	28.0	20.3	18.8	24.0	28.7	29.5	36.4	18.1	56.1	42.0	**87.7**	87.6
4	40.7	5.8	7.3	57.6	45.5	52.2	62.2	13.7	18.1	68.5	**83.9**	82.4
5	51.7	27.6	13.8	58.0	54.7	51.3	68.3	23.5	79.1	67.7	**80.8**	80.5
6	36.3	46.3	11.9	94.2	94.4	12.6	96.0	21.0	95.6	95.5	**96.1**	95.4
7	50.0	20.0	40.0	80.0	70.0	40.0	80.0	20.0	80.0	50.0	**90.0**	80.0
8	52.4	47.6	47.6	85.7	90.5	57.1	90.5	61.9	76.2	85.7	**95.2**	90.5
9	57.9	65.8	42.1	50.0	\	44.7	65.8	47.4	65.8	68.4	**73.7**	57.9
10	62.5	32.5	70.0	75.0	\	62.5	77.5	67.5	77.5	77.5	**82.5**	75.0
Average	43.2±14.1	30.5±17.0	28.1±19.7	59.5±24.7	56.7±26.2	42.7±17.7	65.4±23.5	35.4±18.1	70.0±21.3	63.3±22.4	**87.9±8.8**	84.6±11.8

It shows that our algorithm can effectively reduce the number of features but still maintain the classification performance comparable to the original data.

7 Discussion

In this section, we will empirically verify the properties related to the uniform stability bound and generalization bound in Theorems 1 and 2. Further, we will discuss the algorithmic stability and the stability of selected features and also analyze the time complexity of (2).

Effect of n. We plot the curves of error difference $L^{\mathrm{selec}}\left(\Phi_*^{\max_k}, S\right) - L_{emp}^{\mathrm{selec}}\left(\Phi_*^{\max_k}, S\right)$ and test error versus n in Figure 2 (a). It is observed that n has a direct effect on the error difference and test error: (1) The more training samples, generally the smaller the test error. This observation verifies that small training sets cause overfitting and, by increasing the training set size, the generalization of our algorithm becomes improved with the test error decreased. (2) The error difference decreases in n. This phenomenon is well in line with the theoretical result in Theorem 2.

Effect of λ_1. We plot the curves of the error difference and test error versus λ_1 in Figure 2 (b). Two observations can be made: (1) The larger λ_1, the smaller the error difference. This experimental result aligns well with Theorem 2. (2) The test error decreases at first and then increases with λ_1. The reason may be as follows: by increasing λ_1 from zero to about 0.01, the feature scorer will play an increasingly important role and facilitate to find appropriate scores to reduce the reconstruction error, which helps decrease the test error. The regularization role of the scorer is evident: when λ_1 increases from 0 to a small value, the test error decreases. But if λ_1 increases too much, it would over-emphasize the scorer and the minimization of the reconstruction error, making the feature selector underfit training samples and thus incurring larger test errors. These empirical curves offer informative clues for understanding the role of regularization in the generalization bound and choosing a proper λ_1 in our experiments.

Effect of k. We plot the curves of the error difference and test error versus k in Figure 2 (c). It is seen that the larger k, the larger the error difference. This observation is in line with Theorem 2. As discussed below this theorem, the generalization error bound of our algorithm has a similar convergence rate to that under the ℓ_2 regularization. To see how the selection affects the error difference, we plot the curves of Frobenius norms of $W_E W_D$ and $W_0 W_E W_D$ in Figure 2 (d). Note that they have a similar increase tendency to the error difference. The reason may be that selecting more features implies that $L^{\mathrm{selec}}\left(\Phi_*^{\max_k}, S\right)$ and $L_{emp}^{\mathrm{selec}}\left(\Phi_*^{\max_k}, S\right)$ depend on more variables, and would be more easily affected by the perturbations from the variables; as a result, the feature selector would be more difficult to fit. From Figure 2 (c) we can also observe that the larger k, the smaller the test error, which is sensible because more selected features mean less loss of original data and the reconstruction would be better. In addition, from Figure 2 (a) and (c), different Φ_* scorers, such as $\lvert W_I \rvert$ and W_I^2, have similar behaviors, which reflects the tendency implied in Theorem 2.

Algorithmic stability analysis. Adopting the same experiment design on MNIST-Fashion in Section 6, we vary n from $3,000$ to $6,000$ with a step size of $1,000$ to obtain different S; meanwhile, we delete a sample for each of these S to get the corresponding $S^{\backslash i}$ and then calculate the left-hand

side of (4) on the testing set for these trained models. From the plots in Figure 2 (e) and (f), it is seen that with the increase of n, the curve of the uniform stability bound presents a downward tendency, which is consistent with our theoretical analysis.

Figure 2: Empirical interpretation of generalization bound and stability analysis on MNIST-Fashion. (a)-(c) show the curves of error difference and test error versus n, λ_1, and k, respectively; (d) plots the overall size of network weights versus k; (e) and (f) are for algorithmic stability; (g) and (h) are for the stability analysis of 10 selected features. In each of (a)-(c), the left vertical axis represents error difference, and the right vertical axis represents test error.

Overall, the above four experiments for interpreting the generalization bound are related to the training sample size n, the regularization parameter λ_1, and number of selected features k, and stability bound, showing different aspects or behaviors of our algorithm. Taken together, these experiments verify the properties revealed by Theorems 1 and 2.

Stability analysis of selected features. We empirically analyze the stability of features selected by (2). We randomly split the samples of MNIST-Fashion into the training and testing sets and then use (2) to perform feature selection. We repeat this procedure 10 times with different random seeds and plot the selection results in Figure 2 (g) and (h). Note that the selected features almost overlap for different splits and are stable. More results are provided in the Supplementary Material.

Computational complexity. Experimentally, the computational time of our algorithm (2) is about twice that of AE. Our algorithm has only an additional sub-NN compared to AE and shares parameters with the global-NN. Also, the fitting error term of sub-NN is quadratic and similar to that of AE. Therefore, the overall computational complexity of (2) is of the same order as AE.

Ethical statement. This paper focuses on feature selection, which is a dimensionality reduction approach. To our best knowledge, there are no ethical issues and negative societal impacts of the proposed technique in this paper.

8   Conclusions

In this paper, we propose an innovative unsupervised feature selection algorithm with provable performance guarantees, which consists of a feature scorer and a feature selector. Theoretically, we prove the uniform stability and provide the generalization error upper bound for our algorithm. Empirically, we show that our algorithm achieves performance better than the contemporary algorithms on various real-world datasets; meanwhile, the selected features by the proposed algorithm show comparable performance to the original features. Also, we experimentally verify the properties revealed by our theoretical analysis with respect to the training sample size, the regularization, the number of selected features, and the uniform stability.

References

[1] A. Abid, M. F. Balin, and J. Zou. Concrete autoencoders: Differentiable feature selection and reconstruction. In *International Conference on Machine Learning*, pages 444–453, Long Beach, California, United States, June 2019.

[2] S. Alelyani, J. Tang, and H. Liu. Feature selection for clustering: A review. In C. C. Aggarwal and C. K. Reddy, editors, *Data Clustering: Algorithms and Applications*, chapter 2, pages 29–60. CRC Press, 1st edition, August 2013.

[3] R. C. Anafi, L. J. Francey, J. B. Hogenesch, and J. Kim. CYCLOPS reveals human transcriptional rhythms in health and disease. *The Proceedings of the National Academy of Sciences*, 114(20): 5312–5317, April 2017.

[4] D. Anguita, A. Ghio, L. Oneto, X. Parra, and J. L. Reyes-Ortiz. A public domain dataset for human activity recognition using smartphones. In *European Symposium on Artificial Neural Networks, Computational Intelligence And Machine Learning*, pages 437–442, Bruges, Belgium, April 2013.

[5] D. H. Ballard. Modular learning in neural networks. In *National Conference on Artificial Intelligence*, pages 279–284, Seattle, Washington, United States, July 1987.

[6] P. L. Bartlett and S. Mendelson. Rademacher and gaussian complexities: Risk bounds and structural results. *Journal of Machine Learning Research*, 3:463–482, November 2002.

[7] R. Bellman. *Dynamic Programming*. Princeton University Press, Princeton, New Jersey, United States, 1st edition, 1957.

[8] O. Bousquet and A. Elisseeff. Stability and generalization. *Journal of Machine Learning Research*, 2:499–526, March 2002.

[9] D. Cai, C. Zhang, and X. He. Unsupervised feature selection for multi-cluster data. In *International conference on Knowledge discovery and data mining*, pages 333–342, Washington, District of Columbia, United States, July 2010.

[10] G. Doquet and M. Sebag. Agnostic feature selection. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pages 343–358, Würzburg, Germany, September 2019.

[11] K. Dunne, P. Cunningham, and F. Azuaje. Solutions to instability problems with sequential wrapper-based approaches to feature selection. Technical Report TCD- CS-2002-28, School of Computer Science, Trinity College Dublin, Dublin, Ireland, July 2002.

[12] P. Geurts, D. Ernst, and L. Wehenkel. Extremely randomized trees. *Machine learning*, 63(1): 3–42, March 2006.

[13] Y. Hamo and S. Markovitch. The COMPSET algorithm for subset selection. In *International Joint Conference on Artificial Intelligence*, pages 728–733, Edinburgh, Scotland, United Kingdom, July-August 2005.

[14] K. Han, Y. Wang, C. Zhang, C. Li, and C. Xu. Autoencoder inspired unsupervised feature selection. In *International Conference on Acoustics, Speech and Signal Processing*, pages 2941–2945, Calgary, Alberta, Canada, April 2018.

[15] Y. Han and L. Yu. A variance reduction framework for stable feature selection. In *IEEE International Conference on Data Mining*, pages 206–215, Sydney, Australia, December 2010.

[16] X. He, D. Cai, and P. Niyogi. Laplacian score for feature selection. In *Advances in Neural Information Processing Systems*, pages 507–514, Vancouver, British Columbia, Canada, December 2005.

[17] P. Ji, T. Zhang, H. Li, M. Salzmann, and I. Reid. Deep subspace clustering networks. In *Advances in Neural Information Processing Systems*, pages 23–32, Long Beach, California, United States, December 2017.

[18] A. Kalousis, J. Prados, and M. Hilario. Stability of feature selection algorithms. In *IEEE International Conference on Data Mining*, pages 218–225, Texas, USA, November 2005.

[19] Z. Kang, X. Zhao, C. Peng, H. Zhu, J. T. Zhou, X. Peng, W. Chen, and Z. Xu. Partition level multiview subspace clustering. *Neural Networks*, 122:279–288, February 2020.

[20] D. P. Kingma and J. L. Ba. Adam: A method for stochastic optimization. In *International Conference for Learning Representations*, San Diego, California, USA, May 2015.

[21] P. Krizek. *Feature selection: stability, algorithms, and evaluation*. PhD thesis, Czech Technical University, June 2008.

[22] A. P. Kumar and P. Valsala. Feature selection for high dimensional dna microarray data using hybrid approaches. *Bioinformation*, 9(16):824–828, September 2013.

[23] L. Le, A. Patterson, and M. White. Supervised autoencoders: Improving generalization performance with unsupervised regularizers. In *Advances in Neural Information Processing Systems*, pages 107–117, Montreal, Canada, December 2018.

[24] J. Li, K. Cheng, S. Wang, F. Morstatter, R. P. Trevino, J. Tang, and H. Liu. Feature selection: A data perspective. *ACM Computing Surveys*, 50(6):1–45, December 2017.

[25] Y. Li, J. Si, G. Zhou, S. Huang, and S. Chen. FREL: A stable feature selection algorithm. *IEEE Transactions on Neural Networks and Learning Systems*, 26(7):1388–1402, July 2015.

[26] Z. Li, Y. Yang, J. Liu, X. Zhou, and H. Lu. Unsupervised feature selection using nonnegative spectral analysis. In *AAAI Conference on Artificial Intelligence*, pages 1026–1032, Toronto, Ontario, Canada, July 2012.

[27] S. Liang, A. Ma, S. Yang, Y. Wang, and Q. Ma. A review of matched-pairs feature selection methods for gene expression data analysis. *Computational and Structural Biotechnology Journal*, 16:88–97, February 2018.

[28] T. Liu, D. Tao, M. Song, and S. J. Maybank. Algorithm-dependent generalization bounds for multi-task learning. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 39(2): 227–241, February 2017.

[29] C.-Y. Lu, H. Min, Z.-Q. Zhao, L. Zhu, D.-S. Huang, and S. Yan. Robust and efficient subspace segmentation via least squares regressio. In *European Conference on Computer Vision*, pages 347–360, Florence, Italy, October 2012.

[30] Y. Lu, I. Cohen, X. S. Zhou, and Q. Tian. Feature selection using principal feature analysis. In *International conference on Multimedia*, pages 301–304, Augsburg, Bavaria, Germany, September 2007.

[31] B. K. Natarajan. Sparse approximate solutions to linear systems. *SIAM Journal on Computing*, 24(2):227–234, April 1995.

[32] S. A. Nene, S. K. Nayar, and H. Murase. Columbia object image library (COIL-20). Technical Report CUCS-005-96, Department of Computer Science, Columbia University, New York, United States, February 1996.

[33] S. Nogueira, K. Sechidis, and G. Brown. On the stability of feature selection algorithms. *Journal of Machine Learning Research*, 18(174):1–54, April 2018.

[34] K. Pearson. LIII. On lines and planes of closest fit to systems of points in space. *The London, Edinburgh, and Dublin Philosophical Magazine and Journal of Science*, 2(11):559–572, November 1901.

[35] R. M. Rifkin. *Everything old is new again : a fresh look at historical approaches in machine learning*. PhD thesis, Massachusetts Institute of Technology, September 2002.

[36] G. Roffo, S. Melzi, and M. Cristani. Infinite feature selection. In *International Conference on Computer Vision*, pages 4202–4210, Santiago, Chile, December 2015.

[37] D. E. Rumelhart, G. E. Hinton, and R. J. Williams. Learning internal representations by error propagation. ICS Report 8506, Institute for Cognitive Science, University of California, San Diego, La Jolla, California, United States, September 1985.

[38] A. N. Tikhonov. On the stability of inverse problems (in Russian). *Doklady Akademii Nauk SSSR*, 39(5):195–198, 1943.

[39] A. N. Tikhonov, A. V. Goncharsky, V. V. Stepanov, and A. G. Yagola. *Numerical Methods for the Solution of Ill-Posed Problems*. Springer Netherlands, Moscow, Russia, 1st edition, 1995.

[40] V. N. Vapnik. An overview of statistical learning theory. *IEEE Transactions on Neural Networks*, 10(5):988–999, September 1999.

[41] X. Wu, J. Zhang, and F.-Y. Wang. Stability-based generalization analysis of distributed learning algorithms for big data. *IEEE Transactions on Neural Networks and Learning Systems*, 31(3): 801–812, March 2020.

[42] H. Xiao, K. Rasul, and R. Vollgraf. Fashion-MNIST: a novel image dataset for benchmarking machine learning algorithms. *arXiv: 1708.07747v2, https://arxiv.org/pdf/1708.07747.pdf*, September 2017.

[43] J. Xie, R. Girshick, and A. Farhadi. Unsupervised deep embedding for clustering analysis. In *International Conference on Machine Learning*, pages 478–487, New York, United States, June 2016.

[44] H. Xu and S. Mannor. Robustness and generalization. *Machine Learning*, 86(3):391–423, March 2012.

[45] Y. Yang, H. T. Shen, Z. Ma, Z. Huang, and X. Zhou. $\ell_{2,1}$-norm regularized discriminative feature selection for unsupervised learning. In *International Joint Conference on Artificial Intelligence*, pages 1589–1594, Barcelona, Catalonia, Spain, July 2011.

[46] Z. Zhao and H. Liu. Spectral feature selection for supervised and unsupervised learning. In *International Conference on Machine Learning*, pages 1151–1157, Corvallis, Oregon, United States, June 2007.