VIMA: General Robot Manipulation with Multimodal Prompts

Abstract

Prompt-based learning has emerged as a successful paradigm in natural language processing, where a single general-purpose language model can be instructed to perform any task specified by input prompts. Yet task specification in robotics comes in various forms, such as imitating one-shot demonstrations, following language instructions, and reaching visual goals. They are often considered different tasks and tackled by specialized models. This work shows that we can express a wide spectrum of robot manipulation tasks with *multimodal prompts*, interleaving textual and visual tokens. We design a transformer-based generalist robot agent, VIMA, that processes these prompts and outputs motor actions autoregressively. To train and evaluate VIMA, we develop a new simulation benchmark with thousands of procedurally-generated tabletop tasks with multimodal prompts, 600K+ expert trajectories for imitation learning, and four levels of evaluation protocol for systematic generalization. VIMA achieves strong scalability in both model capacity and data size. It outperforms prior SOTA methods in the hardest zero-shot generalization setting by up to $2.9\times$ task success rate given the same training data. With $10\times$ less training data, VIMA still performs $2.7\times$ better than the top competing approach. Video demos are available at https://iclr3081.github.io/.

1 Introduction

Transformers have given rise to remarkable multi-task consolidation across many AI domains. For example, users can describe a task using natural language prompt to GPT-3 (Brown et al., 2020), allowing the same model to perform question answering, machine translation, text summarization, etc. Prompt-based learning provides an accessible and flexible interface to communicate a natural language understanding task to a general-purpose model.

We envision that a generalist robot agent should have a similarly intuitive and expressive interface for task specification. What does such an interface for robot learning look like? As a motivating example, consider a personal robot tasked with household activities. We can ask the robot to bring us a cup of water by a simple natural language instruction. If we require more specificity, we can instead instruct the robot to "bring me <image of the cup>". For tasks requiring new skills, the robot should be able to adapt preferably from a few video demonstrations (Duan et al., 2017). Tasks that need interaction with unfamiliar objects can be easily explained via a few image examples for *novel concept grounding* (Hermann et al., 2017). Finally, to ensure safe deployment, we can further specify visual constraints like "do not enter <image> room".

To enable a single agent with all these capabilities, we make three key contributions in this work: 1) a novel **multimodal prompting formulation** that converts a wide spectrum of robot manipulation tasks into one sequence modeling problem; 2) a new **robot agent model** capable of multi-tasking and zero-shot generalization; and 3) a **large-scale benchmark** with diverse tasks to systematically evaluate the scalability and generalization of our agents.

We start with the observation that many robot manipulation tasks can be formulated by **multimodal prompts that interleave language and images or video frames** (denoted by "{image}" in Fig. 1). For example, Rearrangement (Batra et al., 2020), a type of *Visual Goal*, can be formulated as "Please rearrange objects to match this {scene_image}"; *Novel Concept Grounding* looks like "This is a dax {new_object}$_1$ and this is a blicket {new_object}$_2$. Put two metal dax on the marble blicket."; *Few-shot Imitation* can embed video snippet in the prompt "Follow this motion

Figure 1: **Multimodal prompts for task specification.** We observe that many robot manipulation tasks can be expressed as *multimodal prompts* that interleave language and image/video frames. We propose VIMA, an embodied agent model capable of processing mulitimodal prompts (left) and controlling a robot arm to solve the task (right).

trajectory for the wooden cube: {frame₁}, {frame₂}, {frame₃}, {frame₄}"; and expressing *Visual Constraint* is as simple as adding the clause "without touching {safety_boundary}".

Multimodal prompts not only have more expressive power than individual modalities, but also enable a **uniform sequence IO interface** for training generalist robot agents. Previously, different robot manipulation tasks require distinct policy architectures, objective functions, data pipelines, and training procedures (Aceituno et al., 2021; Stengel-Eskin et al., 2022; Lynch & Sermanet, 2021), leading to siloed robot systems that cannot be easily combined for a rich set of use cases. Instead, our multimodal prompt interface allows us to harness the latest advances in large transformer models (Lin et al., 2021; Tay et al., 2020; Khan et al., 2021) for developing scalable multi-task robot learners.

To this end, we design a novel **Vi**suo**M**otor **A**ttention model (VIMA). The architecture follows the encoder-decoder transformer design proven to be effective and scalable in NLP (Raffel et al., 2020). VIMA encodes an input sequence of interleaving textual and visual prompt tokens with a pretrained language model (Tsimpoukelli et al., 2021), and decodes robot control actions autoregressively for each environment interaction step. The transformer decoder is conditioned on the prompt via cross-attention layers that alternate with the usual causal self-attention. Instead of operating on raw pixels, VIMA adopts an object-centric approach. We parse all images in the prompt or observation into objects by off-the-shelf detectors (He et al., 2017), and flatten them into sequences of object tokens. All these design choices combined deliver a conceptually simple architecture with strong model and data scaling properties.

To systematically evaluate our proposed algorithm, we introduce a new benchmark (VIMA-BENCH) built on the Ravens simulator (Zeng et al., 2020; Shridhar et al., 2021). We provide 17 representative meta-tasks with multimodal prompt templates, which can be procedurally instantiated into thousands of individual tasks by various combinations of textures and tabletop objects. VIMA-BENCH establishes a 4-level protocol to evaluate progressively stronger generalization capabilities, from randomized object placement to novel tasks altogether (Fig. 2). To demonstrate the scalability of VIMA, we train a spectrum of 7 models ranging from 2M to 200M parameters. Our approach outperforms strong prior SOTA methods such as Gato (Reed et al., 2022), Decision Transformer (Chen et al., 2021), and Flamingo (Alayrac et al., 2022) across all 4 levels of zero-shot generalization and all model capacities, sometimes by a large margin (up to 2.9× task success rate given the same amount of

training data, and $2.7\times$ better even with $10\times$ less data). We plan to open-source the simulation environment, training dataset, algorithm code, and pretrained model checkpoints to ensure reproducibility and facilitate future works from the community. We attach supplementary materials as Appendix to this PDF, and present video demos and anonymized code at `https://iclr3081.github.io/`.

2 RELATED WORK

Multi-task Learning by Sequence Modeling. Transformers have enabled task unification across many AI domains (Raffel et al., 2020; Radford et al., 2019; Brown et al., 2020; Chen et al., 2022a;b; Lu et al., 2022; Wang et al., 2022c; Alayrac et al., 2022; Reed et al., 2022). For example, in **NLP**, T5 (Raffel et al., 2020) unifies all language problems into the same text-to-text format. GPT-3 (Brown et al., 2020), PaLM (Chowdhery et al., 2022), and Megatron-Turing NLG (Shoeybi et al., 2019) demonstrate emergent behaviours of intuitive task specifications by zero-shot prompting without any finetuning. In **computer vision**, Florence (Yuan et al., 2021), BiT (Kolesnikov et al., 2020), and MuST (Ghiasi et al., 2021) pre-train a shared backbone model at scale for general visual representations and transfer it across downstream vision tasks. Pix2Seq (Chen et al., 2022b) casts many vision problems into a unified sequence format. In **multimodal learning**, Flamingo (Alayrac et al., 2022) and Frozen (Tsimpoukelli et al., 2021) design a universal API that ingests an interleaving sequence of images and text and generates free-form text. Gato (Reed et al., 2022) is a massively multi-task model across NLP, vision, and embodied agents. Our work is most similar in spirit to Gato, but we focus primarily on enabling an intuitive, multimodal prompting interface for a generalist robot agent.

Foundation Models for Embodied Agents. Foundation models (Bommasani et al., 2021; Brown et al., 2020; Raffel et al., 2020; Ramesh et al., 2022; Wei et al., 2022) have demonstrated strong emergent properties like zero-shot prompting and complex reasoning. There are many ongoing efforts to replicate this success for embodied agents, focusing on 3 aspects: 1) **Transformer agent architecture**: Decision Transformer (Chen et al., 2021; Janner et al., 2021; Zheng et al., 2022) and Gato (Reed et al., 2022) leverage the powerful self-attention models for sequential decision making. CLIPort (Shridhar et al., 2021) and Perceiver-Actor (Shridhar et al., 2022) apply large transformers to robot manipulation tasks. 2) **Pre-training for better representations**: Masked ViT (Gupta et al., 2022), R3M (Nair et al., 2022), and Parisi et al. (2022) pre-train general visual representations for robotic perception. Li et al. (2022); Reid et al. (2022) finetune from LLM checkpoints to accelerate policy learning. MineDojo (Fan et al., 2022) and Ego4D (Grauman et al., 2021) provide large-scale multimodal databases to facilitate scalable policy training. 3) **Large language models for robot learning**: SayCan (Ahn et al., 2022) leverages the 500B PaLM (Chowdhery et al., 2022) for zero-shot concept grounding. Socratic Models (Zeng et al., 2022) composes multiple vision and language foundation models (VLMs) for multimodal reasoning in videos. Huang et al. (2022a), Inner Monologue (Huang et al., 2022b) and LM-Nav (Shah et al., 2022) successfully apply LLMs to long-horizon robot planning. VIMA differs from these works in our novel multimodal prompting formulation, which existing LLMs and VLMs do not easily support.

Robot Manipulation and Benchmarks. There are a wide range of robot manipulation tasks that require different skills and task specification formats, such as instruction following (Stepputtis et al., 2020; Shridhar et al., 2021; Lynch & Sermanet, 2021), one-shot imitation (Finn et al., 2017; Dasari & Gupta, 2020; Duan et al., 2017), rearrangement (Batra et al., 2020; Weihs et al., 2021; Szot et al., 2021), constraint satisfaction (Brunke et al., 2021; Srinivasan et al., 2020; Thananjeyan et al., 2021), and reasoning (Shridhar et al., 2020; Gupta et al., 2019; Ahmed et al., 2021; Toyer et al., 2020; Lim et al., 2021). Multiple physics simulation benchmarks are introduced to study the above tasks. For example, iGibson (Shen et al., 2020; Li et al., 2021; Srivastava et al., 2021) simulates interactive household scenarios. Ravens (Zeng et al., 2020) and Robosuite (Zhu et al., 2020; Fan et al., 2021) design various tabletop manipulation tasks with realistic robot arms. Our VIMA-BENCH is the first robot learning benchmark to support multimodal-prompted tasks. We also standardize the evaluation protocol to systematically measure an agent's generalization capabilities.

A more extended literature review can be found in Appendix, Sec. F.

Figure 2: **Evaluation Protocol in VIMA-BENCH**. We design 4 levels of evaluation settings to measure the zero-shot generalization capability of an agent systematically. Each level deviates more from the training distribution, and thus is strictly more challenging than the previous level.

3 MULTIMODAL PROMPTS FOR TASK SPECIFICATION

A central and open problem in robot learning is task specification (Agrawal, 2022). Our key insight is that various task specification paradigms (such as goal conditioning, video demonstration, natural language instruction) can all be instantiated as multimodal prompts (Fig. 1). Concretely, a multimodal prompt $\mathcal{P}$ of length l is defined as an ordered sequence of arbitrarily interleaved texts and images $\mathcal{P} := [x_0, x_1, \ldots, x_l]$, where each element $x_i \in \{\text{text}, \text{image}\}$.

Task Suite.   The flexibility afforded by multimodal prompts allows us to specify and build models for a huge variety of task specification formats. Here we consider the following six task categories:

1. **Simple object manipulation**: simple tasks like "put `<object>` into `<container>`", where each image in the prompt corresponds to a single object;

2. **Visual goal reaching**: manipulating objects to reach a goal configuration, *e.g.*, *Rearrangement* (Batra et al., 2020);

3. **Novel concept grounding**: the prompt contains unfamiliar words like "dax" and "blicket", which are explained by in-prompt images and then immediately used in an instruction. This tests the agent's ability to rapidly internalize new concepts;

4. **One-shot video imitation**: watching a video demonstration and learning to reproduce the same motion trajectory for a particular object;

5. **Visual constraint satisfaction**: the robot must manipulate the objects carefully and avoid violating the (safety) constraints;

6. **Visual reasoning**: tasks that require reasoning skills, such as appearance matching "move all objects with same textures as `<object>` into a container", and visual memory, "put `<object>` in container and then restore to their original position".

Note that these six categories are not mutually exclusive. For example, a task may introduce a previously unseen verb (*Novel Concept*) by showing a video demonstration, or combine goal reaching with visual reasoning. More details about the task suite are discussed in Appendix, Sec. B.

4 VIMA-BENCH: BENCHMARK FOR MULTIMODAL ROBOT LEARNING

Simulation Environment. Existing benchmarks are generally geared towards a particular task specification. To our knowledge, there is no benchmark that provides a rich suite of multimodal tasks and a comprehensive testbed for targeted probing of agent capabilities. To this end, we introduce a new benchmark suite for multimodal robot learning thta we call VIMA-BENCH. We built our benchmark by extending the Ravens robot simulator (Zeng et al., 2020). VIMA-BENCH supports extensible collections of objects and textures to compose multimodal prompts and procedurally generate a large number of tasks. Specifically, we provide 17 meta-tasks with multimodal prompt templates, which can be instantiated into 1000s of individual tasks. Each meta-task belongs to one or more of 6 task specification methods mentioned above. VIMA-BENCH can generate large quantities of imitation learning data via scripted oracle agents. More details are elaborated in Appendix, Sec. A.

Figure 3: **VIMA.** We encode the multimodal prompts with a pre-trained T5 model, and condition the robot controller on the prompt through cross-attention layers. The controller is a causal transformer decoder consisting of alternating self and cross attention layers that predicts motor commands conditioned on prompts and interaction history.

Observation and Actions. The observation space of our simulator includes RGB images rendered from both frontal view and top-down view. Groundtruth object segmentations and bounding boxes are also provided for training object-centric models (Sec. 5). We inherit the high-level action space from Zeng et al. (2020), which consists of primitive motor skills like "pick and place" and "wipe". These are parameterized by poses of the end effector. Our simulator also features scripted oracle programs that can generate expert demonstrations by using privileged simulator state information, such as the precise location of all objects, and the groundtruth interpretation of the multimodal instruction.

Training Dataset. We leverage the pre-programmed oracles to generate a large offline dataset of expert trajectories for imitation learning. Our dataset includes 50K trajectories per meta-task, and 650K successful trajectories in total. We hold out a subset of object models and textures for evaluation, and designate 4 out of 17 meta-tasks as a testbed for zero-shot generalization.

Evaluating Zero-Shot Generalization. Each task in VIMA-BENCH has a binary success criterion and does not provide partial reward signals. During test time, we execute the agent policies in the physics simulator for multiple episodes to compute a success rate in percentage. The average success rate over all evaluated meta-tasks will be the final reported metric.

We design a 4-level evaluation protocol (Fig. 2) to systematically probe the generalization capabilities of learned agents. Each level deviates more from the training distribution, and is thus strictly harder than the previous one — Level 1) **placement generalization**: all prompts are seen verbatim during training, but only the placement of objects on the tabletop is randomized at testing; Level 2) **combinatorial generalization**: all materials (adjectives) and 3D objects (nouns) are seen during training, but new combinations of them appear in testing; Level 3) **novel object generalization**: test prompts and the simulated workspace include novel adjectives and objects; Level 4) **novel task generalization**: new meta-tasks with novel prompt templates at test time.

5 VIMA: VISUOMOTOR ATTENTION MODEL

Our goal is to build a robot agent which can perform any task specified by multimodal prompts. To learn an effective multi-task robot policy, we propose VIMA, a minimalistic multi-task encoder-decoder architecture with object-centric design (Fig. 3). Concretely, we learn a robot policy $\pi(a_t|\mathcal{P}, \mathcal{H})$, where $\mathcal{H} := [o_1, a_1, o_2, a_2, \ldots, o_t]$ denotes the past interaction history, and $o_t \in \mathcal{O}, a_t \in \mathcal{A}$ are observations and actions at each interaction steps. We encode the prompt via a *frozen* pre-trained langauge model and decode the robot motor commands conditioned on the encoded prompt via cross-attention layers.

Tokenization. There are 3 formats of raw input in the prompt — text, image of a single object, and image of a full tabletop scene (*e.g.*, for *Rearrangement* or imitation from video frames). For **text inputs**, we use pre-trained T5 tokenizer and word embedding to obtain word tokens. For **images of full scenes**, we first extract individual objects using off-the-shelf Mask R-CNN (He et al., 2017). Each object is represented as a bounding box and a cropped image. We then compute object tokens by encoding them with a bounding box encoder and a ViT, respectively. For **images of single objects**, we obtain tokens in the same way except with a dummy bounding box. We then follow Tsimpoukelli et al. (2021) to produce prompt encoding by passing the resulted token sequence to a pre-trained T5 encoder model. Our positional embedding is learnable and absolute.

Robot Controller. A challenging aspect of designing multi-modal multi-task policy is to select a suitable conditioning mechanism. In our schema (Fig. 3), the robot controller (decoder) is conditioned on the prompt sequence $\mathcal{P}$ by a series of cross-attention layers between $\mathcal{P}$ and the trajectory history sequence $\mathcal{H}$. Each cross-attention layer generates an output sequence $\mathcal{H}' = \text{softmax}\left(\frac{Q_{\mathcal{H}}K_{\mathcal{P}}^{\mathsf{T}}}{\sqrt{d}}\right)V_{\mathcal{P}}$, where d is the embedding dimension. This design choice enjoys three advantages, including 1) strengthened connection to prompt, 2) intact and deep flow of the original prompt tokens, and 3) better computational efficiency. VIMA decoder consists of L alternating cross-attention and self-attention layers. Finally, for ease of learning and optimization, we follow common practice (Baker et al., 2022) to map predicted action tokens to discretized coordinates of the robot arm.

Training. We follow the standard behavioral cloning to train our models by minimizing the negative log-likelihood of predicted actions. Concretely, for a trajectory with T steps, we minimize $\min_\theta \sum_{t=1}^{T} - \log \pi_\theta(a_t|\mathcal{P}, \mathcal{H})$. The entire training is conducted on an offline dataset with no access to the physics simulator. To make VIMA robust to detection inaccuracies and failures, we apply *object augmentation* by randomly injecting *false-positive* detection outputs. After training, we select model checkpoints for evaluation based on the aggregated accuracy on a held-out validation set. The evaluation involves interacting with the physics simulator. We follow the best practices to train Transformer models using the AdamW optimizer (Loshchilov & Hutter, 2019), learning rate warm-up, cosine annealing (Loshchilov & Hutter, 2016), etc. See Appendix Sec. D for a comprehensive listing of our model and training hyperparameters.

6 EXPERIMENTS

In this section, we aim to answer three main questions: (1) How does VIMA compare with prior SOTA transformer-based agents on a diverse collection of multimodal-prompted tasks? (2) What are the **scaling properties** of our approach in model capacity and data size? (3) How do different visual tokenizers, prompt conditioning, and prompt encoding affect decision making?

6.1 BASELINES

Gato (Reed et al., 2022) introduces a decoder-only model that solves tasks from multiple domains where tasks are specified by prompting the model with the observation and action subsequence. For fair comparison, we provide the same conditioning as VIMA, *i.e.*, our multimodal embedded prompt. Input images are divided into patches and encoded by a ViT (Dosovitskiy et al., 2020) model to produce observation tokens.

Flamingo (Alayrac et al., 2022) is a vision-language model that learns to generate textual completion in response to multimodal prompts. It embeds a variable number of prompt images into a fixed number of tokens via the Perceiver Resampler module, and conditions the language decoder on the

Figure 4: **Scaling model and data**. *Top:* We compare performance of different methods with model sizes ranging from 2M to 200M parameters. Across all model sizes and generalization levels VIMA outperforms prior works. *Bottom:* For a fixed model size of 92M parameters we compare the effect of imitation learning dataset size of 0.1%, 1%, 10%, and full imitation data. VIMA is extremely sample efficient and can achieve performance comparable to other methods with $10\times$ less data.

encoded prompt by cross-attention. Flamingo does not work with embodied agents out of the box. We adapt it to support decision-masking by replacing the output layer with robot action heads.

Decision Transformer (DT) (Chen et al., 2021; Janner et al., 2021) is among the first works to reinterpret the RL problem as transformer sequence modeling. In visual RL domains like Atari games, DT is prompted on the desired reward value and outputs actions autoregressively given the RGB observation embedding. We replace DT's initial reward prompt with our multimodal task prompt embeddings, and remove all subsequent reward tokens.

6.2 EVALUATION RESULTS

We compare VIMA against other SOTA methods on the four levels of generalization provided in our benchmark for different model and training dataset sizes.

Model scaling. We train all methods for a spectrum of model capacities from 2M to 200M parameters, evenly spaced on the log scale. The encoder size is kept constant (pretrained T5-Base) for all methods and excluded from the parameter count. Across *all* levels of zero-shot generalization, we find that VIMA strongly outperforms prior work. Although models like Gato and Flamingo show improved performance with bigger model sizes, VIMA consistently achieves superior performance over *all* model sizes. We note that this can only be achieved with *both* cross-attention and object token sequence representation — altering any component will degrade the performance significantly, especially in the low model capacity regime (ablations in Sec. 6.3).

Data scaling. Next we investigate how different methods scale with varying dataset sizes. We compare model performance at 0.1%, 1%, 10% and full imitation learning dataset provided in VIMA-BENCH (Fig. 4). VIMA is extremely sample efficient and with just 1% of the data can achieve performance similar to baseline methods trained with $10\times$ more data for L1 and L2 levels of generalization. In fact, for L4 we find that with just 1% of training data, VIMA already outperforms prior work trained with *entire* dataset. Finally, across all levels with just 10% of the data, VIMA can outperforms prior work trained with the full dataset by a significant margin. We hypothesize that the data efficiency can be attributed to VIMA's object-centric representation, which is less prone to overfitting than learning directly from pixels in the low-data regime. This is consistent with findings

Figure 5: **Ablation on visual tokenizers**. We compare the performance of VIMA-200M model across different visual tokenizers. Our proposed object tokens outperform all methods that learn directly from raw pixels, and *Object Perceiver* that downsamples the object sequence to a fixed number of tokens.

from Sax et al. (2018), which demonstrates that embodied agents conditioned on mid-level visual representations tend to be significantly more sample-efficient than end-to-end control from raw pixels.

Progressive Generalization. Finally, we compare the relative degradation in performance as we test the models on progressively challenging zero-shot evaluation levels without further finetuning (Fig. 6). Our method exhibits a minimal performance regression, especially between $L1 \rightarrow L2$ and $L1 \rightarrow L3$. In contrast, other methods can degrade as much as 20%, particularly in the more difficult generalization testing scenarios. Although all methods degrade significantly when evaluated on $L4$ (*Novel Tasks*), the drop in performance for VIMA is only *half* as severe as all other baselines. This results suggest that VIMA has developed more generalizable policy and robust representations than the competing approaches.

6.3 ABLATION STUDIES

Through extensive experiments, we ablate different design choices in VIMA and study their impact on robot decision making. We focus on the following 3 aspects: visual tokenization, prompt encoding, and prompt conditioning variants.

Visual tokenization. As explained in Sec. 5, VIMA processes the prompt and observation images into a variable number of object tokens with an off-the-shelf Mask R-CNN implementation. How important is this particular choice of visual tokenizer? We study 5 different variants and empirically evaluate their 4 levels of generalization performance on VIMA-BENCH. (1) **Ours (Oracle)**: instead of using Mask R-CNN, we directly read out the groundtruth bounding box from the simulator. In other words, we use a perfect object detector to estimate the upper bound on the performance of this study; (2) **Object Perceiver**: we apply a Perceiver module (Jaegle et al., 2021b;a) to convert the variable number

Figure 6: VIMA incurs much less performance drop than baselines as we evaluate on progressively harder zero-shot generalization.

Figure 7: **Ablation: Prompt conditioning**. We compare our method (*xattn*: cross-attention prompt conditioning) with a vanilla transformer decoder (*gpt-decoder*) across different model sizes. Cross-attention is especially helpful in low-parameter regime and for harder generalization tasks.

of objects detected in each frame to a *fixed* number of tokens. Perceiver is more computationally efficient because it reduces the average sequence length; (3) **Image Perceiver**: the same architecture as the *Perceiver Resampler* in Flamingo, which converts an image to a small, fixed number of tokens; (4) **Image patches**: following Gato, we divide an RGB frame into square patches, and extract ViT embedding tokens. The number of patches is more than the output of Image Perceiver; (5) **Single image**: Decision Transformer's tokenizer, which encodes one image into a single token.

Fig. 5 shows the ablation results. We highlight a few findings. First, we note that our Mask R-CNN detection pipeline (Appendix, Sec. A.20) **incurs a minimal performance loss** compared to the oracle bounding boxes, thanks to the object augmentation (Sec. 5) that boosts robustness during training. Second, tokenizing from raw pixels (Image Perceiver, patches, or single embedding) consistently underperforms our object-centric format. We hypothesize that these tokenizers have to allocate extra internal capacity to parse the objects from low-level pixels, which likely impedes learning. Sax et al. (2018) echoes our finding that using mid-level vision can greatly improve agent generalization compared to an end-to-end pipeline. Third, even though *Ours* and *Object Perceiver* both use the same object bounding box inputs, the latter is significantly worse in decision making. We conclude that it is important to pass the **variable sequence of objects directly** to the robot controller rather than downsampling to a fixed number of tokens.

Prompt Conditioning. VIMA conditions the robot controller (decoder) on the encoded prompt by cross-attention. A simple alternative is to concatenate the prompt $\mathcal{P}$ and interaction history $\mathcal{H}$ into one big sequence, and then apply a decoder-only transformer like GPT (Radford et al., 2018) to predict actions. In this ablation, we keep the object tokenizer constant, and only switch the conditioning mechanism to causal sequence modeling. Fig. 7 shows the comparison of VIMA (`xattn`) and the `gpt-decoder` variant across 4 generalization levels. While GPT achieves comparable performance in larger models, cross-attention still dominates in the small-capacity range and generalizes better in the most challenging L4 (*Novel Task*) setting. Our hypothesis is that cross-attention helps the controller stay better focused on the prompt instruction at each interaction step. This bears resemblance to the empirical results in Sanh et al. (2021); Wang et al. (2022b), which show that well-tuned encoder-decoder architectures can outperform GPT-3 in zero-shot generalization.

Prompt Encoding. We vary the size of the pre-trained T5 encoder (Raffel et al., 2020) to study the effect of prompt encoding. We experiment with three T5 model capacities: `t5-small` (30M), `t5-base` (111M), to `t5-large` (368M). For all T5 variants, we fine-tune the last two layers and freeze all other layers. We find that no significant difference among the variants (Appendix, Sec. E.2), thus we set `t5-base` as default for all our models.

7 CONCLUSION

Similar to GPT-3, a generalist robot agent should have an intuitive and expressive interface for human users to convey their intent. In this work, we introduce a novel *multimodal* prompting formulation that converts diverse robot manipulation tasks into a uniform sequence modeling problem. We propose VIMA, a conceptually simple transformer-based agent capable of solving tasks like visual goal, one-shot video imitation, and novel concept grounding with a single model. VIMA exhibits superior model and data scaling properties, and provides a strong starting point for future work.

8 REPRODUCIBILITY STATEMENT

We provide comprehensive details to reproduce our work in the Appendix. Concretely, the specifications of each meta-task in the benchmarking suite are explained in Sec. B. Model architectures are elaborated in Sec. C. Hyperparameter configurations are listed in Sec. D. Furthermore, we host anonymized code at https://iclr3081.github.io/ for review.

REFERENCES

Bernardo Aceituno, Alberto Rodriguez, Shubham Tulsiani, Abhinav Gupta, and Mustafa Mukadam. A differentiable recipe for learning visual non-prehensile planar manipulation. In *5th Annual Conference on Robot Learning*, 2021. URL https://openreview.net/forum?id=f7KaqYLO3iE.

Pulkit Agrawal. The task specification problem. In Aleksandra Faust, David Hsu, and Gerhard Neumann (eds.), *Proceedings of the 5th Conference on Robot Learning*, volume 164 of *Proceedings of Machine Learning Research*, pp. 1745–1751. PMLR, 08-11 Nov 2022. URL https://proceedings.mlr.press/v164/agrawal22a.html.

Ossama Ahmed, Frederik Träuble, Anirudh Goyal, Alexander Neitz, Manuel Wuthrich, Yoshua Bengio, Bernhard Schölkopf, and Stefan Bauer. Causalworld: A robotic manipulation benchmark for causal structure and transfer learning. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. URL https://openreview.net/forum?id=SK7A5pdrgov.

Michael Ahn, Anthony Brohan, Noah Brown, Yevgen Chebotar, Omar Cortes, Byron David, Chelsea Finn, Keerthana Gopalakrishnan, Karol Hausman, Alex Herzog, Daniel Ho, Jasmine Hsu, Julian Ibarz, Brian Ichter, Alex Irpan, Eric Jang, Rosario Jauregui Ruano, Kyle Jeffrey, Sally Jesmonth, Nikhil J Joshi, Ryan Julian, Dmitry Kalashnikov, Yuheng Kuang, Kuang-Huei Lee, Sergey Levine, Yao Lu, Linda Luu, Carolina Parada, Peter Pastor, Jornell Quiambao, Kanishka Rao, Jarek Rettinghouse, Diego Reyes, Pierre Sermanet, Nicolas Sievers, Clayton Tan, Alexander Toshev, Vincent Vanhoucke, Fei Xia, Ted Xiao, Peng Xu, Sichun Xu, and Mengyuan Yan. Do as i can, not as i say: Grounding language in robotic affordances. *arXiv preprint arXiv: Arxiv-2204.01691*, 2022.

Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katie Millican, Malcolm Reynolds, Roman Ring, Eliza Rutherford, Serkan Cabi, Tengda Han, Zhitao Gong, Sina Samangooei, Marianne Monteiro, Jacob Menick, Sebastian Borgeaud, Andrew Brock, Aida Nematzadeh, Sahand Sharifzadeh, Mikolaj Binkowski, Ricardo Barreira, Oriol Vinyals, Andrew Zisserman, and Karen Simonyan. Flamingo: a visual language model for few-shot learning. *arXiv preprint arXiv: Arxiv-2204.14198*, 2022.

Bowen Baker, Ilge Akkaya, Peter Zhokhov, Joost Huizinga, Jie Tang, Adrien Ecoffet, Brandon Houghton, Raul Sampedro, and Jeff Clune. Video pretraining (vpt): Learning to act by watching unlabeled online videos. *arXiv preprint arXiv: Arxiv-2206.11795*, 2022.

Dhruv Batra, Angel X. Chang, Sonia Chernova, Andrew J. Davison, Jia Deng, Vladlen Koltun, Sergey Levine, Jitendra Malik, Igor Mordatch, Roozbeh Mottaghi, Manolis Savva, and Hao Su. Rearrangement: A challenge for embodied ai. *arXiv preprint arXiv: Arxiv-2011.01975*, 2020.

Homanga Bharadhwaj, Aviral Kumar, Nicholas Rhinehart, Sergey Levine, Florian Shkurti, and Animesh Garg. Conservative safety critics for exploration. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. URL https://openreview.net/forum?id=iaO86DUuKi.

Rishi Bommasani, Drew A. Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S. Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, Erik Brynjolfsson, Shyamal Buch, Dallas Card, Rodrigo Castellon, Niladri Chatterji, Annie Chen, Kathleen Creel, Jared Quincy Davis, Dora Demszky, Chris Donahue, Moussa Doumbouya, Esin Durmus, Stefano Ermon, John Etchemendy, Kawin Ethayarajh, Li Fei-Fei, Chelsea Finn, Trevor Gale, Lauren Gillespie, Karan Goel, Noah Goodman, Shelby Grossman, Neel Guha, Tatsunori Hashimoto, Peter

Henderson, John Hewitt, Daniel E. Ho, Jenny Hong, Kyle Hsu, Jing Huang, Thomas Icard, Saahil Jain, Dan Jurafsky, Pratyusha Kalluri, Siddharth Karamcheti, Geoff Keeling, Fereshte Khani, Omar Khattab, Pang Wei Koh, Mark Krass, Ranjay Krishna, Rohith Kuditipudi, Ananya Kumar, Faisal Ladhak, Mina Lee, Tony Lee, Jure Leskovec, Isabelle Levent, Xiang Lisa Li, Xuechen Li, Tengyu Ma, Ali Malik, Christopher D. Manning, Suvir Mirchandani, Eric Mitchell, Zanele Munyikwa, Suraj Nair, Avanika Narayan, Deepak Narayanan, Ben Newman, Allen Nie, Juan Carlos Niebles, Hamed Nilforoshan, Julian Nyarko, Giray Ogut, Laurel Orr, Isabel Papadimitriou, Joon Sung Park, Chris Piech, Eva Portelance, Christopher Potts, Aditi Raghunathan, Rob Reich, Hongyu Ren, Frieda Rong, Yusuf Roohani, Camilo Ruiz, Jack Ryan, Christopher Ré, Dorsa Sadigh, Shiori Sagawa, Keshav Santhanam, Andy Shih, Krishnan Srinivasan, Alex Tamkin, Rohan Taori, Armin W. Thomas, Florian Tramèr, Rose E. Wang, William Wang, Bohan Wu, Jiajun Wu, Yuhuai Wu, Sang Michael Xie, Michihiro Yasunaga, Jiaxuan You, Matei Zaharia, Michael Zhang, Tianyi Zhang, Xikun Zhang, Yuhui Zhang, Lucia Zheng, Kaitlyn Zhou, and Percy Liang. On the opportunities and risks of foundation models. *arXiv preprint arXiv: Arxiv-2108.07258*, 2021.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, volume 33, pp. 1877–1901, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/1457c0d6bfcb4967418bfb8ac142f64a-Abstract.html.

Lukas Brunke, Melissa Greeff, Adam W. Hall, Zhaocong Yuan, Siqi Zhou, Jacopo Panerati, and Angela P. Schoellig. Safe learning in robotics: From learning-based control to safe reinforcement learning. *arXiv preprint arXiv: Arxiv-2108.06266*, 2021.

Arthur Bucker, Luis Figueredo, Sami Haddadin, Ashish Kapoor, Shuang Ma, Sai Vemprala, and Rogerio Bonatti. Latte: Language trajectory transformer. *arXiv preprint arXiv: Arxiv-2208.02918*, 2022.

Lili Chen, Kevin Lu, Aravind Rajeswaran, Kimin Lee, Aditya Grover, Michael Laskin, Pieter Abbeel, Aravind Srinivas, and Igor Mordatch. Decision transformer: Reinforcement learning via sequence modeling. In Marc'Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 15084–15097, 2021. URL https://proceedings.neurips.cc/paper/2021/hash/7f489f642a0ddb10272b5c31057f0663-Abstract.html.

Ting Chen, Saurabh Saxena, Lala Li, David J. Fleet, and Geoffrey E. Hinton. Pix2seq: A language modeling framework for object detection. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*. OpenReview.net, 2022a. URL https://openreview.net/forum?id=e42KbIw6Wb.

Ting Chen, Saurabh Saxena, Lala Li, Tsung-Yi Lin, David J. Fleet, and Geoffrey Hinton. A unified sequence interface for vision tasks. *arXiv preprint arXiv: Arxiv-2206.07669*, 2022b.

Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, Parker Schuh, Kensen Shi, Sasha Tsvyashchenko, Joshua Maynez, Abhishek Rao, Parker Barnes, Yi Tay, Noam Shazeer, Vinodkumar Prabhakaran, Emily Reif, Nan Du, Ben Hutchinson, Reiner Pope, James Bradbury, Jacob Austin, Michael Isard, Guy Gur-Ari, Pengcheng Yin, Toju Duke, Anselm Levskaya, Sanjay Ghemawat, Sunipa Dev, Henryk Michalewski, Xavier Garcia, Vedant Misra, Kevin Robinson, Liam Fedus, Denny Zhou, Daphne Ippolito, David Luan, Hyeontaek Lim, Barret Zoph, Alexander Spiridonov, Ryan Sepassi, David Dohan, Shivani Agrawal, Mark Omernick, Andrew M. Dai, Thanumalayan Sankaranarayana Pillai, Marie Pellat, Aitor Lewkowycz, Erica Moreira, Rewon Child, Oleksandr Polozov, Katherine Lee, Zongwei Zhou, Xuezhi Wang, Brennan Saeta, Mark

Diaz, Orhan Firat, Michele Catasta, Jason Wei, Kathy Meier-Hellstern, Douglas Eck, Jeff Dean, Slav Petrov, and Noah Fiedel. Palm: Scaling language modeling with pathways. *arXiv preprint arXiv: Arxiv-2204.02311*, 2022.

Jack Collins, Shelvin Chand, Anthony Vanderkop, and David Howard. A review of physics simulators for robotic applications. *IEEE Access*, 9:51416–51431, 2021.

Erwin Coumans and Yunfei Bai. Pybullet, a python module for physics simulation for games, robotics and machine learning. http://pybullet.org, 2016–2021.

Sudeep Dasari and Abhinav Gupta. Transformers for one-shot visual imitation. In Jens Kober, Fabio Ramos, and Claire J. Tomlin (eds.), *4th Conference on Robot Learning, CoRL 2020, 16-18 November 2020, Virtual Event / Cambridge, MA, USA*, volume 155 of *Proceedings of Machine Learning Research*, pp. 2071–2084. PMLR, 2020. URL https://proceedings.mlr.press/v155/dasari21a.html.

Matt Deitke, Eli VanderBilt, Alvaro Herrasti, Luca Weihs, Jordi Salvador, Kiana Ehsani, Winson Han, Eric Kolve, Ali Farhadi, Aniruddha Kembhavi, and Roozbeh Mottaghi. Procthor: Large-scale embodied ai using procedural generation. *arXiv preprint arXiv: Arxiv-2206.06994*, 2022.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv: Arxiv-2010.11929*, 2020.

Laura Downs, Anthony Francis, Nate Koenig, Brandon Kinman, Ryan Hickman, Krista Reymann, Thomas B McHugh, and Vincent Vanhoucke. Google scanned objects: A high-quality dataset of 3d scanned household items. *arXiv preprint arXiv:2204.11918*, 2022.

Jiafei Duan, Samson Yu, Hui Li Tan, Hongyuan Zhu, and Cheston Tan. A survey of embodied AI: from simulators to research tasks. *IEEE Trans. Emerg. Top. Comput. Intell.*, 6(2):230–244, 2022. doi: 10.1109/TETCI.2022.3141105. URL https://doi.org/10.1109/TETCI.2022.3141105.

Yan Duan, Marcin Andrychowicz, Bradly C. Stadie, Jonathan Ho, Jonas Schneider, Ilya Sutskever, Pieter Abbeel, and Wojciech Zaremba. One-shot imitation learning. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pp. 1087–1098, 2017. URL https://proceedings.neurips.cc/paper/2017/hash/ba3866600c3540f67c1e9575e213be0a-Abstract.html.

Kiana Ehsani, Winson Han, Alvaro Herrasti, Eli VanderBilt, Luca Weihs, Eric Kolve, Aniruddha Kembhavi, and Roozbeh Mottaghi. Manipulathor: A framework for visual object manipulation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 4497–4506, June 2021.

Linxi Fan, Guanzhi Wang, De-An Huang, Zhiding Yu, Li Fei-Fei, Yuke Zhu, and Animashree Anandkumar. SECANT: self-expert cloning for zero-shot generalization of visual policies. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pp. 3088–3099. PMLR, 2021. URL http://proceedings.mlr.press/v139/fan21c.html.

Linxi Fan, Guanzhi Wang, Yunfan Jiang, Ajay Mandlekar, Yuncong Yang, Haoyi Zhu, Andrew Tang, De-An Huang, Yuke Zhu, and Anima Anandkumar. Minedojo: Building open-ended embodied agents with internet-scale knowledge. *arXiv preprint arXiv: Arxiv-2206.08853*, 2022.

Chelsea Finn, Tianhe Yu, Tianhao Zhang, Pieter Abbeel, and Sergey Levine. One-shot visual imitation learning via meta-learning. *arXiv preprint arXiv: Arxiv-1709.04905*, 2017.

Chuang Gan, Siyuan Zhou, Jeremy Schwartz, Seth Alter, Abhishek Bhandwaldar, Dan Gutfreund, Daniel L. K. Yamins, James J DiCarlo, Josh McDermott, Antonio Torralba, and Joshua B. Tenenbaum. The threedworld transport challenge: A visually guided task-and-motion planning benchmark for physically realistic embodied ai. *arXiv preprint arXiv: Arxiv-2103.14025*, 2021.

Golnaz Ghiasi, Barret Zoph, Ekin D. Cubuk, Quoc V. Le, and Tsung-Yi Lin. Multi-task self-training for learning general representations. In *2021 IEEE/CVF International Conference on Computer Vision, ICCV 2021, Montreal, QC, Canada, October 10-17, 2021*, pp. 8836–8845. IEEE, 2021. doi: 10.1109/ICCV48922.2021.00873. URL https://doi.org/10.1109/ICCV48922.2021.00873.

Kristen Grauman, Andrew Westbury, Eugene Byrne, Zachary Chavis, Antonino Furnari, Rohit Girdhar, Jackson Hamburger, Hao Jiang, Miao Liu, Xingyu Liu, Miguel Martin, Tushar Nagarajan, Ilija Radosavovic, Santhosh Kumar Ramakrishnan, Fiona Ryan, Jayant Sharma, Michael Wray, Mengmeng Xu, Eric Zhongcong Xu, Chen Zhao, Siddhant Bansal, Dhruv Batra, Vincent Cartillier, Sean Crane, Tien Do, Morrie Doulaty, Akshay Erapalli, Christoph Feichtenhofer, Adriano Fragomeni, Qichen Fu, Abrham Gebreselasie, Cristina Gonzalez, James Hillis, Xuhua Huang, Yifei Huang, Wenqi Jia, Weslie Khoo, Jachym Kolar, Satwik Kottur, Anurag Kumar, Federico Landini, Chao Li, Yanghao Li, Zhenqiang Li, Karttikeya Mangalam, Raghava Modhugu, Jonathan Munro, Tullie Murrell, Takumi Nishiyasu, Will Price, Paola Ruiz Puentes, Merey Ramazanova, Leda Sari, Kiran Somasundaram, Audrey Southerland, Yusuke Sugano, Ruijie Tao, Minh Vo, Yuchen Wang, Xindi Wu, Takuma Yagi, Ziwei Zhao, Yunyi Zhu, Pablo Arbelaez, David Crandall, Dima Damen, Giovanni Maria Farinella, Christian Fuegen, Bernard Ghanem, Vamsi Krishna Ithapu, C. V. Jawahar, Hanbyul Joo, Kris Kitani, Haizhou Li, Richard Newcombe, Aude Oliva, Hyun Soo Park, James M. Rehg, Yoichi Sato, Jianbo Shi, Mike Zheng Shou, Antonio Torralba, Lorenzo Torresani, Mingfei Yan, and Jitendra Malik. Ego4d: Around the world in 3,000 hours of egocentric video. *arXiv preprint arXiv: Arxiv-2110.07058*, 2021.

Abhishek Gupta, Vikash Kumar, Corey Lynch, Sergey Levine, and Karol Hausman. Relay policy learning: Solving long-horizon tasks via imitation and reinforcement learning. In Leslie Pack Kaelbling, Danica Kragic, and Komei Sugiura (eds.), *3rd Annual Conference on Robot Learning, CoRL 2019, Osaka, Japan, October 30 - November 1, 2019, Proceedings*, volume 100 of *Proceedings of Machine Learning Research*, pp. 1025–1037. PMLR, 2019. URL http://proceedings.mlr.press/v100/gupta20a.html.

Agrim Gupta, Stephen Tian, Yunzhi Zhang, Jiajun Wu, Roberto Martín-Martín, and Li Fei-Fei. Maskvit: Masked visual pre-training for video prediction. *arXiv preprint arXiv: Arxiv-2206.11894*, 2022.

Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask r-cnn. *arXiv preprint arXiv: Arxiv-1703.06870*, 2017.

Tracy H Heibeck and Ellen M Markman. Word learning in children: An examination of fast mapping. *Child development*, pp. 1021–1034, 1987.

Karl Moritz Hermann, Felix Hill, Simon Green, Fumin Wang, Ryan Faulkner, Hubert Soyer, David Szepesvari, Wojciech Marian Czarnecki, Max Jaderberg, Denis Teplyashin, Marcus Wainwright, Chris Apps, Demis Hassabis, and Phil Blunsom. Grounded language learning in a simulated 3d world. *arXiv preprint arXiv: Arxiv-1706.06551*, 2017.

De-An Huang, Danfei Xu, Yuke Zhu, Animesh Garg, Silvio Savarese, Li Fei-Fei, and Juan Carlos Niebles. Continuous relaxation of symbolic planner for one-shot imitation learning. In *2019 IEEE/RSJ International Conference on Intelligent Robots and Systems, IROS 2019, Macau, SAR, China, November 3-8, 2019*, pp. 2635–2642. IEEE, 2019. doi: 10.1109/IROS40897.2019.8967761. URL https://doi.org/10.1109/IROS40897.2019.8967761.

Wenlong Huang, Pieter Abbeel, Deepak Pathak, and Igor Mordatch. Language models as zero-shot planners: Extracting actionable knowledge for embodied agents. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvári, Gang Niu, and Sivan Sabato (eds.), *International Conference on Machine Learning, ICML 2022, 17-23 July 2022, Baltimore, Maryland, USA*, volume 162 of *Proceedings of Machine Learning Research*, pp. 9118–9147. PMLR, 2022a. URL https://proceedings.mlr.press/v162/huang22a.html.

Wenlong Huang, Fei Xia, Ted Xiao, Harris Chan, Jacky Liang, Pete Florence, Andy Zeng, Jonathan Tompson, Igor Mordatch, Yevgen Chebotar, Pierre Sermanet, Noah Brown, Tomas Jackson, Linda Luu, Sergey Levine, Karol Hausman, and Brian Ichter. Inner monologue: Embodied reasoning through planning with language models. *arXiv preprint arXiv: Arxiv-2207.05608*, 2022b.

Andrew Jaegle, Sebastian Borgeaud, Jean-Baptiste Alayrac, Carl Doersch, Catalin Ionescu, David Ding, Skanda Koppula, Daniel Zoran, Andrew Brock, Evan Shelhamer, Olivier Hénaff, Matthew M. Botvinick, Andrew Zisserman, Oriol Vinyals, and João Carreira. Perceiver io: A general architecture for structured inputs & outputs. *arXiv preprint arXiv: Arxiv-2107.14795*, 2021a.

Andrew Jaegle, Felix Gimeno, Andrew Brock, Andrew Zisserman, Oriol Vinyals, and Joao Carreira. Perceiver: General perception with iterative attention. *arXiv preprint arXiv: Arxiv-2103.03206*, 2021b.

Stephen James, Zicong Ma, David Rovick Arrojo, and Andrew J. Davison. Rlbench: The robot learning benchmark & learning environment. *arXiv preprint arXiv: Arxiv-1909.12271*, 2019.

Michael Janner, Qiyang Li, and Sergey Levine. Offline reinforcement learning as one big sequence modeling problem. In Marc'Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 1273–1286, 2021. URL https://proceedings.neurips.cc/paper/2021/hash/099fe6b0b444c23836c4a5d07346082b-Abstract.html.

Salman Khan, Muzammal Naseer, Munawar Hayat, Syed Waqas Zamir, Fahad Shahbaz Khan, and Mubarak Shah. Transformers in vision: A survey. *arXiv preprint arXiv: Arxiv-2101.01169*, 2021.

Apoorv Khandelwal, Luca Weihs, Roozbeh Mottaghi, and Aniruddha Kembhavi. Simple but effective: Clip embeddings for embodied ai. *arXiv preprint arXiv: Arxiv-2111.09888*, 2021.

Iasonas Kokkinos. Ubernet: Training a 'universal' convolutional neural network for low-, mid-, and high-level vision using diverse datasets and limited memory. *arXiv preprint arXiv: Arxiv-1609.02132*, 2016.

Alexander Kolesnikov, Lucas Beyer, Xiaohua Zhai, Joan Puigcerver, Jessica Yung, Sylvain Gelly, and Neil Houlsby. Big transfer (bit): General visual representation learning. In Andrea Vedaldi, Horst Bischof, Thomas Brox, and Jan-Michael Frahm (eds.), *Computer Vision - ECCV 2020 - 16th European Conference, Glasgow, UK, August 23-28, 2020, Proceedings, Part V*, volume 12350 of *Lecture Notes in Computer Science*, pp. 491–507. Springer, 2020. doi: 10.1007/978-3-030-58558-7_29. URL https://doi.org/10.1007/978-3-030-58558-7_29.

Alexander Kolesnikov, André Susano Pinto, Lucas Beyer, Xiaohua Zhai, Jeremiah Harmsen, and Neil Houlsby. Uvim: A unified modeling approach for vision with learned guiding codes. *arXiv preprint arXiv: Arxiv-2205.10337*, 2022.

Chengshu Li, Fei Xia, Roberto Martín-Martín, Michael Lingelbach, Sanjana Srivastava, Bokui Shen, Kent Elliott Vainio, Cem Gokmen, Gokul Dharan, Tanish Jain, Andrey Kurenkov, C. Karen Liu, Hyowon Gweon, Jiajun Wu, Li Fei-Fei, and Silvio Savarese. igibson 2.0: Object-centric simulation for robot learning of everyday household tasks. In Aleksandra Faust, David Hsu, and Gerhard Neumann (eds.), *Conference on Robot Learning, 8-11 November 2021, London, UK*, volume 164 of *Proceedings of Machine Learning Research*, pp. 455–465. PMLR, 2021. URL https://proceedings.mlr.press/v164/li22b.html.

Shuang Li, Xavier Puig, Chris Paxton, Yilun Du, Clinton Wang, Linxi Fan, Tao Chen, De-An Huang, Ekin Akyürek, Anima Anandkumar, Jacob Andreas, Igor Mordatch, Antonio Torralba, and Yuke Zhu. Pre-trained language models for interactive decision-making. *arXiv preprint arXiv: Arxiv-2202.01771*, 2022.

Michael H. Lim, Andy Zeng, Brian Ichter, Maryam Bandari, Erwin Coumans, Claire Tomlin, Stefan Schaal, and Aleksandra Faust. Multi-task learning with sequence-conditioned transporter networks. *arXiv preprint arXiv: Arxiv-2109.07578*, 2021.

Tianyang Lin, Yuxin Wang, Xiangyang Liu, and Xipeng Qiu. A survey of transformers. *arXiv preprint arXiv: Arxiv-2106.04554*, 2021.

Ziyuan Liu, Wei Liu, Yuzhe Qin, Fanbo Xiang, Minghao Gou, Songyan Xin, Maximo A Roa, Berk Calli, Hao Su, Yu Sun, et al. Ocrtoc: A cloud-based competition and benchmark for robotic grasping and manipulation. *IEEE Robotics and Automation Letters*, 7(1):486–493, 2021.

Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts. *arXiv preprint arXiv: Arxiv-1608.03983*, 2016.

Ilya Loshchilov and Frank Hutter. SGDR: stochastic gradient descent with warm restarts. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017. URL https://openreview.net/forum?id=Skq89Scxx.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net, 2019. URL https://openreview.net/forum?id=Bkg6RiCqY7.

Jiasen Lu, Vedanuj Goswami, Marcus Rohrbach, Devi Parikh, and Stefan Lee. 12-in-1: Multi-task vision and language representation learning. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2020, Seattle, WA, USA, June 13-19, 2020*, pp. 10434–10443. Computer Vision Foundation / IEEE, 2020. doi: 10.1109/CVPR42600.2020.01045. URL https://openaccess.thecvf.com/content_CVPR_2020/html/Lu_12-in-1_Multi-Task_Vision_and_Language_Representation_Learning_CVPR_2020_paper.html.

Jiasen Lu, Christopher Clark, Rowan Zellers, Roozbeh Mottaghi, and Aniruddha Kembhavi. Unified-io: A unified model for vision, language, and multi-modal tasks. *arXiv preprint arXiv: Arxiv-2206.08916*, 2022.

Corey Lynch and Pierre Sermanet. Language conditioned imitation learning over unstructured data. In Dylan A. Shell, Marc Toussaint, and M. Ani Hsieh (eds.), *Robotics: Science and Systems XVII, Virtual Event, July 12-16, 2021*, 2021. doi: 10.15607/RSS.2021.XVII.047. URL https://doi.org/10.15607/RSS.2021.XVII.047.

Bryan McCann, Nitish Shirish Keskar, Caiming Xiong, and Richard Socher. The natural language decathlon: Multitask learning as question answering. *arXiv preprint arXiv: Arxiv-1806.08730*, 2018.

Nathan Morrical, Jonathan Tremblay, Stan Birchfield, and Ingo Wald. NVISII: Nvidia scene imaging interface, 2020. https://github.com/owl-project/NVISII/.

Suraj Nair, Aravind Rajeswaran, Vikash Kumar, Chelsea Finn, and Abhinav Gupta. R3m: A universal visual representation for robot manipulation. *arXiv preprint arXiv: Arxiv-2203.12601*, 2022.

Tom Le Paine, Sergio Gómez Colmenarejo, Ziyu Wang, Scott Reed, Yusuf Aytar, Tobias Pfaff, Matt W. Hoffman, Gabriel Barth-Maron, Serkan Cabi, David Budden, and Nando de Freitas. One-shot high-fidelity imitation: Training large-scale deep nets with rl. *arXiv preprint arXiv: Arxiv-1810.05017*, 2018.

Simone Parisi, Aravind Rajeswaran, Senthil Purushwalkam, and Abhinav Gupta. The unsurprising effectiveness of pre-trained vision models for control. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvári, Gang Niu, and Sivan Sabato (eds.), *International Conference on Machine Learning, ICML 2022, 17-23 July 2022, Baltimore, Maryland, USA*, volume 162 of *Proceedings of Machine Learning Research*, pp. 17359–17371. PMLR, 2022. URL https://proceedings.mlr.press/v162/parisi22a.html.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and

R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8024–8035. Curran Associates, Inc., 2019.

Alec Radford, Karthik Narasimhan, Tim Salimans, and Ilya Sutskever. Improving language understanding by generative pre-training. *OpenAI*, 2018.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pp. 8748–8763. PMLR, 2021.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *J. Mach. Learn. Res.*, 21:140:1–140:67, 2020. URL http://jmlr.org/papers/v21/20-074.html.

Aditya Ramesh, Prafulla Dhariwal, Alex Nichol, Casey Chu, and Mark Chen. Hierarchical text-conditional image generation with clip latents. *arXiv preprint arXiv: Arxiv-2204.06125*, 2022.

Harish Ravichandar, Athanasios S Polydoros, Sonia Chernova, and Aude Billard. Recent advances in robot learning from demonstration. *Annual review of control, robotics, and autonomous systems*, 3: 297–330, 2020.

Scott Reed, Konrad Zolna, Emilio Parisotto, Sergio Gomez Colmenarejo, Alexander Novikov, Gabriel Barth-Maron, Mai Gimenez, Yury Sulsky, Jackie Kay, Jost Tobias Springenberg, Tom Eccles, Jake Bruce, Ali Razavi, Ashley Edwards, Nicolas Heess, Yutian Chen, Raia Hadsell, Oriol Vinyals, Mahyar Bordbar, and Nando de Freitas. A generalist agent. *arXiv preprint arXiv: Arxiv-2205.06175*, 2022.

Machel Reid, Yutaro Yamada, and Shixiang Shane Gu. Can wikipedia help offline reinforcement learning? *arXiv preprint arXiv: Arxiv-2201.12122*, 2022.

Victor Sanh, Albert Webson, Colin Raffel, Stephen H. Bach, Lintang A. Sutawika, Zaid Alyafeai, Antoine Chaffin, Arnaud Stiegler, Teven Le Scao, Arun Raja, Manan Dey, M Saiful Bari, Canwen Xu, Urmish Thakker, Shanya Sharma, Eliza Szczechla, Taewoon Kim, Gunjan Chhablani, Nihal V. Nayak, Debajyoti Datta, Jonathan Chang, Mike Tian-Jian Jiang, Han Wang, Matteo Manica, Sheng Shen, Zheng Xin Yong, Harshit Pandey, Rachel Bawden, Thomas Wang, Trishala Neeraj, Jos Rozen, Abheesht Sharma, Andrea Santilli, Thibault Févry, Jason Alan Fries, Ryan Teehan, Stella Rose Biderman, Leo Gao, T. Bers, Thomas Wolf, and Alexander M. Rush. Multitask prompted training enables zero-shot task generalization. *Iclr*, 2021.

Manolis Savva, Abhishek Kadian, Oleksandr Maksymets, Yili Zhao, Erik Wijmans, Bhavana Jain, Julian Straub, Jia Liu, Vladlen Koltun, Jitendra Malik, Devi Parikh, and Dhruv Batra. Habitat: A platform for embodied ai research. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, October 2019.

Alexander Sax, Bradley Emi, Amir R. Zamir, Leonidas Guibas, Silvio Savarese, and Jitendra Malik. Mid-level visual representations improve generalization and sample efficiency for learning visuomotor policies. *arXiv preprint arXiv: Arxiv-1812.11971*, 2018.

Dhruv Shah, Blazej Osinski, Brian Ichter, and Sergey Levine. Lm-nav: Robotic navigation with large pre-trained models of language, vision, and action. *arXiv preprint arXiv: Arxiv-2207.04429*, 2022.

Noam Shazeer. Glu variants improve transformer. *arXiv preprint arXiv: Arxiv-2002.05202*, 2020.

Bokui Shen, Fei Xia, Chengshu Li, Roberto Martín-Martín, Linxi Fan, Guanzhi Wang, Claudia Pérez-D'Arpino, Shyamal Buch, Sanjana Srivastava, Lyne P. Tchapmi, Micael E. Tchapmi, Kent Vainio, Josiah Wong, Li Fei-Fei, and Silvio Savarese. igibson 1.0: a simulation environment for interactive tasks in large realistic scenes. *arXiv preprint arXiv: Arxiv-2012.02924*, 2020.

Mohammad Shoeybi, Mostofa Patwary, Raul Puri, Patrick LeGresley, Jared Casper, and Bryan Catanzaro. Megatron-lm: Training multi-billion parameter language models using model parallelism. *arXiv preprint arXiv:1909.08053*, 2019.

Mohit Shridhar, Jesse Thomason, Daniel Gordon, Yonatan Bisk, Winson Han, Roozbeh Mottaghi, Luke Zettlemoyer, and Dieter Fox. ALFRED: A benchmark for interpreting grounded instructions for everyday tasks. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2020, Seattle, WA, USA, June 13-19, 2020*, pp. 10737–10746. Computer Vision Foundation / IEEE, 2020. doi: 10.1109/CVPR42600.2020.01075. URL https://openaccess.thecvf.com/content_CVPR_2020/html/Shridhar_ALFRED_A_Benchmark_for_Interpreting_Grounded_Instructions_for_Everyday_Tasks_CVPR_2020_paper.html.

Mohit Shridhar, Lucas Manuelli, and Dieter Fox. Cliport: What and where pathways for robotic manipulation. *arXiv preprint arXiv: Arxiv-2109.12098*, 2021.

Mohit Shridhar, Lucas Manuelli, and Dieter Fox. Perceiver-actor: A multi-task transformer for robotic manipulation. *arXiv preprint arXiv: Arxiv-2209.05451*, 2022.

Krishnan Srinivasan, Benjamin Eysenbach, Sehoon Ha, Jie Tan, and Chelsea Finn. Learning to be safe: Deep rl with a safety critic. *arXiv preprint arXiv: Arxiv-2010.14603*, 2020.

Sanjana Srivastava, Chengshu Li, Michael Lingelbach, Roberto Martín-Martín, Fei Xia, Kent Elliott Vainio, Zheng Lian, Cem Gokmen, Shyamal Buch, C. Karen Liu, Silvio Savarese, Hyowon Gweon, Jiajun Wu, and Li Fei-Fei. BEHAVIOR: benchmark for everyday household activities in virtual, interactive, and ecological environments. In Aleksandra Faust, David Hsu, and Gerhard Neumann (eds.), *Conference on Robot Learning, 8-11 November 2021, London, UK*, volume 164 of *Proceedings of Machine Learning Research*, pp. 477–490. PMLR, 2021. URL https://proceedings.mlr.press/v164/srivastava22a.html.

Elias Stengel-Eskin, Andrew Hundt, Zhuohong He, Aditya Murali, Nakul Gopalan, Matthew Gombolay, and Gregory Hager. Guiding multi-step rearrangement tasks with natural language instructions. In Aleksandra Faust, David Hsu, and Gerhard Neumann (eds.), *Proceedings of the 5th Conference on Robot Learning*, volume 164 of *Proceedings of Machine Learning Research*, pp. 1486–1501. PMLR, 08–11 Nov 2022. URL https://proceedings.mlr.press/v164/stengel-eskin22a.html.

Simon Stepputtis, Joseph Campbell, Mariano Phielipp, Stefan Lee, Chitta Baral, and Heni Ben Amor. Language-Conditioned Imitation Learning for Robot Manipulation Tasks, October 2020. URL http://arxiv.org/abs/2010.12083. arXiv:2010.12083 [cs].

Andrew Szot, Alexander Clegg, Eric Undersander, Erik Wijmans, Yili Zhao, John Turner, Noah Maestre, Mustafa Mukadam, Devendra Singh Chaplot, Oleksandr Maksymets, Aaron Gokaslan, Vladimir Vondrus, Sameer Dharur, Franziska Meier, Wojciech Galuba, Angel X. Chang, Zsolt Kira, Vladlen Koltun, Jitendra Malik, Manolis Savva, and Dhruv Batra. Habitat 2.0: Training home assistants to rearrange their habitat. In Marc'Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 251–266, 2021. URL https://proceedings.neurips.cc/paper/2021/hash/021bbc7ee20b71134d53e20206bd6feb-Abstract.html.

Yi Tay, Mostafa Dehghani, Dara Bahri, and Donald Metzler. Efficient transformers: A survey. *arXiv preprint arXiv: Arxiv-2009.06732*, 2020.

Brijen Thananjeyan, Ashwin Balakrishna, Suraj Nair, Michael Luo, Krishnan Srinivasan, Minho Hwang, Joseph E. Gonzalez, Julian Ibarz, Chelsea Finn, and Ken Goldberg. Recovery RL: safe reinforcement learning with learned recovery zones. *IEEE Robotics Autom. Lett.*, 6(3):4915–4922, 2021. doi: 10.1109/LRA.2021.3070252. URL https://doi.org/10.1109/LRA.2021.3070252.

Sam Toyer, Rohin Shah, Andrew Critch, and Stuart Russell. The MAGICAL benchmark for robust imitation. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/d464b5ac99e74462f321c06ccacc4bff-Abstract.html.

Maria Tsimpoukelli, Jacob Menick, Serkan Cabi, S. M. Ali Eslami, Oriol Vinyals, and Felix Hill. Multimodal few-shot learning with frozen language models. In Marc'Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 200–212, 2021. URL https://proceedings.neurips.cc/paper/2021/hash/01b7575c38dac42f3cfb7d500438b875-Abstract.html.

Peng Wang, An Yang, Rui Men, Junyang Lin, Shuai Bai, Zhikang Li, Jianxin Ma, Chang Zhou, Jingren Zhou, and Hongxia Yang. Ofa: Unifying architectures, tasks, and modalities through a simple sequence-to-sequence learning framework. *arXiv preprint arXiv: Arxiv-2202.03052*, 2022a.

Thomas Wang, Adam Roberts, Daniel Hesslow, Teven Le Scao, Hyung Won Chung, Iz Beltagy, Julien Launay, and Colin Raffel. What language model architecture and pretraining objective work best for zero-shot generalization? *Icml*, 2022b. doi: 10.48550/arXiv.2204.05832.

Wenhui Wang, Hangbo Bao, Li Dong, Johan Bjorck, Zhiliang Peng, Qiang Liu, Kriti Aggarwal, Owais Khan Mohammed, Saksham Singhal, Subhojit Som, and Furu Wei. Image as a foreign language: Beit pretraining for all vision and vision-language tasks. *arXiv preprint arXiv: Arxiv-2208.10442*, 2022c.

Jason Wei, Yi Tay, Rishi Bommasani, Colin Raffel, Barret Zoph, Sebastian Borgeaud, Dani Yogatama, Maarten Bosma, Denny Zhou, Donald Metzler, Ed H. Chi, Tatsunori Hashimoto, Oriol Vinyals, Percy Liang, Jeff Dean, and William Fedus. Emergent abilities of large language models. *arXiv preprint arXiv: Arxiv-2206.07682*, 2022.

Luca Weihs, Matt Deitke, Aniruddha Kembhavi, and Roozbeh Mottaghi. Visual room rearrangement. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2021, virtual, June 19-25, 2021*, pp. 5922–5931. Computer Vision Foundation / IEEE, 2021. doi: 10.1109/CVPR46437.2021.00586. URL https://openaccess.thecvf.com/content/CVPR2021/html/Weihs_Visual_Room_Rearrangement_CVPR_2021_paper.html.

Andrea Weikert, Andy Goralczyk, Basse Salmela, Ben Dansie, Campbell Barton, Enrico Valenza, Gleb Alexandrov, Ian Hubert, Kjartan Tysdal, Lech Sokolowski, Manu Järvinen, Massimiliana Pulieso, Matt Ebb, Pablo Vazquez, Rob Tuytel, Roland Hess, Sarah Feldlaufer, Sebastian König, Sebastian Platen, and Sönke Mäter. Blender online libraries for textures, 2022. URL https://cloud.blender.org/p/textures/.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander M. Rush. Huggingface's transformers: State-of-the-art natural language processing. *arXiv preprint arXiv: Arxiv-1910.03771*, 2019.

Yuxin Wu, Alexander Kirillov, Francisco Massa, Wan-Yen Lo, and Ross Girshick. Detectron2. https://github.com/facebookresearch/detectron2, 2019.

Tianhe Yu, Deirdre Quillen, Zhanpeng He, Ryan Julian, Avnish Narayan, Hayden Shively, Adithya Bellathur, Karol Hausman, Chelsea Finn, and Sergey Levine. Meta-world: A benchmark and evaluation for multi-task and meta reinforcement learning. *arXiv preprint arXiv: Arxiv-1910.10897*, 2019.

Lu Yuan, Dongdong Chen, Yi-Ling Chen, Noel Codella, Xiyang Dai, Jianfeng Gao, Houdong Hu, Xuedong Huang, Boxin Li, Chunyuan Li, Ce Liu, Mengchen Liu, Zicheng Liu, Yumao Lu, Yu Shi, Lijuan Wang, Jianfeng Wang, Bin Xiao, Zhen Xiao, Jianwei Yang, Michael Zeng, Luowei Zhou,

and Pengchuan Zhang. Florence: A new foundation model for computer vision. *arXiv preprint arXiv: Arxiv-2111.11432*, 2021.

Andy Zeng, Pete Florence, Jonathan Tompson, Stefan Welker, Jonathan Chien, Maria Attarian, Travis Armstrong, Ivan Krasin, Dan Duong, Ayzaan Wahid, Vikas Sindhwani, and Johnny Lee. Transporter networks: Rearranging the visual world for robotic manipulation. *arXiv preprint arXiv: Arxiv-2010.14406*, 2020.

Andy Zeng, Adrian Wong, Stefan Welker, Krzysztof Choromanski, Federico Tombari, Aveek Purohit, Michael Ryoo, Vikas Sindhwani, Johnny Lee, Vincent Vanhoucke, and Pete Florence. Socratic models: Composing zero-shot multimodal reasoning with language. *arXiv preprint arXiv: Arxiv-2204.00598*, 2022.

Mandi Zhao, Fangchen Liu, Kimin Lee, and Pieter Abbeel. Towards more generalizable one-shot visual imitation learning. In *2022 International Conference on Robotics and Automation, ICRA 2022, Philadelphia, PA, USA, May 23-27, 2022*, pp. 2434–2444. IEEE, 2022. doi: 10.1109/ICRA46639.2022.9812450. URL https://doi.org/10.1109/ICRA46639.2022.9812450.

Qinqing Zheng, Amy Zhang, and Aditya Grover. Online decision transformer. *arXiv preprint arXiv: Arxiv-2202.05607*, 2022.

Yuke Zhu, Josiah Wong, Ajay Mandlekar, and Roberto Martín-Martín. robosuite: A modular simulation framework and benchmark for robot learning. *arXiv preprint arXiv: Arxiv-2009.12293*, 2020.

A SIMULATOR DETAILS

We build our VIMA-BENCH simulation suite upon the Ravens physics simulator (Zeng et al., 2020). Our benchmark can be represented as an eight-element tuple $(\mathcal{S}, \mathcal{O}, \mathcal{A}, \mathbf{\Gamma}, \mathbf{T}^{\mathcal{P}}, \mathbf{F_T}, \mathbf{\Omega}, \mathbf{\Psi})$, where $\mathcal{S}$ is the state space, $\mathcal{O}$ is the observation space, $\mathcal{A}$ is the action space, $\mathbf{\Gamma}(s_{t+1},|s_t, a_t)$ is the transition function. We denote $\mathbf{T}^{\mathcal{P}}$ as a task distribution with 17 task templates that can be procedurally instantiated from. Each drawn task is paired with a multimodal prompt $\mathcal{P}$. $\mathbf{F_T}$ defines a set of success criteria for all tasks within distribution $\mathbf{T}^{\mathcal{P}}$. $\mathbf{\Omega}$ and $\mathbf{\Psi}$ denote sets of object geometries and textures. Instantiated from $\mathbf{\Omega} \times \mathbf{\Psi}$, all object instances can be rendered as RGB images appeared in multimodal prompts. Figure A.1 displays all object geometries. Figure A.2 displays all textures. Note that these two sets are easily extensible to include more diverse visual appearances.

The observation space $\mathcal{O}$ of VIMA-BENCH includes RGB images from both frontal and top-down views. It also includes a one-hot vector $\in \{0, 1\}^2$ to indicate type of the end-effector $\in$ {suction cup, spatula}. While a suction cup is employed in most manipulation tasks, a spatula is used in particular for visual constraint tasks, where an agent is asked to "wipe" objects. VIMA-BENCH inherits the same action space $\mathcal{A}$ from Zeng et al. (2020) and Shridhar et al. (2021), which consists of primitive actions of "pick and place" for tasks with a suction cup as the end effector, and "push" for tasks with a spatula. Both primitive actions contain two coordinates $\in \mathbf{SE}(2)$ specifying target poses of the end effector.

Inherited from Zeng et al. (2020) and Shridhar et al. (2021), VIMA-BENCH provides scripted oracles to generate successful demonstrations for all tasks. We leverage them to construct an offline imitation dataset for behavioral cloning.

B TASK SUITE

We develop 6 task categories with 17 task templates paired with multimodal prompts. Note that task categories are not mutually exclusive. See Fig. A.1 for an overview of object shapes and Fig. A.2 for all textures that are applied in our task suite. Demonstrations are interacted in PyBullet (Coumans & Bai, 2016–2021) environment, but we further render them by NVISII (Morrical et al., 2020) for better illustration purpose. We present task templates in each category in the following subsections.

B.1 SIMPLE OBJECT MANIPULATION

Tasks for following the basic instructions provided by multimodal prompts with objects specifications.

Task 01: Pick the specified object(s) and place it into the specified object based on the prompt.

- **Prompt**: `Put the {object}`$_1$ `into the {object}`$_2$`.`
- **Description**: The image placeholder `{object}`$_1$ is the object to be picked and the `{object}`$_2$ is the object at which to be placed. The agent requires to recognize the objects with the correct color-shape combinations. To extend the difficulties, it supports more than one object to be picked or placed. For example, the prompt `Put the {object}`$_1$ `and {object}`$_2$ `into the {object}`$_3$`.` asks to pick two different objects and place into a target base object. Distractors with different color-shape combo for dragged objects and base objects are sampled with equal probability as well.
- **Success Criteria**: All target dragged object(s) are within the bounds of the base object(s), with specified shapes and textures provided in the prompt.
- **Oracle Trajectory**: Shown in Fig. A.3 with its multimodal prompt.

Task 02: In the workspace, put the objects with a specified texture shown in the scene image in the prompt into base object(s) with a specified color. This task requires the agent to find the correct object to manipulate by grounding the color attributes in both natural language and the visual scene image.

- **Prompt**: `Put the {texture}`$_1$ `object in {scene} into the {texture}`$_2$
  `object.`

Figure A.1: **Object Gallery in VIMA-BENCH** textured with random textures. Bowl and pan are from Google Scanned Objects (Downs et al., 2022) while others are from Ravens (Zeng et al., 2020)

Figure A.2: **Texture Gallery in VIMA-BENCH**. The first row of image-based textures are from Blender Cloud Libraries (Weikert et al., 2022), while others are hard-coded.

Put the R into the 🟩.

Figure A.3: Simple Object Manipulation: Task 01

- **Description**: The text placeholder $\{\texttt{texture}\}_1$ and $\{\texttt{texture}\}_2$ are sampled textures for dragged objects to be picked and the base objects to be placed respectively. The number of dragged objects with the same texture can be varied. $\{\texttt{scene}\}$ is the workspace-like scene placeholder which is an image containing the objects with the equivalent texture as the dragged texture. There is a designated number of distractors with different textures (and potentially different shapes) in the scene. For each distractor in the workspace, it has 50% chance to be either dragged or base distractor object with different textures from those specified in the prompt.
- **Success Criteria**: All objects in the workspace with the $\{\texttt{texture}\}_1$ are within the bounds of any base object with the $\{\texttt{texture}\}_2$.
- **Oracle Trajectory**: Shown in Fig. A.4 with its multimodal prompt.

Put the green and blue stripe object in [workspace image] into the yellow paisley object.

Figure A.4: Simple Object Manipulation: Task 02

Task 03: Rotate objects clockwise by certain degrees along z-axis. The rotational symmetry is defined for which the object can be rotated to coincide with itself. Therefore, only the objects without rotational symmetry can be added to this task.

- **Prompt**: `Rotate the` $\{\texttt{object}\}_1$ `{angles} degrees.`
- **Description**: The agent is required to rotate all objects in the workspace same as the dragged object in the image placeholder $\{\texttt{object}\}_1$. To extend the difficulty for this task, more than one kind of dragged object is supported, such that the prompt would be `Rotate the` $\{\texttt{object}\}_1$ `and` $\{\texttt{object}\}_2$ `{angles} degrees.` if there are two dragged objects of interest for instance. There are also objects with different color-shape combinations in the workspace for distraction. $\{\texttt{angles}\}$ is the sampled degree angle that the dragged object needs to be rotated. For consistency, possible angles for rotation are specified as clockwise, and by default, the target angle is sampled from $30°$, $60°$, $90°$, $120°$, and $150°$.
- **Success Criteria**: The position of the specified dragged object matches its original position, and the orientation matches the orientation after rotating specific angles.

- **Oracle Trajectory**: Shown in Fig. A.5 with its multimodal prompt.

Figure A.5: Simple Object Manipulation: Task 03

B.2 VISUAL GOAL REACHING

Tasks require the agent to manipulate objects in the workspace to reach the goal state illustrated in the prompt.

__Task 04:__   Rearrange the objects of interest in the workspace based on the given configuration in the prompt. Note that to achieve the goal of rearranged configuration, distractors may need to be moved away first.

- **Prompt**: `Rearrange to this {scene}.`
- **Description**: Objects in the scene placeholder `{scene}` are target objects of interest to be manipulated and rearranged. In the workspace, the same objects of interest are sampled randomly, and distractor objects can also be sampled. With a defined distractor conflict rate, the position of each distractor has this probability occupied the position of any object of interest in the scene such that the rearrangement only can be succeeded if moving away from that distractor first.
- **Success Criteria**: All poses of objects shown in the prompt scene match the poses of corresponding objects in the scene. Manipulating the distractor to any position is allowed (sometimes required) in this task.
- **Oracle Trajectory**: Shown in Fig. A.6 with its multimodal prompt. .

Figure A.6: Visual Goal Reaching: Task 04

Task 05: Extend the task *04* by requiring the agent to restore objects in the scene to the initial setup after finishing the phase 1 rearrangement.

- **Prompt**: `Rearrange objects to this setup {scene} and then restore.`
- **Description**: Same as the task *04*, except introducing the instruction "restore". Note that moving away the distractor is possible for both the "rearrange" and "restore" phase.
- **Success Criteria**: Meet the success criteria of the task *04*, and then within the allowed max steps, the poses of objects in the workspace that is also shown in the prompt match their poses at the initial state. Note that only conflicted distractors that manipulated in the rearrange phase are allowed to (and have to) manipulate in the restore phase.
- **Oracle Trajectory**: Shown in Fig. A.7 with its multimodal prompt.

Rearrange objects to this setup ▢ and then restore.

Figure A.7: Visual Goal Reaching: Task 05

B.3 NOVEL CONCEPT GROUNDING

In this category, tasks require the agent to ground the new concepts of adjectives, nouns, or verbs via visual perception and language in the prompt. Prompts consist of two phases: a definition phase followed by the instruction phase. In the definition phase, novel conceptions are defined by multimodal illustrations with multiple supporting examples, and in the instruction phase, the agent is instructed to achieve the goal while applying concepts in the definition phase accordingly. The assignment of unique nonsense words is varied and independent for each task instance such that tasks can be solved consistently only if the agent applies the mapping between the words' conception in the definition phase to the decision-making in the instruction phase. This ability is also referred to as *fast-mapping* (Heibeck & Markman, 1987)).

Task 06: Ground the comparative adjectives by comparing the size or the lightness of objects and manipulating the correct object(s) instructed in the prompt.

- **Prompt**:`{demo_object}`$_1$ `is {novel_adj} than {demo_object}`$_2$`. Put the {adv} {novel_adj} {object}`$_1$ `into the {object}`$_2$`.`
- **Description**: This task supports multiple examples with the format `{demo_object}`$_i$ `is {novel_adj} than {demo_object}`$_{i+1}$. The color-shape combo of objects in different examples is sampled differently. The sampled adjective `{novel_adj}` is a nonsense adjective for agent grounding. By default, the novel adjective set is {`daxer`, `blicker`, `modier`, `kobar`}. Equivalently, the real compassion is sampled from the size (smaller/larger), height (shorter/taller), or lightness (lighter/darker texture). The image placeholders `{demo_object}`$_1$ and `{demo_object}`$_2$ illustrate how the novel adjective is defined per-episode. For example, if the real comparison is "taller", then the sampled object in `{demo_object}`$_1$ is taller than `{demo_object}`$_2$. The choices of the novel adjective and the real comparison are independently sampled mapping for different episodes.

In the instruction phase, the task is performed similarly to the task *01*, where the agent is required to pick the specified dragged object(s) with the novel adjective attribute and then place it into the specified base object. To avoid spoiling which objects to be picked, objects in image placeholders for target dragged objects are normal size and gray. With 50% chance, the target object to be picked has the flipped adjective attribute as the adjective defined in the definition phase, with extra `adv` "less" added in the prompt (e.g. if the target comparison is for "taller" and the dragged object is the block, then the object to be picked should be shorter block). The primary distractor would sampled as constructing the comparison, while keeping other attributes the same. For example, if the target dragged object is a taller block, then the first distractor is the shorter block. Due to the limited size of the workspace, we only use "shorter/taller" and "lighter color/darker color" in experiments.

- **Success Criteria**: All target dragged objects with the specified adjective attribute implicitly illustrated in the prompt is within the bounds of the specified base object.
- **Oracle Trajectory**: Shown in Fig. A.8 with its multimodal prompt.

Figure A.8: Novel Concept Grounding: Task 06

Task 07: Extend the task *01* by requiring to learn mappings between novel nouns and dragged objects and base objects instead.

- **Prompt**: `This is a {novel_name}`$_1$ `{object}`$_1$`. This is a {novel_name}`$_2$ `{object}`$_2$`. Put {novel_name}`$_1$ `into a {novel_name}`$_2$`.`
- **Description**: The novel noun words are defined with the text placeholders `{novel_name}`$_1$ and `{novel_name}`$_2$, following with its mapped image placeholders `{object}`$_1$ and `{object}`$_2$, for the target dragged object and base object respectively. Multiple dragged objects are supported like the task *01*, with separate novel names and the same definition prompt format. The default novel nouns are sampled from `{dax, blicket, wug, zup}`. In the instruction phase, objects are expressed as novel nouns defined in the previous definition phase. Distractors are defined the same as task *01*.
- **Success Criteria**: All target dragged object(s) are within the bounds of the base object(s), with specified novel name and visual illustration mappings in the prompt. The color-shape combos of target objects are the same as the objects in the prompt.
- **Oracle Trajectory**: Shown in Fig. A.8 with its multimodal prompt.

Task 08: Combine with the task *06* and task *07*.

- **Prompt**: `This is a {novel_name}`$_1$ `{object}`$_1$`. This is a {novel_name}`$_2$ `{object}`$_2$`. {demo_object}`$_1$ `is {adj} than {demo_object}`$_2$`. Put the {adv} {novel_adj} {novel_name}`$_1$ `into the {novel_name}`$_2$`.`
- **Description**: see task description for task *06* and task *07*.
- **Success Criteria**: Objects to be picked and placed follow the success criteria of the task *07* while others follow criteria of the task *06*.
- **Oracle Trajectory**: Shown in Fig. A.10 with its multimodal prompt.

Figure A.9: Novel Concept Grounding: Task 07

Figure A.10: Novel Concept Grounding: Task 08

Task 09: Ground the verb "twist" which is defined as rotating a specific angle corresponding with several examples for each task instance. This task is similar to the task *03*, but it needs to learn what is the exact angle to twist from each task prompt and to ground verbs that are semantically similar but different in exact definitions.

- **Prompt**: `"Twist"` `is defined as rotating object a specific angle.` `For examples:  From {before_twist}`$_i$` to {after_twist}`$_i$`. Now twist` `all {texture} objects.`

- **Description**: This task supports multiple examples with the format `From {before_twist}`$_i$` to {after_twist}`$_i$`.` where i corresponds with the order of examples. `{before_twist}`$_i$ and `{after_twist}`$_i$ are both scene placeholders where `{before_twist}`$_i$ is a workspace-like scene with a randomly sampled object pose before "twist" and `{after_twist}`$_i$ is the scene showing the object pose after "twist". All examples illustrate the same sampled angle of the rotation. In the workspace, the target manipulated objects have the same texture as `{texture}` , and shapes are randomly sampled. Instead of defining the specific number of the manipulated object as the task *03*, the total number of objects is defined in this task, where the number of targets manipulated objects and distractor objects (at least one) with a different texture(s) from `{texture}` are randomly sampled.

- **Success Criteria**: Same as the task *03*.

- **Oracle Trajectory**: Shown in Fig. A.11 with its multimodal prompt.

B.4 ONE-SHOT VIDEO IMITATION

Tasks require the agent to imitate the moves with the strict manipulation sequence in the given one-shot video trajectory. We define video trajectories by the variable length of step-wise observation frames in the prompt.

Figure A.11: Novel Concept Grounding: Task 09

Task 10: Follow motions from the video trajectory as a specified walk along a polygon that approximates a circle around a central object.

- **Prompt**: `Follow this motion for {object}: {frame}`$_1$`...{frame}`$_i$`...` `{frame}`$_n$`.`
- **Description**: Image placeholder `{object}` is the target object to be manipulated and `{{frame}`$_i$`}` is set of workspace-like scene placeholders for the imitation video trajectory frames, where n is the trajectory length and. There is an object sampled at the center in both the workspace and trajectory frames but with different textures, which naturally becomes a distractor. In each frame of the video trajectory, the target dragged object is sampled at random vertices of an invisible polygon centered at the distracting object. Note that the position of the target dragged object at the initial state is the same as it is in the `{frame}`$_1$. The color-shape combos of the target dragged object in the workspace and frames are the same.
- **Success Criteria**: For each step, the pose of the target dragged object matches the pose of it in each corresponding frame in the prompt. The incorrect manipulation sequence at a time step is considered a failure.
- **Oracle Trajectory**: Shown in Fig. A.12 with its multimodal prompt.

Figure A.12: One-shot video imitation: Task 10

Task 11: Stack objects with the order illustrated in the video trajectory in the prompt.

- **Prompt**: `Stack objects in this order {frame}`$_1$`...{frame}`$_i$`...{frame}`$_n$`.`
- **Description**: There are multiple objects with the same shape but different textures sampled in the workspace without any stacking initially. For convenience, they are sampled as a line at the center of the workspace. Distractor objects with different shapes can be sampled in the workspace but not for the trajectory frames. Objects without the distractor(s) in the workspace in the initial state share the same positions in `{frame}`$_1$. For the rest of the

trajectory frames in the prompt, one of the (uppermost) objects is stacked over another object or at the empty position, in comparison with the previous frame.

- **Success Criteria**: For each step, poses of all objects without the distractor(s) in the workspace match the poses of the same objects in each corresponding frame. The incorrect manipulation sequence at a time step is considered a failure.

- **Oracle Trajectory**: Shown in Fig. A.13 with its multimodal prompt.

Figure A.13: One-shot video imitation: Task 11

B.5 VISUAL CONSTRAINT SATISFACTION

Tasks for manipulating a specific number of objects in the workspace to achieve the goal while also required to satisfy the given constraint in the prompt.

Task 12: Sweep the designated number of objects into the specified bounds of the zone without exceeding the constraint area in the workspace.

- **Prompt**: `Sweep {quantifier} {object} into {bounds} without exceeding {constraint}.`

- **Description**: {object} is the image placeholder of the target swept object which is sampled with the random number and same texture in the workspace. Distractors with the same number, same shape, and different color from target swept objects are sampled as well. {quantifier} is the text placeholder to determine the target number of swept objects to be actually manipulated, sampled from `any`, `one`, `two`, `three`, and `all`. {bounds} in experiments is the image placeholder for a three-sided rectangle with sampled color for blocks being swept in, and { constraint} is the line with sampled color that is a constraint for exceeding by sweeping blocks.

- **Success Criteria**: The exact number of target swept objects that should be manipulated are all inside the specified bounds of the zone. If any distractor is swept, the target swept objects are exceeding the constraint area, or the number of objects in the zone is exceeded the target number of objects to be manipulated, the task is considered as failed.

- **Oracle Trajectory**: Shown in Fig. A.14 with its multimodal prompt.

Task 13: Sweep the designated number of objects into the specified bounds of the zone without touching the constraint area in the workspace.

- **Prompt**: `Sweep {quantifier} {object} into {bounds} without touching {constraint}.`

- **Description**: Same as the task *12* but providing not directly accessible goal states with the constraint. The agent has to learn to avoid "touching" the constraint line in this case.

- **Success Criteria**: Same as the task *12* except the constraint is touching in this case.

- **Oracle Trajectory**: Shown in Fig. A.15 with its multimodal prompt.

Figure A.14: Visual Constraint Satisfaction: Task 12

Figure A.15: Visual Constraint Satisfaction: Task 13

B.6 Visual Reasoning

Tasks require the agent to make decisions by reasoning from the implicitly instructional prompt. Inclusively, tasks may require the agent to memorize over a long horizon as well. Those tasks may have two phases, where the first phase requires the agent to act with the explicit instruction in the prompt while the second phase requires the agent to act with the instruction with implicit information from the previous or initial state. The action sequence also has to follow the order of two phases.

Task 14: By reasoning the "same texture", the agent is required to pick all objects in the workspace with the same texture as the target base objects specified in the prompt and place them into it.

- **Prompt**: `Put all objects with the same texture as {object} into it.`
- **Description**: {object} is the sampled target base object to be placed. In the workspace, there is a predefined number of objects with potentially different shapes and the same texture as the target base objects. For the distraction, several numbers of distractors with different textures are sampled.
- **Success Criteria**: All objects with the same texture as the target base object are within the bounds of the target base object illustrated in the prompt.
- **Oracle Trajectory**: Shown in Fig. A.16 with its multimodal prompt.

Task 15: By reasoning the "same profile", the agent is required to pick all objects in the workspace with the same profile as the target base objects specified in the prompt and place them into it. *Profile* here is defined as the shape attribute of an object. For example, the object block and pallet are both considered as *square-like* profile.

- **Prompt**: `Put all objects with the same profile as {object} into it.`

Put all objects with the same texture as ⬤ into it.

Figure A.16: Visual Reasoning: Task 14

- **Description**: Similar to the task *14* except the objects to be picked and placed are with the same profile as the specified base object in the prompt. Without further elaboration, there are three different profiles in our object set used in experiments for sampling: *square-like* (e.g. block and pallet), *circle-like* (e.g. ring and bowl), and *undetermined* for the rest.

- **Success Criteria**: All objects with the same profile as the target base object are within the bounds of the target base object illustrated in the prompt.

- **Oracle Trajectory**: Shown in Fig. A.17 with its multimodal prompt.

Put all objects with the same profile as ⬤ into it.

Figure A.17: Visual Reasoning: Task 15

Task 16: Put the target object into the target base object, and then put its old neighbor from a sampled direction into that base object.

- **Prompt**: `First put {object}`$_1$` into {object}`$_2$` then put the object that was previously at its {direction} into the same {object}`$_2$`.

- **Description**: Objects in image placeholders $\{$`object`$\}_1$ and $\{$`object`$\}_2$ are the first dragged target object to be picked and the base object to be placed respectively. There is an invisible $r \times h$ gridworld for objects to be sampled initially. Besides the target dragged object, the second neighbor object is implicitly required to be picked and placed at the possible direction $\{$`direction`$\}$ in terms of the target (first) dragged object. By default, directions can be sampled from $\{$`north, south, west, east`$\}$, corresponding with $(-1, 0)$, $(1, 0)$, $(0, -1)$, and $(0, 1)$ coordinates change in the gridworld respectively. Distractors in this task are defined as the *real* distractor and the *null* distractor. The *real* distractors are sampled with different color-shape combos from the target dragged object, and the *null* distractors are just the empty space in the gridworld. Note that the total number of distractors is defined as $r \times h - 2$. As positions of distractors are randomly sampled, positional configurations of each task instance are different for the general purpose.

- **Success Criteria**: The target dragged object is within the bounds of the base object, and the object previously at the specified direction of the target dragged object is also within the bounds of the base object. The moving sequence is constrained by manipulating the target dragged object to the base object first and then the second neighbor object.

- **Oracle Trajectory**: Shown in Fig. A.18 with its multimodal prompt.

Figure A.18: Visual Reasoning: Task 16

Task 17: Pick and place the target dragged objects illustrated in the prompt to the target base objects with specified colors accordingly then put it into its initial base object.

- **Prompt**: `Put {object}₁ into {object}₂. Finally restore it into its original container.`
- **Description**: The object in the image placeholder `{object}₁` is the target dragged object to be picked and placed across the task. In the workspace, there is also an invisible gridworld that is placed with sampled base objects with the same shape but different textures for all grid points. There can be more than one target base objects to be placed (e.g. `Put {object}₁ into {object}₂ then {object}₃.Finally restore it into its original container.` for two target base objects to be placed in order). The rest of sampled base objects are naturally becoming distractors.
- **Success Criteria**: The target dragged object is within the bounds of each target base object first. If there are more than one target base objects, the manipulation sequence is constrained by the order in the prompt. After meeting the before criteria, the target dragged object is within the bounds of the first base object that contains it in the initial state.
- **Oracle Trajectory**: Shown in Fig.A.19 with its multimodal prompt.

Figure A.19: Visual Reasoning: Task 17

C MODEL ARCHITECTURE

In this section, we provide comprehensive details about VIMA model architecture as well as other adapted baseline methods. We implement all models in PyTorch (Paszke et al., 2019) and adapt Transformer-related implementation from Wolf et al. (2019).

C.1 VIMA ARCHITECTURE

C.1.1 MULTIMODAL PROMPT TOKENIZATIONS

As introduced in Section 5, there are 3 types of input formats in multimodal prompts, namely (1) **text inputs**, (2) **images of full scenes**, and (3) **images of single objects**.

For **text inputs**, we follow the standard pipeline in NLP to first tokenize raw languages to discrete indices through pre-trained `t5-base` tokenizer. We then obtain corresponding word tokens from the

Table 1: Model hyperparameters for multimodal prompt tokenization.

Hyperparameter	Value
Text Tokenization	
Tokenizer	`t5-base` tokenizer
Embedding Dimension	768
Image Tokenization	
ViT Input Image Size	32×32
ViT Patch Size	16
ViT Width	768
ViT Layer	4
ViT Number of Heads	24
Bounding Box MLP	
Hidden Dimension	768
Hidden Depth	2
Prompt Encoding	
Pre-trained LM	`t5-base`
Unfreeze Last N Layers	2
Positional Embedding	Absolute
Token Adapter MLP Depth	2

embedding look-up of the pre-trained `t5-base` model. For **images of full scenes**, we first parse the scene through a fine-tuned mask R-CNN detection model to extract individual object. Each object representation contains a bounding box and a cropped image. The bounding box is in the format of $[x_{\text{center}}, y_{\text{center}}, \text{height}, \text{width}]$. We normalize it to be within $[0, 1]$ by dividing each dimension with corresponding upper-bound value. We then pass it through a bounding box encoder MLP and obtain a feature vector. To process the cropped image, we first pad non-square image to a square by padding along the shorter dimension. We then resize it to a configured size and pass it through a ViT (trained from scratch) to obtain the image feature. Finally, an object token is obtained by concatenating the bounding box feature and the image feature and mapping to the embedding dimension. Detailed model hyperparameters about tokenizations are listed in Table 1.

After obtaining a sequence of prompt tokens, we follow Tsimpoukelli et al. (2021) to pass it through a pre-trained `t5-base` encoder to obtain encoded prompt. Note that we add adapter NLP between object tokens and the T5 encoder. We adopt learned absolute positional embedding. Model hyperparameters are listed in Table 1 as well.

C.1.2 OBSERVATION ENCODING

Since all RGB observations are images of full scenes, we follow the same procedure discussed above to obtain flattened object tokens. Because we provide RGBs from two views (frontal and top-down), we order object tokens by following the order of [frontal, top-down]. We one-hot encode the state of the end effector. We then concatenate object tokens with the end-effector state and transform to observation tokens. We adopt learned absolute positional embedding. Detailed model hyperparameters about observation encoding is provided in Table 2.

Table 2: Model hyperparameters for observation encoding.

Hyperparameter	Value
Observation Token Dimension	768
End Effector Embedding Dimension	2
Positional Embedding	Absolute

C.1.3   ACTION ENCODING

Since our model is conditioned on observation-action interleaved trajectory history, we also tokenize past actions. We follow common practice in Chen et al. (2021); Zheng et al. (2022) to encode past actions with a two-layer MLP. It has a hidden dimension of 256. We then map outputs to token dimension and obtain action tokens.

C.1.4   SEQUENCE MODELING

The robot controller in VIMA is a causal decoder that autoregressively predicts actions. To condition the decoder on prompt tokens, we perform cross-attention between trajectory history tokens and prompt tokens (Figure 3). Concretely, we pass trajectory history tokens as the query sequence and prompt tokens as the key-value sequence into cross-attention blocks. The output prompt-aware trajectory tokens then go through causal self-attention blocks. We alternate cross-attention and self-attention L times. This procedure is technically described in Pseudocode 1.

```python
def xattn_sequence_modeling(
    prompt_tokens,      # the [L, d] prompt tokens (L=prompt length)
    obs_tokens,         # the [T, d] obs tokens (T=time step)
    act_tokens,         # the [T-1, d] action tokens
    traj_pos_embd,      # learned positional embedding for trajectory
    prompt_pos_embd,    # learned positional embedding for prompt
):
    # interleave obs and action tokens
    traj_tokens = interleave(obs_tokens, act_tokens)  # [2T-1, d]
    # add positional embedding to trajectory tokens
    x = traj_tokens + traj_pos_embd
    # add positional embedding to prompt tokens
    prompt_tokens = prompt_tokens + prompt_pos_embd

    # apply xattn and causal self-attn
    for i in range(num_layers):
        # cross-attention
        x = x + attn_i(q=x, kv=prompt_tokens)
        # feed forward
        x = x + ffw_xattn_i(x)
        # self-attention
        x = x + causal_attn_i(q=x, kv=x)
        # feed forward
        x = x + ffw_i(x)

    # the last token is the predicted action token
    predicted_act_token = x[-1]
    return predicted_act_token
```

Pseudocode 1: Cross-attention operation that conditions the trajectory history on prompt. We repetitively alternate cross-attention and self-attention to model the trajectory given a specific task.

C.1.5   ACTION DECODING

After obtaining the predicted action token, we map it to the action space $\mathcal{A}$ and obtain the predicted action. This is achieved though a group of action heads. Since the action space consists of two $\mathbf{SE}(2)$ poses, for each pose we use six independent heads to decode discrete actions (two for xy coordinate and four for rotation represented in quaternion). These discrete actions are then de-discretized and mapped to continuous actions through affine transformation. The two poses are modeled independently. Early ablations show that this independent modeling has no difference with, for example, auto-regressive modeling. Detailed model hyperparameters are listed in Table 3.

Table 3: Model hyperparameters for action decoders.

Hyperparameter	Value
Hidden Dimension	512
Hidden Depth	2
Activation	ReLU
X-axis Discrete Bins	50
Y-axis Discrete Bins	100
Rotation Discrete Bins	50

Table 4: Model hyperparameters for ViT used in baseline methods.

Hyperparameter	Value
Image Size	64 x 128
Patch Size	32
ViT Width	768
ViT Layers	4
ViT Heads	24

C.2   BASELINES ARCHITECTURES

In this section, we elaborate model architectures for baseline methods. Some components such as the action decoder are same across all baseline methods and ours. Therefore, we only discuss unique model components.

C.2.1   GATO

Gato (Reed et al., 2022) introduces a decoder-only model that solves tasks from multiple domains where tasks are specified by prompting the model with the observation and action subsequence. There are two differences between Gato and our method. (1) **Different visual tokenizers**. In Gato, observation tokens are represented as sequence of image patches instead of object tokens as in our method. We deviate from the original Gato implementation by replacing the ResNet with a ViT to encode image patches. (2) **Different prompt conditioning**. In Gato, prompt tokens are directly prepended to trajectory history tokens. This sequence of temporally concatenated tokens are then passed through a decoder-only model. Hyperparameters of Gato's ViT is listed in Table 4. The decoder-style sequence modling is technically illustrated in Pseudocode 2.

```
1  def causal_sequence_modeling(
2      prompt_tokens,   # the [L, d] prompt tokens (L=prompt length)
3      sep_token,       # the [1, d] learned token to separate prompt and
       trajectory history
4      obs_tokens,      # the [T, d] obs tokens (T=time step)
5      act_tokens,      # the [T-1, d] action tokens
6      pos_embd,        # learned positional embedding
7  ):
8      # interleave obs and action tokens
9      traj_tokens = interleave(obs_tokens, act_tokens)  # [2T-1, d]
10     # assemble input tokens
11     x = concat([prompt_tokens, sep_token, traj_tokens])
12     x = x + pos_embd
13
14     # apply GPT layers with causal mask
15     for i in range(num_layers):
16         # self-attention
17         x = x + causal_attn_i(q=x, kv=x)
18         # feed forward
19         x = x + ffw_i(x)
20
21     # the last token is the predicted action token
22     predicted_act_token = x[-1]
23     return predicted_act_token
```

Pseudocode 2: Plain sequence modeling that temporally concatenates prompt and trajectory history and repetitively perform causal self-attention operation.

C.2.2 FLAMINGO

Flamingo (Alayrac et al., 2022) is a vision-language model that learns to generate textual completion in response to multimodal prompts. It embeds a variable number of prompt images into a fixed number of tokens via the Perceiver Resampler module (Jaegle et al., 2021b), and conditions the language decoder on the encoded prompt by cross-attention. Therefore, the only difference between Flamingo and our method lies at the visual tokenizer. Concretely, in Flamingo we first use a ViT (hyperparameters in Table 4) to obtain an encoded sequence of image patches. We then apply a Perceiver Resampler to down-sample these image patches to a fixed number of tokens. We refer interested readers to Section 3.1.1 in Alayrac et al. (2022) for more technical details. Model hyperparameters for the Perceiver Resampler is listed in Table 5. Because Flamingo does not work with embodied agents out of the box. We adapt it to support decision-masking by replacing the original word prediction head with robot action heads with same hyperparameters listed in Table 3.

Table 5: Model hyperparameters for Perceiver Resampler used in Flamingo method.

Hyperparameter	Value
Number of Latent Queries	4
Number of Blocks	4
Self-attn per Block	4
Self-attn Heads	24
Cross-attn Heads	24

C.2.3 DECISION TRANSFORMER

Decision Transformer (DT) (Chen et al., 2021; Janner et al., 2021) is among the first works to reinterpret the RL problem as transformer sequence modeling. In visual RL domains like Atari games, DT is prompted on the desired reward value and outputs actions autoregressively given the RGB observation embedding. We replace DT's initial reward prompt with our multimodal task prompt embeddings, and remove all subsequent reward tokens. For visual tokenizer, we employ a learned ViT with hyperparameters listed in Table 4 to map an observed image to a single "state" token.

C.3 MASK R-CNN DETECTION MODEL

Finally, we elaborate the mask R-CNN model (He et al., 2017) for scene parsing and object extraction. We fine-tuned a pre-trained lightweight mask R-CNN from Wu et al. (2019) to adapt to scenes and images in our tabletop environment. A visualization of its output is provided in Figure A.20. We do not use the predicted object names in our models.

Figure A.20: Visualization of fine-tuned mask R-CNN. Left: Prediction from the detection model. Right: Ground-truth scene parsing. The detection model agrees well with ground-truth objects.

D   VIMA TRAINING DETAILS

We follow the best practices to train Transformer models using the AdamW optimizer (Loshchilov & Hutter, 2019), learning rate warm-up, cosine annealing (Loshchilov & Hutter, 2017), etc. Training hyperparameters are provided in Table 6. We use GEGLU activation (Shazeer, 2020) within Transformer models across all methods.

Table 6: Hyperparameters used during training.

Hyperparameter	Value
Learning Rate	0.0001
Warmup Steps	7K
LR Cosine Annealing Steps	17K
Weight Decay	0
Dropout	0.1
Gradient Clip Threshold	1.0

To make trained models robust to detection inaccuracies and failures, we apply *object augmentation* by randomly injecting *false-positive* detection outputs. Concretely, for observation at each time step, we sample number of augmented objects i.i.d. $n_{\text{augmented objects}} \sim \text{Cat}(K, \mathbf{p})$, where $\text{Cat}(\cdot)$ denotes a multi-categorical distribution with K supports parameterized by $\mathbf{p}$. For each augmented object, we then randomly sample a bounding box and corresponding cropped image to add to object tokens. In our experiments, we set $\mathbf{p} = \{0 : 0.95, 1 : 0.05\}$ with $K = 2$.

D.1   VARY MODEL CAPACITY

We train a spectrum of 7 models ranging from 2M to 200M parameters. To vary the model capacity, we follow prior work (Chowdhery et al., 2022) to change embedding dimension and number of layers. We list configurations for methods with cross-attention prompt conditioning (i.e., ours and Flamingo) in Table 7, and configurations for methods only with causal self-attention in Table 8.

E   MORE EXPERIMENT RESULTS

E.1   BREAKDOWN RESULTS

We show breakdown results for Figure 4 in Tables 9, 10, 11, and 12, respectively.

Table 7: Configurations for different sized models with cross-attention prompt conditioning.

Model Size (M)	Embedding Dimension	Num Blocks	X-attn Heads	Self-attn Heads
2	256	1	8	8
4	256	2	8	8
9	320	3	10	10
20	384	4	12	12
43	512	5	16	16
92	640	7	20	20
200	768	11	24	24

Table 8: Configurations for different sized models with causal self-attention prompt conditioning.

Model Size (M)	Embedding Dimension	Num Blocks	Self-attn Heads
2	64	1	2
4	96	2	3
9	192	3	6
20	320	4	10
43	512	5	16
92	768	7	24
200	768	18	24

Table 9: L1 level generalization results. Model indicates robot controller parameter count.

Model	Method	Task 01	Task 02	Task 03	Task 04	Task 05	Task 06	Task 07	Task 09	Task 11	Task 12	Task 15	Task 16	Task 17
2M	Ours	100.0	100.0	100.0	96.0	37.0	100.0	100.0	9.5	87.0	64.0	93.5	45.0	63.0
	Gato	62.0	61.0	22.5	13.5	7.0	44.5	54.0	4.0	48.0	85.0	44.5	43.0	0.0
	Flamingo	56.0	56.0	53.5	36.5	37.5	45.0	55.5	3.5	54.0	83.5	40.5	28.5	2.0
	DT	59.5	50.5	7.5	7.0	0.5	43.5	49.5	2.0	61.5	76.5	27.5	5.0	0.0
20M	Ours	100.0	100.0	100.0	99.5	59.5	100.0	100.0	13.5	74.0	72.5	96.5	39.5	47.5
	Gato	61.5	62.0	32.5	49.0	38.0	46.0	60.0	5.0	68.0	83.0	47.0	46.5	2.0
	Flamingo	63.0	61.5	55.0	50.0	42.5	41.5	58.0	6.0	62.0	83.0	44.0	38.5	1.0
	DT	60.5	64.0	50.5	44.0	41.0	48.0	61.5	7.0	85.0	84.0	44.5	39.0	2.5
200M	Ours	100.0	100.0	99.5	100.0	56.5	100.0	100.0	18.0	77.0	93.0	97.0	76.5	43.0
	Gato	79.0	68.0	91.5	57.0	44.5	54.0	74.0	18.0	61.0	88.5	83.5	33.5	2.5
	Flamingo	56.0	58.5	63.0	48.5	38.0	48.5	62.5	3.5	66.5	86.0	40.0	43.5	2.5
	DT	62.0	57.5	41.0	55.5	45.5	47.5	54.5	8.5	77.0	81.5	41.0	38.0	0.5

Table 10: L2 level generalization results. Model indicates robot controller parameter count.

Model	Method	Task 01	Task 02	Task 03	Task 04	Task 05	Task 06	Task 07	Task 09	Task 11	Task 12	Task 15	Task 16	Task 17
2M	Ours	100.0	100.0	100.0	95.5	37.5	100.0	100.0	17.5	87.5	67.0	97.5	46.0	54.5
	Gato	49.5	49.0	23.0	17.5	0.5	47.5	46.5	5.5	50.0	82.5	49.0	42.0	0.5
	Flamingo	45.5	46.0	56.0	39.5	35.5	49.0	47.0	9.0	53.0	80.0	43.0	29.5	1.0
	DT	51.0	45.5	9.5	7.0	0.5	45.5	45.0	0.0	65.0	81.5	32.0	5.0	0.0
20M	Ours	100.0	100.0	100.0	100.0	61.0	100.0	100.0	16.5	75.5	75.0	96.0	37.5	47.5
	Gato	44.0	51.5	39.0	51.0	38.5	47.5	52.5	6.0	65.5	84.0	52.5	40.5	1.0
	Flamingo	48.5	49.0	55.5	48.0	42.5	46.5	52.0	6.0	66.0	82.0	47.5	37.0	0.5
	DT	50.5	49.5	53.0	44.5	43.5	47.0	46.0	8.0	83.5	80.0	46.5	41.0	2.5
200M	Ours	100.0	100.0	99.5	100.0	54.5	100.0	100.0	17.5	77.0	93.0	98.5	75.0	45.0
	Gato	56.5	53.5	88.0	55.5	43.5	55.5	53.0	14.0	63.0	90.5	81.5	33.0	4.0
	Flamingo	51.0	52.5	61.5	49.5	38.5	47.5	55.5	5.5	70.5	82.0	42.0	39.0	3.0
	DT	52.0	52.0	49.5	54.5	45.5	52.5	51.0	11.0	76.5	84.0	43.0	38.0	0.5

E.2 VARY T5 ENCODER SIZES

We vary the size of the pre-trained T5 encoder (Raffel et al., 2020) to study the effect of prompt encoding. We experiment with three T5 model capacities: `t5-small` (30M), `t5-base` (111M), to `t5-large` (368M). For all T5 variants, we fine-tune the last two layers and freeze all other layers. We fix the parameter count of the decision-making part to be 200M. As shown in Table 13, we find that no significant difference among the variants. Thus we set the standard `t5-base` as default for all our models.

Table 11: L3 level generalization results. Model indicates robot controller parameter count.

Model	Method	Task 01	Task 02	Task 03	Task 04	Task 05	Task 06	Task 07	Task 09	Task 11	Task 15	Task 16	Task 17
2M	Ours	100.0	100.0	100	98.0	34.5	100.0	99.5	17.0	97.5	94.0	48.5	39.0
	Gato	45.5	48	28.0	23.0	3.0	45.5	45.0	2.5	40.5	29.5	37.0	1
	Flamingo	41.5	54.5	50.5	39.5	29	45.0	49.5	5.5	57.5	22.5	25.0	0.0
	DT	48.5	50.0	5.0	7.0	2.5	47	45.5	2.0	69.5	22.5	5.0	0.0
20M	Ours	98.0	100.0	100	98.5	55.5	100.0	99.5	15.0	88.5	99.5	44.0	29.5
	Gato	46.5	55	44.5	57.0	31.5	47.5	51.5	2.5	72.5	30.5	44.0	0
	Flamingo	47.0	54.5	53.0	55.0	36	42.5	48.0	6.5	70.0	33.0	41.5	0.0
	DT	50.0	60.5	56.5	48.0	33.5	51	46.0	6.5	92.5	32.5	43.5	1.5
200M	Ours	99.0	100.0	100	97.0	54.5	100.0	99.0	17.5	90.5	97.5	46.0	43.5
	Gato	51.0	58	84.5	56.5	35.5	53.5	49.0	15.0	65.0	52.0	33.0	0
	Flamingo	49.0	50.0	66.5	47.0	35	47.5	50.0	4.0	66.0	30.5	43.5	0.5
	DT	52.0	51.0	55.0	49.5	40.0	46	50.5	5.0	82.0	37.0	38.0	1.5

Table 12: L4 level generalization results. Model indicates robot controller parameter count.

Model	Method	Task 08	Task 10	Task 13	Task 14
2M	Ours	6.5	0	0	96.5
	Gato	21.0	0.5	0	32
	Flamingo	22.0	0	0	27.5
	DT	22.5	0.0	0	22.0
20M	Ours	100.0	0	0	95.5
	Gato	20.5	0.0	0	29
	Flamingo	21.0	0	0	27.5
	DT	20.5	0.5	0	36.0
200M	Ours	100.0	0	0	94.5
	Gato	30.5	0.0	0	37
	Flamingo	24.5	0	0	24.0
	DT	20.0	0.0	0	28.5

Table 13: Performances of our method with different sized pre-trained T5 prompt encoder. We fix the parameter count of the decision-making part to be 200M.

	t5-small (30M)	t5-base (111M)	t5-large (368M)
L1	78.8	81.5	80.8
L2	79.0	81.5	81.0
L3	80.3	78.7	81.0
L4	49.1	48.6	49.3

F EXTENDED RELATED WORK

In this section, we provide an extended review of related work as complementary to Section 2.

Multi-task Learning by Sequence Modeling. In NLP domain, T5 (Raffel et al., 2020) and GPT (Radford et al., 2019; Brown et al., 2020) are among the earliest architectures to use a single model for generation, reasoning, translation, etc. The Natural Language Decathlon (McCann et al., 2018) adopts a consistent question-answering format for a suite of 10 NLP tasks. In computer vision, Mask R-CNN (He et al., 2017), UberNet (Kokkinos, 2016), 12-in-1 (Lu et al., 2020) leverages a single backbone model with multiple independent heads for different tasks. Pix2Seq (Chen et al., 2022a;b) casts object detection, instance segmentation, and keypoint detection into a common sequence setting. UVim (Kolesnikov et al., 2022) is another unified approach for vision that uses a language model (LM) to generate the guiding code for a second model to predict raw vision outputs. In multimodal learning, Unified-IO (Lu et al., 2022), BeiT (Wang et al., 2022c), Flamingo (Alayrac et al., 2022), and Gato (Reed et al., 2022) are able to unify a wide range of vision, language, and policy learning problems. OFA (Wang et al., 2022a) leverages a sequence-to-sequence learning framework with a unified vocabulary for all the image and text tokens. Perceivers (Jaegle et al., 2021b;a) propose an efficient architecture to handle general-purpose inputs and outputs. BEiT-3 (Wang et al., 2022c) performs masked data modeling on images, texts and image-text pairs to pre-train the backbone then transfer to various downstream tasks.

Foundation Models for Embodied Agents. Embodied agent research (Duan et al., 2022; Batra et al., 2020; Ravichandar et al., 2020; Collins et al., 2021) is also adopting the large-scale pre-training paradigm. From the aspect of **pre-training for better representations**, LaTTe (Bucker et al., 2022), CLIPort (Shridhar et al., 2021), and Embodied-CLIP (Khandelwal et al., 2021) leverage the frozen visual and textual representations of CLIP (Radford et al., 2021) for robotic manipulation. When **using pre-trained models for better policies**, Li et al. (2022) and Reid et al. (2022) use pre-trained LMs as policy backbone and outperform baselines without pre-trained models.

Robot Manipulation and Benchmarks. There are more prior works that are not mentioned in the main paper that study different robotic manipulation tasks, such as instruction following (Stepputtis et al., 2020; Shridhar et al., 2021; Lynch & Sermanet, 2021), constraint satisfaction (Bharadhwaj et al., 2021), one-shot imitation (Paine et al., 2018; Huang et al., 2019; Aceituno et al., 2021; Zhao et al., 2022), and rearrangement (Liu et al., 2021; Ehsani et al., 2021; Gan et al., 2021; Stengel-Eskin et al., 2022). Multiple simulation benchmarks are introduced to study the above tasks: 1) **Indoor simulation environments**: Habitat (Savva et al., 2019; Szot et al., 2021) is equipped with a high-performance 3D simulator for fast rendering and proposes a suite of common tasks for assistive robots. AI2-THOR (Ehsani et al., 2021; Deitke et al., 2022) is a framework that supports visual object manipulation and procedural generation of environments. 2) **Tabletop environments**: Meta-World (Yu et al., 2019) and RLBench (James et al., 2019) are widely used simulator benchmarks studying robotics manipulation with tabletop settings. CausalWorld (Ahmed et al., 2021) is a benchmark for causal structure and transfer learning in manipulation, requiring long-horizon planning and precise low-level motor control. However, these simulators and benchmarks still lack task unification and do not support task prompts with multiple modalities.