Does Momentum Change the Implicit Regularization on Separable Data?

Abstract

The momentum acceleration technique is widely adopted in many optimization algorithms. However, there is no theoretical answer on how the momentum affects the generalization performance of the optimization algorithms. This paper studies this problem by analyzing the implicit regularization of momentum-based optimization. We prove that on the linear classification problem with separable data and exponential-tailed loss, gradient descent with momentum (GDM) converges to the L_2 max-margin solution, which is the same as vanilla gradient descent. That means gradient descent with momentum acceleration still converges to a low-complexity model, which guarantees their generalization. We then analyze the stochastic and adaptive variants of GDM (i.e., SGDM and deterministic Adam) and show they also converge to the L_2 max-margin solution. Technically, to overcome the difficulty of the error accumulation in analyzing the momentum, we construct new potential functions to analyze the gap between the model parameter and the max-margin solution. Numerical experiments are conducted and support our theoretical results.

1 Introduction

It is widely believed that the optimizers have the implicit regularization in terms of selecting output parameters among all the minima on the landscape [22, 14, 39]. Parallel to the analysis of *coordinate descent* ([27, 35]), [29] shows that *gradient descent* would converge to the L^2 max-margin solution for the linear classification task with exponential-tailed loss, which mirrors its good generalization property in practice. Since then, many efforts have been taken on analyzing the implicit regularization of various local-search optimizers, including stochastic gradient descent [20], steepest descent [6], AdaGrad [25] and optimizers for homogeneous neural networks [18, 11, 37].

However, though the momentum acceleration technique is widely adopted in the optimization algorithms in both convex and non-convex learning tasks [32, 36, 33], the understanding of how the momentum would affect the generalization performance of the optimization algorithms is still unclear, as the historical gradients in the momentum may significantly change the searching direction of the optimization dynamics. A natural question is:

Can we theoretically analyze the implicit regularization of momentum-based optimizers?

In this paper, we take the first step to analyze the convergence of momentum-based optimizers and unveil their implicit regularization. Our study starts from the classification problem with the linear model and exponential-tailed loss using Gradient Descent with Momentum (GDM) optimizer. Then the variants of GDM such as Stochastic Gradient Descent with Momentum (SGDM) and deterministic Adam are also analyzed. We consider the optimizers with constant learning rate and constant momentum hyper-parameters, which are widely adopted in practice, e.g., the default

Table 1: The algorithms investigated in this paper (GDM and Adam) along with algorithms (GD) already investigated in the existing literature. We also compare the learning rates required to obtain the characterization of implicit regularization. As for stochastic Adam with $\beta_1 \neq 0$, we leave its implicit regularization as future work.

Method	With Random Sampling	Learning Rate	Corresponding Literature
GD	$\times$	Constant	[29]
	$\checkmark$	Constant	[20]
GDM	$\times$	Constant	This Work
	$\checkmark$	Constant	This Work
Adam	$\times$	Constant	This Work
	$\checkmark$	Decaying $\left(\frac{1}{\sqrt{t}}\right)$	$\beta_1 = 0$ in this Work

setting in popular machine learning frameworks [23] and in experiments [40]. Our main results are summarized in Theorem 1.

Theorem 1 (informal)**.** *With linearly separable dataset $\boldsymbol{S}$, linear model and exponential-tailed loss:*

- *For GDM with a constant learning rate, the parameter norm diverges to infinity, with its direction converging to the L^2 max-margin solution. The same conclusion holds for SGDM with a constant learning rate.*

- *For deterministic Adam with a constant learning rate and stochastic RMSProp (i.e., Adam without momentum) with a decaying learning rate, the same conclusion holds.*

Theorem 1 states that GDM and its variants converge to the L^2 max-margin solution, which is the same as their without-momentum versions, indicating that momentum does not affect the convergent direction. Therefore, the good generalization behavior of the output parameters of these optimizers is well validated as the margin of a classifier is positively correlated with its generalization error [13] and is supported by existing experimental observations (e.g., [29, 19, 37]).

Our contributions are significant in terms of the following aspects:

- We establish the implicit regularization of the momentum-based optimizers, an open problem since the initial work [29]. The momentum-based optimizers are widely used in practice, and our theoretical characterization deepens the understanding of their generalization property, which is important on its own.

- Technically, we design a two-stage framework to analyze the momentum-based optimizers, which generalizes the proof techniques in [29] and [20]. The first stage shows the convergence of the loss. New potential functions for SGDM and Adam are proposed and can be of independent interest for convergence analysis of momentum-based optimizers. The second stage shows the convergence of the parameter. We propose an easy-to-check condition of whether the difference between learned parameters and the scaled max-margin solution is bounded. This condition can be generalized to implicit regularization analyses of other momentum-based optimizers.

- We further verify our theory through numerical experiments.

Organization of This Paper. Section 2 collects further related works on the implicit regularization of the first order optimizers and the convergence of momentum-based optimizers. Section 3 shows basic settings and assumptions which will be used throughout this paper. Section 4 studies the implicit regularization of GDM, while Section 5 and Section 6 explore respectively the implicit regularization of SGDM and Adam. Discussions of these results are put in Section 7. Detailed proofs and experiments can be found in the appendix.

2 Further related works

Implicit Regularization of First-order Optimization Methods. [29] prove that gradient descent on linear classification problem with exponential-tailed loss converges to the direction of the max L^2 margin solution of the corresponding hard-margin Support Vector Machine. [20] extend the results in [29] to the stochastic case, proving that the convergent direction of SGD is the same as GD almost surely. [25] go beyond the vanilla gradient descent methods and consider the AdaGrad optimizer instead. They prove that the convergent direction of AdaGrad has a dependency on the optimizing trajectory, which varies according to the initialization. [12] propose a primal-dual analysis framework for the linear classification models and prove a faster convergent rate of the margin by increasing the learning rate according to the loss. Based on [12], [9] design another algorithm with an even faster convergent rate of margin by applying the Nesterov's Acceleration Method on the dual space. However, the corresponding form of the algorithm on the primal space is no longer a Nesterov's Acceleration Method nor GDM, which is significantly different from our settings.

On the other hand, another line of work is trying to extend the linear case result to deep neural networks. [10, 7] study the deep linear network and [29] study the two-layer neural network with ReLU activation. [18] propose a framework to analyze the asymptotic direction of GD on homogeneous neural networks, proving that given there exists a time the network achieves 100% training accuracy, GD will converge to some KKT point of the L^2 max-margin problem. [37] extend the framework of [18] to adaptive optimizers and prove RMSProp and Adam without momentum have the same convergent direction as GD, while AdaGrad does not. The results [18, 37] indicate that results in the linear model can be extended to deep homogeneous neural networks and suggest that the linear model is an appropriate starting point to study the implicit bias.

Except for the exponential-tailed loss, there are also works on the implicit bias with squared loss. Interesting readers can refer to [26, 16, 1] etc. for details.

Convergence of Momentum-Based Optimization Methods. For convex optimization problems, the convergence rate of Nesterov's Acceleration Method [21] has been proved in various approaches (e.g., [21, 30, 38]). In contrast, although GDM (Polyak's Heavy-Ball Method) was proposed in [24] before the Nesterov's Acceleration Method, the convergence of GDM on convex loss with Lipschitz gradient was not solved until [5] provides an ergodic convergent result for GDM, i.e., the convergent result for the running average of the iterates. [31] provide a non-ergodic analysis when the training loss is coercive (the training loss goes to infinity whenever parameter norm goes to infinity), convex, and globally smooth. However, all existing results cannot be directly applied to exponential-tailed loss, which is non-coercive.

There are also works on the convergence of SGDM under various settings. [41] prove SGDM converges to a bounded region assuming both bounded gradient norm and bounded gradient variance. The bounded gradient norm assumption is further removed by [42, 17]. Nevertheless, a converging-to-stationary-point analysis is required in the implicit regularization analysis. Thus their results can not be directly applied. [34] analyze a particular case when the momentum parameter increases over iterations, which, however, does not agree with the practice where the momentum parameter is fixed.

As for (stochastic) Adam, its convergence analysis is still an open problem, and the current analyses are restricted to specific settings (e.g., bounded gradient, dynamical momentum hyperparameters). We recommend interested readers to refer to [4, 3, 28, 8] for details.

3 Preliminaries

This paper focuses on the linear model with the exponential-tailed loss. We mainly investigate binary classification. However, the methodology can be easily extended to the multi-class classification problem (please refer to Appendix E.3 for details).

Problem setting. The dataset used for training is denoted as $\boldsymbol{S} = (\boldsymbol{x}_i, \boldsymbol{y}_i)_{i=1}^N$, where $\boldsymbol{x}_i \in \mathbb{R}^d$ is the i-th input feature, and $\boldsymbol{y}_i \in \mathbb{R}$ is the i-th label ($i = 1, 2, \cdots, N$). We will use the linear model to fit the label: for any feature $\boldsymbol{x} \in \mathbb{R}^d$ and parameter $\boldsymbol{w} \in \mathbb{R}^d$, the prediction is given by $\langle \boldsymbol{w}, \boldsymbol{x} \rangle$.

For binary classification, given any data $\boldsymbol{z}_i = (\boldsymbol{x}_i, \boldsymbol{y}_i) \in \boldsymbol{S}$, the individual loss for parameter $\boldsymbol{w}$ is given as $\ell(\boldsymbol{y}_i \langle \boldsymbol{w}, \boldsymbol{x}_i \rangle)$. As only $\boldsymbol{y}_i \boldsymbol{x}_i$ is used in the loss, we then ensemble the feature and label together and assume $\boldsymbol{y}_i = 1$ ($\forall i \in \{1, \cdots, N\}$) without the loss of generality. We then drop $\boldsymbol{y}_i$ for

brevity and redefine $\boldsymbol{S} = (\boldsymbol{x}_i)_{i=1}^N$. The spectral norm of the data matrix $(\boldsymbol{x}_1, \cdots, \boldsymbol{x}_N)$ is defined as σ_{max}. We use $\tilde{\ell}(\boldsymbol{w}, \boldsymbol{x}) \triangleq \ell(\langle \boldsymbol{w}, \boldsymbol{x} \rangle)$ for brevity.

The optimization target is defined as the averaged loss: $\mathcal{L}(\boldsymbol{w}) = \frac{\sum_{i=1}^N \tilde{\ell}(\boldsymbol{w}, \boldsymbol{x}_i)}{N}$.

Optimizer. Here we will introduce the update rules of GDM, SGDM and deterministic Adam. GDM's update rule is

$$\boldsymbol{m}(0) = \boldsymbol{0}, \boldsymbol{m}(t) = \beta \boldsymbol{m}(t-1) + (1-\beta)\nabla \mathcal{L}(\boldsymbol{w}(t)), \boldsymbol{w}(t+1) = \boldsymbol{w}(t) - \eta \boldsymbol{m}(t). \quad (1)$$

SGDM can be viewed as a stochastic version of GDM by randomly choosing a subset of the dataset to update. Specifically, SGDM changes the update of $\boldsymbol{m}(t)$ into

$$\boldsymbol{m}(t) = \beta \boldsymbol{m}(t-1) + (1-\beta)\nabla \mathcal{L}_{\boldsymbol{B}(t)}(\boldsymbol{w}(t)), \quad (2)$$

where $\boldsymbol{B}(t)$ is a subset of $\boldsymbol{S}$ with size b which can be sampled either with replacement (**abbreviated as "w/. r"**) or without replacement (i.e., with random shuffling, **abbreviated as "w/o. r"**), and $\mathcal{L}_{\boldsymbol{B}(t)}$ is defined as $\mathcal{L}_{\boldsymbol{B}(t)}(\boldsymbol{w}) = \frac{\sum_{\boldsymbol{x} \in \boldsymbol{B}(t)} \tilde{\ell}(\boldsymbol{w}, \boldsymbol{x})}{b}$. We also define $\mathcal{F}_t$ as the sub-sigma algebra over the mini-batch sampling, such that $\forall t \in \mathbb{N}$, $\boldsymbol{w}(t)$ is adapted with respect to the sigma algebra flow $\mathcal{F}_t$.

The Adam optimizer can be viewed as a variant of SGDM in which the preconditioner is adopted, whose form is characterized as follows:

$$\boldsymbol{m}(0) = \boldsymbol{0}, \boldsymbol{m}(t) = \beta_1 \boldsymbol{m}(t-1) + (1-\beta_1)\nabla \mathcal{L}_{\boldsymbol{B}(t)}(\boldsymbol{w}(t)),$$
$$\boldsymbol{\nu}(0) = 0, \boldsymbol{\nu}(t) = \beta_2 \boldsymbol{\nu}(t-1) + (1-\beta_2)\nabla \mathcal{L}(\boldsymbol{w}(t)) \odot \nabla \mathcal{L}(\boldsymbol{w}(t))$$
$$\hat{\boldsymbol{m}}(t) = \frac{1}{1-\beta_1^t}\boldsymbol{m}(t), \hat{\boldsymbol{\nu}}(t) = \frac{1}{1-\beta_2^t}\boldsymbol{\nu}(t),$$
$$(\textit{Update Rule}): \ \boldsymbol{w}(t) = \boldsymbol{w}(t-1) - \eta \frac{1}{\sqrt{\hat{\boldsymbol{\nu}}(t-1) + \varepsilon \mathbb{1}_d}} \odot \hat{\boldsymbol{m}}(t-1), \quad (3)$$

where $\frac{1}{\sqrt{\hat{\boldsymbol{\nu}}(t-1) + \varepsilon \mathbb{1}_d}}$ is called the preconditioner.

Assumptions: The analysis of this paper are based on three common assumptions in existing literature (first proposed by [29]). They are respectively on the separability of the dataset, the individual loss behavior at the tail, and the smoothness of the individual loss. We list them as follows:

Assumption 1 (Linearly Separable Dataset). *There exists one parameter $\boldsymbol{w} \in \mathbb{R}^d$, such that*

$$\langle \boldsymbol{w}, \boldsymbol{x}_i \rangle > 0, \ \forall i \in [N].$$

Assumption 2 (Exponential-tailed Loss). *The individual loss ℓ is exponential-tailed, i.e.,*

- *Differentiable and monotonically decreasing to zero, with its derivative converging to zero at positive infinity and to non-zero at negative infinity, i.e., $\lim_{x \to \infty} \ell(x) = \lim_{x \to \infty} \ell'(x) = 0$, $\overline{\lim}_{x \to -\infty} \ell'(x) < 0$, and $\ell'(x) < 0$, $\forall x \in \mathbb{R}$;*

- *Close to exponential loss when x is large enough, i.e., there exist positive constants $c, a, \mu_+, \mu_-, x_+,$ and x_-, such that,*

$$\forall x > x_+ : -\ell'(x) \le c(1 + e^{-\mu_+ x})e^{-ax}, \quad (4)$$
$$\forall x > x_- : -\ell'(x) \ge c(1 - e^{-\mu_- x})e^{-ax}. \quad (5)$$

Assumption 3 (Smooth Loss). *Either of the following assumptions holds regarding the case:*

(D): (Without Stochasticity) The individual loss ℓ is locally smooth, i.e., for any $s_0 \in \mathbb{R}$, there exists a positive real H_{s_0}, such that $\forall x, y \ge s_0$, $|\ell'(x) - \ell'(y)| \le H_{s_0}|x - y|$.

(S): (With Stochasticity) The individual loss ℓ is globally smooth, i.e., there exists a positive real H, such that $\forall x, y \in \mathbb{R}$, $|\ell'(x) - \ell'(y)| \le H|x - y|$.

We provide explanations of these three assumptions, respectively. Based on Assumption 1, we can formally define the margin and the maximum margin solution of an optimization problem:

Definition 1. *Let the margin $\hat{\gamma}(\boldsymbol{w})$ of parameter $\boldsymbol{w}$ defined as the lowest score of the prediction of $\boldsymbol{w}$ over the dataset $\boldsymbol{S}$, i.e., $\hat{\gamma}(\boldsymbol{w}) = \min_{\boldsymbol{x} \in \boldsymbol{S}} \langle \boldsymbol{w}, \boldsymbol{x} \rangle$. We then define the maximum margin solution $\hat{\boldsymbol{w}}$ and the L^2 max margin γ of the dataset S as follows:*

$$\hat{\boldsymbol{w}} \overset{\triangle}{=} \arg\min_{\hat{\gamma}(\boldsymbol{w}) \ge 1} \|\boldsymbol{w}\|^2, \ \gamma \overset{\triangle}{=} \frac{1}{\|\hat{\boldsymbol{w}}\|}$$

154 Since $\|\cdot\|^2$ is strongly convex and set $\{\boldsymbol{w} : \hat{\gamma}(\boldsymbol{w}) \geq 1\}$ is convex, $\hat{\boldsymbol{w}}$ is uniquely defined.

155 Assumption 2 constraints the loss to be exponential-tailed, which is satisfied by many popular choices
156 of ℓ, including the exponential loss ($\ell_{exp}(x) = e^{-x}$) and the logistic loss ($\ell_{log}(x) = \log(1 + e^{-x})$).
157 Also, as c and a can be respectively absorbed by resetting the learning rate and data as $\eta = c\eta$ and
158 $\boldsymbol{x}_i = a\boldsymbol{x}_i$, without loss of generality, **in this paper we only analyze the case that $c = a = 1$.**

159 The globally smooth assumption (Assumption 3. (S)) is strictly stronger than the locally smooth
160 assumption (Assumption 3. (D)). One can easily verify that both the exponential loss and the logistic
161 loss meet Assumption 3. (**D**), and the logistic loss also meets Assumption 3. (**S**).

4 The implicit regularization of GDM

163 In this section, we analyze the implicit regularization of GDM with a two-stage framework [1]. Later,
164 we will use this framework to investigate SGDM further and deterministic Adam. The formal
165 theorem of the implicit regularization of GDM is as follows:

166 **Theorem 2.** *Let Assumptions 1, 2, and 3. (**D**) hold. Let $\beta \in [0, 1)$ and $\eta < 2\frac{N}{\sigma_{max}^2 H_{\ell-1}(N\mathcal{L}(\boldsymbol{w}_1))}$ (ℓ^{-1}*
167 *is the inverse function of ℓ). Then, for almost every data set S, with arbitrary initialization point $\boldsymbol{w}(1)$,*
168 *GDM (Eq. equation 1) satisfies that $\boldsymbol{w}(t) - \ln(t)\hat{\boldsymbol{w}}$ is bounded as $t \to \infty$, and $\lim_{t\to\infty} \frac{\boldsymbol{w}(t)}{\|\boldsymbol{w}(t)\|} = \frac{\hat{\boldsymbol{w}}}{\|\hat{\boldsymbol{w}}\|}$.*

169 Theorem 2 shows that the implicit regularization of GDM agrees with GD in linear classification with
170 exponential-tailed loss (c.f. [29] for results on GD). This consistency can be verified by existing and
171 our experiments (c.f. Section 7 for detailed discussions).

172 **Remark 1** (On the hyperparameter setting). *Firstly, the learning rate upper bound*
173 $2\frac{N}{\sigma_{max}^2 H_{\ell-1}(N\mathcal{L}(\boldsymbol{w}_1))}$ *agrees with that of GD exactly [29], indicating our analysis is tight. Sec-*
174 *ondly, Theorem 2 adopts a constant momentum hyper-parameter, which agrees with the practical use*
175 *(e.g., β is fixed to be 0.9 [40]). Also, Theorem 2 puts no restriction on the range of β, which allows*
176 *wider choices of hyper-parameter tuning.*

177 We then present a proof sketch of Theorem 2, which is divided into two parts: we first prove that the
178 sum of squared gradients is bounded, which indicates both the loss and the norm of gradient converge
179 to 0 and the parameter diverges to infinity; these properties will then be applied to show the difference
180 between $\boldsymbol{w}(t)$ and $\ln(t)\hat{\boldsymbol{w}}$ is bounded, and therefore, the direction of $\hat{\boldsymbol{w}}$ dominates as $t \to \infty$.

181 **Stage I: Loss Dynamics.** The goal of this stage is to characterize the dynamics of the loss and prove
182 the convergence of GDM. The core of this stage is to select a proper potential function $\xi(t)$, which is
183 required to correlate with the training loss $\mathcal{L}$ and be non-increasing along the optimization trajectory.
184 For GD, since $\mathcal{L}$ is non-increasing with a properly chosen learning rate, we can pick $\xi(t) = \mathcal{L}(t)$.
185 However, as the update of GDM does not align with the direction of the negative gradient, training
186 loss $\mathcal{L}(t)$ in GDM is no longer monotonously decreasing, and the potential function requires special
187 construction. Inspired by [31], we choose the following $\xi(t)$:

188 **Lemma 1.** *Let all conditions in Theorem 2 hold. Define $\xi(t) \overset{\triangle}{=} \mathcal{L}(\boldsymbol{w}(t)) + \frac{1-\beta}{2\beta\eta}\|\boldsymbol{w}(t) - \boldsymbol{w}(t-1)\|^2$.*
189 *Define C_1 as a positive real with $C_1 \overset{\triangle}{=} \frac{\sigma_{max}^2 H_{\ell-1}(N\mathcal{L}(\boldsymbol{w}_1))}{2N}\eta$. We then have*

$$\xi(t) \geq \xi(t+1) + \frac{1 - C_1}{\eta}\|\boldsymbol{w}(t+1) - \boldsymbol{w}(t)\|^2. \tag{6}$$

190 **Remark 2.** *Although this potential function is obtained by [31] by directly examining Taylor's*
191 *expansion at $\boldsymbol{w}(t)$, the proof here is non-trivial as we only require the loss to be locally smooth*
192 *instead of globally smooth in [31]. We need to prove that the smoothness parameter along the*
193 *trajectory is upper bounded. We defer the detailed proof to Appendix B.1.1.*

194 By Lemma 1, we have that $\xi(t)$ is monotonously decreasing by gap $\frac{1-C_1}{\eta}\|\boldsymbol{w}(t+1) - \boldsymbol{w}(t)\|^2$.
195 As $\xi(1) = \mathcal{L}(\boldsymbol{w}(1))$ is a finite number, we have $\sum_{t=1}^{\infty}\|\boldsymbol{w}(t+1) - \boldsymbol{w}(t)\|^2 < \infty$. By that $(1 -$

---

[1] It should be noticed that the proof sketches in Sections 4, 5, and 6 only hold for almost every dataset (means except a zero-measure set in $\mathbb{R}^{d \times N}$), as we want the presentation more simple and straightforward. However, the proof can be extended to every dataset with a more careful analysis (please refer to Appendix E.1 for details).

$\beta)\eta\nabla\mathcal{L}(\boldsymbol{w}(t)) = (\boldsymbol{w}(t+1) - \boldsymbol{w}(t)) - \beta(\boldsymbol{w}(t) - \boldsymbol{w}(t-1))$, it immediately follows that $\sum_{t=1}^{\infty} \|\nabla\mathcal{L}(\boldsymbol{w}(t))\|^2 < \infty$.

Stage II. Parameter Dynamics. The goal of this stage is to characterize the dynamics of the parameter and show that GDM asymptotically converges (in direction) to the max-margin solution $\hat{\boldsymbol{w}}$. To see this, we define a residual term $\boldsymbol{r}(t) \triangleq \boldsymbol{w}(t) - \ln(t)\hat{\boldsymbol{w}} - \tilde{\boldsymbol{w}}$ with some constant vector $\tilde{\boldsymbol{w}}$ (specified in Appendix B.1.2). If we can show the norm of $\boldsymbol{r}(t)$ is bounded over the iterations, we complete the proof as $\ln(t)\hat{\boldsymbol{w}}$ will then dominates the dynamics of $\boldsymbol{w}(t)$.

For simplicity, we use the continuous dynamics approximation of GDM [31] to demonstrate why $\boldsymbol{r}(t)$ is bounded:

$$\frac{\beta}{1-\beta}\frac{\mathrm{d}^2\boldsymbol{w}(t)}{\mathrm{d}t^2} + \frac{\mathrm{d}\boldsymbol{w}(t)}{\mathrm{d}t} + \eta\nabla\mathcal{L}(\boldsymbol{w}(t)) = 0. \tag{7}$$

We start by directly examining the evolution of $\|\boldsymbol{r}(t)\|$, i.e.,

$$\frac{1}{2}\|\boldsymbol{r}(T)\|^2 - \frac{1}{2}\|\boldsymbol{r}(1)\|^2 = \int_1^T \frac{1}{2}\frac{\mathrm{d}\|\boldsymbol{r}(s)\|^2}{\mathrm{d}s}\mathrm{d}s$$
$$= \int_1^T \left\langle \boldsymbol{r}(s), -\eta\nabla\mathcal{L}(\boldsymbol{w}(s)) - \frac{1}{s}\hat{\boldsymbol{w}} \right\rangle \mathrm{d}s + \int_1^T \frac{\beta}{1-\beta}\left\langle \boldsymbol{r}(s), -\frac{\mathrm{d}^2\boldsymbol{w}(s)}{\mathrm{d}s^2} \right\rangle \mathrm{d}s,$$

which by integration by part leads to

$$\text{RHS} = \int_1^T \left\langle \boldsymbol{r}(s), -\eta\nabla\mathcal{L}(\boldsymbol{w}(s)) - \frac{1}{s}\hat{\boldsymbol{w}} \right\rangle \mathrm{d}s + \frac{\beta}{1-\beta}\left(\left\langle \boldsymbol{r}(T), -\frac{\mathrm{d}\boldsymbol{w}(T)}{\mathrm{d}t} \right\rangle - \left\langle \boldsymbol{r}(1), -\frac{\mathrm{d}\boldsymbol{w}(1)}{\mathrm{d}t} \right\rangle + \int_1^T \left\langle \frac{\mathrm{d}\boldsymbol{r}(s)}{\mathrm{d}s}, \frac{\mathrm{d}\boldsymbol{w}(s)}{\mathrm{d}s} \right\rangle \mathrm{d}s\right),$$

We then check the terms one by one:

- $\int_1^T \left\langle \boldsymbol{r}(s), -\eta\nabla\mathcal{L}(\boldsymbol{w}(s)) - \frac{1}{s}\hat{\boldsymbol{w}} \right\rangle \mathrm{d}s$: This term also occurs in the analysis of GD [29], and has been proved to be bounded;

- $\langle \boldsymbol{r}(T), -\frac{\mathrm{d}\boldsymbol{w}(T)}{\mathrm{d}t} \rangle$: as shown in Stage I, $\frac{\mathrm{d}\boldsymbol{w}(T)}{\mathrm{d}t} \to 0$ (i.e., $\boldsymbol{w}(T) - \boldsymbol{w}(T-1) \to 0$ in the discrete case) as $T \to \infty$. Thus, this term is $\boldsymbol{o}(\|\boldsymbol{r}(T)\|)$;

- $\int_1^T \left\langle \frac{\mathrm{d}\boldsymbol{r}(s)}{\mathrm{d}s}, \frac{\mathrm{d}\boldsymbol{w}(s)}{\mathrm{d}s} \right\rangle \mathrm{d}s$: finite due to $\frac{\mathrm{d}\boldsymbol{r}(s)}{\mathrm{d}s} = \frac{\mathrm{d}\boldsymbol{w}(s)}{\mathrm{d}s} - \frac{1}{s}\hat{\boldsymbol{w}}$ and $\int_1^\infty \|\frac{\mathrm{d}\boldsymbol{w}(s)}{\mathrm{d}s}\|^2\mathrm{d}s$ is finite (i.e., $\sum_{t=1}^\infty \|\boldsymbol{w}(t+1) - \boldsymbol{w}(t)\|^2 < \infty$ in the discrete case) by Stage I.

Putting them together, we show that $\|\boldsymbol{r}(T)\|^2 + \boldsymbol{o}(\|\boldsymbol{r}(T)\|)$ is upper bounded over the iterations, which immediately leads to that $\|\boldsymbol{r}(T)\|$ is bounded. Applying similar methodology to the discrete update rule, we have the following lemma (the proof can be found in Appendix B.1.2).

Lemma 2. *Define potential function* $g : \mathbb{Z}^+ \to \mathbb{R}$ *as*

$$g(t) \triangleq \frac{1}{2}\|\boldsymbol{r}(t)\|^2 + \frac{\beta}{1-\beta}\langle \boldsymbol{r}(t), \boldsymbol{w}(t) - \boldsymbol{w}(t-1)\rangle.$$

$g(t)$ *is upper bounded, which further indicates* $\|\boldsymbol{r}(t)\|$ *is upper bounded.*

Remark 3. *Our technique for analyzing GDM here is essentially more complex and elaborate than that for GD in [29] due to the historical information of gradients GDM. The approach in [29] cannot be directly applied. It is worth mentioning that we provide a more easy-to-check condition for whether $\boldsymbol{r}(t)$ is bounded, i.e., "is $g(t)$ upper-bounded?". This condition can be generalized for other momentum-based implicit regularization analyses. E.g., SGDM and Adam later in this paper.*

5 Tackle the difficulty brought by random sampling

In this section, we analyze the implicit regularization of SGDM. Parallel to GDM, we establish the following implicit regularization result for SGDM:

Theorem 3. *Let Assumption 1, 2, and 3. (S) hold. Let $\beta \in [0,1)$ and $\eta < \frac{1}{\frac{H\beta\sigma_{max}^3}{\sqrt{N}b\gamma(1-\beta)} + \frac{H\sigma_{max}^4}{2b\gamma^2}}$. Then, with arbitrary initialization point $\boldsymbol{w}(1)$, SGDM (w/. r) satisfies $\boldsymbol{w}(t) - \ln(t)\hat{\boldsymbol{w}}$ is bounded as $t \to \infty$ and $\lim_{t\to\infty} \frac{\boldsymbol{w}(t)}{\|\boldsymbol{w}(t)\|} = \frac{\hat{\boldsymbol{w}}}{\|\hat{\boldsymbol{w}}\|}$, almost surely (a.s.).*

Similar to the GDM case, Theorem 3 shows that the implicit regularization of SGDM under this setting is consistent with SGD (c.f. [20] for the implicit regularization of SGD). This matches the observations in practice (c.f. Section 7 for details), and is later supported by our experiments (e.g., Figure 1). We add two remarks on the learning rate upper bound and extension to SGDM (w/. r).

Remark 4 (On the learning rate). *Firstly, our learning rate upper bound $\frac{1}{\frac{H\beta\sigma_{max}^3}{\sqrt{Nb}\gamma(1-\beta)} + \frac{H\sigma_{max}^4}{2b\gamma^2}}$ exactly matches that of SGD $2\frac{b\gamma^2}{H\sigma_{max}^4}$ [20] when $\beta = 0$, and matches that of SGD in terms of the order of σ_{max}, H, and b when $\beta \neq 0$. This indicates our analysis is tight. Secondly, as the bound is monotonously increasing with respect to batch size b, Theorem 3 also sheds light on the learning rate tuning, i.e., the larger the batch size is, the larger the learning rate is.*

Remark 5. *(On SGDM (w/o. r)) Theorem 3 can be similarly extended to SGDM (w/o. r). We defer the detailed description of the corresponding theorem together with the proof to Appendix E.2.*

Next, we show the proof sketch for Theorem 3. The proof also contains two stages, where Stage II is similar to that for GDM. However, we highlight that **Stage I for SGDM is not a trivial extension of that for GDM and has its merit for other optimization analyses for SGDM**. Specifically, the methodology used to construct GDM's potential function fails for SGDM due to the random sampling. We defer a detailed discussion to Appendix B.2.3. We then need to find a proper potential function for SGDM. Inspired by SGD's simple update rule, we rearrange the update rule of SGDM such that only the gradient information of the current step is contained, i.e.,

$$\frac{\boldsymbol{w}(t+1) - \beta\boldsymbol{w}(t)}{1-\beta} = \frac{\boldsymbol{w}(t) - \beta\boldsymbol{w}(t-1)}{1-\beta} - \eta\nabla\mathcal{L}_{\boldsymbol{B}(t)}(\boldsymbol{w}(t)).$$

By defining $\boldsymbol{u}(t) \triangleq \frac{\boldsymbol{w}(t) - \beta\boldsymbol{w}(t-1)}{1-\beta} = \boldsymbol{w}(t) + \frac{\beta}{1-\beta}(\boldsymbol{w}(t) - \boldsymbol{w}(t-1))$, we have that $\boldsymbol{u}(t)$ is close to $\boldsymbol{w}(t)$ (differs by order of one-step update $\boldsymbol{w}(t) - \boldsymbol{w}(t-1)$), and the update rule of $\boldsymbol{u}(t)$ only contains the current-step-gradient information $\nabla\mathcal{L}(\boldsymbol{w}(t))$. We then select potential function as $\mathcal{L}(\boldsymbol{u}(t))$, and a simple Taylor's expansion directly leads to:

$$\mathbb{E}[\mathcal{L}(\boldsymbol{u}(t+1))|\mathcal{F}_t] \approx \mathcal{L}(\boldsymbol{u}(t)) - \eta\langle\nabla\mathcal{L}(\boldsymbol{w}(t)), \nabla\mathcal{L}(\boldsymbol{u}(t))\rangle \approx \mathcal{L}(\boldsymbol{u}(t)) - \eta\|\nabla\mathcal{L}(\boldsymbol{w}(t))\|^2,$$

i.e., $\mathcal{L}(\boldsymbol{u}(t))$ is a proper potential function. We formalize the above discussion into the following lemma.

Lemma 3. *Let all conditions in Theorem 3 hold. Then, there exists a positive constant C_2, such that*

$$\mathbb{E}[\mathcal{L}(\boldsymbol{u}(t+1))] \leq \mathcal{L}(\boldsymbol{u}(1)) - \sum_{s=1}^{t} C_2\eta\mathbb{E}\|\nabla\mathcal{L}(\boldsymbol{w}(s))\|^2.$$

By letting $T \to \infty$ in the second claim of Lemma 3, we have $\sum_{s=1}^{\infty}\mathbb{E}\|\nabla\mathcal{L}(\boldsymbol{w}(s))\|^2 < \infty$, which is indeed what we need in Stage I.

6 Analyze the effect of preconditioners

6.1 Implicit regularization of deterministic Adam

This section presents the implicit regularization of deterministic Adam, i.e., Adam without random sampling.

Theorem 4. *Let Assumption 1, 2, and 3. (**D**) hold. Let $1 > \beta_2 > \beta_1^4 \geq 0$, and the learning rate η is a small enough constant (The upper bound of learning rate is complex, and we defer it to Appendix C.1). Then, with arbitrary initialization point $\boldsymbol{w}(1)$, deterministic Adam (Eq. 3) satisfies that $\boldsymbol{w}(t) - \ln(t)\hat{\boldsymbol{w}}$ is bounded as $t \to \infty$, and $\lim_{t\to\infty}\frac{\boldsymbol{w}(t)}{\|\boldsymbol{w}(t)\|} = \frac{\hat{\boldsymbol{w}}}{\|\hat{\boldsymbol{w}}\|}$.*

Remark 6 (On the β_1 and β_2 range). *Almost all existing literature assume a time-decaying hyper-parameter choice of β_1 or β_2 (c.f., [15, 2]). On the other hand, our result proves that deterministic Adam converges with constant settings of β_1 and β_2, which agrees with the practical use.*

Remark 7 ((Discussion on the results in [29])). *[29] observe that, on a synthetic dataset, the direction of the output parameter by Adam still does not converge to the max-margin direction after 2×10^6 iterations (but is getting closer). At the same time, GD seems to converge to the max-margin direction. This seems to contradict with Theorem 4. We reconduct the experiments (please refer to Appendix*

F.1.2 for details) and found (1). such a phenomenon occurs because a large learning rate is selected,
using which GD will also stick in a direction close to the max-margin direction (but not equal); (2).
the constructed synthetic dataset is ill-posed, as the non-support data is larger than the support data
by order of magnitude (which is also rare in practice). On a well-posed dataset, we observe that both
Adam and GD will converge to the max-margin solution rapidly (Figure 1).

We simply introduce the proof idea here and put the full proof in Appendix C. The proof of determin-
istic Adam is very similar to that of GDM with minor changes in potential functions. Specifically,
$\xi(t)$ in Lemma 1 is changed to

$$\xi(t) \triangleq \mathcal{L}(\boldsymbol{w}(t)) + \frac{1}{2} \frac{1 - \beta_1^{t-1}}{\eta(1 - \beta_1)} \left\| \sqrt[4]{\varepsilon \mathbb{1}_d + \hat{\boldsymbol{\nu}}(t-1)} \odot (\boldsymbol{w}(t) - \boldsymbol{w}(t-1)) \right\|^2,$$

and $g(t)$ in Lemma 2 is changed to

$$g(t) \triangleq \left\langle \boldsymbol{r}(t), (1 - \beta_1^{t-1})\sqrt{\varepsilon \mathbb{1}_d + \hat{\boldsymbol{\nu}}(t-1)} \odot (\boldsymbol{w}(t) - \boldsymbol{w}(t-1)) \right\rangle \frac{\beta_1}{1 - \beta_1} + \frac{\sqrt{\varepsilon}}{2} \|\boldsymbol{r}(t)\|^2.$$

The rest of the proof then flows similarly to the GDM case.

6.2 What if random sampling is added?

We have obtained the implicit regularization for GDM, SGDM, and deterministic Adam. One may
wonder whether the implicit regularization of stochastic Adam can be obtained. Unfortunately, the
gap can not be closed yet. This is because an implicit regularization analysis requires the knowledge
of the loss dynamics, little of which, however, has been ever known even for stochastic RMSProp
(i.e., Adam with $\beta_1 = 0$ in Eq. (3)) with constant learning rates. Specifically, the main difficulty lies
in bounding the change of conditioner $\frac{1}{\sqrt{\varepsilon \mathbb{1}_d + \hat{\boldsymbol{\nu}}(t)}}$ across iterations, which is required to make the
drift term $\langle \nabla \mathcal{L}(\boldsymbol{w}(t)), \mathbb{E}(\boldsymbol{w}(t+1) - \boldsymbol{w}(t)) \rangle$ (derived by Taylor's expansion of the epoch start from
Kt) negative to ensure a non-increasing loss.

On the other hand, if we adopt decaying learning rates $\eta_t = \frac{1}{\sqrt{t}}$, [28] shows β_2 close enough to 1, the
following equation holds for stochastic RMSProp (w/o. r) (recall that $K \triangleq \frac{N}{b}$ is the epoch size)

$$\sum_{t=0}^{T} \frac{1}{\sqrt{t+1}} \|\nabla \mathcal{L}(\boldsymbol{w}(Kt))\| = \mathcal{O}(\ln T). \tag{8}$$

Based on this result, we have the following theorem for stochastic RMSProp (w/o. r):

Theorem 5. *Let Assumptions 1, 2, and 3. (S) hold. Let β_2 be close enough to 1. Then, with arbitrary
initialization point $\boldsymbol{w}(1)$, stochastic RMSProp (w/o. r) converges to the L^2 max-margin solution.*

Remark 8 (On the decaying learning rate)**.** *The decaying learning rate is a "stronger" setting
compared to the constant learning rate, both in the sense that GDM, SGDM, and deterministic Adam
can be shown to converge to the max-margin solution following the same routine as Theorems 2, 3,
and 4, and in the sense that we usually adopt constant learning rate in practice.*

The proof is on the grounds of a novel characterization of the loss convergence rate derived from Eq.
(8), and readers can find the details in Appendix D. Furthermore, the proof can be easily extended to
the Stochastic Adaptive Heavy Ball (SAHB) algorithm (proposed by [34]), which can be viewed as a
momentum version of RMSProp (but different from Adam) with the following update rule

$$\boldsymbol{w}(t+1) = \boldsymbol{w}(t) - \boldsymbol{m}(t), \boldsymbol{m}(t) = \eta_t(1 - \beta_1)\frac{\nabla \mathcal{L}_{\boldsymbol{B}(t)}(\boldsymbol{w}(t))}{\sqrt{\varepsilon \mathbb{1}_d + \hat{\boldsymbol{\nu}}(t)}} + \beta_1(\boldsymbol{w}(t) - \boldsymbol{w}(t-1)).$$

The proof of Theorem 5 can be easily extended to SAHB, based on the fact that $\boldsymbol{u}(t) = \frac{\boldsymbol{w}(t) - \beta_1 \boldsymbol{w}(t-1)}{1 - \beta_1}$
has a simple update, i.e.,

$$\boldsymbol{u}(t+1) = -\eta \frac{\nabla \mathcal{L}_{\boldsymbol{B}(t)}(\boldsymbol{w}(t))}{\sqrt{\varepsilon \mathbb{1}_d + \hat{\boldsymbol{\nu}}(t)}} + \boldsymbol{u}(t).$$

and $\mathcal{L}(\boldsymbol{u}(t))$ can be used as a potential function just as the SGDM case.

(a) Training Accuracy

(b) Angle gap between the parameter direction and the max margin solution

Figure 1: Comparison of the implicit regularization of (S)GD, (S)GDM, deterministic Adam and stochastic RMSProp. We use the synthetic dataset in [29] with learning rate 0.1. Figure (b) shows (1). all the optimizers converge to the max margin solution, and (2). the asymptotic behaviors with & without momentum are similar. The experimental observation support our theoretical results.

7 Discussions

Consistency with the Experimental Results. We conduct experiments to verify our theoretical findings. Specifically, we (1). run GD, GDM, SGD, SGDM, and Adam on a synthetic dataset to observe their implicit regularization; (2). run GD and Adam on ill-posed dataset proposed in [29] to verify Theorem 4; (3). run SGD and SGDM on neural networks to classify the MNIST dataset and compare their implicit regularization. The experimental observations stand with our theoretical results. Furthermore, it is worth mentioning that experimental phenomenons that adding momentum will not change the implicit regularization have also been observed by existing literature [29, 19, 37].

Influence of hyperparameters on convergence rates. Our results can be further extended to provide a precise characterization of the influence of the hyperparameters η and β on the convergence rate of (S)GDM. Specifically, in Appendix E.4, we show that the asymptotic convergence rate of (S)GDM is $C\frac{1}{\eta}\frac{1}{t}$, where C is some constant independent of β and η. Therefore, increase η can lead to a faster convergence rate (with learning rate requirements in Theorems 2 and 3 satisfied). However, changing β does not affect the convergence rate, which is also observed in our experiments (e.g., Figure 1). While this seems weird, as replacing gradient with momentum in deep learning often accelerates the training, we hypothesize that such an acceleration appears as the landscape of neural networks is highly non-convex and thus can not be observed in the case considered by this paper.

Gap Between The Linear Model and Deep Neural Networks. While our results only hold for the linear classification problem, extending the results to the deep neural networks is possible. Specifically, existing literature [18, 37] provide a framework for deriving implicit regularization for deep homogeneous neural networks. However, the approach in [18, 37] can not be trivially applied to the momentum-based optimizers, as their proofs require the specific gradient-based updates to lower bound a smoothed margin (c.f., Theorem 4.1, [18]). It remains an exciting work to see how our results can be expanded to GDM and Adam for deep neural networks.

8 Conclusion

This paper studies the implicit regularization of momentum-based optimizers in linear classification with exponential-tailed loss. Our results indicate that for SGD and the deterministic version of Adam, adding momentum will not influence the implicit regularization, and the direction of the parameter converges to the L^2 max-margin solution. Our theoretical results stand with existing experimental observations, and developed techniques such as the potential functions may inspire the analyses on other momentum-based optimizers. Motivated by the results and techniques for linear cases in this paper, it has the potential to extend them to the homogeneous neural network in the future. Another topic left for future work is to derive the implicit regularization of constant learning rate stochastic Adam. As discussed in Section 6.2, this topic is non-trivial, and it requires new techniques and assumptions to be developed.

References

[1] A. Ali, E. Dobriban, and R. Tibshirani. The implicit regularization of stochastic gradient flow for least squares. In *International Conference on Machine Learning*, pages 233–244. PMLR, 2020.

[2] X. Chen, S. Liu, R. Sun, and M. Hong. On the convergence of a class of adam-type algorithms for non-convex optimization. In *International Conference on Learning Representations*, 2018.

[3] S. De, A. Mukherjee, and E. Ullah. Convergence guarantees for rmsprop and adam in non-convex optimization and an empirical comparison to nesterov acceleration. *arXiv preprint arXiv:1807.06766*, 2018.

[4] A. Défossez, L. Bottou, F. Bach, and N. Usunier. A simple convergence proof of adam and adagrad. *arXiv preprint arXiv:2003.02395*, 2020.

[5] E. Ghadimi, H. R. Feyzmahdavian, and M. Johansson. Global convergence of the heavy-ball method for convex optimization. In *2015 European control conference (ECC)*, pages 310–315. IEEE, 2015.

[6] S. Gunasekar, J. Lee, D. Soudry, and N. Srebro. Characterizing implicit bias in terms of optimization geometry. In *International Conference on Machine Learning*, pages 1832–1841. PMLR, 2018.

[7] S. Gunasekar, J. D. Lee, D. Soudry, and N. Srebro. Implicit bias of gradient descent on linear convolutional networks. In *Advances in Neural Information Processing Systems*, pages 9461–9471, 2018.

[8] Z. Guo, Y. Xu, W. Yin, R. Jin, and T. Yang. A novel convergence analysis for algorithms of the adam family. *arXiv preprint arXiv:2112.03459*, 2021.

[9] Z. Ji, N. Srebro, and M. Telgarsky. Fast margin maximization via dual acceleration. In *International Conference on Machine Learning*, pages 4860–4869. PMLR, 2021.

[10] Z. Ji and M. Telgarsky. Gradient descent aligns the layers of deep linear networks. *arXiv preprint arXiv:1810.02032*, 2018.

[11] Z. Ji and M. Telgarsky. Directional convergence and alignment in deep learning. *arXiv preprint arXiv:2006.06657*, 2020.

[12] Z. Ji and M. Telgarsky. Characterizing the implicit bias via a primal-dual analysis. In *Algorithmic Learning Theory*, pages 772–804. PMLR, 2021.

[13] Y. Jiang, B. Neyshabur, H. Mobahi, D. Krishnan, and S. Bengio. Fantastic generalization measures and where to find them. *arXiv preprint arXiv:1912.02178*, 2019.

[14] N. S. Keskar, D. Mudigere, J. Nocedal, M. Smelyanskiy, and P. T. P. Tang. On large-batch training for deep learning: Generalization gap and sharp minima. In *International Conference on Learning Representations*, 2017.

[15] D. P. Kingma and J. Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

[16] J. Lin and L. Rosasco. Optimal rates for multi-pass stochastic gradient methods. *The Journal of Machine Learning Research*, 18(1):3375–3421, 2017.

[17] Y. Liu, Y. Gao, and W. Yin. An improved analysis of stochastic gradient descent with momentum. *Advances in Neural Information Processing Systems*, 33, 2020.

[18] K. Lyu and J. Li. Gradient descent maximizes the margin of homogeneous neural networks. *arXiv preprint arXiv:1906.05890*, 2019.

[19] M. S. Nacson, J. Lee, S. Gunasekar, P. H. P. Savarese, N. Srebro, and D. Soudry. Convergence of gradient descent on separable data. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pages 3420–3428. PMLR, 2019.

[20] M. S. Nacson, N. Srebro, and D. Soudry. Stochastic gradient descent on separable data: Exact convergence with a fixed learning rate. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pages 3051–3059. PMLR, 2019.

[21] Y. Nesterov. A method for solving a convex programming problem with convergence rate o (1/k2). In *Soviet Mathematics. Doklady*, volume 27, pages 367–372, 1983.

[22] B. Neyshabur, R. Tomioka, and N. Srebro. In search of the real inductive bias: On the role of implicit regularization in deep learning. In *ICLR*, 2015.

[23] A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimelshein, L. Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32:8026–8037, 2019.

[24] B. T. Polyak. Some methods of speeding up the convergence of iteration methods. *Ussr computational mathematics and mathematical physics*, 4(5):1–17, 1964.

[25] Q. Qian and X. Qian. The implicit bias of adagrad on separable data. In *Advances in Neural Information Processing Systems*, pages 7761–7769, 2019.

[26] L. Rosasco and S. Villa. Learning with incremental iterative regularization. In *Proceedings of the 28th International Conference on Neural Information Processing Systems-Volume 1*, pages 1630–1638, 2015.

[27] R. E. Schapire and Y. Freund. Boosting: Foundations and algorithms. *Kybernetes*, 2013.

[28] N. Shi, D. Li, M. Hong, and R. Sun. Rmsprop converges with proper hyper-parameter. In *International Conference on Learning Representations*, 2021.

[29] D. Soudry, E. Hoffer, M. S. Nacson, S. Gunasekar, and N. Srebro. The implicit bias of gradient descent on separable data. *The Journal of Machine Learning Research*, 19(1):2822–2878, 2018.

[30] W. Su, S. Boyd, and E. Candes. A differential equation for modeling nesterov's accelerated gradient method: theory and insights. *Advances in neural information processing systems*, 27, 2014.

[31] T. Sun, P. Yin, D. Li, C. Huang, L. Guan, and H. Jiang. Non-ergodic convergence analysis of heavy-ball algorithms. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 5033–5040, 2019.

[32] I. Sutskever, J. Martens, G. Dahl, and G. Hinton. On the importance of initialization and momentum in deep learning. In *International conference on machine learning*, pages 1139–1147. PMLR, 2013.

[33] M. Tan and Q. Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *International Conference on Machine Learning*, pages 6105–6114. PMLR, 2019.

[34] W. Tao, S. Long, G. Wu, and Q. Tao. The role of momentum parameters in the optimal convergence of adaptive polyak's heavy-ball methods. *arXiv preprint arXiv:2102.07314*, 2021.

[35] M. Telgarsky. Margins, shrinkage, and boosting. In *International Conference on Machine Learning*, pages 307–315. PMLR, 2013.

[36] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pages 5998–6008, 2017.

[37] B. Wang, Q. Meng, W. Chen, and T.-Y. Liu. The implicit bias for adaptive optimization algorithms on homogeneous neural networks. In *International Conference on Machine Learning*, pages 10849–10858. PMLR, 2021.

[38] A. C. Wilson, B. Recht, and M. I. Jordan. A lyapunov analysis of accelerated methods in optimization. *Journal of Machine Learning Research*, 22(113):1–34, 2021.

[39] A. C. Wilson, R. Roelofs, M. Stern, N. Srebro, and B. Recht. The marginal value of adaptive gradient methods in machine learning. In *Advances in neural information processing systems*, pages 4148–4158, 2017.

[40] S. Xie, R. Girshick, P. Dollár, Z. Tu, and K. He. Aggregated residual transformations for deep neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1492–1500, 2017.

[41] Y. Yan, T. Yang, Z. Li, Q. Lin, and Y. Yang. A unified analysis of stochastic momentum methods for deep learning. In *IJCAI International Joint Conference on Artificial Intelligence*, 2018.

[42] H. Yu, R. Jin, and S. Yang. On the linear speedup analysis of communication efficient momentum sgd for distributed non-convex optimization. In *International Conference on Machine Learning*, pages 7184–7193. PMLR, 2019.