Marksman Backdoor: Backdoor Attacks with Arbitrary Target Class

Abstract

In recent years, machine learning models have been shown to be vulnerable to backdoor attacks. Under such attacks, an adversary embeds a stealthy backdoor into the trained model such that the compromised models will behave normally on clean inputs but will misclassify according to the adversary's control on maliciously constructed input with a trigger. While these existing attacks are very effective, the adversary's capability is limited: given an input, these attacks can only cause the model to misclassify toward a single pre-defined or target class. In contrast, this paper exploits a novel backdoor attack with a much more powerful payload, denoted as Marksman, where the adversary can arbitrarily choose which target class the model will misclassify given any input during inference. To achieve this goal, we propose to represent the trigger function as a class-conditional generative model and to inject the backdoor in a constrained optimization framework, where the trigger function learns to generate an optimal trigger pattern to attack any target class at will while simultaneously embedding this generative backdoor into the trained model. Given the learned trigger-generation function, during inference, the adversary can specify an arbitrary backdoor attack target class, and an appropriate trigger causing the model to classify toward this target class is created accordingly. We show empirically that the proposed framework achieves high attack performance (e.g., 100% attack success rates in several experiments) while preserving the clean-data performance in several benchmark datasets, including MNIST, CIFAR10, GTSRB, and TinyImageNet. The proposed Marksman backdoor attack can also easily bypass existing backdoor defenses that were originally designed against backdoor attacks with a single target class. Our work takes another significant step toward understanding the extensive risks of backdoor attacks in practice.

1 Introduction

Machine learning, especially deep neural networks (DNN), rapidly advances and transforms our daily lives in various fields and applications. Such intelligence is becoming prevalent and pervasive, embedded ubiquitously from centralized servers to fully distributed Internet-of-Things (IoT). Unfortunately, since well-trained models now are viewed as high-value assets that demand extensive computer resources, annotated data, and machine learning expertise, they are becoming increasingly attractive targets for cyberattacks. Prior research has shown deep learning algorithms are vulnerable to a wide range of attacks, including adversarial examples [3, 25], poisoning attacks [27, 32, 15], backdoor attacks [24, 22, 13], and privacy leakages [33, 12]. Among these, backdoor attacks expose the vulnerability in the model building supply chain that seeks to inject a stealthy backdoor into a model through poisoning the data or manipulating the training process [24, 22, 13]. Ideally, the model with injected backdoor should behave normally with clean inputs, but whenever with the presence of the trigger, the input will be misclassified into the target class.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Figure 1: The payloads of Marksman and the existing backdoor attacks (top row). Marksman can attack an arbitrary target at will by generating the suitable trigger pattern via the class-conditional generative trigger function to cause the classifier to predict the chosen target (details in bottom row).

Past years have seen the development of backdoor attacks in various trigger forms, such as the patch-based in BadNets [13] and TrojanNN [22], blended and dynamic triggers [7, 31], and recently input-aware, invisible triggers [8, 28, 9, 29]. In the fields of malware backdoor [4] and hardware Trojan [35, 39], these attacks are typically decomposed into two main components: the **trigger** that determines the activation mechanism and the **payload** that is used to control the modified malicious behavior. However, compared to the trigger mechanism, the payload of backdoor attacks on DNN is much less studied. The majority of the existing approaches consider either 1) all-to-one attacks where all the inputs with the trigger are mapped into one specific target class or 2) all-to-all attacks where the inputs from each true class will have different target labels [13]. As opposed to what the name of the all-to-all attacks indicates, such an attack is still only able to manipulate the inputs within one true class label into one target class. Nevertheless, these prior works are single-trigger and single-payload backdoor attacks with predefined target backdoor class(es). Even for the input-aware ones that generate the trigger based on the content of the input image to minimize the perceptual distinction, the target backdoor class is still predefined.

In this paper, we exploit the design of a backdoor attack with arbitrary target classes after injecting the backdoor into the model. Since we need to expand the payload capability of the backdoor attack, efficiently and effectively implementing such backdoor attacks is not trivial. One may argue that an adversary can repeatedly inject different trigger patterns for all the target classes to achieve such an adversarial objective. For instance, the adversary can use a specific trigger pattern for each target class and inject all the classes' trigger patterns into the model by using the patch-based backdoor strategy. Obviously, this method will lead to a much larger model perturbation than the single-trigger and single-payload attack. As the number of target classes increases, both the attack success rate (ASR) and the clean data accuracy will be significantly degraded.

To tackle these challenges, we follow the similar concept of invisible and input-aware backdoor attacks [8, 28, 9] that train a generative model during the backdoor injection, usually called trigger generator or trigger function, for generating triggers. In order to activate the backdoor, the adversary will feed the input image to the trigger generator/function, which will embed an input-specific trigger into the image. In these scenarios, the secret held by the adversary is the trigger function instead of fixed pixel patterns as in patch-based backdoor attacks. We efficiently incorporate the malicious functionalities that link to all the output classes into the trigger function to expand the payload. Consequently, as depicted in Figure 1, the adversary can arbitrarily choose the target class to misclassify given any input during inference, significantly enhancing the adversarial capability of the backdoor attack. The only works that we are aware of consider varying the payload are [40, 41], which yield different target classes by controlling the intensities of the same backdoor [40] and embedding multiple triggers into different channels (i.e., RGB channels) of an image [41], respectively. However, the possible numbers of target classes in these works are limited by 4 and 3, bounded by the performance and the number of channels (i.e., 3 in RGB images). The work of DeepPayload [19]

attempts to directly inject the malicious logic through reverse-engineering instead of training the backdoor into the model, which does not consider varying the target backdoor class as in this paper.

Our contributions are summarized below:

- We propose a new type of backdoor attack where the adversary can flexibly attack any target label during inference. This attack maliciously modifies the model by establishing a causal link between the trigger function and all output classes.

- We propose a class-condition generative trigger function that, given the target label, can generate an imperceptible trigger pattern to cause the model to predict the target label. We then propose a constrained optimization objective that can effectively and efficiently learn the trigger function and poison the model.

- Finally, we empirically demonstrate the effectiveness of the proposed method and its robustness against several representative defensive mechanisms. We show that the proposed method can achieve high attack success rates with any arbitrarily chosen target class while preserving the behavior of the model under normal conditions.

The rest of the paper is organized as follows. We review the background of DNN backdoor attacks in Section 2. The threat model is defined in Section 3. We present the details of the proposed methodology in Section 4, and evaluate the performance and compare to prior works in Section 5. Finally, Section 6 concludes this paper. We present more details about experimental settings and additional results in the supplementary material.

2 Background

2.1 Backdoor Attacks

Under image classification tasks, backdoor attacks on DNN seek to inject malicious behavior into the model that will associate a trigger to a target backdoor class [13, 22], which can also be interpreted as the payload as in malware backdoor and hardware Trojan. The injection of the backdoor are typically achieved by poisoning the training data [13, 22] or manipulating the training process or model parameters [16, 10]. An important performance requirement for the backdoor attack is its stealthiness, such that the existence of the backdoor in a model cannot be easily identified. Hence, backdoor attack should preserve the normal functionality or inference accuracy for clean images (i.e., images without the trigger).

The designs of the trigger have been extensively studied in the literature, from the early obvious patch-based triggers [7, 22] to more invisible ones with utilization of blended [7], sinusoidal strips (SIG) [2], reflection (ReFool) [23], single-pixel [1], warping (WaNet) [29], discrete cosine transform (DCT) steganography [41], and adversarial example generation [34, 17]. As opposed to a universal trigger, several recent works have investigated input-aware backdoor attacks that minimize the visibility of the trigger by generating the trigger pattern based on the content of each input image [8, 28, 9]. For instance, LIRA [9] trains a generative model as the trigger function for each image, while simultaneously injecting the backdoor into the model, which has shown to be able to generate completely invisible triggers.

All of these attacks, under either all-to-one or all-to-all scenarios, are only able to manipulate the prediction of a given input image to one target class. While the works in [40, 41] considered a less narrow form for the payload, the number of possible target backdoor classes is still limited, i.e., 3 or 4. In contrast, this paper exploits a much stronger attack that is able to misclassify a given input image to any arbitrary target class.

2.2 Backdoor Defenses

Meanwhile, various backdoor defensive solutions have also been developed, aimed at either detecting [5, 37, 11] or mitigating [20, 38, 6, 30, 18] the attacks. Popular methods include Neural Cleanse [38] that detects the backdoor by searching for possible trigger patches, fine-pruning [20] that prunes the model to erase the backdoor, spectral signature [37] that detects outliers based on the latent representations, and STRIP [11] that uses perturbations to detect potential backdoor triggers. Besides, input mitigation methods have also been studied, which seek to filter the images with triggers to avoid the activation of the backdoor [24, 18].

126 A successful backdoor attack has to be able to bypass the existing defenses. We evaluate our proposed
127 Marksman backdoor against representative defensive solutions in our experiments.

3 Threat Model

129 Consistent with prior works on input-aware backdoor attacks that train a generative model for trigger
130 generation [8, 28, 9], we also consider the threat model where the adversary has full access to the
131 model. During the training phase, the adversary attempts to inject the backdoor into a model. After
132 that, the model will be delivered to victim users, who might employ the existing backdoor defensive
133 measures to check the model. During the inference phase, the adversary is able to query the victim
134 model with any inputs.

4 Proposed Methodology: Marksman Backdoor

4.1 Preliminaries

137 Consider the supervised learning setting where the goal is to learn a classifier $f_\theta : \mathcal{X} \to \mathcal{Y}$ that maps
138 an input $x \in \mathcal{X}$ to a label $y \in \mathcal{Y}$. In empirical risk minimization (ERM), the parameters θ are learned
139 using a training dataset $\mathcal{S} = \{(x_1, y_1), ..., (x_N, y_N))\}$ where $x_i \in \mathcal{X}$ and $y_i \in \mathcal{Y}$.

140 In a standard backdoor attack, a subset of M ($M < N$) examples are first selected from $\mathcal{S}$ to create
141 the poisoned subset $\mathcal{S}_p$. Each sample (x, y) in this subset is transformed into a backdoor sample
142 $(T(x), \eta(y))$, where $T : \mathcal{X} \to \mathcal{X}$ is the trigger function and η is the target labeling function. The
143 trigger function T determines how a trigger pattern is placed on the input x to create the backdoor
144 input $T(x)$ while the target labeling function specifies how the classifier should predict in the presence
145 of the backdoor input. The remaining samples in $\mathcal{S}$ comprise the clean subset $\mathcal{S}_c$, i.e., $\mathcal{S}_c = \mathcal{S} \setminus \mathcal{S}_p$.

146 Under ERM, we can alter the behavior of the classifier f (i.e., inject the backdoor) by training f with
147 both the clean samples $\mathcal{S}_c$ and the backdoor samples $\mathcal{S}_p$, as follows:

$$\theta^* = \arg \min_\theta \sum_{(x,y) \in \mathcal{S}_c \cup \mathcal{S}_p} \mathcal{L}(f_\theta(x), y).$$

148 where $\mathcal{L}$ is the classification loss, e.g., cross-entropy loss. During inference, for a clean input x and
149 its true label y, the learned f will behave as follows:

$$f(x) = y, \quad f(T(x)) = \eta(y)$$

4.2 Marksman's Payload: Arbitrary Attack Target Class

151 The training process described in the previous section essentially induces the payload, or the causal
152 association between the trigger and the target label. As we discussed above, there are two common
153 types of the payload in the backdoor domain [13]: all-to-one and all-to-all. Under the all-to-one
154 attack, all input with the trigger are predicted with a constant label, denoted as $\hat{\mathbf{y}}$, regardless of the
155 original label y:

$$f(T(x)) = \hat{\mathbf{y}}, \quad \forall(x, y)$$

156 For the all-to-all attack, the input with the trigger is predicted with a label that depends on its true
157 label y; for example, a commonly studied target function is

$$f(T(x)) = (y + 1) \bmod |\mathcal{Y}|, \quad \forall(x, y)$$

158 Note that, for both the all-to-one and all-to-all attacks, the attacker can only trigger one predefined
159 target label. During inference, given an input, it is not possible to causally force f to predict an
160 arbitrary choice of a target label.

161 The goal of this work is to design a backdoor attack with a more flexible and powerful payload where
162 the attacker can arbitrarily choose any target label during inference. Formally, we aim to alter the
163 behavior of f so that:

$$f(x) = y, \quad f(T(c, x)) = c, \quad \forall c \in \mathcal{Y} \text{ and } \forall(x, y) \tag{1}$$

164 Under this setting of Equation (1), the trigger pattern, devised by the function T, is associated with
165 the attack target c. This represents a more flexible payload design and a stronger backdoor attack
166 because the adversary can freely choose to attack any target label during inference.

4.3 Learning the Marksman's Trigger Function

Modeling and eventually learning the trigger function to achieve the objective (i.e., injecting the backdoor into f) in Equation (1) face some crucial challenges. First, the design of the trigger function should be systematic. Each causal association between an image and a specific target label is embedded in one unique trigger pattern. Thus, a large number of trigger patterns is needed to capture the multi-trigger and multi-payload requirement. Second, the injection of these trigger patterns into the model should preserve the clean-data performance while achieving a high attack success rate. On top of these, we also observe empirically that the straightforward baseline approach, which repeatedly injects these trigger patterns using the existing backdoor-attack methods such as the patch-based attack [13], fails to achieve this adversarial objective: either the clean-data performance noticeably drops below an acceptable threshold or the attack success rate is not satisfactory.

To tackle these challenges, we first propose representing the process of creating the trigger pattern with a class-conditional generative model. The trigger function $T_\xi : \mathcal{Y} \times \mathcal{X} \to \mathcal{X}$ learns to generate a trigger pattern that is conditioned on the attack's target class and imperceptibly blended into the input image. The input to the generative model is a label c and an image x, and its output is a backdoor input $T(c, x)$ with a trigger pattern that can activate the backdoor to attack the target label c. Formally, we can model T using a class-conditional noise (or trigger pattern) generator g as follows:

$$T(c, x) = x + g(c, x), \quad ||g(c, x)||_\infty \leq \epsilon \tag{2}$$

where the ∞-norm constraint is used to ensure a small perturbation (within an L_∞-ball with radius ϵ) of the clean image for an optimal visual stealthiness. The proposed class-conditional generative trigger gives the adversary a flexible control for systematically creating the trigger for any target class, as illustrated in Figure 1.

Given the class-conditional generative trigger function $T(c, x)$, we need to learn its parameters ξ and to poison the classifier f. Recall that the objective is to preserve the clean-data performance while successfully performing the backdoor attack. Inspired by recent works in learning input-aware attacks [8, 28, 9], we propose to jointly learn $T(c, x)$ and poison f via the following constrained optimization objective:

$$\min_\theta \sum_{(x,y) \in \mathcal{S}_c} \mathcal{L}(f_\theta(x), y) + \alpha \sum_{\substack{(x,y) \in \mathcal{S}_p \\ c \neq y}} \mathcal{L}(f_\theta(T_{\xi^*(\theta)}(c, x)), c) \tag{3}$$

$$s.t. \quad \xi^* = \arg\min_\xi \sum_{(x,y) \in \mathcal{S}_p, c \neq y} \mathcal{L}(f_\theta(T_\xi(c, x)), c) - \beta||g(c, x)||_2$$

In this problem, an optimal generative trigger function T_{ξ^*} is associated with an optimally poisoned classifier. The poisoning process seeks the parameters θ of the classifier to minimize a linear combination of the clean accuracy and backdoor objectives. At the same time, the generative trigger function learns to optimally craft the backdoor images, conditioned on arbitrary target labels. To avoid trivial solutions (i.e., sparse and small trigger patterns), we also maximize the L_2-norm of the trigger pattern (the output of g) within the L_∞-ball. This allows the generated trigger patterns to stretch over the entire input image. The hyperparameter α balances the mixing weights of the clean and backdoor objectives in training f while the hyperparameter β controls the effect of the penalty on sparser and smaller trigger patterns.

4.4 Marksman's Optimization

To solve the non-convex, constrained optimization in Equation (3), we can alternately update

---

Algorithm 1 Marksman Optimization Algorithm

Input:
  (1) $S = \{(x_i, y_i), i = 1, ..., N\}$
  (2) training iterations K
  (3) iterations k to update T
  (4) learning rate γ_f and γ_T
  (5) batch size b, hyperparameters α and β

Output:
  learned parameters ξ for T and θ for f

1: Initialize θ and ξ, $\hat{\xi} \leftarrow \xi$, $j \leftarrow 0$
2: **repeat**
3:     Sample minibatch $\mathcal{S}_c = \{(x, y)\} \subset \mathcal{S}$
4:     Sample $S_p = \{(x, c) : c \neq y, (x, y) \in S\}$
5:     $\theta \leftarrow \theta - \gamma_f \nabla_\theta (\sum_{\mathcal{S}_c} \mathcal{L}(f_\theta(x), y) + \alpha \sum_{\mathcal{S}_p} \mathcal{L}(f_\theta(T_\xi(c, x)), c))$
6:     $\hat{\xi} \leftarrow \hat{\xi} - \gamma_T \nabla_{\hat{\xi}} (\sum_{\mathcal{S}_p} \mathcal{L}(f_\theta(T_{\hat{\xi}}(x)), c) - \beta||g(c, x)||_2)$
7:     $\xi \leftarrow \hat{\xi}$ if $j\%k = 0$, $j \leftarrow j + 1$
8: **until** $j = K$

---

214 f and T while fixing the other one. However, since our ultimate goal is to learn the poisoned f,
215 constantly updating T will cause the training process to converge very slowly. Inspired by some
216 commonly accepted optimization tricks in reinforcement learning [26], we propose to update T less
217 frequently. During training, f is updated at every alternating step, while T is only updated once in
218 several steps, e.g., after every training epoch. The backdoor samples to train f at a step are generated
219 using T with parameter ξ updated in the previous epoch. We observe that this approach effectively
220 stabilizes the training process and allows f to reach the optimal-clean data and attack performance in
221 fewer training epochs. The training algorithm is presented in Algorithm 1.

5 Evaluation

5.1 Experimental Setup

224 We demonstrate the effectiveness of the proposed Marksman backdoor through comprehensive
225 experiments on several widely-used datasets for backdoor attack study: **MNIST**, **CIFAR10**, **GT-**
226 **SRB**, and TinyImagenet (**T-IMNET**). We follow the previous works [34, 37, 5, 29] and consider
227 various architectures for the classifier f: a CNN model [29] for MNIST, Pre-activation Resnet18
228 (**PreActResnet18**) [14] for CIFAR10 and GTSRB, and **Resnet18** [14] for T-IMNET.

229 As mentioned in previous sections, to the best of our knowledge, Marksman is the first work that
230 studies multi-trigger and multi-payload backdoor with the capability of misclassifying an input to any
231 target class. For comparison, we design a baseline approach by injecting different trigger patterns
232 repeatedly for different target classes. In our experiments, we use a different patch-based trigger
233 pattern [13] for a target class. We denote this baseline approach as **PatchMT**.

234 **Hyperparameters:** For each method, we train the classifiers using the momentum SGD optimizer
235 (initial learning rate of 0.01, and after every 100 epochs, the learning rate is decayed by a factor of
236 0.1). For Marksman, we train f and T alternately but update T slowly after every epoch. To achieve a
237 high-degree visual stealthiness of Marksman, we select ϵ as small as 0.05 for all datasets. We perform
238 grid searches to select the best α and β using the CIFAR10 dataset and use these values for all the
239 experiments. We also observe that a value of α closer to 1.0 (specifically, around 0.8) achieves the
240 optimal poisoning objective (i.e., highest clean-data accuracy and best ASR). More details of the
241 experimental setup can be found in the supplementary material.

5.2 Effectiveness of Marksman

243 This section presents the attack success rates of Marksman and PatchMT. To evaluate the performance
244 in the multi-trigger multi-payload scenario, for each test sample (x, y), we enumerate the all possible
245 target labels c other than the true label y and use the compared attack method to activate the backdoor
246 associated with these target labels. For each clean image, our attack only needs to feed it to the
247 trigger function with a specified target class for generating the image with the trigger. The attack is
248 considered successful for each input x and a target label c when the f correctly predicts c.

5.2.1 Attack Performance

250 The clean-data accuracy (**Clean**) and attack success rates (**Attack**) of Marksman and PatchMT are
251 presented in Tables 1 and 2 when poisoning 50% and 10% of the clean samples, respectively. As
252 we can observe from these tables, PatchMT's clean-data performance drops significantly at a higher
253 poisoning rate (50%), while its attack performance is very low (below 50%) at a lower poisoning
254 rate (10%). As expected, when the number of labels in the classification task is higher (e.g., 200
255 for T-IMNET), the attack's success rate of PatchMT also decreases (e.g., reaching the performance,
256 ≈ 0.003, of a random attack on 10% poisoning rate).

257 In comparison, Marksman is highly effective: 100% attack success rates on almost all datasets.
258 Marksman can achieve such high ASRs without sacrificing the clean-data performance (only a trivial
259 drop in performance). Since the objective of our method is to have the capability of misclassifying a
260 given input to any target class during inference, we also report the attack success rate for each class
261 of both Marksman and PatchMT in Table 3. We report the performance of GTSRB and T-IMNET
262 with more classes in the supplementary material. It can be seen that the Marksman achieves excellent
263 performance for any arbitrary target classes. The success of Marksman confirms the existence of

an attack with a significantly more flexible and powerful payload than the previous studies in the backdoor domain and encourages future research on the corresponding defensive approaches.

Table 1: Clean and attack performance with 50% poisoning rate. Red values represent the performance drop w.r.t the original benign classifier.

Dataset	PatchMT		Marksman	
	Clean	Attack	Clean	Attack
MNIST	0.967/*0.022*	0.996	0.988/*0.001*	1.000
CIFAR10	0.882/*0.058*	0.990	0.941/*0.007*	1.000
GTSRB	0.943/*0.051*	0.993	0.986/*0.001*	0.999
T-IMNET	0.527*0.052*	0.951	0.577/*0.002*	0.999

Table 2: Clean and attack performance with 10% poisoning rate. Red values represent the relative performance drop w.r.t the original benign classifier.

Dataset	PatchMT		Marksman	
	Clean	Attack	Clean	Attack
MNIST	0.975/*0.014*	0.298	0.983/*0.006*	1.000
CIFAR10	0.933/*0.007*	0.487	0.943/*0.005*	1.000
GTSRB	0.958/*0.031*	0.376	0.979/*0.010*	0.997
T-IMNET	0.577/*0.002*	0.003	0.575/*0.004*	0.999

Table 3: Attack success rate for each target class with 10% poisoning rate.

MNIST	1	2	3	4	5	6	7	8	9	10
PatchMT	0.373	0.209	0.162	0.267	0.288	0.390	0.149	0.368	0.172	0.621
Marksman	0.997	0.998	1.000	1.000	0.999	1.000	1.000	1.000	0.998	0.998

CIFAR10	1	2	3	4	5	6	7	8	9	10
PatchMT	0.397	0.362	0.449	0.744	0.418	0.534	0.725	0.369	0.384	0.399
Marksman	1.000	1.000	1.000	0.999	1.000	1.000	1.000	1.000	0.999	1.000

5.2.2 Attack Performance with Different Poisoning Rates

We can understand the challenges in adapting the existing backdoor attack methods for the multi-trigger multi-payload scenario and the effectiveness of Marksman by investigating the clean and backdoor performance of PatchMT and Marksman, respectively. Figure 2 shows the clean-data accuracy and ASR for different poisoning rates (i.e., $|\mathcal{S}_p|/(|\mathcal{S}_p| + |\mathcal{S}_c|)$) between 5% and 50%. We can observe that, for PatchMT, the classifier either performs noticeably worse on clean data with higher attack performance or preserves the clean-data performance with significantly lower ASR. In contrast, the performance of Marksman is consistent across different poisoning rates.

Figure 2: Clean (**/C**) and attack (**/B**) performance with different poisoning rates.

5.2.3 Performance of Trained Trigger Function on Other Models

While Marksman's threat model assumes that the adversary has full control of the training process, in this section, we demonstrate that the learned class-conditional trigger function can be used to attack

other classifiers. In other words, Marksman can still be effective when the adversary has only access
to the training data but does not control the training process or knows the internal structure of f. To
perform the experiments, we freeze the parameters of the class-conditional trigger function T after it
is jointly learned with a classifier f, then generate poisoned samples to attack another classifier f'
whose network can be either similar or different from f's architecture.

Table 4 shows the clean and attack performance when T is jointly trained with a PreActResnet18
classifier (f) and f' is another PreActResnet18 (**Same Arch.**) or Vgg11 (**Different Arch.**), either of
which is trained from scratch on the poisoned data created by T. It can be seen that Marksman is
still effective: nearly optimal clean-data performance and almost 100% ASR. This transferability
of T after it is learned is very interesting. We conjecture that the training process of T is related to
approximating adversarial example generation of f that shows decent transferability [21, 36], while
the detailed investigation is beyond the scope of this paper. Note that the trigger is produced by the
trigger generator/function that is the secret held by the adversary, which is qualitatively different from
adversarial examples.

Table 4: Clean and attack performance on other models.

Dataset	Same Arch.		Different Arch.	
	Clean	Attack	Clean	Attack
CIFAR10	0.935	1.000	0.904	0.999
GTSRB	0.986	0.999	0.973	0.997

5.3 Performance against Defensive Measures

In this section, we evaluate the backdoor-injected classifiers by the proposed Marksman framework
against popular defensive mechanisms, including Neural Cleanse (model mitigation defense) [38],
STRIP (detection based defense) [11], and Spectral Signature (latent-space inspection) [37]. It is
important to note that these defenses are originally designed for conventional backdoor attacks with a
weaker capability that are only able to misclassify an input to a specific target class.

5.3.1 Model Mitigation: Neural Cleanse

We evaluate the robustness of Marksman against Neural Cleanse, a widely-used defensive method
based on the pattern optimization approach. Specifically, for every possible label, Neural Cleanse
learns the optimal trigger pattern to attack this target label. It then quantifies whether any of the
learned trigger patterns is an outlier via a metric called Anomaly Index. Neural Cleanse determines if
a model has a backdoor if the Anomaly Index is greater than 2; otherwise, the model is benign.

The results of the benign classifier and the backdoor-injected classifier by Marksman are presented in
Figure 3. It can be observed that Marksman bypasses the Neural Cleanse on all datasets.

Figure 3: Performance against Neural Cleanse. The benign model is trained without backdoor attacks.
A model with Anomaly Index > 2 is considered to have backdoor.

5.3.2 Input Perturbation: STRIP

Next, we evaluate the robustness of Marksman against STRIP [11], a representative inference-phase detection method, which perturbs the input image and calculates the entropy of the predictions of these perturbed images. STRIP determines if an image is a backdoor input by relying on the fact that the entropy of the perturbed backdoor input tends to be lower than that of the clean one.

We plot the entropy of clean and backdoor images computed by STRIP in Figure 4. As we can observe from this figure, the entropy distributions of the backdoor samples and clean samples are similar. Thus, Marksman can also bypass the STRIP defense.

(a) MNIST	(b) CIFAR10	(c) GTSRB	(d) T-IMNET

Figure 4: Performance against STRIP.

5.3.3 Latent-space Inspection: Spectral Signature

Spectral Signature [37] is another representative defensive approach that inspects the latent space of the trained classifier. Spectral Signature first finds the top-right singular vector of the covariance matrix of the latent vectors using a small subset of clean samples. Then it calculates the correlation of each sample to this singular vector. Those with the outlier scores are identified as backdoor samples.

We follow the same experiments in [37] and select 5,000 clean samples and 500 backdoor samples for each dataset. Then, we calculate the correlation scores and plot the histograms of the scores for both sets of samples. As we can observe in Figure 5, there is no clear separation between the correlation scores of the backdoor samples and the clean samples, validating the stealthiness of the proposed Marksman backdoor.

(a) MNIST	(b) CIFAR10	(c) GTSRB	(d) T-IMNET

Figure 5: Performance against Spectral Signature.

6 Conclusion

In this paper, we proposed a novel backdoor attack, Marksman, with a much more powerful payload where the adversary can arbitrarily choose the target class given any input during inference. This framework is able to effectively and efficiently learn the trigger function and inject the backdoor into a DNN model. Our experimental results over popular datasets demonstrate the effectiveness of Marksman and the stealthiness against the existing representative defenses.

Societal Impacts: Our work on the backdoor attack is likely to increase the awareness and understanding of such vulnerability on neural networks. The proposed attack, if not appropriately used, may bring security threats to the existing DNN applications. We believe our study is an important step towards understanding the full capability of backdoor attacks. This knowledge will, in turn, facilitate the further development of secure and trustworthy DNN models and powerful defensive solutions.

References

[1] Eugene Bagdasaryan and Vitaly Shmatikov. Blind backdoors in deep learning models. *arXiv preprint arXiv:2005.03823*, 2020.

[2] Mauro Barni, Kassem Kallas, and Benedetta Tondi. A new backdoor attack in CNNs by training set corruption without label poisoning. In *Proceedings of the 2019 IEEE International Conference on Image Processing (ICIP)*, pages 101–105, Taipei, 2019.

[3] Nicholas Carlini and David A. Wagner. Adversarial examples are not easily detected: Bypassing ten detection methods. In Bhavani M. Thuraisingham, Battista Biggio, David Mandell Freeman, Brad Miller, and Arunesh Sinha, editors, *Proceedings of the 10th ACM Workshop on Artificial Intelligence and Security (AISec@CCS)*, pages 3–14, Dallas, TX, 2017.

[4] S Sibi Chakkaravarthy, D Sangeetha, and V Vaidehi. A survey on malware analysis and mitigation techniques. *Computer Science Review*, 32:1–23, 2019.

[5] Bryant Chen, Wilka Carvalho, Nathalie Baracaldo, Heiko Ludwig, Benjamin Edwards, Taesung Lee, Ian M. Molloy, and Biplav Srivastava. Detecting backdoor attacks on deep neural networks by activation clustering. In *Proceedings of the Workshop on Artificial Intelligence Safety*, Honolulu, HI, 2019.

[6] Huili Chen, Cheng Fu, Jishen Zhao, and Farinaz Koushanfar. Deepinspect: A black-box trojan detection and mitigation framework for deep neural networks. In *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence (IJCAI)*, pages 4658–4664, Macao, China, 2019.

[7] Xinyun Chen, Chang Liu, Bo Li, Kimberly Lu, and Dawn Song. Targeted backdoor attacks on deep learning systems using data poisoning. *arXiv preprint arXiv:1712.05526*, 2017.

[8] Siyuan Cheng, Yingqi Liu, Shiqing Ma, and Xiangyu Zhang. Deep feature space trojan attack of neural networks by controlled detoxification. *arXiv preprint arXiv:2012.11212*, 2020.

[9] Khoa Doan, Yingjie Lao, Weijie Zhao, and Ping Li. LIRA: Learnable, imperceptible and robust backdoor attacks. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 11966–11976, 2021.

[10] Jacob Dumford and Walter J. Scheirer. Backdooring convolutional neural networks via targeted weight perturbations. In *Proceedings of the 2020 IEEE International Joint Conference on Biometrics (IJCB)*, pages 1–9, Houston, TX, 2020.

[11] Yansong Gao, Change Xu, Derui Wang, Shiping Chen, Damith Chinthana Ranasinghe, and Surya Nepal. STRIP: a defence against trojan attacks on deep neural networks. In *Proceedings of the 35th Annual Computer Security Applications Conference (ACSAC)*, pages 113–125, San Juan, PR, 2019.

[12] Jonas Geiping, Hartmut Bauermeister, Hannah Dröge, and Michael Moeller. Inverting gradients-how easy is it to break privacy in federated learning? *Advances in Neural Information Processing Systems*, 33:16937–16947, 2020.

[13] Tianyu Gu, Kang Liu, Brendan Dolan-Gavitt, and Siddharth Garg. BadNets: Evaluating backdooring attacks on deep neural networks. *IEEE Access*, 7:47230–47244, 2019.

[14] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the 2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 770–778, Las Vegas, NV, 2016.

[15] W Ronny Huang, Jonas Geiping, Liam Fowl, Gavin Taylor, and Tom Goldstein. Metapoison: Practical general-purpose clean-label data poisoning. *Advances in Neural Information Processing Systems*, 33:12080–12091, 2020.

[16] Keita Kurita, Paul Michel, and Graham Neubig. Weight poisoning attacks on pre-trained models. *arXiv preprint arXiv:2004.06660*, 2020.

[17] Shaofeng Li, Minhui Xue, Benjamin Zi Hao Zhao, Haojin Zhu, and Xinpeng Zhang. Invisible backdoor attacks on deep neural networks via steganography and regularization. *IEEE Trans. Dependable Secur. Comput.*, 18(5):2088–2105, 2021.

[18] Yiming Li, Tongqing Zhai, Baoyuan Wu, Yong Jiang, Zhifeng Li, and Shutao Xia. Rethinking the trigger of backdoor attack. *arXiv preprint arXiv:2004.04692*, 2020.

[19] Yuanchun Li, Jiayi Hua, Haoyu Wang, Chunyang Chen, and Yunxin Liu. Deeppayload: Black-box backdoor attack on deep learning models through neural payload injection. In *2021 IEEE/ACM 43rd International Conference on Software Engineering (ICSE)*, pages 263–274. IEEE, 2021.

[20] Kang Liu, Brendan Dolan-Gavitt, and Siddharth Garg. Fine-pruning: Defending against back-dooring attacks on deep neural networks. In *Proceedings of the 21st International Symposium on Research in Attacks, Intrusions, and Defenses (RAID)*, pages 273–294, Heraklion, Crete, Greece, 2018.

[21] Yanpei Liu, Xinyun Chen, Chang Liu, and Dawn Song. Delving into transferable adversarial examples and black-box attacks. *arXiv preprint arXiv:1611.02770*, 2016.

[22] Yingqi Liu, Shiqing Ma, Yousra Aafer, Wen-Chuan Lee, Juan Zhai, Weihang Wang, and Xiangyu Zhang. Trojaning attack on neural networks. In *Proceedings of the 25th Annual Network and Distributed System Security Symposium (NDSS)*, San Diego, CA, 2018.

[23] Yunfei Liu, Xingjun Ma, James Bailey, and Feng Lu. Reflection backdoor: A natural backdoor attack on deep neural networks. In *Proceedings of the 16th European Conference on Computer Vision (ECCV), Part X*, pages 182–199, Glasgow, UK, 2020.

[24] Yuntao Liu, Yang Xie, and Ankur Srivastava. Neural trojans. In *Proceedings of the 2017 IEEE International Conference on Computer Design (ICCD)*, pages 45–48, Boston, MA, 2017.

[25] Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *Proceedings of the 6th International Conference on Learning Representations (ICLR)*, Vancouver, Canada, 2018.

[26] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *nature*, 518(7540):529–533, 2015.

[27] Luis Muñoz-González, Battista Biggio, Ambra Demontis, Andrea Paudice, Vasin Wongras-samee, Emil C. Lupu, and Fabio Roli. Towards poisoning of deep learning algorithms with back-gradient optimization. In *Proceedings of the 10th ACM Workshop on Artificial Intelligence and Security (AISec@CCS)*, pages 27–38, Dallas, TX, 2017.

[28] Tuan Anh Nguyen and Anh Tran. Input-aware dynamic backdoor attack. *Advances in Neural Information Processing Systems*, 33:3454–3464, 2020.

[29] Tuan Anh Nguyen and Anh Tuan Tran. Wanet - imperceptible warping-based backdoor attack. In *Proceedings of the 9th International Conference on Learning Representations (ICLR)*, Virtual Event, Austria, 2021.

[30] Ximing Qiao, Yukun Yang, and Hai Li. Defending neural backdoors via generative distribution modeling. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 14004–14013, Vancouver, Canada, 2019.

[31] Ahmed Salem, Rui Wen, Michael Backes, Shiqing Ma, and Yang Zhang. Dynamic backdoor attacks against machine learning models. *arXiv preprint arXiv:2003.03675*, 2020.

[32] Ali Shafahi, W. Ronny Huang, Mahyar Najibi, Octavian Suciu, Christoph Studer, Tudor Dumitras, and Tom Goldstein. Poison frogs! targeted clean-label poisoning attacks on neural networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 6106–6116, Montréal, Canada, 2018.

[33] Reza Shokri, Marco Stronati, Congzheng Song, and Vitaly Shmatikov. Membership inference attacks against machine learning models. In *2017 IEEE Symposium on Security and Privacy (SP)*, pages 3–18. IEEE, 2017.

[34] Te Juin Lester Tan and Reza Shokri. Bypassing backdoor detection algorithms in deep learning. In *Proceedings of the IEEE European Symposium on Security and Privacy (EuroS&P)*, pages 175–183, Genoa, Italy, 2020.

[35] Mohammad Tehranipoor and Farinaz Koushanfar. A survey of hardware trojan taxonomy and detection. *IEEE design & test of computers*, 27(1), 2010.

[36] Florian Tramèr, Nicolas Papernot, Ian Goodfellow, Dan Boneh, and Patrick McDaniel. The space of transferable adversarial examples. *arXiv preprint arXiv:1704.03453*, 2017.

[37] Brandon Tran, Jerry Li, and Aleksander Madry. Spectral signatures in backdoor attacks. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 8011–8021, Montréal, Canada, 2018.

[38] Bolun Wang, Yuanshun Yao, Shawn Shan, Huiying Li, Bimal Viswanath, Haitao Zheng, and Ben Y. Zhao. Neural cleanse: Identifying and mitigating backdoor attacks in neural networks. In *Proceedings of the 2019 IEEE Symposium on Security and Privacy (SP)*, pages 707–723, San Francisco, CA, 2019.

[39] Kan Xiao, Domenic Forte, Yier Jin, Ramesh Karri, Swarup Bhunia, and M Tehranipoor. Hardware trojans: Lessons learned after one decade of research. *ACM Transactions on Design Automation of Electronic Systems (TODAES)*, 22(1):6, 2016.

[40] Mingfu Xue, Can He, Jian Wang, and Weiqiang Liu. One-to-n & n-to-one: Two advanced backdoor attacks against deep learning models. *IEEE Transactions on Dependable and Secure Computing*, 2020.

[41] Mingfu Xue, Shifeng Ni, Yinghao Wu, Yushu Zhang, Jian Wang, and Weiqiang Liu. Imperceptible and multi-channel backdoor attack against deep neural networks. *arXiv preprint arXiv:2201.13164*, 2022.