Composing Efficient, Robust Tests for Policy Selection

Abstract

Modern reinforcement learning systems produce many high-quality policies throughout the learning process. However, to choose which policy to actually deploy in the real world, they must be tested under an intractable number of environmental conditions. We introduce RPOSST, an algorithm to select a small set of test cases from a larger pool based on a relatively small number of sample evaluations. RPOSST treats the test case selection problem as a 2-player game and optimizes a solution with provable k-of-N robustness, bounding the error relative to a test that used all the test cases in the pool. Empirical results demonstrate that RPOSST finds a small set of test cases that identify high quality policies in a toy one-shot game, poker datasets, and a high-fidelity racing simulator.

1 INTRODUCTION

Reinforcement learning (RL) [Sutton and Barto, 2018] policies have made a number of stunning breakthroughs in multiplayer games [Silver et al., 2016, Moravčík et al., 2017, Brown and Sandholm, 2018, Vinyals et al., 2019, Brown and Sandholm, 2019, Wurman et al., 2022, FAIR et al., 2022, Perolat et al., 2022]. However, the process of choosing an RL policy for production usage, either in an exhibition or deployment for end users, is challenging. Practitioners often generate many policies that perform well during training but which require thorough vetting on alternative conditions or opponents. Ideally, we would construct a test case for every conceivable deployment scenario, evaluate each policy on each test case, and rank each policy according to a weighted average of test case results. However, such a procedure is typically infeasible because of the sheer numbers of policies and deployment scenarios, especially if test cases are lengthy or involve people. In this work, we present a method of selecting a small number test cases from a larger pool that minimizes the reduction in test quality.

Practitioners from other fields, *e.g.*, educational testing [van der Linden, 2005], will recognize this problem as *test construction*–selecting a small yet robust set of test cases, based on limited data, to evaluate many candidates. This set of test cases should contain enough information to indicate performance over the whole test case pool. For instance, if a policy can defeat a skilled opponent, we can infer that it can defeat an unskilled opponent.

Complicated domains contain complex intransitive relationships between policies, necessitating test case diversity. In addition, there is considerable uncertainty over what policies may be produced in the future and what test cases are the most important to game designers. Therefore, a robust solution is required.

We introduce a framework, *robust population optimization for a small set of test cases* (*RPOSST*), to compose an efficient robust test of a fixed size. RPOSST tunes its test to approximate the test scores of adversarially selected policies and test case averaging weights, given test case results on a small set of policies. We present two versions of a RPOSST algorithm representing different use cases, focusing on $\text{RPOSST}_{\text{SEQ}}$, which is better suited to current RL deployment pipelines. We provide robustness guarantees for $\text{RPOSST}_{\text{SEQ}}$ and CVaR $\text{RPOSST}_{\text{SEQ}}$ (a convenient special case) for k-of-N robustness measures [Chen and Bowling, 2012]. These guarantees provide confidence that RPOSST test scores for future deployment candidates are reliable.

Our contributions include the RPOSST framework, including two algorithm versions, robustness guarantees, and thorough empirical validation in domains widely ranging in complexity. Empirical results are presented for a toy one-shot game simulating race car passing, computer poker competition datasets, and the high fidelity racing simulator, Gran Turismo 7™. They show that RPOSST can dramatically reduce the number of test cases needed to identify good deployment policies.

Submitted to the 39th Conference on Uncertainty in Artificial Intelligence (UAI 2023). **To be used for reviewing only**.

Figure 1: Policy testing with RPOSST. From left to right, the result matrix A is constructed from rollouts, *i.e.*, $A_{i,j}$ is the average rollout outcome for tuning policy j on test case i. RPOSST analyzes A, taking into account uncertainty distribution Ψ and a (possibly empty) initial set of test cases that must be used, τ^0. RPOSST outputs an efficient robust test $\langle \tau^*, \hat{\sigma}_{\tau^*}^* \rangle$, here using only $m = 3$ test cases (if $\mathcal{T}$ is too large to select all 3 test cases at once, τ^* can be fed back into RPOSST as τ^0). New candidate deployment policies are tested against each test case in τ^* and each result is weighted according to $\hat{\sigma}_{\tau^*}^*$, producing a test score for each candidate deployment policy.

2 PROBLEM DEFINITION

The goal of *policy testing* is to evaluate the strengths and weaknesses of a large set of candidate deployment policies, $\Pi_{\mathrm{CDP}} \subseteq \Pi$, in order to choose one for deployment. A *policy* $\pi \in \Pi$ in this setting can be any mapping from environment observations to a distribution over actions (*e.g.*, Markov policies; Sutton and Barto [2018]). A policy is evaluated on a *test* consisting of various test cases chosen from a pool, $\mathcal{T}$. Each *test case* simulates an important aspect of the deployment environment, for example, different parameter settings like weather conditions or different opponent policies in a competative game. For straightforward comparisons between policies, we summarize a policy π's test results with a scalar *test score*, computed as the weighted average of π's test case results according to *test case weights*, $\sigma \in \triangle^{|\mathcal{T}|}$.

If $\mathcal{T}$ is small, then right before deployment we could simply test each policy, rank the policies in Π_{CDP} according to the test scores, and deploy the best one. However, if policies will encounter a wide range of conditions during deployment, *e.g.*, hundreds or thousands of different players for a policy deployed to a popular video game, then $\mathcal{T}$ ostensibly needs to be large in order to adequately reflect such diversity. The linear scaling in $|\mathcal{T}|$ presents not just a computational burden, but also costs in sample complexity (if the test cases are lengthy) or even in person-time if human quality assurance testers might be needed for test cases.

This work addresses the problem of composing an efficient *test*, $\langle \tau, \hat{\sigma}_\tau \rangle$, by selecting a small number of test cases $\tau \subset \mathcal{T}$ and test case weights $\hat{\sigma} \in \triangle^{|\tau|}$ to approximate a full test, $\langle \mathcal{T}, \sigma \in \triangle^{|\mathcal{T}|} \rangle$. Complicating this task are two sources of uncertainty to which the efficient test must be robust. First,

$\langle \tau, \hat{\sigma}_\tau \rangle$ ought to be used on new candidate deployment policies, so Π_{CDP} is unknown before $\langle \tau, \hat{\sigma}_\tau \rangle$ is chosen. Second, the desired *target distribution*, σ, defining the full test to approximate may drift after $\langle \tau, \hat{\sigma}_\tau \rangle$ is chosen.

We assume access to a small set of representative *tuning policies* $\Pi_{\mathrm{TNP}} \subset \Pi$ for immediate testing (Section 4 discusses practical considerations in the composition of Π_{TNP}). Additionally, our algorithm takes as input a joint distribution Ψ over Π_{TNP} and $\triangle^{|\mathcal{T}|}$ to represent the combined uncertainty about which policies the output test will be applied to and which target distribution to approximate. See Figure 1 for an illustration of the test composition pipeline.

3 BACKGROUND

In order to compose an efficient and robust test, we utilize established game-theoretic frameworks for modeling robustness and learning optimal decisions (specifically, regret minimization). The following subsections present background material on these two topics.

3.1 ROBUSTNESS

The idea of *robustness* is to prepare for an unfavorable portion of possible outcomes sampled from an uncertainty distribution. In our formulation of policy testing the uncertainty distribution covers the future policies in Π_{CDP} and the target distribution. A *percentile robustness measure* [Charnes and Cooper, 1959], μ, is a formal representation of a robustness criterion as a probability distribution over percentiles. For example, if μ has all of its weight on 0.01, then an

m-size test with weights $\hat{\sigma}_\tau$ that is robust according to μ, then the test minimizes test score error on $\hat{\sigma}_\tau$'s worst 1% of policy–target-distribution pairs sampled from Ψ.

The *k-of-N robustness measures* [Chen and Bowling, 2012] are percentile robustness measures defined by parameters $k, N \in \mathbb{N}, 1 \leq k \leq N$, that permit *tractable* optimization procedures. This parameterization reflects the mechanics of how an efficient test $\langle \tau, \hat{\sigma}_\tau \rangle$ is evaluated on such a measure: N policy–target-distribution pairs are sampled from Ψ and $\hat{\sigma}_\tau$'s performance is averaged over the k worst pairs for $\hat{\sigma}_\tau$. Every k-of-N robustness measure is a non-increasing function, *i.e.*, more weight is placed on smaller percentiles, and the fraction k/N represents the percentile (technically the fractile) around which the measure decreases.

In our test construction setting, the choice of k and N reflects the designer's tolerance for test scores that deviate drastically from those in worst-case target distributions, as well as the expected difference between the set of tuning and candidate deployment policies. Optimizing for performance under small percentiles (*e.g.*, setting $k = 1, N = 100$) yields tests with a small maximum test score error across Π_{TNP}. Then, even if each candidate deployment policy resembles the tuning policy that has the largest test score error, the optimized test will yield small test score errors. In contrast, optimizing for the uniform measure ($k = N$) optimizes for mean performance across Π_{TNP}, essentially assuming $\Pi_{\text{CDP}} = \Pi_{\text{TNP}}$, which can lead to large test score error on the actual candidate deployment policies.

As $N \to \infty$, the k-of-N robustness measure approaches the *conditional value at risk* (*CVaR*) robustness measure at the k/N fractile [Chen and Bowling, 2012], which evenly weights all of the fractiles $\leq k/N$ and puts a weight of zero on all larger fractiles. Formally, the robustness optimization objective is to minimize the *percentile performance loss*:

$$L_{\mu,\Psi}(\hat{\sigma}_\tau) = \inf_{\substack{y \in \mathcal{Y} \\ \eta \in [0,1], \, \mathbb{P}[\ell(\hat{\sigma}_\tau;\pi,\sigma) \leq y(\eta)] \geq \eta}} \int y(\eta)\mu(d\eta), \quad (1)$$

under a loss function $\ell : \triangle^{|\mathcal{T}|} \times \Pi_{\text{TNP}} \times \triangle^{|\mathcal{T}|} \to \mathbb{R}$ where we overload ℓ for incomplete test case weight vectors by filling in zeros for missing elements, $\langle \pi, \sigma \rangle \sim \Psi$, and $\mathcal{Y}$ is the class of real-valued, bounded, μ-integrable functions on $[0, 1]$. An *efficient μ-robust test* is a minimizer of $L_{\mu,\Psi}$.

The optimization of the percentile performance loss under a k-of-N robustness measure can be modeled as a zero-sum imperfect information game [Chen and Bowling, 2012]. Here, a protagonist player constructs efficient tests and an antagonist chooses a tuning policy to test and a target distribution. The antagonist receives the test score error as their payoff, while the protagonist receives the negation. The k and N parameters determine which target distributions and tuning policies that the antagonist can choose from and how many pairs must be averaged across. At the start of the game, N target-distribution–tuning-policy pairs are sampled. From

these N pairs, the antagonist must select k of them. Finally, one of these k pairs is sampled and both players receive their payoffs according to the error between the test score produced by applying the protagonist's test to the antagonist's tuning policy and that policy's test score according to the full set of test cases averaged according to the antagonist's target distribution. A *minimax* test for the protagonist, *i.e.*, one that minimizes the protagonist's maximum loss in this game is a $\mu_{k\text{-of-}N}$-robust decision.

3.2 REGRET

While the game above models the optimization process, it does not instruct the protagonist on *how* to choose test cases to win. A no-regret *online decision process* (*ODP*) algorithm can find approximate minimax decisions by repeatedly playing out the game and improving over time from payoff feedback. Formally, on each round t of the game, an ODP algorithm chooses an efficient test $\langle \tau^t, \hat{\sigma}_{\tau^t}^t \rangle$ and receives the *payoff function* $v^t = -\nabla_{\hat{\sigma}_{\tau^t}^t} \ell(\hat{\sigma}_{\tau^t}^t; \pi^t, \sigma^t)$ as feedback given $\langle \pi^t, \sigma^t \rangle$ chosen by the antagonist. If the antagonist always plays a best response to the ODP algorithm, that is, the tuning-policy–target-distribution pair that maximizes the loss of $\hat{\sigma}_{\tau^t}^t$ on each round $t \in \{1, \dots, T\}$, $T \geq 1$, then the *no-regret* property ensures that at least one of the tests in the sequence $\langle \langle \tau^t, \hat{\sigma}_{\tau^t}^t \rangle \rangle_{t=1}^T$ is at most $\mathcal{O}(G/\sqrt{T})$ away from the minimax value, where $G > 0$ is the maximum magnitude of the loss gradient (see Lockhart et al. [2019a,b] and Proposition 4 in our appendix for more details).

Regret matching$^+$ [Tammelin, 2014, Tammelin et al., 2015] is a no-regret algorithm for simplex decision sets, *e.g.*, the m dimensional test case weight space $\triangle^m$, that selects $\hat{\sigma}_{\tau^t}^t = \frac{q^{1:t-1}}{\mathbf{1}^\top q^{1:t-1}}$ using *pseudoregrets* $q^{1:t} = [q^{1:t-1} + \rho^t]_+$, $q^{1:0} = \mathbf{0}$, where $\rho^t = v^t - (v^t)^\top \hat{\sigma}_{\tau^t}^t$ is the *instantaneous regret* vector ($\hat{\sigma}_{\tau^t}^t = \frac{1}{d}\mathbf{1}$ if none of the pseudoregrets are positive).

4 RPOSST

Our approach, *robust population optimization for a small set of test cases* (*RPOSST*) begins by evaluating each tuning policy $\pi \in \Pi_{\text{TNP}}$ on each test case $c \in \mathcal{T}$, yielding a $|\mathcal{T}| \times |\Pi_{\text{TNP}}|$ result matrix A of test case results. As an optimization approach, RPOSST aims to minimize prediction errors, as measured by a bounded convex function $\Delta : \mathbb{R} \times \mathbb{R} \to [0, L]$, *e.g.*, the absolute difference $\Delta(\hat{x}, x) = |\hat{x} - x|$. RPOSST robustly optimizes for a small set of test cases and a weighting over them according to how well it reproduces test scores admitted by A as measured by a loss function

$$\ell : \hat{\sigma}; \pi_j, \sigma \mapsto \Delta(\underbrace{E_{i \sim \hat{\sigma}}[A_{i,j}]}_{\hat{\sigma}\text{'s test score for } \pi_j.} , \underbrace{E_{i \sim \sigma}[A_{i,j}]}_{\sigma\text{'s test score for } \pi_j.}),$$

where loss is computed for test case distribution $\hat{\sigma} \in \triangle^{|\mathcal{T}|}$ compared to target distribution $\sigma \in \triangle^{|\mathcal{T}|}$ with respect to test results from the j^{th} tuning policy π_j. Our goal is to select a small number of test cases, so we constrain RPOSST to output weights $\hat{\sigma}_\tau \in \triangle^m$ for groups of test cases $\tau \subset \mathcal{T}$ of size m.

Though $\mathcal{T}$ is large, the cost of computing A is balanced by the savings of using fewer test cases for future policies. RPOSST is robust to any distribution over Π_{TNP}, so as long as this set covers the space of Π_{CDP} (i.e., $\pi \in \Pi_{\text{CDP}}$ are convex mixtures of Π_{TNP}), this robustness imparts a minimum test accuracy guarantee even on deployment candidates. Intuitively, this means the quality of RPOSST's tests will tend to improve with more diverse tuning policies. Accordingly, it should be beneficial for a tuning policy to represent an extreme point in a reasonable region of policy space, or at least for it to be generated with a method similar to that which will generate deployment candidates (e.g., sampled from checkpoints of RL training runs). That way, the tuning policies include a diverse collection of skilled and unskilled policies with random variations, while retaining architectural and algorithmic similarities to future deployment candidates.

Following the earlier discussion of k-of-N robustness, we frame the optimization in RPOSST as a zero-sum game. By adversarially choosing policies to test, the antagonist forces RPOSST to compose tests that are better at accurately testing the more difficult to assess policies in the tuning set, providing a degree of robustness to the distribution of future deployment candidates. Similarly, by adversarially choosing the target distribution, the antagonist also forces RPOSST to be robust along this dimension. The steps of each round $t = 1, \ldots, T$ of our optimization game follows.

1. The protagonist must choose an m-tuple of test cases $\tau^t \subset \mathcal{T}$ and weights $\hat{\sigma}_{\tau^t}^t \in \triangle^m$.

2. N target distributions and policies to test, $\langle\langle \pi_{j_i}, \sigma_i \rangle\rangle_{i=1}^N$, are sampled from uncertainty distribution Ψ.

3. The antagonist chooses the k worst target distributions and policies, i.e., those that maximize $\ell(\hat{\sigma}_{\tau^t}^t; \pi_{j_i}, \sigma_i)$.

4. One of the k worst configurations is uniformly sampled, leading to the end of the round, at which point the protagonist receives the expected payoff

$$-\mathbb{E}_{k \sim \text{Unif}(\{1,\ldots,N\})}\big[\ell\big(\hat{\sigma}_{\tau^t}^t, \pi_{j_{(i)}}, \sigma_{(i)}\big)\big],$$

where $\cdot_{(i)}$ denotes the i^{th} element of a sorted list in descending order (the i^{th} worst for the protagonist).

The more rounds of the game that are run (the larger T is), the closer RPOSST gets to returning a minimax strategy, and consequently, a robust optimal selection of test cases and an associated distribution. Thus, in application, T can be set as large as is convenient under computational and time constraints. Theorem A.8 gives a precise rate for RPOSST's

improvement, with high probability, as a function of T. Although the protagonist must consider an exponential (in m) number of test case combinations, the premise of RPOSST is that we want a small set of test cases, so m will be small. To decrease computational requirements, RPOSST can be run in a loop to select test cases iteratively until m have been selected, at a potential cost to test accuracy compared to optimizing for the entire m-tuple at once.

4.1 ANTAGONIST INFORMATION MODELS

We consider two RPOSST algorithm variants that utilize different models of the information that the antagonist in our optimization game has before they make their choice. These models correspond to two policy testing use cases. The first, "simultaneous move" model is less pessimistic, but has impractical aspects, which are addressed by the subsequent "sequential move" model.

Simultaneous move. The simultaneous move model is a naïve application of the original k-of-N game by [Chen and Bowling, 2012]. In this model, the antagonist does not observe which m-tuple of test cases, τ^t, is selected by the protagonist on each round t. Instead, it is randomized with a distribution $\hat{\sigma}_\mathcal{T}^t \in \triangle^{|\mathcal{T}|^m}$. This model corresponds to the policy testing use case where a new m-tuple of test cases is sampled independently for each test that is performed. Every test only evaluates m cases, as desired from a computational efficiency perspective, however, the particular test cases used in each test could be different, making results incomparable across tests. See Appendix for additional details.

Sequential move. In the sequential move model, antagonist observes τ^t before acting. The antagonist is thus able to tailor their choice of $\langle\langle \pi_{j_{(i)}}, \sigma_{(i)} \rangle\rangle_{i=1}^k$ to whichever τ^t is selected, and randomizing over the m-tuple of test cases has no benefit to the protagonist. In fact, the selection of τ^t does not impact the protagonist's updates or weight choices, $\langle \hat{\sigma}_\tau^t \rangle_{\tau \in \mathcal{T}^m}$, so we need not explicitly select an m-tuple until the very end of the algorithm. Algorithm 1 shows how to implement RPOSST for the sequential move model using regret matching$^+$ for tuning the test case weights and the Successive Rejects (SR) [Audibert et al., 2010] algorithm for the final selection of an m-tuple. In certain applications, an example of which we will see in Section 4.2 and our experiments, we can construct our optimization game so that it is deterministic, and consequently, we can replace SR with a simple argmax.

The RPOSST$_{\text{SIM}}$ objective is the percentile performance loss

$$\min_{\substack{\tau \in \mathcal{T}^m \\ \hat{\sigma}_\tau \in \triangle^m}} \inf_{\substack{y \in \mathcal{Y} \\ \eta \in [0,1] \\ \mathbb{P}[\ell(\hat{\sigma}_\tau; \pi_j, \hat{\sigma}) \leq y(\eta)] \geq \eta}} \int y(\eta) \mu_{k\text{-of-}N}(d\eta), \qquad (2)$$

where $\langle \pi_j, \sigma \rangle \sim \Psi$.

Algorithm 1 (left column):

```
1  Inputs: ⟨k, N, T₁, m, Ψ, τ⁰, ℓ, T₂⟩
```

$$1 \quad \textbf{Inputs: } \langle k, N, T_1, m, \Psi, \tau^0, \ell, T_2 \rangle$$

$2 \quad q_\tau^{1:0} \leftarrow \mathbf{0} \in \mathbb{R}^{m+|\tau^0|} \textbf{ for } \tau \in \mathcal{T}^m$

$3 \quad T' \sim \text{Unif}(\{1, \dots, T_1\})$

$4 \quad \textbf{for } t \leftarrow 1, \dots, T' \textbf{ do}$

$5 \quad\quad \textbf{for } \tau \in \mathcal{T}^m \textbf{ do}$

$6 \quad\quad\quad z^t \leftarrow \mathbf{1}^\top q_\tau^{1:t-1}$

$7 \quad\quad\quad \hat{\sigma}_\tau^t \leftarrow q_\tau^{1:t-1}/z^t \textbf{ if } z^t > 0 \textbf{ else } \mathbf{1}/m$

$8 \quad\quad\quad$ // Fill in zeros so that $\hat{\sigma}_\tau^t \in \triangle^{|\mathcal{T}|}$.

$9 \quad\quad\quad \sigma_\tau^t(x) \leftarrow 0 \textbf{ for } x \in \mathcal{T} \setminus (\tau \cup \tau^0)$

$10 \quad\quad\quad [\ell_{\tau,(i)}]_{i=1}^k \leftarrow \mathcal{L}_{\text{k-of-N}}(\hat{\sigma}_\tau^t, \langle k, N \rangle, \Psi, \ell)$

$11 \quad\quad\quad v_\tau^t \leftarrow \dfrac{-1}{k} \sum_{i=1}^k \dfrac{\partial \ell_{\tau,(i)}, \pi_{j(i)}}{\partial \hat{\sigma}_\tau^t}$

$12 \quad\quad\quad$ // Update regret matching⁺.

$13 \quad\quad\quad \rho_\tau^t \leftarrow v_\tau^t - (\hat{\sigma}_\tau^t)^\top v_\tau^t$

$14 \quad\quad\quad q_\tau^{1:t} \leftarrow [q_\tau^{1:t-1} + \rho_\tau^t]_+$

$15 \quad \tau^* \leftarrow$
$$\text{SR}\left(\tau \mapsto \frac{1}{2kL} \mathbf{1}^\top \mathcal{L}_{\text{k-of-N}}(\hat{\sigma}_\tau^t, \langle k, N \rangle, \Psi, \ell), T_2 \right)$$

$16 \quad \textbf{return } \tau^*, \hat{\sigma}_{\tau^*}^{T'}$

$1 \quad \textbf{Procedure } \mathcal{L}_{\text{k-}of\text{-N}} \quad \textbf{Inputs: } \langle \hat{\sigma}, k, N, \Psi, \ell \rangle$

$2 \quad \textbf{for } i = 1 \dots N \textbf{ do}$

$3 \quad\quad$ // Sample antagonist actions.

$4 \quad\quad \pi_{j_i}, \sigma_i \sim \Psi$

$5 \quad\quad$ // Evaluate σ.

$6 \quad\quad \ell_{\tau,i} \leftarrow \ell(\sigma; \pi_{j_i}, \sigma_i)$

$7 \quad$ // Sort to identify the worst k.

$8 \quad \text{Sort}\left([\ell_i]_{i=1}^N \right)$

$9 \quad \textbf{return } [\ell_{(i)}]_{i=1}^k$

Algorithm 1: RPOSST$_{\text{SEQ}}$ with regret matching⁺ and Successive Rejects

The sequential move model represents the policy testing use case where we select and fix m test cases and test case weights for all future test policies. Test scores are easily reproducible and comparable across test applications since the test cases never change.

Theorem 4.1. *After $T' \sim \text{Unif}(\{1, \dots, T_1\})$, $T_1 > 0$, rounds of its optimization game, Algorithm 1 selects an m-tuple of test cases, τ^* and weights $\hat{\sigma}_{\tau^*}^{T'} \in \triangle^m$ that, with probability $(1-p)(1-q)(1-\alpha)$, $p, q, \alpha > 0$, are $\frac{\varepsilon}{q}$-optimal for Equation (2), where $\varepsilon = \mathcal{O}\left(\sqrt{\frac{1}{T_1}|\mathcal{T}|} + \sqrt{\frac{1}{T_1} \log(1/p)} \right)$ and $\alpha = \mathcal{O}(e^{-T_2})$.*

All proofs deferred to the Appendix. In the extreme case where Π_{TNP} covers Π, then this optimality result, (in terms of an upper bounded percentile loss integral), extends to all deployment candidates Π_{CDP}.

4.2 DETERMINISTIC CVAR RPOSST

It is possible to choose hyperparameters for a RPOSST algorithm (and k-of-N optimizers more generally) so that it and its optimality to guarantees are determinstic. Such deterministic versions of RPOSST are more reliable, and simpler to implement and evaluate. If we fix the ratio k/N and allow $N \to \infty$, the k-of-N robustness measure converges toward the CVaR measure at the k/N fractile. A k-of-N algorithm where $N \to \infty$ cannot be implementing with the usual sampling procedure, but it could be implemented if we could identify a finite set of tuning-policy–target-distribution pairs with cumulative probability k/N that maximizes the protagonist's error. We can identify such a set if the distribution characterizing our uncertainty, Ψ, is only supported on a discrete set of manageable size.

Sampling Ψ infinitely would result in sampling all world configurations in its support exactly in proportion to their probabilities. Rather than selecting k tuning-policy–target-distribution pairs, the antagonist must select tuning-policy–target-distribution pairs until their cumulative probability sums to k/N. Finally, these tuning-policy–target-distribution pairs are sampled according to their probabilities under Ψ divided by k/N.

The robustness guarantees become deterministic because the entire RPOSST algorithm, denoted as CVaR(η) RPOSST for the η fractile, can be run using exact expectations (excluding randomness in A, which is taken as given in RPOSST). Determinism in RPOSST$_{\text{SEQ}}$ allows us to directly check the exact expected loss of each test case distribution on each round, letting us track the lowest loss test case distribution across all rounds. This tracking, in turn, allows us to avoid both sampling T' and running the SR algorithm to do the final selection. Instead, we can simply return the lowest loss test case distribution across all T rounds.

The expected loss of the protagonist on round t is $L^t = \min_{\tau \in \mathcal{T}^m} \frac{-1}{k} \sum_{i=1}^k \ell(\hat{\sigma}_\tau^t; \pi_{j(i)}, \sigma_{(i)})$, where $\tau^* = \arg\min_{\tau \in \mathcal{T}^m} \frac{-1}{k} \sum_{i=1}^k \ell(\hat{\sigma}_\tau^t; \pi_{j(i)}, \sigma_{(i)})$. The round with the lowest expected loss is then $t^* = \arg\min_{t \in \{1, \dots, T\}} L^t$, which allows us to state the following corollary.

Corollary 4.2. *Assume that $\Psi \in \triangle^d$ for some finite $d \geq 1$. After T rounds of the CVaR(η) RPOSST$_{\text{SEQ}}$ optimization game (using regret matching⁺), τ^* and $\sigma_{\tau^*}^{t^*}$ are ε-optimal for Equation (2) under the η-fractile CVaR robustness measure, where $\varepsilon = \mathcal{O}\left(\sqrt{\frac{1}{T}|\mathcal{T}|} \right)$.*

In addition, we can construct a series of ablations of CVaR RPOSST$_{\text{SEQ}}$ to act as baselines for experiments, and to make a connection to the test-assembly literature.

CVaR RPOSST$_{\text{SEQ}}$ generalizes an intuitive greedy algorithm: find the m-tuple of test cases that minimizes the maximum error assuming a uniform distribution over the tuple.

This *minimax uniform* algorithm is implemented by executing only the initialization and selection steps of CVaR(0) $\text{RPOSST}_{\text{SEQ}}$ ($T = 0$). Further simplifying, *minimax(TTD) uniform* performs the antagonist maximization only over target distributions and assumes a uniform distribution over tuning policies. *Minimax(TNP) uniform* performs the antagonist maximization only over tuning policies and assumes a uniform target distribution. *Miniaverage uniform* assumes both a uniform distribution over tuning policies and for the target distribution.

Additionally, we could select test cases one at a time to minimize the maximum error, echoing greedy algorithms from the test-assembly literature (Chapter 4 of van der Linden [2005]). This *iterative minimax* algorithm is almost the same as running the initialization and return steps of CVaR(0) $\text{RPOSST}_{\text{SEQ}}$ to select a single test case in a loop. The sole difference being that iterative minimax could select the same test case multiple times within its loop to adjust the test case weighting away from unifom.

5 EXPERIMENTS

We explore CVaR $\text{RPOSST}_{\text{SEQ}}$'s performance in three 2-player games spanning the range of complexity from a toy one-shot game to a high-fidelity racing simulator, in comparison with minimax and miniaverage baselines. We show that robustness does tend to decrease test score errors on holdout policies and that RPOSST specifically either outperforms or performs about as well as each baseline in each domain.

5.1 EXPERIMENTAL SETUP

In each domain, we start with data from playing out every pairing of $n > 0$ policies, yielding a matrix of scores for the column policy. Each policy along the rows of this matrix is then treated as a test case, making the score at row i and column j the result of evaluating policy j on test case i.

To emulate unknown deployment candidate policies to be tested, we hold out $h > 0$ columns of this matrix and call the policy associated with a holdout column a *holdout policy*. The remaining columns represent the test case results for the set of tuning policies. The resulting $n \times (n - h)$ matrix is shifted and rescaled so that all entries are between zero and one, and then it is set as the test result matrix A that our methods take as input. Note, although h test cases are generated by holdout policies, as test cases they cannot provide any special information about what tests would be effective on the holdout policies. To simulate scenarios where the set of tuning policies covers the set of future candidate deployment policies to varying degrees, we run experiments with three different values of h: $0.2n$, $0.4n$, and $0.6n$. 100 different holdout sets are randomly sampled for each value of h and in each domain.

Given results for n test cases, the goal is to produce a distribution over $m < n$ test cases that provides accurate test results on the set of holdout policies, according to a set of target distributions. For our experiments, we use $m = 2$ and the set of target distributions generated from the softmax function applied to the negative average test case result under four different scales, specifically, $\exp\left(\frac{-\beta}{n} A\mathbf{1}\right) / \mathbf{1}^{\top} \exp\left(\frac{-\beta}{n} A\mathbf{1}\right)$ for $\beta \in \{0, 1, 2, 4\}$ so that the distributions put varying degrees of emphasis on test cases that are more difficult on average across the tuning policies. We set the RPOSST uncertainty distribution, Ψ, to be uniform over each tuning-policy–target-distribution pair. We set the CVaR percentile to 1% so that it is nearly optimizing for the worst-case, but is slightly less pessimistic, to add an additional distinguishing factor to RPOSST compared to the minimax and minaverage baselines. We use the absolute difference loss for both optimization and evaluation.

5.2 DOMAINS

We test RPOSST on the following three domains of varying complexity. Each domain has two variants arising from asymmetry, multiple datasets, or alternative scoring rules. The Appendix provides further details on each domain.

Racing Arrows. Racing Arrows is a 2-player, zero-sum, one-shot, continuous action game invented for tour experiments that replicates aspects of a passing scenario in a race featuring a "leader" player and faster "follower" player. The follower tries to pass the leader while the latter tries to block. Scores are recored as 0 or $+1$ for a loss or win, respectively, for the column player, which is either the leader or the follower, depending on the configuration. We run RPOSST on both configurations. For our experiments, we sample 50 different leader and follower policies evenly spread through the valid policy space, angles in $[0, \pi]$, by taking 50 evenly spaced angles between $[0.05\pi, (1-0.05)\pi]$ and then shifting them independently with uniform samples in $[-0.05\pi, 0.05\pi]$.

Annual Computer Poker Competition. We take two open datasets from the Annual Computer Poker Competition (ACPC) [Bard et al., 2013] containing pairwise match data for poker agents submitted to the 2017 2-player, no-limit competition and the 2012 2-player, limit competition. These competitions contain different agent populations of agents since they are separated by five years and are in different game formats (limit and no-limit). The 2017 competition consists of 15 agents and the 2012 competition consists of 12 agents. Scores are recorded as chip differentials of duplicate matches (two sets of hands where players play with the same set of shuffled decks in both seats).

Gran Turismo 1-on-1 races. Gran Turismo 7™ (GT)[1] is a high fidelity racing simulator on the PlayStation™ platform.

---

[1] https://www.gran-turismo.com/us/

Figure 2: Expected test score error (absolute difference) across holdout-policy–target-distribution pairs on (top left and middle) Racing Arrows, (top right) the 2012 2-player, limit competition of the ACPC, (bottom left) the 2017 2-player, no-limit competition of the ACPC, (bottom middle and right) Gran Turismo 7™ races, between CVaR(1%) RPOSST$_{SEQ}$ and baseline tests on 100 randomly sampled sets of holdout policies (20% of the full set of policies; 80% used as tuning policies). Holdout-policy–target-distribution pairs are sorted according to test score error. Each RPOSST$_{SEQ}$ is run for 500 rounds ($T = 500$). Errorbars represent 95% t-distribution confidence intervals.

Previous versions of GT served as benchmarks for training RL policies [Fuchs et al., 2021, Song et al., 2021] including policies that out-raced the best human competitors [Wurman et al., 2022] in 4-on-4 racing. We consider a simpler 1-on-1 racing scenario (see Appendix for details). We carry out two experiments, one where test case results are average winrates, and another where policies receive 0 for a loss, $+1$ for a win, and -1 if there was a collision, making the game non-zero-sum. The test case pool is comprised of 43 trained RL policies and 3 built-in "AI" policies.

5.3 RESULTS AND ANALYSIS

The results of running CVaR(1%) RPOSST$_{SEQ}$ on each domain, with 20% of policies marked as holdout policies, are shown in Figure 2. The same set of figures with 40% and 60% holdout policies are qualitatively similar, except that the differences between the algorithms are typically smaller, and are provided in the appendix.

Looking across each domain and variant, we can see that RPOSST$_{SEQ}$ performs nearly as well or better than all of the minimax and miniaverage baselines, particularly in terms of maximum error across holdout-policy–target-distribution pairs. We can see that RPOSST$_{SEQ}$ has noticeably lower error in ACPC 2017 and GT (winrate) on the four most difficult holdout-policy–target-distribution pairs to accurately evaluate. The improvement over the next best method is substantial in ACPC 2017. On the other variant in each domain, RPOSST$_{SEQ}$ is within the group of the lowest error methods. In the two Racing Arrows domains, RPOSST$_{SEQ}$ and minimax uniform, substantially outperform the other methods, at

least on the most difficult holdout-policy–target distribution pairs, showing that robustness is indeed beneficial here, but the uniform distribution over the selected two opponents happens to be quite effective. The GT variant where -1 is assigned to a collision appears to be more difficult than the winrate variant, as all the methods cluster together in this variant at a higher errors than in the winrate variant.

In addition, these results illustrate the utility of incorporating robustness generally, as all of the robust methods tend to outperform miniaverage uniform. Minimax uniform and iterative minimax are the only baselines that minimize their maximum error over both tuning policy and target distribution uncertainty, and they are usually the next best methods after RPOSST$_{SEQ}$. Minimax(TNP) uniform typically outperforms minimax(TTD) uniform, showing that it is more important to be robust to the tuning policy than the target distribution, in these domains. When the target distributions are the same in the optimization and holdout evaluation phases, robustness should directly improve the minimum performance across holdout realizations. Since no effort was made to enforce any relationship between the tuning and holdout policies, this result suggests that robustness to the tuning policy can yield large error reductions when Π_{TNP} are even somewhat similar to the holdout policies.

As an example of RPOSST's capabilities, consider the pairs of opponent policy chosen as test cases in GT (winrate) over 100 experiment seeds (Table 2 in Appendix). RPOSST$_{SEQ}$ is both more accurate (Figure 2) and very consistent, choosing the same pair 90% of the time. Figure 3 illustrates the portion of the result matrix for just the two test cases most frequently chosen by RPOSST$_{SEQ}$ (test races against oppo-

Figure 3: The GT test results of candidate deployment policies against the test case pair most favoured by RPOSST (Blue and red indicates positive and negative winrates respectively w.r.t the candidate deployment policy).

nents 16 and 41). The race against policy 41 (bottom row) is chosen because that policy wins/loses about half the time, providing a 50/50 information split. Policy 16 is a weaker policy in many ways (more blue in the top row) but it serves to differentiate worse performing polices as well as higher performing policies (darker blue squares in the top right). Specifically, the best performing policies almost always win against policy 16, which provides a strong complementary signal to the noisier but more competitive policy 41 test case. Overall, the two test cases indicate policies 1, 29, and 43 (darkest blue columns) are the strongest for deployment. Policy 1 is a built-in AI in an overpowered car but 29 and 43 are very strong RL policies. Looking at the overall winrate matrix (Appendix Figure 4b) we see that the same conclusion (the three darkest blue columns overall) would have been chosen using all 46 tests. Compressing from 46 tests to 2 presents a massive saving in test time and robustness for future policies and shows RPOSST$_{SEQ}$ can construct small tests to select deployment policies in a real and complex video game.

6 RELATED WORK

The bulk of the work on policy selection in RL focuses on selecting opponents for *training* with self-play algorithms Hernandez et al. [2021]. In that case, diversity is key for training further agents to cooperate Rahman et al. [2022] or beat Liu et al. [2021], McAleer et al. [2022] existing policies. However, the selection of policies as training opponents is often guided by metrics of agent performance computed over the entire population Li et al. [2019], Lanctot et al. [2017], Omidshafiei et al. [2019], Balduzzi et al. [2018] and thus do not reduce the number of test cases (or opponent pairings) needed for assessment.

On the testing side, researchers in complex domains develop procedures for testing skill competency using hand-calibrated Wurman et al. [2022] or randomly generated tests with complex percentile-scoring functions Team et al. [2021]. Our work seeks to automate and target test construction in such scenarios. Complementary work Rowland et al. [2019] treats the computation of a result matrix as a multi-armed bandit problem, each entry represented by one arm. While this method can greatly reduce sampling costs in the presence of low-variance outcomes, it does not generalize

to agents outside its input population, with the testing of a new policy requiring adding extra arms to be estimated from scratch. However, this method could be used in tandem with RPOSST to reduce the samples required to compute A.

Learning to rank methods Oosterhuis and de Rijke [2021], Bruch [2021], Hu et al. [2018] aim to find a function that ranks a set of items (*e.g.*, documents) based on the relevance of a given query, with hopes to generalize to future queries. Indeed, Akiyama et al. [2016] use learning to rank to evaluate action sequences. However, predicting unseen policy performances under this model requires the tuning policies to be the queries, which would produce a ranking of the test cases themselves. Such a result cannot compare across policies, which is our main objective.

Test construction in educational modeling van der Linden [2005] starts from an item bank and a statistical model (*e.g.*, Item Response Theory Embretson et al. [2000]) predicting the probability of answering each item correctly given a student's (unobserved) skill level. That model yields an *information matrix* and then automatic test construction methods, including linear optimization or greedy heuristics, can then build a finite-sized test. By contrast, we do not assume a known model of the response variance or a univariate skill measurement, so a closed-form calculation of information is often infeasible. However, we do empirically compare our optimization approach to the greedy heuristic.

7 CONCLUSION AND FUTURE WORK

RPOSST is, to the best of our knowledge, the first algorithm to directly address test construction for reinforcement learning policies. By leveraging the k-of-N framework, RPOSST provides bounds on the approximation error of the resulting test despite uncertainty over the exact policies that will be evaluated and the desired test case weighting in the future. Thus, RPOSST provides a much needed tool for policy selection in real-world deployment scenarios. An interesting direction for future work is generating the test cases themselves [Marris et al., 2021, Pugh et al., 2016], which is challenging on its own [Balduzzi et al., 2019].

References

Hidehisa Akiyama, Masashi Tsuji, and Shigeto Aramaki. Learning evaluation function for decision making of soccer agents using learning to rank. In *2016 Joint 8th International Conference on Soft Computing and Intelligent Systems (SCIS) and 17th International Symposium on Advanced Intelligent Systems (ISIS)*, pages 239–242. IEEE, 2016.

Jean-Yves Audibert, Sébastien Bubeck, and Rémi Munos. Best arm identification in multi-armed bandits. In *COLT*, pages 41–53. Citeseer, 2010.

David Balduzzi, Karl Tuyls, Julien Perolat, and Thore Graepel. Re-evaluating evaluation. *Advances in Neural Information Processing Systems*, 31, 2018.

David Balduzzi, Marta Garnelo, Yoram Bachrach, Wojciech Czarnecki, Julien Perolat, Max Jaderberg, and Thore Graepel. Open-ended learning in symmetric zero-sum games. In *International Conference on Machine Learning*, pages 434–443. PMLR, 2019.

Nolan Bard, John Hawkin, Jonathan Rubin, and Martin Zinkevich. The annual computer poker competition. *AI Magazine*, 34(2):112–112, 2013.

Noam Brown and Tuomas Sandholm. Superhuman AI for heads-up no-limit poker: Libratus beats top professionals. *Science*, 359(6374):418–424, 2018.

Noam Brown and Tuomas Sandholm. Superhuman AI for multiplayer poker. *Science*, 365(6456):885–890, 2019.

Sebastian Bruch. An alternative cross entropy loss for learning-to-rank. In *Proceedings of the Web Conference 2021*, pages 118–126, 2021.

Neil Burch. *Time and space: Why imperfect information games are hard*. PhD thesis, University of Alberta, 2017.

Abraham Charnes and William W Cooper. Chance-constrained programming. *Management science*, 6(1): 73–79, 1959.

Katherine Chen and Michael Bowling. Tractable objectives for robust policy optimization. *Advances in Neural Information Processing Systems*, 25:2069–2077, 2012.

S.E. Embretson, S.E. Embretson, and S.P. Reise. *Item Response Theory for Psychologists*. Multivariate applications book series. L. Erlbaum Associates, 2000. ISBN 9780805828184.

Meta FAIR, Anton Bakhtin, Noam Brown, Emily Dinan, Gabriele Farina, Colin Flaherty, Daniel Fried, Andrew Goff, Jonathan Gray, Hengyuan Hu, et al. Human-level play in the game of diplomacy by combining language models with strategic reasoning. *Science*, 378(6624): 1067–1074, 2022.

Gabriele Farina, Christian Kroer, and Tuomas Sandholm. Stochastic regret minimization in extensive-form games. In *International Conference on Machine Learning*, pages 3018–3028, 2020.

Yoav Freund and Robert E. Schapire. A decision-theoretic generalization of on-line learning and an application to boosting. *Journal of Computer and System Sciences*, 55 (1):119–139, 1997.

Florian Fuchs, Yunlong Song, Elia Kaufmann, Davide Scaramuzza, and Peter Dürr. Super-human performance in Gran Turismo Sport using deep reinforcement learning. *IEEE Robotics and Automation Letters*, 6(3):4257–4264, 2021. doi: 10.1109/LRA.2021.3064284.

Daniel Hernandez, Kevin Denamganai, Sam Devlin, Spyridon Samothrakis, and James Alfred Walker. A comparison of self-play algorithms under a generalized framework. *IEEE Transactions on Games*, 14(2):221–231, 2021.

Yujing Hu, Qing Da, Anxiang Zeng, Yang Yu, and Yinghui Xu. Reinforcement learning to rank in e-commerce search engine: Formalization, analysis, and application. In *Proceedings of the 24th ACM SIGKDD international conference on knowledge discovery & data mining*, pages 368–377, 2018.

Michael Johanson, Nolan Bard, Neil Burch, and Michael Bowling. Finding optimal abstract strategies in extensive form games. In *26th AAAI Conference on Artificial Intelligence (AAAI-12)*, 2012.

Marc Lanctot, Vinicius Zambaldi, Audrunas Gruslys, Angeliki Lazaridou, Karl Tuyls, Julien Pérolat, David Silver, and Thore Graepel. A unified game-theoretic approach to multiagent reinforcement learning. *Advances in neural information processing systems*, 30, 2017.

Ang Li, Ola Spyra, Sagi Perel, Valentin Dalibard, Max Jaderberg, Chenjie Gu, David Budden, Tim Harley, and Pramod Gupta. A generalized framework for population based training. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 1791–1799, 2019.

Xiangyu Liu, Hangtian Jia, Ying Wen, Yujing Hu, Yingfeng Chen, Changjie Fan, Zhipeng Hu, and Yaodong Yang. Towards unifying behavioral and response diversity for open-ended learning in zero-sum games. *Advances in Neural Information Processing Systems*, 34:941–952, 2021.

Edward Lockhart, Marc Lanctot, Julien Pérolat, Jean-Baptiste Lespiau, Dustin Morrill, Finbarr Timbers, and Karl Tuyls. Computing approximate equilibria in sequential adversarial games by exploitability descent. In *IJCAI 2019*, 2019a.

Edward Lockhart, Marc Lanctot, Julien Pérolat, Jean-Baptiste Lespiau, Dustin Morrill, Finbarr Timbers, and Karl Tuyls. Computing approximate equilibria in sequential adversarial games by exploitability descent. *arXiv preprint arXiv:1903.05614*, 2019b.

Luke Marris, Paul Muller, Marc Lanctot, Karl Tuyls, and Thore Graepel. Multi-agent training beyond zero-sum with correlated equilibrium meta-solvers. In *International Conference on Machine Learning*, pages 7480–7491. PMLR, 2021.

Stephen McAleer, Kevin Wang, John B Lanier, Marc Lanctot, Pierre Baldi, Tuomas Sandholm, and Roy Fox. Anytime psro for two-player zero-sum games. 2022.

Colin McDiarmid. Concentration. In *Probabilistic methods for algorithmic discrete mathematics*, pages 195–248. 1998.

Matej Moravčík, Martin Schmid, Neil Burch, Viliam Lisỳ, Dustin Morrill, Nolan Bard, Trevor Davis, Kevin Waugh, Michael Johanson, and Michael Bowling. Deepstack: Expert-level artificial intelligence in heads-up no-limit poker. *Science*, 356(6337):508–513, 2017.

Shayegan Omidshafiei, Christos Papadimitriou, Georgios Piliouras, Karl Tuyls, Mark Rowland, Jean-Baptiste Lespiau, Wojciech M Czarnecki, Marc Lanctot, Julien Perolat, and Remi Munos. α-rank: Multi-agent evaluation by evolution. *Scientific reports*, 9(1):1–29, 2019.

Harrie Oosterhuis and Maarten de de Rijke. Robust generalization and safe query-specializationin counterfactual learning to rank. In *Proceedings of the Web Conference 2021*, pages 158–170, 2021.

Julien Perolat, Bart De Vylder, Daniel Hennes, Eugene Tarassov, Florian Strub, Vincent de Boer, Paul Muller, Jerome T Connor, Neil Burch, Thomas Anthony, et al. Mastering the game of stratego with model-free multi-agent reinforcement learning. *Science*, 378(6623):990–996, 2022.

Justin K Pugh, Lisa B Soros, and Kenneth O Stanley. Quality diversity: A new frontier for evolutionary computation. *Frontiers in Robotics and AI*, page 40, 2016.

Arrasy Rahman, Elliot Fosong, Ignacio Carlucho, and Stefano V Albrecht. Towards robust ad hoc teamwork agents by creating diverse training teammates. *arXiv preprint arXiv:2207.14138*, 2022.

Mark Rowland, Shayegan Omidshafiei, Karl Tuyls, Julien Perolat, Michal Valko, Georgios Piliouras, and Remi Munos. Multiagent evaluation under incomplete information. *NeurIPS*, 32, 2019.

David Silver, Aja Huang, Chris J. Maddison, Arthur Guez, Laurent Sifre, George van den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, Sander Dieleman, Dominik Grewe, John Nham, Nal Kalchbrenner, Ilya Sutskever, Timothy Lillicrap, Madeleine Leach, Koray Kavukcuoglu, Thore Graepel, and Demis Hassabis. Mastering the game of go with deep neural networks and tree search. *Nature*, 529(7587): 484–489, 2016.

Yunlong Song, HaoChih Lin, Elia Kaufmann, Peter Dürr, and Davide Scaramuzza. Autonomous Overtaking in Gran Turismo Sport Using Curriculum Reinforcement Learning. In *ICRA*, 2021.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

Oskari Tammelin. Solving large imperfect information games using cfr+. *arXiv preprint arXiv:1407.5042*, 2014.

Oskari Tammelin, Neil Burch, Michael Johanson, and Michael Bowling. Solving heads-up limit texas hold'em. In *24th International Joint Conference on Artificial Intelligence (IJCAI 2015)*, 2015.

Open Ended Learning Team, Adam Stooke, Anuj Mahajan, Catarina Barros, Charlie Deck, Jakob Bauer, Jakub Sygnowski, Maja Trebacz, Max Jaderberg, Michaël Mathieu, Nat McAleese, Nathalie Bradley-Schmieg, Nathaniel Wong, Nicolas Porcel, Roberta Raileanu, Steph Hughes-Fitt, Valentin Dalibard, and Wojciech Marian Czarnecki. Open-ended learning leads to generally capable agents. *ArXiv Pre-Print*, abs/2107.12808, 2021. URL https://arxiv.org/abs/2107.12808.

Wim J. van der Linden. *Linear models for optimal test design*. Springer, 2005.

Oriol Vinyals, Igor Babuschkin, Wojciech M. Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H. Choi, Richard Powell, Timo Ewalds, Petko Georgiev, et al. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *Nature*, pages 1–5, 2019.

Peter R Wurman, Samuel Barrett, Kenta Kawamoto, James MacGlashan, Kaushik Subramanian, Thomas J Walsh, Roberto Capobianco, Alisa Devlic, Franziska Eckert, Florian Fuchs, et al. Outracing champion gran turismo drivers with deep reinforcement learning. *Nature*, 602 (7896):223–228, 2022.