Invariance Learning in Deep Neural Networks with Differentiable Laplace Approximations

Abstract

Data augmentation is commonly applied to improve performance of deep learning by enforcing the knowledge that certain transformations on the input preserve the output. Currently, the used data augmentation is chosen by human effort and costly cross-validation, which makes it cumbersome to apply to new datasets. We develop a convenient gradient-based method for selecting the data augmentation without validation data and during training of a deep neural network. Our approach relies on phrasing data augmentation as an invariance in the prior distribution and learning it using Bayesian model selection, which has been shown to work in Gaussian processes, but not yet for deep neural networks. We propose a differentiable Kronecker-factored Laplace approximation to the marginal likelihood as our objective, which can be optimised without human supervision or validation data. We show that our method can successfully recover invariances present in the data, and that this improves generalisation and data efficiency on image datasets.

1   Introduction

Data augmentation is a commonly used machine learning technique that is essential to high-performing deep learning and computer vision systems. It aims to obtain a model that is *invariant* to a set or distribution of transformations, by fitting a model with inputs that are transformed in a way that is known to leave the output class unchanged. This procedure can be regarded as artificially creating more data, and is well known to increase generalisation performance and data efficiency. Yet, choosing the right transformations is an expensive and task-specific process that relies on domain knowledge and human effort, as well as trial-and-error through cross-validation. This can quickly become intractable when many parameters are considered, particularly if they are continuous, because each setting requires training a model to convergence.

We aim to make selecting suitable transformations easier, by learning them via gradient descent. Our approach is inspired by the procedure of Van der Wilk et al. (2018), which casts learning invariances and data augmentations as a Bayesian model selection problem. This view suggests selecting invariances by maximising the *marginal likelihood* with gradient-based optimisation. While this approach was successful in Gaussian process models, it has not yet been demonstrated in deep neural networks, where the marginal likelihood is harder to approximate.

To circumvent this problem, we built upon the scalable Laplace approximation to the marginal likelihood developed by Immer et al. (2021a), who recently showed that maximising it can successfully select neural network hyperparameters, such as architectures. We extend their method to enable optimisation of complex hyperparameters that control invariances in deep neural networks. To that end, we propose an efficient and differentiable Kronecker-factored Laplace approximation for invariant neural networks and a method to obtain stochastic gradients with respect to invariance parameters, which is also useful for optimising other complex hyperparameters.

Step A: sample S augmented data points/sets dependent on invariance parameter η (here controls max rotation)

Step B: obtain invariant deep neural network by averaging over augmentation samples $\mathbf{x}'$ from $p(\mathbf{x}'|\mathbf{x}, \eta)$

Step C: Approximate and differentiate marginal likelihood wrt. η to optimize invariance during training

Figure 1: Illustration of our approach on a data set with rotational invariance. Steps A and B allow to define a Bayesian neural network with a likelihood dependant on invariance parameter η (van der Wilk et al., 2018). Our contributions enable tractable marginal likelihood estimation and differentiation during training, as illustrated in Step C. The right-most figure shows the posterior predictive of our Bayesian neural network after learning the correct invariance present in the data.

Our approach is illustrated in Fig. 1. We specify invariances as a distribution on perturbations of the network's input, similar to data augmentation (Step A). Samples are taken from the distribution and the model output is averaged (Step B), which yields a Bayesian neural network with likelihood dependent on the perturbations (Nabarro et al., 2021). We derive a marginal likelihood approximation for invariant models, and show how to efficiently compute its gradients with respect to the invariance parameters (Step C). By approximating the marginal likelihood, we can differentiably learn invariances, without validation data.

We demonstrate experimentally that our method can differentiably learn useful distributions over affine invariances on various versions of image classification data sets MNIST, FashionMNIST and CIFAR-10, without validation data. This ensures models are robust to similar data perturbations, without the effort required for selecting classical data augmentations. On original datasets, this improves test performance with up to 8-10 percentage points for ResNets on CIFAR-10. Furthermore, we show that our method can greatly improve data efficiency, sometimes more than two-fold on random subsets of image classification data sets. Our work strengthens how Bayesian methods can be useful for deep learning beyond predictive uncertainty estimation.

2   Related Work

Invariances in deep learning.   Since the inception of the convolutional neural network (CNN) (Fukushima and Miyake, 1982; LeCun et al., 1998), building invariances and equivariances into deep learning models has drastically increased data efficiency and generalisation (Cohen et al., 2018; Brandstetter et al., 2021), for instance, on image classification (Cohen and Welling, 2016), molecular dynamics (Batzner et al., 2021), and reinforcement learning (van der Pol et al., 2020). However, these approaches require knowing the invariances a priori. In this work, on the other hand, we aim to automatically learn the correct type and amount of invariance from data without supervision.

Learning invariances.   Learning invariances from data is hard, because symmetries define constraints on the functions a network can represent, and therefore do not improve data fit according to the training loss, even if they would lead to better generalisation on test data. Some methods have therefore proposed to learn invariances or data augmentation by estimating gradients on the validation loss. For example, AutoAugment (Cubuk et al., 2018) learns data augmentation using policy gradients, Lorraine et al. (2020) use the implicit function theorem, and Zhou et al. (2020) phrase the problem as meta-learning. Such approaches require validation sets of sufficient size to prevent overfitting (Lorraine et al., 2020). Here, we tackle the problem of learning invariances when validation data is not available.

Validation-free invariance learning.   When casting invariance learning as a Bayesian model selection problem, we can select helpful invariances using the marginal likelihood of the model using training data alone. This has been successfully demonstrated in Gaussian processes (van der Wilk et al., 2018) and in the weight-space of single-layer neural networks (van der Ouderaa and van der Wilk, 2021). To scale this approach to deep networks, Schwöbel et al. (2022) attempt to

use a marginal likelihood that is only computed in the last layer. While the latter was successful for small neural networks, it failed to learn invariances on more complex datasets that require deep neural networks, likely due to known limitations of last-layer approaches (Ober et al., 2021; van Amersfoort et al., 2021). Augerino (Benton et al., 2020) is an alternative to Bayesian model selection that works for deep learning by regularising invariances to increase during training. This approach depends on the chosen parameterisation of the invariance and may still require a validation set to tune the regularisation strength. In contrast, our proposed method uses a Bayesian marginal likelihood estimate in deep neural networks that is parameterisation invariant and improves performance. The main differences between our proposed method and the alternatives are summarised in App. A.

Bayesian model selection for deep learning. Marginal likelihood approximations have recently enabled gradient-based hyperparameter optimisation for deep neural networks (Immer et al., 2021a; Ober and Aitchison, 2021; Antorán et al., 2022) and overcome issues with last-layer approaches (Ober et al., 2021; Daxberger et al., 2021). Laplace approximations with structured Hessian approximations, such as KFAC (Martens and Grosse, 2015), or linearisation have been shown to improve generalisation, for example, by optimising weight regularisation (Immer et al., 2021a; Daxberger et al., 2021) and learning length-scales of convolutions (Antorán et al., 2022). We extend scalable Laplace approximations to enable gradient-based optimisation of more complex hyperparameters like invariances.

3 Background

We consider a supervised learning task with data set $\mathcal{D} = \{(\mathbf{x}_n, \mathbf{y}_n)\}_{n=1}^N$ consisting of N inputs $\mathbf{x} \in \mathbb{R}^D$ and targets $\mathbf{y} \in \mathbb{R}^C$. Our goal is to learn the function $\mathbf{f} : \mathbb{R}^D \to \mathbb{R}^C$ that relates the inputs and outputs, which we represent as a neural network $\mathbf{f}(\mathbf{x}; \boldsymbol{\theta})$ with parameters $\boldsymbol{\theta}$. We control which solutions for $\mathbf{f}$ are preferred over others (i.e. the *inductive bias*) with hyperparameters $\mathcal{H}$, which parameterise the prior over $\boldsymbol{\theta}$ and $\mathbf{f}$. Invariance is a particularly helpful inductive bias that constrains the output of $\mathbf{f}$ to remain similar for certain transformations of the input $\mathbf{x}$, which can improve generalisation by allowing a single datapoint to inform predictions for a wider range of inputs. Our goal is to learn useful invariances together with the network weights.

3.1 Parameterising Invariance

To construct and parameterise invariant functions, we consider a local invariance that intuitively requires the function to not change "too much" in response to transformed inputs. To obtain such an invariant function $\hat{\mathbf{f}}$, we average an unconstrained function $\mathbf{f}$ over a perturbation distribution $p(\mathbf{x}'|\mathbf{x}, \boldsymbol{\eta})$. In practice, we sample $\mathbf{x}'$ by reparameterising $\boldsymbol{\epsilon} \sim p(\boldsymbol{\epsilon})$ with a differentiable function $\mathbf{g}$ (van der Wilk et al., 2018; Benton et al., 2020):

$$\hat{\mathbf{f}}(\mathbf{x}; \boldsymbol{\theta}, \boldsymbol{\eta}) = \mathbb{E}_{p(\mathbf{x}'|\mathbf{x}, \boldsymbol{\eta})}[\mathbf{f}(\mathbf{x}'; \boldsymbol{\theta})] = \mathbb{E}_{p(\boldsymbol{\epsilon})}[\mathbf{f}(\mathbf{g}(\mathbf{x}, \boldsymbol{\epsilon}; \boldsymbol{\eta}), \boldsymbol{\theta})], \tag{1}$$

where $\hat{\mathbf{f}}$ is differentiable in the parameters $\boldsymbol{\eta}$ that control the perturbation distribution, and therefore the invariance. When the perturbation distribution is uniform on the orbit of a group, we recover exact invariance in $\hat{\mathbf{f}}$ (Kondor, 2008; Ginsbourger et al., 2016). The perturbation distribution resembles data augmentation and is also used at test time (because $\hat{\mathbf{f}}$ depends on it). Because the unconstrained function $\mathbf{f}$ is a neural network, we refer to $\hat{\mathbf{f}}$ as **invariant neural network**.

Given that we can parameterise a suitable data augmentation distribution $p(\mathbf{x}'|\mathbf{x}, \boldsymbol{\eta})$, we can learn invariances in arbitrary domains or group structures. What parameterisation works best in practice remains a research question. In our experiments, we consider a combination of uniform distributions and corresponding parameters $\boldsymbol{\eta} \in \mathbb{R}^6$ over 6 generator matrices that define a probability density over the group of affine transformations, similar to Benton et al. (2020) and detailed in App. B.

Finding invariance parameters $\boldsymbol{\eta}$ is hard because $\hat{\mathbf{f}}$ is a constrained version of $\mathbf{f}$ and, especially for flexible models, this cannot improve the data fit according to the standard training loss. To overcome this, we propose to use Bayesian inference which provides a convenient framework to optimise invariance parameters with gradients, jointly with network parameters, without extra validation data.

3.2 Bayesian Model Selection

Bayesian inference prescribes how unknowns, such as invariance parameters, should be determined from data. To infer hyperparameters $\mathcal{H}$ from data, we are interested in the their posterior, $p(\mathcal{H}|\mathcal{D}) \propto$

$p(\mathcal{D}|\mathcal{H})p(\mathcal{H})$ (MacKay, 2003). Because this posterior is intractable, type II maximum likelihood (ML-II) is often used instead, which obtains a point estimate $\mathcal{H}^*$ for the optimal hyperparameters according to the likelihood $p(\mathcal{D}|\mathcal{H})$, the so-called *marginal likelihood*.

ML-II is routinely used in Gaussian processes (Rasmussen and Williams, 2006, § 5.2), and trades off model simplicity with data fit (Rasmussen and Ghahramani, 2001). There are also strong relations to quantities from other statistical frameworks, like cross-validation (Fong and Holmes, 2020), Minimum Description Length (Grünwald, 2007), and generalisation error bounds (Germain et al., 2016). Van der Wilk et al. (2018) showed its usefulness for selecting invariances, and elaborated on the mechanism by which it works. The main advantage of the marginal likelihood,

$$p(\mathcal{D}|\mathcal{H}) = \int p(\mathcal{D}|\boldsymbol{\theta},\mathcal{H})p(\boldsymbol{\theta}|\mathcal{H})\,\mathrm{d}\boldsymbol{\theta} = \int \prod_{n=1}^N p(\mathbf{y}_n|\mathbf{f}(\mathbf{x}_n;\boldsymbol{\theta}),\mathcal{H})p(\boldsymbol{\theta}|\mathcal{H})\,\mathrm{d}\boldsymbol{\theta}\,, \tag{2}$$

is that it can be computed from the training data alone and optimised with gradients. In our work, the integration is over the neural network parameters and requires particularly scalable approximations.

3.3 Bayesian Model Selection for Deep Learning

Computing the marginal likelihood for neural networks involves intractable integrals. The Laplace approximation (Laplace, 1774; MacKay, 2003, § 27) offers a solution by approximating the log joint of the parameters and data, $p(\mathcal{D},\boldsymbol{\theta}|\mathcal{H})$, with a second-order Taylor expansion around a mode $\boldsymbol{\theta}_*$:

$$\log p(\mathcal{D}|\mathcal{H}) \approx \log p(\mathcal{D},\boldsymbol{\theta}_*|\mathcal{H}) - \tfrac{1}{2}\log\left|\tfrac{1}{2\pi}\mathbf{H}_{\boldsymbol{\theta}_*}\right|\,, \tag{3}$$

where the first term decomposes into the log likelihood, a sum over data points, and the log prior, both of which are cheap and easy to evaluate and correspond to a typical training loss evaluated at a mode $\boldsymbol{\theta}_*$. The second term depends on the log determinant of the log joint Hessian at the same mode

$$\mathbf{H}_{\boldsymbol{\theta}_*} \stackrel{\text{def}}{=} -\nabla^2_{\boldsymbol{\theta}}\log p(\mathcal{D},\boldsymbol{\theta}|\mathcal{H})|_{\boldsymbol{\theta}=\boldsymbol{\theta}_*} = \mathbf{H}^{\text{NLL}}_{\boldsymbol{\theta}_*} - \nabla^2_{\boldsymbol{\theta}}\log p(\boldsymbol{\theta}|\mathcal{H})|_{\boldsymbol{\theta}=\boldsymbol{\theta}_*}\,, \tag{4}$$

where $\mathbf{H}^{\text{NLL}}_{\boldsymbol{\theta}_*}$ denotes the Hessian of the negative log likelihood. This approach allows to estimate the marginal likelihood using a MAP estimate $\boldsymbol{\theta}_*$ of the weights, and its local curvature $\mathbf{H}_{\boldsymbol{\theta}_*}$.

To circumvent the high cost of estimating the full Hessian, structured generalised Gauss-Newton (GGN) approximations are preferred for model selection in deep learning, as also in optimisation (Martens, 2020; Bottou, 2010). Immer et al. (2021a) recently demonstrated successful hyperparameter and architecture selection with such approximations. Further, they observe empirically that their algorithm does not require to be at a mode $\boldsymbol{\theta}_*$, which allows for interleaved gradient-based optimisation of parameters and hyperparameters during training. With the Jacobian matrix $\mathbf{J}_{\boldsymbol{\theta}}(\mathbf{x}) \stackrel{\text{def}}{=} \frac{\partial \mathbf{f}(\mathbf{x};\boldsymbol{\theta})}{\partial \boldsymbol{\theta}} \in \mathbb{R}^{C\times P}$ of the network output given input $\mathbf{x}$ w.r.t. parameters, and Hessian of the log likelihood w.r.t. network outputs $\boldsymbol{\Lambda}(\mathbf{f}) = -\nabla^2_{\mathbf{f}}\log p(\mathbf{y}|\mathbf{f})$, the GGN simplifies the negative-log-likelihood-dependant term of the Hessian:

$$\mathbf{H}^{\text{NLL}}_{\boldsymbol{\theta}} \approx \mathbf{H}^{\text{GGN}}_{\boldsymbol{\theta}} \stackrel{\text{def}}{=} \sum_{n=1}^N \mathbf{J}_{\boldsymbol{\theta}}(\mathbf{x}_n)^\mathsf{T}\boldsymbol{\Lambda}(\mathbf{f}(\mathbf{x}_n;\boldsymbol{\theta}))\mathbf{J}_{\boldsymbol{\theta}}(\mathbf{x}_n). \tag{5}$$

Here, we assume that $\mathbf{f}$ forms the natural parameters of an exponential family likelihood function (Murphy, 2012). In classification, for example, $\mathbf{f}$ are the logits. We refer to the resulting approximations as Laplace-GGN. To overcome the still intractable quadratic size of $\mathbf{H}^{\text{GGN}}_{\boldsymbol{\theta}}$ in P, Immer et al. (2021a) use structured approximations like KFAC (Martens and Grosse, 2015). Cheaper approximations, such as diagonal ones, often compromise accuracy (App. F; Daxberger et al., 2021).

3.4 Kronecker-Factored Gauss-Newton Approximation (KFAC)

Kronecker-factored approximations to the Gauss-Newton, such as KFAC, are commonly used for Laplace approximations as they currently seem to provide the optimal trade-off between performance and complexity (Ritter et al., 2018; Daxberger et al., 2021). KFAC is a block-diagonal approximation to the Gauss-Newton matrix $\mathbf{H}^{\text{GGN}}_{\boldsymbol{\theta}}$ where each block corresponds to a layer in the neural network (Martens and Grosse, 2015; Botev et al., 2017). It is particularly efficient because each blocks is represented as two Kronecker factors instead of one dense matrix. For example, the GGN block of a layer with $D \times G$ parameters, e.g. a fully-connected layer connecting D to G neurons, would have quadratic memory complexity $\mathcal{O}(D^2G^2)$ while the corresponding Kronecker approximation of KFAC is in $\mathcal{O}(D^2 + G^2)$ and is therefore even tractable for wide neural networks.

Mathematically, KFAC approximates the GGN of the lth block of the neural network parameters by enforcing a Kronecker factorisation across data points. This would only be exact for a single data point $\mathbf{x}_n$, for which we can write the GGN block corresponding to the parameters of the lth layer as

$$\mathbf{H}_{l,n}^{\mathrm{GGN}} = [\mathbf{a}_{l,n} \otimes \mathbf{g}_{l,n}]\mathbf{\Lambda}_n[\mathbf{a}_{l,n} \otimes \mathbf{g}_{l,n}]^{\mathsf{T}} = [\mathbf{a}_{l,n}\mathbf{a}_{l,n}^{\mathsf{T}}] \otimes [\mathbf{g}_{l,n}\mathbf{\Lambda}_n\mathbf{g}_{l,n}^{\mathsf{T}}] \stackrel{\mathrm{def}}{=} \mathbf{A}_{l,n} \otimes \mathbf{G}_{l,n}, \quad (6)$$

where $\mathbf{a}_{l,n} \in \mathbb{R}^{D_l}$ is the input to the lth layer for data point $\mathbf{x}_n$, $\mathbf{g}_{l,n} \in \mathbb{R}^{G_l \times C}$ is the transposed Jacobian of the network output with respect to the output of the lth layer for $\mathbf{x}_n$, and $\mathbf{\Lambda}_n = \mathbf{\Lambda}(\mathbf{f}(\mathbf{x}_n; \boldsymbol{\theta}))$. Thus, the factors in Eq. 6 are the Jacobian terms as in the GGN (Eq. 5) but only for the lth layer, i.e. $\mathbf{J}_{\boldsymbol{\theta}_l}(\mathbf{x}_n)^{\mathsf{T}} = \mathbf{a}_{l,n} \otimes \mathbf{g}_{l,n}$. KFAC then approximates the sum over N data points by summing up the Kronecker factors individually instead of breaking the Kronecker-factored structure:

$$\mathbf{H}_l^{\mathrm{GGN}} = \sum_{n=1}^{N}[\mathbf{a}_{l,n}\mathbf{a}_{l,n}^{\mathsf{T}}] \otimes [\mathbf{g}_{l,n}\mathbf{\Lambda}_n\mathbf{g}_{l,n}^{\mathsf{T}}] \approx \frac{1}{N}\left[\underbrace{\sum_{n=1}^{N}\mathbf{a}_{l,n}\mathbf{a}_{l,n}^{\mathsf{T}}}_{\stackrel{\mathrm{def}}{=}\mathbf{A}_l}\right] \otimes \left[\underbrace{\sum_{n=1}^{N}\mathbf{g}_{l,n}\mathbf{\Lambda}_n\mathbf{g}_{l,n}^{\mathsf{T}}}_{\stackrel{\mathrm{def}}{=}\mathbf{G}_l}\right], \quad (7)$$

where $\mathbf{A}_l \in \mathbb{R}^{D_l \times D_l}$ and $\mathbf{G}_l \in \mathbb{R}^{G_l \times G_l}$ can be understood as the uncentered covariance over N data points of the inputs to the lth layer and the Jacobians wrt. the output of the lth layer, respectively. For a single-layer model, i.e. a linear model, KFAC would be exact.

4 Invariance Learning with Differentiable Laplace Approximations

We propose a Laplace-GGN approximation to the marginal likelihood for invariant neural networks and enable gradient-based optimisation of their invariance parameters during training, without the use of validation data (see Fig. 1 for a high-level overview). In our approach, we integrate the augmentation distribution $p(\mathbf{x}'|\mathbf{x}, \boldsymbol{\eta})$ into a Bayesian neural network model such that the marginal likelihood directly depends on the invariance parameters $\boldsymbol{\eta} \in \mathcal{H}$. In particular, this is due to a modified likelihood function $p(\mathbf{y}|\hat{\mathbf{f}}(\mathbf{x}; \boldsymbol{\theta}, \boldsymbol{\eta}), \mathcal{H})$ (c.f. Nabarro et al., 2021). In principle, this model enables optimisation of the invariance parameters $\boldsymbol{\eta}$ using gradient ascent on the log marginal likelihood,

$$\boldsymbol{\eta} \leftarrow \boldsymbol{\eta} + \nabla_{\boldsymbol{\eta}} \log p(\mathcal{D}|\mathcal{H} = \{\boldsymbol{\eta}, \mathcal{M}\}), \quad (8)$$

where $\mathcal{M} = \mathcal{H} \setminus \{\boldsymbol{\eta}\}$ are remaining hyperparameters, such as regularisation strength or model architecture. However, the tractable Laplace-GGN and KFAC approximations are not available for invariant Bayesian neural networks, which prohibits straightforward application of the update in Eq. 8 using the methods described in Sec. 3.

In the following, we extend the Laplace-GGN and KFAC approximations to invariant neural networks (Secs. 4.1 and 4.2), which enables optimising the log marginal likelihood in parallel to the neural network parameters, as in Immer et al. (2021a). However, their algorithm has an intractable memory complexity for computing the gradients w.r.t. invariance parameters or other complex hyperparameters that act on the neural network function $\mathbf{f}$ directly. In practice, they only considered gradient-based optimisation of hyperparameters that act linearly on the Hessian $\mathbf{H}_{\boldsymbol{\theta}}$, for example regularisation strength and observation noise. In Sec. 4.3, we lift this constraint by proposing a method to obtain gradients w.r.t. complex hyperparameters without memory overhead. The final algorithm and a discussion of approximations for invariance learning are detailed in Apps. E and F.

4.1 Laplace-GGN for an Invariant Neural Network

To define the Laplace-GGN approximation to the log marginal likelihood, the hyperparameter objective, we need to extend the GGN to invariant neural networks. For an invariant neural network, the log marginal likelihood approximation is given by

$$\log p(\mathcal{D}|\boldsymbol{\eta}, \mathcal{M}) \approx \sum_{n=1}^{N} \log p(\mathbf{y}_n|\hat{\mathbf{f}}(\mathbf{x}_n; \boldsymbol{\theta}, \boldsymbol{\eta}), \mathcal{M}) + \log p(\boldsymbol{\theta}_*|\mathcal{M}) - \frac{1}{2}\log|\frac{1}{2\pi}\hat{\mathbf{H}}_{\boldsymbol{\theta}_*}^{\mathrm{GGN}}(\boldsymbol{\eta})|, \quad (9)$$

where the first two terms constitute the training loss of the invariant neural network and correspond to the log joint as in the vanilla Laplace approximation in Eq. 3 and the last term is the Gauss-Newton approximation $\hat{\mathbf{H}}_{\boldsymbol{\theta}_*}^{\mathrm{GGN}}$ of the invariant neural network $\hat{\mathbf{f}}$, which we derive below. The first and last term depend on the invariance parameter $\boldsymbol{\eta}$ that we want to learn and differentiate with respect to.

With Eq. 1, the first term can be approximated with S Monte Carlo samples $\boldsymbol{\epsilon}_{1,...,S} \sim p(\boldsymbol{\epsilon})$ as

$$\sum_{n=1}^{N} \log p(\mathbf{y}_n|\hat{\mathbf{f}}(\mathbf{x}_n; \boldsymbol{\theta}, \boldsymbol{\eta}), \mathcal{M}) \approx \sum_{n=1}^{N} \log p(\mathbf{y}_n|\frac{1}{S}\sum_s \mathbf{f}(\mathbf{g}(\mathbf{x}_n, \boldsymbol{\epsilon}_s; \boldsymbol{\eta}), \boldsymbol{\theta}), \mathcal{M}), \quad (10)$$

where we sample $\boldsymbol{\epsilon}_s$ independently per data point to reduce correlation. We can obtain a stochastic gradient w.r.t. $\boldsymbol{\eta}$ by sampling a mini-batch of $M \leq N$ data but it is not possible to batch over the S augmentations that parameterise the likelihood function. Both runtime and memory complexity are therefore increased by a factor of S. For a subset of data and $10 \leq S \leq 100$ perturbation samples, the gradient can be computed using backpropagation as in Benton et al. (2020).

The last term requires derivation of the Gauss-Newton approximation for an invariant neural network. Interchanging derivative and expectation, its Jacobian can be written as

$$\hat{\mathbf{J}}_{\boldsymbol{\theta}}(\mathbf{x}; \boldsymbol{\eta}) \stackrel{\text{def}}{=} \frac{\partial}{\partial \boldsymbol{\theta}} \mathbb{E}_{p(\boldsymbol{\epsilon})}[\mathbf{f}(\mathbf{g}(\mathbf{x}, \boldsymbol{\epsilon}; \boldsymbol{\eta}), \boldsymbol{\theta})] = \mathbb{E}_{p(\boldsymbol{\epsilon})}[\mathbf{J}_{\boldsymbol{\theta}}(\mathbf{g}(\mathbf{x}, \boldsymbol{\epsilon}; \boldsymbol{\eta}))], \tag{11}$$

which means that it can be estimated by averaging Jacobians and depends on the invariance parameter $\boldsymbol{\eta}$. The GGN of an invariant neural network can then be written and estimated with MC samples:

$$\hat{\mathbf{H}}_{\boldsymbol{\theta}}^{\text{GGN}}(\boldsymbol{\eta}) \stackrel{\text{def}}{=} \sum_{n=1}^{N} \hat{\mathbf{J}}_{\boldsymbol{\theta}}(\mathbf{x}_n; \boldsymbol{\eta})^{\mathsf{T}} \boldsymbol{\Lambda}(\hat{\mathbf{f}}(\mathbf{x}_n; \boldsymbol{\theta}, \boldsymbol{\eta})) \hat{\mathbf{J}}_{\boldsymbol{\theta}}(\mathbf{x}_n; \boldsymbol{\eta}) \tag{12}$$

$$= \sum_{n=1}^{N} \left[\frac{1}{S} \sum_s \mathbf{J}_{\boldsymbol{\theta}}(\mathbf{g}(\mathbf{x}_n, \boldsymbol{\epsilon}_s; \boldsymbol{\eta})) \right]^{\mathsf{T}} \boldsymbol{\Lambda} \left(\frac{1}{S} \sum_s \mathbf{f}(\mathbf{g}(\mathbf{x}_n, \boldsymbol{\epsilon}_s; \boldsymbol{\eta})) \right) \left[\frac{1}{S} \sum_s \mathbf{J}_{\boldsymbol{\theta}}(\mathbf{g}(\mathbf{x}_n, \boldsymbol{\epsilon}_s; \boldsymbol{\eta})) \right]$$

where $\boldsymbol{\Lambda}(\hat{\mathbf{f}})$ denotes the Hessian of the log-likelihood function w.r.t. $\hat{\mathbf{f}}$ (Eq. 5) and the GGN depends explicitly on the augmentation parameters $\boldsymbol{\eta}$. The GGN for an invariant model requires MC-estimates for the Jacobians and loss Hessians individually. Averaging the GGN over the augmentation samples, which corresponds to data augmentation in an improper Bayesian model (Wenzel et al., 2020), would thus be incorrect. Like for the first term, computing the GGN of an invariant model increases the runtime by a factor of S. Finally, the Laplace-GGN is obtained by computing the log determinant.

The Laplace-GGN approximation derived here already allows to learn small invariant neural networks with few layers and small datasets by automatic differentiation. For example, this is tractable for the classification example illustrated in Fig. 1. However, *computing* the log determinant of the GGN has a cubic complexity in the number of parameters P and is therefore intractable for deep neural networks on larger datasets. To enable its estimation, we extend KFAC to invariant neural networks in Sec. 4.2. Further, *differentiating* the log determinant has intractable memory complexity because it does not allow for a stochastic gradient but requires construction of a computational graph for the entire GGN approximation. This is a key limitation of the method proposed by Immer et al. (2021a) for optimising complex hyperparameters, for which we provide a solution in Sec. 4.3.

4.2 Extending KFAC to Invariant Neural Networks

Computing KFAC as described in Sec. 3 for an invariant neural network would not preserve the Kronecker structure and therefore be intractable for deep neural networks due to the quadratic cost in the numbers of parameters per layer. In particular in Eq. 6, KFAC uses the fact that the Jacobian w.r.t. the parameters of the lth layer, $\mathbf{J}_{\boldsymbol{\theta}_l}(\mathbf{x}_n)$ can be written as the Kronecker product $\mathbf{a}_{l,n} \otimes \mathbf{g}_{l,n}$. For an invariant neural network, the Kronecker structure cannot be maintained because of the expectation over perturbed data points $\mathbf{x}'$ in the MC estimation

$$\hat{\mathbf{J}}_{\boldsymbol{\theta}_l}(\mathbf{x}_n, \boldsymbol{\eta}) = \mathbb{E}_{p(\mathbf{x}'_n | \mathbf{x}_n, \boldsymbol{\eta})}[\mathbf{a}'_{l,n} \otimes \mathbf{g}'_{l,n}] \approx \frac{1}{S} \sum_s [\mathbf{a}_{l,n}^{(s)} \otimes \mathbf{g}_{l,n}^{(s)}], \tag{13}$$

where $\mathbf{a}', \mathbf{g}'$ indicate the dependency on $\mathbf{x}'$ and $\mathbf{a}^{(s)}, \mathbf{g}^{(s)}$ depend on the sth sample $\mathbf{x}_s = \mathbf{g}(\mathbf{x}, \boldsymbol{\epsilon}_s; \boldsymbol{\eta})$. In general, the sum of Kronecker products does not allow for efficient computation and requires evaluating the products, which is intractable as it requires $\mathcal{O}(D_l^2 G_l^2)$ instead of $\mathcal{O}(D_l^2 + G_l^2)$ memory.

Similar to the idea underlying KFAC itself (Martens and Grosse, 2015), we enforce the efficient Kronecker-factored structure by approximating the sum of a Kronecker product as a Kronecker product of sums, which also underlies extensions to convolutional layers (Grosse and Martens, 2016). In particular, we approximate the GGN of the lth layer of the invariant neural network as

$$\hat{\mathbf{H}}_{l,n}^{\text{GGN}} = \mathbb{E}[\mathbf{a}'_{l,n} \otimes \mathbf{g}'_{l,n}] \boldsymbol{\Lambda}(\hat{\mathbf{f}}_n) \mathbb{E}[\mathbf{a}'_{l,n} \otimes \mathbf{g}'_{l,n}]^{\mathsf{T}} \approx \frac{1}{S} \sum_s [\mathbf{a}_{l,n}^{(s)} \otimes \mathbf{g}_{l,n}^{(s)}] \boldsymbol{\Lambda}(\hat{\mathbf{f}}_n) \frac{1}{S} \sum_s [\mathbf{a}_{l,n}^{(s)} \otimes \mathbf{g}_{l,n}^{(s)}]$$

$$\approx \frac{1}{S^4} \left[\sum_s [\mathbf{a}_{l,n}^{(s)}] \sum_s [\mathbf{a}_{l,n}^{(s)}]^{\mathsf{T}} \right] \otimes \left[\sum_s [\mathbf{g}_{l,n}^{(s)}] \boldsymbol{\Lambda}(\frac{1}{S} \sum_s \mathbf{f}_n^{(s)}) \sum_s [\mathbf{g}_{l,n}^{(s)}]^{\mathsf{T}} \right]. \tag{14}$$

To compute the full KFAC, we then accumulate the Kronecker factors for the lth layer, $\hat{\mathbf{A}}_{l,n}$ and $\hat{\mathbf{G}}_{l,n}$, of the invariant neural network to $\hat{\mathbf{A}}_l$ and $\hat{\mathbf{G}}_l$ as in Eq. 7 for vanilla KFAC. Like vanilla KFAC, our approximation for invariant models remains exact for linear models.

Figure 2: Trajectories of invariance parameters $\boldsymbol{\eta} = [\eta_1, \eta_2, ..., \eta_6]^T$ over training epochs for different versions of the MNIST dataset. From each distribution, two sampled transformations are represented as flow fields with arrow lengths scaled to pixel movement. The model automatically learns the correct type and amount of invariance dependent on the observed training data.

The log determinant required for the marginal likelihood approximation can be computed from $\hat{\mathbf{G}}_l$, $\hat{\mathbf{A}}_l$ individually (Immer et al., 2021a) and has a complexity of $\mathcal{O}(D_l^3 + G_l^3)$ as opposed to the intractable $\mathcal{O}(D_l^3 G_l^3)$. This enables us to apply our method to deep invariant neural networks with widths of order 10^4 like vanilla KFAC. We discuss computational complexities in depth in App. C. We note that KFAC for invariant neural networks could further be of independent interest for second-order optimisation and inference (Martens and Grosse, 2015; Osawa et al., 2020; Zhang et al., 2018).

4.3 Efficient Gradient Estimation of the Laplace-GGN w.r.t. Complex Hyperparameters

Automatic differentiation (AD) of the log determinant term in the Laplace-GGN w.r.t. complex hyperparameters, such as invariances, has an intractable memory complexity. Here, we propose a method to estimate the gradient of the log determinant in the Laplace-GGN without memory overhead. For AD, the *memory* complexity is equivalent to the *runtime* complexity of computing the log determinant, which is at least $\mathcal{O}(NP)$, the cost of training a deep neural network for one epoch. Such computation is only tractable due to batching, e.g. for standard training losses, and otherwise would require several terabytes of memory for deep neural networks. However, the log determinant does not allow for a batched gradient and therefore AD requires the storing the full training data pass.

Our approach to reduce the memory complexity relies on computing a vector-Jacobian product where both the vector and the Jacobian can be estimated from batches of data. Mathematically, the problem reduces to differentiation of the log determinant of a sum of square matrices w.r.t. hyperparameter $\boldsymbol{\eta}$, i.e. $\frac{\partial}{\partial \boldsymbol{\eta}} \log |\mathbf{H}(\boldsymbol{\eta})|$ with $\mathbf{H}(\boldsymbol{\eta}) = \sum_n \mathbf{H}_n(\boldsymbol{\eta}) \in \mathbb{R}^{D \times D}$. For a positive definite matrix $\mathbf{H}$, we have $\frac{\partial \log |\mathbf{H}|}{\partial \mathbf{H}} = \mathbf{H}^{-1}$ (e.g., Petersen et al., 2008). Therefore, we can differentiate w.r.t. $\boldsymbol{\eta}$ with

$$\frac{\partial}{\partial \boldsymbol{\eta}} \log |\mathbf{H}(\boldsymbol{\eta})| = \sum_{p=1}^{P} \sum_{q=1}^{P} [\mathbf{H}^{-1}(\boldsymbol{\eta})]_{p,q} [\frac{\partial}{\partial \boldsymbol{\eta}} \sum_{n=1}^{N} \mathbf{H}_n(\boldsymbol{\eta})]_{p,q}$$
$$= \text{vec}\left(\mathbf{H}^{-1}(\boldsymbol{\eta})\right)^{\mathsf{T}} \sum_{n=1}^{N} \frac{\partial}{\partial \boldsymbol{\eta}} \text{vec}\left(\mathbf{H}_n(\boldsymbol{\eta})\right) , \qquad (15)$$

where the two vectorised matrices are D^2-dimensional vectors and can both be computed from individual batches of $\mathbf{H}_n$. The first term acts as a *preconditioner* and can be computed by summing up the batches and inverting the resulting matrix $\mathbf{H}$ without storing the computation. We can stochastically estimate or accumulate the second term, a sum over N terms, with $M \ll N$ data points. The second term is a Jacobian w.r.t. $\boldsymbol{\eta}$ and the gradient can therefore be estimated using (accumulated) vector-Jacobian products, a standard feature of AD (Paszke et al., 2017).

The proposed method allows to aggregate gradients with respect to complex hyperparameters with memory complexity that is controlled by the batch size. This enables gradient-based optimisation of the log determinant in Eq. 9 w.r.t. the augmentation parameters for deep invariant networks on large datasets. More generally, our method enables gradient-based marginal likelihood optimisation for more complex hyperparameters than previously considered (Immer et al., 2021a; Daxberger et al., 2021; Antorán et al., 2022). In App. D, we describe the gradient computation for KFAC in detail.

5 Experiments

We evaluate our invariance learning approach by learning affine invariances on different MNIST (Le-Cun and Cortes, 2010), FashionMNIST (Xiao et al., 2017) and CIFAR-10 (Krizhevsky et al., 2009) classification tasks. To validate whether the model is capable of learning appropriate invariances, we construct several additional datasets that have been augmented by known sets of transformations. We consider the following affine transformations: full-rotation, partial-rotation, translation, and scaling (full details in App. B). We compare our approach with a non-invariant baseline and the Augerino method (Benton et al., 2020), which is, to our knowledge, the only other method that is capable of learning invariances on complex image datasets in deep neural networks without validation data. In the non-invariant model, prior parameters are learned using the marginal likelihood (Immer et al., 2021a). For invariance learning, prior parameters and $\boldsymbol{\eta}$ are jointly learned based on the marginal likelihood. For Augerino, we minimise the regular cross entropy with added regularising term $-10^{-2}||\boldsymbol{\eta}||_2$ and a fixed weight decay of 10^{-4} following the original paper (Benton et al., 2020). The same parameterisation, network architecture and initialisations (in particular $\boldsymbol{\eta} = \mathbf{0}$) were used for all methods. We assess performance of our approach by inspecting learned invariances $\boldsymbol{\eta}$, marginal likelihoods, and final test performances.

5.1 Recovering Known Invariances

To assess the invariances learned by the model, we can inspect the learned invariance parameter. The invariance parameter vector $\boldsymbol{\eta} = [\eta_1, \eta_2, ..., \eta_6]^T$ describes affine invariances with components corresponding to x-translation, y-translation, rotation, horizontal and vertical scaling, and shearing (App. B. As an MLP has little symmetry encoded in the architecture itself, we expect $\boldsymbol{\eta}$ to almost correctly recover the invariances. In Fig. 2, we plot the trajectories of each vector component over the course of training for an MLP model on different transformed MNIST datasets. As reference, we show the amount of invariance that was imposed on each dataset as a dashed line. From the figure, we can observe that for each dataset the model learns the correct invariance as well as the amount of each invariance. To some extent, the model also learned translational invariance on the regular MNIST dataset which can be explained by intrinsic translational invariance of the dataset.

Other network architectures have certain symmetries already built-in to some extend (e.g., translational equivariance of convolutional layers). Yet, we find that our method is also capable of inferring the correct invariances with such larger and other network architectures and on a variety of data sets in App. H.3. In App. F we further show that cheaper approximations, such as the diagonal GGN instead of KFAC and empirical Fisher approximations lead to worse performance for invariance learning. This suggests that our extension of KFAC to invariant neural networks is necessary for sufficient invariance learning. While Immer et al. (2021a) find that diagonal approximations can suffice for learning regularisation hyperparameters, this does not apply for the more complex invariance parameters considered here and more accurate approximations tend to increase performance.

Dataset	Network	Method	Fully Rotated	Partially Rotated	Translated	Scaled	Original
MNIST	MLP	Baseline	93.82 ±0.10	95.83 ±0.03	94.15 ±0.02	97.07 ±0.06	98.20 ±0.03
		Augerino	**97.83** ±0.03	96.35 ±0.02	94.47 ±0.08	97.45 ±0.03	98.45 ±0.03
		Learned η (**ours**)	97.74 ±0.07	**97.81** ±0.11	**97.28** ±0.05	**98.33** ±0.05	**98.98** ±0.05
	CNN	Baseline	95.97 ±0.33	97.51 ±0.17	96.54 ±0.29	98.37 ±0.00	99.09 ±0.02
		Augerino	**99.04** ±0.02	98.91 ±0.03	97.79 ±0.09	98.77 ±0.06	98.26 ±0.10
		Learned η (**ours**)	98.83 ±0.07	**98.92** ±0.05	**98.69** ±0.07	**99.01** ±0.06	**99.42** ±0.02
F-MNIST	MLP	Baseline	77.62 ±0.30	81.10 ±0.23	77.68 ±0.10	81.84 ±0.05	88.48 ±0.56
		Augerino	77.76 ±0.15	81.40 ±0.05	78.05 ±0.10	82.46 ±0.09	89.10 ±0.13
		Learned η (**ours**)	**87.39** ±0.06	**86.72** ±0.13	**84.62** ±0.08	**84.31** ±0.06	**89.94** ±0.12
	CNN	Baseline	78.69 ±0.28	82.12 ±0.35	80.33 ±0.19	83.66 ±0.37	89.54 ±0.23
		Augerino	85.76 ±3.23	81.54 ±0.19	82.94 ±0.13	83.58 ±0.08	90.07 ±0.12
		Learned η (**ours**)	**89.45** ±0.03	**88.40** ±0.00	**87.73** ±0.20	**87.33** ±0.00	**91.92** ±0.21
CIFAR-10	ResNet	Baseline	54.16 ±0.40	59.90 ±0.12	69.65 ±0.16	66.06 ±0.13	74.13 ±0.51
		Augerino	75.40 ±0.19	74.76 ±0.34	73.71 ±0.31	72.07 ±0.09	79.03 ±1.04
		Learned η (**ours**)	**79.50** ±0.62	**77.71** ±0.46	**79.21** ±0.17	**76.03** ±0.15	**84.19** ±0.76

Table 1: Test accuracy for models using GGN-KFAC on different versions of the MNIST, F-MNIST and CIFAR-10 datasets, averaged over three random seeds. Our proposed method outperforms the non-invariant and Augerino baseline for most models and datasets.

Figure 3: Comparison of test accuracies between baseline, Augerino, and our proposed invariance learning model using a ResNet architecture on different versions of the CIFAR-10 dataset, demonstrating improved data efficiency when invariances are learned.

5.2 Invariance Learning in Different Networks

To quantify the benefit of models with learned invariances, we present final test accuracies for different models on each of the datasets in Table 1. Additional marginal likelihood scores can be found in App. H.2. In terms of test accuracy and marginal likelihood, we find that learning invariances always outperforms the non-invariant baseline and that our approach improves over Augerino in almost all cases. This holds across

ResNet (14-16)	Marginal Likelihood	Test accuracy
Baseline	-40.7 k $_{\pm 268}$	79.5 $_{\pm 0.26}$
Augerino	-	83.0 $_{\pm 0.12}$
Learned η (**ours**)	**-8.4 k** $_{\pm 982}$	**88.1** $_{\pm 0.17}$

Table 2: Invariance Learning with KFAC on CIFAR-10 with ResNet (14-16) achieves best test accuracy and marginal likelihood.

the augmented datasets and original datasets. On CIFAR-10, we find that our method results in an 8-10 percentage point increase in test accuracy (Tables 1 and 2) compared to the baseline.

5.3 Invariance Learning Improves Data Efficiency

Invariances can be particularly useful for data-efficiency, which can be evaluated by measuring performance on subsets of data. In Fig. 3, we show the test accuracy of our model, the non-invariant baseline and Augerino trained on different subsets of the MNIST dataset and provide results for all models as well as on F-MNIST and CIFAR-10 in App. H.5. In general, we find that invariance learning with both Augerino and our method always improves performance across datasets and subset sizes. Most notably on a subset of 1000 regular CIFAR-10 dataset samples, Augerino improved performance by 18 percentage points compared to the non-invariant baseline, whereas our method showed an improvement of 22 percentage points. These findings suggest that learning invariances is useful in general, and in particular when data acquisition is costly or limited data is available.

5.4 On the Learned Distributions

In some instances (see CIFAR-10 results in Apps. H.3 and H.4), we observed that the model learned translational invariance on the scaled dataset rather than scale invariance. Our independent uniform distributions over invariance components cannot capture correlations between components whereas the scaled dataset was jointly scaled across the horizontal and vertical axes and thus is correlated. We hypothesise that more complex distributions that do allow for capturing correlations could offer a potential solution in such cases, but leave investigation of more complex families to future work.

6 Conclusion

We presented a method that enables automatic invariance learning in deep neural networks directly from training data, without requiring supervision or validation data. The approach is inspired by using the marginal likelihood, which is a parameterisation-independent quantity coinciding with generalisation performance. To make this practical, we use a differentiable Laplace approximation to allow for gradient-based optimisation of invariances in deep learning. While the accuracy of the approximation is difficult to verify, we do show experimentally that the method is capable of learning invariances in MNIST, F-MNIST, and CIFAR-10 datasets, leading to better marginal likelihoods and higher test performances. Our work shows that approximate Bayesian inference methods can be useful for learning complex hyperparameters, even in deep learning, and are therefore relevant beyond predictive uncertainty estimation. In future work, it would be interesting to improve the scalability and accuracy of marginal likelihood approximations which could enable learning even more complex hyperparameters, such as augmentation distributions parameterised by neural networks.

References

Javier Antorán, Riccardo Barbano, Johannes Leuschner, José Miguel Hernández-Lobato, and Bangti Jin. A probabilistic deep image prior for computational tomography. *arXiv preprint arXiv:2203.00479*, 2022.

Simon Batzner, Albert Musaelian, Lixin Sun, Mario Geiger, Jonathan P Mailoa, Mordechai Kornbluth, Nicola Molinari, Tess E Smidt, and Boris Kozinsky. Se (3)-equivariant graph neural networks for data-efficient and accurate interatomic potentials. *arXiv preprint arXiv:2101.03164*, 2021.

Gregory Benton, Marc Finzi, Pavel Izmailov, and Andrew Gordon Wilson. Learning invariances in neural networks. *arXiv preprint arXiv:2010.11882*, 2020.

Aleksandar Botev, Hippolyt Ritter, and David Barber. Practical Gauss-Newton optimisation for deep learning. In *International Conference on Machine Learning*, International Convention Centre, Sydney, Australia, 2017. PMLR.

Léon Bottou. Large-scale machine learning with stochastic gradient descent. In *Proceedings of COMPSTAT'2010*, pages 177–186. Springer, 2010.

Johannes Brandstetter, Rob Hesselink, Elise van der Pol, Erik Bekkers, and Max Welling. Geometric and physical quantities improve e (3) equivariant message passing. *arXiv preprint arXiv:2110.02905*, 2021.

Taco Cohen and Max Welling. Group equivariant convolutional networks. In *International conference on machine learning*, pages 2990–2999. PMLR, 2016.

Taco S Cohen, Mario Geiger, Jonas Köhler, and Max Welling. Spherical cnns. *arXiv preprint arXiv:1801.10130*, 2018.

Ekin D Cubuk, Barret Zoph, Dandelion Mane, Vijay Vasudevan, and Quoc V Le. Autoaugment: Learning augmentation policies from data. *arXiv preprint arXiv:1805.09501*, 2018.

Erik Daxberger, Agustinus Kristiadi, Alexander Immer, Runa Eschenhagen, Matthias Bauer, and Philipp Hennig. Laplace redux-effortless bayesian deep learning. *Advances in Neural Information Processing Systems*, 34, 2021.

Edwin Fong and CC Holmes. On the marginal likelihood and cross-validation. *Biometrika*, 107(2): 489–496, 2020.

Kunihiko Fukushima and Sei Miyake. Neocognitron: A self-organizing neural network model for a mechanism of visual pattern recognition. In *Competition and cooperation in neural nets*, pages 267–285. Springer, 1982.

Pascal Germain, Francis Bach, Alexandre Lacoste, and Simon Lacoste-Julien. Pac-bayesian theory meets bayesian inference. In D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016.

David Ginsbourger, Olivier Roustant, and Nicolas Durrande. On degeneracy and invariances of random fields paths with applications in gaussian process modelling. *Journal of Statistical Planning and Inference*, 170:117–128, 2016. ISSN 0378-3758.

Roger Grosse and James Martens. A kronecker-factored approximate fisher matrix for convolution layers. In *International Conference on Machine Learning*, pages 573–582. PMLR, 2016.

Peter D Grünwald. *The minimum description length principle*. MIT press, 2007.

Alexander Immer, Matthias Bauer, Vincent Fortuin, Gunnar Rätsch, and Mohammad Emtiyaz Khan. Scalable marginal likelihood estimation for model selection in deep learning. *arXiv preprint arXiv:2104.04975*, 2021a.

Alexander Immer, Maciej Korzepa, and Matthias Bauer. Improving predictions of bayesian neural nets via local linearization. In *Proceedings of The 24th International Conference on Artificial Intelligence and Statistics*, pages 703–711, 2021b.

Max Jaderberg, Karen Simonyan, Andrew Zisserman, et al. Spatial transformer networks. *Advances in neural information processing systems*, 28:2017–2025, 2015.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations*, 2015.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Imre Risi Kondor. Group theoretical methods in machine learning, 2008.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Pierre-Simon de Laplace. Mémoire sur la probabilité des causes par les événements. *Mémoires de l'Académie royale des sciences de Paris (Savants étrangers)*, 6:621–656, 1774.

Yann LeCun and Corinna Cortes. MNIST handwritten digit database. http://yann.lecun.com/exdb/mnist/, 2010. URL http://yann.lecun.com/exdb/mnist/.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Jonathan Lorraine, Paul Vicol, and David Duvenaud. Optimizing millions of hyperparameters by implicit differentiation. In Silvia Chiappa and Roberto Calandra, editors, *Proceedings of the Twenty Third International Conference on Artificial Intelligence and Statistics*, volume 108 of *Proceedings of Machine Learning Research*, pages 1540–1552. PMLR, 26–28 Aug 2020.

David JC MacKay. *Information theory, inference and learning algorithms*. Cambridge university press, 2003.

James Martens. New insights and perspectives on the natural gradient method. *Journal of Machine Learning Research*, 21(146):1–76, 2020.

James Martens and Roger Grosse. Optimizing neural networks with kronecker-factored approximate curvature. In *International conference on machine learning*, pages 2408–2417, 2015.

Cleve Moler and Charles Van Loan. Nineteen dubious ways to compute the exponential of a matrix, twenty-five years later. *SIAM review*, 45(1):3–49, 2003.

Kevin P Murphy. *Machine learning: a probabilistic perspective*. MIT press, 2012.

Seth Nabarro, Stoil Ganev, Adrià Garriga-Alonso, Vincent Fortuin, Mark van der Wilk, and Laurence Aitchison. Data augmentation in bayesian neural networks and the cold posterior effect. *arXiv preprint arXiv:2106.05586*, 2021.

Sebastian W Ober and Laurence Aitchison. Global inducing point variational posteriors for bayesian neural networks and deep gaussian processes. In *International Conference on Machine Learning*, pages 8248–8259. PMLR, 2021.

Sebastian W. Ober, Carl E. Rasmussen, and Mark van der Wilk. The promises and pitfalls of deep kernel learning. In Cassio de Campos and Marloes H. Maathuis, editors, *Proceedings of the Thirty-Seventh Conference on Uncertainty in Artificial Intelligence (UAI)*, volume 161 of *Proceedings of Machine Learning Research*, pages 1206–1216. PMLR, 27–30 Jul 2021.

Kazuki Osawa, Yohei Tsuji, Yuichiro Ueno, Akira Naruse, Chuan-Sheng Foo, and Rio Yokota. Scalable and practical natural gradient for large-scale deep learning. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2020.

Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. Automatic differentiation in pytorch. 2017.

Kaare Brandt Petersen, Michael Syskind Pedersen, et al. The matrix cookbook. *Technical University of Denmark*, 7(15):510, 2008.

Carl Edward Rasmussen and Zoubin Ghahramani. Occam's razor. In *Advances in neural information processing systems*, pages 294–300, 2001.

Carl Edward Rasmussen and Christopher KI Williams. *Gaussian processes for machine learning*. MIT press Cambridge, MA, 2006.

Hippolyt Ritter, Aleksandar Botev, and David Barber. A scalable laplace approximation for neural networks. In *International Conference on Learning Representations*, 2018.

Pola Schwöbel, Martin Jørgensen, Sebastian W. Ober, and Mark van der Wilk. Last layer marginal likelihood for invariance learning. In *Proceedings of the Twenty Fifth International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2022.

Joost van Amersfoort, Lewis Smith, Andrew Jesson, Oscar Key, and Yarin Gal. Improving deterministic uncertainty estimation in deep learning for classification and regression. *CoRR*, abs/2102.11409, 2021.

Tycho FA van der Ouderaa and Mark van der Wilk. Learning invariant weights in neural networks. In *Workshop in Uncertainty & Robustness in Deep Learning, ICML*, 2021.

Elise van der Pol, Daniel Worrall, Herke van Hoof, Frans Oliehoek, and Max Welling. Mdp homomorphic networks: Group symmetries in reinforcement learning. *Advances in Neural Information Processing Systems*, 33, 2020.

Mark van der Wilk, Matthias Bauer, ST John, and James Hensman. Learning invariances using the marginal likelihood. In *Advances in Neural Information Processing Systems*, pages 9938–9948, 2018.

Florian Wenzel, Kevin Roth, Bastiaan S Veeling, Jakub Światkowski, Linh Tran, Stephan Mandt, Jasper Snoek, Tim Salimans, Rodolphe Jenatton, and Sebastian Nowozin. How good is the bayes posterior in deep neural networks really? In *International Conference on Machine Learning*, 2020.

Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms, 2017.

Guodong Zhang, Shengyang Sun, David Duvenaud, and Roger Grosse. Noisy natural gradient as variational inference. In *International Conference on Machine Learning*, pages 5852–5861, 2018.

Hongyi Zhang, Yann N Dauphin, and Tengyu Ma. Fixup initialization: Residual learning without normalization. In *International Conference on Learning Representations*, 2019.

Allan Zhou, Tom Knowles, and Chelsea Finn. Meta-learning symmetries by reparameterization. *arXiv preprint arXiv:2007.02933*, 2020.