Sample-Efficient Preference-based Reinforcement Learning by Encoding Environment Dynamics in the Reward Function

Abstract: Preference-based reinforcement learning (PbRL) aligns a robot behavior with human preferences via a reward function learned from binary feedback over agent behaviors. We show that encoding environment dynamics in the reward function improves the sample efficiency of PbRL by an order of magnitude. In our experiments we iterate between: (1) encoding environment dynamics in a state-action representation z^{sa} via a self-supervised temporal consistency task, and (2) bootstrapping the preference-based reward function from z^{sa}, which results in faster policy learning and better final policy performance. For example, on quadruped-walk, walker-walk, and cheetah-run, with 50 preference labels we achieve the same performance as existing approaches with 500 preference labels, and we recover 83% and 66% of ground truth reward policy performance versus only 38% and 21% without environment dynamics. The performance gains demonstrate that *explicitly encoding environment dynamics improves preference-learned reward functions*.

Keywords: human-in-the-loop learning, preference-based RL, RLHF

1 Introduction

The quality of a reinforcement learned (RL) policy depends on the quality of the reward function used to train it. However, specifying a reliable numerical reward function is challenging. For example, a robot may learn to maximize a defined reward function without actually completing a desired task, known as reward hacking [1, 2]. Instead, preference-based reinforcement learning (PbRL) infers the reward values by way of preference feedback used to train a policy [3, 4, 5, 6, 7, 8, 9, 10, 11, 12]. Using preference feedback negates the need to manually define absolute numerical reward values (e.g. in TAMER [13]) and is easier to provide than corrective feedback (e.g. in DAGGER [14]). However, many existing PbRL methods require either demonstrations [5], which are not always feasible to provide, or an impractical number of feedback samples [3, 4, 11, 12, 15].

We target sample-efficient reward function learning by exploring the benefits of encoding environment dynamics in preference-learned reward functions or **R**ewards **E**ncoding **E**nvironment **D**ynamics (REED) (Section 4.1). Fast alignment between robot behaviors and human needs is essential for robots operating on real world domains. Given the difficulty people face when providing feedback for a single state-action pair [13], and the importance of defining preferences over transitions instead of single state-action pairs [4], *it is likely that people's internal reward functions are defined over outcomes rather than state-action pairs*. We hypothesize that: (1) modelling the relationship between state, action, and next-state triplets is essential to learn preferences over transitions, (2) encoding environment dynamics with a temporal consistency objective will allow the reward function to better generalize over states and actions with similar outcomes, and (3) exposing

Submitted to the 7th Conference on Robot Learning (CoRL 2023). Do not distribute.

the reward model to all transitions experienced by the policy during training will result in more stable reward estimations during reward and policy learning. Therefore, we incorporate environment dynamics via a self-supervised temporal consistency task using the state-of-the-art self-predictive representations (SPR) [16] as one such method for capturing environment dynamics.

We evaluate the benefits of REED using the current state-of-the-art in preference learning [3, 4]. In our experiments, which follow Lee et al. [10], REED reward functions outperform non-REED reward functions across different preference dataset sizes, quality of preference labels, observation modalities, and tasks (Section 5). *REED reward functions lead to faster policy training and reduce the number of preference samples needed (Section 6) supporting our hypotheses about the importance of environments dynamics for preference-learned reward functions.*

2 Related Work

Learning from Human Feedback. Learning reward functions from preference-based feedback [17, 18, 19, 20, 21, 22, 23, 7] has been used to address the limitations of learning policies directly from human feedback [24, 25, 26] by inferring reward functions from either task success [27, 28, 29] or real-valued reward labels [30, 31]. Learning policies directly from human feedback is inefficient as near constant supervision is commonly assumed. Inferring reward functions from task success feedback requires examples of success, which can be difficult to acquire in complex and multi-step task domains. Finally, people have difficulty providing reliable, real-valued reward labels. PbRL was extended to deep RL domains by Christiano et al. [3], then improved and made more efficient by Lee et al. [4] followed by Park et al. [11], Liu et al. [12], and Liang et al. [15]. To reduce the feedback complexity of PbRL, Lee et al. [4] sped up policy learning via (1) intrinsically-motivated exploration, and (2) relabelling the experience replay buffer. Both techniques improved the sample complexity of the policy and the trajectories generated by the policy, which were then used to seek feedback. SURF Park et al. [11] reduced feedback complexity by incorporating augmentations and pseudo-labelling into the reward model learning. RUNE Liang et al. [15] improved feedback sample complexity by guiding policy exploration with reward uncertainty. Meta-Reward-Net (MRN) Liu et al. [12] incorporated policy performance in reward model updates, but further investigation is required to ensure that the method does not allow the policy to influence and bias how the reward function is learned, two concerns called out by Armstrong et al. [32]. Additionally, preference-learning has also been incorporated into data-driven skill extraction and execution in the absence of a known reward function [33]. Of the extensions of and improvements to PbRL, only Liu et al. [12], like REED, explores the benefits of auxiliary information.

Encoding Environment Dynamics. Prior work has demonstrated the benefits of encoding environment dynamics in the state-action representation of a policy [16, 34, 35]. We instead encode environment dynamics in the **reward function**, which, as far as we are aware, has not been done before. It is nonetheless common for dynamics models to predict both the next state and the environment's reward [34], which suggests it is important to imbue the reward function with some understanding of dynamics. The primary self-supervised approach to learning a dynamics model is to predict the latent next state [16, 34, 36, 37] and the current state-of-the-art in data efficient RL [16, 35] uses SPR [16] to do exactly this.

3 Preference-based Reinforcement Learning

RL trains an agent to achieve tasks via environment interactions and reward signals [38]. For each time step t the environment provides a state s_t used by the agent to select an action according to its policy $a_t \sim \pi_\phi(a|s_t)$. Then a_t is applied to the environment, which returns a next state according to its transition function $s_{t+1} \sim \tau(s_t, a_t)$ and a reward $r(s_t, a_t)$. The agent's goal is to learn a policy π_ϕ maximizing the expected discounted return, $\sum_{k=0}^{\infty} \gamma^k r(s_{t+k}, a_{t+k})$. In PbRL [3, 5, 7, 8, 9, 4, 10] π_ϕ is trained with a reward function $\hat{r}_\psi$ distilled from preferences P_ψ iteratively queried from a teacher,

where r_ψ is assumed to be a latent factor explaining the preference P_ψ. A buffer $\mathcal{B}$ of transitions is accumulated as π_ϕ learns and explores.

A labelled preference dataset $\mathcal{D}_\mathrm{pref}$ is acquired by querying a teacher for preference labels every K steps of policy training and is stored as triplets $(\sigma^1, \sigma^2, y_p)$, where σ^1 and σ^2 are trajectory segments (sequences of state-action pairs) of length l, and y_p is a preference label indicating which, if any, of the trajectories is preferred [10]. To query the teacher, the M *maximally informative* pairs of trajectory segments (e.g. pairs that most reduce model uncertainty) are sampled from $\mathcal{B}$, sent to the teacher for preference labelling, and stored in $\mathcal{D}_\mathrm{pref}$ [10, 23, 39, 40]. Typically $\mathcal{D}_\mathrm{pref}$ is used to update $\hat{r}_\psi$ on a schedule conditioned on the training steps for π_ϕ (e.g. every time the teacher is queried).

The preference triplets $(\sigma^1, \sigma^2, y_p)$ create a supervised preference prediction task to approximate r_ψ with $\hat{r}_\psi$ [19, 3, 4]. The prediction task follows the Bradley-Terry model (1952) for a stochastic teacher and assumes that the preferred trajectory has a higher cumulative reward according to the teacher's r_ψ. The probability of the teacher preferring σ^1 over σ^2 ($\sigma^1 \succ \sigma^2$) is formalized as:

$$P_\psi[\sigma^1 \succ \sigma^2] = \frac{\exp \sum_t \hat{r}_\psi(s_t^1, a_t^1)}{\sum_{i \in \{1,2\}} \exp \sum_t \hat{r}_\psi(s_t^i, a_t^i)}, \tag{1}$$

where s_t^i is the state at time step t of trajectory $i \in \{1, 2\}$, and a_t^i is the corresponding action taken.

The parameters ψ of $\hat{r}_\psi$ are optimized such that the binary cross-entropy over $\mathcal{D}_\mathrm{pref}$ is minimized:

$$\mathcal{L}^\psi = - \mathop{\mathbb{E}}_{(\sigma^1, \sigma^2, y_p) \sim \mathcal{D}_\mathrm{pref}} \left[y_p(0) \log P_\psi[\sigma^2 \succ \sigma^1] + y_p(1) \log P_\psi[\sigma^1 \succ \sigma^2] \right]. \tag{2}$$

While $P_\psi[\sigma^1 \succ \sigma^2]$ and $\mathcal{L}^\psi$ are defined over trajectory segments, $\hat{r}_\psi$ operates over individual (s_t, a_t) pairs. Each reward estimation in Equation 1 is made *independently* of the other (s_t, a_t) pairs in the trajectory and $P_\psi[\sigma^1 \succ \sigma^2]$ simply sums the independently estimated rewards. Therefore, environment dynamics, or the outcome of different actions in different states, are not explicitly encoded in the reward function, limiting its ability to model the relationship between state-action pairs and the values associated with their outcomes. By supplementing the supervised preference prediction task with a self-supervised temporal consistency task (Section 4.1), we can take advantage of all transitions experienced by π_ϕ to learn a state-action representation in a way that explicitly encodes environment dynamics, and can be used to learn to solve the preference prediction task.

4 Encoding Environment Dynamics in the Reward Function

In this section, we present our approach to encoding environment dynamics via a temporal consistency task into the state-action representation of a preference-learned reward function. There are many methods for encoding dynamics and we show results using SPR, the current state of the art. The main idea is to learn a state-action representation that is predictive of the latent representation of the next state using a self-supervised temporal consistency task and all transitions experienced by π_ϕ. Preferences are then learned with a linear layer over the state-action representation.

4.1 Rewards Encoding Environment Dynamics (REED)

We use the SPR [16] self-supervised temporal consistency task to learn state-action representations that are predictive of likely future states and thus environment dynamics. The state-action representations are then bootstrapped to solve the preference prediction task in Equation 1 (see Figure 1 for an overview of the architecture). The SPR network is parameterized by ψ and θ, where ψ is shared with $\hat{r}_\psi$ and θ is unique to the SPR network. At train time, batches of (s_t, a_t, s_{t+1}) triplets are sampled from a buffer $\mathcal{B}$ and encoded: $f_s(s_t, \psi_s) \to z_t^s$, $f_a(a_t, \psi_a) \to z_t^a$, $f_{sa}(z_t^s, z_t^a, \psi_{sa}) \to z_t^{sa}$, and $f_s(s_{t+t}, \psi_s) \to z_{t+1}^s$. The embedding z_{t+1}^s is used to form our target for Equations 3 and 4. A dynamics function $g_d(z_t^{sa}, \theta_d) \to \hat{z}_{t+1}^s$ then predicts the latent representation of the next state z_{t+1}^s. The functions $f_s(\cdot)$, $f_a(\cdot)$, and $g_d(\cdot)$ are multi-layer perceptrons (MLPs), and $f_{sa}(\cdot)$ concatenates z_t^s and z_t^a along the feature dimension before encoding them with a MLP. To encourage knowledge of environment dynamics in z_t^{sa}, $g_d(\cdot)$ is kept simple, e.g. a linear layer.

Figure 1: Architecture for self-predictive representation (SPR) objective [16] (in yellow), and preference-learned reward function (in blue). Modules in green are shared between SPR and the preference-learned reward function.

Following Schwarzer et al. [16], a projection head $h_{\text{pro}}(\cdot, \theta_{\text{pro}})$ is used to project both the predicted and target next state representations to smaller latent spaces via a bottleneck layer and a prediction head $h_{\text{pre}}(\cdot, \theta_{\text{pre}})$ is used to predict the target projections: $\hat{y}_{t+1}^d = h_{\text{pre}}(h_{\text{pro}}(\hat{z}_{t+1}, \theta_{\text{pro}}), \theta_{\text{pre}})$ and $y_{t+1}^d = h_{\text{pro}}(z_{t+1}, \theta_{\text{pro}})$. Both h_{pro} and h_{pre} are modelled using linear layers.

The benefits of REED should be independent of the self-supervised objective function. Therefore, we present results for two different self-supervised objectives: Distillation (i.e. SimSiam with loss $\mathcal{L}^{\text{SS}}$) [42, 35] and Contrastive (i.e. SimCLR with loss $\mathcal{L}^{\text{C}}$) [43, 44, 45], referred to as Distillation REED and Contrastive REED respectively. $\mathcal{L}^{\text{SS}}$ and $\mathcal{L}^{\text{C}}$ are defined as:

$$\mathcal{L}^{\text{SS}} = -\cos(\hat{y}_{t+1}^d, \text{sg}(y_{t+1}^d)), \tag{3}$$

$$\mathcal{L}^{\text{C}} = -\log \frac{\exp(\cos(\hat{y}_{t+1}^d, \text{sg}(y_{t+1}^d))/\tau)}{\sum_{k=1}^{2N} \mathbb{1}_{[s_k \neq s_{t+1}]} \exp(\cos(y_{t+1}^d, \hat{y}_k^d)/\tau)}. \tag{4}$$

In $\mathcal{L}^{\text{SS}}$, a stop gradient operation, sg(...), is applied to y_{t+1}^d and then $\hat{y}_{t+1}^d$ is pushed to be consistent with z_{t+1}^s via a negative cosine similarity loss. In $\mathcal{L}^{\text{C}}$, a stop gradient operation is applied to y_{t+1}^d and then $\hat{y}_{t+1}^d$ is pushed to be predictive of which candidate next state is the true next state via the NT-Xent loss.

Rather than applying augmentations to the input, temporally adjacent states are used to create the different views [16, 35, 44, 45]. Appendix D details the architectures for the SPR component networks.

State-Action Fusion Reward Network. REED requires a modification to the reward network architecture used by Christiano et al. [3] and Lee et al. [4] as latent *state* representations are compared. Instead of concatenating raw state-action features, we separately encode the state, $f_s(\cdot)$, and action, $f_a(\cdot)$, before concatenating the embeddings and passing them to the body of our reward network. For the purposes of comparison, we refer to the modified reward network as the state-action fusion (SAF) reward network. For architecture details, see Appendix D.

4.2 Incorporating REED into PbRL

The self-supervised temporal consistency task is used to update the parameters ψ and θ each time the reward network is updated (every K steps of policy training, Section 3). All transitions in the buffer $\mathcal{B}$ are used to update the state-action representation z^{sa}, which effectively increases the amount of data used to train the reward function from $M \cdot K$ preference triplets to all state-action pairs experienced by the policy[1]. REED precedes selecting and presenting the M queries to the teacher for feedback. Updating ψ and θ *prior* to querying the teacher exposes z^{sa} to a larger space of environment dynamics (all transitions collected since the last model update), which enables the model to learn more about the world prior to selecting informative trajectory pairs for the teacher

---

[1]Note the reward function is still trained with $M \cdot K$ triplets, but the state-action encoder has the opportunity to better capture the dynamics of the environment.

159 to label. The state-action representation z^{sa} and a linear prediction layer are used to solve the
160 preference prediction task (Equation 1). After each update to $\hat{r}_\psi$, π_ϕ is trained on the updated $\hat{r}_\psi$.
161 See Appendix C for REED incorporated into PrefPPO [3] and PEBBLE [4].

5   Experimental Setup

163 Our experimental results in Section 6 demonstrate that explicitly encoding environment dynamics
164 in the reward function improves PbRL policy performance for both state-space and image-space
165 observations. To verify that the performance improvements are due to encoding environment dy-
166 namics rather than just the inclusion of a self-supervised auxiliary task, we compared against an
167 image-augmentation-based auxiliary task (Image Aug.). The experiments and results are provided
168 in Appendix G) and show that indeed the performance improvements are due specifically to encod-
169 ing environment dynamics in the reward function. Additionally, we compare against the SURF [11],
170 RUNE [15], and MRN [12] extensions to PEBBLE.

171 We follow the experiments outlined by the B-Pref benchmark [10]. Models are evaluated on the
172 DeepMind Control Suite (DMC) [46] and Meta-World [47] environment simulators. DMC pro-
173 vides locomotion tasks with varying degrees of difficulty and Meta-World provides object manip-
174 ulation tasks. For each DMC and Meta-World task, we evaluate performance on varying amounts
175 of feedback, i.e. different preference dataset sizes, and different labelling strategies for the synthetic
176 teacher. The number of queries (M) presented to the teacher every K steps is set such that for a
177 given task, teacher feedback always stops at the same episode. Feedback is provided by simulated
178 teachers following [3, 4, 10, 11, 33], where six different labelling strategies are used to evaluate
179 model performance under different types and amounts of label noise. The teaching strategies were
180 first proposed by Lee et al. [10]. An overview of the labelling strategies is provided in Appendix B.

181 Following Christiano et al. [3] and Lee et al. [4], $\hat{r}_\psi$ is modelled with an ensemble of three networks
182 with a corresponding ensemble for the SPR auxiliary task. The ensemble is key for disagreement-
183 based query sampling (Appendix A) and has been shown to improve final policy performance [10].
184 All queried segments are of a fixed length ($l = 50$)[2]. The Adam optimizer [48] with $\beta_1 = 0.9$,
185 $\beta_2 = 0.999$, and no L_2-regularization [49] is used to train the reward functions. For all PEBBLE-
186 related methods, intrinsic policy training is reported in the learning curves and occurs over the
187 first 9000 steps. The batch size for training on the preference dataset is M, matching the number of
188 queries presented to the teacher, and varies based on the amount of feedback. For details about model
189 architectures, hyper-parameters, and the image augmentations used in the image-augmentation self-
190 supervised auxiliary task, refer to Appendices D, E, and G. None of the hyper-parameters nor archi-
191 tectures are altered from the original SAC [50], PPO [51], PEBBLE [4], PrefPPO [4], Meta-reward-
192 net [12], RUNE [15], nor SURF [11] papers. The policy and preference learning implementations
193 provided in the B-Pref repository [52] are used for all experiments.

6   Results

195 The synthetic preference labellers allow policy performance to be evaluated against the ground truth
196 reward function and is reported as mean and standard deviation over 10 runs. Both learning curves
197 and mean normalized returns are reported, where mean normalized returns [10] are given by:

$$\text{normalized returns} = \frac{1}{T} \sum_t \frac{r_\psi(s_t, \pi_\phi^{\hat{r}_\psi}(a_t))}{r_\psi(s_t, \pi_\phi^{r_\psi}(a_t))}, \tag{5}$$

198 where T is the number of policy training training steps or episodes, r_ψ is the ground truth reward
199 function, $\pi_\phi^{\hat{r}_\psi}$ is the policy trained on the learned reward function, and $\pi_\phi^{r_\psi}$ is the policy trained on
200 the ground truth reward function.

---

[2]Fixed segments lengths are not strictly necessary, and, when evaluating with simulated humans, are harmful
when the reward is a constant step penalty.

Table 1: Mean and $\pm$ s.d. normalized return (Equation 5) over 10 random seeds with the oracle labeller and disagreement sampling. The best result for each condition is in **bold**. BASE refers to the PEBBLE or PrefPPO baseline, +DISTILL distillation REED, and +CONTRAST contrastive REED.SURF, RUNE, and MRN are baselines. Results are normalized relative to SAC for PEBBLE conditions and PPO for PREFPPO conditions. See Appendices H.2 and H.4 for all tasks and feedback amounts.

TASK	FEED.	PEBBLE						PREFPPO		
		BASE	+DISTILL	+CONTRAST	SURF [11]	RUNE [15]	MRN [12]	BASE	+DISTILL	+CONTRAST
WALKER WALK	500	0.74 ± 0.18	0.86 ± 0.20	$\mathbf{0.90 \pm 0.17}$	0.78 ± 0.12	0.76 ± 0.20	0.77 ± 0.20	$\mathbf{0.95 \pm 0.05}$	0.88 ± 0.07	0.93 ± 0.06
	50	0.21 ± 0.10	$\mathbf{0.66 \pm 0.24}$	0.62 ± 0.22	0.47 ± 0.13	0.23 ± 0.12	0.38 ± 0.12	0.51 ± 0.13	$\mathbf{0.58 \pm 0.13}$	$\mathbf{0.58 \pm 0.12}$
QUADRUPED WALK	500	0.56 ± 0.21	$\mathbf{1.10 \pm 0.21}$	$\mathbf{1.10 \pm 0.21}$	0.80 ± 0.18	$\mathbf{1.10 \pm 0.20}$	$\mathbf{1.10 \pm 0.21}$	0.46 ± 0.18	0.52 ± 0.22	0.47 ± 0.18
	50	0.38 ± 0.26	0.65 ± 0.16	0.31 ± 0.18	0.48 ± 0.19	0.44 ± 0.21	$\mathbf{0.83 \pm 0.12}$	0.68 ± 0.30	0.90 ± 0.19	$\mathbf{1.20 \pm 0.34}$
CHEETAH RUN	500	0.86 ± 0.14	0.88 ± 0.22	$\mathbf{0.94 \pm 0.21}$	0.56 ± 0.16	0.61 ± 0.17	0.80 ± 0.16	0.62 ± 0.04	$\mathbf{0.67 \pm 0.06}$	0.66 ± 0.06
	50	0.35 ± 0.11	0.63 ± 0.23	$\mathbf{0.70 \pm 0.28}$	0.55 ± 0.18	0.32 ± 0.12	0.38 ± 0.16	$\mathbf{0.50 \pm 0.07}$	0.44 ± 0.04	0.47 ± 0.05
BUTTON PRESS	10K	$\mathbf{0.66 \pm 0.26}$	*Collapses*	0.65 ± 0.27	0.68 ± 0.29	0.45 ± 0.21	0.59 ± 0.27	$\mathbf{0.18 \pm 0.03}$	*Collapses*	0.15 ± 0.04
	2.5K	0.37 ± 0.18	*Collapses*	$\mathbf{0.49 \pm 0.25}$	0.40 ± 0.18	0.22 ± 0.10	0.35 ± 0.15	$\mathbf{0.14 \pm 0.04}$	*Collapses*	$\mathbf{0.14 \pm 0.04}$
SWEEP INTO	10K	0.28 ± 0.12	*Collapses*	$\mathbf{0.47 \pm 0.23}$	0.48 ± 0.26	0.29 ± 0.15	0.28 ± 0.25	$\mathbf{0.16 \pm 0.05}$	*Collapses*	0.11 ± 0.03
	2.5K	0.15 ± 0.09	*Collapses*	$\mathbf{0.21 \pm 0.13}$	0.25 ± 0.13	0.16 ± 0.11	0.22 ± 0.12	$\mathbf{0.092 \pm 0.03}$	*Collapses*	0.058 ± 0.02

Learning curves for state-space observations for SAC and PPO trained on the ground truth reward, PEBBLE, PrefPPO, PEBBLE + REED, PrefPPO + REED, Meta-reward-net, SURF, and RUNE are shown in Figure 2, and mean normalized returns [10] are shown in Table 1. The learning curves show that reward functions learned using REED consistently outperform the baseline methods for locomotive tasks. While REED performance gains are larger for the locomotive tasks, for manipulation tasks REED methods are consistently a top performer, especially for smaller amounts of feedback.

Figure 2: Learning curves for three DMC and two Meta-World tasks with 50 and 500 (DMC) and 2.5k and 10k (Meta-World) pieces of feedback, for state-space observations, disagreement sampling, and oracle labels. Refer to Appendices H.1 and H.3 for more tasks and feedback amounts.

Learning curves for image-space observations are presented for the PEBBLE and PEBBLE+REED methods in Figure 3, and mean normalized returns [10] in Appendix H.4 . The impact of preference label quality on policy performance for PEBBLE and PEBBLE+REED is shown as learning curves in Figure 4.

Figures 2, 3 and 4 show that REED improves the speed of policy learning and the final performance of the learned policy relative to non-REED methods. The increase in policy performance is observed across environments, labelling strategies, amount of feedback, and observation type. We ablated the impact of the modified reward architecture and found that the REED performance improvements are not due to the modified reward network architecture (Appendix F). Refer to Appendix H for results across all combinations of task, feedback amount, and teacher labelling strategies for state-space observations (H.1 and H.2), and image-space Meta-World results on more tasks (drawer open, drawer close, window open, and door open) and feedback amounts (H.3 and H.4). The trends

Figure 3: Learning curves for three DMC and two Meta-World tasks with 50 and 500 (DMC) and 2.5k and 10k (Meta-World) pieces of feedback, for image–space observations, disagreement sampling, and oracle labels. Only PEBBLE is evaluated for the image-space due to the poor state-space performance of PrefPPO. Results for more tasks and feedback amounts are available in Appendices H.1 and H.3.

Figure 4: Impact of labeller strategy on quadruped-walk with 50 and 500 pieces of feedback and state-space observations. Across all labeller strategies PEBBLE+Dist. and PEBBLE+Contr. outperform the baselines.

observed in the subset of tasks included in Table 1, and Figures 2 and 3 are also observed in the additional tasks and experimental conditions in the Appendices.

6.1 Source of Improvements

There is no clear advantage between the Distillation and Contrastive REED objectives on the DMC locomotion tasks, suggesting the improved policy performance stems from encoding environment dynamics rather than any particular self-supervised objective. However in the MetaWorld object manipulation tasks, Distillation REED tends to collapse with Contrastive REED being the more robust method. From comparing SAC, PEBBLE, PEBBLE+REED, and PEBBLE+Image Aug. (Appendix G.3), we see that PEBBLE+Image Aug. improves performance over PEBBLE with large amounts of feedback (e.g. 4.2 times higher mean normalized returns for walker-walk at 1000 pieces of feedback), but does not have a large effect on performance for lower-feedback regimes (e.g. 5.6% mean normalized returns with PEBBLE+Image Aug. versus 5.5% with PEBBLE for walker-walk at 50 pieces of feedback). In contrast, incorporating REED always yields higher performance than both the baseline and PEBBLE+Image Aug. regardless of the amount of feedback.

7 Discussion and Limitations

The benefits of encoding environment dynamics are especially pronounced for labelling types that introduce incorrect labels (i.e. mistake and noisy) (Figure 4) and smaller amounts of preference feedback. For example, on state-space observation DMC tasks with 50 pieces of feedback, REED methods more closely recover the performance of the policy trained on the ground truth reward recovering 62 – 66% versus 21% on walker-walk, and 65 – 85% versus 38% on quadruped-walk for PEBBLE-based methods (Table 1). Additionally, PEBBLE+REED methods retain policy performance with a factor of 10 fewer pieces of feedback compared to PEBBLE. Likewise, when considering image-space observations, PEBBLE+REED methods trained with 10 times less feedback

exceed the performance of base PEBBLE on all DMC tasks. For instance, PEBBLE+Contrastive REED achieves a mean normalized return of 53% with 50 pieces of feedback whereas baseline PEBBLE reaches 36% on the same task with 500 pieces of feedback.

The policy improvements are smaller for REED reward functions on Meta-World tasks than they are for DMC tasks and are generally smaller for PrefPPO than PEBBLE due to a lack of data diversity in the buffer $\mathcal{B}$ used to train on the temporal consistency task. For PrefPPO lack of data diversity is due to slow learning and for MetaWorld a high similarity between observations. In particular, Distillation REED methods on state-space observations frequently suffer representation collapse and are not reported here. The objective, in this case SimSiam, learns a degenerate solution, where states are encoded by an constant function and actions are ignored due to the source and target views having a near perfect cosine similarity. However, representation collapse is not observed for the image-space observations, and baseline performance is retained with one quarter the amount of feedback when training with PEBBLE+REED methods. If the amount of feedback is kept constant, we notice a 25% to 70% performance improvement over the baseline for all PEBBLE+REED methods in the Button Press task.

The benefits of encoding environment dynamics can be compared against the benefits of other approaches to improving feedback sample complexity, specifically pseudo-labelling (in SURF) [11], guiding policy exploration with reward uncertainty (in RUNE) [15], and incorporating policy performance into reward updates (in MRN) [12]. REED methods consistently outperform SURF, RUNE, and MRN on the DMC tasks demonstrating the importance of encoding environment dynamics for locomotion tasks. On the MetaWorld object manipulation tasks, REED frequently outperforms SURF, RUNE, and MRN, especially for smaller amounts of feedback, but the performance gains are smaller than for DMC. Smaller performance gains on MetaWorld relative to other sample efficiency methods is in line with general REED findings for MetaWorld (above) that relate to the slower environment dynamics. However, it is important to call out that all four methods are complementary and can be combined.

Across tasks and feedback amounts, policy performance is higher for rewards that are learned on the state-space observations compared to those learned on image-space observations. There are several tasks, such as cheetah-run and sweep into, for which PEBBLE, and therefore all REED experiments that build on PEBBLE, are not able to learn reward functions that lead to reasonable policy performance when using the image-space observations.

The results demonstrate the benefits and importance of environment dynamics to preference-learned reward functions.

Limitations The limitations of REED are: (1) more complex tasks still require a relatively large number of preference labels, (2) extra compute and time are required, (3) Distillation REED can collapse when observations have high similarity, and (4) redundant transitions in the buffer $\mathcal{B}$ from slow policy learning or state spaces with low variability result in over-fitting on the temporal consistency task.

8 Conclusion

We have demonstrated the benefits of encoding environment dynamics in a preference-learned reward for PbRL, **especially when feedback is limited or noisy**. Across experimental conditions, we found REED methods retain the performance of PEBBLE with a 10-fold decrease in feedback. The benefits are observed across tasks, observation modalities, and labeller types. Additionally, we found that, compared to the other PbRL extensions targeting sample efficiency, REED most consistently produced the largest performance gains, especially for smaller amounts of feedback. The resulting sample efficiency is necessary for learning reward functions aligned with user preferences in practical robotic settings.

References

[1] D. Amodei, C. Olah, J. Steinhardt, P. Christiano, J. Schulman, and D. Mané. Concrete problems in AI safety. *arXiv preprint arXiv:1606.06565*, 2016.

[2] D. Hadfield-Menell, S. Milli, P. Abbeel, S. Russell, and A. Dragan. Inverse reward design. *Advances in Neural Information Processing Systems*, 30, 2017.

[3] P. Christiano, J. Leike, T. Brown, M. Martic, S. Legg, and D. Amodei. Deep reinforcement learning from human preferences. volume 30, 2017.

[4] K. Lee, L. Smith, and P. Abbeel. PEBBLE: Feedback-efficient interactive reinforcement learning via relabeling experience and unsupervised pre-training. In *Proceedings of the International Conference on Machine Learning*, pages 6152–6163. PMLR, 2021.

[5] B. Ibarz, J. Leike, T. Pohlen, G. Irving, S. Legg, and D. Amodei. Reward learning from human preferences and demonstrations in Atari. *Advances in Neural Information Processing Systems*, 31, 2018.

[6] D. Hadfield-Menell, S. Russell, P. Abbeel, and A. Dragan. Cooperative inverse reinforcement learning. *Advances in Neural Information Processing Systems*, 29, 2016.

[7] J. Leike, D. Krueger, T. Everitt, M. Martic, V. Maini, and S. Legg. Scalable agent alignment via reward modeling: A research direction. *arXiv preprint arXiv:1811.07871*, 2018.

[8] N. Stiennon, L. Ouyang, J. Wu, D. Ziegler, R. Lowe, C. Voss, A. Radford, D. Amodei, and P. Christiano. Learning to summarize with human feedback. *Advances in Neural Information Processing Systems*, 33:3008–3021, 2020.

[9] J. Wu, L. Ouyang, D. Ziegler, N. Stiennon, R. Lowe, J. Leike, and P. Christiano. Recursively summarizing books with human feedback. *arXiv preprint arXiv:2109.10862*, 2021.

[10] K. Lee, L. Smith, A. Dragan, and P. Abbeel. B-Pref: Benchmarking preference-based reinforcement learning. *Neural Information Processing Systems*, 2021.

[11] J. Park, Y. Seo, J. Shin, H. Lee, P. Abbeel, and K. Lee. SURF: Semi-supervised reward learning with data augmentation for feedback-efficient preference-based reinforcement learning. *arXiv preprint arXiv:2203.10050*, 2022.

[12] R. Liu, F. Bai, Y. Du, and Y. Yang. Meta-Reward-Net: Implicitly differentiable reward learning for preference-based reinforcement learning. *Advances in Neural Information Processing Systems*, 35, 2022.

[13] W. Knox and P. Stone. Tamer: Training an agent manually via evaluative reinforcement. In *Proceedings of the International Conference on Development and Learning*, pages 292–297. IEEE, 2008.

[14] S. Ross, G. Gordon, and D. Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In *Proceedings of the International Conference on Artificial Intelligence and Statistics*, pages 627–635, 2011.

[15] X. Liang, K. Shu, K. Lee, and P. Abbeel. Reward uncertainty for exploration in preference-based reinforcement learning. 2022.

[16] M. Schwarzer, A. Anand, R. Goel, R. Hjelm, A. Courville, and P. Bachman. Data-efficient reinforcement learning with self-predictive representations. In *Proceedings of the International Conference on Learning Representations*, 2020.

[17] R. Akrour, M. Schoenauer, and M. Sebag. Preference-based policy learning. In *Proceedings of the Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pages 12–27. Springer, 2011.

[18] R. Akrour, M. Schoenauer, and M. Sebag. April: Active preference learning-based reinforcement learning. In *Proceedings of the Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pages 116–131. Springer, 2012.

[19] A. Wilson, A. Fern, and P. Tadepalli. A Bayesian approach for policy learning from trajectory preference queries. *Advances in Neural Information Processing Systems*, 25, 2012.

[20] H. Sugiyama, T. Meguro, and Y. Minami. Preference-learning based inverse reinforcement learning for dialog control. In *Proceedings of Interspeech*, 2012.

[21] C. Wirth and J. Fürnkranz. Preference-based reinforcement learning: A preliminary survey. In *Proceedings of the Workshop on Reinforcement Learning from Generalized Feedback: Beyond Numeric Rewards*, 2013.

[22] C. Wirth, J. Fürnkranz, and G. Neumann. Model-free preference-based reinforcement learning. In *Proceedings of the Conference on Artificial Intelligence (AAAI)*, 2016.

[23] D. Sadigh, A. Dragan, S. Sastry, and S. Seshia. Active preference-based learning of reward functions. 2017.

[24] P. Pilarski, M. Dawson, T. Degris, F. Fahimi, J. Carey, and R. Sutton. Online human training of a myoelectric prosthesis controller via actor-critic reinforcement learning. In *Proceedings of the International Conference on Rehabilitation Robotics*, pages 1–7. IEEE, 2011.

[25] J. MacGlashan, M. Ho, R. Loftin, B. Peng, G. Wang, D. Roberts, M. Taylor, and M. Littman. Interactive learning from policy-dependent human feedback. In *Proceedings of the International Conference on Machine Learning*, pages 2285–2294. PMLR, 2017.

[26] D. Arumugam, J. Lee, S. Saskin, and M. Littman. Deep reinforcement learning from policy-dependent human feedback. *arXiv preprint arXiv:1902.04257*, 2019.

[27] M. Zhang, S. Vikram, L. Smith, P. Abbeel, M. Johnson, and S. Levine. Solar: Deep structured representations for model-based reinforcement learning. In *Proceedings of the International Conference on Machine Learning*, pages 7444–7453. PMLR, 2019.

[28] A. Singh, L. Yang, K. Hartikainen, C. Finn, and S. Levine. End-to-end robotic reinforcement learning without reward engineering. *arXiv preprint arXiv:1904.07854*, 2019.

[29] L. Smith, N. Dhawan, M. Zhang, P. Abbeel, and S. Levine. AVID: Learning multi-stage tasks via pixel-level translation of human videos. *arXiv preprint arXiv:1912.04443*, 2019.

[30] W. Knox and P. Stone. Interactively shaping agents via human reinforcement: The TAMER framework. In *Proceedings of the International Conference on Knowledge Capture*, pages 9–16, 2009.

[31] G. Warnell, N. Waytowich, V. Lawhern, and P. Stone. Deep Tamer: Interactive agent shaping in high-dimensional state spaces. In *Proceedings of the Conference on Artificial Intelligence (AAAI)*, volume 32, 2018.

[32] S. Armstrong, J. Leike, L. Orseau, and S. Legg. Pitfalls of learning a reward function online. *arXiv preprint arXiv:2004.13654*, 2020.

[33] X. Wang, K. Lee, K. Hakhamaneshi, P. Abbeel, and M. Laskin. Skill preferences: Learning to extract and execute robotic skills from human feedback. In *Proceedings of the Conference on Robot Learning*, pages 1259–1268. PMLR, 2021.

[34] A. Zhang, R. McAllister, R. Calandra, Y. Gal, and S. Levine. Learning invariant representations for reinforcement learning without reconstruction. *arXiv preprint arXiv:2006.10742*, 2020.

[35] W. Ye, S. Liu, T. Kurutach, P. Abbeel, and Y. Gao. Mastering Atari games with limited data. *Advances in Neural Information Processing Systems*, 34, 2021.

[36] D. Hafner, T. Lillicrap, I. Fischer, R. Villegas, D. Ha, H. Lee, and J. Davidson. Learning latent dynamics for planning from pixels. In *Proceedings of the International Conference on Machine Learning*, pages 2555–2565. PMLR, 2019.

[37] A. Lee, A. Nagabandi, P. Abbeel, and S. Levine. Stochastic latent actor-critic: Deep reinforcement learning with a latent variable model. *Advances in Neural Information Processing Systems*, 33:741–752, 2020.

[38] R. Sutton and A. Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

[39] E. Biyik and D. Sadigh. Batch active preference-based learning of reward functions. In *Proceedings of the Conference on Robot Learning*, pages 519–528. PMLR, 2018.

[40] E. Biyik, N. Huynh, M. Kochenderfer, and D. Sadigh. Active preference-based gaussian process regression for reward learning. In *Proceedings of the Robotics: Science and Systems*, 2020.

[41] R. Bradley and M. Terry. Rank analysis of incomplete block designs: I. The method of paired comparisons. *Biometrika*, 39(3/4):324–345, 1952.

[42] X. Chen and K. He. Exploring simple Siamese representation learning. In *Proceedings of the Conference on Computer Vision and Pattern Recognition*, pages 15750–15758, 2021.

[43] T. Chen, S. Kornblith, M. Norouzi, and G. Hinton. A simple framework for contrastive learning of visual representations. In *Proceedings of the International Conference on Machine Learning*, pages 1597–1607. PMLR, 2020.

[44] A. Oord, Y. Li, and O. Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

[45] B. Mazoure, R. Tachet des Combes, T. Doan, P. Bachman, and R. Hjelm. Deep reinforcement and InfoMax learning. *Advances in Neural Information Processing Systems*, 33:3686–3698, 2020.

[46] Y. Tassa, Y. Doron, A. Muldal, T. Erez, Y. Li, D. Casas, D. Budden, A. Abdolmaleki, J. Merel, A. Lefrancq, et al. Deepmind control suite. *arXiv preprint arXiv:1801.00690*, 2018.

[47] T. Yu, D. Quillen, Z. He, R. Julian, K. Hausman, C. Finn, and S. Levine. Meta-World: A benchmark and evaluation for multi-task and meta reinforcement learning. In *Proceedings of the Conference on Robot Learning*, pages 1094–1100. PMLR, 2020.

[48] D. Kingma and J. Ba. ADAM: A method for stochastic optimization. volume 3, 2015.

[49] A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimelshein, L. Antiga, A. Desmaison, A. Kopf, E. Yang, Z. DeVito, M. Raison, A. Tejani, S. Chilamkurthy, B. Steiner, L. Fang, J. Bai, and S. Chintala. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32, 2019.

[50] T. Haarnoja, A. Zhou, P. Abbeel, and S. Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *Proceedings of the International Conference on Machine Learning*, pages 1861–1870. PMLR, 2018.

[51] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov. Proximal policy optimization algorithms, 2017.

[52] K. Lee, L. Smith, A. Dragan, and P. Abbeel. B-Pref, 2021. URL https://github.com/rll-research/BPref.

[53] Z. Mandi, F. Liu, K. Lee, and P. Abbeel. Towards more generalizable one-shot visual imitation learning. In *Proceedings of the International Conference on Robotics and Automation*, pages 2434–2444. IEEE, 2022.

[54] P. Goyal, S. Niekum, and R. Mooney. Pixl2r: Guiding reinforcement learning using natural language by mapping pixels to rewards. In *Proceedings of the Conference on Robot Learning*, pages 485–497. PMLR, 2021.

A Disagreement Sampling

For all experiments in this paper, disagreement sampling is used to select which trajectory pairs will be presented to the teacher for preference labels. Disagreement-based sampling selects trajectory pairs as follows: (1) N segments are sampled uniformly from the replay buffer; (2) the M pairs of segments with the largest variance in preference prediction across the reward network ensemble are sub-sampled. Disagreement-based sampling is used as it reliably resulted in highest performing policies compared to the other sampling methods discussed in Lee et al. [10].

B Labelling Strategies

An overview of the six labelling strategies is provided below, ordered from least to most noisy (see [10] for details and configuration specifics):

1. **oracle** - prefers the trajectory segment with the larger return and equally prefers both segments when their returns are identical

2. **skip** - follows oracle, except randomly selects 10% of the M query pairs to discard from the preference dataset $\mathcal{D}_{pref}$

3. **myopic** - follows oracle, except compares discounted returns ($\gamma = 0.9$) placing more weight on transitions at the end of the trajectory

4. **equal** - follows oracle, except marks trajectory segments as equally preferable when the difference in returns is less than 0.5% of the average ground truth returns observed during the last K policy training steps

5. **mistake** - follows oracle, except randomly selects 10% of the M query pairs and assigns incorrect labels in a structured way (e.g., a preference for segment two becomes a preference for segment one)

6. **noisy** - randomly assigns labels with probability proportional to the relative returns associated with the pair, but labels the segments as equally preferred when they have identical returns

C REED Algorithm

The REED task is specified in Algorithm 1 in the context of the PEBBLE preference-learning algorithm. The main components of the PEBBLE algorithm are included, with our modifications identified in the comments. For the original and complete specification of PEBBLE, please see [4] - Algorithm 2.

Algorithm 1 PEBBLE + REED Training Procedure

1: **Given:**
2:   K ▷ *teacher feedback frequency*
3:   M ▷ *queries per feedback*
4: **Initializes:**
5:   Q_θ ▷ *parameters for Q-function*
6:   $\hat{r}_\psi$ ▷ *learned reward function*
7:   $\text{SPR}_{(\psi,\theta)}$ ▷ *self-future consistency (ψ parameters shared with $\hat{r}_\psi$)*
8:   $\mathcal{D}_{\text{pref}} \leftarrow \emptyset$ ▷ *preference dataset*
9:   $\mathcal{D}_{\text{SPR}} \leftarrow \emptyset$ ▷ *SPR dataset*

10: ▷ *unsupervised policy training and exploration*   ◁
11: $\mathcal{B}, \pi_\phi \leftarrow \text{EXPLORE}()$ ▷ *[4] - Algorithm 1*

12: ▷ *joint policy and reward training*   ◁
13: **for** policy train step **do**
14:   **if** step $\% K = 0$ **then**
15:    $D_{\text{sfc}} \leftarrow D_{\text{sfc}} \bigcup \mathcal{B}$ ▷ *update SPR dataset*
16:    **for** each SPR gradient step **do**
17:     $\{(s_t, a_t, s_{t+1})\} \sim \mathcal{D}_{\text{sfc}}$ ▷ *sample minibatch*
18:     $\{(\hat{z}_{t+1}^s, z_{t+1}^s)\} \leftarrow \text{SFC\_FORWARD}(\{(s_t, a_t, s_{t+1})\})$ ▷ *Section D.2*
19:     **optimize** $\mathcal{L}^{\text{reed}}$ with respect to $\text{SPR}_{(\psi,\theta)}$ ▷ *Equations (3) and (4)*
20:    $\hat{r}_\psi \leftarrow \text{SPR}_\psi$ ▷ *copy shared SPR parameters to reward model*
21:    **update** $\mathcal{D}_{\text{pref}}$, $\hat{r}_\psi$, and $\mathcal{B}$ ▷ *following [4] - Algorithm 2 [lines 9 - 18]*
22:   **update** $\mathcal{B}$, π_ϕ, and Q_θ ▷ *following [4] - Algorithm 2 [lines 20 - 27]*

D Architectures

The network architectures are specified in PyTorch 1.13. For architecture hyper-parameters, e.g. hidden size and number of hidden layers, see Appendix E.2

D.1 Self-Predictive Representations Network

The SPR network is implemented in PyTorch. The architectures for the next_state_projector and consistency_predictor when image observations are used come from [53]. The image encoder architecture comes from [54]. The SPR network is initialized as follows:

```python
def build_spr_network(
    self,
    state_size: int,
    state_embed_size: int,
    action_size: int,
    action_embed_size: int,
    hidden_size: int,
    consistency_projection_size: int,
    consistency_comparison_hidden_size: int,
    with_consistency_prediction_head: bool,
    num_layers: int,
    image_observations: bool,
    image_hidden_num_channels: int
):
    """
    The network architecture and build logic to the complete the REED
    self-supervised temporal consistency task based on SPR.

    Args:
        state_size: number of features defining the agent's state space
        state_embed_size: number of dimensions in the state embedding
        action_size: number of features defining the agent's actions
        action_embed_size: number of dimensions in the action embedding
        hidden_size: number of dimensions in the hidden layers of
                     state-action embedding network
        consistency_projection_size: number of units used to compare the
                                     predicted and target latent next
                                     state
        consistency_comparison_hidden_size: number of units in the hidden
                                     layers of the next_state_projector
                                     and the consistency_predictor
        with_consistency_prediction_head: when using the contrastive of
                                     objective the consistency
                                     prediction is not used, but is
                                     when using the distillation
                                     objective
        num_layers: number of hidden layers used to embed the
                    state-action representation
        image_observations: whether image observations are used. If image
                            observations are not used, state-space
                            observations are used
        image_hidden_num_channels: the number of channels to use in the
                                     image encoder's hidden layers
    """
    # build the network that will encode the state features
    if image_observations:
        state_conv_encoder = nn.Sequential(
            nn.Conv2d(
                state_size[0],
                image_hidden_num_channels,
                3,
                stride=1
            ),
```

```
516             nn.ReLU(),
517             nn.MaxPool2d(2, 2),
518
519             nn.Conv2d(
520                 image_hidden_num_channels,
521                 image_hidden_num_channels,
522                 3,
523                 stride=1
524             ),
525             nn.ReLU(),
526             nn.MaxPool2d(2, 2),
527
528             nn.Conv2d(
529                 image_hidden_num_channels,
530                 image_hidden_num_channels,
531                 3,
532                 stride=1
533             ),
534             nn.ReLU(),
535             nn.MaxPool2d(2, 2)
536         )
537         conv_out_size = torch.flatten(
538                 _state_conv_encoder(
539                     torch.rand(size=[1] + list(state_size))
540                 )).size()[0]
541         self.state_encoder = nn.Sequential(
542             _state_conv_encoder
543             nn.Linear(conv_out_size, state_embed_size)
544             nn.LeakyReLU(negative_slope=1e-2)
545         )
546     else:
547         self.state_encoder = torch.nn.Sequential(
548             torch.nn.Linear(state_size, state_embed_size),
549             torch.nn.LeakyReLU(negative_slope=1e-2),
550         )
551
552     # build the network that will encode the action features
553     self.action_encoder = torch.nn.Sequential(
554         torch.nn.Linear(action_size, action_embed_size),
555         torch.nn.LeakyReLU(negative_slope=1e-2),
556     )
557
558     # build the network that models the relationship between the
559     # state and action embeddings
560     state_action_encoder = []
561     hidden_in_size = action_embed_size + state_embed_size
562     for i in range(num_layers):
563         state_action_encoder.append(
564             torch.nn.Linear(hidden_in_size, hidden_size),
565         )
566         state_action_encoder.append(
567             torch.nn.LeakyReLU(negative_slope=1e-2),
568         )
569         hidden_in_size = hidden_size
570     self.state_action_encoder = torch.nn.Sequential(*state_action_encoder)
571     # this is a single dense layer because we want to focus as much of
572     # the useful semantic information as possible in the state-action
573     # representation
574     self.next_state_predictor = torch.nn.Linear(
575         hidden_size, state_embed_size
576     )
577
578     if image_observations:
579         self.next_state_projector = nn.Sequential(
580             nn.BatchNorm1d(state_embed_size),
```

```
581                nn.ReLU(inplace=True),
582                nn.Linear(
583                    state_embed_size,
584                    consistency_comparison_hidden_size
585                ),
586                nn.ReLU(inplace=True),
587                nn.Linear(
588                    consistency_comparison_hidden_size,
589                    consistency_projection_size
590                ),
591                nn.LayerNorm(consistency_projection_size)
592            )
593        if with_consistency_prediction_head:
594            self.consistency_predictor = nn.Sequential(
595                nn.ReLU(inplace=True),
596                nn.Linear(
597                    consistency_projection_size,
598                    consistency_comparison_hidden_size
599                ),
600                nn.ReLU(inplace=True),
601                nn.Linear(
602                    consistency_comparison_hidden_size,
603                    consistency_projection_size
604                ),
605                nn.LayerNorm(consistency_projection_size)
606            )
607        else:
608            predictor = None
609    else:
610
611        self.next_state_projector = torch.nn.Linear(
612            state_embed_size,
613            consistency_projection_size
614        )
615        if with_consistency_prediction_head:
616            self.consistency_predictor = nn.Linear(
617                consistency_projection_size,
618                consistency_projection_size
619            )
620        else:
621            self.consistency_predictor = None
```

622 A forward pass through the SFC network is as follows:

```
623  def spr_forward(self,
624                  transitions: EnvironmentTransitionBatch,
625                  with_consistency_prediction_head: bool):
626      """
627      The logic for a forward pass through the SPR network.
628      Args:
629        transitions: a batch of environment transitions composed of
630                     states, actions, and next states
631        with_consistency_prediction_head: when using the contrastive of
632                                   objective the consistency
633                                   prediction is not used, but is
634                                   when using the distillation
635                                   objective
636      Returns:
637        predicted embedding of the next state - p in SimSiam paper
638        next state embedding (detached from graph) - z in SimSiam paper
639        dimensionality: (batch, time step)
640      """
641      # encode the state, the action, and the state-action pair
642      # s_t → z_t^s
643      states_embed = self.state_encoder(transitions.states)
```

```python
644        #  a_t → z_t^a
645        actions_embed = self.action_encoder(transitions.actions)
646        #  (s_t, a_t) → z_t^{sa}
647        state_action_embeds = torch.concat(
648            [states_embed, actions_embed], dim=-1
649        )
650        state_action_embed = self.state_action_encoder(
651            state_action_embeds
652        )
653
654        # predict and project the representation of the next state
655        #  z_t^{sa} → ẑ_{t+1}^s
656        next_state_pred = self.next_state_predictor(state_action_embed)
657        next_state_pred = self.next_state_projector(next_state_pred)
658        if with_consistency_prediction_head:
659            next_state_pred = self.consistency_predictor(next_state_pred)
660
661        # we don't want gradients to back-propagate into the learned
662        # parameters from anything we do with the next state
663        with torch.no_grad():
664            #  s_{t+1} → z_{t+1}^s
665            # embed the next state
666            next_state_embed = self.state_encoder(transitions.next_states)
667            # project the next state embedding into a space where it can be
668            # compared with the predicted next state
669            projected_next_state_embed = self.next_state_projector(
670                next_state_embed
671            )
672
673        # from the SimSiam paper, this is p and z
674        return next_state_pred, projected_next_state_embed
```

D.2   SAF Reward Network

The architecture of the SAF Reward Network is a subset of the SFC network with the addition of a linear to map the state-action representation to predicted rewards. The SFC network is implemented in PyTorch and is initialized following the below build method:

```python
679 def build_saf_network(
680     self,
681     state_size: int,
682     state_embed_size: int,
683     action_size: int,
684     action_embed_size: int,
685     hidden_size: int,
686     num_layers: int,
687     final_activation_type: str,
688     image_observations: bool,
689     image_hidden_num_channels: int
690 ):
691     """
692     Args:
693       state_size: number of features defining the agent's state space
694       state_embed_size: number of dimensions in the state embedding
695       action_size: number of features defining the agent's actions
696       action_embed_size: number of dimensions in the action embedding
697       hidden_size: number of dimensions in the hidden layers of
698                    state-action embedding network
699       num_layers: number of hidden layers used to embed the
700                   state-action representation
701       final_activation_type: the activation used on the final layer
702       image_observations: whether image observations are used. If image
703                           observations are not used, state-space
704                           observations are used
```

```
705          image_hidden_num_channels: the number of channels to use in the
706                                     image encoder's hidden layers
707        """
708            # build the network that will encode the state features
709        if image_observations:
710            state_conv_encoder = nn.Sequential(
711                nn.Conv2d(
712                    state_size[0],
713                    image_hidden_num_channels,
714                    3,
715                    stride=1
716                ),
717                nn.ReLU(),
718                nn.MaxPool2d(2, 2),
719
720                nn.Conv2d(
721                    image_hidden_num_channels,
722                    image_hidden_num_channels,
723                    3,
724                    stride=1
725                ),
726                nn.ReLU(),
727                nn.MaxPool2d(2, 2),
728
729                nn.Conv2d(
730                    image_hidden_num_channels,
731                    image_hidden_num_channels,
732                    3,
733                    stride=1
734                ),
735                nn.ReLU(),
736                nn.MaxPool2d(2, 2)
737            )
738            conv_out_size = torch.flatten(
739                    _state_conv_encoder(
740                        torch.rand(size=[1] + list(state_size))
741                    )).size()[0]
742            self.state_encoder = nn.Sequential(
743                _state_conv_encoder
744                nn.Linear(conv_out_size, state_embed_size)
745                nn.LeakyReLU(negative_slope=1e-2)
746            )
747        else:
748            self.state_encoder = torch.nn.Sequential(
749                torch.nn.Linear(state_size, state_embed_size),
750                torch.nn.LeakyReLU(negative_slope=1e-2),
751            )
752
753        # build the network that will encode the action features
754        self.action_encoder = torch.nn.Sequential(
755            torch.nn.Linear(action_size, action_embed_size),
756            torch.nn.LeakyReLU(negative_slope=1e-2),
757        )
758
759        # build the network that models the relationship between the
760        # state and action embeddings
761        state_action_encoder = []
762        hidden_in_size = action_embed_size + state_embed_size
763        for i in range(num_layers):
764            state_action_encoder.append(
765                torch.nn.Linear(hidden_in_size, hidden_size),
766            )
767            state_action_encoder.append(
768                torch.nn.LeakyReLU(negative_slope=1e-2),
769            )
```

```
770        hidden_in_size = hidden_size
771    self.state_action_encoder = torch.nn.Sequential(*state_action_encoder)
772
773    # build the prediction head and select a final activation
774    self.prediction_head = torch.nn.Linear(hidden_size, 1)
775    if final_activation_type == "tanh":
776        self.final_activation = torch.nn.Tanh()
777    elif final_activation_type == "sig":
778        self.final_activation = torch.nn.Sigmoid()
779    else:
780        self.final_activation_type = torch.nn.ReLU()
```

A forward pass through the SAF network is as follows:

```
782  def saf_forward(self, transitions: EnvironmentTransitionBatch):
783      """
784      Args:
785        transitions: a batch of environment transitions composed of
786                     states, actions, and next states
787      Returns:
788        predicted embedding of the next state - p in SimSiam paper
789        next state embedding (detached from graph) - z in SimSiam paper
790        dimensionality: (batch, time step)
791      """
792      # encode the state, the action, and the state-action pair
793      # s_t -> z_t^s
794      states_embed = self.state_encoder(transitions.states)
795      # a_t -> z_t^a
796      actions_embed = self.action_encoder(transitions.actions)
797      # (s_t, a_t) -> z_t^{sa}
798      state_action_embeds = torch.concat(
799          [states_embed, actions_embed], dim=-1
800      )
801      state_action_embed = self.state_action_encoder(
802          state_action_embeds
803      )
804
805      return self.final_activation(
806          self.prediction_head(state_action_embed)
807      )
```

E Hyper-parameters

E.1 Train Hyper-parameters

This section specifies the hyper-parameters (e.g. learning rate, batch size, etc) used for the experiments and results (Section **??**). The SAC, PPO, PEBBLE, and PrefPPO experiments all match those used in [50], [51], and [4] respectively. The SAC and PPO hyper-parameters are specified in Table 2, the PEBBLE and PrefPPO hyper-parameters are given in Table 3, and the hyper-parameters used to train on the REED task are in Table 4.

The image-space models were trained on images of size 50x50. For PEBBLE and REED on DMC tasks, color images were used, and for Meta-World tasks, grayscale images were used. All pixel values were scaled to the range $[0.0, 1.0]$.

For the image-based REED methods, we found that a larger value of k was important for the Meta-World experiments compared to the DMC experiments due to slower environment dynamics. In Meta-World the differences between subsequent observations are far more similar than in DMC. In the state-space, the mean cosine similarity between all observations accumulated in the replay buffer was 0.9. For the image-space observations, the mean cosine similarity was 0.7. Additionally, for sweep into, due to the similarity in Meta-World observations, the slower environment dynamics, and

difficulty of tasks like sweep into, we found it beneficial to update on the REED objective every 5^{th} update to the reward model in order to avoid over fitting on the REED objective and reducing the accuracy of the $\hat{r}_\psi$ preference predictions.

Table 2: Training hyper-parameters for SAC [50] and PPO [51].

HYPER-PARAMETER	VALUE
SAC	
Learning rate	1e-3 (cheetah), 5e-4 (walker), 1e-4 (quadruped), 3e-4 (Meta-World)
Batch size	512 (DMC), 1024 (Meta-World)
Total timesteps	500k, 1M (quadruped, sweep into)
Optimizer	Adam [48]
Critic EMA τ	5e-3
Critic target update freq.	2
$(\mathcal{B}_1, \mathcal{B}_2)$	$(0.9, 0.999)$
Initial Temperature	0.1
Discount γ	0.99
PPO	
Learning rate	5e-5 (DMC), 3e-4 (Meta-World)
Batch size	128 (all but cheetah), 512 (cheetah)
Total timesteps	500k (cheetah, walker, button press), 1M (quadruped, sweep into)
Envs per worker	8 (sweep into), 16 (cheetah, quadruped), 32 (walker, sweep into)
Optimizer	Adam [48]
Discount γ	0.99
Clip range	0.2
Entropy bonus	0.0
GAE parameter λ	0.92
Timesteps per rollout	250 (Meta-World), 500 (DMC)

Table 3: Training hyper-parameters for PEBBLE [4] and PrefPPO [3, 4]. The only hyper-parameter that differs between PEBBLE and PrefPPO is the DMC learning rate. The batch size for the reward network changes based per total feedback amount to match the number of queries M sent to the teacher for labelling each feedback session.

HYPER-PARAMETER	VALUE
Learning rate PEBBLE	3e-4
Learning rate PrefPPO	5e-4 (DMC), 3e-4 (Meta-World)
Optimizer	Adam [48]
Segment length l	50 (DMC), 25 (Meta-World)
Feedback amount / number queries (M)	1k/100, 500/50, 200/20, 100/10, 50/5 (DMC) 20k/100, 10k/50, 5k/25, 2.5k/12 (Meta-World)
Steps between queries (K)	20k (walker, cheetah), 30k (quadruped), 5k (Meta-World)

Table 4: Training hyper-parameters for REED with the SPR objective [16] (Section 4.1). The REED hyper-parameters were used with both the PEBBLE [4] and PrefPPO [3, 4] preference-learning algorithms. Hyper-parameters are by environment/task and shared by the two SSL objectives: Distillation versus Contrastive (Section 4.1). Training on the REED task occurred every K steps (specified in Table 3) prior to updating on the preference task. The SPR objective predicts future latent states k steps in the future. While our hyper-parameter sweep evaluated multiple values for k, we found that $k = 1$ vs. $k > 1$ had no real impact on learning quality for these state-action feature spaces. For Contrastive REED experiments (state-space and image-space observations), $\tau = 0.005$. In general, the image-based experiments REED were less sensitive to the hyper-parameters than the state-space experiments experiments.

ENVIRONMENT	LEARNING RATE	EPOCHS PER UPDATE	BATCH SIZE	OPTIMIZER	K
STATE-SPACE OBSERVATIONS					
Walker	1e-3	20	12	SGD	1
Cheetah	1e-3	20	12	SGD	1
Quadruped	1e-4	20	128	Adam [48]	1
Button Press	1e-4	10	128	Adam [48]	1
Sweep Into	5e-5	5	256	Adam [48]	1
IMAGE-SPACE OBSERVATIONS					
Walker	1e-4	5	256	Adam [48]	1
Cheetah	1e-4	5	256	Adam [48]	1
Quadruped	1e-4	5	256	Adam [48]	1
Button Press	1e-4	5	256	Adam [48]	5
Sweep Into	1e-4	5	512	Adam [48]	5
Drawer Open	1e-4	5	256	Adam [48]	5
Drawer Close	1e-4	5	256	Adam [48]	5
Window Open	1e-4	5	256	Adam [48]	5
Door Open	1e-4	5	256	Adam [48]	5

E.2 Architecture Hyper-parameters

The network hyper-parameters (e.g. hidden dimension, number of hidden layers, etc) used for the experiments and results (Section **??**) are specified in Table 5.

Table 5: Architecture hyper-parameters for SAC [50], PPO [51], the base reward model (used for PEBBLE [4] and PrePPO [3, 4]), the SAF reward model (Section 4.1), and the SPR model (Section 4.1). The hyper-parameters reported here are intended to inform the values to used to initialize the architectures in Appendix D. Hyper-parameters not relevant to a model are indicated with "N/A". The SPR model is what REED uses to construct the self-supervised temporal consistency task. The base reward model is used with PEBBLE and PrefPPO in Lee et al. [4] and [10]. The SAF reward network is used for all REED conditions in Section **??**. The "Final Activation" refers to the activation function used just prior to predicting the reward for a given state action pair. The action embedding sizes are the same for the state-space and image-space observations.

HYPER-PARAMETER	SAC	PPO	BASE REWARD	SAF REWARD	SPR NET
STATE-SPACE OBSERVATIONS					
State embed size	N/A	N/A	N/A	20 (walker), 17 (cheetah), 78 (quadruped), 30 (Meta-World)	20 (walker), 17 (cheetah), 78 (quadruped), 30 (Meta-World)
Action embed size	N/A	N/A	N/A	10 (walker), 6 (cheetah), 12 (quadruped), 4 (Meta-World)	10 (walker), 6 (cheetah), 12 (quadruped), 4 (Meta-World)
Comparison units	N/A	N/A	N/A	N/A	5 (walker), 4 (cheetah), 10 (quadruped), 5 (Meta-World)
Num. hidden	2 (DMC), 3 (Meta-World)	3	3	3	3
Units per layer	1024 (DMC), 256 (Meta-World)	256	256	256	256
Final activation	N/A	N/A	tanh	tanh	N/A
IMAGE-SPACE OBSERVATIONS					
State embed size	N/A	N/A	N/A	20 (walker), 17 (cheetah), 78 (quadruped), 30 (Meta-World)	20 (walker), 17 (cheetah), 78 (quadruped), 30 (Meta-World)
Comparison units	N/A	N/A	N/A	N/A	128
Num. hidden	2 (DMC), 3 (Meta-World)	3	3	3	3
Units per layer	1024 (DMC), 256 (Meta-World)	256	256	256	256
Final activation	N/A	N/A	tanh	tanh	N/A

F SAF Reward Net Ablation

Figure 5: Ablation of the SAF reward net for walker-walk, quadruped-walk, sweep into, and button press with 500 (walker and quadruped) and 5k (sweep into and button press) teacher-labelled queries with disagreement-based sampling and the oracle labelling strategy.

We present results ablating the impact of our modified SAF reward network architecture in Table 6, see Section 4.1, State-Action Fusion Reward Network, for details. In our ablation, we replace the original PEBBLE reward network architecture from [4] with our SAF network and then evaluate on the joint experimental condition with no other changes to reward function learning. We evaluate the impact of the SAF reward network on the walker-walk, quadruped-walk, sweep into, and button press tasks. Policy and reward function learning is evaluated across feedback amounts and labelling styles. All hyper-parameters match those used in all other experiments in the paper (see Appendix E). We compare PEBBLE with the SAF reward network architecture (PEBBLE + SAF) against SAC trained on the ground truth reward, PEBBLE with the original architecture (PEBBLE), PEBBLE with Distillation REED (PEBBLE+Dist.), and PEBBLE with Contrastive REED (PEBBLE+Contr.).

The inclusion of the SAF reward network architecture does not meaningfully impact policy performance. In general, across domains and experimental conditions, PEBBLE + SAF performs on par with or slightly worse than PEBBLE. The lack of performance improvements suggest that the performance improvements observed when the auxiliary temporal consistency objective are due to the auxiliary objective and not the change in network architecture.

Table 6: The impact of the SAF reward network is ablated. Ratio of policy performance on learned versus ground truth rewards for **walker-walk**, **quadruped-walk**, **sweep into**, and **button press** across preference learning methods, labelling methods and feedback amounts (with disagreement sampling).

FEEDBACK	METHOD	ORACLE	MISTAKE	EQUAL	SKIP	MYOPIC	NOISY	MEAN
				WALKER-WALK				
1K	PEBBLE	0.85 (0.17)	0.76 (0.21)	0.88 (0.16)	0.85 (0.17)	0.79 (0.18)	0.81 (0.18)	0.83
	+SAF	0.81 (0.19)	0.62 (0.18)	0.88 (0.16)	0.81 (0.19)	0.74 (0.17)	0.81 (0.19)	0.78
	+DIST.	0.9 (0.16)	0.77 (0.2)	0.91 (0.12)	0.89 (0.16)	0.8 (0.17)	0.88 (0.17)	0.86
	+CONTR.	0.9 (0.16)	0.77 (0.2)	0.91 (0.12)	0.89 (0.16)	0.8 (0.17)	0.88 (0.17)	0.86
500	PEBBLE	0.74 (0.18)	0.61 (0.17)	0.84 (0.19)	0.75 (0.19)	0.67 (0.19)	0.69 (0.19)	0.72
	+SAF	0.68 (0.17)	0.51 (0.13)	0.76 (0.17)	0.68 (0.17)	0.56 (0.15)	0.68 (0.17)	0.65
	+DIST.	0.86 (0.2)	0.71 (0.2)	0.87 (0.2)	0.87 (0.2)	0.82 (0.22)	0.84 (0.2)	0.83
	+CONTR.	0.9 (0.17)	0.81 (0.19)	0.9 (0.14)	0.9 (0.17)	0.88 (0.16)	0.88 (0.18)	0.88
250	PEBBLE	0.59 (0.17)	0.41 (0.12)	0.67 (0.2)	0.56 (0.17)	0.43 (0.13)	0.51 (0.13)	0.53
	+SAF	0.53 (0.16)	0.41 (0.15)	0.59 (0.18)	0.53 (0.16)	0.36 (0.1)	0.48 (0.14)	0.48
	+DIST.	0.8 (0.23)	0.6 (0.16)	0.85 (0.21)	0.8 (0.24)	0.75 (0.26)	0.8 (0.24)	0.77
	+CONTR.	0.85 (0.19)	0.73 (0.23)	0.85 (0.19)	0.85 (0.2)	0.79 (0.2)	0.85 (0.22)	0.82
				QUADRUPED-WALK				
2K	PEBBLE	0.94 (0.15)	0.55 (0.19)	1.1 (0.26)	1.0 (0.16)	0.93 (0.13)	0.56 (0.19)	0.86
	+SAF	0.97 (0.15)	0.45 (0.17)	1.2 (0.22)	0.87 (0.19)	0.76 (0.13)	0.59 (0.14)	0.81
	+DIST.	1.3 (0.31)	0.47 (0.19)	1.4 (0.37)	1.3 (0.26)	1.2 (0.18)	0.96 (0.15)	1.09
	+CONTR.	1.3 (0.25)	0.7 (0.16)	1.2 (0.24)	1.3 (0.29)	1.3 (0.28)	1.0 (0.16)	1.13
1K	PEBBLE	0.86 (0.15)	0.53 (0.19)	0.88 (0.15)	0.91 (0.14)	0.73 (0.18)	0.48 (0.25)	0.73
	+SAF	0.79 (0.16)	0.44 (0.19)	0.99 (0.23)	0.9 (0.19)	0.63 (0.15)	0.6 (0.2)	0.72
	+DIST.	1.1 (0.19)	0.59 (0.14)	1.2 (0.22)	1.3 (0.3)	1.1 (0.21)	1.0 (0.15)	1.04
	+CONTR.	1.1 (0.19)	0.63 (0.16)	1.2 (0.29)	1.1 (0.19)	1.1 (0.19)	0.83 (0.14)	0.99
500	PEBBLE	0.56 (0.21)	0.48 (0.21)	0.66 (0.2)	0.64 (0.15)	0.47 (0.22)	0.48 (0.23)	0.55
	+SAF	0.63 (0.16)	0.4 (0.22)	0.85 (0.14)	0.75 (0.19)	0.56 (0.18)	0.5 (0.19)	0.61
	+DIST.	1.1 (0.21)	0.58 (0.16)	1.2 (0.24)	1.0 (0.22)	1.0 (0.19)	0.68 (0.16)	0.93
	+CONTR.	1.1 (0.21)	0.64 (0.11)	1.1 (0.22)	1.1 (0.17)	1.0 (0.17)	0.85 (0.14)	0.97
250	PEBBLE	0.53 (0.18)	0.36 (0.23)	0.64 (0.15)	0.62 (0.16)	0.46 (0.22)	0.47 (0.21)	0.51
	+SAF	0.51 (0.2)	0.36 (0.22)	0.73 (0.18)	0.53 (0.17)	0.53 (0.19)	0.45 (0.24)	0.52
	+DIST.	0.98 (0.15)	0.58 (0.18)	1.0 (0.19)	0.79 (0.12)	0.9 (0.18)	0.77 (0.16)	0.84
	+CONTR.	0.98 (0.15)	0.58 (0.18)	1.0 (0.19)	0.79 (0.12)	0.9 (0.18)	0.77 (0.16)	0.84
				BUTTON PRESS				
20K	PEBBLE	0.72 (0.26)	0.57 (0.26)	0.77 (0.25)	0.75 (0.26)	0.68 (0.21)	0.72 (0.24)	0.70
	+SAF	0.77 (0.23)	0.72 (0.28)	0.84 (0.23)	0.75 (0.24)	0.78 (0.21)	0.77 (0.22)	0.77
	+CONTR.	0.65 (0.25)	0.61 (0.28)	0.67 (0.27)	0.67 (0.27)	0.67 (0.24)	0.69 (0.26)	0.66
10K	PEBBLE	0.66 (0.26)	0.47 (0.21)	0.67 (0.27)	0.63 (0.26)	0.67 (0.24)	0.6 (0.26)	0.62
	+SAF	0.7 (0.25)	0.66 (0.26)	0.74 (0.23)	0.71 (0.25)	0.67 (0.19)	0.71 (0.25)	0.70
	+CONTR.	0.65 (0.27)	0.61 (0.3)	0.66 (0.27)	0.62 (0.26)	0.6 (0.25)	0.68 (0.28)	0.64
5K	PEBBLE	0.48 (0.21)	0.31 (0.12)	0.56 (0.25)	0.54 (0.24)	0.59 (0.23)	0.52 (0.23)	0.50
	+SAF	0.63 (0.25)	0.55 (0.24)	0.65 (0.26)	0.68 (0.24)	0.62 (0.21)	0.7 (0.24)	0.64
	+CONTR.	0.55 (0.24)	0.54 (0.26)	0.65 (0.27)	0.63 (0.26)	0.57 (0.24)	0.63 (0.28)	0.60
2.5K	PEBBLE	0.37 (0.18)	0.21 (0.088)	0.44 (0.21)	0.34 (0.15)	0.4 (0.17)	0.34 (0.18)	0.35
	+SAF	0.58 (0.26)	0.38 (0.17)	0.61 (0.26)	0.54 (0.23)	0.52 (0.21)	0.54 (0.2)	0.53
	+CONTR.	0.49 (0.25)	0.42 (0.22)	0.52 (0.24)	0.5 (0.23)	0.44 (0.17)	0.45 (0.21)	0.47
				SWEEP INTO				
20K	PEBBLE	0.53 (0.25)	0.26 (0.15)	0.51 (0.23)	0.52 (0.27)	0.47 (0.28)	0.47 (0.26)	0.46
	+SAF	0.5 (0.24)	0.36 (0.15)	0.47 (0.22)	0.39 (0.19)	0.49 (0.21)	0.6 (0.21)	0.47
	+CONTR.	0.5 (0.22)	0.36 (0.13)	0.41 (0.2)	0.6 (0.22)	0.54 (0.21)	0.61 (0.25)	0.50
10K	PEBBLE	0.28 (0.12)	0.22 (0.13)	0.45 (0.21)	0.33 (0.17)	0.47 (0.25)	0.51 (0.24)	0.38
	+SAF	0.41 (0.2)	0.32 (0.19)	0.48 (0.2)	0.47 (0.17)	0.46 (0.2)	0.57 (0.24)	0.45
	+CONTR.	0.47 (0.23)	0.3 (0.14)	0.45 (0.24)	0.32 (0.21)	0.42 (0.22)	0.44 (0.21)	0.40
5K	PEBBLE	0.17 (0.099)	0.17 (0.089)	0.28 (0.19)	0.24 (0.15)	0.23 (0.13)	0.22 (0.12)	0.22
	+SAF	0.36 (0.15)	0.2 (0.13)	0.4 (0.23)	0.38 (0.17)	0.19 (0.11)	0.41 (0.2)	0.32
	+CONTR.	0.34 (0.14)	0.23 (0.19)	0.52 (0.24)	0.37 (0.2)	0.4 (0.24)	0.44 (0.18)	0.38
2.5K	PEBBLE	0.15 (0.086)	0.13 (0.076)	0.16 (0.1)	0.16 (0.09)	0.18 (0.075)	0.25 (0.11)	0.17
	+SAF	0.33 (0.19)	0.12 (0.082)	0.32 (0.17)	0.18 (0.09)	0.27 (0.11)	0.22 (0.14)	0.25
	+CONTR.	0.21 (0.13)	0.19 (0.22)	0.29 (0.17)	0.17 (0.09)	0.25 (0.15)	0.28 (0.16)	0.23

G   Image Aug. Task Details

We present results ablating the impact of environment dynamics on top of the PEBBLE model to show how much of the REED gains come from encoding environment dynamics versus incorporating an auxiliary task. In our ablation, we replace the REED auxiliary task with an image-augmentation-based self-supervised learning auxiliary task that compares a batch of image observation states with augmented versions of the same observations using either LSS (Equation 3), or LC (Equation 4). We compare the impact of the SSL data augmentation auxiliary task (PEBBLE + Img. Aug.) with the impact of PEBBLE + REED on the image-based PEBBLE preference learning algorithm using the walker-walk, quadruped-walk, and cheetah-run DMC tasks. Policy and reward function learning is evaluated across feedback amounts and with the oracle labeler. All hyper-parameters match those specified in Appendix E, with the exception of those listed below (Table 7).

The Img. Aug. task learns representations of the state, not state-action pairs, as is done in REED, and so the Img. Aug. representations do not encode environment dynamics. To separate out states and actions, the Img. Aug. task uses the SAF reward model architecture. The data augmentations match those used in [53].

The PEBBLE + Img. Aug. algorithm is the same as PEBBLE + REED (Algorithm C), except, instead of updating the SPR network using the temporal dynamics task, the SSL Image Augmentation network (Appendix G.2) is updated using the image-augmentation task. The state encoder is shared between the reward and the SSL Image Augmentation networks.

The inclusion of an auxiliary task to improve the state encodings does improve the performance of PEBBLE, but does not improve as much as with the encoded environment dynamics. This can be seen across feedback types and DMC environments (see Figure 6 and Table 11). The performance improvement against the PEBBLE baseline suggests that having the auxiliary task does have some benefit. However, the performance improvements of REED against the image augmentation auxiliary task suggest that the performance improvements observed when the auxiliary task encodes environment dynamics gives meaningful improvements.

G.1   Data Augmentation Parameters

This section presents the PEBBLE + Img. Aug. method for creating the augmented image observations. We evaluate the impact of both the "weak" and "strong" image augmentations used in [53]. The augmentation parameters for both the weak and strong styles are given in Table 8.

Table 7: Image Augmentation hyper-parameters for the PEBBLE reward + SSL model that differ from the parameters outlined in Appendix E.

HYPER-PARAMETER	VALUE
REWARD MODEL	
Learning Rate	1e-4
Grayscale Images	False
Normalize Images	True
SSL DATA AUGMENTATION MODEL	
Learning Rate	5e-5
Grayscale Images	False
Normalize Images	True
Use Strong Augmentations (Table 8)	False
Batch Size	256
Loss	Distillation

Table 8: Data Augmentation hyper-parameters for PEBBLE+SSL as specified in MOSAIC [53].

HYPER-PARAMETER	VALUE
WEAK AUGMENTATIONS	
Random Jitter (ρ)	0.01
Normalization (μ, σ)	[0.485, 0.456, 0.406], [0.229, 0.224, 0.225]
Random Resize Crop (scale min/max, ratio)	[0.7, 1.0], [1.8, 1.8]
STRONG AUGMENTATIONS	
Random Jitter (ρ)	0.01
Random Grayscale (ρ)	0.01
Random Horizontal Flip (ρ)	0.01
Normalization (μ, σ)	[0.485, 0.456, 0.406], [0.229, 0.224, 0.225]
Random Gaussian Blur (σ min/max, ρ)	[0.1, 2.0], 0.01
Random Resize Crop (scale min/max, ratio)	[0.6, 1.0], [1.8, 1.8]

G.2 SSL Data Augmentation Architecture

The SSL Image Augmentation network is implemented in PyTorch. The architecture for the consistency_predictor comes from [53]. The image encoder architecture comes from [54]. The SSL network is initialized as follows:

```python
def build_ssl_network(self,
                      state_size: t.List[int],
                      state_embed_size: int,
                      consistency_projection_size: int,
                      consistency_comparison_hidden_size: int,
                      with_consistency_prediction_head: bool,
                      image_hidden_num_channels: int):
    """
    The network architecture and build logic to the complete the REED
    self-supervised temporal consistency task based on SPR.
    Args:
    state_size: dimensionality of the states
    state_embed_size: number of dimensions in the state embedding
    consistency_projection_size: number of units used to compare the
                                 predicted and target latent next
                                 state
    consistency_comparison_hidden_size: number of units in the hidden
                                        layers of the next_state_projector
                                        and the consistency_predictor
    with_consistency_prediction_head: when using the contrastive of
                                      objective the consistency
                                      prediction is not used, but is
                                      when using the distillation
                                      objective
    image_hidden_num_channels: the number of channels to use in the
                               image encoder's hidden layers
    """

    # Build the network that will encode the state features.
    state_conv_encoder = nn.Sequential(
        nn.Conv2d(state_size[0], image_hidden_num_channels, 3, stride=1),
        nn.ReLU(),
        nn.MaxPool2d(2, 2),
        nn.Conv2d(
            image_hidden_num_channels,
            image_hidden_num_channels,
            3, stride=1),
        nn.ReLU(),
        nn.MaxPool2d(2, 2),
        nn.Conv2d(
            image_hidden_num_channels,
            image_hidden_num_channels,
            3, stride=1),
        nn.ReLU(),
        nn.MaxPool2d(2, 2)
    )
    conv_out_size = torch.flatten(state_conv_encoder(torch.rand(size=[1] + list(state_size
    self.state_encoder = nn.Sequential(
        state_conv_encoder,
        nn.Linear(conv_out_size, state_embed_size),
        nn.LeakyReLU(negative_slope=1e-2)
    )

    self.consistency_projector = nn.Sequential(
        # Rearrange('B T d H W -> (B T) d H W'),
        nn.BatchNorm1d(state_embed_size), nn.ReLU(inplace=True),
        # Rearrange('BT d H W -> BT (d H W)'),
        nn.Linear(state_embed_size, consistency_comparison_hidden_size), nn.ReLU(inplace=T
```

```
940            nn.Linear(consistency_comparison_hidden_size, consistency_projection_size),
941            nn.LayerNorm(consistency_projection_size)
942        )
943        # from: https://github.com/rll-research/mosaic/blob/561814b40d33f853aeb93f1113a301508
944        if with_consistency_prediction_head:
945            self.consistency_predictor = nn.Sequential(
946                nn.ReLU(inplace=True),
947                nn.Linear(consistency_projection_size, consistency_comparison_hidden_size),
948                nn.ReLU(inplace=True),
949                nn.Linear(consistency_comparison_hidden_size, consistency_projection_size),
950                nn.LayerNorm(consistency_projection_size))
951        else:
952            self.consistency_predictor = None
```

A forward pass through the SSL network is as follows:

```
954    def ssl_forward(self,
955                    observations: RawAugmentedObservationsBatch,
956                    with_consistency_prediction_head: bool):
957        """
958        The logic for a forward pass through the SSL network.
959        Args:
960          observations: a batch of environment raw observations and
961                        augmented observations
962          with_consistency_prediction_head: when using the contrastive
963                                            objective the consistency
964                                            prediction is not used, but is
965                                            when using the distillation
966                                            objective
967        Returns:
968          predicted embedding of the augmented state and the augmented state embedding (detac
969          dimensionality: (batch, time step)
970        """
971
972        # Encode the observations.
973        observations_embed = self.state_encoder(observations.states)
974
975        # Predict the augmented observations.
976        if with_consistency_prediction_head:
977            augmented_observation_pred = self.consistency_predictor(self.state_projector(obse
978        else:
979            augmented_observation_pred = self.state_projector(observations_embed)
980
981        # we don't want gradients to back-propagate into the learned parameters from anything
982        with torch.no_grad():
983            # embed the augmented observation
984            augmented_observation_embed = self.state_encoder(observations.augmented_states)
985            # project the augmented observation embedding into a space where it can be compar
986            projected_agumented_observation_embed = self.state_projector(augmented_observatio
987
988        return augmented_observation_pred, projected_agumented_observation_embed
```

G.3 Image Aug. Auxiliary Task Results

We present results comparing the impact of REED's temporal auxiliary task and the Image Aug. auxiliary task. Learning curves (Figure 6) and normalized returns (Table 9) are provided for image-space observation walker-walk, cheetah-run, and quadruped-walk tasks across different amounts of feedback. We compare the contributions of the Image Aug. auxiliary task to PEBBLE against SAC trained on the ground truth reward, PEBBLE, PEBBLE + Distillation REED (+Dist.), and PEBBLE + Contrastive REED (+Contr.). Results are reported for the Image Aug. task using the distillation objective (Equation 3) as +Dist.+Img. Aug.

The inclusion of the Image Aug. auxiliary task improves performance relative to PEBBLE, but does not reach the level of performance achieved by REED. The gap policy performance between REED and the Image Aug. auxiliary task suggests that encoding environment dynamics in the reward function and not including an auxiliary task that trains on all policy experiences is the cause of the performance gains observed from REED.

Figure 6: Episode returns learning curves for **walker walk**, **quadruped walk**, and **cheetah run** across preference-based RL methods and feedback amounts for image-based observations. The oracle labeller is used to generate preference feedback. Mean policy returns are plotted along the y-axis with number of steps (in units of 1000) along the x-axis. There is one plot per environment (grid columns) and feedback amount (grid rows) with corresponding results per learning methods in each plot. The learning methods evaluated are SAC trained on the ground truth reward, PEBBLE, PEBBLE with the Image Aug. auxiliary task (pebble+img. aug.), PEBBLE + Distillation REED (pebble+dist.), and PEBBLE + Contrastive REED (pebble+contr.). From top to bottom, the rows correspond to 2.5k, 5k, 10k, and 20k pieces of teacher feedback. From left to right, the columns correspond to walker walk, quadruped walk, and cheetah run.

Table 9: Ratio of policy performance on learned versus ground truth rewards for **walker-walk**, **cheetah-run**, and **quadruped-walk** across feedback amounts (with disagreement sampling). The results are reported as means (standard deviations) over 10 random seeds.

		DMC					
TASK	METHOD	50	100	250	500	1000	MEAN
WALKER-WALK	PEBBLE	0.06 (0.02)	0.07 (0.02)	0.09 (0.02)	0.11 (0.03)	0.11 (0.03)	0.09
	+DIST.	0.18 (0.03)	0.33 (0.10)	0.40 (0.09)	0.57 (0.16)	0.68 (0.23)	0.43
	+CONTR.	0.28 (0.12)	0.35 (0.13)	0.46 (0.14)	0.58 (0.14)	0.61 (0.16)	0.46
	+DIST.+IMG.AUG.	0.06 (0.02)	0.10 (0.02)	0.16 (0.02)	0.24 (0.03)	0.46 (0.11)	0.20
QUADRUPED-WALK	PEBBLE	0.28 (0.23)	0.23 (0.19)	0.23 (0.15)	0.23 (0.19)	0.47 (0.09)	0.29
	+DIST.	0.56 (0.15)	0.59 (0.16)	0.61 (0.12)	0.71 (0.14)	0.72 (0.19)	0.64
	+CONTR.	0.53 (0.16)	0.64 (0.10)	0.69 (0.17)	0.73 (0.22)	0.71 (0.16)	0.66
	+DIST.+IMG.AUG.	0.43 (0.19)	0.35 (0.17)	0.42 (0.17)	0.68 (0.17)	0.62 (0.16)	0.50
CHEETAH-RUN	PEBBLE	0.01 (0.01)	0.02 (0.01)	0.02 (0.02)	0.02 (0.03)	0.03 (0.02)	0.02
	+DIST.	0.06 (0.03)	0.07 (0.04)	0.07 (0.02)	0.12 (0.04)	0.18 (0.07)	0.10
	+CONTR.	0.05 (0.02)	0.14 (0.04)	0.14 (0.04)	0.23 (0.09)	0.16 (0.06)	0.14
	+DIST.+IMG.AUG.	0.02 (0.01)	0.05 (0.02)	0.14 (0.05)	0.11 (0.04)	0.12 (0.05)	0.09

H Complete Joint Results

Results are presented for all tasks, feedback amounts, and teacher labelling styles. The benefits of the SPR rewards are greatest: 1) for increasingly more challenging tasks, 2) when there is limited feedback available, and 3) when the labels are increasingly noisy.

H.1 State-space Observations Learning Curves

Learning curves are provided for walker-walk (Figure 7), cheetah-run (Figure 8), quadruped-walk (Figure 9), button press (Figure 10), and sweep into (Figure 11) across feedback amounts and all teacher labelling strategies for state-space observations.

Figure 7: Returns learning curves for **walker-walk** across preference-based RL methods, labelling style, and feedback amount for state-space observations. Mean policy returns are plotted along the y-axis with number of steps (in units of 1000) along the x-axis. There is one plot per labelling style (grid columns) and feedback amount (grid rows) with corresponding results per learning methods in each plot. From top to bottom, the rows correspond to 50, 100, 500, and 1000 pieces of teacher feedback. From left to right, the columns correspond to equal, noisy, mistake, myopic, oracle, and skip labelling styles (see Appendix B for details).

Figure 8: Returns learning curves for **cheetah-run** across preference-based RL methods, labelling style, and feedback amount for state-space observations. Mean policy returns are plotted along the y-axis with number of steps (in units of 1000) along the x-axis. There is one plot per labelling style (grid columns) and feedback amount (grid rows) with corresponding results per learning methods in each plot. From top to bottom, the rows correspond to 50, 100, 500, and 1000 pieces of teacher feedback. From left to right, the columns correspond to equal, noisy, mistake, myopic, oracle, and skip labelling styles (see Appendix B for details).

Figure 9: Returns learning curves for **quadruped-walk** across preference-based RL methods, labelling style, and feedback amount for state-space observations. Mean policy returns are plotted along the y-axis with number of steps (in units of 1e6) along the x-axis. There is one plot per labelling style (grid columns) and feedback amount (grid rows) with corresponding results per learning methods in each plot. From top to bottom, the rows correspond to 50, 100, 500, 1000, and 2000 pieces of teacher feedback. From left to right, the columns correspond to equal, noisy, mistake, myopic, oracle, and skip labelling styles (see Appendix B for details).

Figure 10: Success rate learning curves for **button press** across preference-based RL methods, labelling style, and feedback amount for state-space observations. Mean success rates are plotted along the y-axis with number of steps (in units of 1000) along the x-axis. There is one plot per labelling style (grid columns) and feedback amount (grid rows) with corresponding results per learning methods in each plot. From top to bottom, the rows correspond to 2.5k, 5k, 10k, and 20k pieces of teacher feedback. From left to right, the columns correspond to equal, noisy, mistake, myopic, oracle, and skip labelling styles (see Appendix B for details).

Figure 11: Success rate learning curves for **sweep into** across preference-based RL methods, labelling style, and feedback amount for state-space observations. Mean success rates are plotted along the y-axis with number of steps (in units of 1000) along the x-axis. There is one plot per labelling style (grid columns) and feedback amount (grid rows) with corresponding results per learning methods in each plot. From top to bottom, the rows correspond to 2.5k, 5k, 10k, and 20k pieces of teacher feedback. From left to right, the columns correspond to equal, noisy, mistake, myopic, oracle, and skip labelling styles (see Appendix B for details).

H.2 State-space Normalized Returns

The normalized returns (see Section **??** and Equation 5) for walker-walk, quadruped-walk, cheetah-run, button press, and sweep into, across all teacher labelling styles and a larger range of feedback amounts for state-space observations, are given in Table 10.

Table 10: Ratio of policy performance on learned versus ground truth rewards for **walker-walk**, **cheetah-run**, **quadruped-walk**, **sweep into**, and **button press** across preference learning methods, labelling methods and feedback amounts (with disagreement sampling). The results are reported as means (standard deviations) over 10 random seeds.

FEEDBACK	METHOD	ORACLE	MISTAKE	EQUAL	SKIP	MYOPIC	NOISY	MEAN
				WALKER-WALK				
	PEBBLE	0.85 (0.17)	0.76 (0.21)	0.88 (0.16)	0.85 (0.17)	0.79 (0.18)	0.81 (0.18)	0.83
	+DIST.	0.9 (0.16)	0.77 (0.2)	0.91 (0.12)	0.89 (0.16)	0.8 (0.17)	0.88 (0.17)	0.86
	+CONTR.	0.9 (0.16)	0.77 (0.2)	0.91 (0.12)	0.89 (0.16)	0.8 (0.17)	0.88 (0.17)	0.86
1K								
	PREFPPO	1.0 (0.034)	0.92 (0.056)	1.0 (0.029)	1.0 (0.031)	1.0 (0.044)	0.96 (0.056)	0.99
	+DIST.	1.1 (0.025)	0.92 (0.05)	1.0 (0.031)	1.0 (0.02)	0.99 (0.035)	0.96 (0.046)	1.00
	+CONTR.	1.0 (0.029)	0.93 (0.043)	1.1 (0.021)	1.0 (0.028)	0.98 (0.033)	0.95 (0.045)	1.00
	PEBBLE	0.74 (0.18)	0.61 (0.17)	0.84 (0.19)	0.75 (0.19)	0.67 (0.19)	0.69 (0.19)	0.72
	+DIST.	0.86 (0.2)	0.71 (0.2)	0.87 (0.2)	0.87 (0.2)	0.82 (0.22)	0.84 (0.2)	0.83
	+CONTR.	0.9 (0.17)	0.81 (0.19)	0.9 (0.14)	0.9 (0.17)	0.88 (0.16)	0.88 (0.18)	0.88
500								
	PREFPPO	0.95 (0.052)	0.83 (0.087)	0.95 (0.044)	0.96 (0.058)	0.89 (0.076)	0.88 (0.069)	0.91
	+DIST.	0.88 (0.074)	0.81 (0.084)	0.98 (0.025)	0.95 (0.027)	0.9 (0.073)	0.9 (0.069)	0.90
	+CONTR.	0.93 (0.061)	0.85 (0.077)	0.95 (0.046)	0.92 (0.059)	0.82 (0.085)	0.77 (0.098)	0.88
	PEBBLE	0.52 (0.17)	0.46 (0.15)	0.67 (0.2)	0.54 (0.15)	0.46 (0.13)	0.45 (0.14)	0.52
	+DIST.	0.74 (0.2)	0.65 (0.21)	0.79 (0.22)	0.74 (0.19)	0.64 (0.21)	0.8 (0.25)	0.73
	+CONTR.	0.84 (0.2)	0.69 (0.2)	0.84 (0.18)	0.84 (0.2)	0.75 (0.19)	0.84 (0.21)	0.80
200								
	PREFPPO	0.93 (0.058)	0.83 (0.076)	0.93 (0.027)	0.88 (0.045)	0.87 (0.079)	0.82 (0.06)	0.88
	+DIST.	0.78 (0.087)	0.68 (0.11)	0.81 (0.062)	0.77 (0.081)	0.77 (0.077)	0.78 (0.053)	0.77
	+CONTR.	0.81 (0.088)	0.81 (0.079)	0.86 (0.044)	0.85 (0.055)	0.76 (0.13)	0.74 (0.1)	0.80
	PEBBLE	0.34 (0.11)	0.31 (0.11)	0.37 (0.1)	0.37 (0.12)	0.29 (0.085)	0.41 (0.13)	0.35
	+DIST.	0.68 (0.23)	0.57 (0.2)	0.72 (0.25)	0.67 (0.23)	0.61 (0.19)	0.66 (0.24)	0.65
	+CONTR.	0.78 (0.21)	0.69 (0.22)	0.74 (0.22)	0.74 (0.19)	0.68 (0.19)	0.74 (0.22)	0.73
100								
	PREFPPO	0.68 (0.08)	0.59 (0.093)	0.73 (0.065)	0.73 (0.065)	0.58 (0.11)	0.68 (0.072)	0.67
	+DIST.	0.67 (0.08)	0.63 (0.11)	0.71 (0.075)	0.71 (0.084)	0.63 (0.099)	0.63 (0.094)	0.66
	+CONTR.	0.72 (0.084)	0.49 (0.14)	0.71 (0.063)	0.65 (0.091)	0.64 (0.1)	0.58 (0.13)	0.63
	PEBBLE	0.21 (0.1)	0.22 (0.12)	0.22 (0.12)	0.23 (0.14)	0.21 (0.11)	0.18 (0.11)	0.21
	+DIST.	0.66 (0.24)	0.44 (0.13)	0.6 (0.21)	0.64 (0.24)	0.44 (0.12)	0.48 (0.15)	0.54
	+CONTR.	0.62 (0.22)	0.44 (0.11)	0.72 (0.22)	0.62 (0.22)	0.54 (0.16)	0.54 (0.17)	0.58
50								
	PREFPPO	0.51 (0.13)	0.41 (0.18)	0.57 (0.12)	0.59 (0.11)	0.51 (0.14)	0.51 (0.14)	0.52
	+DIST.	0.58 (0.13)	0.41 (0.17)	0.6 (0.13)	0.56 (0.13)	0.58 (0.12)	0.48 (0.13)	0.54
	+CONTR.	0.58 (0.12)	0.54 (0.15)	0.62 (0.12)	0.63 (0.11)	0.5 (0.13)	0.57 (0.12)	0.57

Continues on next page...

FEEDBACK	METHOD	ORACLE	MISTAKE	EQUAL	SKIP	MYOPIC	NOISY	MEAN
				CHEETAH-RUN				
	PEBBLE	0.87 (0.18)	0.82 (0.18)	0.91 (0.2)	0.89 (0.17)	0.87 (0.16)	0.82 (0.18)	0.86
	+DIST.	0.93 (0.2)	0.83 (0.18)	0.88 (0.14)	0.92 (0.16)	1.0 (0.18)	0.86 (0.21)	0.90
	+CONTR.	0.9 (0.17)	0.84 (0.18)	0.89 (0.17)	0.96 (0.17)	1.0 (0.21)	0.85 (0.13)	0.91
1K								
	PREFPPO	0.71 (0.064)	0.72 (0.086)	0.76 (0.069)	0.71 (0.076)	0.75 (0.066)	0.69 (0.093)	0.72
	+DIST.	0.67 (0.054)	0.7 (0.076)	0.75 (0.08)	0.66 (0.064)	0.79 (0.084)	0.65 (0.081)	0.70
	+CONTR.	0.7 (0.069)	0.8 (0.11)	0.72 (0.07)	0.71 (0.065)	0.78 (0.089)	0.65 (0.083)	0.73
	PEBBLE	0.86 (0.14)	0.84 (0.18)	0.86 (0.19)	0.71 (0.16)	0.79 (0.16)	0.71 (0.15)	0.79
	+DIST.	0.88 (0.22)	0.83 (0.18)	0.93 (0.15)	0.76 (0.15)	0.85 (0.14)	0.8 (0.19)	0.84
	+CONTR.	0.94 (0.21)	0.72 (0.14)	0.9 (0.21)	0.89 (0.18)	0.93 (0.18)	0.82 (0.16)	0.87
500								
	PREFPPO	0.62 (0.043)	0.63 (0.047)	0.77 (0.089)	0.66 (0.06)	0.66 (0.04)	0.72 (0.09)	0.67
	+DIST.	0.67 (0.062)	0.74 (0.14)	0.7 (0.072)	0.63 (0.069)	0.67 (0.076)	0.68 (0.081)	0.68
	+CONTR.	0.66 (0.062)	0.61 (0.072)	0.73 (0.082)	0.69 (0.065)	0.61 (0.047)	0.67 (0.073)	0.66
	PEBBLE	0.71 (0.23)	0.62 (0.22)	0.71 (0.24)	0.57 (0.2)	0.75 (0.18)	0.6 (0.22)	0.66
	+DIST.	0.77 (0.28)	0.61 (0.19)	0.77 (0.22)	0.79 (0.25)	0.76 (0.25)	0.65 (0.27)	0.72
	+CONTR.	0.73 (0.22)	0.67 (0.21)	0.83 (0.25)	0.8 (0.24)	0.83 (0.19)	0.76 (0.23)	0.77
200								
	PREFPPO	0.57 (0.042)	0.73 (0.13)	0.66 (0.059)	0.54 (0.052)	0.64 (0.073)	0.56 (0.099)	0.62
	+DIST.	0.53 (0.066)	0.52 (0.047)	0.66 (0.066)	0.53 (0.049)	0.55 (0.054)	0.57 (0.085)	0.56
	+CONTR.	0.62 (0.071)	0.49 (0.046)	0.61 (0.06)	0.63 (0.1)	0.56 (0.062)	0.58 (0.048)	0.58
	PEBBLE	0.4 (0.14)	0.4 (0.13)	0.61 (0.22)	0.47 (0.2)	0.55 (0.21)	0.42 (0.14)	0.48
	+DIST.	0.69 (0.26)	0.59 (0.22)	0.79 (0.28)	0.65 (0.29)	0.67 (0.26)	0.53 (0.21)	0.65
	+CONTR.	0.64 (0.28)	0.65 (0.21)	0.78 (0.21)	0.7 (0.29)	0.81 (0.26)	0.72 (0.25)	0.72
100								
	PREFPPO	0.46 (0.036)	0.51 (0.061)	0.58 (0.051)	0.58 (0.054)	0.6 (0.047)	0.59 (0.054)	0.55
	+DIST.	0.49 (0.036)	0.47 (0.088)	0.49 (0.046)	0.49 (0.038)	0.52 (0.04)	0.52 (0.081)	0.50
	+CONTR.	0.54 (0.037)	0.51 (0.06)	0.59 (0.085)	0.5 (0.059)	0.59 (0.061)	0.45 (0.039)	0.53
	PEBBLE	0.35 (0.11)	0.26 (0.098)	0.39 (0.14)	0.39 (0.12)	0.4 (0.15)	0.24 (0.089)	0.34
	+DIST.	0.63 (0.23)	0.59 (0.27)	0.69 (0.25)	0.62 (0.23)	0.68 (0.31)	0.46 (0.22)	0.61
	+CONTR.	0.7 (0.28)	0.51 (0.21)	0.72 (0.28)	0.53 (0.2)	0.66 (0.28)	0.66 (0.28)	0.63
50								
	PREFPPO	0.5 (0.066)	0.49 (0.07)	0.44 (0.076)	0.4 (0.038)	0.34 (0.062)	0.3 (0.066)	0.41
	+DIST.	0.44 (0.041)	0.38 (0.039)	0.44 (0.082)	0.3 (0.063)	0.44 (0.085)	0.47 (0.11)	0.41
	+CONTR.	0.47 (0.051)	0.42 (0.039)	0.47 (0.093)	0.43 (0.038)	0.46 (0.039)	0.31 (0.061)	0.43
				QUADRUPED-WALK				
2K	PEBBLE	0.94 (0.15)	0.55 (0.19)	1.1 (0.26)	1.0 (0.16)	0.93 (0.13)	0.56 (0.19)	0.86
	+DIST.	1.3 (0.31)	0.47 (0.19)	1.4 (0.37)	1.3 (0.26)	1.2 (0.18)	0.96 (0.15)	1.09

FEEDBACK	METHOD	ORACLE	MISTAKE	EQUAL	SKIP	MYOPIC	NOISY	MEAN
	+CONTR.	1.3 (0.25)	0.7 (0.16)	1.2 (0.24)	1.3 (0.29)	1.3 (0.28)	1.0 (0.16)	1.13
2K	PREFPPO	1.1 (0.18)	0.89 (0.18)	1.2 (0.22)	1.2 (0.17)	1.0 (0.25)	1.1 (0.18)	1.07
	+DIST.	1.1 (0.22)	1.0 (0.2)	1.2 (0.23)	1.1 (0.24)	1.1 (0.26)	0.91 (0.1)	1.06
	+CONTR.	1.0 (0.24)	0.9 (0.2)	1.4 (0.3)	1.2 (0.29)	1.1 (0.38)	1.6 (0.32)	1.28
	PEBBLE	0.86 (0.15)	0.53 (0.19)	0.88 (0.15)	0.91 (0.14)	0.73 (0.18)	0.48 (0.25)	0.73
	+DIST.	1.1 (0.19)	0.59 (0.14)	1.2 (0.22)	1.3 (0.3)	1.1 (0.21)	1.0 (0.15)	1.04
	+CONTR.	1.1 (0.19)	0.63 (0.16)	1.2 (0.29)	1.1 (0.19)	1.1 (0.19)	0.83 (0.14)	0.99
1K	PREFPPO	0.9 (0.17)	0.88 (0.17)	1.1 (0.15)	0.98 (0.21)	0.89 (0.18)	0.83 (0.17)	0.92
	+DIST.	1.2 (0.21)	0.88 (0.23)	1.2 (0.27)	1.2 (0.23)	1.1 (0.26)	1.1 (0.16)	1.11
	+CONTR.	1.1 (0.19)	0.68 (0.28)	1.2 (0.25)	1.1 (0.2)	0.82 (0.31)	0.56 (0.25)	0.82
	PEBBLE	0.56 (0.21)	0.48 (0.21)	0.66 (0.2)	0.64 (0.15)	0.47 (0.22)	0.48 (0.23)	0.55
	+DIST.	1.1 (0.21)	0.58 (0.16)	1.2 (0.24)	1.0 (0.22)	1.0 (0.19)	0.68 (0.16)	0.93
	+CONTR.	1.1 (0.21)	0.64 (0.11)	1.1 (0.22)	1.1 (0.17)	1.0 (0.17)	0.85 (0.14)	0.97
500	PREFPPO	0.8 (0.18)	0.81 (0.22)	0.96 (0.12)	0.72 (0.18)	0.74 (0.24)	0.88 (0.17)	0.82
	+DIST.	1.1 (0.2)	0.76 (0.19)	1.0 (0.2)	1.1 (0.25)	0.89 (0.21)	0.81 (0.25)	0.95
	+CONTR.	1.1 (0.21)	0.63 (0.25)	0.9 (0.28)	0.89 (0.22)	0.88 (0.16)	1.5 (0.48)	0.95
	PEBBLE	0.54 (0.19)	0.49 (0.22)	0.64 (0.15)	0.46 (0.2)	0.43 (0.22)	0.48 (0.23)	0.51
	+DIST.	0.9 (0.17)	0.57 (0.17)	0.77 (0.16)	0.89 (0.14)	0.76 (0.11)	0.68 (0.15)	0.76
	+CONTR.	0.95 (0.15)	0.53 (0.16)	0.86 (0.16)	0.88 (0.14)	0.77 (0.12)	0.74 (0.16)	0.79
200	PREFPPO	0.7 (0.23)	0.59 (0.28)	0.82 (0.17)	0.65 (0.27)	0.8 (0.25)	0.82 (0.27)	0.73
	+DIST.	0.89 (0.15)	0.79 (0.23)	0.95 (0.18)	0.87 (0.16)	0.76 (0.26)	0.79 (0.17)	0.84
	+CONTR.	1.0 (0.33)	0.7 (0.15)	0.95 (0.21)	0.86 (0.18)	1.2 (0.43)	1.2 (0.24)	1.01
	PEBBLE	0.38 (0.21)	0.47 (0.17)	0.64 (0.14)	0.42 (0.22)	0.46 (0.2)	0.44 (0.22)	0.47
	+DIST.	0.78 (0.16)	0.54 (0.2)	0.98 (0.19)	0.72 (0.15)	0.75 (0.16)	0.67 (0.18)	0.74
	+CONTR.	0.67 (0.18)	0.47 (0.2)	0.89 (0.14)	0.76 (0.15)	0.79 (0.17)	0.65 (0.19)	0.71
100	PREFPPO	0.56 (0.31)	0.81 (0.31)	0.66 (0.22)	0.62 (0.28)	0.51 (0.31)	0.6 (0.29)	0.63
	+DIST.	1.0 (0.24)	0.8 (0.23)	0.82 (0.19)	0.71 (0.23)	0.76 (0.17)	0.81 (0.26)	0.82
	+CONTR.	0.91 (0.19)	0.52 (0.42)	0.61 (0.32)	0.6 (0.27)	0.99 (0.21)	0.53 (0.37)	0.69
	PEBBLE	0.38 (0.26)	0.4 (0.23)	0.49 (0.2)	0.42 (0.25)	0.42 (0.26)	0.36 (0.26)	0.41
	+DIST.	0.65 (0.16)	0.47 (0.24)	0.77 (0.14)	0.68 (0.18)	0.67 (0.2)	0.56 (0.19)	0.63
	+CONTR.	0.83 (0.12)	0.49 (0.23)	0.8 (0.14)	0.65 (0.18)	0.69 (0.16)	0.62 (0.19)	0.68
50	PREFPPO	0.68 (0.3)	0.64 (0.28)	0.58 (0.28)	0.49 (0.26)	0.49 (0.3)	0.5 (0.31)	0.56
	+DIST.	0.9 (0.19)	0.71 (0.29)	0.9 (0.25)	0.83 (0.18)	0.68 (0.26)	0.77 (0.29)	0.80
	+CONTR.	1.2 (0.34)	0.58 (0.29)	0.9 (0.27)	0.82 (0.16)	0.47 (0.44)	1.1 (0.35)	0.85

TABLE 10 – *continued from previous page*

FEEDBACK	METHOD	ORACLE	MISTAKE	EQUAL	SKIP	MYOPIC	NOISY	MEAN
				BUTTON-PRESS				
20K	PEBBLE	0.72 (0.26)	0.57 (0.26)	0.77 (0.25)	0.75 (0.26)	0.68 (0.21)	0.72 (0.24)	0.70
	+CONTR.	0.65 (0.25)	0.61 (0.28)	0.67 (0.27)	0.67 (0.27)	0.67 (0.24)	0.69 (0.26)	0.66
	PREFPPO	0.18 (0.03)	0.18 (0.04)	0.21 (0.03)	0.18 (0.03)	0.17 (0.04)	0.17 (0.04)	0.18
	+CONTR.	0.22 (0.03)	0.17 (0.03)	0.22 (0.02)	0.17 (0.03)	0.19 (0.03)	0.17 (0.04)	0.19
10K	PEBBLE	0.66 (0.26)	0.47 (0.21)	0.67 (0.27)	0.63 (0.26)	0.67 (0.24)	0.6 (0.26)	0.62
	+CONTR.	0.65 (0.27)	0.61 (0.3)	0.66 (0.27)	0.62 (0.26)	0.6 (0.25)	0.68 (0.28)	0.64
	PREFPPO	0.18 (0.03)	0.14 (0.04)	0.19 (0.03)	0.17 (0.04)	0.18 (0.03)	0.17 (0.04)	0.17
	+CONTR.	0.15 (0.04)	0.12 (0.05)	0.18 (0.03)	0.17 (0.03)	0.17 (0.03)	0.16 (0.03)	0.16
5K	PEBBLE	0.48 (0.21)	0.31 (0.12)	0.56 (0.25)	0.54 (0.24)	0.59 (0.23)	0.52 (0.23)	0.50
	+CONTR.	0.55 (0.24)	0.54 (0.26)	0.65 (0.27)	0.63 (0.26)	0.57 (0.24)	0.63 (0.28)	0.60
	PREFPPO	0.15 (0.04)	0.13 (0.05)	0.19 (0.03)	0.16 (0.04)	0.16 (0.04)	0.14 (0.04)	0.15
	+CONTR.	0.14 (0.04)	0.13 (0.05)	0.18 (0.03)	0.14 (0.04)	0.14 (0.04)	0.14 (0.03)	0.14
2.5K	PEBBLE	0.37 (0.18)	0.21 (0.088)	0.44 (0.21)	0.34 (0.15)	0.4 (0.17)	0.34 (0.18)	0.35
	+CONTR.	0.49 (0.25)	0.42 (0.22)	0.52 (0.24)	0.5 (0.23)	0.44 (0.17)	0.45 (0.21)	0.47
	PREFPPO	0.14 (0.04)	0.12 (0.05)	0.13 (0.05)	0.13 (0.05)	0.13 (0.05)	0.14 (0.05)	0.13
	+CONTR.	0.14 (0.04)	0.11 (0.05)	0.15 (0.04)	0.11 (0.04)	0.14 (0.04)	0.13 (0.04)	0.13
				SWEEP-INTO				
20K	PEBBLE	0.53 (0.25)	0.26 (0.15)	0.51 (0.23)	0.52 (0.27)	0.47 (0.28)	0.47 (0.26)	0.46
	+CONTR.	0.5 (0.22)	0.36 (0.13)	0.41 (0.2)	0.6 (0.22)	0.54 (0.21)	0.61 (0.25)	0.50
	PREFPPO	0.16 (0.046)	0.14 (0.047)	0.16 (0.069)	0.18 (0.065)	0.19 (0.063)	0.08 (0.026)	0.15
	+CONTR.	0.23 (0.064)	0.11 (0.042)	0.2 (0.058)	0.2 (0.051)	0.19 (0.054)	0.1 (0.034)	0.17
10K	PEBBLE	0.28 (0.12)	0.22 (0.13)	0.45 (0.21)	0.33 (0.17)	0.47 (0.25)	0.51 (0.24)	0.38
	+CONTR.	0.47 (0.23)	0.3 (0.14)	0.45 (0.24)	0.32 (0.21)	0.42 (0.22)	0.44 (0.21)	0.40
	PREFPPO	0.16 (0.048)	0.19 (0.064)	0.18 (0.05)	0.18 (0.049)	0.12 (0.055)	0.058 (0.024)	0.15
	+CONTR.	0.11 (0.034)	0.12 (0.046)	0.15 (0.046)	0.16 (0.056)	0.11 (0.052)	0.054 (0.029)	0.12
5K	PEBBLE	0.17 (0.099)	0.17 (0.089)	0.28 (0.19)	0.24 (0.15)	0.23 (0.13)	0.22 (0.12)	0.22
	+CONTR.	0.34 (0.14)	0.23 (0.19)	0.52 (0.24)	0.37 (0.2)	0.4 (0.24)	0.44 (0.18)	0.38
	PREFPPO	0.1 (0.039)	0.078 (0.027)	0.1 (0.032)	0.092 (0.025)	0.1 (0.038)	0.051 (0.019)	0.09
	+CONTR.	0.14 (0.052)	0.097 (0.034)	0.12 (0.032)	0.14 (0.076)	0.1 (0.026)	0.043 (0.026)	0.11
2.5K	PEBBLE	0.15 (0.086)	0.13 (0.076)	0.16 (0.1)	0.16 (0.088)	0.18 (0.075)	0.25 (0.11)	0.17

TABLE 10 – *continued from previous page*

FEEDBACK	METHOD	ORACLE	MISTAKE	EQUAL	SKIP	MYOPIC	NOISY	MEAN
	+CONTR.	0.21 (0.13)	0.19 (0.22)	0.29 (0.17)	0.17 (0.092)	0.25 (0.15)	0.28 (0.16)	0.23
2.5K	PREFPPO	0.092 (0.032)	0.097 (0.044)	0.15 (0.051)	0.15 (0.049)	0.099 (0.035)	0.032 (0.022)	0.10
	+CONTR.	0.058 (0.019)	0.048 (0.018)	0.11 (0.032)	0.072 (0.035)	0.07 (0.016)	0.036 (0.017)	0.07

H.3 Image-space Observations Learning Curves

Learning curves are provided for the walker-walk, cheetah-run, and quadruped-walk DMC tasks (Figure 12), and for the button press, sweep into, drawer open, drawer close, window open, and door close Meta-World tasks (Figure 13) across feedback amounts for image-space observations. For all image-based results, the orable labeller is used to provide the preference feedback.

Figure 12: Episode returns learning curves for **walker walk**, **quadruped walk**, and **cheetah run** across preference-based RL methods and feedback amounts for image-based observations. The oracle labeller is used to generate preference feedback. Mean policy returns are plotted along the y-axis with number of steps (in units of 1000) along the x-axis. There is one plot per environment (grid columns) and feedback amount (grid rows) with corresponding results per learning methods in each plot. From top to bottom, the rows correspond to 2.5k, 5k, 10k, and 20k pieces of teacher feedback. From left to right, the columns correspond to walker walk, quadruped walk, and cheetah run.

Figure 13: Success rate learning curves for **button press**, **sweep into**, **drawer open**, **drawer close**, **window open**, and **door close** across preference-based RL methods and feedback amounts for image-based observations. The oracle labeller is used to generate preference feedback. Mean success rates are plotted along the y-axis with number of steps (in units of 1000) along the x-axis. There is one plot per environment (grid columns) and feedback amount (grid rows) with corresponding results per learning methods in each plot. From top to bottom, the rows correspond to 2.5k, 5k, 10k, and 20k pieces of teacher feedback. From left to right, the columns correspond to button press, sweep into, drawer open, drawer close, window open, and door close.

H.4 Image-space Observations Normalized Returns

The normalized returns (see Section **??** and Equation 5) for walker-walk, quadruped-walk, cheetah-run, button press, sweep into, drawer open, drawer close, window open, and door close across a larger range of feedback amounts for image-space observations are given in Table 11.

Table 11: Ratio of policy performance on learned versus ground truth rewards for the image-observations space **walker-walk**, **cheetah-run**, **quadruped-walk**, **sweep into**, **button press**, **drawer open**, **drawer close**, **window open**, and **door open** tasks across preference learning methods, labelling methods and feedback amounts (with disagreement sampling). The results are reported as means (standard deviations) over 10 random seeds.

		DMC					
TASK	METHOD	50	100	250	500	1000	MEAN
WALKER-WALK	PEBBLE	0.06 (0.02)	0.07 (0.02)	0.09 (0.02)	0.11 (0.03)	0.11 (0.03)	0.09
	+DIST.	0.18 (0.03)	0.33 (0.10)	0.40 (0.09)	0.57 (0.16)	0.68 (0.23)	0.43
	+CONTR.	0.28 (0.12)	0.35 (0.13)	0.46 (0.14)	0.58 (0.14)	0.61 (0.16)	0.46
QUADRUPED-WALK	PEBBLE	0.28 (0.23)	0.23 (0.19)	0.23 (0.15)	0.23 (0.19)	0.47 (0.09)	0.29
	+DIST.	0.56 (0.15)	0.59 (0.16)	0.61 (0.12)	0.71 (0.14)	0.72 (0.19)	0.64
	+CONTR.	0.53 (0.16)	0.64 (0.097)	0.69 (0.17)	0.73 (0.22)	0.71 (0.16)	0.66
CHEETAH-RUN	PEBBLE	0.01 (0.01)	0.02 (0.01)	0.02 (0.02)	0.02 (0.03)	0.03 (0.02)	0.02
	+DIST.	0.07 (0.03)	0.07 (0.03)	0.07 (0.02)	0.12 (0.04)	0.18 (0.07)	0.10
	+CONTR.	0.05 (0.02)	0.14 (0.04)	0.14 (0.04)	0.23 (0.09)	0.16 (0.06)	0.14
		META-WORLD					
TASK	METHOD	2.5K	5K	10K	20K		MEAN
BUTTON PRESS	PEBBLE	0.16 (0.07)	0.20 (0.07)	0.27 (0.09)	0.33 (0.11)		0.24
	+DIST.	0.25 (0.04)	0.35 (0.09)	0.46 (0.16)	0.58 (0.23)		0.41
	+CONTR.	0.27 (0.04)	0.35 (0.10)	0.34 (0.07)	0.42 (0.11)		0.35
SWEEP INTO	PEBBLE	0.03 (0.02)	0.05 (0.03)	0.04 (0.04)	0.10 (0.08)		0.06
	+DIST.	0.06 (0.05)	0.10 (0.10)	0.10 (0.06)	0.10 (0.11)		0.09
	+CONTR.	0.10 (0.11)	0.12 (0.06)	0.11 (0.07)	0.12 (0.05)		0.11
DRAWER OPEN	PEBBLE	0.39 (0.10)	0.50 (0.12)	0.55 (0.11)	0.60 (0.14)		0.51
	+DIST.	0.55 (0.07)	0.60 (0.11)	0.65 (0.08)	0.70 (0.08)		0.63
	+CONTR.	0.60 (0.11)	0.60 (0.12)	0.67 (0.08)	0.71 (0.08)		0.64
DRAWER CLOSE	PEBBLE	0.93 (0.22)	0.82 (0.16)	0.90 (0.17)	0.86 (0.17)		0.88
	+DIST.	0.95 (0.11)	0.97 (0.12)	0.93 (0.09)	0.97 (0.06)		0.96
	+CONTR.	0.97 (0.13)	0.93 (0.11)	0.93 (0.13)	0.95 (0.08)		0.95
WINDOW OPEN	PEBBLE	0.23 (0.16)	0.18 (0.078)	0.22 (0.1)	0.35 (0.15)		0.25
	+DIST.	0.26 (0.13)	0.35 (0.17)	0.49 (0.19)	0.51 (0.19)		0.40
	+CONTR.	0.26 (0.12)	0.46 (0.20)	0.48 (0.19)	0.58 (0.19)		0.44
DOOR OPEN	PEBBLE	0.17 (0.06)	0.26 (0.06)	0.23 (0.04)	0.26 (0.06)		0.23
	+DIST.	0.34 (0.07)	0.33 (0.08)	0.34 (0.09)	0.49 (0.13)		0.37
	+CONTR.	0.19 (0.03)	0.34 (0.15)	0.33 (0.07)	0.40 (0.05)		0.32

I   Complete Reward Stability Results

Additional stability results are not included in the Appendices as we were able to fit the results in the

main body of the paper. We are leaving the subsection here for now to not mess up the connection

between appendices referenced in the main text and the appendix section names here.

J   Complete Reward Reuse Results

The complete reward reuse results for walker-walk (Figure 16), quadruped-walk (Figure 15), and

cheetah-run across feedback amounts and teacher labelling strategies. For details about how the

reward reuse experiments were run, refer to Section **??**.

Figure 14: Learning curves for **walker-walk** comparing joint reward and policy learning with policy
learning using a previously learned reward function across preference-based RL method, labelling
style, and feedback amount. Mean policy returns are plotted along the y-axis with number of steps
(in units of 1000) along the x-axis. There is one plot per labelling style (grid columns) and feedback
amount (grid rows) with corresponding results per learning methods in each plot. From top to
bottom, the rows correspond to 50, 100, 200, 500, and 1000 pieces of teacher feedback. From left
to right, the columns correspond to equal, noisy, mistake, myopic, oracle, and skip labelling styles
(see Appendix B for details).

Figure 15: Learning curves for **quadruped-walk** comparing joint reward and policy learning with policy learning using a previously learned reward function across preference-based RL method, labelling style, and feedback amount. Mean policy returns are plotted along the y-axis with number of steps (in units of 1000) along the x-axis. There is one plot per labelling style (grid columns) and feedback amount (grid rows) with corresponding results per learning methods in each plot. From top to bottom, the rows correspond to 50, 100, 200, 500, 1000, and 2000 pieces of teacher feedback. From left to right, the columns correspond to equal, noisy, mistake, myopic, oracle, and skip labelling styles (see Appendix B for details).

Figure 16: Learning curves for **cheetah-run** comparing joint reward and policy learning with policy learning using a previously learned reward function across preference-based RL method, labelling style, and feedback amount. Mean policy returns are plotted along the y-axis with number of steps (in units of 1000) along the x-axis. There is one plot per labelling style (grid columns) and feedback amount (grid rows) with corresponding results per learning methods in each plot. From top to bottom, the rows correspond to 50, 100, 200, 500, and 1000 pieces of teacher feedback. From left to right, the columns correspond to equal, noisy, mistake, myopic, oracle, and skip labelling styles (see Appendix B for details).