SmartFRZ: An Efficient Training Framework using Attention-Based Layer Freezing

Abstract

There has been a proliferation of artificial intelligence applications, where model training is key to promising high-quality services for these applications. However, the model training process is both time-intensive and energy-intensive, inevitably affecting the user's demand for application efficiency. Layer freezing, an efficient model training technique, has been proposed to improve training efficiency. Although existing layer freezing methods demonstrate the great potential to reduce model training costs, they still remain shortcomings such as lacking generalizability and compromised accuracy. For instance, existing layer freezing methods either require manually pre-training defined freeze configurations, which do not apply to different networks, or use heuristic freezing criteria that is hard to guarantee decent accuracy in different scenarios. Therefore, there lacks a generic and smart layer freezing method that can automatically perform "in-situation" layer freezing for different networks during training processes. To this end, we propose a generic and efficient training framework (SmartFRZ). The core proposed technique in SmartFRZ is attention-guided layer freezing, which can automatically select the appropriate layers to freeze without compromising accuracy. Experimental results show that SmartFRZ effectively reduces the amount of computation in training and achieves significant training acceleration, and outperforms the state-of-the-art layer freezing approaches.

1 Introduction

Deep neural networks (DNNs) have become the core enabler of a wide spectrum of AI applications, such as natural language processing (Vaswani et al., 2017; Kenton & Toutanova, 2019), visual recognition (Li et al., 2022; Faraki et al., 2021), and automatic machine translation (Sun et al., 2020; Zheng et al., 2021), and also the emerging application domains such as robot-assisted eldercare (Do et al., 2018; Bemelmans et al., 2012), mobile diagnosis (Panindre et al., 2021; Abdel-Basset et al., 2020), and wild surveillance (Akbari et al., 2021; Ke et al., 2020). To satisfy the growing demand for adaptability and training efficiency of DNN models in deployment, a surge of research efforts has been devoted to designing efficient training paradigms (He et al., 2021; Yuan et al., 2021). For example, sparse training (Evci et al., 2020; Yuan et al., 2021) and low-precision training (Yang et al., 2020; Zhao et al., 2021) are two active research areas for efficient training that can effectively reduce training costs, such as computing FLOPs and memory. However, there are still fundamental limitations in the generality of these methods when used in practice. Concretely, sparse training methods generally require the support of dedicated libraries or compiler optimizations (Chen et al., 2018; Niu et al., 2020) to leverage the model sparsity and save computation costs. Similarly, low-precision training (e.g., INT-8 or fewer bits) is hard to be supported by GPUs and requires specialized designs for edge devices such as field-programmable gate arrays (FPGAs) and application-specific integrated circuits (ASICs). Therefore, it is desirable to have a generic efficient training method that can be easily and effectively adapted to various application scenarios.

Recent studies (Brock et al., 2017; Liu et al., 2021) revealed that freezing some DNN layers at a certain stage (i.e., training iteration) during the training process will not degrade the accuracy of the final trained model and can effectively reduce training costs. Most importantly, layer freezing can be achieved using native training frameworks such as PyTorch/TensorFlow without additional support, making it more accessible to wide applications and users for training costs reduction and acceleration. Previous work has mainly used heuristic freezing strategies, such as empirically selecting

which DNN layers to freeze and when to freeze (Lee et al., 2019; Yuan et al., 2022). As such, these heuristic freezing strategies require a trial-and-error process to find appropriate freezing configurations for individual tasks/networks, resulting in inconvenience and inefficiency when deployed to various application scenarios. Some recent works attempt to freeze the DNN layers in an adaptive manner by using the gradient-norm (Liu et al., 2021) or SVCCA score (He et al., 2021). However, it is known that DNN models generally do not monotonically converge to their optimal position. As a result, these adaptive methods, which decide whether the layers are frozen or not using the criteria based on the layers' current state, are less robust to the fluctuation of model training, leading to compromised accuracy. Therefore, we raise a fundamental question that has seldom been asked:

> *Is there a layer freezing method that can overcome the above-mentioned shortcomings while keeping the method efficient?*

Inspired by the outstanding performance of attention mechanism in solving sequence classification problems such as classification tasks (Long et al., 2018), dialog detection (Shen & Lee, 2016), and affect recognition (Gorrostieta et al., 2018), it is possible that the attention mechanism could also be a promising solution for layer freezing in efficient training, but it has never been explored in prior literature. In this paper, we inventively introduce attention mechanism for layer freezing. In specific, we design a lightweight attention-based predictor to collect and rank the DNN context information from multiple timestamps during training process. Based on the prediction, we adaptively freeze DNN layers to save training computation costs and accelerate training process while maintaining high model accuracy. To train the attention-based predictor, we propose a layer representational similarity-based method to generate a special training dataset using publicly available dataset (e.g., ImageNet). Then, the predictor is trained offline once, and learns the generic convergence pattern along the training history, which can be generalized across different models and datasets. We summarize our contributions as:

- We design a novel and lightweight predictor using attention mechanism for layer freezing in efficient training. The predictor automatically captures DNN context information from multiple timestamps and adaptively freezes the layers during the training process.

- We propose to leverage the layer representational similarity to generate a special dataset for training the attention-based predictor. The trained predictor can be used for different dataset and networks.

- Combining the attention-based predictor design and its training method, we propose a generic efficient training framework, namely **SmartFRZ**, which can effectively reduce the training costs and accelerate training time. Specifically, for fine-tuning scenarios, Smart-FRZ consistently achieves higher training acceleration while maintaining similar or higher accuracy compared to the prior works. For training from scratch scenarios, our Smart-FRZ shows more significant advantages compared to the baseline methods including full training, linear freezing, and AutoFreeze, which achieves 0.16%, 2.65%, and 4.82% higher accuracy with 24%, 13%, and 15% less training time, respectively.

2 BACKGROUND AND RELATED WORK

Layer Freezing. Recent researches (Brock et al., 2017; Kornblith et al., 2019) have found that not all layers in deep nerual networks need to be trained equally. For example, the early layers in DNNs are responsible for low-level features extraction and usually have fewer parameters than the later layers, making the early layers converge faster during training. Therefore, the layer freezing techniques are proposed, which stop updating certain layers during the training process to save the training costs (Lee et al., 2019; Zhang & He, 2020).

The previous work mainly uses heuristic strategies to determine which layers to freeze and when to freeze them. For example, Brock et al. (2017) uses a linear/cubic schedule to freeze the layers sequentially (one by one from the first layers to the later layers). The recent work Yuan et al. (2022) also freezes layer by layer in a constant interval, but uses target training FLOPs reduction to decide the time to start freezing. Another branch of works attempt to freeze DNN layers adaptively and use the criteria such as gradient-norm (Liu et al., 2021) or SVCCA score (He et al., 2021) to control the freezing. However, all of these heuristic-based freezing strategies require manually designed

Figure 1: Overview of our attention-based layer freezing framework SmartFRZ. SmartFRZ continuously records the weights of all actively being-trained layers during the training process. Periodically, there will be a freezing stage, when SmartFRZ applies an attention-based predictor to determine whether each active layer can be frozen at this moment, based on the collected historical data. After the freezing stage, the model training process continues, and the frozen layer will not be updated and its weights will not be recorded anymore. In this figure, we assume that the attention-based predictor predicts to freeze layer 1 only.

freezing configurations or threshold, which can be varied between different networks and datasets. In this paper, we intend to address these shortcomings and propose a generic freezing method that can be adopted to different scenarios.

Training Costs Reduction through Layer Freezing. Layer freezing technique can generally save training costs including *computation FLOPs* and *memory accesses*. Generally, each iteration of DNN training consists of forward propagation and backward propagation. On the one hand, once a layer is frozen, it still needs to compute the forward propagation since the subsequent layers still need its output features as their input features. Therefore, layer freezing cannot save training costs in forward propagation. On the other hand, the backward propagation consists of two parts of computations: i) calculating the gradients of weights and ii) calculating the gradients of activations. A frozen layer can always eliminate the computation cost and memory cost of the former part since the weights in the layer will not be updated anymore. However, the computation costs and memory costs of the latter part can only be eliminated if all the predecessor layers earlier than the current layer are frozen as well. This is because if a predecessor layer is not frozen, it needs to calculate the gradients of activations of the current layer to maintain the data pass backward propagation. Compared to the other efficient training techniques such as pruning or quantization, one significant advantage of layer freezing is that it does not require dedicated supports such as compiler optimizations or specialized hardware. It can be easily integrated into the general deep learning frameworks (e.g., PyTorch) and achieve almost linear acceleration according to the computation FLOPs reduction (Yuan et al., 2022). Meanwhile, it focuses on layers as granularity which is more efficient in reducing the training cost, and potentially, it can be combined with pruning and quantization to bring combined benefits.

3 SMARTFRZ FRAMEWORK DESIGN

3.1 FRAMEWORK OVERVIEW

In this section, we introduce our proposed layer freezing framework for efficient training, which can automatically freeze appropriate network layers to reduce unnecessary computation during the training process without compromising accuracy. Figure 1 shows the overview of the SmartFRZ framework. The core component of our framework is a lightweight attention-based predictor, which can automatically decide which layers will be frozen and when to freeze them during the training process. However, the attention-based predictor cannot be directly trained using conventional dataset for the classification tasks such as ImageNet. Therefore, we propose a novel method to generate the training dataset. We adopt offline training to train the predictor. Once the predictor is well-trained, it can be used for different datasets and networks since it learns generic converging patterns from collected training histories.

Figure 2: (a) An illustrated example of noisy weight history in which a darker shade within the circle indicates a lower loss. The training loss decreases at iteration $\{1, 2, 5\}$, yet increases at iterations $\{3, 4\}$. So the predictor needs to pay more attention to the weight history from iteration $\{1, 2, 5\}$ and less attention to the weight history from iterations $\{3, 4\}$ since the latter converge towards less optimal directions. (b) Detailed workflow of the attention-based predictor. At timestamp t, the predictor decides whether to freeze a specific layer l in three steps. First, it encodes the training history independently into feature vectors (i.e., K_l^j, Q_l^j, V_l^j). Second, it computes attention scores α_l^j and aggregates the historical state feature into a context vector C_l^t. Third, it predicts the confidence scores of freezing or not and selects the decision with higher confidence.

In the following parts of this section, we will first introduce the design principle and workflow of our attention-based predictor in Section 3.2 and Section 3.3. Then, we will introduce how to create the special training dataset for the predictor in Section 3.4.

3.2 Design Principle of the Attention-based Predictor

The goal of the predictor is to decide whether to freeze a layer or not at a specific training iteration. While existing approaches measure the gradient norm change between two timestamps (Liu et al., 2021), the patterns of long-term converging history are missed. To this end, it is desirable to leverage the long-term weight history sequence for the prediction. Specifically, the predictor is designed to capture the generic converging pattern within the model training histories. We can define the task of the predictor as follows:

Freezing Prediction Task (Definition #1). For a layer l, whose weights at timestamp j can be denoted as W_l^j: Given a sequence of its weight history $(W_l^j)_{j=0}^t$ at timestamp t, yield positive decision to freeze the layer at the current iteration (i.e. $d_l^t = 1$) if the layer is ready to be frozen, and yield negative decision (i.e. $d_l^t = 0$) if the layer needs further training.

The task is non-trivial due to noisy weight history information within the input sequence. Since the training model does not monotonically converge to the optimal solution, there exist scenarios such that: the history weight W_l^n from iteration n is less optimal than the history weight W_l^m from iteration m, even if the W_l^n is updated from W_l^m (i.e., $n > m$). We call weights like W_l^n as noisy weight history. These noisy weight histories represent incorrect converging directions, thus introducing unnecessary noises. We illustrate an example of the scenario in Figure 2(a). To this end, the predictor should avoid leveraging these misleading weight histories and selectively focus on other weight histories that provide more accurate training information toward the optimal weights.

We apply an attention-based predictor to meet the requirement. The predictor ranks the information from each timestamp (i.e., sampled iteration) and adaptively aggregates weight history from the input sequence. The aggregation is input-dependent and can select the history from those preferred timestamps. The detailed workflow is discussed in Section 3.3

Layer Tailoring. The predictor introduces additional model parameters, thus introducing additional overheads. To bound the overheads, instead of training one predictor for each layer, we intend to implement only one predictor serving for all the layers. However, the predictor expects fixed-sized weight information as inputs due to the fixed-sized MLP encoder (details are discussed in

Figure 3: The histogram of the gradient value frequency distribution of a network layer at a certain point during the training. Figure (a) counts all the parameters of the layer, while Figure (b) counts the randomly selected 1024 parameters. These gradient values belong to the 30th CONV layer of ResNet50 and were sampled during the training of ResNet50 on CIFAR-10. The range of the X-axis of these two sub-figures is the same.

3.3). Therefore, we need to tailor all the layers to a uniform size (e.g., 1024) to fit into the predictor model. In fact, the over-parameterization not only exists in the inference process but also in the training process (Frankle & Carbin, 2019). The over-parameterization means that there are redundant parameters (i.e., weights) that can be pruned across all the layers of a network. It offers an opportunity to use a fixed-sized subset of parameters to represent all the parameters of a layer, satisfying the fixed-size input requirement of our predictor.

We conduct an experiment to explore the relationship between the parameter subsets and all the parameters. Figure 3 shows the gradient value frequency distribution, and we can observe from the figure that for a network layer, the gradient distribution of all weights is similar to the gradient distribution of the weights subset. And the gradient distribution is one of the indicators that best characterizes the features of parameters during the training process. Therefore, we make the assumption that the parameter subsets can represent the whole layer. As such, we decide to tailor the network layer by random sampling, and the position of sampled weights of the same layer should be the same across the whole training process.

3.3 WORKFLOW OF THE ATTENTION-BASED PREDICTOR

The overview of its detailed workflow is depicted in Figure 2(b) For each historical weight W_l^j (sampled parameter of layer l at timestamp $j \in \{0, 1, \cdots, t\}$), the predictor first encodes them into a query vector Q_l^j, a key vector K_l^j, and a value vector V_l^j, following Equation 1, in which $MLP_{k/q/v}(\cdot)$ denotes the trainable Multi-Layer-Perceptron.

$$K_l^j = MLP_k(W_l^j), Q_l^j = MLP_q(W_l^j), V_l^j = MLP_v(W_l^j), j \in \{0, 1, \cdots, t\} \tag{1}$$

Next, it computes the correlation score a_l^j between the current time (i.e., iteration t) and each previous timestamp j. Specifically, it conducts dot-product between query vector at time t (i.e., Q_l^t) with key vectors from timestamp j (i.e., K_l^j), then gets a normalized attention score α_l^j by softmax across all previous timestamps, following Equation 2.

$$a_l^j = Q_l^t \cdot K_l^j, j \in \{0, 1, \cdots, t\} \tag{2}$$

$$\alpha_l^j = \frac{\exp\left(a_l^j\right)}{\sum_{i=0}^t \exp(a_l^i)}, j \in \{0, 1, \cdots, t\}$$

The value vector from each timestamp j (i.e., v_l^j) is weighted by the attention score α_l^j, and accumulated to the final context vector C_l^t, following Equation 3. Hence, the aggregated context vector keeps more information from those with higher attention scores while paying less attention to those with low scores.

$$C_l^t = \sum_{j=0}^t \alpha_l^j V_l^j \tag{3}$$

In the end, the prediction module $MLP_z(\cdot)$ computes confident scores of freezing or not as a two-element vector. We choose a decision with higher confidence, as shown in Equation 4. If $d_l^t = 1$, we will freeze layer l at timestamp t; otherwise, we continue its training at the moment.

$$d_l^t = Argmax(MLP_z(C_l^t)) \tag{4}$$

3.4 TRAINING THE PREDICTOR

In order to not seize the computational resources during the model training, we decide to train the predictor offline and then use it during the training process instead of jointly training the predictor. To train the attention-based predictor, we need to generate a dataset ourselves. As mentioned in Section 3.2, we use the layer weights as input data and then apply a layer representational similarity-based method to label the input data.

Layer Representational Similarity. As training proceeds, the model layers are continuously being updated, and the representational similarity between a layer of the model being trained and the corresponding layer of the well-trained model will increase. The representational similarity indicates the feature extraction capability of a specific layer. We adopt a widely-used index Centered Kernel Alignment (CKA) to indicate the representational similarity of two layers (Kornblith et al., 2019). CKA is obtained by comparing the output feature maps of two layers under the same input image batch. It is calculated as:

$$CKA(X, Y) = \left\|Y^\mathrm{T} X\right\|_\mathrm{F}^2 / \left(\left\|X^\mathrm{T} X\right\|_\mathrm{F} \left\|Y^\mathrm{T} Y\right\|_\mathrm{F}\right) \tag{5}$$

where X and Y are the output feature maps from two layers, and $\|\cdot\|_\mathrm{F}^2$ represents the square of the Frobenius norm of a matrix. A higher CKA value indicates that the two layers will output more similar feature maps with the same inputs. Further, if the CKA value of a layer stabilizes during the training process, we consider this layer is converged and ready to be frozen.

Figure 4 plots the CKA value curve of several CONV layers as training proceeds. As one can observe from the figure, after a period of fine-tuning, the layer's CKA stabilizes, which means that the feature extraction capability of those layers hardly changes even if the training continues. At this moment, freezing those layers will have little impact on accuracy. Moreover, the similarity with the well-trained model is not monotonically increasing but fluctuating, which correlates with our discussion in section 3.2 that it is not always the most recent model that has the most significant impact on the current model parameters. We can also observe from the figure that different layers require different training epochs to stabilize, and basically the layers in the front stabilize faster than the layers in the

Figure 4: CKA variation curve as training proceeds. Result is obtained while training ResNet50 on CIFAR-10 and the ResNet50 is pre-trained on ImageNet.

back (e.g., layers 10 and 20 stabilize faster than layers 40 and 50). But it is interesting to see that the layer in the back is possible to stabilize faster than the front layer (e.g., layer 30 stabilizes faster than layers 10 and 20). This is due to the presence of residual connections in the ResNet architecture, which allows some of the later layers to behave like the earlier layers (Veit et al., 2016). These observations demonstrate the need for an adaptive layer freezing method, which is exactly what the SmartFRZ does, rather than forcing sequential freezing from front to back. Note that we cannot directly use this representational similarity-guided freezing because we cannot obtain the well-trained reference model in advance in practice.

Generating the Training Dataset. We first train a model on a certain dataset and use it as a well-trained reference model for CKA calculation. Then we train the same network on the same dataset again, in which we periodically calculate the CKA value between the well-trained model and the model under training for all the layers. With the CKA value, we are able to determine whether to freeze a layer or not. In this way, each piece of training data includes a sequence of historical weights of a layer and a label indicating whether to freeze that layer or not at the moment of the latest record of this sequence.

We conduct an experiment to show the effectiveness of labeling the data through layer representational similarity. Specifically, we first train and obtain well-trained ResNet50 (He et al., 2016) and

Table 1: Comparison of model accuracy and total computation of the training process using different methods: full training and layer representational similarity-guided freezing. Results are obtained using ResNet50 and VGG11 on CIFAR-10. Both models are pre-trained on the ImageNet dataset and then trained for 10 epochs on CIFAR-10.

Method	ResNet50		VGG11	
	Accuracy	Comp. (TFLOPs)	Accuracy	Comp. (TFLOPs)
Full Training	81.68%	12,360	74.95%	22,950
Similarity-Guided Freezing	81.75%	6,454	74.89%	12,811

Table 2: Comparison of different freezing methods. All the models are pre-trained using Imagenet dataset (Deng et al., 2009). And then all the models will be trained for 10 epochs to converge, using a cosine annealing learning rate scheduler according to the training epochs.

Model	Method	CIFAR-10			CIFAR-100		
		Accuracy	Time (Second)	Computation (TFLOPs)	Accuracy	Time (Second)	Computation (TFLOPs)
ResNet50	Full Training	96.10%	2,594	12,360	81.68%	2,500	12,360
	Linear Freezing	96.05%	1,980	8,247	81.48%	1,844	7,085
	AutoFreeze	96.24%	2,424	8,716	81.30%	1,963	7,716
	SmartFRZ (Ours)	96.12%	1,955	8,122	81.73%	1,787	6,398
VGG11	Full Training	93.36%	2,698	22,950	74.95%	2,703	22,950
	Linear Freezing	92.35%	1,587	10,291	73.26%	1,846	12,307
	AutoFreeze	93.08%	1,895	13,350	74.74%	2,027	13,946
	SmartFRZ (Ours)	93.58%	1,554	10,059	74.66%	1,831	12,121
MobileNetV2	Full Training	94.15%	1,369	960	76.52%	1,371	960
	Linear Freezing	94.19%	977	567	75.59%	1,000	540
	AutoFreeze	94.26%	1,245	678	76.43%	1,248	652
	SmartFRZ (Ours)	94.03%	972	561	76.73%	986	532

VGG11 (Simonyan & Zisserman, 2015) models on the CIFAR-100 (Krizhevsky & Hinton, 2009) dataset. Then we train another ResNet50 and VGG11 model with CIFAR-100 dataset again and freeze the network layers under the guidance of layer representational similarity during the training process. In this experiment, the freezing is conducted at the end of each epoch. Table 1 shows the experimental results of the training with and without layer freezing. As shown in the table, training the networks using the representational similarity-guided freezing method can significantly reduce the computation cost (e.g., it saves 48% computation for training ResNet50) while maintaining the model accuracy, demonstrating the effectiveness of our similarity-guided labeling method and the correctness of the generated dataset.

4 EVALUATION

4.1 EXPERIMENTAL SETUP

In this section, we evaluate the proposed SmartFRZ framework on an NVIDIA Tesla P100 GPU server using three representative DNN models ResNet50, VGG11, and MobileNetV2 (Sandler et al., 2018), and two dataset CIFAR-10 and CIFAR-100. The training data is divided into batches with a size of 32. For layer freezing, when a CONV layer is frozen, we also freeze its corresponding BN layer to avoid unnecessary computation costs in back-propagation. The attention-based predictor is trained on ImageNet using ResNet50. The attention window size for the predictor is 30. And we tailor all the layers into the size of 1024 by random sampling to fit into the generic predictor. All the accuracy results in this paper are the average number of 5 runs using different random seeds. A benchmark is defined as a model-dataset combination (e.g., VGG11+CIFAR-100).

4.2 MAIN RESULTS

Fine-tuning. Table 2 shows the results of applying different freezing methods (Linear Freezing (Brock et al., 2017) and AutoFreeze (Liu et al., 2021)). Linear freezing is a manually determined

sequential freezing method. In our experiments, we set the number of frozen layers to increase exponentially according to the number of epochs. AutoFreeze is a sequential freezing scheme and uses the variation of gradients norm as the metric to guide the freezing. SmartFRZ is able to significantly reduce computation and time for training without compromising accuracy compared to full training. And it consistently outperforms Linear Freezing and AutoFreeze.

Compared to Linear Freezing, SmartFRZ provides up to 1.4% higher accuracy (VGG11 CIFAR-100), with 0.7% higher on average, and consumes similar time and energy. This is because Linear Freezing freezes layers in a fixed order at a pre-determined time, so some layers that are not well-trained might also be frozen. Moreover, linear freezing performs poorly on some benchmarks (i.e., VGG11 CIFAR-10, VGG11 CIFAR-100, and MobileNetV2 CIFAR-100). This is because linear freezing is highly dependent on a predefined freezing configuration, which does not adapt to different scenarios. For example, the training epochs required to converge is definitely different when training different model on different datasets with different complexity (e.g., ImageNet vs. MNIST), so the freeze configuration should also be different.

Compared to AutoFreeze, SmartFRZ reduces up to 20.4% time (MobileNetV2 CIFAR-10 benchmark) and 24.7% computation cost (VGG11 CIFAR-10 benchmark) while providing similar accuracy. The reasons behind this are three-fold. First, SmartFRZ applies an attention-based predictor that can precisely determine the moment to freeze a layer. Second, AutoFreeze only freezes the layer where all the layers in front of it have been frozen. However, as discussed in Section 3.4, one layer might stabilize earlier than some of the layers in front of it. Therefore, forcing sequential freezing may result in wasting computation. Third, AutoFreeze incurs considerable overhead as it needs to compute the L2 Norm for all the gradients. Specifically, this overhead consumes 20%, 12%, and 3% of the total training time while training ResNet50, MobileNetV2, and VGG11, respectively. As a result, AutoFreeze only shows a marginal improvement in time consumption on the MobileNetV2 benchmark.

Training From Scratch. In addition to fine-tuning, we also investigate the performance of our SmartFRZ framework in training a model from scratch. As shown in table 3, SmartFRZ saves training time by 24% without compromising accuracy compared to full training. SmartFRZ also consistently outperforms linear freezing and AutoFreeze in training from scratch. Compared to linear freezing, SmartFRZ provides 2.65% higher accuracy with 13% less time consumption. The performance of linear freezing degrades

Table 3: Comparison of different freezing methods in training a model from scratch (160 epochs). The result is obtained using ResNet50 on CIFAR-100.

Method	Accuracy	Time (Minute)
Full Training	77.48%	711
Linear Freezing	74.99%	615
AutoFreeze	72.82%	630
SmartFRZ (Ours)	77.64%	538

severely compared to fine-tuning. This is because the robustness of the raw model in the training from scratch experiment is much lower than that of the pre-trained model in the fine-tuning experiment. Linear freezing, which relies heavily on manually predefined freezing configuration, cannot handle this more complex training scenario. Compared to AutoFreeze, SmartFRZ provides a significantly 4.82% higher accuracy with 15% less time consumption.

4.3 MEMORY COST REDUCTION AND FREEZING PATTERN

Our SmartFRZ framework not only reduces training computation costs by freezing layers, but also reduces memory costs due to the reduction of intermediate data generated during back-propagation. Figure 5(a) shows the memory cost as training proceeds. We can observe from the figure that SmartFRZ can significantly save more than 80% memory for ResNet50 and about 50% memory for VGG11 and MobileNetV2. Considering the limited GPU memory capacity, our approach enlarges the potential of accommodating multiple DNN tasks within a single GPU. Figure 5(b) shows the freezing moment for each layer while training ResNet50 on CIFAR-100. As shown in the figure, although there are still some layers in the back getting frozen earlier than some front layers, SmartFRZ tends to freeze the front layers earlier than the layers in the back. This is because the front layers mainly extract low-level features (e.g., detecting edges), while the back layers extract high-level features (Yosinski et al., 2014; Zeiler & Fergus, 2014). And the low-level feature extraction capability can be inherited from the pre-training process more easily.

Figure 5: (a) Memory cost as training proceeds. Results are obtained by training VGG11, ResNet50, and MobileNetV2 on CIFAR-100 dataset. (b) The frozen moment for each layer while training ResNet50 on CIFAR-100.

Table 4: Comparison of the model accuracy when the attention window size for freezing prediction varies. The results are obtained using ResNet50 and VGG11 on CIFAR-100. The tailored layer size is set to 1024.

Model	Window Size			
	20	30	40	50
ResNet50	81.17%	81.73%	81.75%	82.11%
VGG11	74.45%	74.66%	75.11%	74.67%

Table 5: Comparison of the model accuracy when the uniform tailored layer size varies. The results are obtained using ResNet50 and VGG11 on CIFAR-100. The attention window size is set to 30.

Model	Tailored Layer Size			
	512	1024	2048	4096
ResNet50	81.28%	81.73%	81.33%	81.69%
VGG11	73.98%	74.66%	74.48%	75.12%

4.4 SENSITIVITY STUDY

We investigate the effect of adopting different attention window sizes (i.e., the number of historical data used) to predict the freezing probability. Table 4 shows the accuracy when the attention window size varies. As one can observe, SmartFRZ consistently delivers a high model accuracy under different window sizes. It demonstrates the robustness of SmartFRZ in handling scenarios of different attention window sizes. This is because the attention mechanism adaptively selects valuable information within the long window ranges.

We also study how the uniform tailored layer size affects our SmartFRZ framework. As shown in table 5, our proposed SmartFRZ framework remains robust except for a very slight accuracy drop in accuracy (i.e., less than 1%) when the layer size is 512. And the reason behind this is that too few sampled parameters might be too random, thus making it hard to represent the whole layer. Therefore, we will tailor the layer to the size of at least 1024.

Regarding the overhead, since our attention-based predictor consists of several lightweight MLPs, it only requires negligible less than 0.1% of total training time. Moreover, since we tailor the layers into a size of 1024, it only requires hundreds of KB to store the whole model once (e.g., 212 KB for ResNet50). As such, SmartFRZ only requires about 10 MB of memory to store the historical weights for freezing prediction even with a large attention window of size 50.

5 CONCLUSION

This work considers an efficient training technique layer freezing on both fine-tuning and training from scratch scenarios. We propose an attention-based layer freezing framework SmartFRZ. The key idea is to leverage the training histories to predict the freezing probability of a layer during the training process. Our attention-based layer freezing predictor can learn comprehensive information about the network layer, such as the changing pattern of layer parameters and their distributions. The predictor is trained offline on a dataset with layer weights as input data which is labeled by a layer representation similarity-based method. Our extensive experiments demonstrate that Smart-FRZ significantly saves training time and computation by automatically freezing layers without compromising accuracy.

REFERENCES

Mohamed Abdel-Basset, Weiping Ding, and Laila Abdel-Fatah. The fusion of internet of intelligent things (ioit) in remote diagnosis of obstructive sleep apnea: A survey and a new model. Information Fusion, 61:84–100, 2020.

Younes Akbari, Noor Almaadeed, Somaya Al-Maadeed, and Omar Elharrouss. Applications, databases and open computer vision research from drone videos and images: a survey. Artificial Intelligence Review, 54(5):3887–3938, 2021.

Roger Bemelmans, Gert Jan Gelderblom, Pieter Jonker, and Luc De Witte. Socially assistive robots in elderly care: a systematic review into effects and effectiveness. Journal of the American Medical Directors Association, 13(2):114–120, 2012.

Andrew Brock, Theodore Lim, James M Ritchie, and Nick Weston. Freezeout: Accelerate training by progressively freezing layers. arXiv preprint arXiv:1706.04983, 2017.

Tianqi Chen, Thierry Moreau, Ziheng Jiang, Lianmin Zheng, Eddie Yan, Haichen Shen, Meghan Cowan, Leyuan Wang, Yuwei Hu, Luis Ceze, Carlos Guestrin, and Arvind Krishnamurthy. Tvm: An automated end-to-end optimizing compiler for deep learning. In 13th USENIX Symposium on Operating Systems Design and Implementation (OSDI 18), pp. 578–594, 2018.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In 2009 IEEE conference on computer vision and pattern recognition, pp. 248–255. Ieee, 2009.

Ha Manh Do, Minh Pham, Weihua Sheng, Dan Yang, and Meiqin Liu. Rish: A robot-integrated smart home for elderly care. Robotics and Autonomous Systems, 101:74–92, 2018.

Utku Evci, Trevor Gale, Jacob Menick, Pablo Samuel Castro, and Erich Elsen. Rigging the lottery: Making all tickets winners. In International Conference on Machine Learning, pp. 2943–2952. PMLR, 2020.

Masoud Faraki, Xiang Yu, Yi-Hsuan Tsai, Yumin Suh, and Manmohan Chandraker. Cross-domain similarity learning for face recognition in unseen domains. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pp. 15292–15301, 2021.

Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. In International Conference on Learning Representations, 2019. URL https://openreview.net/forum?id=rJl-b3RcF7.

Cristina Gorrostieta, Richard Brutti, Kye Taylor, Avi Shapiro, Joseph Moran, Ali Azarbayejani, and John Kane. Attention-based sequence classification for affect detection. In Interspeech, pp. 506–510, 2018.

Chaoyang He, Shen Li, Mahdi Soltanolkotabi, and Salman Avestimehr. Pipetransformer: Automated elastic pipelining for distributed training of transformers. arXiv preprint arXiv:2102.03161, 2021.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR), June 2016.

Ruimin Ke, Yifan Zhuang, Ziyuan Pu, and Yinhai Wang. A smart, efficient, and reliable parking surveillance system with edge artificial intelligence on iot devices. IEEE Transactions on Intelligent Transportation Systems, 22(8):4962–4974, 2020.

Jacob Devlin Ming-Wei Chang Kenton and Lee Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In Proceedings of NAACL-HLT, pp. 4171–4186, 2019.

Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey Hinton. Similarity of neural network representations revisited. In International Conference on Machine Learning, pp. 3519–3529. PMLR, 2019.

Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. 2009.

Jaejun Lee, Raphael Tang, and Jimmy Lin. What would elsa do? freezing layers during transformer fine-tuning. arXiv preprint arXiv:1911.03090, 2019.

Yehao Li, Ting Yao, Yingwei Pan, and Tao Mei. Contextual transformer networks for visual recognition. IEEE Transactions on Pattern Analysis and Machine Intelligence, 2022.

Yuhan Liu, Saurabh Agarwal, and Shivaram Venkataraman. Autofreeze: Automatically freezing model blocks to accelerate fine-tuning. arXiv preprint arXiv:2102.01386, 2021.

Xiang Long, Chuang Gan, Gerard De Melo, Jiajun Wu, Xiao Liu, and Shilei Wen. Attention clusters: Purely attention based local feature integration for video classification. In Proceedings of the IEEE conference on computer vision and pattern recognition, pp. 7834–7843, 2018.

Wei Niu, Xiaolong Ma, Sheng Lin, Shihao Wang, Xuehai Qian, Xue Lin, Yanzhi Wang, and Bin Ren. Patdnn: Achieving real-time dnn execution on mobile devices with pattern-based weight pruning. In Proceedings of the Twenty-Fifth International Conference on Architectural Support for Programming Languages and Operating Systems, pp. 907–922, 2020.

Prabodh Panindre, Vijay Gandhi, and Sunil Kumar. Artificial intelligence-based remote diagnosis of sleep apnea using instantaneous heart rates. In 2021 11th International Conference on Cloud Computing, Data Science & Engineering (Confluence), pp. 169–174. IEEE, 2021.

Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov, and Liang-Chieh Chen. Mobilenetv2: Inverted residuals and linear bottlenecks. In Proceedings of the IEEE conference on computer vision and pattern recognition, pp. 4510–4520, 2018.

Sheng-syun Shen and Hung-yi Lee. Neural attention models for sequence classification: Analysis and application to key term extraction and dialogue act detection. arXiv preprint arXiv:1604.00077, 2016.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. In International Conference on Learning Representations, 2015.

Zeyu Sun, Jie M Zhang, Mark Harman, Mike Papadakis, and Lu Zhang. Automatic testing and improvement of machine translation. In Proceedings of the ACM/IEEE 42nd International Conference on Software Engineering, pp. 974–985, 2020.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. Advances in neural information processing systems, 30, 2017.

Andreas Veit, Michael J Wilber, and Serge Belongie. Residual networks behave like ensembles of relatively shallow networks. Advances in neural information processing systems, 29, 2016.

Yukuan Yang, Lei Deng, Shuang Wu, Tianyi Yan, Yuan Xie, and Guoqi Li. Training high-performance and large-scale deep neural networks with full 8-bit integers. Neural Networks, 125:70–82, 2020.

Jason Yosinski, Jeff Clune, Yoshua Bengio, and Hod Lipson. How transferable are features in deep neural networks? Advances in neural information processing systems, 27, 2014.

Geng Yuan, Xiaolong Ma, Wei Niu, Zhengang Li, Zhenglun Kong, Ning Liu, Yifan Gong, Zheng Zhan, Chaoyang He, Qing Jin, et al. Mest: Accurate and fast memory-economic sparse training framework on the edge. Advances in Neural Information Processing Systems, 34:20838–20850, 2021.

Geng Yuan, Yanyu Li, Sheng Li, Zhenglun Kong, Sergey Tulyakov, Xulong Tang, Yanzhi Wang, and Jian Ren. Layer freezing & data sieving: Missing pieces of a generic framework for sparse training. arXiv preprint arXiv:2209.11204, 2022.

Matthew D Zeiler and Rob Fergus. Visualizing and understanding convolutional networks. In European conference on computer vision, pp. 818–833. Springer, 2014.

Minjia Zhang and Yuxiong He. Accelerating training of transformer-based language models with progressive layer dropping. *Advances in Neural Information Processing Systems*, 33:14011–14023, 2020.

Kang Zhao, Sida Huang, Pan Pan, Yinghan Li, Yingya Zhang, Zhenyu Gu, and Yinghui Xu. Distribution adaptive int8 quantization for training cnns. In *Proceedings of the Thirty-Fifth AAAI Conference on Artificial Intelligence*, 2021.

Zaixiang Zheng, Xiang Yue, Shujian Huang, Jiajun Chen, and Alexandra Birch. Towards making the most of context in neural machine translation. In *Proceedings of the Twenty-Ninth International Conference on International Joint Conferences on Artificial Intelligence*, pp. 3983–3989, 2021.