# ThinknCheck: Grounded Claim Verification with Compact, Reasoning-Driven, and Interpretable Models

## Abstract

We present ThinknCheck, a 1B-parameter verifier for grounded claim verification that first produces a short, structured rationale and then a binary verdict. We construct LLMAggreFact-Think, a 24.1k reasoning-augmented training set derived from LLMAggreFact, and fine-tune a 4-bit Gemma3 model to follow this format. On LLMAggreFact, ThinknCheck attains 78.1 balanced accuracy (BAcc), surpassing MiniCheck-7B (77.4) with 7x fewer parameters; removing the reasoning step reduces BAcc to 57.5. On SciFact, ThinknCheck reaches 64.7 BAcc, a +14.7 absolute gain over MiniCheck-7B. By contrast, zero-shot chain-of-thought on the base Gemma3-1B harms accuracy relative to direct answers, and preference optimization with a simple format+accuracy reward underperforms supervised reasoning. A qualitative audit of generated rationales indicates current verification datasets over-reward lexical overlap and under-test multi-sentence and numerical reasoning. To probe the latter, we introduce GSMClaims and a domain-specialized variant, ThinknCheck-Science, which improves across benchmarks, including 61.0% accuracy on GSMClaims. Overall, explicit, supervised reasoning enables compact verifiers that are competitive while remaining resource-efficient and interpretable.

## 1 Introduction

Large Language Models (LLMs) are increasingly pivotal in modern AI-driven workflows involving natural language claim verification (Thorne et al., 2018), yet their propensity for hallucinations (Zhang et al., 2023), reasoning errors (Chen et al., 2023), and their opaque nature limit broader deployment, particularly in high-stakes domains like healthcare and scientific innovation.

Current claim verification approaches, while evolving, often face challenges. Some methods

---

**Claim:** Momentum P $\approx$ 10.0 $\pm$ 1.1 kg · m/s

**Document:** Mass M = 5.0 $\pm$ 0.1 kg. Velocity V = 2.0 $\pm$ 0.2 m/s.

.................................................................................

**MiniCheck-7B verification result:**

DOES NOT SUPPORT

.................................................................................

**ThinknCheck-Science-1B verification result:**

SUPPORTS

**ThinknCheck-Science-1B reasoning:**

*The momentum is calculated by multiplying the mass and the velocity: 5.0 kg $\times$ 2.0 m/s = 10.0 kg · m/s. The relative uncertainty in the mass is 0.1/5.0 = 2% and in the velocity is 0.2/2.0 = 10%. When uncertainties are combined for multiplication, they add in quadrature: $\sqrt{((2\%)^2 + (10\%)^2)} = \sqrt{(0.0004 + 0.01)} = \sqrt{(0.0104)} \approx 10.2\%$. This results in an uncertainty of about 10.2% $\times$ 10.0 kg · m/s $\approx$ 1.0 kg · m/s. A better calculation using maximum and minimum values yields $P_{max}$ = 5.1 kg $\times$ 2.2 m/s = 11.22 kg · m/s and $P_{min}$ = 4.9 kg $\times$ 1.8 m/s = 8.82 kg · m/s. The range between $P_{max}$ and $P_{min}$ is 11.22 8.82 = 2.4 kg · m/s, implying an uncertainty of approximately $\pm$ 1.2 kg · m/s. Since both approaches yield an uncertainty around $\pm$ 1.0 to $\pm$ 1.2 kg · m/s, the claim of 10.0 $\pm$ 1.1 kg · m/s is consistent with the uncertainties derived from the document.*

Figure 1: A non-trivial document-grounded claim verification example showing ThinknCheck-Science (1B) and MiniCheck-7B in action. Notice how ThinknCheck verifies a quantitative claim by producing a concise, structured rationale that computes momentum and propagates measurement uncertainty while the current SOTA model MiniCheck-7B rejects it. This example highlights numerically grounded, interpretable reasoning beyond surface lexical overlap.

---

can be computationally intensive, requiring multiple LLM calls for a single verification (Malaviya et al., 2024; Jacovi et al., 2024a). Verification using large, closed-source models also raises concerns regarding cost, privacy, and data security. While the trend in general reasoning models has seen the de-

Figure 2: A sample from the LLMAggreFact-Think dataset, which also illustrates our formulation of the claim verification task: Given a pair of claim and document, our goal is to produce cogent reasoning in addition to the verification label. The [...] represents parts of the reasoning tokens that we elided to accommodate the example in this figure.

velopment of very large systems, such as OpenAI's o-series and DeepSeek's R1 (DeepSeek-AI et al., 2025), which aim for broad reasoning capabilities, there is a concurrent need for smaller, more specialized models (Tang et al., 2024) that can perform robustly on specific tasks like claim verification, especially in resource-constrained environments. Our work aligns with this latter direction, focusing on creating efficient yet powerful verification models.

To address these challenges, we introduce ThinknCheck, a suite of novel low-footprint claim verification models that explicitly generate structured reasoning chains *before* rendering a verification decision. Specifically ThinknCheck is a 4-bit quantized 1B parameter Gemma3 (GemmaTeam et al., 2025) model, fine-tuned on our newly createdLLMAggreFact-Think dataset—a version of theLLMAggreFact benchmark (Tang et al., 2024) that we augmented with explicit reasoning traces. As illustrated in Figures 1 and 2, explicitly generating reasoning allows ThinknCheck to handle claims that require multi-step inference, a common scenario where prior models falter. Our contributions are as follows:

- Introduce THINKNCHECK, a **reasoning-optimized document-grounded claim verifier** that reasons before verifying, improving accuracy and interpretability by producing a concise rationale before the decision.
- Demonstrate ThinknCheck's explicit reasoning significantly **boosts verification accuracy** (+20.6 points over non-reasoning ablation) and **substantially improves out-of-domain generalization** (+14.7 points on scientific claims).
- Create and release GSMClaims, a novel

benchmark from reformulated grade school math problems, to **evaluate arithmetic reasoning capabilities in claim verification systems**.
- Develop ThinknCheck-Science, a specialized variant **optimized for scientific and mathematical verification**, achieving significant performance improvements across relevant benchmarks.
- Provide a qualitative analysis of generated reasoning traces that lifts the veil on current claim verification datasets: **an over-dependence on surface-level evidence matching and an under-representation of claims requiring multi-sentence synthesis and numerical reasoning**.
- Answer how much "thinking" is optimal for small models: To demystify this, we empirically relate rationale length to verification accuracy. We observe an inverted-U pattern: mid-length reasoning performs best, while **very short and very long chains degrade performance in distinct ways** (See Fig. 4).
- **Open source all** created datasets and models under an Apache 2.0 license[1].

## 2 Related Work

Our work connects five threads: (i) claim verification/fact-checking, (ii) reasoning in LMs, (iii) lightweight specialized verifiers, (iv) benchmarks, and (v) supervision for reasoning.

**Claim verification and fact-checking.** Early large-scale resources such as FEVER and SCI-FACT established document-grounded claim verification as a supervised classification task map-

---

[1]URL withheld for blind-review

ping a (claim, document) pair to a support decision (Thorne et al., 2018; Wadden et al., 2020; Tang et al., 2024). At the same time, hallucination and opacity concerns with LLMs motivate verifiers that are accurate and interpretable (Chen et al., 2023; Zhang et al., 2023).

**Reasoning-augmented verification.** Reasoning traces (e.g., Chain-of-Thought) can help models explain intermediate steps (Wei et al., 2022) and have been adapted via verifiable-CoT and ReAct to interleave reasoning with actions (Jacovi et al., 2024b; Yao et al., 2023). While very large models (e.g., DeepSeek R1) aim for broad reasoning (DeepSeek-AI et al., 2025), multiple studies find that vanilla CoT can underperform at small scales (Li et al., 2025; Liu et al., 2025a). Our setup follows this evidence: we fine-tune a compact model to produce structured, pre-decision rationales specific to claim verification, and we observe that preference-optimization methods such as GRPO—which have shown promise at larger scales (Shao et al., 2024a; Liu et al., 2025c; Zheng et al., 2025)—do not help and can be counter-productive at 1B parameters.

**Lightweight and specialized verifiers.** There is growing interest in small, efficient models for deployment (Allal et al., 2025). MiniCheck (7B) demonstrated the value of a purpose-built verifier trained on synthetic data and outperformed AlignScore on LLMAggreFact (Tang et al., 2024; Zha et al., 2023). However, MiniCheck struggles on multi-step cases and does not produce explanations that are important for trust and collaboration (Bansal et al., 2020; Fan et al., 2021; Javaid and Estivill-Castro, 2021). In contrast, ThinknCheck is a 1B model that *reasons before deciding*, yielding concise rationales and stronger performance with substantially lower footprint.

**Benchmarks.** LLMAggreFact aggregates nine sources to test diverse claim-verification scenarios (Tang et al., 2022; Nallapati et al., 2016; Narayan et al., 2018; Zhu et al., 2021; Hu et al., 2023; Liu et al., 2023; Malaviya et al., 2023; Wang et al., 2023; Kamoi et al., 2023). Domain-specific suites such as SCIFACT probe scientific claims, while GSM8K targets math reasoning (Wadden et al., 2020; Cobbe et al., 2021). To directly assess numerical reasoning in verification, we reformulate GSM8K into GSMCLAIMS.

**Supervising reasoning.** We supervise rationales via SFT on synthetic traces (knowledge distillation) (Xu et al., 2024). Although RL-style preference op-

timization (e.g., GRPO) is another path (Shao et al., 2024b; Zheng et al., 2025; Liu et al., 2025c), in our 1B setting SFT on structured reasoning yields better outcomes. We use a standard TRL stack for reproducibility (von Werra et al., 2020).

## 3 Problem Formulation

The standard formulation of document-grounded claim verification, as used by Tang et al. (2024) and predecessors, is a classification task: a discriminator $\mathcal{M}$ maps a claim (from space $\mathcal{C}$) and document (from space $\mathcal{D}$) to a discrete label in $\{0, 1\}$ (1 for supported, 0 otherwise): $\mathcal{M} : \mathcal{C} \times \mathcal{D} \rightarrow \{0, 1\}$

Our work extends this by incorporating explicit reasoning. We define this task with a reasoner $\mathcal{R}$ that maps the input claim-document pair to a reasoning trace $\mathcal{T}$ and a boolean verification label: $\mathcal{R} : \mathcal{C} \times \mathcal{D} \rightarrow \mathcal{T} \times \{0, 1\}$ This richer output format enhances interpretability and aims to improve accuracy by requiring the model to articulate its reasoning. We adopt the binary labels SUPPORTED (1) and NOTSUPPORTED (0) from prior work, treating "REFUTES" and "NOTSUPPORTED" identically[2].

## 4 Dataset and Model Development

This section details the creation of our training dataset LLMAggreFact-Think and the model training procedures for ThinknCheck.

### 4.1 LLMAggreFact-Think Dataset Construction

To train our reasoning-based verifier, we created LLMAggreFact-Think by augmenting the 30.4K examples in the LLMAggreFact development set with reasoning chains. Using zero-shot prompting, GPT-4o-mini[3] generated a step-by-step reasoning process and a YES/NO verification label for each (document, claim) pair — see Figure 2; prompt in Appendix C. For high-quality reasoning, we filtered instances where GPT-4o-mini's generated label mismatched the original LLMAggreFact label, reducing the dataset from 30.4K to 24.1K examples[4]. This filtered set, LLMAggreFact-Think, contains 4-tuples: (claim, document, verification

---

[2] We concur with Tang et al. (2024) that "REFUTES", common in general NLI problems, is rare in claim verification.

[3] Accessed on March 4, 2025. We did not use the o-series models for this as it does not provide access to raw reasoning tokens.

[4] Notably, ~21% of LLMAggreFact dev set labels differed from GPT-4o-mini's predictions; analyzing this discrepancy is beyond this paper's scope. Hence we chose to only train on examples with agreement.

label, reasoning). We opted against using reasoning traces from `Deepseek R1` (DeepSeek-AI et al., 2025) due to their verbosity and token inefficiency (See Figure 5). To ensure quality, we randomly sampled 100 samples across all 9 datasets in LLMAggreFact and manually inspected the reasoning traces derived from GPT-4o and found them to be accurate.

### 4.2 ThinknCheck-1B Model Training

We implemented ThinknCheck-1B by fine-tuning a 4-bit quantized Gemma3 1B model on LLMAggreFact-Think (training details in Appendix D). Our choice of Gemma3 was inspired by its size, recency, and its overall performance across diverse LLM benchmarks (GemmaTeam et al., 2025). The fine-tuning prompt (Appendix E) mirrored the LLMAggreFact-Think data structure, constraining the model to output both reasoning and the final verification solution.[5] For finetuning we used the 24.1K examples constructed as reported in Section 4.1 and retained 20% of that as a development set.

### 4.3 Ablation Model Variants: Base model, Non-thinking, CoT, and GRPO

To isolate the reasoning step's impact, we trained an ablation model, ThinknCheck-nothink-1B. It shares ThinknCheck-1B's architecture, data, and hyperparameters but was trained with a prompt (Appendix F) requesting only the final solution, omitting reasoning generation. This ablation ensures that observed performance gains are not solely due to our choice of Gemma3 as the backbone. For context, we also evaluate the Gemma3-1B base model without fine-tuning (direct YES/NO) and with a Chain-of-Thought (CoT) prompt (Wei et al., 2022) at inference time using the same decoding settings; these rows appear in Table 1. Beyond SFT, we train a preference-optimized variant using the Dr. GRPO variant with GSPO enabled in HuggingFace's TRL library (von Werra et al., 2020). We experimented with LoRA adapters initialized with and without SFT warm start, each jointly optimizing a two-term reward: (i) a *format-adherence* bonus that requires the model to emit both `<REASONING>` and `<SOLUTION>` in order; and (ii) a *class-weighted accuracy* term that upweights the minority class to counter label imbal-

ance. [6] Full reward definitions, numeric weights, sampling limits, logging/checkpointing, and other reproducibility details are provided in Appendix G; empirical results are reported in Table 2.

## 5 What Current Claim Verification Datasets Actually Test: A Qualitative Analysis of Reasoning Traces

LLMAggreFact aggregates nine widely used claim-verification datasets, yet the reasoning complexity they elicit is poorly characterized. Because ThinknCheck generates structured rationales, we can directly inspect what types of reasoning are actually exercised and, by extension, what these datasets truly test.

Figure 3: Distribution of reasoning patterns across LLMAggreFact-Think. Direct evidence extraction (A) dominates the verification strategies (27,988 instances), followed by other reasoning strategies. See Section 5.2 for a detailed discussion.

### 5.1 Methodology

We sampled 1,000 instances from LLMAGGREFACT-THINK with stratified sampling over the dataset source, then manually reviewed the generated rationales for each (document, claim) pair. For every instance, annotators identified the primary strategy used to justify the predicted label. Through an iterative pass, we consolidated categories, recorded recurring patterns, and selected representative examples (Appendix I).

---

[5]Inference uses parameters recommended by the Gemma3 paper: temperature=1.0, top_p=0.95, and top_k=64.

[6]We keep 4bit loading and the same LoRA configuration as in Section 4.2, generate 5 candidates per prompt, and train for a single epoch (400 steps) with fused AdamW ($5\times10^{-6}$ LR), warmup ratio 0.1, per-device batch size 4 and gradient accumulation 4.

## 5.2 Reasoning Patterns Observed in LLMAggreFact-Think

We observe six recurring strategies: (A) *Direct evidence extraction & matching* (quoting or paraphrasing spans that explicitly support/contradict the claim); (B) *Handling nuance & implication* (contextual or partial support without verbatim statements); (C) *Absence of evidence identification* (stating that the document lacks the requisite information); (D) *Synthesis of multiple information points* (integrating evidence across sentences/sections); (E) *Addressing scope/specificity mismatches* (claim broader/narrower or adding elements absent from the source); and (F) *Step-by-step verification* (checking procedural or sequential claims). See Appendix I for examples.

## 5.3 Findings and Implications

Overall distribution (Figure 3) shows a strong dominance of direct extraction (A), with substantially smaller shares for nuance (B), absence identification (C), and multi-sentence synthesis (D); step-by-step verification (F) is rare. The dataset-level breakdown (Figure 7) reveals clear biases: e.g., AggreFact-CNN requires information synthesis in roughly half of cases, whereas even the dataset with the highest rate of multi-step verification (RAGTruth) exhibits it in only ∼0.9% of instances. We also observe complementarity between patterns: sources with very high direct extraction (A) tend to have low synthesis (D). Scope/nuance phenomena (E/B) are more prominent in FactCheck-GPT and Wice, while absence identification (C) varies drastically by formulation (from < 1% in AggreFact-CNN to > 70% in FactCheck-GPT). These findings imply: (i) high scores on current benchmarks primarily reflect retrieval-plus-entailment skills; (ii) capabilities crucial for robust verification—synthesizing distributed evidence and numerical/multi-step reasoning—are under-tested, so systems optimized only for surface matching are unlikely to generalize to harder claims.

## 6 Probing Complex Reasoning Capabilities of Claim Verification Models

Many verification systems falter on claims that require multi-step numerical reasoning (cf. Figures 1, 2), and LLMAggreFact only lightly exercises such cases. To probe and improve this capability, we introduce a focused benchmark for arithmetic verification and a domain-specialized model variant designed for quantitatively and scientifically complex claims.

### 6.1 GSMClaims Dataset for Arithmetic Reasoning

We construct **GSMClaims** from the GSM8K test set (Cobbe et al., 2021) by reframing each problem into *two* claim-verification instances using GPT-4o: (1) convert the problem context into a reference document; (2) generate a *positive* claim whose answer is the correct computed value; and (3) generate a *negative* claim with a plausible but incorrect value reflecting common calculation errors. This 3-step process (illustrated in Figure 6) yields **2,634** balanced items in which verification hinges on performing the arithmetic grounded in the document. We manually inspected a subset of 100 positive and negative claims and found them to be nearperfectly accurate; the prompt template is provided in Appendix H.

### 6.2 ThinknCheck-Science: Specializing for Complex Claims

To better handle quantitative and scientific claims, we train **ThinknCheck-Science**, a targeted variant of ThinknCheck-1B. We augment the LLMAggreFact-Think training data with **614** reasoning-enhanced examples from SciFact (Wadden et al., 2020) and **398** from GSMClaims, emphasizing specialized knowledge and arithmetic calculation. ThinknCheck-Science retains the base architecture, quantization, and training procedure of ThinknCheck-1B, differing only in the enriched supervision set aimed at strengthening numerical and domain-specific reasoning.

## 7 Experiments: Evaluating ThinknCheck

**Research Questions.** We structure the evaluation around four questions: **RQ1**. Do explicit, supervised rationales help at 1B scale? **RQ2**. Do they improve out-of-domain generalization (SCIFACT) over specialized baselines? **RQ3**. Do coarse preference rewards (GRPO) help or hurt? **RQ4**. What reasoning do current verification benchmarks actually test, and where are the gaps? We conducted extensive experiments to assess ThinknCheck's effectiveness across multiple dimensions, comparing against competitive baselines and analyzing the impact of our architectural decisions.

## 7.1 Evaluation Metrics

Following prior work (Tang et al., 2022; Fabbri et al., 2021; Laban et al., 2022; Tang et al., 2024), we adopt Balanced Accuracy (BAcc) as our primary metric for evaluating potentially imbalanced datasets like LLMAggreFact and SciFact. [7] For the balanced GSMClaims dataset, we report standard accuracy, so our results are interpretable with previous works.

## 7.2 Baselines

We compare ThinknCheck against three categories of baselines: (1) closed LLMs in zero-shot settings (GPT-4, GPT-4o, Claude-Sonnet-3.5) as reported by Tang et al. (2024). All significance statements use 10k bootstrap resamples over the 29.3k LLMAggreFact test instances with paired resampling across models. Our goal is not to compete with these private and massive foundation models, but to provide context., (2) specialized verification models (AlignScore, MiniCheck-7B), and (3) ThinknCheck variants (ThinknCheck-nothink, ThinknCheck, ThinknCheck-Science) to isolate the impact of reasoning and data augmentation components.

## 7.3 Core Verification Performance: ThinknCheck vs. Abalation Variants (Base model, Non-thinking, CoT, and GRPO)

Table 1 summarizes results on the 29.3k-example LLMAggreFact test set. The reasoning-supervised **ThinknCheck-1B** (4-bit) attains **78.1** BAcc, surpassing MiniCheck-7B (77.4) despite using $\sim 7\times$ fewer parameters, and matching or exceeding zero-shot closed models (GPT-4: 75.3; GPT-4o: 75.9; Claude Sonnet 3.5: 77.2). Reasoning is essential: removing it (*ThinknCheck-nothink*) drops BAcc to 57.5, a $-20.6$ point decline. On the 1B base, zero-shot CoT hurts relative to direct answers (Gemma3-1B 55.7 $\rightarrow$ 51.4), whereas supervised reasoning reverses the pattern and yields the best 1B result. All deltas are significant under paired bootstrap over test instances ($p < 0.05$). Preference optimization with a simple two-term reward (format + class-weighted accuracy) underperforms supervised reasoning (Table 2): GRPO from base yields 52.6 BAcc (below 55.7), and GRPO from an SFT

---

[7]
$$\text{BAcc} = \frac{1}{2}\left(\frac{\text{TP}}{\text{TP} + \text{FN}} + \frac{\text{TN}}{\text{TN} + \text{FP}}\right),$$
where TP, TN, FP, and FN represent true positives, true negatives, false positives, and false negatives, respectively.

| Model | BAcc |
|---|---|
| GPT-4 (zero-shot) | 75.3 |
| GPT-4o (zero-shot) | 75.9 |
| Claude-Sonnet-3.5 (zero-shot) | 77.2 |
| AlignScore (355M/fp16) | 70.4 |
| MiniCheck (7B/fp16) | 77.4 |
| Gemma3 (1B/fp4) ("base") | 55.7 |
| Gemma3 + CoT (1B/fp4) | 51.4 |
| ThinknCheck-nothink (1B/fp4) | 57.5 |
| ThinknCheck (1B/fp4) | **78.1** |

Table 1: Balanced accuracy (BAcc) on the LLMAG-GREFACT test set (29.3k examples). The 1B *reasoning-supervised* ThinknCheck model attains 78.1 BAcc, exceeding the specialized 7B MiniCheck (77.4). In contrast, applying Chain-of-Thought (CoT) at inference to the *non-fine-tuned* 1B base model reduces performance relative to direct answering (55.7 $\rightarrow$ 51.4), while answer-only SFT yields only a small gain (57.5). Significance is assessed via paired bootstrap over test instances ($p < 0.05$).

| Method (Gemma3-1B, fp4) | BAcc |
|---|---|
| GRPO on Gemma3 ("base") | 52.6 |
| GRPO on Gemma3-SFT-400 ("warm start") | 74.2 |

Table 2: Preference optimization via GRPO on LLMAggreFact. Under a two-term reward (format adherence + class-weighted accuracy), GRPO reduces accuracy both from base ($-3.1$ points vs. direct) and from the SFT checkpoint ($-3.9$ points). A qualitative audit shows the GRPO policy over-relies on lexical overlap between claim and document rather than evidence-grounded reasoning; see Section 8 for the corresponding error type. Training details and rewards are in Appendix G.

warm start reaches 74.2 (below 78.1). A manual audit indicates GRPO gravitates toward a lexical-overlap shortcut (predicting YES when the claim reuses document phrasing), aligning with the error profile in Section 8 and the length analysis in Section 7.6. At 1B scale, explicit reasoning supervision is a more reliable path than zero-shot CoT or coarse preference rewards for grounded verification.

## 7.4 Robustness and Generalization: Evaluation on SciFact

Beyond core performance, we investigated ThinknCheck's robustness to distribution shifts. Scientific claims in the SciFact benchmark often require implicit reasoning or conceptual understanding beyond simple lexical overlap (as illustrated in Figure 1). We hypothesized that ThinknCheck's explicit reasoning process would enhance out-of-domain generalization compared to models focused

solely on classification.

Table 3 strongly supports this hypothesis. ThinknCheck-1B achieves 64.7 BAcc on the Sci-Fact development set, a substantial 14.7 absolute point improvement (29.4% relative gain) over MiniCheck-7B (50.0 BAcc). The ThinknCheck-nothink ablation performs poorly (21.7 BAcc), confirming that the reasoning capability drives this enhanced generalization. These results demonstrate that ThinknCheck handles claims requiring deeper understanding more effectively, suggesting important implications for practical deployment in domain-shifting scenarios.

| Model | BAcc |
|---|---|
| MiniCheck-7B | 50.0 |
| ThinknCheck-nothink-1B | 21.7 |
| ThinknCheck-1B | **64.7** |

Table 3: Performance on the SciFact development set. The reasoning mechanism in ThinknCheck-1B leads to vastly superior out-of-domain generalization compared to MiniCheck-7B and the non-reasoning ablation. Statistical significance determined via bootstrap resampling of balanced accuracy ($p < 0.05$) across the SciFact dev set.

## 7.5 Performance on Complex Reasoning: GSMClaims & ThinknCheck-Science

We used the GSMClaims dataset introduced in Section 6.1 to evaluate performance on claims requiring arithmetic reasoning. Table 4 shows the zero-shot performance across models. As expected, both ThinknCheck-1B (52.1% Acc) and MiniCheck-7B (51.3% Acc) find this task challenging, particularly struggling to verify correct positive claims. This confirms that current datasets relying heavily on textual entailment are insufficient for reliable numerical reasoning.

| Model | Positive | Negative | Overall |
|---|---|---|---|
| Uniform Baseline | 50.0 | 50.0 | 50.0 |
| MiniCheck-7B | 14.4 | 88.1 | 51.3 |
| ThinknCheck-nothink-1B | 1.0 | 97.8 | 49.4 |
| ThinknCheck-1B | 14.6 | 89.8 | **52.2** |

Table 4: Zero-shot performance on GSMClaims (Accuracy %). Both ThinknCheck and MiniCheck struggle with arithmetic reasoning, particularly verifying positive (correct) claims Statistical significance determined via paired t-test ($p < 0.05$) on the per-example accuracy across the GSMClaims test set.

To address this limitation, we evaluated ThinknCheck-Science, our model specifically trained with additional scientific and arithmetic

data (introduced in Section 4.2). Table 5 compares its performance against other models across all benchmarks and Figure 1 shows ThinknCheck-Science in action with a highly non-trivial claim verification example requiring complex reasoning. ThinknCheck-Science achieves the best performance on GSMClaims (61.0% Acc), demonstrating that the ThinknCheck architecture can be effectively specialized through targeted training to significantly improve quantitative reasoning capabilities. Importantly, it also shows improvements on LLMAggreFact and SciFact, indicating that the specialized training enhances rather than compromises its general verification abilities.

| Model | LLMAggre Fact | SciFact (dev) | GSM Claims |
|---|---|---|---|
| MiniCheck-7B | 77.4 | 50.0 | 51.3 |
| ThinknCheck-nothink-1B | 57.5 | 21.7 | 49.4 |
| ThinknCheck-1B | 78.1 | 64.7 | 52.2 |
| ThinknCheck-Science-1B | **79.2** | **66.4** | **61.0** |

Table 5: Performance of ThinknCheck-Science across datasets. Targeted training significantly improves performance not only on arithmetic (GSMClaims) and scientific (SciFact) verification, but also on general claim verification (LLMAggreFact).

These results demonstrate that ThinknCheck-Science offers comprehensive improvements across all evaluation benchmarks, with 17% relative improvement over the base model on GSMClaims.

## 7.6 How much reasoning is enough? Reasoning Length vs. Accuracy

We study ThinknCheck-1B on the LLMAggreFact test set to relate the amount of generated reasoning to correctness: we tokenize the `<REASONING>` span with the Gemma3 tokenizer, bucket examples into ten equal-sized deciles by token length, and compute BAcc per decile (Figure 4). Accuracy follows an inverted-U: mid-length rationales yield the best BAcc, whereas very short and very long chains underperform. Short chains exhibit recall exceeding precision, consistent with liberal "YES" predictions triggered by shallow matches; at the longest lengths, recall drops below precision, reflecting conservative behavior and more false negatives. Length is not causal—longer chains co-vary with instance difficulty and the need to aggregate more evidence—but the pattern aligns with our error taxonomy (Section 8): terse chains co-occur with lexical-overlap false positives, and very long chains with over-cautiousness and insufficient aggregation. Together with the ablations in Sec-

tion 7.3, the takeaway is that focused, succinct-but-substantive reasoning, rather than maximal length, is most reliable at 1B scale.

## 8 Error Analysis

A comprehensive error analysis of ThinknCheck-1B on LLMAggreFact, SciFact, and GSMClaims datasets, using a unified error taxonomy (Figure 11a), revealed varied error profiles. **Lexical Overlap Bias** was most prevalent in LLMAggreFact (5.3%) but lower in GSMClaims (3.9%). In GSMClaims, mathematical claims led to dominant **Arithmetic Reasoning** errors (20.7%). **Overcautiousness**, the leading error in SciFact (41.4%), reflects difficulty confirming complex, ungrounded scientific assertions. **Negation/Temporal** errors were significant in SciFact (32.7%) and LLMAggreFact (3.3%) but rare in GSMClaims (0.4%), highlighting domain-specific reasoning issues. **Insufficient Aggregation** occurred across datasets, critically in LLMAggreFact (4.6%) where multi-hop synthesis is key. These patterns show significant domain-specific error profile variations, underscoring the need for dataset-specific claim verification strategies. We also examined errors after GRPO optimization (c.f. Sections 4.3, 7.3), and discovered that GRPO increased the share of *lexical-overlap* false positives: the policy frequently predicted YES when the claim reused phrases from the document, without verifying entailment. This aligns with our qualitative audit and supports the hypothesis that the coarse reward encouraged a superficial overlap heuristic. Consistent with Sec. 7.6, terse rationales coincide with lexical-overlap false positives (inflated recall), while very long rationales correlate with over-cautiousness and insufficient aggregation (reduced recall), indicating qualitatively different failure modes at length extremes. Our findings show domain-specific error patterns: general-domain verification was most affected by lexical overlap bias and insufficient aggregation (Appendix K); scientific claims by a high rate of overcautious false negatives and negation errors (Appendix L); and mathematical claims by arithmetic reasoning failures and multi-step aggregation issues (Appendix M). These insights suggest targeted mitigations like adversarial data mining and domain-specific prompting. Detailed examples and further recommendations are in the respective appendices

Figure 4: **Reasoning length vs. balanced accuracy (LLMAggreFact).** ThinknCheck-1B outputs are grouped into deciles by the token length of the `<REASONING>` span (Gemma tokenizer). BAcc peaks for mid-length rationales and drops for very short and very long chains. Short chains show recall > precision; very long chains show the opposite trend.

## 9 Conclusion

We introduced ThinknCheck, a compact verifier trained to reason before deciding. At 1B parameters, supervised rationales raise performance on LLMAggreFact to 78.1 BAcc and improve out-of-domain generalization on SciFact (64.7 BAcc vs. 50.0 for MiniCheck-7B). Removing the reasoning step lowers BAcc by 20.6 points, and both zero-shot chain-of-thought on the base model and GRPO with a simple reward degrade accuracy under our setup. Analysis of model traces suggests that widely used verification datasets emphasize surface matching while under-testing evidence synthesis and arithmetic. Our GSMClaims benchmark and the domain-adapted ThinknCheck-Science address these gaps and yield gains across tasks, including 61.0% accuracy on GSMClaims. A reasoning length study further indicates that mid-length rationales are most reliable for this setting, though length likely correlates with instance difficulty rather than causing accuracy changes. In sum, the results support small, reasoning-supervised verifiers as practical building blocks for grounded verification when compute, privacy, or latency constrain model size. Immediate next steps include constructing harder, balanced datasets that require multi-sentence synthesis and numerical reasoning, adding lightweight tool use for arithmetic, and learning adaptive reasoning budgets that keep rationales concise without sacrificing correctness.

## 10 Limitations

ThinknCheck advances claim verification, and we identify several promising directions for future development. Our CoT result reflects a single prompt and decoding setup; while consistent with recent reports that CoT can hurt small models without adaptation, we did not exhaustively analyze all CoT prompt variations. Our GRPO setup uses a concise, two-term reward and a short training horizon (400 steps); alternative rewards (e.g., evidence-aware or contrastive), stronger KL or behavior-cloning constraints to the SFT policy, or longer training may change outcomes. We therefore interpret the GRPO results as a negative finding under a transparent, reproducible configuration rather than a general indictment of preference optimization. While the Gemma3-1B backbone supports a 32k-token context window, our experiments do not stress this limit: we evaluate single-document verification with relatively short inputs – a limitation of current claim verification benchmarks. Extending ThinknCheck to truly long-context settings (multi-document packs (Poli et al., 2023; Waleffe et al., 2024), ≥10k tokens) is left for future work. We also used a fixed maximum decoding budget for the <REASONING> span; making this budget adaptive could reduce both under- and over-thinking. Furthermore, performance on tasks like GSMClaims suggests that integrating external tools (e.g., calculators) (Patil et al., 2024) is a key step for complex arithmetic reasoning. Finally, aligning with challenges in prior work (Tang et al., 2024; Zha et al., 2023), calibrating output logits to serve as reliable confidence scores (Liu et al., 2025b) remains an important area for ongoing investigation and future refinement of ThinknCheck.

## 11 Ethical Considerations and Broader Impact

Please see Appendix N for a detailed discussion of broader impact of this work and its ethical ramifications.

## 12 Reproducibility Statement

We are committed to ensuring the reproducibility of our research. To this end, we provide details regarding our datasets, models, and experimental setup in Appendix O.

## References

Loubna Ben Allal, Anton Lozhkov, Elie Bakouch, Gabriel Martín Blázquez, Guilherme Penedo, Lewis Tunstall, Andrés Marafioti, Hynek Kydlíček, Agustín Piqueres Lajarín, Vaibhav Srivastav, et al. 2025. Smollm2: When smol goes big–data-centric training of a small language model. *arXiv preprint arXiv:2502.02737*.

Gagan Bansal, Tongshuang Sherry Wu, Joyce Zhou, Raymond Fok, Besmira Nushi, Ece Kamar, Marco Tulio Ribeiro, and Daniel S. Weld. 2020. Does the whole exceed its parts? the effect of ai explanations on complementary team performance. *Proceedings of the 2021 CHI Conference on Human Factors in Computing Systems*.

Hung-Ting Chen, Fangyuan Xu, Shane A Arora, and Eunsol Choi. 2023. Understanding retrieval augmentation for long-form question answering. *arXiv preprint arXiv:2310.12150*.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. Training verifiers to solve math word problems. *Preprint*, arXiv:2110.14168.

DeepSeek-AI, Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, Xiaokang Zhang, Xingkai Yu, Yu Wu, Z. F. Wu, Zhibin Gou, Zhihong Shao, Zhuoshu Li, Ziyi Gao, Aixin Liu, Bing Xue, Bingxuan Wang, Bochao Wu, Bei Feng, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, and many more. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *Preprint*, arXiv:2501.12948.

Alexander R Fabbri, Chien-Sheng Wu, Wenhao Liu, and Caiming Xiong. 2021. Qafacteval: Improved qa-based factual consistency evaluation for summarization. *arXiv preprint arXiv:2112.08542*.

Mingming Fan, Xianyou Yang, Tsz Tung Yu, Vera Q. Liao, and J. Zhao. 2021. Human-ai collaboration for ux evaluation: Effects of explanation and synchronization. *ArXiv*, abs/2112.12387.

GemmaTeam, Aishwarya Kamath, Johan Ferret, Shreya Pathak, Nino Vieillard, Ramona Merhej, Sarah Perrin, Tatiana Matejovicova, Alexandre Ramé, Morgane Rivière, Louis Rouillard, Thomas Mesnard, Geoffrey Cideron, Jean bastien Grill, Sabela Ramos, Edouard Yvinec, Michelle Casbon, Etienne Pot, Ivo Penchev, Gal Liu, Francesco Visin, Kathleen Kenealy, Lucas Beyer, Xiaohai Zhai, Anton Tsitsulin, Robert Busa-Fekete, Alex Feng, Noveen Sachdeva, Benjamin Coleman, and many more. 2025. Gemma 3 technical report. *Preprint*, arXiv:2503.19786.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2021. Lora: Low-rank adaptation of large language models. *Preprint*, arXiv:2106.09685.

Yebowen Hu, Tim Ganter, Hanieh Deilamsalehy, Franck Dernoncourt, Hassan Foroosh, and Fei Liu. 2023. Meetingbank: A benchmark dataset for meeting summarization. *arXiv preprint arXiv:2305.17529*.

Alon Jacovi, Yonatan Bitton, Bernd Bohnet, Jonathan Herzig, Or Honovich, Michael Tseng, Michael Collins, Roee Aharoni, and Mor Geva. 2024a. A chain-of-thought is as strong as its weakest link: A benchmark for verifiers of reasoning chains. *Preprint*, arXiv:2402.00559.

Alon Jacovi, Yonatan Bitton, Bernd Bohnet, Jonathan Herzig, Or Honovich, Michael Tseng, Michael Collins, Roee Aharoni, and Mor Geva. 2024b. A chain-of-thought is as strong as its weakest link: A benchmark for verifiers of reasoning chains. *arXiv preprint arXiv:2402.00559*.

Misbah Javaid and Vladimir Estivill-Castro. 2021. Explanations from a robotic partner build trust on the robot's decisions for collaborative human-humanoid interaction. *Robotics*, 10:51.

Ryo Kamoi, Tanya Goyal, Juan Diego Rodriguez, and Greg Durrett. 2023. Wice: Real-world entailment for claims in wikipedia. *arXiv preprint arXiv:2303.01432*.

Philippe Laban, Tobias Schnabel, Paul N Bennett, and Marti A Hearst. 2022. Summac: Re-visiting nli-based models for inconsistency detection in summarization. *Transactions of the Association for Computational Linguistics*, 10:163–177.

Yuetai Li, Xiang Yue, Zhangchen Xu, Fengqing Jiang, Luyao Niu, Bill Yuchen Lin, Bhaskar Ramasubramanian, and Radha Poovendran. 2025. Small models struggle to learn from strong reasoners. *Preprint*, arXiv:2502.12143.

Nelson F Liu, Tianyi Zhang, and Percy Liang. 2023. Evaluating verifiability in generative search engines. *arXiv preprint arXiv:2304.09848*.

Ryan Liu, Jiayi Geng, Addison J. Wu, Ilia Sucholutsky, Tania Lombrozo, and Thomas L. Griffiths. 2025a. Mind your step (by step): Chain-of-thought can reduce performance on tasks where thinking makes humans worse. *Preprint*, arXiv:2410.21333.

Xiaoou Liu, Tiejin Chen, Longchao Da, Chacha Chen, Zhen Lin, and Hua Wei. 2025b. Uncertainty quantification and confidence calibration in large language models: A survey. *arXiv preprint arXiv:2503.15850*.

Zichen Liu, Changyu Chen, Wenjun Li, Penghui Qi, Tianyu Pang, Chao Du, Wee Sun Lee, and Min Lin. 2025c. Understanding r1-zero-like training: A critical perspective. *Preprint*, arXiv:2503.20783.

Chaitanya Malaviya, Subin Lee, Sihao Chen, Elizabeth Sieber, Mark Yatskar, and Dan Roth. 2023. Expertqa: Expert-curated questions and attributed answers. *arXiv preprint arXiv:2309.07852*.

Chaitanya Malaviya, Subin Lee, Sihao Chen, Elizabeth Sieber, Mark Yatskar, and Dan Roth. 2024. ExpertQA: Expert-curated questions and attributed answers. In *2024 Annual Conference of the North American Chapter of the Association for Computational Linguistics*.

Ramesh Nallapati, Bowen Zhou, Caglar Gulcehre, Bing Xiang, et al. 2016. Abstractive text summarization using sequence-to-sequence rnns and beyond. *arXiv preprint arXiv:1602.06023*.

Shashi Narayan, Shay B Cohen, and Mirella Lapata. 2018. Don't give me the details, just the summary! topic-aware convolutional neural networks for extreme summarization. *arXiv preprint arXiv:1808.08745*.

Shishir G Patil, Tianjun Zhang, Xin Wang, and Joseph E Gonzalez. 2024. Gorilla: Large language model connected with massive apis. *Advances in Neural Information Processing Systems*, 37:126544–126565.

Michael Poli, Stefano Massaroli, Eric Nguyen, Daniel Y Fu, Tri Dao, Stephen Baccus, Yoshua Bengio, Stefano Ermon, and Christopher Ré. 2023. Hyena hierarchy: Towards larger convolutional language models. In *International Conference on Machine Learning*, pages 28043–28078. PMLR.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. 2024a. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *Preprint*, arXiv:2402.03300.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Y Wu, et al. 2024b. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*.

Liyan Tang, Tanya Goyal, Alexander R Fabbri, Philippe Laban, Jiacheng Xu, Semih Yavuz, Wojciech Kryściński, Justin F Rousseau, and Greg Durrett. 2022. Understanding factual errors in summarization: Errors, summarizers, datasets, error detectors. *arXiv preprint arXiv:2205.12854*.

Liyan Tang, Philippe Laban, and Greg Durrett. 2024. Minicheck: Efficient fact-checking of llms on grounding documents. *Preprint*, arXiv:2404.10774.

James Thorne, Andreas Vlachos, Christos Christodoulopoulos, and Arpit Mittal. 2018. Fever: a large-scale dataset for fact extraction and verification. *arXiv preprint arXiv:1803.05355*.

Leandro von Werra, Younes Belkada, Lewis Tunstall, Edward Beeching, Tristan Thrush, Nathan Lambert, Shengyi Huang, Kashif Rasul, and Quentin Gallouédec. 2020. Trl: Transformer reinforcement learning. https://github.com/huggingface/trl.

David Wadden, Shanchuan Lin, Kyle Lo, Lucy Lu Wang, Madeleine van Zuylen, Arman Cohan, and Hannaneh Hajishirzi. 2020. Fact or fiction: Verifying scientific claims. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 7534–7550, Online. Association for Computational Linguistics.

Roger Waleffe, Wonmin Byeon, Duncan Riach, Brandon Norick, Vijay Korthikanti, Tri Dao, Albert Gu, Ali Hatamizadeh, Sudhakar Singh, Deepak Narayanan, et al. 2024. An empirical study of mamba-based language models. *arXiv preprint arXiv:2406.07887*.

Yuxia Wang, Revanth Gangi Reddy, Zain Muhammad Mujahid, Arnav Arora, Aleksandr Rubashevskii, Jiahui Geng, Osama Mohammed Afzal, Liangming Pan, Nadav Borenstein, Aditya Pillai, et al. 2023. Factcheck-bench: Fine-grained evaluation benchmark for automatic fact-checkers. *arXiv preprint arXiv:2311.09000*.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837.

Xiaohan Xu, Ming Li, Chongyang Tao, Tao Shen, Reynold Cheng, Jinyang Li, Can Xu, Dacheng Tao, and Tianyi Zhou. 2024. A survey on knowledge distillation of large language models. *arXiv preprint arXiv:2402.13116*.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2023. React: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations (ICLR)*.

Yuheng Zha, Yichi Yang, Ruichen Li, and Zhiting Hu. 2023. Alignscore: Evaluating factual consistency with a unified alignment function. *Preprint*, arXiv:2305.16739.

Muru Zhang, Ofir Press, William Merrill, Alisa Liu, and Noah A Smith. 2023. How language model hallucinations can snowball. *arXiv preprint arXiv:2305.13534*.

Chujie Zheng, Shixuan Liu, Mingze Li, Xiong-Hui Chen, Bowen Yu, Chang Gao, Kai Dang, Yuqiong Liu, Rui Men, An Yang, Jingren Zhou, and Junyang Lin. 2025. Group sequence policy optimization. *Preprint*, arXiv:2507.18071.

Chenguang Zhu, Yang Liu, Jie Mei, and Michael Zeng. 2021. Mediasum: A large-scale media interview dataset for dialogue summarization. *arXiv preprint arXiv:2103.06410*.

Figure 5: Comparing reasoning traces derived from Deepseek R1 vs. gpt-4o with the same prompt (c.f. Appendix C) on claim verification problems in LLAggreFact. These metrics showed high variance (which we didn't plot here for legibility) for R1 and low variance for GPT-4o. GPT-4o is significantly token efficient compared to R1, making it our choice for harvesting reasoning traces.

## A Reasoning Efficiency of GPT-4o vs. Deepseek R1

## B Illustration of GSMCLAIMS construction

Figure 6 shows the construction process for GSM-CLAIMS.

## C Prompt for generating LLMAggreFact-Think

> You are expert fact checker with a strong attention to detail and access to a wealth of information. Given a document and a claim, determine if the claim is entailed by the document, only using the facts in the document.
> Respond in the following format:
>
> ```
> <reasoning>
> ... // clear, but short description of your
>     step by step
>   // thinking to arrive at the entailment
>   // keep the reasoning sentences separated
>       by a newline.
> </reasoning>
> <entailment>
> ... // This is always a single word, either
>     "YES" or "NO"
> </entailment>
> ```

## D ThinknCheck finetuning: hyperparameter details

For fine-tuning, we used LoRA (Hu et al., 2021) with rank=64, lora_alpha=64, and a learning rate of 2e-4 scheduled linearly. We updated the query, key, value, and output projection layers, as well as MLP gate, up, and down projections. The fine-tuning was performed on an A100 GPU for 1 epoch, with 5

Figure 6: To build GSMClaims, we reframe GSM8K (Cobbe et al., 2021) problems as claim verification problems requiring arithmetic processing. See Appendix H for the prompt used in the LLM call.

warmup steps, a batch size of 4 with 4 accumulated steps, and an 8bit-AdamW optimizer with a weight decay of 0.01.

## E Finetuning Prompt for ThinknCheck

> You are given a document and a claim. The document is enclosed between <DOCUMENT> and </DOCUMENT>. The claim is between <CLAIM> and </CLAIM>. Determine if the claim is entailed by the document. Think about the problem and provide your reasoning. Place the reasoning between <REASONING> and </REASONING>. Then, provide your entailment solution between <SOLUTION> and </SOLUTION>. The entailment should be either a YES or a NO.
>
> ```
> <DOCUMENT>
> {document}
> </DOCUMENT>
> <CLAIM>
> {claim}
> </CLAIM>
> <REASONING>
> {reasoning}
> </REASONING>
> <SOLUTION>
> {solution}
> </SOLUTION>
> ```

## F Finetuning Prompt for ThinknCheck-nothink

> You are given a document and a claim. The document is enclosed between <DOCUMENT> and </DOCUMENT>. The claim is between <CLAIM> and </CLAIM>. Determine if the claim is entailed by the document. Provide your entailment solution between <SOLUTION> and </SOLUTION>. The entailment should be either a YES or a NO.
>
> ```
> <DOCUMENT>
> {document}
> </DOCUMENT>
> <CLAIM>
> {claim}
> </CLAIM>
> <SOLUTION>
> {solution}
> </SOLUTION>
> ```

## G GRPO Variant: Training and Reproducibility

### G.1 Model, Initialization, and Tokenization

**Backbone and loading.** We build on a 1B-parameter GEMMA3 instruction-tuned checkpoint loaded in 4-bit with bitsandbytes for memory efficiency. The tokenizer uses the "gemma-3" chat template. We set a maximum sequence length of 4,684 tokens to accommodate (document, claim, rationale, answer) for long inputs.

**LoRA configuration.** We apply LoRA with rank $r=64$, $\alpha=64$, and dropout $0$. Adapters are attached to *all* transformer layers, covering attention (Q, K, V, O) and MLP (gate, up, down) modules (finetune_attention_modules=True, finetune_mlp_modules=True). Gradient checkpointing is enabled ("unsloth" implementation). We fix the random seed to 3407 for reproducibility.

**Warm start from supervised SFT.** Before GRPO, we initialize LoRA adapters from a checkpoint obtained after 400 SFT steps on the same task data ("SFT400"), which stabilizes early exploration.

## G.2 Reward Design

We optimize a sum of two rewards, $R(\hat{y}) = \lambda_{\text{fmt}}R_{\text{fmt}}(\hat{y}) + \lambda_{\text{acc}}R_{\text{acc}}(\hat{y})$, using $\lambda_{\text{fmt}}$=0.5 and $\lambda_{\text{acc}}$=1.0.

**Format-adherence reward ($R_{\text{fmt}}$).** A binary regex validator checks that the completion contains both tags in order:

```
<REASONING>.*?</REASONING>\s*<SOLUTION>.*?</
    SOLUTION>
```

Valid outputs receive $+1.0$; otherwise $-1.0$.

**Class-weighted accuracy reward ($R_{\text{acc}}$).** We robustly parse the `<SOLUTION>` span to extract a final label in {YES, NO}. To counter class imbalance, we compute per-class weights via the inverse-frequency rule

$$w_c = \frac{N}{C \cdot \text{count}(c)},$$

using training-label frequencies. This yields $w_{\text{YES}}$=0.6356 and $w_{\text{NO}}$=2.3435. A correct YES receives $+4.0 \times 0.6356$, a correct NO $+4.0 \times 2.3435$; incorrect predictions receive the corresponding negative value. This discourages the trivial majority-class policy.

## G.3 GRPO Optimization Setup

We use `TRL`'s `GRPOTrainer` with the Dr. GRPO loss and sequence-level importance sampling (GSPO).

**Sampling and lengths.** Per prompt we draw 5 completions (`num_generations=5`). We cap the prompt at $4{,}306$ tokens and completions at $378$ tokens. Generation runs through `vLLM` in "colocate" mode.

**Batching and optimizer.** Training proceeds for one epoch (400 steps) with `adamw_torch_fused`, learning rate $5\times10^{-6}$, warmup ratio 0.1, per-device batch size 4, and gradient accumulation 4 (effective batch size 16).

## G.4 Prompt Format and Inference Settings (for comparability)

GRPO variants use the same structured I/O format as SFT (Appendix E) and the paper's decoding defaults (temperature=1.0, top_p=0.95, top_k=64) so that comparisons to SFT and to zero-shot baselines are apples-to-apples.

## H Prompt to generate GSMClaims

Given an arithmetic problem and a solution, rewrite them as a document and a a pair of positive and negative claims such the positive claim is entailed by the document (after solving some arithmetic) and the negative claim is not entailed by the document (after solving some arithmetic). Produce your answer only as a JSON. Do not add anything before and after the JSON.

## I Examples of Reasoning Patterns in LLMAggreFact-Think

**Direct Evidence Extraction & Matching:**

*Claim:* "Proper clean-up prior to insertion of the vaginoscope is essential."
*Reasoning:* "The document contains a sentence that explicitly states 'Proper clean-up prior to insertion of the vaginoscope is essential.' This directly matches the claim made..."

**Absence of Evidence Identification:**

*Claim:* "A star's temperature is determined by the amount of mass and energy it has."
*Reasoning:* "The document discusses determining the effective temperature of a star from its spectrum but does not mention the relationship between a star's mass, energy, and temperature... Therefore, the claim is not backed by the facts in the document..."

**Synthesis of Multiple Information Points:**

*Claim:* "However, according to customer reviews, the quality of the food served at the restaurant is subpar."
*Reasoning:* "The document contains multiple customer reviews expressing dissatisfaction... One review explicitly states that the food was 'horrible,'... Another review criticizes the broth as 'least flavorful'... Together, these reviews confirm that the quality of food... is indeed regarded as subpar by customers."

**Addressing Scope and Specificity Mismatches:**

*Claim:* "Thermodynamics provides the fundamental laws of energy conservation, mass conservation, and chemical equilibrium that govern the behavior of chemical systems."
*Reasoning:* "The document discusses the first law of thermodynamics, which addresses energy conservation, aligning with part of the claim. However, it does not support the components of mass conservation and chemical equilibrium... Therefore, the claim goes beyond what is explicitly stated... and is only partially supported."

**Handling Nuance and Implication:**

*Claim:* "The restaurant's use of fresh and high-quality

ingredients, such as shrimp and pork belly, has also been commended by reviewers."

*Reasoning:* "...One review even states that 'the shrimp you could really sink your teeth into,' suggesting that the shrimp is fresh and of high quality. The combination of positive comments about these specific ingredients supports the claim."

## Step-by-Step Verification:

*Claim:* "Return beef and any accumulated juices to the pan, along with tomato sauce, liver spread, and bay leaves."

*Reasoning:* "...passage 3 explicitly states to 'Return beef and accumulated juices to pan' and also adds 'Add water, tomato sauce, liver spread and bay leaf.' Therefore, all elements of the claim are present in the passage..."

## J Distribution of the Reasoning Methods across datasets

Figure 7: Comparative distribution of reasoning strategies employed for claim verification across various source datasets within LLMAggreFact-Think. Each subplot (A-F) corresponds to a distinct reasoning method identified in Section 5: (A) Direct evidence extraction & matching, (B) Handling nuance & implication, (C) Absence of evidence identification, (D) Synthesis of multiple information points, (E) Addressing scope & specificity of mismatches, and (F) Step-by-step verification. The figure highlights how different datasets predominantly elicit different reasoning patterns.

# K Comprehensive Error Analysis and Mitigation Strategies: LLMAggreFact

## K.1 Error Taxonomy and Case Counts

Through systematic analysis of model predictions, we identified five distinct error categories that capture the primary failure modes in claim verification:

**Lexical Overlap Bias** occurs when the model incorrectly predicts YES based on surface-level lexical similarity between the claim and context, without proper semantic entailment assessment. **Insufficient Aggregation** manifests as the model's failure to synthesize information distributed across multiple sentences or paragraphs – a critical requirement for complex, multi-hop claims. **Negation/Temporal Confusion** involves mishandling negations or temporal relationships, often resulting in incorrect entailment decisions. **Overcautiousness** is observed when the model requires complete and explicit evidence for all components of a composite claim, defaulting to NO even when most sub-claims are well-supported. Finally, **Hallucinated Justification** errors arise when the model generates confident reasoning unsupported by the document, particularly prevalent when input is truncated.

Our quantitative analysis of the development set reveals the following distribution of these error types:

| Error Type | Case Count |
|---|---|
| Lexical Overlap Bias | 1,543 |
| Insufficient Aggregation | 1,350 |
| Negation/Temporal | 959 |
| Overcautiousness | 837 |
| Hallucinated/Truncation | 29 |

Table 6: Counts of each error type in the analysis set.

## K.2 Representative Error Snippets

We present characteristic examples of each error type, illustrating the specific patterns and reasoning failures observed:

**Lexical Overlap Bias:**

    **Claim:** Roberto Martinez felt Seamus Coleman should have been awarded a free-kick before the defender conceded the penalty that allowed Swansea to pinch a 1-1 draw at the Liberty Stadium.
    **Ground Truth:** NO

Figure 8: This figure shows the percentage of errors in the development set attributed to each major error type identified during our analysis of the ThinknCheck claim verification model. The most prevalent error is Lexical Overlap Bias (5.3%), where the model incorrectly predicts support for a claim based primarily on surface-level phrase overlap between the claim and document, rather than true entailment. Insufficient Aggregation (4.6%) represents failures to synthesize evidence across multiple sentences or paragraphs – often required for complex, multi-hop claims. Negation/Temporal errors (3.3%) arise when the model fails to correctly handle negation or temporal relationships, frequently confusing past, future, or negated statements. Overcautiousness (2.9%) is observed when the model predicts "NO" unless every aspect of a composite claim is explicitly supported, leading to false negatives even when most sub-claims are correct. The least frequent category, Hallucinated/Truncation (0.1%), captures instances where the model generates unsupported or speculative justifications, typically due to truncated input context. These findings highlight key areas for targeted mitigation and future improvement in LLM-based claim verification systems.

    **Predicted:** YES
    **Analysis:** The model matches surface phrases without verifying true entailment.

**Negation/Temporal Confusion:**

    **Claim:** Lazio beat Napoli 1-0 on Wednesday to reach the Coppa Italia final...
    **Ground Truth:** YES
    **Predicted:** NO
    **Analysis:** The model confuses event chronology, failing to parse past vs. fu-

ture events.

**Hallucinated Justification (Truncation):**

**Claim:** [Claim regarding match details, with evidence cut off by truncation]
**Truncated:** True
**Predicted:** YES
**Analysis:** The model fills in missing information with confident, unsupported rationale.

**Insufficient Aggregation (Multi-hop):**

**Claim:** Leicester City are just three points from safety... have won back-to-back games against Arsenal and West Brom...
**Ground Truth:** YES
**Predicted:** NO
**Analysis:** Model fails to aggregate evidence across sentences.

**Overcautiousness:**

**Claim:** Maxime Machenaud crossed for Racing Metro 92 in the first half. Charlie Hodgson kicked two penalties... Marcelo Bosch won the match with a last-minute penalty.
**Ground Truth:** YES
**Predicted:** NO
**Analysis:** Model returns NO unless every part is perfectly supported, even if most are.

### K.3 Mitigation Strategies

Based on our error analysis, we propose targeted mitigation approaches for each error category:

For **Lexical Overlap Bias**, we recommend incorporating adversarial examples with high lexical overlap but contradictory semantics, multi-task training with established NLI datasets, and explicit prompting for evidence-based reasoning that requires justification of entailment decisions.

To address **Insufficient Aggregation**, enriching training data with multi-hop claims is essential, alongside chain-of-thought prompting or structured claim decomposition techniques. Having the model explicitly highlight or enumerate relevant evidence sentences across the document can also enhance multi-hop reasoning capabilities.

For **Negation/Temporal Confusion**, augmenting training with carefully constructed examples

highlighting negation and temporal relationships is critical. Explicit instructions to attend to these linguistic cues, potentially combined with integration of specialized temporal parsers, could significantly improve performance.

**Overcautiousness** might be mitigated by introducing finer-grained labeling schemes such as "PARTIAL" or "INSUFFICIENT" support, requiring the model to verify each claim component separately, and calibrating the model to avoid overuse of NO predictions for partially supported claims.

Finally, **Hallucinated Justification** errors can be addressed by training with truncated documents explicitly labeled as providing "Insufficient Information," prompting the model to recognize and flag missing evidence, and implementing confidence calibration techniques specific to incomplete inputs.

Our findings underscore that claim verification remains challenging for LLMs, particularly in contexts involving high lexical overlap, multi-hop reasoning requirements, or truncated evidence. We contend that structured data augmentation, adversarial example mining, and carefully designed prompting strategies are essential to addressing these challenging cases and advancing the state of LLM-based claim verification.

## L Comprehensive Error Analysis and Mitigation Strategies: SciFact

### L.1 Error Taxonomy and Distribution

Our analysis of model errors on the SciFact development set identified four primary error categories, with distinct distributions from the general claim verification dataset:

**Overcautiousness** dominates the scientific claim verification errors, manifesting as the model predicting NO unless every component of a claim is directly and explicitly supported, even when the majority of elements are correct. **Negation/Temporal** errors involve misinterpretation of negations, risk factors, associations, or causal and temporal relationships – particularly problematic in scientific contexts where precise interpretation of these elements is critical. **Lexical Overlap Bias** occurs when the model incorrectly predicts YES based on surface-level terminology matches without proper scientific entailment. **Insufficient Aggregation** errors, while less frequent in SciFact compared to general news verification, still occur when the model fails to synthesize distributed evidence for

complex scientific claims.

Figure 9: This bar chart shows the percentage of errors attributable to each major error type. The most frequent is Overcautiousness (41.4%), where the model predicts "NO" unless every component of a scientific claim is directly supported by the abstract. Negation/Temporal errors (32.8%) arise from failure to correctly process negations or temporal/causal relations, often leading to mistakes about risk, association, or event directionality. Lexical Overlap Bias (24.1%) refers to errors where the model incorrectly predicts "YES" based on surface word overlap, without true scientific entailment. Insufficient Aggregation (1.7%) captures failures in synthesizing multi-hop or compositional evidence, a rare but notable error on SciFact. This distribution highlights the unique challenges of scientific claim verification for LLMs.

### L.2 Representative Error Examples

The following examples illustrate characteristic instances of each error type on scientific claims:

**Overcautiousness:**

**Claim:** 1,000 genomes project enables mapping of genetic sequence variation consisting of rare variants with larger penetrance effects than common variants.
**Ground Truth:** YES
**Predicted:** NO
**Analysis:** The document discusses the identification of common variants and the implications of synthetic associations arising from rare variants... but does not provide any information about the specific number of genomes being mapped...

**Negation/Temporal:**

**Claim:** APOE4 expression in iPSC-derived neurons increases AlphaBeta production and tau phosphorylation causing GABA neuron degeneration.
**Ground Truth:** YES
**Predicted:** NO
**Analysis:** ...ApoE4 resulted in higher levels of tau phosphorylation and increased A$\beta$ production, but these effects were not observed in mouse neurons...

**Lexical Overlap Bias:**

**Claim:** ALDH1 expression is associated with better breast cancer outcomes.
**Ground Truth:** NO
**Predicted:** YES
**Analysis:** The document states that ALDH1 expression is correlated with poor prognosis in breast cancers... which is directly supported by the information provided in the document.

**Insufficient Aggregation:**

**Claim:** The YAP1 and TEAD complex translocates into the nucleus where it interacts with transcription factors and DNA-binding proteins that modulate target gene transcription.
**Ground Truth:** YES
**Predicted:** NO
**Analysis:** ...discusses the regulation of the Hippo pathway and mentions YAP/-TAZ are co-activators that interact with TEAD, but does not explicitly state that YAP1 and TEAD complex translocates and interacts as claimed...

### L.3 Mitigation Strategies

To address the specific challenges of scientific claim verification, we propose several targeted mitigation strategies:

For **Overcautiousness**, implementing more nuanced verification labels such as "PARTIAL" or "INSUFFICIENT" support could capture the varying degrees of evidence often found in scientific literature. Additionally, prompting the model to explicitly assess each component of a complex scientific claim independently may mitigate the tendency toward global rejection of partially supported claims.

To address **Negation/Temporal** errors, which are particularly problematic in scientific contexts,

targeted data augmentation with examples emphasizing negation, risk factors, and causal relationships is essential. Specialized instruction to attend to these linguistic features, possibly combined with domain-specific pre-training on scientific literature with these relations, could improve performance.

For **Lexical Overlap Bias**, incorporating challenging negative examples with high domain-specific terminology overlap but contradictory semantics is crucial. Training the model to articulate precise scientific evidence for its predictions, rather than relying on terminology matches, may reduce this error type.

Finally, while less frequent, **Insufficient Aggregation** errors could be addressed by including more complex multi-hop scientific claims in training and employing claim decomposition or structured chain-of-thought prompting to facilitate evidence synthesis across abstracts.

These domain-specific approaches, tailored to the unique challenges of scientific text, are essential for improving the robustness of LLM-based scientific claim verification systems.

## M GSMClaims Error Analysis and Mitigation

### M.1 Error Taxonomy and Distribution

Our analysis of mathematical claim verification errors revealed distinct patterns requiring tailored mitigation strategies. We extended our general error taxonomy with an additional category specific to mathematical reasoning:

**Arithmetic Reasoning** errors occur when the model fails to execute the correct computation or misapplies a mathematical operation, despite correctly understanding the problem structure. **Overcautiousness** manifests as the model predicting NO unless every calculation step is made fully explicit, even when the reasoning is largely correct. **Insufficient Aggregation** errors arise when the model struggles to combine multiple steps or facts required for a multi-hop calculation. **Lexical Overlap Bias** involves incorrectly predicting YES due to matching numbers or mathematical terms, rather than validating computational correctness. **Negation/Temporal** errors, while rare in this domain, occur when the model mishandles negation or temporal aspects of mathematical problems.

| Error Type | Percentage (%) |
|---|---|
| Arithmetic Reasoning | 43.2 |
| Overcautiousness | 25.0 |
| Insufficient Aggregation | 22.7 |
| Lexical Overlap Bias | 8.2 |
| Negation/Temporal | 0.9 |

Table 7: Distribution of error types in the GSMClaims test set.

Figure 10: This histogram shows the percentage of errors attributed to each major error type. The most common are Arithmetic Reasoning errors (43.2%), where the model fails to perform the correct computation or makes mistakes in multi-step math. Overcautiousness (25.0%) and Insufficient Aggregation (22.7%) indicate, respectively, that the model tends to say "NO" unless every calculation is explicit, or struggles to combine multiple facts or operations across the scenario. Lexical Overlap Bias (8.2%) arises when the model is fooled by matching numbers or phrases even if the math is wrong. Negation/Temporal errors are rare (0.9%), reflecting occasional mishandling of negatives or time-dependent claims. This distribution highlights the special challenges of claim verification in math word problems, especially around robust arithmetic reasoning.

### M.2 Representative Error Examples

The following examples illustrate characteristic instances of each error type in mathematical claim verification:

**Arithmetic Reasoning:**

   **Claim:** Janet makes $18 every day at the farmers' market.
   **Ground Truth:** YES
   **Predicted:** NO

**Analysis:** The document states that Janet sells the remainder of her eggs at the farmers' market for $2 per egg... To determine the total earnings, we need to calculate the total revenue... [model fails in calculation].

**Overcautiousness:**

**Claim:** Josh made a profit of $70,000.
**Ground Truth:** YES
**Predicted:** NO
**Analysis:** The document states that Josh buys a house for $80,000 and invests $50,000 in repairs, resulting in an increase in value by 150%... Therefore, the claim... is not directly supported...

**Insufficient Aggregation:**

**Claim:** The robe takes 2 bolts of fabric in total.
**Ground Truth:** NO
**Predicted:** YES
**Analysis:** The document states a robe takes 2 bolts of blue fiber and half that much white fiber... total is 2 bolts + 1 bolt, not 2...

**Lexical Overlap Bias:**

**Claim:** Cynthia will spend $24.00 on ice cream after 60 days.
**Ground Truth:** NO
**Predicted:** YES
**Analysis:** ... calculates surface numbers but matches claim even if the computation is wrong.

**Negation/Temporal:**

**Claim:** 120 pounds of carrots will not be used.
**Ground Truth:** YES
**Predicted:** NO
**Analysis:'** ... Model misreads the negation, misinterpreting the distribution and what's left unused.

### M.3 Mitigation Strategies

The unique challenges of mathematical claim verification require domain-specific mitigation strategies:

For **Arithmetic Reasoning** errors, which constitute the largest error category, we propose augmenting training with intermediate calculation supervision to improve computational accuracy. Prompting for step-by-step computation with explicit requirements to output and verify intermediate values could substantially improve performance. Integration with symbolic calculators or specialized numerical modules may also enhance computation reliability.

To address **Overcautiousness**, implementing partial credit mechanisms for nearly correct answers and encouraging model self-correction through additional verification steps could be beneficial. Training on intentionally ambiguous or underspecified mathematical claims may also reduce the tendency toward rejecting claims that require implicit calculation steps.

For **Insufficient Aggregation** errors, incorporating more multi-hop mathematical problems in training data is essential. Enforcing structured multi-step solution explanations with clearly delineated sub-problems could enhance the model's ability to integrate distributed mathematical information.

**Lexical Overlap Bias** could be mitigated through adversarial training with examples containing similar numerical values but different computational pathways and outcomes. Requiring explicit calculation steps rather than allowing the model to match surface-level numbers would reduce these errors.

Finally, for the rare **Negation/Temporal** errors, targeted data augmentation focusing on problems involving mathematical negation and time-dependent calculations could improve performance in these edge cases.

These findings highlight the distinct challenges of mathematical claim verification in language models, particularly around arithmetic reasoning and computational accuracy. While sharing some error categories with general claim verification, mathematical verification requires specialized approaches focusing on computational precision and structured reasoning.

## N  Ethical Considerations and Broader Impact: Details

The development of automated claim verification systems like ThinknCheck has significant potential for positive societal impact, but also demands careful consideration of ethical challenges and potential

Figure 11: Subfigures (a), (b), and (c) show the distribution of key error types on LLMAggreFact, SciFact, and GSMClaims, respectively revealed during our error analysis. For further discussion of these error types see Section 8.

risks.

## N.1 Broader Impact and Potential Benefits

- **Combating Misinformation:** By providing tools to assess the factual grounding of claims against provided evidence, ThinknCheck aims to contribute to efforts to identify and mitigate the spread of misinformation. The explicit reasoning component is designed to offer transparency, which can be crucial in understanding why a claim is deemed supported or unsupported.

- **Enhancing Transparency and Trust in AI:** The generation of structured reasoning alongside verification decisions is a step towards more interpretable AI. This can foster greater understanding and appropriate trust from users, moving beyond "black box" systems.

- **Democratizing Fact-Checking Tools:** Our work demonstrates the feasibility of building state-of-the-art reasoning and verification models that are considerably smaller (1B parameters) than many leading systems. This improved efficiency can make such tools more accessible for deployment on edge devices or by organizations with limited computational resources, broadening their availability.

- **Supporting Specialized Domains:** Variants like ThinknCheck-Science, with improved capabilities in scientific and arithmetic claim verification, can be valuable in academic, research, or educational settings for verifying complex information.

- **Fostering Research:** The introduction of reasoning-augmented datasets like LLMAggreFact-Think and the GSMClaims

benchmark for arithmetic reasoning are intended to spur further research into more robust, explainable, and nuanced claim verification systems. Our commitment to releasing datasets and models openly supports this goal.

## N.2 Potential Risks and Ethical Challenges

- **Perpetuation of Biases:** ThinknCheck models are trained on existing benchmarks (LLMAggreFact, SciFact) and reasoning traces generated by large language models (GPT-4o-mini for LLMAggreFact-Think). These underlying data sources may contain societal biases (e.g., related to viewpoints, topics, or demographic representation) which could be learned and propagated by our models. While ThinknCheck aims for factual grounding based on provided text, the interpretation and reasoning patterns learned could inadvertently reflect these biases.

- **Over-reliance and Misplaced Trust:** While explanations are intended to improve transparency, there is a risk that users might overly rely on the system's output, especially if the generated reasoning appears plausible but is subtly flawed. A "DOES NOT SUPPORT" label, for instance, might be misinterpreted as active refutation rather than an absence of evidence in the provided document. The quality and true faithfulness of explanations remain an ongoing research challenge.

- **Dual Use and Adversarial Attacks:** Sophisticated claim verification tools, including those that generate reasoning, could potentially be exploited by malicious actors. For instance, they might be used to understand how

to craft more convincing misinformation that can evade detection, or to generate plausible-sounding but false justifications.

- **Errors and Their Consequences:** Despite outperforming baselines, ThinknCheck is not infallible. False negatives (correct claims marked as unsupported) could lead to the dismissal of valid information, while false positives (incorrect claims marked as supported, particularly if backed by flawed reasoning) could contribute to the spread of inaccuracies. The impact of such errors can vary depending on the application domain.

- **Scope of Verification:** It is crucial to recognize that ThinknCheck verifies claims only against the provided document(s). It does not perform open-world fact-checking against comprehensive world knowledge unless that knowledge is present in the input text. This limitation must be clearly communicated to users to prevent misinterpretation of its capabilities.

We are committed to responsible AI development. The open release of our models and datasets is intended to facilitate scrutiny, further research into robustness and fairness, and the development of better evaluation methodologies. Future work should include dedicated audits for bias in both the datasets and model outputs. We also advocate for the use of systems like ThinknCheck as tools to assist human experts and critical thinking, rather than as infallible arbiters of truth. Further research into improving the faithfulness and comprehensibility of the generated reasoning, and educating users on the capabilities and limitations of such systems, will be essential for their responsible deployment.

## O  Reproducibility Statement: Details

### O.1  Datasets

- Core Benchmarks: Our experiments utilize several publicly available benchmarks:

  ★ LLMAggreFact (Tang et al., 2024), which aggregates 9 existing datasets detailed in their work.
  ★ SciFact (Wadden et al., 2020) for scientific claim verification.
  ★ GSM8K (Cobbe et al., 2021) was used as the source for our new GSMClaims dataset.

- Newly Created Datasets: We introduce two new datasets:

  ★ LLMAggreFact-Think: This dataset was created by augmenting the 30.4K examples in the LLMAggreFact development set with reasoning chains generated by GPT-4o-mini. After filtering for label consistency, this resulted in 24.1K examples. The prompt used for generating these reasoning traces is provided in Appendix A.
  ★ GSMClaims: This dataset, comprising 2,634 balanced claim verification instances requiring arithmetic reasoning, was generated from the GSM8K test set using GPT-4o to reformat problems and create positive/negative claims. The generation prompt is detailed in Appendix D.

- Availability: As stated in our contributions, LLMAggreFact-Think and GSMClaims will be released openly under an Apache 2.0 license.

### O.2  Models

- ThinknCheck Models:

  ★ Our primary model, ThinknCheck-1B, is a Gemma3 1B parameter model fine-tuned on LLMAggreFact-Think.
  ★ The ablation model, ThinknCheck-nothink-1B, uses the same Gemma3 1B architecture and data but is trained without the reasoning generation step.
  ★ ThinknCheck-Science-1B is the ThinknCheck-1B model further fine-tuned on a combination of LLMAggreFact-Think, SciFact, and GSMClaims data.

- Baselines: We compare against several models:

  – AlignScore (Zha et al., 2023).
  – MiniCheck-7B (Tang et al., 2024), which is available at https://huggingface.co/bespokelabs/Bespoke-MiniCheck-7B.

- Availability: Our developed models (ThinknCheck-1B, ThinknCheck-nothink-1B, and ThinknCheck-Science-1B) and training

code will be released openly under an Apache 2.0 license. We also note a relevant Hugging Face resource provided in the context of our problem formulation: `URL withheld for blind review.`

## P  AI Writing/Coding Assistance Disclosure

In accordance with the ACL Policy on AI Writing Assistance[8], the authors attest that we used generative AI tools for assistance purely with the language of the paper, including spell checking, grammar fixes, and proof reading. Additionally, we used GPT-4o to fix LaTeX issues, and to generate LaTeX tables from spreadsheets. In all such uses, the outputs were verified by the first author for correctness.

---

[8]https://www.aclweb.org/adminwiki/index.php/
ACL_Policy_on_Publication_Ethics#Guidelines_for_
Generative_Assistance_in_Authorship