Training Compute-Optimal Large Language Models

Jordan Hoffmann[*]   **Sebastian Borgeaud**[*]   **Arthur Mensch**[*]   **Elena Buchatskaya**

Trevor Cai   **Eliza Rutherford**   **Diego de Las Casas**   **Lisa Anne Hendricks**

Johannes Welbl   **Aidan Clark**   **Tom Hennigan**   **Eric Noland**   **Katie Millican**

George van den Driessche   **Bogdan Damoc**   **Aurelia Guy**   **Simon Osindero**

Karen Simonyan   **Erich Elsen**   **Oriol Vinyals**   **Jack W. Rae**   **Laurent Sifre**[*]

[*] Equal contributions

DeepMind
(sborgeaud|amensch|sifre)@deepmind.com

Abstract

We investigate the optimal model size and number of tokens for training a Transformer language model under a given compute budget. We find that current large language models are significantly undertrained, a consequence of the recent focus on scaling language models whilst keeping the amount of training data constant. By training over 400 language models ranging from 70 million to over 16 billion parameters on 5 to 500 billion tokens, we find that for compute-optimal training, the model size and the number of training tokens should be scaled equally: for every doubling of model size the number of training tokens should also be doubled. We test this hypothesis by training a predicted compute-optimal model, *Chinchilla*, that uses the same compute budget as *Gopher* but with 70B parameters and 4× more more data. *Chinchilla* uniformly and significantly outperforms *Gopher* (280B), GPT-3 (175B), Jurassic-1 (178B), and Megatron-Turing NLG (530B) on a large range of downstream evaluation tasks. This also means that *Chinchilla* uses substantially less compute for fine-tuning and inference, greatly facilitating downstream usage. As a highlight, *Chinchilla* reaches a state-of-the-art average accuracy of 67.5% on the MMLU benchmark, greater than a 7% improvement over *Gopher*.

1 Introduction

A series of *Large Language Models* (LLMs) have recently been introduced [6, 30, 38, 48, 52], with the largest dense language models now having over 500 billion parameters. These large autoregressive transformers [53] have demonstrated impressive performance on many tasks using a variety of evaluation protocols: zero-shot generalization, few-shot training, and as a basis for fine-tuning. The compute and energy cost for training large language models is substantial [38, 52] and rises with increasing model size. In practice, the allocated training compute budget is often known in advance: practitioners have access to a certain number of accelerators for a given period of time. Since it

36th Conference on Neural Information Processing Systems (NeurIPS 2022).

Figure 1: **Overlaid predictions.** We overlay the predictions from our three different approaches, along with projections from [23]. We find that all three methods predict that current large models should be substantially smaller and therefore trained much longer than is currently done. In Figure A3, we show the results with the predicted optimal tokens plotted against the optimal number of parameters for fixed FLOP budgets. ***Chinchilla* outperforms *Gopher* and the other large models (see Section 4.2).**

Table 1: **Current LLMs**. We show five of the current largest dense transformer models, their size, and the number of training tokens. Other than LaMDA [52], most models are trained for approximately 300 billion tokens. We introduce *Chinchilla*, a substantially smaller model, trained for much longer than 300B tokens. Table A3 shows our projected optimal relation between model size and tokens.

Model	Size (# Parameters)	Training Tokens
LaMDA [52]	137 Billion	768 Billion
GPT-3 [6]	175 Billion	300 Billion
Jurassic [30]	178 Billion	300 Billion
Gopher [38]	280 Billion	300 Billion
MT-NLG 530B [48]	530 Billion	270 Billion
Chinchilla	70 Billion	1.4 Trillion

is typically only feasible to train these large models once, accurately estimating the best model hyperparameters for a given compute budget is critical [51].

Kaplan et al. [23] showed that there is a power law relationship between the number of parameters in an autoregressive language model (LM) and its performance (measured in evaluation perplexity). One notable conclusion in [23] is that large models should not be trained to their lowest possible loss to be compute optimal; they argue that model size should grow faster than the size of the training set for a given increase of computational budget. As a result, the field has been training larger and larger models while keeping the size of the training set to approximately 300 billion tokens, expecting performance improvements (Table 1). While we find that there is effectively a trade-off between model size and training set size, we estimate that large models should be trained for many more training tokens than recommended by [23]. Specifically, given a $10\times$ increase computational budget we find that model size and the number of training tokens should be scaled in equal proportions.

In this work, we revisit the question: *Given a fixed FLOPs budget,*[1] *how should one trade-off model size and the number of training tokens?* To answer this question, we model the final pre-training loss[2] $L(N, D)$ as a function of the number of model parameters N, and the number of training tokens, D. Since the computational budget C is a deterministic function FLOPs(N, D) of the number of seen training tokens and model parameters, we are interested in minimizing L under the constraint

---

[1]For example, knowing the number of accelerators and a target training duration.

[2]For simplicity, we perform our analysis on the smoothed training loss which is an unbiased estimate of the test loss, as the number of training tokens is less than the number of tokens in the entire corpus.

FLOPs$(N, D) = C$:

$$N_{opt}(C), D_{opt}(C) = \underset{N,D \text{ s.t. FLOPs}(N,D)=C}{\text{argmin}} L(N, D). \tag{1}$$

The functions $N_{opt}(C)$, and $D_{opt}(C)$ describe the optimal allocation of a computational budget C. We empirically estimate these functions based on the losses of over 400 models, ranging from under 70M to over 16B parameters, and trained on 5B to over 400B tokens – with each model configuration trained for several different training horizons. Our approach leads to considerably different results than that of [23]. We highlight our results in Figure 1 and how our approaches differ in Section 2.

Based on our estimated compute-optimal frontier, we predict that for the compute budget used to train *Gopher*, an optimal model should be 4 times smaller, while being training on 4 times more tokens. We verify this by training a more *compute-optimal* 70B model, called *Chinchilla*, on 1.4 trillion tokens. Not only does *Chinchilla* outperform its much larger counterpart, *Gopher*, but its reduced model size reduces inference cost considerably and greatly facilitates downstream uses on smaller hardware. The energy cost of a large language model is amortized through its usage for inference and fine-tuning. The benefits of a more optimally trained smaller model, therefore, extend beyond the immediate benefits of its improved performance.

2 Related Work

Large language models. A variety of large language models have been introduced in the last few years. These include both dense transformer models [6, 30, 48, 38, 52] and mixture-of-expert (MoE) models [11, 12, 60]. The largest dense transformers have passed 500 billion parameters [48, 8]. The drive to train larger and larger models is clear—so far increasing the size of language models has been responsible for improving the state-of-the-art in many language modelling tasks. Nonetheless, large language models face several challenges, including their overwhelming computational requirements (the cost of training and inference increase with model size) [38, 52] and the need for acquiring more high-quality training data. In fact, in this work we find that larger, high quality datasets will play a key role in any further scaling of language models. Concurrent to our work, a 540 billion parameter model trained on 768 billion tokens was released– PaLM [8]. While this model outperforms *Chinchilla*, it uses approximately $5\times$ the compute and is nearly $8\times$ larger, making it more difficult to use.

Modelling the scaling behavior. Understanding the scaling behaviour of language models and their transfer properties has been important in the development of recent large models [23, 18]. Kaplan et al. [23] first showed a predictable relationship between model size and loss over many orders of magnitude. The authors investigate the question of choosing the optimal model size to train for a given compute budget. Similar to us, they address this question by training various models. Our work differs from Kaplan et al. [23] in several important ways. First, the authors use a fixed number of training tokens and learning rate schedule for all models; this prevents them from modelling the impact of these hyperparameters on the loss. In contrast, we find that setting the learning rate schedule to approximately match the number of training tokens results in the best final loss regardless of model size—see Figure A1. For a fixed learning rate cosine schedule to 130B tokens, the intermediate loss estimates (for $D' << 130B$) are therefore overestimates of the loss of a model trained with a schedule length matching D'. Using these intermediate losses results in underestimating the effectiveness of training models on less data than 130B tokens, and eventually contributes to the conclusion that model size should increase faster than training data size as compute budget increases. In contrast, our analysis predicts that both quantities should scale at roughly the same rate. Secondly, we include models with up to 16B parameters, as we observe that there is slight curvature in the FLOP-loss frontier (see Appendix E)—in fact, the majority of the models used in our analysis have more than 500 million parameters, in contrast the majority of runs in [23] are significantly smaller—many being less than 100M parameters. Clark et al. [9] specifically looked in to the scaling properties of Mixture of Expert language models, showing that the scaling with number of experts diminishes as the model size increases—their approach models the loss as a function of two variables: the model size and the number of experts. However, the analysis is done with a fixed number of tokens, potentially underestimating the improvements of branching.

Estimating hyperparameters for large models. The model size and the number of training tokens are not the only two parameters to chose when selecting a language model and a procedure to train

Figure 2: **Training curve envelope.** On the **left** we show all of our different runs. We launched a range of model sizes going from 70M to 10B, each for four different cosine cycle lengths. From these curves, we extracted the envelope of minimal loss per FLOP, and we used these points to estimate the optimal model size (**center**) for a given compute budget and the optimal number of training tokens (**right**). In green, we show projections of optimal model size and training token count based on the number of FLOPs used to train *Gopher* (5.76×10^{23}).

it. Other important factors include learning rate, learning rate schedule, batch size, optimiser, and width-to-depth ratio. In this work, we focus on model size and the number of training steps, and we rely on existing work and provided experimental heuristics to determine the other necessary hyperparameters. Yang et al. [57] investigates how to choose a variety of these parameters for training an autoregressive transformer, including the learning rate and batch size. McCandlish et al. [33] finds only a weak dependence between optimal batch size and model size. Shallue et al. [46], Zhang et al. [59] suggest that using larger batch-sizes than those we use is possible. Levine et al. [28] investigates the optimal depth-to-width ratio for a variety of standard model sizes. We use slightly less deep models than proposed as this translates to better wall-clock performance on our hardware.

Improved model architectures. Recently, various promising alternatives to traditional dense transformers have been proposed. For example, through the use of conditional computation large MoE models like the 1.7 trillion parameter Switch transformer [12], the 1.2 Trillion parameter GLaM model [11], and others [1, 60] are able to provide a large effective model size despite using relatively fewer training and inference FLOPs. However, for very large models the computational benefits of routed models seems to diminish [9]. An orthogonal approach to improving language models is to augment transformers with explicit retrieval mechanisms, as done by [4, 15, 29]. This approach effectively increases the number of data tokens seen during training (by a factor of ~ 10 in [4]). This suggests that the performance of language models may be more dependant on the size of the training data than previously thought.

3 Estimating the optimal parameter/training tokens allocation

We present three different approaches to answer the question driving our research: *Given a fixed FLOPs budget, how should one trade-off model size and the number of training tokens?* In all three cases we start by training a range of models varying both model size and the number of training tokens and use the resulting training curves to fit an empirical estimator of how they should scale. We assume a power-law relationship between compute and model size as done in [9, 23], though future work may want to include potential curvature in this relationship for large model sizes. The resulting predictions are similar for all three methods and suggest that parameter count and number of training tokens should be increased equally with more compute —with proportions reported in Table 2. This is in clear contrast to previous work on this topic and warrants further investigation.

3.1 Approach 1: Fix model sizes and vary number of training tokens

In our first approach we vary the number of training steps for a fixed family of models (ranging from 70M to over 10B parameters), training each model for 4 different number of training sequences. From these runs, we are able to directly extract an estimate of the minimum loss achieved for a given number of training FLOPs. Training details for this approach can be found in Appendix D.

Figure 3: **IsoFLOP curves.** For various model sizes, we choose the number of training tokens such that the final FLOPs is a constant. The cosine cycle length is set to match the target FLOP count. We find a clear valley in loss, meaning that for a given FLOP budget there is an optimal model to train (**left**). Using the location of these valleys, we project optimal model size and number of tokens for larger models (**center** and **right**). In green, we show the estimated number of parameters and tokens for an *optimal* model trained with the compute budget of *Gopher*.

For each parameter count N we train 4 different models: each uses a different horizon (measured in number of training tokens) over which we decay the learning rate by a factor of $10\times$; the range of horizons varies by a factor of $16\times$ for each parameter count. We smooth and linearly interpolate each training loss curve. From this, we obtain a continuous mapping from FLOP count to training loss for each run. We then determine which run achieves the lowest loss for each FLOP count. Using these interpolants, we obtain a mapping from FLOP count C to the most efficient choice of model size N_{opt} and number of training tokens D_{opt} such that FLOPs$(N_{opt}, D_{opt}) = C$.[3] We apply this mapping onto logarithmically spaced values of C and obtain many empirical triplets $(C_i, N_{opt,i}, D_{opt,i})_i$. Finally, we fit power laws to these empirical data, estimating a and b such that $N_{opt} \propto C^a$ and $D_{opt} \propto C^b$. We find that $a = 0.50$ and $b = 0.50$—as summarized in Table 2. We perform a simple experiment for early validating our analysis: given a budget of 10^{21} FLOPs, we compare the performance of training a model with a size recommended by our analysis to training a model with a size suggested by the analysis of [23]—using the model size we predict has a clear advantage (Section D.4).

3.2 Approach 2: IsoFLOP profiles

In our second approach we vary the model size for a fixed set of 9 different training FLOP counts (ranging from 6×10^{18} to 3×10^{21} FLOPs), and consider the final training loss for each point. This differs from the first approach that considers points $(N_i, D_i, L_i)_i$ along the entire training runs; the data points are here scarcer but more representative of the performance of a fully trained model.

For each FLOP budget, we plot the final loss (after smoothing) against the parameter count in Figure 3 (left). In all cases, we ensure that we have trained a diverse enough set of model sizes to see a clear minimum in the loss. We fit a parabola to each IsoFLOPs curve to directly estimate at what model size the minimum loss is achieved (Figure 3 (left)). As with the previous approach, we then fit a power law between FLOPs and loss-optimal model size and number of training tokens, shown in Figure 3 (center, right). Again, we fit exponents of the form $N_{opt} \propto C^a$ and $D_{opt} \propto C^b$ and we find that $a = 0.49$ and $b = 0.51$—as summarized in Table 2.

3.3 Approach 3: Fitting a parametric loss function

Lastly, we model all final losses from experiments in Approach 1 & 2 as a parametric function of model parameter count and the number of seen tokens. Following a classical risk decomposition (see Section D.2), we propose the following functional form

$$\hat{L}(N, D) \triangleq E + \frac{A}{N^{\alpha}} + \frac{B}{D^{\beta}}. \tag{2}$$

The first term captures the loss for an ideal generative process on the data distribution, and should correspond to the entropy of natural text. The second term captures the fact that a perfectly trained

---

[3]Note that all selected points are within the last 15% of training. Thus, when training a model over D tokens, we should pick a cosine cycle length that decays $10\times$ over approximately D tokens—see Appendix B.

Figure 4: **Parametric fit.** We fit a parametric modelling of the loss $\hat{L}(N, D)$ and display contour (**left**) and isoFLOP slices (**right**). For each isoFLOP slice, we include a corresponding dashed line in the left plot. In the left plot, we show the efficient frontier in blue, which is a line in log-log space. Specifically, the curve goes through each iso-loss contour at the point with the fewest FLOPs. We project the optimal model size given the *Gopher* FLOP budget to be 40B parameters.

transformer with N parameters underperforms the ideal generative process. The final term captures the fact that the transformer is not trained to convergence, as we only make a finite number of optimisation steps, on a sample of the dataset distribution.

Model fitting.   To estimate (A, B, E, α, β), we minimize the Huber loss [19] between the predicted and observed log loss using the L-BFGS algorithm [36]:

$$\min_{A,B,E,\alpha,\beta} \quad \sum_{\text{Runs } i} \text{Huber}_\delta \Big(\log \hat{L}(N_i, D_i) - \log L_i \Big) \tag{3}$$

We account for possible local minima by selecting the best fit from a grid of initialisations. The Huber loss ($\delta = 10^{-3}$) is robust to outliers, which we find important for good predictive performance over held-out data points. Section D.2 details the fitting procedure and the loss decomposition.

Efficient frontier.   We approximate the functions N_{opt} and D_{opt} by minimizing the parametric loss $\hat{L}$ under the constraint $\text{FLOPs}(N, D) \approx 6ND$ [23]. The resulting N_{opt} and D_{opt} balance the two terms in Equation (3) that depend on model size and data. By construction, they have a power-law form. We show contours of the fitted function $\hat{L}$ in Figure 4 (left), and the closed-form efficient computational frontier in blue. From this approach, we find that $a = 0.46$ and $b = 0.54$—as summarized in Table 2.

3.4   Optimal model scaling

We find that the three approaches, despite using different fitting methodologies and different trained models, yield comparable predictions for the optimal scaling in parameters and tokens with FLOPs (shown in Table 2). All three approaches suggest that as compute budget increases, model size and the amount of training data should be increased in approximately equal proportions. The first and second approaches yield very similar predictions for optimal model sizes, as shown in Figure 1 and Figure A3. The third approach predicts even smaller models being optimal at larger compute budgets. We note that the observed points (L, N, D) for low training FLOPs ($C \leq 1e21$) have larger residuals $\|L - \hat{L}(N, D)\|_2^2$ than points with higher computational budgets. The fitted model places increased weight on the points with more FLOPs—automatically considering the low-computational budget points as outliers due to the Huber loss. As a consequence of the empirically observed negative curvature in the frontier $C \to N_{opt}$ (see Appendix E), this results in predicting a lower N_{opt} than the two other approaches.

Table 2: **Estimated parameter and data scaling with increased training compute.** The listed values are the exponents, a and b, on the relationship $N_{opt} \propto C^a$ and $D_{opt} \propto C^b$. Our analysis suggests a near equal scaling in parameters and data with increasing compute which is in clear contrast to previous work on the scaling of large models. The 10^{th} and 90^{th} percentiles are estimated via bootstrapping data (80% of the dataset is sampled 100 times) and are shown in parenthesis.

Approach	Coeff. a where $N_{opt} \propto C^a$	Coeff. b where $D_{opt} \propto C^b$
1. Minimum over training curves	0.50 (0.488, 0.502)	0.50 (0.501, 0.512)
2. IsoFLOP profiles	0.49 (0.462, 0.534)	0.51 (0.483, 0.529)
3. Parametric modelling of the loss	0.46 (0.454, 0.455)	0.54 (0.542, 0.543)
Kaplan *et al.* (2020) [23]	0.73	0.27

In Table A3 we show the estimated number of FLOPs and tokens that would ensure that a model of a given size lies on the compute-optimal frontier. Our findings suggests that the current generation of large language models are considerably over-sized, given their respective compute budgets, as shown in Figure 1. Furthermore, the amount of training data that is projected to be needed is far beyond what is currently used to train large models, and underscores the importance of dataset collection in addition to engineering improvements that allow for model scale. While there is significant uncertainty extrapolating out many orders of magnitude, our analysis clearly suggests that given the training compute budget for many current LLMs, smaller models should have been trained on more tokens to achieve the most performant model. In Appendix C, we reproduce the IsoFLOP analysis on two additional datasets: C4 [40] and GitHub code [38]. In both cases we reach the similar conclusion that model size and number of training tokens should be scaled in equal proportions.

4 *Chinchilla*

Based on our analysis in Section 3, the optimal model size for the *Gopher* compute budget is somewhere between 40 and 70 billion parameters. We test this hypothesis by training a model on the larger end of this range—70B parameters—for 1.4T tokens, due to both dataset and computational efficiency considerations. In this section we compare this model, which we call *Chinchilla*, to *Gopher* and other LLMs. Both *Chinchilla* and *Gopher* have been trained for the same number of FLOPs but differ in the size of the model and the number of training tokens. While pre-training a large language model has a considerable compute cost, downstream fine-tuning and inference also make up substantial compute usage [38]. Due to being $4\times$ smaller than *Gopher*, both the memory footprint and inference cost of *Chinchilla* are also smaller.

4.1 Model and training details

The full set of hyperparameters used to train *Chinchilla* are given in Table 3. *Chinchilla* uses the same model architecture and training setup as *Gopher* with the exception of the differences listed below.

- We train *Chinchilla* on *MassiveText* (the same dataset as *Gopher*) but use a slightly different subset distribution (Table A1) to account for the increased number of training tokens.

- We use AdamW [32] for *Chinchilla* rather than Adam [24] as this improves the language modelling loss and the downstream task performance after finetuning.[4]

- We train *Chinchilla* with a slightly modified SentencePiece [25] tokenizer that does not apply NFKC normalisation. The vocabulary is very similar– 94.15% of tokens are the same as those used for training *Gopher*. We find that this particularly helps with the representation of mathematics and chemistry, for example.

- Whilst the forward and backward pass are computed in `bfloat16`, we store a `float32` copy of the weights in the distributed optimiser state [41]. See *Lessons Learned* from [38] for additional details.

---

[4]A model trained with AdamW only passes the training performance of a model trained with Adam around 80% of the way through the cosine cycle, though the ending performance is notably better– see Figure A7

In Appendix G we show the impact of the various optimiser related changes between *Chinchilla* and *Gopher*. All models in this analysis have been trained on TPUv3/TPUv4 [22] with JAX [5] and Haiku [17]. We include a *Chinchilla* model card [35] in Table A13.

4.2 Results

We perform an extensive evaluation of *Chinchilla*, comparing against various large language models. We evaluate on a large subset of the tasks presented in [38], shown in Table A6. As the focus of this work is on optimal model scaling, we included a large representative subset, and introduce a few new evaluations to allow for better comparison to other existing large models. The evaluation details for all tasks are the same as described in [38].

Language modelling. *Chinchilla* significantly outperforms *Gopher* on all evaluation subsets of The Pile [13], as shown in Figure A8. Compared to Jurassic-1 (178B) [30], *Chinchilla* is more performant on all but two subsets– `dm_mathematics` and `ubuntu_irc`– see Table A7 for a raw bits-per-byte comparison. On Wikitext103 [34], *Chinchilla* reaches 7.16 perplexity compared to 7.75 for *Gopher*.

MMLU. The Massive Multitask Language Understanding (MMLU) benchmark [16] consists of a range of exam-like questions on academic subjects. In Table A8, we report *Chinchilla*'s average 5-shot performance on MMLU (the full breakdown of results is shown in Table A9). On this benchmark, *Chinchilla* significantly outperforms *Gopher* despite being much smaller, with an average accuracy of 67.6% (improving upon *Gopher* by 7.6%). Remarkably, *Chinchilla* even outperforms the expert forecast for June 2023 of 63.4% accuracy (see Table A8) [50]. Furthermore, *Chinchilla* achieves greater than 90% accuracy on 4 different individual tasks– `high_school_gov_and_politics`, `international_law`, `sociology`, and `us_foreign_policy`. To our knowledge, no other model has achieved greater than 90% accuracy on a subset. In Figure A9, we show a comparison to *Gopher* broken down by task.

Reading comprehension. On the final word prediction dataset LAMBADA [37], *Chinchilla* achieves 77.4% accuracy, compared to 74.5% accuracy from *Gopher* and 76.6% from MT-NLG 530B (see Table 4). On RACE-h and RACE-m [27], *Chinchilla* greatly outperforms *Gopher*, improving accuracy by more than 10% in both cases—see Table 4.

BIG-bench. We analysed *Chinchilla* on the same set of BIG-bench tasks [49] reported in [38]. Similar to what we observed in MMLU, *Chinchilla* outperforms *Gopher* on the vast majority of tasks (see Figure A10). We find that *Chinchilla* improves the average performance by 10.7%, reaching an accuracy of 65.1% versus 54.4% for *Gopher*. Full accuracy results can be found in Table A10.

Common sense. We evaluate *Chinchilla* on various common sense benchmarks: PIQA [3], SIQA [45], Winogrande [44], HellaSwag [58], and BoolQ [10]. We find that *Chinchilla* outperforms both *Gopher* and GPT-3 on all tasks and outperforms MT-NLG 530B on all but one task—see Table 5. On TruthfulQA [31], *Chinchilla* reaches 43.6%, 58.5%, and 66.7% accuracy with 0-shot, 5-shot, and 10-shot respectively. In comparison, *Gopher* achieved only 29.5% 0-shot and 43.7% 10-shot accuracy. In stark contrast with the findings of [31], the large improvements (14.1% in 0-shot accuracy) achieved by Chinchilla suggest that better modelling of the pre-training data alone can lead to substantial improvements on this benchmark.

Closed-book question answering. Results on closed-book question answering benchmarks are reported in Table A11. On the Natural Questions dataset [26], *Chinchilla* achieves new closed-book SOTA accuracies: 31.5% 5-shot and 35.5% 64-shot, compared to 21% and 28% respectively, for *Gopher*. On TriviaQA [21] we show results for both the filtered (previously used in retrieval and open-

Table 3: *Chinchilla* **architecture details.** We list the number of layers, the key/value size, the bottleneck activation size d_{model}, the maximum learning rate, and the training batch size (# tokens). The feed-forward size is always set to $4 \times d_{model}$. Note that we double the batch size midway through training for both *Chinchilla* and *Gopher*.

Model	Layers	Number Heads	Key/Value Size	d_{model}	Max LR	Batch Size
Gopher 280B	80	128	128	16,384	4×10^{-5}	3M → 6M
Chinchilla 70B	80	64	128	8,192	1×10^{-4}	1.5M → 3M

Table 4: **Reading comprehension.** On RACE-h and RACE-m [27], *Chinchilla* considerably improves performance over *Gopher*. Note that GPT-3 and MT-NLG 530B use a different prompt format than we do on RACE-h/m, so results are not comparable to *Gopher* and *Chinchilla*. On LAMBADA [37], *Chinchilla* outperforms both *Gopher* and MT-NLG 530B.

	Chinchilla	*Gopher*	GPT-3	MT-NLG 530B
LAMBADA Zero-Shot	**77.4**	74.5	76.2	76.6
RACE-m Few-Shot	**86.8**	75.1	58.1	-
RACE-h Few-Shot	**82.3**	71.6	46.8	47.9

Table 5: **Zero-shot comparison on Common Sense benchmarks.** We show a comparison between *Chinchilla*, *Gopher*, and MT-NLG 530B on various Common Sense benchmarks. We see that *Chinchilla* matches or outperforms *Gopher* and GPT-3 on all tasks. On all but one *Chinchilla* outperforms the much larger MT-NLG 530B model.

	Chinchilla	*Gopher*	GPT-3	MT-NLG 530B	Supervised SOTA
HellaSWAG	**80.8%**	79.2%	78.9%	80.2%	93.9%
PIQA	81.8%	81.8%	81.0%	**82.0%**	90.1%
Winogrande	**74.9%**	70.1%	70.2%	73.0%	91.3%
SIQA	**51.3%**	50.6%	-	-	83.2%
BoolQ	**83.7**%	79.3%	60.5%	78.2%	91.4%

book work) and unfiltered set (previously used in large language model evaluations). In both cases, *Chinchilla* substantially out performs *Gopher*. On the filtered version, Chinchilla lags behind the open book SOTA [20] by 7.9%. On the unfiltered set, *Chinchilla* outperforms GPT-3 (see Table A11).

5   Discussion & Conclusion

The trend so far in large language model training has been to increase the model size, often without increasing the number of training tokens. The largest dense transformer, MT-NLG 530B, is now over $3\times$ larger than GPT-3's 170 billion parameters from just two years ago. However, this model, as well as the majority of existing large models, have all been trained for a comparable number of tokens—around 300 billion. While the desire to train these mega-models has led to substantial engineering innovation, we hypothesize that the race to train larger and larger models is resulting in models that are substantially underperforming compared to what could be achieved with the same compute budget.

We propose three predictive approaches towards optimally setting model size and training duration, based on the outcome of over 400 training runs. All three approaches predict that *Gopher* is substantially over-sized and estimate that for the same compute budget a smaller model trained on more data will perform better. We directly test this hypothesis by training *Chinchilla*, a 70B parameter model, and show that it outperforms *Gopher* and even larger models on nearly every measured evaluation task.

Whilst our method allows us to make predictions on how to scale large models when given additional compute, there are several limitations. Due to the cost of training large models, we only have two comparable training runs at large scale (*Chinchilla* and *Gopher*), and we do not have additional tests at intermediate scales. Furthermore, we assume that the efficient computational frontier can be described by a power-law relationship between the compute budget, model size, and number of training tokens. However, we observe some concavity in $\log(N_{opt})$ at high compute budgets (see Appendix E). This suggests that we may still be overestimating the optimal size of large models. Finally, the training runs for our analysis have all been trained on less than an epoch of data; future work may consider the multiple epoch regime. Despite these limitations, the comparison of *Chinchilla* to *Gopher* validates our performance predictions, that have thus enabled training a better (and more lightweight) model at the same compute budget.

Though there has been significant recent work allowing larger and larger models to be trained, our analysis suggests an increased focus on dataset scaling is needed. Speculatively, we expect that scaling to larger and larger datasets is only beneficial when the data is high-quality. This calls for responsibly collecting larger datasets with a high focus on dataset quality. Larger datasets will require extra care to ensure train-test set overlap is properly accounted for, both in the language modelling loss but also with downstream tasks. Finally, training for trillions of tokens introduces many ethical and privacy concerns. Large datasets scraped from the web will contain toxic language, biases, and private information. With even larger datasets being used, the quantity (if not the frequency) of such information increases, which makes dataset introspection all the more important. *Chinchilla* does suffer from bias and toxicity but interestingly it seems less affected than *Gopher* (see Appendix I).. Better understanding how performance of large language models and toxicity interact is an important future research question.

While we have applied our methodology towards the training of auto-regressive language models, we expect that there is a similar trade-off between model size and the amount of data in other modalities. As training large models is very expensive, choosing the optimal model size and training steps beforehand is essential. The methods we propose are easy to reproduce in new settings.

Acknowledgments and Disclosure of Funding

We'd like to thank Jean-baptiste Alayrac, Kareem Ayoub, Chris Dyer, Nando de Freitas, Demis Hassabis, Geoffrey Irving, Koray Kavukcuoglu, Nate Kushman and Angeliki Lazaridou for useful comments on the manuscript. We'd like to thank Andy Brock, Irina Higgins, Michela Paganini, Francis Song, and other colleagues at DeepMind for helpful discussions. We are also very grateful to the JAX and XLA team for their support and assistance.

References

[1] M. Artetxe, S. Bhosale, N. Goyal, T. Mihaylov, M. Ott, S. Shleifer, X. V. Lin, J. Du, S. Iyer, R. Pasunuru, G. Anantharaman, X. Li, S. Chen, H. Akin, M. Baines, L. Martin, X. Zhou, P. S. Koura, B. O'Horo, J. Wang, L. Zettlemoyer, M. Diab, Z. Kozareva, and V. Stoyanov. Efficient Large Scale Language Modeling with Mixtures of Experts. *arXiv:2112.10684*, 2021.

[2] E. M. Bender, T. Gebru, A. McMillan-Major, and S. Shmitchell. On the dangers of stochastic parrots: Can language models be too big? In *Proceedings of the ACM Conference on Fairness, Accountability, and Transparency*, 2021.

[3] Y. Bisk, R. Zellers, J. Gao, Y. Choi, et al. PIQA: Reasoning about physical commonsense in natural language. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, 2020.

[4] S. Borgeaud, A. Mensch, J. Hoffmann, T. Cai, E. Rutherford, K. Millican, G. van den Driessche, J.-B. Lespiau, B. Damoc, A. Clark, D. de Las Casas, A. Guy, J. Menick, R. Ring, T. Hennigan, S. Huang, L. Maggiore, C. Jones, A. Cassirer, A. Brock, M. Paganini, G. Irving, O. Vinyals, S. Osindero, K. Simonyan, J. W. Rae, E. Elsen, and L. Sifre. Improving language models by retrieving from trillions of tokens. In *Proceedings of the International Conference on Machine Learning*, 2021.

[5] J. Bradbury, R. Frostig, P. Hawkins, M. J. Johnson, C. Leary, D. Maclaurin, G. Necula, A. Paszke, J. VanderPlas, S. Wanderman-Milne, and Q. Zhang. JAX: composable transformations of Python+NumPy programs. 2018. URL http://github.com/google/jax.

[6] T. Brown, B. Mann, N. Ryder, M. Subbiah, J. D. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell, S. Agarwal, A. Herbert-Voss, G. Krueger, T. Henighan, R. Child, A. Ramesh, D. Ziegler, J. Wu, C. Winter, C. Hesse, M. Chen, E. Sigler, M. Litwin, S. Gray, B. Chess, J. Clark, C. Berner, S. McCandlish, A. Radford, I. Sutskever, and D. Amodei. Language models are few-shot learners. In *Advances in Neural Information Processing Systems*, 2020.

[7] S. Bubeck. Convex Optimization: Algorithms and Complexity. *Foundations and Trends in Machine Learning*, 8(3-4):231–357, 2015.

[8] A. Chowdhery, S. Narang, J. Devlin, M. Bosma, G. Mishra, A. Roberts, P. Barham, H. W. Chung, C. Sutton, S. Gehrmann, et al. PaLM: Scaling language modeling with pathways. *arXiv:2204.02311*, 2022.

[9] A. Clark, D. d. l. Casas, A. Guy, A. Mensch, M. Paganini, J. Hoffmann, B. Damoc, B. Hechtman, T. Cai, S. Borgeaud, G. v. d. Driessche, E. Rutherford, T. Hennigan, M. Johnson, K. Millican, A. Cassirer, C. Jones, E. Buchatskaya, D. Budden, L. Sifre, S. Osindero, O. Vinyals, J. Rae, E. Elsen, K. Kavukcuoglu, and K. Simonyan. Unified scaling laws for routed language models. In *Proceedings of the International Conference on Machine Learning*, 2022.

[10] C. Clark, K. Lee, M.-W. Chang, T. Kwiatkowski, M. Collins, and K. Toutanova. BoolQ: Exploring the surprising difficulty of natural yes/no questions. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, pages 2924–2936, 2019.

[11] N. Du, Y. Huang, A. M. Dai, S. Tong, D. Lepikhin, Y. Xu, M. Krikun, Y. Zhou, A. W. Yu, O. Firat, B. Zoph, L. Fedus, M. Bosma, Z. Zhou, T. Wang, Y. E. Wang, K. Webster, M. Pellat, K. Robinson, K. Meier-Hellstern, T. Duke, L. Dixon, K. Zhang, Q. V. Le, Y. Wu, Z. Chen, and C. Cui. GLaM: Efficient scaling of language models with mixture-of-experts. *arXiv:2112.06905*, 2021.

[12] W. Fedus, B. Zoph, and N. Shazeer. Switch transformers: Scaling to trillion parameter models with simple and efficient sparsity. *arXiv:2101.03961*, 2021.

[13] L. Gao, S. Biderman, S. Black, L. Golding, T. Hoppe, C. Foster, J. Phang, H. He, A. Thite, N. Nabeshima, S. Presser, and C. Leahy. The Pile: An 800GB dataset of diverse text for language modeling. *arXiv:2101.00027*, 2020.

[14] S. Gehman, S. Gururangan, M. Sap, Y. Choi, and N. A. Smith. RealToxicityPrompts: Evaluating neural toxic degeneration in language models. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, 2020.

[15] K. Guu, K. Lee, Z. Tung, P. Pasupat, and M.-W. Chang. REALM: retrieval-augmented language model pre-training. In *Proceedings of the International Conference on Machine Learning*, pages 3929–3938, July 2020.

[16] D. Hendrycks, C. Burns, S. Basart, A. Zou, M. Mazeika, D. Song, and J. Steinhardt. Measuring massive multitask language understanding. *arXiv:2009.03300*, 2020.

[17] T. Hennigan, T. Cai, T. Norman, and I. Babuschkin. Haiku: Sonnet for JAX. 2020. URL http://github.com/deepmind/dm-haiku.

[18] D. Hernandez, J. Kaplan, T. Henighan, and S. McCandlish. Scaling laws for transfer. *arXiv:2102.01293*, 2021.

[19] P. J. Huber. Robust Estimation of a Location Parameter. *The Annals of Mathematical Statistics*, 35(1):73–101, 1964.

[20] G. Izacard and E. Grave. Distilling knowledge from reader to retriever for question answering. In *International Conference on Learning Representations*, 2020.

[21] M. Joshi, E. Choi, D. Weld, and L. Zettlemoyer. TriviaQA: A Large Scale Distantly Supervised Challenge Dataset for Reading Comprehension. *arXiv:1705.03551*, 2017.

[22] N. P. Jouppi, C. Young, N. Patil, D. Patterson, G. Agrawal, R. Bajwa, S. Bates, S. Bhatia, N. Boden, A. Borchers, R. Boyle, P.-l. Cantin, C. Chao, C. Clark, J. Coriell, M. Daley, M. Dau, J. Dean, B. Gelb, T. V. Ghaemmaghami, R. Gottipati, W. Gulland, R. Hagmann, C. R. Ho, D. Hogberg, J. Hu, R. Hundt, D. Hurt, J. Ibarz, A. Jaffey, A. Jaworski, A. Kaplan, H. Khaitan, D. Killebrew, A. Koch, N. Kumar, S. Lacy, J. Laudon, J. Law, D. Le, C. Leary, Z. Liu, K. Lucke, A. Lundin, G. MacKean, A. Maggiore, M. Mahony, K. Miller, R. Nagarajan, R. Narayanaswami, R. Ni, K. Nix, T. Norrie, M. Omernick, N. Penukonda, A. Phelps, J. Ross, M. Ross, A. Salek, E. Samadiani, C. Severn, G. Sizikov, M. Snelham, J. Souter, D. Steinberg, A. Swing, M. Tan, G. Thorson, B. Tian, H. Toma, E. Tuttle, V. Vasudevan, R. Walter, W. Wang, E. Wilcox, and D. H. Yoon. In-datacenter performance analysis of a tensor processing unit. In *Proceedings of the Annual International Symposium on Computer Architecture*, page 1–12, 2017.

[23] J. Kaplan, S. McCandlish, T. Henighan, T. B. Brown, B. Chess, R. Child, S. Gray, A. Radford, J. Wu, and D. Amodei. Scaling laws for neural language models. *arXiv:2001.08361*, 2020.

[24] D. P. Kingma and J. Ba. Adam: A method for stochastic optimization. *arXiv:1412.6980*, 2014.

[25] T. Kudo and J. Richardson. SentencePiece: A simple and language independent subword tokenizer and detokenizer for neural text processing. *arXiv:1808.06226*, 2018.

[26] T. Kwiatkowski, J. Palomaki, O. Redfield, M. Collins, A. Parikh, C. Alberti, D. Epstein, I. Polosukhin, M. Kelcey, J. Devlin, K. Lee, K. N. Toutanova, L. Jones, M.-W. Chang, A. Dai, J. Uszkoreit, Q. Le, and S. Petrov. Natural questions: a benchmark for question answering research. *Transactions of the Association of Computational Linguistics*, 2019.

[27] G. Lai, Q. Xie, H. Liu, Y. Yang, and E. Hovy. RACE: Large-scale ReAding comprehension dataset from examinations. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, 2017.

[28] Y. Levine, N. Wies, O. Sharir, H. Bata, and A. Shashua. The depth-to-width interplay in self-attention. *arXiv:2006.12467*, 2020.

[29] P. Lewis, E. Perez, A. Piktus, F. Petroni, V. Karpukhin, N. Goyal, H. Küttler, M. Lewis, W.-t. Yih, T. Rocktäschel, S. Riedel, and D. Kiela. Retrieval-augmented generation for knowledge-intensive nlp tasks. In *Advances in Neural Information Processing Systems*, 2020.

[30] O. Lieber, O. Sharir, B. Lenz, and Y. Shoham. Jurassic-1: Technical details and evaluation. *White Paper. AI21 Labs*, 2021.

[31] S. Lin, J. Hilton, and O. Evans. TruthfulQA: Measuring how models mimic human falsehoods. *arXiv:2109.07958*, 2021.

[32] I. Loshchilov and F. Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2019.

[33] S. McCandlish, J. Kaplan, D. Amodei, and O. D. Team. An empirical model of large-batch training. *arXiv:1812.06162*, 2018.

[34] S. Merity, C. Xiong, J. Bradbury, and R. Socher. Pointer sentinel mixture models. In *International Conference on Learning Representations*, 2017.

[35] M. Mitchell, S. Wu, A. Zaldivar, P. Barnes, L. Vasserman, B. Hutchinson, E. Spitzer, I. D. Raji, and T. Gebru. Model cards for model reporting. In *Proceedings of the Conference on Fairness, Accountability, and Transparency*, 2019.

[36] J. Nocedal. Updating Quasi-Newton Matrices with Limited Storage. *Mathematics of Computation*, 35(151):773–782, 1980.

[37] D. Paperno, G. Kruszewski, A. Lazaridou, Q. N. Pham, R. Bernardi, S. Pezzelle, M. Baroni, G. Boleda, and R. Fernández. The LAMBADA dataset: Word prediction requiring a broad discourse context. *arXiv:1606.06031*, 2016.

[38] J. Rae, S. Borgeaud, T. Cai, K. Millican, J. Hoffmann, F. Song, J. Aslanides, S. Henderson, R. Ring, S. Young, E. Rutherford, T. Hennigan, J. Menick, A. Cassirer, R. Powell, G. van den Driessche, L. A. Hendricks, M. Rauh, P.-S. Huang, A. Glaese, J. Welbl, S. Dathathri, S. Huang, J. Uesato, J. Mellor, I. Higgins, A. Creswell, N. McAleese, A. Wu, E. Elsen, S. Jayakumar, E. Buchatskaya, D. Budden, E. Sutherland, K. Simonyan, M. Paganini, L. Sifre, L. Martens, X. L. Li, A. Kuncoro, A. Nematzadeh, E. Gribovskaya, D. Donato, A. Lazaridou, A. Mensch, J.-B. Lespiau, M. Tsimpoukelli, N. Grigorev, D. Fritz, T. Sottiaux, M. Pajarskas, T. Pohlen, Z. Gong, D. Toyama, C. de Masson d'Autume, Y. Li, T. Terzi, I. Babuschkin, A. Clark, D. de Las Casas, A. Guy, J. Bradbury, M. Johnson, L. Weidinger, I. Gabriel, W. Isaac, E. Lockhart, S. Osindero, L. Rimell, C. Dyer, O. Vinyals, K. Ayoub, J. Stanway, L. Bennett, D. Hassabis, K. Kavukcuoglu, and G. Irving. Scaling language models: Methods, analysis & insights from training Gopher. *arXiv:2112.11446*, 2021.

[39] J. W. Rae, A. Potapenko, S. M. Jayakumar, T. P. Lillicrap, K. Choromanski, V. Likhosherstov, D. Dohan, X. Song, A. Gane, T. Sarlos, et al. Compressive transformers for long-range sequence modelling. *Advances in Neural Information Processing Systems*, 2020.

[40] C. Raffel, N. Shazeer, A. Roberts, K. Lee, S. Narang, M. Matena, Y. Zhou, W. Li, and P. J. Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of Machine Learning Research*, 21(140):1–67, 2020.

[41] S. Rajbhandari, J. Rasley, O. Ruwase, and Y. He. Zero: Memory optimizations toward training trillion parameter models. In *International Conference for High Performance Computing, Networking, Storage and Analysis*, 2020.

[42] H. Robbins and S. Monro. A Stochastic Approximation Method. *The Annals of Mathematical Statistics*, 22(3):400–407, Sept. 1951.

[43] R. Rudinger, J. Naradowsky, B. Leonard, and B. Van Durme. Gender bias in coreference resolution. In *Proceedings of the Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, 2018.

[44] K. Sakaguchi, R. Le Bras, C. Bhagavatula, and Y. Choi. Winogrande: An adversarial winograd schema challenge at scale. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2020.

[45] M. Sap, H. Rashkin, D. Chen, R. LeBras, and Y. Choi. SocialIQA: Commonsense reasoning about social interactions. *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, 2019.

[46] C. J. Shallue, J. Lee, J. Antognini, J. Sohl-Dickstein, R. Frostig, and G. E. Dahl. Measuring the effects of data parallelism on neural network training. *arXiv:1811.03600*, 2018.

[47] J. W. Siegel and J. Xu. Approximation rates for neural networks with general activation functions. *Neural Networks*, 128:313–321, 2020.

[48] S. Smith, M. Patwary, B. Norick, P. LeGresley, S. Rajbhandari, J. Casper, Z. Liu, S. Prabhumoye, G. Zerveas, V. Korthikanti, E. Zhang, R. Child, R. Y. Aminabadi, J. Bernauer, X. Song, M. Shoeybi, Y. He, M. Houston, S. Tiwary, and B. Catanzaro. Using Deepspeed and Megatron to Train Megatron-turing NLG 530b, A Large-Scale Generative Language Model. *arXiv:2201.11990*, 2022.

[49] A. Srivastava et al. Beyond the Imitation Game: Quantifying and extrapolating the capabilities of language models. *arXiv:2206.04615*, 2022.

[50] J. Steinhardt. Updates and lessons from AI forecasting, 2021. URL https://bounded-regret.ghost.io/ai-forecasting/.

[51] Y. Tay, M. Dehghani, J. Rao, W. Fedus, S. Abnar, H. W. Chung, S. Narang, D. Yogatama, A. Vaswani, and D. Metzler. Scale efficiently: Insights from pre-training and fine-tuning transformers. *arXiv:2109.10686*, 2021.

[52] R. Thoppilan, D. D. Freitas, J. Hall, N. Shazeer, A. Kulshreshtha, H.-T. Cheng, A. Jin, T. Bos, L. Baker, Y. Du, Y. Li, H. Lee, H. S. Zheng, A. Ghafouri, M. Menegali, Y. Huang, M. Krikun, D. Lepikhin, J. Qin, D. Chen, Y. Xu, Z. Chen, A. Roberts, M. Bosma, Y. Zhou, C.-C. Chang, I. Krivokon, W. Rusch, M. Pickett, K. Meier-Hellstern, M. R. Morris, T. Doshi, R. D. Santos, T. Duke, J. Soraker, B. Zevenbergen, V. Prabhakaran, M. Diaz, B. Hutchinson, K. Olson, A. Molina, E. Hoffman-John, J. Lee, L. Aroyo, R. Rajakumar, A. Butryna, M. Lamm, V. Kuzmina, J. Fenton, A. Cohen, R. Bernstein, R. Kurzweil, B. Aguera-Arcas, C. Cui, M. Croak, E. Chi, and Q. Le. LaMDA: Language models for dialog applications. *arXiv:2201.08239*, 2022.

[53] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, 2017.

[54] L. Weidinger, J. Mellor, M. Rauh, C. Griffin, J. Uesato, P.-S. Huang, M. Cheng, M. Glaese, B. Balle, A. Kasirzadeh, Z. Kenton, S. Brown, W. Hawkins, T. Stepleton, C. Biles, A. Birhane, J. Haas, L. Rimell, L. A. Hendricks, W. Isaac, S. Legassick, G. Irving, and I. Gabriel. Ethical and social risks of harm from language models. *arXiv:arXiv:2112.04359*, 2021.

[55] J. Welbl, A. Glaese, J. Uesato, S. Dathathri, J. Mellor, L. A. Hendricks, K. Anderson, P. Kohli, B. Coppin, and P.-S. Huang. Challenges in detoxifying language models. In *Findings of the Association for Computational Linguistics: EMNLP*, 2021.

[56] A. Xu, E. Pathak, E. Wallace, S. Gururangan, M. Sap, and D. Klein. Detoxifying language models risks marginalizing minority voices. In *Proceedings of the Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, 2021.

[57] G. Yang, E. J. Hu, I. Babuschkin, S. Sidor, X. Liu, D. Farhi, N. Ryder, J. Pachocki, W. Chen, and J. Gao. Tuning large neural networks via zero-shot hyperparameter transfer. In *Advances in Neural Information Processing Systems*, 2021.

[58] R. Zellers, A. Holtzman, Y. Bisk, A. Farhadi, and Y. Choi. HellaSwag: Can a machine really finish your sentence? In *Proceedings of the Annual Meeting of the Association for Computational Linguistics*, 2019.

[59] G. Zhang, L. Li, Z. Nado, J. Martens, S. Sachdeva, G. Dahl, C. Shallue, and R. B. Grosse. Which algorithmic choices matter at which batch sizes? insights from a noisy quadratic model. In *Advances in Neural Information Processing Systems*, 2019.

[60] B. Zoph, I. Bello, S. Kumar, N. Du, Y. Huang, J. Dean, N. Shazeer, and W. Fedus. Designing effective sparse expert models. *arXiv:2202.08906*, 2022.

Appendix

A   Training dataset

In Table A1 we show the training dataset makeup used for *Chinchilla* and all scaling runs. Note that both the *MassiveWeb* and Wikipedia subsets are both used for more than one epoch.

	Disk Size	Documents	Sampling proportion	Epochs in 1.4T tokens
MassiveWeb	1.9 TB	604M	45% (48%)	1.24
Books	2.1 TB	4M	30% (27%)	0.75
C4	0.75 TB	361M	10% (10%)	0.77
News	2.7 TB	1.1B	10% (10%)	0.21
GitHub	3.1 TB	142M	4% (3%)	0.13
Wikipedia	0.001 TB	6M	1% (2%)	3.40

Table A1: *MassiveText* **data makeup.** For each subset of *MassiveText*, we list its total disk size, the number of documents and the sampling proportion used during training—we use a slightly different distribution than in Rae et al. [38] (shown in parenthesis). In the rightmost column show the number of epochs that are used in 1.4 trillion tokens.

B   Optimal cosine cycle length

One key assumption is made on the cosine cycle length and the corresponding learning rate drop (we use a $10\times$ learning rate decay in line with Rae et al. [38]).[5] We find that setting the cosine cycle length too much longer than the target number of training steps results in sub-optimally trained models, as shown in Figure A1. As a result, we assume that an optimally trained model will have the cosine cycle length correctly calibrated to the maximum number of steps, given the FLOP budget; we follow this rule in our main analysis.

C   Consistency of scaling results across datasets

We show scaling results from an IsoFLOP (Approach 2) analysis after training on two different datasets: C4 [**?**] and GitHub code (we show results with data from Rae et al. [38]), results are shown in Table A2. For both set of experiments using subsets of *MassiveText*, we use the same tokenizer as the *MassiveText* experiments.

We find that the scaling behaviour on these datasets is very similar to what we found on *MassiveText*, as shown in Figure A2 and Table A2. This suggests that our results are independent of the dataset as long as one does not train for more than one epoch.

Nonetheless, data quality may vary widely, especially as the number of training tokens increases. Further work understanding this relationship better, and potentially the repeated use of high-quality data is required.

D   Details on the scaling analyses

D.1   Approach 1: Fixing model sizes and varying training sequences

We use a maximum learning rate of 2×10^{-4} for the smallest models and 1.25×10^{-4} for the largest models. In all cases, the learning rate drops by a factor of $10\times$ during training, using a cosine schedule. We make the assumption that the cosine cycle length should be approximately matched to the number of training steps. We find that when the cosine cycle overshoots the number of training

---

[5]We find the difference between decaying by $10\times$ and decaying to 0.0 (over the same number of steps) to be small, though decaying by a factor of $10\times$ to be slightly more performant. Decaying by less ($5\times$) is clearly worse.

Figure A1: **Grid over cosine cycle length.** We show 6 curves with the cosine cycle length set to 1, 1.1, 1.25, 1.5, 2, and 5× longer than the target number of training steps. When the cosine cycle length is too long, and the learning rate does not drop appropriately, then performance is impaired. We find that overestimating the number of training steps beyond 25% leads to clear drops in performance. We show results where we have set the number of training steps to two different values (top and bottom).

Figure A2: **C4 and GitHub IsoFLOP curves.** Using the C4 dataset [**?**] and a GitHub dataset [38], we generate 4 IsoFLOP profiles and show the parameter and token count scaling, as in Figure 3. Scaling coefficients are shown in Table A2.

steps by more than 25%, performance is noticeably degraded—see Figure A1.[6] We use Gaussian smoothing with a window length of 10 steps to smooth the training curve.

We trained 5 different 1.1 billion parameter models on random subsets of the data to look at the variance in final performance. We found that the average loss achieved was 2.488 with a standard deviation amongst the 5 runs of 0.00257. Given how small the differences are, we are confident than any given run is very indicative of a model of that size.

---

[6]This further emphasises the point of not only determining model size, but also training length before training begins.

Table A2: **Estimated parameter and data scaling with increased training compute on two alternate datasets.** The listed values are the exponents, a and b, on the relationship $N_{opt} \propto C^a$ and $D_{opt} \propto C^b$. Using IsoFLOP profiles, we estimate the scaling on two different datasets.

Approach	Coef. a where $N_{opt} \propto C^a$	Coef. b where $D_{opt} \propto C^b$
C4	0.50	0.50
GitHub	0.53	0.47
Kaplan et al. [23]	0.73	0.27

D.2 Approach 3: Parametric fitting of the loss

In this section, we first show how Equation (2) can be derived. We repeat the equation below for clarity,

$$\hat{L}(N, D) \triangleq E + \frac{A}{N^\alpha} + \frac{B}{D^\beta}, \tag{4}$$

based on a decomposition of the expected risk between a function approximation term and an optimisation suboptimality term. We then give details on the optimisation procedure for fitting the parameters.

Loss decomposition. Formally, we consider the task of predicting the next token $y \in \mathcal{Y}$ based on the previous tokens in a sequence $x \in \mathcal{Y}^s$, with s varying from 0 to $s_{\max}$—the maximum sequence length. We consider a distribution $P \in \mathcal{D}(\mathcal{X} \times \mathcal{Y})$ of tokens in $\mathcal{Y}$ and their past in $\mathcal{X}$. A predictor $f : \mathcal{X} \to \mathcal{D}(\mathcal{Y})$ computes the probability of each token given the past sequence. The Bayes classifier, $f^\star$, minimizes the cross-entropy of $f(x)$ with the observed tokens y, with expectation taken on the whole data distribution. We let L be the expected risk

$$L(f) \triangleq \mathbb{E}[\log f(x)_y], \qquad \text{and set} \qquad f^\star \triangleq \underset{f \in \mathcal{F}(\mathcal{X}, \mathcal{D}(\mathcal{Y}))}{\operatorname{argmin}} L(f). \tag{5}$$

The set of all transformers of size N, that we denote $\mathcal{H}_N$, forms a subset of all functions that map sequences to distributions of tokens $\mathcal{X} \to \mathcal{D}(\mathcal{Y})$. Fitting a transformer of size N on the expected risk $L(f)$ amounts to minimizing such risk on a restricted functional space

$$f_N \triangleq \underset{f \in \mathcal{H}_N}{\operatorname{argmin}} L(f). \tag{6}$$

When we observe a dataset $(x_i, y_i)_{i \in [1,D]}$ of size D, we do not have access to $\mathbb{E}_P$, but instead to the empirical expectation $\hat{\mathbb{E}}_D$ over the empirical distribution $\hat{P}_D$. What happens when we are given D datapoints that we can only see once, and when we constrain the size of the hypothesis space to be N-dimensional ? We are making steps toward minimizing the empirical risk within a finite-dimensional functional space $\mathcal{H}_N$:

$$\hat{L}_D(f) \triangleq \hat{\mathbb{E}}_D[\log f(x)_y], \qquad \text{setting} \qquad \hat{f}_{N,D} \triangleq \underset{f \in \mathcal{H}_N}{\operatorname{argmin}} \hat{L}_D(f). \tag{7}$$

We are never able to obtain $\hat{f}_{N,D}$ as we typically perform a single epoch over the dataset of size D. Instead, be obtain $\bar{f}_{N,D}$, which is the result of applying a certain number of gradient steps based on the D datapoints—the number of steps to perform depends on the gradient batch size, for which we use well-tested heuristics.

Using the Bayes-classifier $f^\star$, the expected-risk minimizer f_N and the "single-epoch empirical-risk minimizer" $\bar{f}_{N,D}$, we can finally decompose the loss $L(N, D)$ into

$$L(N, D) \triangleq L(\bar{f}_{N,D}) = L(f^\star) + \left(L(f_N) - L(f^\star)\right) + \left(L(\bar{f}_{N,D}) - L(f_N)\right). \tag{8}$$

The loss comprises three terms: the Bayes risk, i.e. the minimal loss achievable for next-token prediction on the full distribution P, a.k.a the "entropy of natural text."; a functional approximation term that depends on the size of the hypothesis space; finally, a stochastic approximation term that captures the suboptimality of minimizing $\hat{L}_D$ instead of L, and of making a single epoch on the provided dataset.

Table A3: **Estimated optimal training FLOPs and training tokens for various model sizes.** For various model sizes, we show the projections from Approach 1 of how many FLOPs and training tokens would be needed to train compute-optimal models. The estimates for Approach 2 & 3 are similar (shown in Section D.3)

Parameters	FLOPs	FLOPs (in *Gopher* unit)	Tokens
400 Million	1.92e+19	$1/29,968$	8.0 Billion
1 Billion	1.21e+20	$1/4,761$	20.2 Billion
10 Billion	1.23e+22	$1/46$	205.1 Billion
67 Billion	5.76e+23	1	1.5 Trillion
175 Billion	3.85e+24	6.7	3.7 Trillion
280 Billion	9.90e+24	17.2	5.9 Trillion
520 Billion	3.43e+25	59.5	11.0 Trillion
1 Trillion	1.27e+26	221.3	21.2 Trillion
10 Trillion	1.30e+28	22515.9	216.2 Trillion

Expected forms of the loss terms.   In the decomposition (8), the second term depends entirely on the number of parameters N that defines the size of the functional approximation space. *On the set of two-layer neural networks*, it is expected to be proportional to $\frac{1}{N^{1/2}}$ [47]. Finally, given that it corresponds to early stopping in stochastic first order methods, the third term should scale as the convergence rate of these methods, which is lower-bounded by $\frac{1}{D^{1/2}}$ [42] (and may attain the bound). This convergence rate is expected to be dimension free [see e.g. 7, for a review] and depends only on the loss smoothness; hence we assume that the second term only depends on D in (2). Empirically, we find after fitting (2) that

$$L(N, D) = E + \frac{A}{N^{0.34}} + \frac{B}{D^{0.28}}, \tag{9}$$

with $E = 1.69$, $A = 406.4$, $B = 410.7$. We note that the parameter/data coefficients are both lower than $\frac{1}{2}$; this is expected for the data-efficiency coefficient (but far from the known lower-bound). Future models and training approaches should endeavor to increase these coefficients.

Fitting the decomposition to data.   We effectively minimize the following problem

$$\min_{a,b,e,\alpha,\beta} \sum_{\text{Run } i} \text{Huber}_\delta\Big(\text{LSE}\big(a - \alpha \log N_i, b - \beta \log D_i, e\big) - \log L_i\Big), \tag{10}$$

where LSE is the log-sum-exp operator. We then set $A, B, E = \exp(a), \exp(b), \exp(e)$.

We use the LBFGS algorithm to find local minima of the objective above, started on a grid of initialisation given by: $\alpha \in \{0., 0.5, \ldots, 2.\}$, $\beta \in \{0., 0.5, \ldots, 2.\}$, $e \in \{-1., -.5, \ldots, 1.\}$, $a \in \{0, 5, \ldots, 25\}$, and $b \in \{0, 5, \ldots, 25\}$. We find that the optimal initialisation is not on the boundary of our initialisation sweep.

We use $\delta = 10^{-3}$ for the Huber loss. We find that using larger values of δ pushes the model to overfit the small compute regime and poorly predict held-out data from larger runs. We find that using a δ smaller than 10^{-3} does not impact the resulting predictions.

D.3   Predicted compute optimal frontier for all three methods

For Approaches 1, 2 and 3, we show the estimated model size and number of training tokens for a variety of compute budgets in Table A3 and Table A4. We plot the predicted number of tokens and parameters for a variety of FLOP budgets for the three methods in Figure A3.

D.4   Small-scale comparison to Kaplan *et al.* (2020)

For 10^{21} FLOPs, we perform a head-to-head comparison of a model predicted by Approach 1 and that predicted by Kaplan et al. [23]. For both models, we use a batch size of 0.5M tokens and a maximum learning rate of 1.5×10^{-4} that decays by $10\times$. From Kaplan et al. [23], we find that the optimal model size should be 4.68 billion parameters. From our approach 1, we estimate a 2.86

Table A4: **Estimated optimal training FLOPs and training tokens for various model sizes.**
Analogous to Table A3, we show the model size/token count projections from Approaches 2 and 3
for various compute budgets.

	Approach 2		Approach 3	
Parameters	FLOPs	Tokens	FLOPs	Tokens
400 Million	1.84e+19	7.7 Billion	2.21e+19	9.2 Billion
1 Billion	1.20e+20	20.0 Billion	1.62e+20	27.1 Billion
10 Billion	1.32e+22	219.5 Billion	2.46e+22	410.1 Billion
67 Billion	6.88e+23	1.7 Trillion	1.71e+24	4.1 Trillion
175 Billion	4.54e+24	4.3 Trillion	1.26e+24	12.0 Trillion
280 Billion	1.18e+25	7.1 Trillion	3.52e+25	20.1 Trillion
520 Billion	4.19e+25	13.4 Trillion	1.36e+26	43.5 Trillion
1 Trillion	1.59e+26	26.5 Trillion	5.65e+26	94.1 Trillion
10 Trillion	1.75e+28	292.0 Trillion	8.55e+28	1425.5 Trillion

Figure A3: **Optimal number of tokens and parameters for a training FLOP budget.** For a fixed
FLOP budget, we show the optimal number of tokens and parameters as predicted by Approaches 1,
2, and 3. For an alternate representation, see Figure 1.

billion parameter model should be optimal. We train a 4.74 billion parameter and a 2.80 billion
parameter transformer to test this hypothesis, using the same depth-to-width ratio to avoid as many
confounding factors as possible. We find that our predicted model outperforms the model predicted
by Kaplan et al. [23] as shown in Figure A4.

E Curvature of the FLOP-loss frontier

We observe that as models increase there is a curvature in the FLOP-minimal loss frontier. This
means that projections from very small models lead to different predictions than those from larger
models. In Figure A5 we show linear fits using the first, middle, and final third of frontier-points. In
this work, we do not take this in to account and we leave this as interesting future work as it suggests
that even smaller models may be optimal for large FLOP budgets.

F FLOPs computation

We include all training FLOPs, including those contributed to by the embedding matrices, in our
analysis. Note that we also count embeddings matrices in the total parameter count. For large models

Figure A4: **Comparison to Kaplan et al. [23] at 10^{21} FLOPs.** We train 2.80 and 4.74 billion parameter transformers predicted as optimal for 10^{21} FLOPs by Approach 1 and by Kaplan et al. [23]. We find that our prediction results in a more performant model at the end of training.

Figure A5: **Training curve envelopes.** We fit to the first third (orange), the middle third (green), and the last third (blue) of all points along the loss frontier. We plot only a subset of the points.

the FLOP and parameter contribution of embedding matrices is small. We use a factor of 2 to describe the multiply accumulate cost. For the forward pass, we consider contributions from:

- Embeddings
  - $2 \times$ seq_len $\times$ vocab_size $\times$ d_model
- Attention (Single Layer)
  - **Key, query and value projections**: $2 \times 3 \times$ seq_len $\times$ d_model $\times$ (key_size $\times$ num_heads)
  - **Key @ Query logits**: $2 \times$ seq_len $\times$ seq_len $\times$ (key_size $\times$ num_heads)
  - **Softmax**: $3 \times$ num_heads $\times$ seq_len $\times$ seq_len
  - **Softmax @ query reductions**: $2 \times$ seq_len $\times$ seq_len $\times$ (key_size $\times$ num_heads)
  - **Final Linear**: $2 \times$ seq_len $\times$ (key_size $\times$ num_heads) $\times$ d_model
- Dense Block (Single Layer)
  - $2 \times$ seq_len $\times$ (d_model $\times$ ffw_size $+$ d_model $\times$ ffw_size)

- Final Logits

  - $2 \times$ seq_len $\times$ d_model $\times$ vocab_size

- **Total forward pass FLOPs:** embeddings $+$ num_layers $\times$ (total_attention $+$ dense_block) $+$ logits

As in Kaplan et al. [23] we assume that the backward pass has twice the FLOPs of the forward pass. We show a comparison between our calculation and that using the common approximation $C = 6DN$ [23] where C is FLOPs, D is the number of training tokens, and N is the number of parameters in Table A5. We find the differences in FLOP calculation to be very small and they do not impact our analysis. Compared to the results presented in Rae et al. [38], we use a slightly more

Table A5: **FLOP comparison.** For a variety of different model sizes, we show the ratio of the FLOPs that we compute per sequence to that using the $6ND$ approximation.

Parameters	num_layers	d_model	ffw_size	num_heads	k/q size	FLOP Ratio (Ours/$6ND$)
73M	10	640	2560	10	64	1.03
305M	20	1024	4096	16	64	1.10
552M	24	1280	5120	10	128	1.08
1.1B	26	1792	7168	14	128	1.04
1.6B	28	2048	8192	16	128	1.03
6.8B	40	3584	14336	28	128	0.99

accurate calculation giving a slightly different value (6.3×10^{23} compared to 5.76×10^{23}).

G   Other differences between *Chinchilla* and *Gopher*

Beyond differences in model size and number of training tokens, there are some additional minor differences between *Chinchilla* and *Gopher*. Specifically, *Gopher* was trained with Adam [24] whereas *Chinchilla* was trained with AdamW [32]. Furthermore, as discussed in *Lessons Learned* in Rae et al. [38], *Chinchilla* stored a higher-precision copy of the weights in the sharded optimiser state.

We show comparisons of models trained with Adam and AdamW in Figure A6 and Figure A7. We find that, independent of the learning rate schedule, AdamW trained models outperform models trained with Adam. In Figure A6 we show a comparison of an 680 million parameter model trained

Figure A6: **Comparison of other differences.** Using an 680 million parameter model, we show a comparison between the setup used to train *Gopher* and *Chinchilla*— the change in optimiser and using a higher precision copy of the weights in the optimiser state. The setup used for *Chinchilla* (orange) clearly outperforms the setup used to train *Gopher* (green).

with and without the higher precision copy of the weights and with Adam/AdamW for comparison.

Figure A7: **Adam vs AdamW.** For a 417M (blue) and 1.4B model (green), we find that training with AdamW improves performance over training with Adam.

Figure A8: **Pile Evaluation.** For the different evaluation sets in The Pile [13], we show the bits-per-byte (bpb) improvement (decrease) of *Chinchilla* compared to *Gopher*. On all subsets, *Chinchilla* outperforms *Gopher*.

H   Results

H.1   The Pile

In Table A7 we show the bits-per-byte (bpb) on The Pile [13] of *Chinchilla*, *Gopher*, and Jurassic-1. *Chinchilla* outperforms *Gopher* on all subsets. Jurassic-1 outperforms *Chinchilla* on 2 subsets— `dm_mathematics` and `ubuntu_irc`.

H.2   MMLU

In Table A9 we show the performance of *Chinchilla* and *Gopher* on each subset of MMLU.

Table A6: **All evaluation tasks.** We evaluate *Chinchilla* on a collection of language modelling along with downstream tasks. Those are largely the same tasks as in Rae et al. [38], to allow for direct comparison.

	# Tasks	Examples
Language Modelling	20	WikiText-103, The Pile: PG-19, arXiv, FreeLaw, . . .
Reading Comprehension	3	RACE-m, RACE-h, LAMBADA
Question Answering	3	Natural Questions, TriviaQA, TruthfulQA
Common Sense	5	HellaSwag, Winogrande, PIQA, SIQA, BoolQ
MMLU	57	High School Chemistry, Astronomy, Clinical Knowledge, . . .
BIG-bench	62	Causal Judgement, Epistemic Reasoning, Temporal Sequences, . . .

Table A7: **Bits-per-Byte on The Pile.** We show the bpb on The Pile for *Chinchilla* compared to *Gopher* and Jurassic-1.

Subset	*Chinchilla* (70B)	*Gopher* (280B)	Jurassic-1 (170B)
pile_cc	**0.667**	0.691	0.669
pubmed_abstracts	**0.559**	0.578	0.587
stackexchange	**0.614**	0.641	0.655
github	**0.337**	0.377	0.358
openwebtext2	**0.647**	0.677	-
arxiv	**0.627**	0.662	0.680
uspto_backgrounds	**0.526**	0.546	0.537
freelaw	**0.476**	0.513	0.514
pubmed_central	**0.504**	0.525	0.579
dm_mathematics	1.111	1.142	**1.037**
hackernews	**0.859**	0.890	0.869
nih_exporter	**0.572**	0.590	0.590
opensubtitles	**0.871**	0.900	0.879
europarl	**0.833**	0.938	-
books3	**0.675**	0.712	0.835
philpapers	**0.656**	0.695	0.742
gutenberg_pg_19	**0.548**	0.656	0.890
bookcorpus2	**0.714**	0.741	-
ubuntu_irc	1.026	1.090	**0.857**

Figure A9: **MMLU results compared to *Gopher*** We find that *Chinchilla* outperforms *Gopher* by 7.6% on average (see Table A8) in addition to performing better on 51/57 individual tasks, the same on 2/57, and worse on only 4/57 tasks.

H.3   Winogender Setup

We follow the same setup as in Rae et al. [38]. To test coreference resolution in *Chinchilla*, we input a sentence which includes a pronoun reference (e.g., "The librarian helped the child pick out a book because {pronoun} liked to encourage reading."), then measure the probability of the model completing the sentence "'{Pronoun}' refers to the" with different sentence roles ("librarian" and "child" in this example). Each example is annotated with the correct pronoun resolution (the pronoun corresponds to the librarian in this example). Each sentence is tested with a female, male, and gender-neutral pronoun. An unbiased model would correctly predict which word the pronoun refers to regardless of pronoun gender.

Table A8: **Massive Multitask Language Understanding (MMLU).** We report the average 5-shot accuracy over 57 tasks with model and human accuracy comparisons taken from Hendrycks et al. [16]. We also include the average prediction for state of the art accuracy in June 2022/2023 made by 73 competitive human forecasters in Steinhardt [50].

Random	25.0%
Average human rater	34.5%
GPT-3 5-shot	43.9%
Gopher 5-shot	60.0%
***Chinchilla* 5-shot**	**67.6%**
Average human expert performance	*89.8%*
June 2022 Forecast	57.1%
June 2023 Forecast	63.4%

Table A9: ***Chinchilla* MMLU results.** For each subset of MMLU [16], we show *Chinchilla*'s accuracy compared to *Gopher*.

Task	Chinchilla	Gopher	Task	Chinchilla	Gopher
abstract_algebra	31.0	25.0	anatomy	70.4	56.3
astronomy	73.0	65.8	business_ethics	72.0	70.0
clinical_knowledge	75.1	67.2	college_biology	79.9	70.8
college_chemistry	51.0	45.0	college_computer_science	51.0	49.0
college_mathematics	32.0	37.0	college_medicine	66.5	60.1
college_physics	46.1	34.3	computer_security	76.0	65.0
conceptual_physics	67.2	49.4	econometrics	38.6	43.0
electrical_engineering	62.1	60.0	elementary_mathematics	41.5	33.6
formal_logic	33.3	35.7	global_facts	39.0	38.0
high_school_biology	80.3	71.3	high_school_chemistry	58.1	47.8
high_school_computer_science	58.0	54.0	high_school_european_history	78.8	72.1
high_school_geography	86.4	76.8	high_school_gov_and_politics	91.2	83.9
high_school_macroeconomics	70.5	65.1	high_school_mathematics	31.9	23.7
high_school_microeconomics	77.7	66.4	high_school_physics	36.4	33.8
high_school_psychology	86.6	81.8	high_school_statistics	58.8	50.0
high_school_us_history	83.3	78.9	high_school_world_history	85.2	75.1
human_aging	77.6	66.4	human_sexuality	86.3	67.2
international_law	90.9	77.7	jurisprudence	79.6	71.3
logical_fallacies	80.4	72.4	machine_learning	41.1	41.1
management	82.5	77.7	marketing	89.7	83.3
medical_genetics	69.0	69.0	miscellaneous	84.5	75.7
moral_disputes	77.5	66.8	moral_scenarios	36.5	40.2
nutrition	77.1	69.9	philosophy	79.4	68.8
prehistory	81.2	67.6	professional_accounting	52.1	44.3
professional_law	56.5	44.5	professional_medicine	75.4	64.0
professional_psychology	75.7	68.1	public_relations	73.6	71.8
security_studies	75.9	64.9	sociology	91.0	84.1
us_foreign_policy	92.0	81.0	virology	53.6	47.0
world_religions	87.7	84.2			

H.4 BIG-bench

In Table A10 we show *Chinchilla* and *Gopher* performance on each subset of BIG-bench that we consider.

H.5 Question Answering

In Table A11 we show results on closed book QA.

Figure A10: **BIG-bench results compared to *Gopher*** *Chinchilla* out performs *Gopher* on all but four BIG-bench tasks considered. Full results are in Table A10.

I Gender bias and toxicity

Large Language Models carry potential risks such as outputting offensive language, propagating social biases, and leaking private information [54, 2]. We expect *Chinchilla* to carry risks similar to *Gopher* because *Chinchilla* is trained on the same data, albeit with slightly different relative weights, and because it has a similar architecture. Here, we examine gender bias (particularly gender and occupation bias) and generation of toxic language. We select a few common evaluations to highlight potential issues, but stress that our evaluations are not comprehensive and much work remains to understand, evaluate, and mitigate risks in LLMs.

Gender bias.   As discussed in Rae et al. [38], large language models reflect contemporary and historical discourse about different groups (such as gender groups) from their training dataset, and we expect the same to be true for *Chinchilla*. Here, we test if potential gender and occupation biases manifest in unfair outcomes on coreference resolutions, using the Winogender dataset [43] in a zero-shot setting. Winogender tests whether a model can correctly determine if a pronoun refers to different occupation words. An unbiased model would correctly predict which word the pronoun refers to regardless of pronoun gender. We follow the same setup as in Rae et al. [38] (described further in Section H.3).

As shown in Table A12, *Chinchilla* correctly resolves pronouns more frequently than *Gopher* across all groups. Interestingly, the performance increase is considerably smaller for male pronouns (increase of 3.2%) than for female or neutral pronouns (increases of 8.3% and 9.2% respectively). We also consider *gotcha* examples, in which the correct pronoun resolution contradicts gender stereotypes (determined by labor statistics). Again, we see that *Chinchilla* resolves pronouns more accurately than *Gopher*. When breaking up examples by male/female gender and *gotcha/not gotcha*, the largest improvement is on female *gotcha* examples (improvement of 10%). Thus, though *Chinchilla* uniformly overcomes gender stereotypes for more coreference examples than *Gopher*, the rate of improvement is higher for some pronouns than others, suggesting that the improvements conferred by using a more compute-optimal model can be uneven.

Sample toxicity.   Language models are capable of generating toxic language—including insults, hate speech, profanities and threats [14, 38]. While toxicity is an umbrella term, and its evaluation in LMs comes with challenges [56, 55], automatic classifier scores can provide an indication for the levels of harmful text that a LM generates. Rae et al. [38] found that improving language modelling loss by increasing the number of model parameters has only a negligible effect on toxic text generation (unprompted); here we analyze whether the same holds true for a lower LM loss achieved via more compute-optimal training. Similar to the protocol of Rae et al. [38], we generate 25,000 unprompted samples from *Chinchilla*, and compare their *PerspectiveAPI* toxicity score distribution to that of

Task	Chinchilla	Gopher	Task	Chinchilla	Gopher
hyperbaton	54.2	51.7	movie_dialog_same_or_diff	54.5	50.7
causal_judgment	57.4	50.8	winowhy	62.5	56.7
formal_fallacies_syllogisms_neg	52.1	50.7	movie_recommendation	75.6	50.5
crash_blossom	47.6	63.6	moral_permissibility	57.3	55.1
discourse_marker_prediction	13.1	11.7	strategyqa	68.3	61.0
general_knowledge_json	94.3	93.9	nonsense_words_grammar	78.0	61.4
sports_understanding	71.0	54.9	metaphor_boolean	93.1	59.3
implicit_relations	49.4	36.4	navigate	52.6	51.1
penguins_in_a_table	48.7	40.6	presuppositions_as_nli	49.9	34.0
intent_recognition	92.8	88.7	temporal_sequences	32.0	19.0
reasoning_about_colored_objects	59.7	49.2	question_selection	52.6	41.4
logic_grid_puzzle	44.0	35.1	logical_fallacy_detection	72.1	58.9
timedial	68.8	50.9	physical_intuition	79.0	59.7
epistemic_reasoning	60.6	56.4	physics_mc	65.5	50.9
ruin_names	47.1	38.6	identify_odd_metaphor	68.8	38.6
hindu_knowledge	91.4	80.0	understanding_fables	60.3	39.6
misconceptions	65.3	61.7	logical_sequence	64.1	36.4
implicatures	75.0	62.0	mathematical_induction	47.3	57.6
disambiguation_q	54.7	45.5	fantasy_reasoning	69.0	64.1
known_unknowns	65.2	63.6	SNARKS	58.6	48.3
dark_humor_detection	66.2	83.1	crass_ai	75.0	56.8
analogical_similarity	38.1	17.2	entailed_polarity	94.0	89.5
sentence_ambiguity	71.7	69.1	irony_identification	73.0	69.7
riddle_sense	85.7	68.2	evaluating_info_essentiality	17.6	16.7
date_understanding	52.3	44.1	phrase_relatedness	94.0	81.8
analytic_entailment	67.1	53.0	novel_concepts	65.6	59.1
odd_one_out	70.9	32.5	empirical_judgments	67.7	52.5
logical_args	56.2	59.1	figure_of_speech_detection	63.3	52.7
alignment_questionnaire	91.3	79.2	english_proverbs	82.4	57.6
similarities_abstraction	87.0	81.8	Human_organs_senses_mcc	85.7	84.8
anachronisms	69.1	56.4	gre_reading_comprehension	53.1	27.3

Table A10: **Chinchilla BIG-bench results.** For each subset of BIG-bench [49], we show *Chinchilla* and *Gopher*'s accuracy.

Gopher-generated samples. Several summary statistics indicate an absence of major differences: the mean (median) toxicity score for *Gopher* is 0.081 (0.064), compared to 0.087 (0.066) for *Chinchilla*, and the 95$^{\text{th}}$ percentile scores are 0.230 for *Gopher*, compared to 0.238 for *Chinchilla*. That is, the large majority of generated samples are classified as non-toxic, and the difference between the models is negligible. In line with prior findings [38], this suggests that toxicity levels in unconditional text generation are largely independent of the model quality (measured in language modelling loss), i.e. that better models of the training dataset are not necessarily more toxic.

J Model Card

We present the *Chinchilla* model card in Table A13, following the framework presented by Mitchell et al. [35].

Model Details	
Model Date	March 2022
Model Type	Autoregressive Transformer Language Model (Section 4.1 for details)

Intended Uses	

Out-of-Scope Uses	Uses of the language model for language generation in harmful or deceitful settings. More generally, the model should not be used for downstream applications without further safety and fairness mitigations.

Factors

Card Prompts – Relevant Factor	Relevant factors include which language is used. Our model is trained on English data. Furthermore, in the analysis of models trained on the same corpus in Rae et al. [38], we found it has unequal performance when modelling some dialects (e.g., African American English). Our model is designed for research. The model should not be used for downstream applications without further analysis on factors in the proposed downstream application.
Card Prompts – Evaluation Factors	See the results in Rae et al. [38] which analyzes models trained on the same text corpus.

Metrics

Model Performance Measures	- Perplexity and bits per byte on language modelling datasets - Accuracy on completion tasks, reading comprehension, MMLU, BIG-bench and fact checking. - Exact match accuracy for question answering. - Generation toxicity from Real Toxicity Prompts (RTP) alongside toxicity classification accuracy. - Gender and occupation bias. Test include comparing the probability of generating different gender terms and the Winogender coreference resolution task. We principally focus on *Chinchilla*'s performance compared to *Gopher* on text likelihood prediction.
Decision thresholds	N/A
Approaches to Uncertainty and Variability	Due to the costs of training large language models, we did not train *Chinchilla* multiple times. However, the breadth of our evaluation on a range of different task types gives a reasonable estimate of the overall performance of the model. Furthermore, the existence of another large model trained on the same dataset (*Gopher*) provides a clear point of comparison.

Evaluation Data

Datasets	
	• Language modelling on LAMBADA, Wikitext103 [34], C4 [40], PG-19 [39] and the Pile [13].
	• Language understanding, real world knowledge, mathematical and logical reasoning on the Massive Multitask Language Understanding (MMLU) benchmark [16] and on the "Beyond the Imitation Game Benchmark" (BIG-bench) [49].
	• Question answering (closed book) on Natural Questions [26] and TriviaQA [21].
	• Reading comprehension on RACE [27]
	• Common sense understanding on HellaSwag [58], PIQA [3], Winogrande [44], SIQA [45], BoolQ [10], and TruthfulQA [31].
Motivation	We chose evaluations from Rae et al. [38] to allow us to most directly compare to *Gopher*.
Preprocessing	Input text is tokenized using a SentencePiece tokenizer with a vocabulary of size 32,000. Unlike the tokenizer used for *Gopher*, the tokenizer used for *Chinchilla* does not perform NFKC normalization.

Training Data

The same dataset is used as in Rae et al. [38]. Differences in sampling are shown in Table A1.

Quantitative Analyses

Unitary Results	Section 4.2 gives a detailed description of our analysis. Main take-aways include:
	• Our model is capable of outputting toxic language as measured by the PerspectiveAPI. This is particularly true when the model is prompted with toxic prompts.
	• Gender: Our model emulates stereotypes found in our dataset, with occupations such as "dietician" and "receptionist" being more associated with women and "carpenter" and "sheriff" being more associated with men.
	• Race/religion/country sentiment: Prompting our model to discuss some groups leads to sentences with lower or higher sentiment, likely reflecting text in our dataset.
Intersectional Results	We did not investigate intersectional biases.

Ethical Considerations

Data	The data is the same as described in Rae et al. [38].
Human Life	The model is not intended to inform decisions about matters central to human life or flourishing.

Mitigations	We considered filtering the dataset to remove toxic content but decided against it due to the observation that this can introduce new biases as studied by Welbl et al. [55]. More work is needed on mitigation approaches to toxic content and other types of risks associated with language models, such as those discussed in Weidinger et al. [54].
Risks and Harms	The data is collected from the internet, and thus undoubtedly there is toxic/biased content in our training dataset. Furthermore, it is likely that personal information is also in the dataset that has been used to train our models. We defer to the more detailed discussion in Weidinger et al. [54].
Use Cases	Especially fraught use cases include the generation of factually incorrect information with the intent of distributing it or using the model to generate racist, sexist or otherwise toxic text with harmful intent. Many more use cases that could cause harm exist. Such applications to malicious use are discussed in detail in Weidinger et al. [54].

Table A13: ***Chinchilla* model card.** We follow the framework presented in Mitchell et al. [35].

K List of trained models

In Table A14 we list the model size and configuration of all models used in this study. Many models have been trained multiple times, for a different number of training steps.

Table A11: **Closed-book question answering.** For Natural Questions [26] and TriviaQA [21], *Chinchilla* outperforms *Gopher* in all cases. On Natural Questions, *Chinchilla* outperforms GPT-3. On TriviaQA we show results on two different evaluation sets to allow for comparison to GPT-3 and to open book SOTA (FiD + Distillation [20]).

	Method	*Chinchilla*	*Gopher*	GPT-3	SOTA (open book)
Natural Questions (dev)	0-shot	16.6%	10.1%	14.6%	
	5-shot	31.5%	24.5%	-	54.4%
	64-shot	35.5%	28.2%	29.9%	
TriviaQA (unfiltered, test)	0-shot	67.0%	52.8%	64.3 %	
	5-shot	73.2%	63.6%	-	-
	64-shot	72.3%	61.3%	71.2%	
TriviaQA (filtered, dev)	0-shot	55.4%	43.5%	-	
	5-shot	64.1%	57.0%	-	72.5%
	64-shot	64.6%	57.2%	-	

Table A12: **Winogender results. Left:** *Chinchilla* consistently resolves pronouns better than *Gopher*. **Right:** *Chinchilla* performs better on examples which contradict gender stereotypes (*gotcha* examples). However, difference in performance across groups suggests *Chinchilla* exhibits bias.

	Chinchilla	*Gopher*
All	78.3%	71.4%
Male	71.2%	68.0%
Female	79.6%	71.3%
Neutral	84.2%	75.0%

	Chinchilla	*Gopher*
Male *gotcha*	62.5%	59.2%
Male *not gotcha*	80.0%	76.7%
Female *gotcha*	76.7%	66.7%
Female *not gotcha*	82.5%	75.8%

Parameters (million)	d_model	ffw_size	kv_size	n_heads	n_layers
44	512	2048	64	8	8
57	576	2304	64	9	9
74	640	2560	64	10	10
90	640	2560	64	10	13
106	640	2560	64	10	16
117	768	3072	64	12	12
140	768	3072	64	12	15
163	768	3072	64	12	18
175	896	3584	64	14	14
196	896	3584	64	14	16
217	896	3584	64	14	18
251	1024	4096	64	16	16
278	1024	4096	64	16	18
306	1024	4096	64	16	20
425	1280	5120	128	10	18
489	1280	5120	128	10	21
509	1408	5632	128	11	18
552	1280	5120	128	10	24
587	1408	5632	128	11	21
632	1536	6144	128	12	19
664	1408	5632	128	11	24
724	1536	6144	128	12	22
816	1536	6144	128	12	25
893	1792	7168	128	14	20
1,018	1792	7168	128	14	23
1,143	1792	7168	128	14	26
1,266	2048	8192	128	16	22
1,424	2176	8704	128	17	22
1,429	2048	8192	128	16	25
1,593	2048	8192	128	16	28
1,609	2176	8704	128	17	25
1,731	2304	9216	128	18	24
1,794	2176	8704	128	17	28
2,007	2304	9216	128	18	28
2,283	2304	9216	128	18	32
2,298	2560	10240	128	20	26
2,639	2560	10240	128	20	30
2,980	2560	10240	128	20	34
3,530	2688	10752	128	22	36
3,802	2816	11264	128	22	36
4,084	2944	11776	128	22	36
4,516	3072	12288	128	24	36
6,796	3584	14336	128	28	40
9,293	4096	16384	128	32	42
11,452	4352	17408	128	32	47
12,295	4608	18432	128	36	44
12,569	4608	18432	128	32	47
13,735	4864	19456	128	32	47
14,940	4992	19968	128	32	49
16,183	5120	20480	128	40	47

Table A14: **All models.** We list the hyperparameters and size of all models trained as part of this work. Many shown models have been trained with multiple learning rate schedules/number of training tokens.