Exploiting Reward Shifting in Value-Based Deep RL

Abstract

In this work, we study the simple yet universally applicable case of reward shaping in value-based Deep Reinforcement Learning (DRL). We show that reward shifting in the form of the linear transformation is equivalent to changing the initialization of the Q-function in function approximation. Based on such an equivalence, we bring the key insight that a positive reward shifting leads to conservative exploitation, while a negative reward shifting leads to curiosity-driven exploration. Accordingly, conservative exploitation improves offline RL value estimation, and optimistic value estimation benefits the exploration of online RL. We validate our insight on a range of RL tasks and show its improvement over baselines: (1) In offline RL, the conservative exploitation leads to improved performance based on off-the-shelf algorithms; (2) In online continuous control, multiple value functions with different shifting constants can be used to tackle the exploration-exploitation dilemma for better sample efficiency; (3) In discrete exploration tasks, a negative reward shifting brings an improvement over the previous curiosity-based exploration method.

1 Introduction

While reward shaping is a well-established practice in reinforcement learning and has a long-standing history [1, 2], specifying a certain reward to incentivize the learning agent requires domain knowledge and thorough understanding of the task [3–6]. Even with careful design and tuning, learning with a shaped reward that intends to accelerate learning may on the contrary hinder the learning performance by incurring the sub-optimal behaviors of the agent [7, 8]. Although Ng et al. [9] theoretically points the optimal policy remains unchanged under a special form of reward transformation, and in the later work of Wiewiora et al. [10] a framework is proposed to guide policies with prior knowledge under tabular setting, the investigation of how it accommodates recent Deep Reinforcement Learning (DRL) algorithms remains much less explored.

Figure 1: Our work is inspired by the observation that reward shifting remarkably helps exploration and outperforms count-based exploration in Q-learning (left). Reward shifting does not change the primal optimal Q-value landscape, and is able to learn a near-optimal Q-value (right). While count-based exploration suffers from the curse of dimensionality, reward shifting can be seamlessly applied to high dimensional tasks including continuous control.

In this work, we focus on the simplest form of reward shaping, the linear transformation, in value-based DRL [11–14]. We start with understanding how such a specific kind of reward shaping works in value-based DRL algorithms. We show that reward shifting, as the simplest reward transformation, is equivalent to manually setting the initial values of the Q-function estimation, extending previous discovery of [10] to the function approximation setting. Figure 1 showcases reward shifting benefits exploration in a maze game and outperforms count-based and ϵ-greedy exploration.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Based on such an equivalence, we introduce the key insight of this work:

A positive reward shifting leads to conservative exploitation, while a negative reward shifting leads to curiosity-driven exploration.

We demonstrate the application of such an insight on three Deep-RL scenarios: (1) for offline RL, we show that conservative exploitation can lead to improved learning performance based on off-the-shelf algorithms; (2) for online RL setting, we show multiple value functions with different reward shifting constants can be used as a trade-off between exploration and exploitation, thus improving learning efficiency; (3) we introduce a simple yet crucial improvement over a prevailing curiosity-based exploration method, the Random Network Distillation [15], making it compatible with value-based DRL algorithms. The experiments on both continuous and discrete action space control tasks shows our method brings the substantial improvement over previous baselines.

Our contributions can be summarized as follows:

1. We introduce the key insight that reward shifting is equivalent to diversified Q-value network initialization in deep-RL, which can be used to improve both curiosity-driven exploration and conservative exploitation;
2. Practically, we present three scenarios motivated by our key insight to show the potential benefit of reward shifting, namely the offline conservative exploitation, the online sample-efficient RL, and the curiosity-driven exploration;
3. Empirically, we demonstrate the effectiveness of the proposed method integrated with off-the-shelf baselines on both continuous and discrete control tasks.

2 Preliminaries and Related Work

2.1 Online RL

We follow a standard MDP formulation in the online RL setting, *i.e.*, $\mathcal{M} = \{\mathcal{S}, \mathcal{A}, \mathcal{T}, \mathcal{R}, \rho_0, \gamma, T\}$, where $\mathcal{S} \subset \mathbb{R}^d$ denotes the d-dim state space, $\mathcal{A}$ is the action space (note for discrete action space $|\mathcal{A}| < \infty$ and for continuous control $|\mathcal{A}| = \infty$), $\mathcal{T} : \mathcal{S} \times \mathcal{A} \mapsto \mathcal{S}$ is the transition dynamics, $\mathcal{R} : \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R}$ is the reward function. ρ_0 denotes the initial state distribution, *i.e.*, $\rho_0 = p(s_0)$. γ is the discount factor and T is the episodic decision horizon. Online RL considers the problem of learning a policy $\pi \in \Pi : \mathcal{S} \mapsto \Delta(\mathcal{A})$ (or $\pi \in \Pi : \mathcal{S} \mapsto \mathcal{A}$ with a deterministic policy class), such that the expected cumulative reward in the Markov decision process is maximized, *i.e.*, $\pi = \arg\max_\pi \mathbb{E}_{a_t \sim \pi, s_{t+1} \sim \mathcal{T}, s_0 \sim \rho_0} \sum_{t=0}^T \gamma^t r_t(s_t, a_t)$, In the online RL setting, an agent normally learns through trials and errors [11], either with an on-policy paradigm [16-18] or an off-policy manner [13, 12, 19, 20, 14]. In this work, we focus on the off-policy value-based methods which are in general more sample efficient. Specifically, our discussions assume the policy learning is based on a learned Q-value function, that approximates the cumulative reward an agent can gain in the following part of an episode. The Q-value function is defined as $Q(s_t, a_t) = \mathbb{E}_{\pi, \mathcal{T}} \sum_{\tau=t}^T \gamma^t r(s_\tau, a_\tau)$, and can be estimated by propagating the Bellman operator $\mathbb{B}Q(s, a) = r(s, a) + \gamma \mathbb{E}Q(s', a')$. For value-based methods, the (soft-)optimal policy is then produced by

$$\pi_\alpha^*(a|s) = \frac{\exp \frac{1}{\alpha} Q^*(s, a)}{\sum_{a'} \exp \frac{1}{\alpha} Q^*(s, a')}, \tag{1}$$

where Q^* is optimal Q-value function. We can also set the temperature parameter close as 0 to have the deterministic policy class. Simplifying the notion we have $\pi^*(s) = \arg\max_a Q^*(s, a)$. Algorithms like DPG [21] can be used to address the intractable analytical argmax issue arises in continuous action space. We choose to develop our work on top of prevailing baseline algorithms of DQN [13], BCQ [22], CQL [23] and TD3 [14] as a minimal example to isolate the source of gains. It should be straightforward to extend the method on top of other learning algorithms.

2.2 Exploration and the Curiosity-Driven Methods

One of the most important issues in online RL is the exploration-exploitation dilemma [11] that the agent must learn to exploit its accumulated knowledge on the task while exploring new states and actions. Previous works address the exploration problem from various perspectives: In the tasks with

Table 1: Comparison with related work. Our proposed method is distinguished by its flexibility of being plugged into both online and offline RL tasks to guarantee conservative exploitation or pursue optimistic exploration. Our method tackles both discrete control and continuous control tasks, with only a little additional computational expense being introduced. Moreover, our method does not introduce bias to the primal task solution.

	Related Work	Plug-in	Online	Offline	Discrete	Continuous	Unbiased	Examples
Exploration	Curiosity	✓	✓	.	✓	.	.	Burda et al. [15]
	Ensemble	.	✓	.	✓	.	✓	Osband et al. [24]
	Initialization	.	✓	.	✓	.	✓	Rashid et al. [25]
	Optimism	.	✓	.	.	✓	.	Ciosek et al. [26]
Exploitation	Conservatism	.	.	✓	✓	✓	.	Bharadhwaj et al. [23]
	Policy Constraints	✓	.	✓	✓	✓	✓	Fujimoto et al. [22]
	Reward Shifting	✓	✓	✓	✓	✓	✓	Ours

discrete action space, count-based methods like Bellemare et al. [27], Ostrovski et al. [28], Tang et al. [29], Choshen et al. [30] are proposed to motivate the policy to explore more on under-explored states. Curiosity-driven methods are investigated by Houthooft et al. [31], Pathak et al. [32], Burda et al. [33, 15], where the intrinsic reward is designed as a supplementary to the primal task reward for better exploration. Self-imitate approaches like Oh et al. [34], Ecoffet et al. [35], Sun et al. [36] repeat success trajectories but require extra assumptions on the environment. The work of DIAYN and DADS [37, 38] show that various skills can be developed even without the primal extrinsic reward. For continuous control tasks, OAC [26] improves the SAC [20] with informative action space noise based on the optimism in face of uncertainty (OFU) [39–42]. GAC [43] addresses the exploration issue with a richer functional class for the policy.

In the work of Rashid et al. [25], the problematic pessimistic initialization is addressed for better exploration, yet the work focuses on specific settings of tabular and discrete control exploration. In the work of Osband et al. [44, 24], ensemble models with diverse initialization and randomized priors are used to resemble the insight of bootstrap sampling and facilitate better value estimation, yet those methods are only applicable to discrete control tasks. Noted that although the reward shifting can be regarded as a special case of these random priors, it can be distinguished by not changing the optimal Q-value, and its flexibility to be plugged in to both continuous and discrete control algorithms.

The Random Network Distillation (RND) [15] proposes to use the difference between a fixed neural network ϕ_1 and a trainable network ϕ_2 to represents the intrinsic reward, *e.g.*,

$$r_{\text{int}}(s, a) = |\phi_2(s, a) - \phi_1(s, a)|, \tag{2}$$

when outputs of both networks are activated by a sigmoid function, and ϕ_2 is optimized to approximate ϕ_1 for the visited (s, a) pairs [1]. Hence, the value of $r_{\text{int}}(s, a)$ will decay to 0 when such state-action pairs are visited frequently but remain high for seldom visited pairs.

In this work, we show that exploratory behavior can be achieved simply by shifting the reward function with a constant. Thus our method is orthogonal to those previous approaches in the sense that our intrinsic exploration behavior is motivated by function approximation error. We demonstrate such an insight by showing that RND in its original design is not suitable for value-based methods in developing exploratory behaviors, but integrating RND with a shifted reward function remarkably improves the learning performance.

2.3 Offline RL

The offline RL, also known as batch-RL, focuses on the problems where the interaction with the environment is impossible, and the policy can only be optimized based on logged dataset. In those tasks, a fixed buffer $\mathcal{B} = \{s_i, a_i, r_i, s_i'\}_{i=[N]}$ is provided. As the agent in the offline RL setting can not correct its potentially biased knowledge through interactions, the most important issue is to address the extrapolation error [22] induced by distributional mismatch [45]. To address such an issue, a series of algorithms optimize the policy learning under the constraint of distributional similarity [45–47].

Bharadhwaj et al. [23] propose CQL to solve the offline RL tasks with a conservative value estimation. Specifically, CQL learns the Q-value estimation by jointly maximizing the Q-values of actions sampled from the behavior offline dataset and minimizing the Q-values of actions sampled with pre-defined prior distributions (*e.g.*, uniform distribution over the action space). As we will show in

---

[1]Or computed with only states, i.e., $r_{\text{int}}(s) = |\phi_2(s) - \phi_1(s)|$.

Figure 2: Illustrative figure for conservative exploitation, with a positive constant bias added to the reward function. **(a)** shifting the reward function with a positive bias term b^+ leads to an uniformly increased Q-value function, namely $Q_{b+}^* = Q^* + \frac{b^+}{1-\gamma}$, during learning, a neural network estimator $\tilde{Q}$ initialized with $\tilde{Q}_0 \approx 0$ is optimized to approximate the Q-value functions (*e.g.*, through Temporal Difference or Monte Carlo estimation). **(b)** for any value-based RL algorithm, the value optimization step can be regarded as a function F that minimizes the difference between the estimated Q-value function $\tilde{Q}_t$ and the optimal one Q^*, given the interaction experience with the environment (*e.g.*, a replay buffer $\mathcal{B}$ for off-policy methods). Note $\tilde{Q}_t$ approximating Q^* better than $\tilde{Q}_{t-1}$ holds in expectation as long as the RL algorithm is designed to approximate the optimal value function. **(c)** similarly, the optimizer given the same interactive experience (*e.g.*, replay buffer $\mathcal{B}$) will learn to minimize the difference between Q-value function $\tilde{Q}_{b+,t}$ and the optimal one Q_{b+}^*, after re-labeling the rewards in the buffer by $r' = r + b^+$. **(d)** according to Remark 2, the optimization conducted in (c) is equivalent to (b) with the neural network Q-value estimator initialized as $\tilde{Q}_0 \approx 0 - \frac{b^+}{1-\gamma}$, rather than $\tilde{Q}_0 \approx 0$. *i.e.*, by shifting the reward with proper positive value b^+, we are able to initialize the Q-value network that lower-bounds the optimal Q-value.

this work, an alternative approach to have a lower bound for the optimal Q-value function is to use an appropriately shifted reward function. This idea leads to the direct application of our proposed framework in the offline setting. In general, reward shift can be plugged in many distribution-matching offline-RL algorithms [22, 45–47] to further improve the performance with conservative Q-value estimation.

Table 1 contextualizes reward shifting with respect to related works in both exploration and exploitation motivated RL algorithms.

3 A Motivating Example

We start with two intuitive remarks and a "counter-intuitive" motivating example in this section before introducing our proposed method.

Remark 1. Given an MDP $\mathcal{M} = \{\mathcal{S}, \mathcal{A}, \mathcal{T}, \mathcal{R}, \rho_0, \gamma\}$, where $|\mathcal{A}| < \infty$, scaling the reward function with linear transformation, *i.e.*, $\mathcal{R}_{k,b} = k \cdot \mathcal{R} + b, \forall k > 0, b \in \mathbb{R}$, such that $r'_t = kr_t + b \in \mathcal{R}_{k,b}$, does not change the optimal policy induced by the corresponding value function $Q_{k,b}^*(s, a) := \sum_t \gamma^t r'_t$:

$$\pi^*(s) = \arg\max_{a \in \mathcal{A}} Q_{k,b}^*(s, a) = \arg\max_{a \in \mathcal{A}} kQ^*(s, a) + \frac{b}{1-\gamma} = \arg\max_{a \in \mathcal{A}} Q^*(s, a), \quad (3)$$

Remark 2. When $|\mathcal{A}| = \infty$, scaling the reward function with linear transformation does not change the optimal policy induced by deterministic policy gradient [21], given proper learning rate $\eta' = \eta/k$:

$$\begin{aligned} \nabla_\theta J(\mu_\theta) &= \mathbb{E}_{s_t}[\nabla_a Q^*(s_t, a_t)|_{a_t = \mu_\theta(s_t)} \nabla_\theta \mu_\theta(s_t)] \\ &= \mathbb{E}_{s_t}[\nabla_a Q_{k,b}^*(s_t, a_t)|_{a_t = \mu_\theta(s_t)} \nabla_\theta \mu_\theta(s_t)]/k, \end{aligned} \quad (4)$$

Remark 1 and Remark 2 declare the fact that constant reward shifting does not affect the optimal policy induced by the optimal Q-value function. However, Figure 1 presents "counter-intuitive" results that in a demonstrative exploration task of Grid World. In this task, an agent is initialized at the upper left corner of the map need to explore the map without reward unless it reaches the goal point located at the lower right corner, where a positive reward of $+1$ will be assigned. We report learning curves with regard to episodic success rate in reaching the goal point and the learned Q-values. In this toy example, we find a negative reward shifting remarkably boosts the learning efficiency of Q-learning, and surpasses the count-based method that is classic for exploration.

Figure 3: Illustrative figure for curiosity-driven exploration with a negative shifted reward. **(a)** While adding a negative constant value b^- on the reward function leads to negatively shifted optimal Q-value function $Q^*_{b^-}$. **(b)** Minimizing the difference between a Q-value approximator and the optimal Q-value will enable calculating an upper-bound estimation for Q^*. **(c)** A positive constant shift added to the reward function can be used for conservative policy update.

Moreover, Remark 1 is empirically verified with such a toy example, *i.e.*, reward shifting does not change the optimal Q-value as well as its induced policy, but on the contrary, accelerating the learning of (near)-optimal policy.

In the following section, we will focus on the scenarios when $k = 1$ to avoid the trivial (though this can be empirically important) discussions on different learning rates. We reveal the importance of selecting the universal bias term, *i.e.*, b in the reward function, through the lens of initialization priors in function approximation. Furthermore, we show such a bias term can be utilized not only in the online RL settings to improve learning efficiency but also in the offline RL settings to conduct conservative exploitation with batched data.

4 Shifted Priors for Q-value Estimation

4.1 Reward Shift Equals to Different Initialization

We start by introducing the central idea of this work: reward shift equals different initialization. Specifically, Figure 2 illustrates the effect of the reward shifting under different settings. The black curves denote the primal optimal Q-value functions (*e.g.*, Q^*), and the red curves denote the optimal Q-value functions with shifted reward $r' = r + b^+$, where $b^+ > 0$ is a positive constant bias, and we will show a different choice of such a bias leads to a different motivation in Q-value estimation. The yellow lines denote Q-value estimators, *e.g.*, neural network predictions of the corresponding Q-values.

To summarize, shifting the reward function with a positive constant is equivalent to initializing the value function network with a smaller value. As the Q-value of unseen state-action pairs during training are much lower than the optimal value, those actions will not be selected in policy updates, leading to conservative learning behaviors that benefit policy learning in offline settings [23].

4.2 Conservative Exploitation

We begin with a natural application in the offline setting, where a policy doesn't interact with the environment and only learns through a logged data set collected from an unknown behavior policy π_β, which can either be an expert that generates high-quality solutions to the task [22, 48, 49] or a non-expert that provides actions that are sub-optimal [46, 45, 50, 49, 51] or a mixture of both [23].

Based on the idea we presented in Section 4.1, we introduce a simple yet effective approach for conservative Q-value estimation that learns to heuristically put a lower bound on the optimal Q-value function in batch settings. As shown in Figure 2(a), a positive constant b^+ added to the reward function will lead to a uniformly (positively) shifted optimal Q-value function, and the gap between the primal Q-value function and the new one is $\frac{b^+}{1-\gamma}$. Optimizing the Q-value function with logged data (*e.g.*, a fixed replay buffer) will minimize the difference between the predicted value and the optimal value with observed data. For the unobserved data point (in the state-action space $\mathcal{S} \times \mathcal{A}$), the near-zero initialization guarantees the prediction is lower than the optimal Q-value, thus conservative exploitation can be conducted with such a value function.

4.3 (Curiosity-Driven) Optimistic Exploration

On the other hand, if we shift the reward function to the negative side, it is equivalent to optimistic initialization. Figure 3 (a-b) illustrate how adding a negative bias leads to curiosity-driven exploration. With sufficiently small b^- (so that $|b^-|$ larger than the maximal value of any s, a-pair), such an upper bound of Q^* can be used to conduct curiosity-driven exploration. Intuitively, initializing a value network that predicts value larger or equal than the true value will lead to curiosity-driven exploration, as any visited state will be assigned a low value and the policy that learns to perform the action with a higher value will tend to choose novel actions.

Based on the discoveries above that (1) a positive constant shift added to the reward function can be used for conservative policy update and (2) a negative constant shift added to the reward function can be used for curiosity-driven exploration, as shown in Figure 3(b). We are ready to access both the upper bound, *i.e.*, the optimistic estimation with b^-, and the lower bound, *i.e.*, the conservative estimation with b^+ of the optimal value function. Formally, we use

$$\tilde{Q}_{\text{LB},t}(s,a) = \tilde{Q}_{b^+,t}(s,a) - \frac{b^+}{1-\gamma} \tag{5}$$

to denote the empirical lower bound of value estimation (c.f. Figure 2(d), orange line), and

$$\tilde{Q}_{\text{UB},t}(s,a) = \tilde{Q}_{b^-,t}(s,a) - \frac{b^-}{1-\gamma} \tag{6}$$

to denote the empirical upper bound of value estimation (c.f. Figure 3(b)). In both notions, t denotes the optimization step. e.g., when $t = 0$, with a near-zero initialization $\tilde{Q}_0 \approx 0$, $\tilde{Q}_{\text{LB},0}(s,a) = -\frac{b^+}{1-\gamma}$ is able to lower bound the unknown optimal Q-value given sufficiently large b^+. (c.f. Figure 2(d), green line). Similarly, Q-value is upper-bounded by $\tilde{Q}_{\text{UB},0}(s,a)$ with a sufficiently small b^-.

Following those notions, we introduce our sample-efficient algorithms for both continuous control and discrete action space respectively. We propose a practical algorithm for general continuous control in Sec. 4.3.1, while focusing on a special class of curiosity-driven exploration method, the RND [15], in Sec. 4.3.2.

4.3.1 Trading-off Exploration and Exploitation with Reward Shift

According to the principle of optimism on the face of uncertainty (OFU), an exploration bonus that manifests the uncertainty of the Q-value function can be introduced into the value estimation: the basic idea starts from integrating optimistic exploration with conservative exploitation, *i.e.*,

$$\begin{aligned}
\hat{Q}(s,a) &= \tilde{Q}_{\text{LB},t}(s,a) + \beta[\tilde{Q}_{\text{UB},t}(s,a) - \tilde{Q}_{\text{LB},t}(s,a)] \\
&= (1-\beta)(\tilde{Q}_{b^+,t}(s,a) - \frac{b^+}{1-\gamma}) + \beta(\tilde{Q}_{b^-,t}(s,a) - \frac{b^-}{1-\gamma}) \\
&= (1-\beta)\tilde{Q}_{b^+,t}(s,a) + \beta\tilde{Q}_{b^-,t}(s,a) - \frac{(1-\beta)b^+ + \beta b^-}{1-\gamma},
\end{aligned} \tag{7}$$

where the second term with coefficient β denotes exploration bonus that is composed of uncertainty.

For those under-explored state-action pairs, *i.e.*, extremely out-of-distribution samples for our neural network, both $\tilde{Q}_{b^+,t}(s,a)$ and $\tilde{Q}_{b^-,t}(s,a)$ will give near-zero predictions as a consequence of initialization (detailed implications are provided in Appendix B). Hence, the explorative bonus becomes $-\frac{(1-\beta)b^+ + \beta b^-}{1-\gamma}$. Note this is equivalent to applying another constant reward shift with value of $c_r = (1-\beta)b^+ + \beta b^-$.

Proposition 4.1. *Assuming we have access to an unbiased estimator for the optimal value function Q^*, e.g., with Monte-Carlo estimation $\hat{Q}^* = \mathbb{E}\sum_t \gamma^t r$, and the optimization is based on minimizing the MSE between the unbiased estimator and the function approximator, i.e., $\epsilon_t^2 = (\tilde{Q}_t - \hat{Q}^*)^2$, $\tilde{Q}_t = \tilde{Q}_{t-1} - 2\eta(\tilde{Q}_{t-1} - \hat{Q}^*)$, then the linear combination in Equation (7) is equivalent to a linear combination of the constants with value of $c_r = (1-\beta)b^+ + \beta b^-$.*

The proof can be found in the Appendix A. According to Proposition 4.1, a grid search for trading-off between the three hyper-parameters: the exploration bias b^-, the exploitation bias b^+ and the

coefficient β in Equation (7) is trivial as they only lead to a linear combination as $c_r = (1 - \beta)b^+ + \beta b^-$, indicating that

Corollary 4.2. *Changing the reward shifting constant b is sufficient to trade off between exploration and exploitation.*

The corollary indicates that, in principle, a meta-learner can be trained to monitor the learning process and select a proper reward shifting constant automatically [52, 53]. For the ease of exposition, in this work we choose to focus on the simplest yet effective uniform sampling strategy from multiple shift constants, which has been shown as a strong baseline of those meta-learner approaches [54, 55], and leave more complicated meta-learner-based approaches for future investigation.

Specifically, we use multiple Q-networks to learn with transition tuples (s, a, r, s') sampled from the identical buffer that collects the policy's historcal interactions with the environment. In propagating Q-values through the temporal difference loss, the primal recorded reward value r is replaced with a new reward with *different* shifted constant bias in those Q-networks. We then uniformly sample one of those learned Q-networks for the optimization of policy network (with e.g., DPG [21]). It is worth noting that our approach only requires post-hoc revision of the primal reward function, rather than interacting with the environment multiple times to collect samples for each value network. We dub the proposed method Random Reward Shift (RRS), and provide the pseudo-code in Algorithm 1 of Appendix C.2.

4.3.2 Improving Value-Based Curiosity-Driven Exploration

The discussion above casts the curiosity-driven exploration method as a special case in the *reward shift equals to initialization* perspective: exploration with RND [15] is equivalent to selecting $b^+ = 0$, *i.e.*, using the primal task reward for exploitation, and using b^- as a fixed random function over $\mathcal{S} \times \mathcal{A}$, *i.e.*, $b^-(s, a) = |\phi_{1,0}(s, a) - \phi_2(s, a)|^2, \forall s, a$, where $\phi_{1,0}$ and ϕ_2 are two neural networks with different random initializations. While $\phi_{1,0}$ is learnable, ϕ_2 is set to be fixed during learning as a random curiosity prior [24]. Without loss of generality, we can assume $\phi_2 = 1$ as a constant initialization, and $\phi_{1,0} = 0$. Then the exploration behavior is fully controlled by the scale of external reward, which is set to be 1.0 with external reward clipped to $[-1, 1]$ in [15]. The final equivalent objective in this case is to use $c_r = |\phi_{1,t}(s, a) - 1|^2, t = 0, 1, 2, \ldots$. Specially, $\phi_{1,0} = 0$ and $c_r = 1$ at beginning.

According to our analysis in the previous section, such a positive shift directly leads to conservative behaviors in Q-value estimation, therefore may hinder the exploration behaviors at the beginning, *i.e.*, when $|\phi_{1,t} - 1| \gg 0$. The exploration bonus in RND only becomes effective when visiting seldom visited states after the predictions of $\phi_{1,t}$ of frequently-visited states are close to 1, and hence encouraging stepping into those novel states and discover new knowledge. To overcome the conservative tendency induced by Q-value estimation in RND, we propose to use $b^-(s, a) = |\phi_{1,0}(s, a) - \phi_2(s, a)|^2 - I, \forall s, a$, where I is a positive constant (*e.g.*, $I = \max_{s,a} |\phi_{1,0}(s, a) - \phi_2(s, a)|^2$) that assures $b^-(s, a)$ is negative-initialized for optimistic exploratory behaviors.

It is worth noting that the curiosity introduced by exploratory bonuses like RND focuses on increasing the temporary Q-value of rarely visited states, which still relies on the visitation behavior itself in random exploration. *i.e.*, without stepping into a non-frequent visited state, the agent will never receive the novelty bonus based on the state. On the other hand, the mechanism of shifting the reward by a constant is an universal optimistic exploration bonus as the curiosity is fused into the initialization across the entire state-action support.

5 Experiments

5.1 Offline RL with Conservative Q-value Estimation

We first demonstrate the proposed method in the offline RL setting. As has been discussed in Section 4.2, shifting the primal reward function with a positive constant provides a natural way of conservative exploitation. By adding a positive reward shift, any visited (s, a) saved in the given replay buffer $\mathcal{B}$ (logged dataset) will be assigned a large reward, while under-explored (s, a) pairs remain the low values due to initialization, as illustrated in Figure 2 (d). Although in general our proposed method can be plugged in to any off-the-shelf offline RL algorithm, in this work we

Figure 4: Results on offline RL settings. We verify our key insight that a positive reward shift equals to conservative exploitation thus helps offline value estimation, while a negative reward shift leads to worse performance. Results reported are from 10 runs. Shaded areas indicate the $25\% - 75\%$ quantile value.

Figure 5: Results on continuous control tasks, the method of Random Reward Shift (RRS) outperforms its value-based baselines in most environments. Results reported are from 10 runs. Shaded areas indicate the $25\% - 75\%$ quantile value.

demonstrate the effectiveness of such a conservative Q-value estimation based on BCQ [22] and CQL [23], *i.e.*, both distribution-matching approach and conservative value estimation approaches in offline RL.

To verify our insight, we experiment with both positive reward shift (**Pos.**) and negative reward shift (**Neg.**), added on either BCQ or CQL. Figure 4 shows our experiment results. We experiment with both the dataset generated in [22] (Hopper Imitate) and the dataset used in [49] (others), and find in our experiments that learning with the CQL dataset is much more stable. The first two panels show results with BCQ as the backbone algorithm. We observe clear performance drop when training with BCQ as the policy overfits the given dataset in these settings, on the other hand, our proposed reward shift can alleviate such a problem and outperform BCQ w.r.t. both best achieved performance and convergence performance. The following three panels in Figure 4 use CQL as the backbone. In all experiments, using a positive reward shift leads to improved learning performance, while a negative reward shift leads to performance decay, as expected. Implementation details and more results can be found in Appendix C.1.

5.2   Online RL with Randomized Priors

We then conduct experiments on the online RL settings. We demonstrate our proposed method in the MuJoCo locomotion benchmarks. As our implementation is based on TD3, we use TD3-based variants as our baselines: The **TD3** is trained with default settings according to Fujimoto et al. [14]. We also include **Ensemble TD3** and **Bootstrapped TD3** as baselines due to they are similar to our work in using multiple Q-networks in value estimation. We follow Osband et al. [44] but extend it to the continuous control settings. Noting that in the continuous control setting, the argmax operator is approximated by the policy network, multiple policy networks are needed to cooperate with the multiple bootstrapped Q-value networks. Otherwise, multiple Q-value networks are not independent of each other thus breaking the condition of bootstrapped value estimation. The Ensemble TD3 presents the baseline performance when multiple Q-networks are used for value estimation in TD3, which also works as an ablation of our method when all reward shift priors are set to be 0.

As has been illustrated in Sec. 4.3.1, learning with different reward shifting values is equivalent to learning with optimistic or conservative initialization. In our method of Random Reward Shift (RRS), we use 3 Q-networks with different priors. In our experiments, we found $\pm 0.5, 0$ work universally as a default setting. Though, further investigation on hyper-parameter may help to further improve the performance.

Results are shown in Figure 5. RRS outperforms the vanilla TD3 in all five environments and outperforms all baseline methods in most tasks. In all experiments, we use 3 Q-networks for a fair comparison. Note that there is a trade-off between computational complexity and sample efficiency,

i.e., using more Q-networks may further improve the performance at the cost of more computational expensive, as reported in [44]. More implementation details, pseudo code of RRS, and ablation studies can be bound in Appendix C.2.

5.3 Optimistic Random Network Distillation

Figure 6: Value-based RND with shifted prior: Plugging the vanilla RND into DQN is not well-motivated according to our analysis in Section 4.3.2. The insight of equivalence between negative reward shifting and curiosity-driven exploration motivates us to shift the vanilla RND with a constant, which drastically improves the performance of RND when working with DQN. Results reported are from 10 runs. Shaded areas indicate the $25\% - 75\%$ quantile value.

Finally, we experiment with five discrete exploration tasks, namely the MountainCar-v0, and four navigation tasks of MiniGrid suite [56], namely the task of Empty-Random, MultiRoom, and FourRooms, to verify our insight on improving RND for value-based curiosity-driven exploration. More environment details are provided in the Appendix C.3.

We compare the vanilla **DQN**, vanilla **RND**, as well as improved DQN and RND according to our proposed insight. **DQN -0.5** indicates the results with a reward shifting of -0.5. Comparing DQN -0.5 with the vanilla DQN, our insight of negative reward shift leads to curiosity-driven exploration is again verified. **RND -1.0** indicates the results when a reward shifting of -1.0 is added to RND based on DQN. RND -1.0 improves the performance of RND and DQN in most environments, showing the effectiveness of the RND-based exploration bonus. Note that for a fair comparison, RND -1.0 should be compared with the vanilla DQN as the -1.0 reward shift just cancels the positive exploration bonus introduced by RND.

Moreover, we can further improve RND by equipping it with reward-shifting-based curiosity-driven exploration. **RND -1.5** (*i.e.*, RND with a -1.5 reward shift) can be compared with the DQN -0.5, as both receive an -0.5 exploration bonus for unseen states. We find in all experiments that our negative reward shift can remarkably improve exploration, not only working with RND to improve its performance but also working effectively in isolation. [2]

6 Conclusion

In this work, we studied how reward shifting affects policy learning in value-based deep reinforcement learning algorithms. Although constant reward shifting should not change the optimal policy induced by the optimal value function, in practice such a constant shift *does affect the function approximation*, and leads to different learning behaviors. Our detailed analysis manifests the fact that a constant reward shift is equivalent to using different initialization in the value function approximation. The proposed idea is then verified through a variety of application settings. Specifically, we show that a negative reward shift leads to curiosity-driven exploration, while a positive reward shift helps conservative exploitation. Importantly, our analysis manifests that changing reward shifting constant itself is sufficient in trading-off between exploration and exploitation. We empirically verify the effectiveness of the proposed method on a variety of experiments, including better exploitation in offline RL, sample-efficient learning in continuous control benchmarks, and enhanced curiosity-driven exploration in value-based discrete control.

While our experiments demonstrate the performance gain is quite robust to the shifting constant, we would like to point out the theoretical guidance for such a shifting constant is missing. Analysis from the perspective of optimization is an important topic, yet is left for future research as it is out of the scope of the current empirical study.

References

[1] Jette Randløv and Preben Alstrøm. Learning to drive a bicycle using reinforcement learning and shaping. In *ICML*, volume 98, pages 463–471. Citeseer, 1998.

[2] Adam Daniel Laud. *Theory and application of reward shaping in reinforcement learning*. University of Illinois at Urbana-Champaign, 2004.

[3] Oriol Vinyals, Igor Babuschkin, Wojciech M Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H Choi, Richard Powell, Timo Ewalds, Petko Georgiev, et al. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *Nature*, 575(7782):350–354, 2019.

[4] Ilge Akkaya, Marcin Andrychowicz, Maciek Chociej, Mateusz Litwin, Bob McGrew, Arthur Petron, Alex Paino, Matthias Plappert, Glenn Powell, Raphael Ribas, et al. Solving rubik's cube with a robot hand. *arXiv preprint arXiv:1910.07113*, 2019.

[5] Christopher Berner, Greg Brockman, Brooke Chan, Vicki Cheung, Przemyslaw Debiak, Christy Dennison, David Farhi, Quirin Fischer, Shariq Hashme, Chris Hesse, et al. Dota 2 with large scale deep reinforcement learning. *arXiv preprint arXiv:1912.06680*, 2019.

[6] Mahmoud Elbarbari, Kyriakos Efthymiadis, Bram Vanderborght, and Ann Nowé. Ltlf-based reward shaping for reinforcement learning. In *Adaptive and Learning Agents Workshop 2021*, 2021.

[7] Carlos Florensa, David Held, Markus Wulfmeier, Michael Zhang, and Pieter Abbeel. Reverse curriculum generation for reinforcement learning. In *Conference on robot learning*, pages 482–495. PMLR, 2017.

[8] Matthias Plappert, Marcin Andrychowicz, Alex Ray, Bob McGrew, Bowen Baker, Glenn Powell, Jonas Schneider, Josh Tobin, Maciek Chociej, Peter Welinder, et al. Multi-goal reinforcement learning: Challenging robotics environments and request for research. *arXiv preprint arXiv:1802.09464*, 2018.

[9] Andrew Y Ng, Daishi Harada, and Stuart Russell. Policy invariance under reward transformations: Theory and application to reward shaping. In *Icml*, volume 99, pages 278–287, 1999.

[10] Eric Wiewiora, Garrison W Cottrell, and Charles Elkan. Principled methods for advising reinforcement learning agents. In *Proceedings of the 20th International Conference on Machine Learning (ICML-03)*, pages 792–799, 2003.

[11] Richard S Sutton and Andrew G Barto. Reinforcement learning: An introduction. 1998.

[12] Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. *arXiv preprint arXiv:1509.02971*, 2015.

[13] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *nature*, 518(7540):529–533, 2015.

[14] Scott Fujimoto, Herke Van Hoof, and David Meger. Addressing function approximation error in actor-critic methods. *arXiv preprint arXiv:1802.09477*, 2018.

[15] Yuri Burda, Harrison Edwards, Amos Storkey, and Oleg Klimov. Exploration by random network distillation. *arXiv preprint arXiv:1810.12894*, 2018.

[16] John Schulman, Sergey Levine, Pieter Abbeel, Michael Jordan, and Philipp Moritz. Trust region policy optimization. In *International conference on machine learning*, pages 1889–1897, 2015.

[17] John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

[18] Karl W Cobbe, Jacob Hilton, Oleg Klimov, and John Schulman. Phasic policy gradient. In *International Conference on Machine Learning*, pages 2020–2027. PMLR, 2021.

[19] Ziyu Wang, Victor Bapst, Nicolas Heess, Volodymyr Mnih, Remi Munos, Koray Kavukcuoglu, and Nando de Freitas. Sample efficient actor-critic with experience replay. *arXiv preprint arXiv:1611.01224*, 2016.

[20] Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. *arXiv preprint arXiv:1801.01290*, 2018.

[21] David Silver, Guy Lever, Nicolas Heess, Thomas Degris, Daan Wierstra, and Martin Riedmiller. Deterministic policy gradient algorithms. In *International conference on machine learning*, pages 387–395. PMLR, 2014.

[22] Scott Fujimoto, David Meger, and Doina Precup. Off-policy deep reinforcement learning without exploration. *arXiv preprint arXiv:1812.02900*, 2018.

[23] Homanga Bharadhwaj, Aviral Kumar, Nicholas Rhinehart, Sergey Levine, Florian Shkurti, and Animesh Garg. Conservative safety critics for exploration. *arXiv preprint arXiv:2010.14497*, 2020.

[24] Ian Osband, John Aslanides, and Albin Cassirer. Randomized prior functions for deep reinforcement learning. In *Advances in Neural Information Processing Systems*, pages 8617–8629, 2018.

[25] Tabish Rashid, Bei Peng, Wendelin Boehmer, and Shimon Whiteson. Optimistic exploration even with a pessimistic initialisation. *arXiv preprint arXiv:2002.12174*, 2020.

[26] Kamil Ciosek, Quan Vuong, Robert Loftin, and Katja Hofmann. Better exploration with optimistic actor critic. In *Advances in Neural Information Processing Systems*, pages 1785–1796, 2019.

[27] Marc Bellemare, Sriram Srinivasan, Georg Ostrovski, Tom Schaul, David Saxton, and Remi Munos. Unifying count-based exploration and intrinsic motivation. *Advances in neural information processing systems*, 29:1471–1479, 2016.

[28] Georg Ostrovski, Marc G Bellemare, Aäron Oord, and Rémi Munos. Count-based exploration with neural density models. In *International conference on machine learning*, pages 2721–2730. PMLR, 2017.

[29] Haoran Tang, Rein Houthooft, Davis Foote, Adam Stooke, Xi Chen, Yan Duan, John Schulman, Filip De Turck, and Pieter Abbeel. # exploration: A study of count-based exploration for deep reinforcement learning. In *31st Conference on Neural Information Processing Systems (NIPS)*, volume 30, pages 1–18, 2017.

[30] Leshem Choshen, Lior Fox, and Yonatan Loewenstein. Dora the explorer: Directed outreaching reinforcement action-selection. *arXiv preprint arXiv:1804.04012*, 2018.

[31] Rein Houthooft, Xi Chen, Yan Duan, John Schulman, Filip De Turck, and Pieter Abbeel. Variational information maximizing exploration. 2016.

[32] Deepak Pathak, Pulkit Agrawal, Alexei A Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pages 16–17, 2017.

[33] Yuri Burda, Harri Edwards, Deepak Pathak, Amos Storkey, Trevor Darrell, and Alexei A Efros. Large-scale study of curiosity-driven learning. *arXiv preprint arXiv:1808.04355*, 2018.

[34] Junhyuk Oh, Yijie Guo, Satinder Singh, and Honglak Lee. Self-imitation learning. *arXiv preprint arXiv:1806.05635*, 2018.

[35] Adrien Ecoffet, Joost Huizinga, Joel Lehman, Kenneth O Stanley, and Jeff Clune. Go-explore: a new approach for hard-exploration problems. *arXiv preprint arXiv:1901.10995*, 2019.

[36] Hao Sun, Zhizhong Li, Xiaotong Liu, Bolei Zhou, and Dahua Lin. Policy continuation with hindsight inverse dynamics. In *Advances in Neural Information Processing Systems*, pages 10265–10275, 2019.

[37] Benjamin Eysenbach, Abhishek Gupta, Julian Ibarz, and Sergey Levine. Diversity is all you need: Learning skills without a reward function. *arXiv preprint arXiv:1802.06070*, 2018.

[38] Archit Sharma, Shixiang Gu, Sergey Levine, Vikash Kumar, and Karol Hausman. Dynamics-aware unsupervised discovery of skills. *arXiv preprint arXiv:1907.01657*, 2019.

[39] Ronen I Brafman and Moshe Tennenholtz. R-max-a general polynomial time algorithm for near-optimal reinforcement learning. *Journal of Machine Learning Research*, 3(Oct):213–231, 2002.

[40] Thomas Jaksch, Ronald Ortner, and Peter Auer. Near-optimal regret bounds for reinforcement learning. *Journal of Machine Learning Research*, 11(Apr):1563–1600, 2010.

[41] Mohammad Gheshlaghi Azar, Ian Osband, and Rémi Munos. Minimax regret bounds for reinforcement learning. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pages 263–272. JMLR. org, 2017.

[42] Chi Jin, Zeyuan Allen-Zhu, Sebastien Bubeck, and Michael I Jordan. Is q-learning provably efficient? In *Advances in Neural Information Processing Systems*, pages 4863–4873, 2018.

[43] Chen Tessler, Guy Tennenholtz, and Shie Mannor. Distributional policy optimization: An alternative approach for continuous control. *arXiv preprint arXiv:1905.09855*, 2019.

[44] Ian Osband, Charles Blundell, Alexander Pritzel, and Benjamin Van Roy. Deep exploration via bootstrapped dqn. In *Advances in neural information processing systems*, pages 4026–4034, 2016.

[45] Aviral Kumar, Justin Fu, George Tucker, and Sergey Levine. Stabilizing off-policy q-learning via bootstrapping error reduction. *arXiv preprint arXiv:1906.00949*, 2019.

[46] Yifan Wu, George Tucker, and Ofir Nachum. Behavior regularized offline reinforcement learning. *arXiv preprint arXiv:1911.11361*, 2019.

[47] Noah Y Siegel, Jost Tobias Springenberg, Felix Berkenkamp, Abbas Abdolmaleki, Michael Neunert, Thomas Lampe, Roland Hafner, Nicolas Heess, and Martin Riedmiller. Keep doing what worked: Behavioral modelling priors for offline reinforcement learning. *arXiv preprint arXiv:2002.08396*, 2020.

[48] Chi Zhang, Sanmukh Rao Kuppannagari, and Viktor Prasanna. Brac+: Going deeper with behavior regularized offline reinforcement learning. 2020.

[49] Justin Fu, Aviral Kumar, Ofir Nachum, George Tucker, and Sergey Levine. D4rl: Datasets for deep data-driven reinforcement learning. *arXiv preprint arXiv:2004.07219*, 2020.

[50] Rishabh Agarwal, Dale Schuurmans, and Mohammad Norouzi. An optimistic perspective on offline reinforcement learning. In *International Conference on Machine Learning*, pages 104–114. PMLR, 2020.

[51] Daniel Jarrett, Alihan Hüyük, and Mihaela Van Der Schaar. Inverse decision modeling: Learning interpretable representations of behavior. In *International Conference on Machine Learning*, pages 4755–4771. PMLR, 2021.

[52] Yan Duan, John Schulman, Xi Chen, Peter L Bartlett, Ilya Sutskever, and Pieter Abbeel. Rl2: Fast reinforcement learning via slow reinforcement learning. *arXiv preprint arXiv:1611.02779*, 2016.

[53] Rémy Portelas, Cédric Colas, Katja Hofmann, and Pierre-Yves Oudeyer. Teacher algorithms for curriculum learning of deep rl in continuously parameterized environments. In *Conference on Robot Learning*, pages 835–853. PMLR, 2020.

[54] Alex Graves, Marc G Bellemare, Jacob Menick, Remi Munos, and Koray Kavukcuoglu. Automated curriculum learning for neural networks. In *international conference on machine learning*, pages 1311–1320. PMLR, 2017.

[55] Tambet Matiisen, Avital Oliver, Taco Cohen, and John Schulman. Teacher–student curriculum learning. *IEEE transactions on neural networks and learning systems*, 31(9):3732–3740, 2019.

[56] Maxime Chevalier-Boisvert, Lucas Willems, and Suman Pal. Minimalistic gridworld environment for openai gym. `https://github.com/maximecb/gym-minigrid`, 2018.