To Answer or to Abstain: Mitigating Search-Agent Hallucinations via Abstention-Aware Reinforcement Learning

Abstract

Recent advances in equipping Large Language Models (LLMs) with search tools and outcome-reward reinforcement learning (RL) have achieved new state-of-the-art results on open-domain QA tasks. However, we argue that current training paradigms harbor a critical vulnerability: they predominantly reward correct answers but fail to penalize fabricated ones when retrieval fails, thereby implicitly exacerbating hallucinations. To address this, we propose Abstention-Aware Reinforcement Learning (`AWA-RL`), which dynamically shapes the abstention reward utilizing the model's query-specific prior capabilities and continuous on-policy training observations. We also introduce a novel metric, `RA-F1`, to measure the capability-reliability trade-off. Compared to non-abstaining baselines, `AWA-RL` boosts absolute precision by up to 10.3% and overall `RA-F1` by 2.9%, with only marginal sacrifice in raw accuracy. These results confirm that `AWA-RL` successfully yields highly capable and reliable search agents.

1 Introduction

Hallucination remains a long-standing and notoriously difficult challenge in LLMs. It is challenging to ensure the factual grounding of generated output. (Bang et al., 2025; Kalai et al., 2025) A prevailing approach to mitigating hallucinations is providing sufficient context to ground the answers. Progressing from early Retrieval-Augmented Generation methods, (Agrawal et al., 2024; Béchard and Ayala, 2024) recent advancements have introduced more advanced search agents. (Li et al., 2025b,a) By leveraging outcome-reward RL, these agents learn to interact with search environments iteratively to arrive at ground-truth answers.

However, this training paradigm harbors a critical vulnerability: current RL objectives predominantly incentivize models to output the correct answer, but lack a mechanism to reward abstention. (Jin et al., 2025) Consequently, when an agent encounters queries beyond its capability boundaries or fails to retrieve sufficient evidence, it tends to fabricate an answer rather than safely abstain. This "over-answering" phenomenon could exacerbate hallucinations. (Song et al., 2025) The critical research question thus arises: *How can we equip search agents with the self-awareness to recognize their capability boundaries and confidently abstain from ungrounded answers?*

Learning to abstain is a non-trivial objective. Existing abstention-related studies (Xu et al., 2024b; Song et al., 2025; Zhou et al., 2026; Zheng et al., 2025; Xu et al., 2024a) primarily suffer from three major limitations[1]: (1) *Mismatched Scenarios*: They predominantly focus on single-turn QA rather than multi-turn agentic settings, where capability boundaries dynamically shift based on tool-use and search results. (2) *Degradation of Capabilities*: Most approaches employ post-hoc pipeline training, which first trains for capability, then tunes for abstention. This disconnected process often severely compromises the model's original search and reasoning abilities. (3) *Reliance on Heuristics*: They heavily rely on synthesizing new unanswerable datasets, which inevitably introduces human heuristics that fail to generalize across models with varying intrinsic capabilities.

To address these challenges, we propose **`AWA-RL`** (**A**bstention-a**WA**re **R**einforcement **L**earning). The core intuition behind `AWA-RL` is that the incentive to abstain should not be a universal constant but rather dynamically calibrated to the model's intrinsic problem-solving capability for each specific query. At a high level, we first estimate the model's prior success rate for a given question to establish a query-aware refusal baseline. Second, to counteract the agent's natural bias toward premature "lazy

---

[1]Detailed discussions on related works in Appendix A.

refusal", we introduce a non-linear optimistic mapping controlled by a single, explainable "courage" factor. Finally, during the RL training phase, we continuously monitor the deviation between the agent's actual abstention behavior and the initial capability estimate, dynamically updating the abstention reward in real time.

Through extensive experiments, we reveal exactly why conventional, intuitive approaches fail to establish a reliable capability-reliability boundary. First, simply manipulating data proportions, such as injecting unanswerable queries or refusal trajectories into the training data, results in highly unpredictable behavior. Second, applying a static refusal reward acts as a blunt instrument that ignores query difficulty variance. Especially in RL from scratch settings, even a minimal static reward triggers catastrophic reward hacking.

In contrast, `AWA-RL` cleanly overcomes these limitations. Compared to standard non-abstaining RL baselines, our method dramatically boosts absolute precision by up to 10.3% and improves overall `RA-F1` by 5.2%, at the cost of only a marginal drop in raw accuracy. Crucially, empirical results confirm that the "courage" factor is remarkably easy to tune, and the policy's abstention behavior is highly responsive to its adjustments. In conclusion, the dynamic reward mechanism of `AWA-RL` provides a vastly more robust and scalable pathway toward genuinely reliable search agents.

2 Methodology

2.1 Task Formulation

We formulate agentic-search-based QA as an interactive decision-making process. Given a query $q \in \mathcal{Q}$, the agent policy π_θ iteratively retrieve evidence. The process terminates with a final output $y \in \mathcal{A} \cup \{\perp\}$, where $\mathcal{A}$ is the space of valid answers and $\perp$ denotes the abstention or refusal action (e.g., outputting "not enough information" when evidence is insufficient).

2.2 Outcome-Reward RL Preliminaries

SOTA search agents are predominantly trained using outcome-reward RL, optionally preceded by cold-start SFT. During RL, the environment provides a sparse binary reward $R(y, y^*) \in \{0, 1\}$, indicating whether the final answer y matches the ground truth y^*. We adopt Group Relative Policy Optimization (GRPO) (Shao et al., 2024) to update π_θ. For each q, GRPO samples a group of G trajectories and optimizes the policy using the relative advantage A_i, computed by normalizing the outcome rewards within the group.

2.3 `AWA-RL`: Abstention-Aware RL

The standard binary reward paradigm fundamentally fails to supervise the abstention action $\perp$. To address this and explicitly optimize the capability-reliability trade-off, `AWA-RL` reformulates the final environment reward $R(y, y^*, q_i)$ provided to the GRPO algorithm. We unify the reward structure by introducing a dynamically adjusted refusal reward $r_{ref}(q_i)$ specifically for abstention:

$$R(y, y^*, q_i) = \begin{cases} 1, \text{if } y = y^* \text{ (Correct)} \\ 0, \text{if } y \neq y^* \text{ and } y \neq \perp \text{ (Incorrect)} \\ r_{ref}(q_i), \text{if } y = \perp \text{ (Abstention)} \end{cases}$$

To effectively calibrate the model's confidence and maintain intra-batch variance for stable RL updates, $r_{ref}(q_i)$ must account for both the intrinsic difficulty of the specific query and the real-time training dynamics. Therefore, we decompose $r_{ref}(q_i)$ into a query-aware base reward and a batch-level dynamic penalty:

$$r_{ref}(q_i) = R_{base}(q_i) - P(E_t)$$

where $R_{base}(q_i)$ establishes a refusal boundary based on the model's estimated capability, and $P(E_t)$ acts as a dynamic stabilizer to correct empirical over-or under-refusal during the RL rollout.

Estimating the Base Refusal Reward (R_{base}). Before abstention-aware RL training, we gauge the model's baseline capability by evaluating a standard, abstain-free checkpoint to compute the estimated correctness probability $p_i = P(y = y^*|q_i)$ for each training query q_i. To prevent premature abstention on inherently difficult questions, we apply a lower bound clip $p_{clip} = \max(p_i, \epsilon_1)$ (e.g., $\epsilon_1 = 0.05$). Furthermore, because executing a multi-step search is computationally and logically harder than simply generating a refusal token, models are naturally biased toward "lazy refusal." To explicitly counteract this inertia and encourage search exploration, we apply a non-linear transformation $p_i^* = (p_{clip})^\gamma$. $\gamma \in (0, 1]$ is the "courage" factor, which scales the model's confidence. The query-specific base refusal reward is then defined as $R_{base}(q_i) = 1 - p_i^*$. This creates a theoretical equilibrium: for queries with high estimated

capability, the expected reward of attempting an answer (p_i^*) mathematically exceeds that of refusing ($1 - p_i^*$), actively driving the agent to answer.

Computing the Dynamic Penalty ($P(E_t)$). During the RL phase, the empirical refusal rate naturally fluctuates and may deviate from the theoretical expectation. To compute the penalty $P(E_t)$, we first define the expected batch-level refusal rate as $\mu_{ref} = 1 - \frac{1}{B}\sum_{i=1}^{B} p_i^*$, where B is the batch size. To avoid division by zero and unbounded penalties, we clip this expectation to $\mu_{clip} = \max(\mu_{ref}, \epsilon_2)$ (e.g., $\epsilon_2 = 0.05$). We then define the batch-level excess refusal rate E_t at training step t as:

$$E_t = \frac{\hat{\mu}_{ref} - \mu_{clip}}{\mu_{clip}}$$

where $\hat{\mu}_{ref} \in [0, 1]$ is the empirical mean refusal rate of the current rollout batch. Consequently, E_t is strictly bounded within $[-1, E_{max}]$, where the upper bound $E_{max} = (1 - \mu_{clip})/\mu_{clip}$.

To penalize policy collapse and guide the model back to optimal boundaries, we dynamically adjust the final refusal reward $r_{ref} \in [-1, 1]$ via a piecewise penalty function $P(E_t)$. This function is designed such that severe over-refusal ($E_t \to E_{max}$) pushes $r_{ref} \to -1$, while severe under-refusal ($E_t \to -1$) pushes $r_{ref} \to 1$:

$$P(E_t) = \begin{cases} \frac{E_t}{E_{max}} \cdot (R_{base}(q_i) + 1), & \text{if } E_t \geq 0 \\ E_t \cdot (1 - R_{base}(q_i)), & \text{if } E_t < 0 \end{cases}$$

By subtracting this penalty from R_{base}, our framework ensures that the policy dynamically self-corrects while honoring the query-specific capability estimation.

In addition to reward shaping, we apply several training recipes to stabilize general RL training. More details can be found in Appendix B.

3 Experimental Setup

Datasets & Implementaion Details. We evaluate on three challenging multi-hop QA benchmarks: HotpotQA (Yang et al., 2018), 2WikiMulti-HopQA (Ho et al., 2020), and MuSiQue (Trivedi et al., 2022). Our primary experiments utilize Qwen2.5-7B-Instruct (Yang et al., 2024) as the base model. To establish the cold-start setting, the model is first fine-tuned on 5,000 search-augmented reasoning trajectories generated by a stronger teacher model (GPT-oss-120b). This bootstraps the agent's initial multi-step search capabilities while preserving sufficient action-space entropy. Subsequently, we conduct reinforcement learning via GRPO on 5,000 filtered queries sampled from the training splits. The agent interacts with a standard Wikipedia search environment. During the RL phase, we employ GPT-oss-120b as the external LLM judge to automatically evaluate both final answer correctness and intermediate citation quality. More implementation details can be found in Appendix C.

Evaluation Metrics. To comprehensively assess the capability-reliability trade-off, let N_c, N_r, and N_w denote the number of correct, refused (abstained), and wrong responses, respectively, where $N_{total} = N_c + N_r + N_w$. Following the evaluation principles of Xu et al. (2024b), we measure policy performance using three metrics. **Accuracy (Acc)**, defined as N_c/N_{total}, evaluates the model's overall helpfulness and serves as our Recall. **Precision (Prec)**, computed as $N_c/(N_c + N_w)$, reflects the model's self-knowledge by measuring correctness strictly when it chooses to answer. Finally, we introduce **Reliability-Aware F1 (RA-F1)**. Calculated as the harmonic mean of Precision and Accuracy (RA-F1 $= 2 \cdot \text{Prec} \cdot \text{Acc}/(\text{Prec} + \text{Acc})$), this single metric holistically captures the optimal balance between answering confidently and abstaining safely.

Baselines. We compare AWA-RL against three representative abstention paradigms. **SFT-Mixed** injects 10%–30% teacher-generated refusal trajectories into the SFT data to test supervised elicitation. **RL-Unanswerable** mixes 10%–30% inherently unanswerable queries into the RL training set, optimizing via standard binary-reward GRPO. Finally, **Static Reward** applies RL with a fixed refusal reward r_{ref} (e.g., 0.5 or 0.9), explicitly discouraging answers unless the model's confidence exceeds this static threshold.

4 Experimental Results

In this section, we evaluate the capability-reliability trade-off. Due to space constraints, averaged metrics across our three benchmarks are reported here (see Appendix F and E for per-dataset breakdowns and rollout cases).

Failures of Conventional Baselines. Tables 1 and 2 demonstrate that static training paradigms fail to establish a reliable abstention boundary. First, manually manipulating data proportions yields

Table 1: Performance with injected refusal or unanswerable data.

Ratio	Acc	Refuse	Prec	RA-F1
SFT with XX% refusal trajectories				
0%	0.530	0.000	0.530	0.530
10%	0.525	0.109	0.593	0.555
20%	0.512	0.131	0.595	0.548
30%	0.505	0.107	0.570	0.534
RL from scratch with XX% unanswerable questions				
0%	0.472	0.005	0.474	0.473
10%	0.483	0.060	0.510	0.496
20%	0.425	0.293	0.578	0.487
30%	0.305	0.522	0.588	0.394
Cold-start RL with XX% unanswerable questions				
0%	0.544	0.002	0.545	0.545
10%	0.545	0.001	0.545	0.545
20%	0.551	0.004	0.553	0.552
30%	0.557	0.018	0.567	0.562

Table 2: Performance under a static refusal reward (r_{ref}).

r_{ref}	Acc	Refuse	Prec	RA-F1
RL from scratch with Static Refusal Reward				
0.00	0.493	0.017	0.500	0.496
0.05	0.000	0.999	0.000	0.000
0.10	0.000	0.999	0.000	0.000
0.20	0.000	0.921	0.000	0.000
Cold-start RL with Static Refusal Reward				
0.00	0.552	0.012	0.559	0.556
0.20	0.488	0.239	0.649	0.553
0.40	0.469	0.338	0.708	0.561
0.60	0.438	0.421	0.750	0.550
0.80	0.426	0.441	0.747	0.540

Table 3: Performance of AWA-RL under varying "courage" factor.

γ	Acc	Refuse	Prec	RA-F1
AWA-RL *from scratch with varying encouragement*				
1.00	0.322	0.360	0.475	0.381
0.50	0.381	0.395	0.605	0.459
0.25	0.441	0.269	0.581	0.499
0.20	0.459	0.246	0.591	**0.515**
0.125	0.487	0.104	0.537	0.511
0.00	0.493	0.017	0.500	0.496
Cold-start AWA-RL *with varying encouragement*				
1.00	0.458	0.383	0.738	0.561
0.50	0.484	0.306	0.699	0.568
0.25	0.509	0.225	0.664	0.573
0.20	0.529	0.192	0.662	**0.585**
0.125	0.545	0.125	0.628	0.582
0.00	0.552	0.012	0.559	0.556

Figure 1: Training dynamics of batch refusal ratios over 90 GRPO steps under different γ settings.

highly unpredictable behaviors. SFT alone struggles to internalize abstention boundaries (refusal rates stagnate around 10-13%). During RL, data manipulation triggers either a "lazy refusal" collapse (e.g., 52.2% refusal from scratch) or stubborn overconfidence (ignoring unanswerable queries in cold-start). Second, applying a static refusal reward (r_{ref}) acts as a blunt instrument. In from-scratch RL, even a marginal $r_{ref} = 0.05$ causes catastrophic reward hacking (99.9% refusal). In cold-start settings, scaling r_{ref} forces a rigid zero-sum trade-off: Precision improves at the severe expense of Accuracy (Recall).

AWA-RL Achieves Optimal and Stable Balance. In contrast, AWA-RL cleanly resolves these limitations by dynamically anchoring rewards to query-specific prior capabilities (Table 3). The "courage" factor γ serves as a highly responsive dial for confidence mapping. At the optimal "sweet spot" ($\gamma = 0.2$), AWA-RL achieves optimal balances in both RL settings. Especially for the cold-started policy, AWA-RL hits a state-of-the-art RA-F1 of 0.585, boosting Precision from 0.559 to 0.662 with only a marginal drop in Accuracy (0.552 to 0.529), break-

ing the zero-sum constraints of static rewards. Furthermore, AWA-RL yields remarkably stable training dynamics (Figure 1). Instead of wild oscillations or rapid reward hacking, the batch-level refusal rates smoothly converge to distinct, predictable plateaus within 20-30 steps corresponding to γ. This confirms that our dynamic reward formulation provides a robust, scalable, and controllable pathway to reliably self-aware agents.

5 Conclusion

We introduced AWA-RL to resolve the critical capability-reliability trade-off in LLM agents. While conventional methods, such as data manipulation or static rewards, inevitably trigger stubborn overconfidence or catastrophic reward hacking, AWA-RL dynamically anchors the refusal reward to the model's query-specific prior capabilities. Controlled by a single, highly responsive "courage" factor (γ), our framework successfully decouples capability acquisition from abstention calibration. By maximizing overall system utility (RA-F1), AWA-RL provides a robust and scalable pathway toward genuinely reliable search agents.

Limitations

While `AWA-RL` demonstrates significant improvements in optimizing the capability-reliability trade-off, we acknowledge a few limitations that pave the way for future research.

Scale and Task Modality. Our current empirical evaluations are primarily focused on the `Qwen2.5-7B-Instruct` model and multi-hop agentic search QA tasks. Although the theoretical formulation of our dynamic reward shaping is inherently model-agnostic and broadly applicable to general agentic RL domains (e.g., complex tool-use, mathematical reasoning, and coding), scaling the validation to larger foundational models and a wider spectrum of task modalities remains an important next step to confirm its universal efficacy.

Dependence on the Courage Factor. `AWA-RL` successfully distills the complex balance between answering and abstaining into a single, intuitive hyperparameter: the courage factor γ. As demonstrated in our training dynamics, the policy is highly responsive to γ, making it practically straightforward to tune. Nevertheless, identifying the strictly optimal value still requires empirical adjustments based on specific dataset difficulties and model initializations. Our future research will explore fully end-to-end, adaptive mechanisms that can auto-calibrate this confidence mapping without human intervention.

Computational Overhead for Prior Estimation. Establishing the optimal base refusal reward (R_{base}) requires a preliminary inference pass over the training set to calculate the prior success rate (p_i). While this offline sampling introduces an initial computational cost, we argue it is a highly worthwhile trade-off: it provides the most faithful and unbiased estimation of the model's intrinsic capabilities, which is the cornerstone for precise refusal boundary control during RL. Still, developing sample-free or computationally lighter proxy metrics to estimate model capability presents an exciting avenue for subsequent optimization.

Ethical Considerations

Our work primarily contributes to the safety and reliability of Large Language Models by explicitly training them to abstain from answering when sufficient evidence is lacking. By addressing the capability-reliability trade-off in agentic QA systems, our `AWA-RL` framework directly mitigates the risks of hallucination and overconfident factual errors, which is a crucial step toward deploying trustworthy AI in real-world scenarios.

Despite these positive impacts, several ethical implications warrant careful consideration:

Disparities in Abstention. In our framework, the abstention boundary is intrinsically anchored to the model's prior capability estimation (p_i). It is well-documented that pre-trained language models often exhibit performance disparities, generally performing worse on topics related to underrepresented demographics, minority cultures, or low-resource languages. Consequently, our dynamic reward shaping might disproportionately encourage the agent to refuse queries from these marginalized domains. While abstaining is safer than hallucinating, this behavior could inadvertently exacerbate inequalities in information access, as users querying non-mainstream topics might consistently receive "not enough information" responses.

Bias in External Knowledge and Evaluators. Our agent's search and reasoning capabilities are optimized interacting with an external corpus (e.g., Wikipedia) and supervised by an LLM-based judge for citation rewards. Any inherent biases, historical prejudices, or misinformation embedded within the retrieval environment can shape the agent's definition of "truth." Furthermore, LLM judges may harbor implicit preferences for certain linguistic styles or mainstream viewpoints. If the judge incorrectly penalizes valid but minority perspectives, the policy might learn to improperly reject valid queries or confidently output biased information.

Future deployments of abstention-aware agents should pair our dynamic reward mechanisms with rigorous bias audits, ensuring equitable capability expansion across diverse user groups and topics.

References

Garima Agrawal, Tharindu Kumarage, Zeyad Alghamdi, and Huan Liu. 2024. Can knowledge graphs reduce hallucinations in llms?: A survey. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 3947–3960.

Yejin Bang, Ziwei Ji, Alan Schelten, Anthony Hartshorn, Tara Fowler, Cheng Zhang, Nicola Cancedda, and Pascale Fung. 2025. Hallulens: Llm hallucination benchmark. In *Proceedings of the 63rd*

Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 24128–24156.

Patrice Béchard and Orlando Marquez Ayala. 2024. Reducing hallucination in structured outputs via retrieval-augmented generation. *arXiv preprint arXiv:2404.08189*.

Zheng Chu, Xiao Wang, Jack Hong, Huiming Fan, Yuqi Huang, Yue Yang, Guohai Xu, Chenxiao Zhao, Cheng Xiang, Shengchao Hu, and 1 others. 2026. Redsearcher: A scalable and cost-efficient framework for long-horizon search agents. *arXiv preprint arXiv:2602.14234*.

Matthijs Douze, Alexandr Guzhva, Chengqi Deng, Jeff Johnson, Gergely Szilvasy, Pierre-Emmanuel Mazaré, Maria Lomeli, Lucas Hosseini, and Hervé Jégou. 2024. The faiss library.

Tianyu Fan, Xinyao Niu, Yuxiang Zheng, Fengji Zhang, Chengen Huang, Bei Chen, Junyang Lin, and Chao Huang. 2025. Understanding deepresearch via reports. *arXiv preprint arXiv:2510.07861*.

Jiazhan Feng, Shijue Huang, Xingwei Qu, Ge Zhang, Yujia Qin, Baoquan Zhong, Chengquan Jiang, Jinxin Chi, and Wanjun Zhong. 2025. Retool: Reinforcement learning for strategic tool use in llms. *arXiv preprint arXiv:2504.11536*.

Jujie He, Jiacai Liu, Chris Yuhao Liu, Rui Yan, Chaojie Wang, Peng Cheng, Xiaoyu Zhang, Fuxiang Zhang, Jiacheng Xu, Wei Shen, and 1 others. 2025. Skywork open reasoner 1 technical report. *arXiv preprint arXiv:2505.22312*.

Xanh Ho, Anh-Khoa Duong Nguyen, Saku Sugawara, and Akiko Aizawa. 2020. Constructing a multi-hop qa dataset for comprehensive evaluation of reasoning steps. In *Proceedings of the 28th International Conference on Computational Linguistics*, pages 6609–6625.

Chen Hu, Haikuo Du, Heng Wang, Lin Lin, Mingrui Chen, Peng Liu, Ruihang Miao, Tianchi Yue, Wang You, Wei Ji, and 1 others. 2025. Step-deepresearch technical report. *arXiv preprint arXiv:2512.20491*.

Bowen Jin, Hansi Zeng, Zhenrui Yue, Jinsung Yoon, Sercan Arik, Dong Wang, Hamed Zamani, and Jiawei Han. 2025. Search-r1: Training llms to reason and leverage search engines with reinforcement learning. *arXiv preprint arXiv:2503.09516*.

Adam Tauman Kalai, Ofir Nachum, Santosh S Vempala, and Edwin Zhang. 2025. Why language models hallucinate. *arXiv preprint arXiv:2509.04664*.

Polina Kirichenko, Mark Ibrahim, Kamalika Chaudhuri, and Samuel J Bell. 2025. Abstentionbench: Reasoning llms fail on unanswerable questions. *arXiv preprint arXiv:2506.09038*.

Baixuan Li, Bo Zhang, Dingchu Zhang, Fei Huang, Guangyu Li, Guoxin Chen, Huifeng Yin, Jialong Wu, Jingren Zhou, and 1 others. 2025a. Tongyi deepresearch technical report. *arXiv preprint arXiv:2510.24701*.

Xiaoxi Li, Guanting Dong, Jiajie Jin, Yuyao Zhang, Yujia Zhou, Yutao Zhu, Peitian Zhang, and Zhicheng Dou. 2025b. Search-o1: Agentic search-enhanced large reasoning models. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 5420–5438.

Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Eric Hambro, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. 2023. Toolformer: Language models can teach themselves to use tools. *Advances in neural information processing systems*, 36:68539–68551.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Yang Wu, and 1 others. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*.

Linxin Song, Taiwei Shi, and Jieyu Zhao. 2025. The hallucination tax of reinforcement finetuning. *arXiv preprint arXiv:2505.13988*.

Zhengwei Tao, Jialong Wu, Wenbiao Yin, Junkai Zhang, Baixuan Li, Haiyang Shen, Kuan Li, Liwen Zhang, Xinyu Wang, Yong Jiang, and 1 others. 2025. Webshaper: Agentically data synthesizing via information-seeking formalization. *arXiv preprint arXiv:2507.15061*.

MiroMind Team, Song Bai, Lidong Bing, Carson Chen, Guanzheng Chen, Yuntao Chen, Zhe Chen, Ziyi Chen, Jifeng Dai, Xuan Dong, and 1 others. 2025. Mirothinker: Pushing the performance boundaries of open-source research agents via model, context, and interactive scaling. *arXiv preprint arXiv:2511.11793*.

Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. 2022. Musique: Multihop questions via single-hop question composition. *Transactions of the Association for Computational Linguistics*, 10:539–554.

Liang Wang, Nan Yang, Xiaolong Huang, Binxing Jiao, Linjun Yang, Daxin Jiang, Rangan Majumder, and Furu Wei. 2022. Text embeddings by weakly-supervised contrastive pre-training. *arXiv preprint arXiv:2212.03533*.

Hongshen Xu, Zichen Zhu, Lei Pan, Zihan Wang, Su Zhu, Da Ma, Ruisheng Cao, Lu Chen, and Kai Yu. 2024a. Reducing tool hallucination via reliability alignment. *arXiv preprint arXiv:2412.04141*.

Hongshen Xu, Zichen Zhu, Situo Zhang, Da Ma, Shuai Fan, Lu Chen, and Kai Yu. 2024b. Rejection improves reliability: Training llms to refuse unknown

questions using rl from knowledge feedback. *arXiv preprint arXiv:2403.18349*.

Ikuya Yamada, Wataru Ikeda, Ko Yoshida, Mengyu Ye, Hinata Sugimoto, Masatoshi Suzuki, Hisanori Ozaki, and Jun Suzuki. 2025. An open and reproducible deep research agent for long-form question answering. *arXiv preprint arXiv:2512.13059*.

Qwen An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Guanting Dong, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxin Yang, Jingren Zhou, Junyang Lin, and 25 others. 2024. Qwen2.5 technical report. *ArXiv*, abs/2412.15115.

Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William Cohen, Ruslan Salakhutdinov, and Christopher D Manning. 2018. Hotpotqa: A dataset for diverse, explainable multi-hop question answering. In *Proceedings of the 2018 conference on empirical methods in natural language processing*, pages 2369–2380.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik R Narasimhan, and Yuan Cao. 2022. React: Synergizing reasoning and acting in language models. In *The eleventh international conference on learning representations*.

Fengji Zhang, Xinyao Niu, Chengyang Ying, Guancheng Lin, Zhongkai Hao, Zhou Fan, Chengen Huang, Jacky Keung, Bei Chen, and Junyang Lin. 2025. A2search: Ambiguity-aware question answering with reinforcement learning. *arXiv preprint arXiv:2510.07958*.

Hang Zheng, Hongshen Xu, Yuncong Liu, Lu Chen, Pascale Fung, and Kai Yu. 2025. Enhancing llm reliability via explicit knowledge boundary modeling. *arXiv preprint arXiv:2503.02233*.

Xinyu Zhou, Chang Jin, Carsten Eickhoff, Zhijiang Guo, and Seyed Ali Bahrainian. 2026. When silence is golden: Can llms learn to abstain in temporal qa and beyond? *arXiv preprint arXiv:2602.04755*.

Appendix

A Related Work

Agentic Search for Open-domain QA. Recent progress in open-domain QA has increasingly shifted from one-shot retrieval-augmented generation to *agentic search*, where LLMs interleave reasoning with explicit actions such as query reformulation, retrieval, and evidence integration. Early paradigms such as ReAct (Yao et al., 2022) and Toolformer (Schick et al., 2023) established the value of coupling reasoning with external actions and tool use, showing that iterative interaction with external knowledge sources can substantially improve factuality and task performance. Building on this line, more recent search and deep research agents train models to perform multi-turn retrieval and synthesis in a more end-to-end manner. For example, Search-R1 (Jin et al., 2025) optimizes interleaved search-and-reason trajectories with reinforcement learning and a simple outcome-based reward, while recent deep research systems combine iterative web search with preference tuning, supervised fine-tuning, or RL to improve long-horizon reasoning and report generation (Yamada et al., 2025; Hu et al., 2025; Fan et al., 2025; Zhang et al.,

2025). These advances have significantly strengthened the capability frontier of search-based QA agents.

However, existing agentic search training paradigms are still largely *correctness-centric*. In representative RL formulations such as Search-R1, the reward is defined only over the final outcome correctness, with no explicit incentive for refusing unsupported answers (Jin et al., 2025; Li et al., 2025a; Team et al., 2025; Chu et al., 2026; Tao et al., 2025; Feng et al., 2025). Likewise, recent deep research systems primarily optimize answer quality, factuality, or task success, rather than calibrating when the agent should abstain. As a result, once retrieval fails, evidence is insufficient, or the problem lies beyond the agent's effective capability boundary, the policy is still biased toward producing an answer. Our work addresses precisely this missing dimension: instead of treating abstention as a post-hoc patch, we incorporate it directly into the same RL process that trains search behavior, so that capability improvement and reliability calibration are optimized jointly rather than separately.

Abstention Training. A growing body of work studies how to make LLMs refuse questions that fall outside their knowledge boundary. One line of research formulates refusal as a reliability-alignment problem. RLKF (Xu et al., 2024b) trains a reward model from knowledge feedback so that refusal is preferred on out-of-knowledge questions, while EKBM (Zheng et al., 2025) explicitly models knowledge boundaries through a fast-slow framework that refines uncertain cases with an additional reasoning stage. Another line focuses on the adverse effect of capability-oriented post-training: Song et al. (2025) show that standard reinforcement finetuning can sharply reduce refusal behavior and increase hallucination on synthetic unanswerable math problems, and Kirichenko et al. (2025) further show that modern reasoning models often exhibit degraded abstention despite higher reasoning accuracy. More task-specific approaches include training abstention on temporal QA with CoT supervision and abstention-aware RL (Zhou et al., 2026), as well as reliability alignment for tool use by expanding the action space with indecisive actions and optimizing on synthesized data (Xu et al., 2024a).

Despite their promise, these methods leave several open issues for search agents. First, most prior abstention work is developed in *single-turn* or otherwise non-agentic settings, such as math QA, temporal QA, dialogue state tracking, or tool selection, where the model's capability boundary is comparatively static (Xu et al., 2024b; Song et al., 2025; Zhou et al., 2026; Zheng et al., 2025; Xu et al., 2024a). In contrast, for search agents, the answerability of a question changes dynamically as the agent interacts with the environment and accumulates evidence. Second, many approaches rely on synthesized unanswerable data, abstained variants of existing benchmarks, or auxiliary reward models/modules, which may introduce task-specific heuristics and reduce portability across models with different intrinsic capabilities (Song et al., 2025; Zhou et al., 2026; Xu et al., 2024b,a). Third, existing reward designs often treat abstention with a fixed bonus or through a separate post-hoc stage, which makes it difficult to preserve the model's willingness to answer when sufficient evidence is actually available (Zhou et al., 2026; Zheng et al., 2025). Our proposed AWA-RL is designed to fill this gap: it learns abstention *within* search-agent RL, uses a dynamically shaped refusal reward tied to an estimated prior capability rather than a static refusal bonus, and adds an explicit generation-encouragement term to avoid collapse into lazy refusal. In this way, our method targets the core unresolved problem left by prior work: how to jointly optimize search capability and abstention reliability under a unified, lightweight RL objective.

B Additional Recipes for Stable RL

In this section, we provide detailed descriptions of the auxiliary training mechanisms utilized to stabilize the reinforcement learning process and to continuously enhance the underlying search capabilities of the agent.

B.1 Reward Stabilization via EMA Smoothing and Step-wise Updates

During the on-policy rollout phase, the empirical refusal rate ($\hat{\mu}_{ref}$) can fluctuate significantly from step to step simply due to the random sampling of prompts and the inherent stochasticity of the model's generation. If the dynamic penalty $P(E_t)$ is updated immediately based on these noisy step-wise fluctuations, the reward landscape will become overly jittery, leading to unstable policy updates and preventing the model from converging to an optimal abstention boundary.

To mitigate this variance, we introduce two robust stabilization mechanisms:

1. **Exponential Moving Average (EMA) Smoothing:** Instead of using the instantaneous excess refusal rate E_t, we maintain a smoothed running average $\bar{E}_t$ across training steps:

$$\bar{E}_t = \alpha\bar{E}_{t-1} + (1 - \alpha)E_t$$

where $\alpha \in [0, 1)$ is the decay factor (set to $\alpha = 0.5$ in our experiments). This EMA acts as a low-pass filter, ensuring that the penalty only responds to sustained trends in over-refusal or under-refusal rather than transient batch noise.

2. **Step-wise Quantization:** To further prevent microscopic, continuous shifts in the refusal reward, we enforce discrete, step-wise updates by quantizing the smoothed excess rate $\bar{E}_t$. Given a predefined step-tier threshold τ (e.g., $\tau = 0.1$), the effective excess rate is discretized as:

$$\tilde{E}_t = \tau\lfloor\bar{E}_t/\tau\rceil$$

where $\lfloor\cdot\rceil$ denotes rounding to the nearest integer.

Ultimately, the dynamic penalty is calculated as $P(\tilde{E}_t)$ rather than $P(E_t)$. This quantization creates a "staircase" effect: the final refusal reward r_{ref} remains strictly constant unless the model's smoothed refusal behavior crosses a significant threshold, thereby providing a much more stable optimization target for the GRPO algorithm.

B.2 Dense Citation Reward and Composite Objective

Relying exclusively on the sparse outcome reward, which assigns 1 for correct, 0 for incorrect, and r_{ref} for abstention, can be highly inefficient for training complex agentic tasks. When the model receives a 0, it lacks granular feedback on *why* it failed (e.g., did it fail to retrieve the right documents, or did it fail to reason over them?).

To provide a dense learning signal that continuously bolsters the model's multi-hop search and reasoning skills, we introduce an LLM-judged citation reward. During generation, the agent is prompted to cite specific supporting document IDs for its claims. An external, powerful LLM acts as a judge to evaluate these citations across two dimensions:

- **Citation Coverage** (R_{cov})**:** The judge evaluates whether the cited documents contain all the necessary logical hops to derive the final answer, outputting a continuous score $R_{cov} \in [0, 1]$.

- **Citation Redundancy** (R_{red})**:** To prevent "citation hacking" (where the agent trivially cites every retrieved document to maximize coverage), the judge simultaneously checks for irrelevant citations, assigning a discrete penalty score $R_{red} \in \{0, 0.25, 0.5, 1\}$.

For the final GRPO update, we combine these dense signals with our sparse outcome reward. To prevent rewards of different scales from dominating the gradient, we independently whiten (z-score normalize) each component within the sampled generation group. Let $\text{Wh}(\cdot)$ denote this intra-group whitening operation. The final composite advantage A_i for a specific trajectory is formulated as a weighted sum:

$$A_i = 2\cdot\text{Wh}(R(y, y^*, q_i)) + 3\cdot\text{Wh}(R_{cov}) - 1\cdot\text{Wh}(R_{red})$$

This composite objective represents a highly effective decoupling strategy. By heavily weighting the dense citation metrics (ratio of 3 for coverage), the agent steadily optimizes its fine-grained search and grounding skills. Meanwhile, the dynamically scaled outcome reward (ratio of 2) is freed up to be exclusively dedicated to balancing the overarching capability-reliability (answer-versus-abstain) trade-off.

C Detailed Experimental Setup

In this section, we provide the comprehensive implementation details, environment configurations, and hyperparameters omitted from the main text.

C.1 Datasets and Search Environment

Evaluation and Training Data. For the main evaluation, we randomly sample 1,000 queries from the official validation sets of HotpotQA, 2WikiMultiHopQA (2Wiki), and MuSiQue. For the RL training phase, we utilize the training splits of 2Wiki and MuSiQue. To ensure the efficiency of the GRPO updates, we conduct a preliminary test rollout on the training set to filter out queries that are either trivially easy (where the model answers correctly in all sampled trajectories) or impossibly hard (where the model fails in all trajectories). Such queries provide zero relative advantage and

contribute little to policy learning. From the remaining filtered pool, we randomly sample 5,000 queries for the final RL training.

Search Environment. We adopt a search environment configuration identical to Search-R1. Specifically, we use the 2018 Wikipedia dump, partitioned into 100-word chunks. These chunks are embedded using the E5 model (Wang et al., 2022) and indexed using FAISS (Douze et al., 2024) for efficient dense retrieval. At each query step, the retriever returns the top-5 passages based on embedding cosine similarity.

C.2 Implementation and Hyperparameters

Model Initialization. All primary experiments are conducted using the Qwen2.5-7B-Instruct model, which inherently possesses strong foundational potential for tool use. For our cold-start setting, we generate 5,000 distinct, successful trajectories using a highly capable teacher model (GPT-oss-120b). The base Qwen model undergoes Supervised Fine-Tuning (SFT) on this dataset for 2 epochs, successfully bootstrapping its search and reasoning skills before RL intervention.

RL Configuration. During the reinforcement learning phase, we train the model for 5 epochs using the GRPO algorithm. The global batch size is set to 256, the PPO mini-batch size is 256, and the group rollout size (G) is set to 16. We use a learning rate of 1×10^{-6}. The maximum context length is capped at 16,384 tokens, and the agent is allowed a maximum of 20 interaction turns with the search environment per query.

Entropy Control and Judges. To maintain exploration and prevent premature policy collapse during RL, we completely remove the standard KL divergence penalty in GRPO. Instead, we apply the dynamic entropy control mechanism introduced in Skywork-OR1 (He et al., 2025), strictly keeping the policy entropy above a threshold of 0.4. Furthermore, two separate GPT-oss-120b instances are employed as LLM judges: one dedicated to evaluating the rigorous correctness of the final answer, and the other to assessing citation quality (coverage and redundancy). All prompt templates used for the agent and the judges are provided in Appendix D.

Hardware. All training and evaluation pipelines are executed on two compute nodes, each equipped with 8×NVIDIA H100 GPUs.

D Prompt Templates

D.1 Prompt for RL Training

Prompt for RL Training

```
You are an assistant tasked with answering user queries
↪ step-by-step using the `wikipedia_search` tool.

Each use of `wikipedia_search` returns a list of documents.
↪ Each document includes:

* `id`: a unique identifier in the format `"x-y"`, where
↪ `x` indicates the search iteration number and `y`
↪ indicates the index within that result set (e.g.,
↪ `"1-1"`, `"1-2"`, `"2-1"`).
* `content`: the title and a chunk of text from the
↪ Wikipedia article.

Tool responses will be returned in the following format:

<tool_response>
```json
[
  {
    "doc_id": "x-y",
    "content": "\"Document Title\"\nText content of the
    ↪ document..."
  },
  ...
]
```
</tool_response>

Your task is to explore the question systematically and
↪ provide reasoning and answer with precise citations
↪ from the returned documents.

Workflow

* Before calling the tool, always generate a `<think>`
↪ block explaining your reasoning.
* For the final answer, use an `<answer>` block containing
↪ a JSON object with:
  * `answer`: a short answer to the question.
  * `rationale`: a concise explanation of how the sources
  ↪ support the answer.
  * `citations`: a list of doc_ids
* You can also return a refusal ("not enough information")
↪ if the question cannot be answered based on the search
↪ engine.

Required Output Format

Reasoning Block

Enclose your reasoning within `<think> </think>` tags, for
↪ example:

<think>
Your reasoning process here...
</think>

Final Answer Block

Enclose your structured answer within `<answer> </answer>`
↪ tags, for example:

<answer>
```json
{
  "answer": "A short answer to the question, preferably in
  ↪ one or few words. Or 'not enough information' if the
  ↪ question cannot be answered.",
  "rationale": "Concise justification of the logic that
  ↪ leads to the answer.",
  "citations": ["x-y", "a-b", ...]
}
```
</answer>

Tools

You may call one or more functions to assist with the user
↪ query.
```
---

```
You are provided with function signatures within
↪  <tools></tools> XML tags:
<tools>
{
  "type": "function",
  "function": {
    "name": "wikipedia_search",
    "description": "Search Wikipedia for information about
    ↪  a specific query. Returns a list of summaries of
    ↪   the related articles.",
    "parameters": {
      "type": "object",
      "properties": {
        "query": {
          "type": "string",
          "description": "The specific query term to search
          ↪  on Wikipedia."
        },
        "top_n": {
          "type": "integer",
          "description": "The number of documents to
          ↪  return."
        }
      },
      "required": ["query", "top_n"]
    }
  }
}
</tools>

For each function call, return a json object with function
↪   name and arguments within <tool_call></tool_call> XML
↪   tags:
<tool_call>
{"name": <function-name>, "arguments": <args-json-object>}
</tool_call>
```

D.2 Prompt for LMJudge

Prompt for LMJudge

```
You will be given a question and its ground truth answer
↪   list where each item can be a ground truth answer.
↪   Provided a pred_answer, you need to judge if the
↪   pred_answer correctly answers the question based on the
↪   ground truth answer list. You should first give your
↪   rationale for the judgement, and then give your
↪   judgement result (i.e., correct or incorrect).

Here is the criteria for the judgement:
1. The pred_answer doesn't need to be exactly the same as
↪   any of the ground truth answers, but should be
↪   semantically same for the question.
2. Each item in the ground truth answer list can be viewed
↪   as a ground truth answer for the question, and the
↪   pred_answer should be semantically same to at least one
↪   of them.

question: {question}
ground truth answers: {gt_answer}
pred_answer: {pred_answer}

The output should in the following json format:
```json
{{
    "rationale": "your rationale for the judgement, as a
    ↪   text",
    "judgement": "your judgement result, can only be
    ↪   'correct' or 'incorrect'"
}}
```

Your output:
```

D.3 Prompt for Citation Reward

Prompt for Citation Reward

```
## Role
You are an expert Citation Quality and Coverage Evaluator.

## Input
You will be provided with:
1. **Question**: The user query.
2. **Ground Truth (GT) Answer**: The correct answer string.
3. **Ground Truth (GT) Atomic Evidence**: A list of
↪   specific supporting facts that should be cited. Each
↪   atomic evidence represents one key piece of
↪   information.
4. **Model Citations**: The citations/evidence passages
↪   that the model has provided in its answer.

## Goal
Evaluate the model's citations on TWO dimensions:
A) **Coverage Count**: How many GT Atomic Evidence items
↪   are covered by the citations?
B) **Redundancy/Irrelevance Severity**: The severity level
↪   of redundant or irrelevant citations (0-3 scale).

## Evaluation Procedure

### A) Coverage Count

**Task**: Count how many items from the GT Atomic Evidence
↪   are adequately covered in the Model Citations.

**Counting Rules**:
1. Go through EACH item in the GT Atomic Evidence list one
↪   by one.
2. For each GT item, check if the Model Citations contain
↪   the **same semantic information**:
   - Exact wording is NOT required
   - BUT specific details (names, dates, numbers, entities)
   ↪   MUST match
   - Vague references do NOT count as coverage
3. If a GT item is sufficiently covered (even partially
↪   across multiple citations), count it as **1**.
4. If a GT item is completely missing or only vaguely
↪   referenced, count it as **0**.

**Output**: `covered_count` = integer, the total number of
↪   GT Atomic Evidence items that are covered.

**Example**:
- GT Atomic Evidence has 5 items: [A, B, C, D, E]
- Model Citations cover: A (fully), B (fully), C (missing),
↪   D (vaguely), E (fully)
- covered_count = 3 (only A, B, E count)

### B) Redundancy/Irrelevance Severity (0-3 scale)

**Task**: Assess the severity of redundant or irrelevant
↪   content in the Model Citations.

**Definitions**:
- **Redundant Citation**: A citation that repeats
↪   information already provided by another citation. The
↪   repeated information must be substantially the same
↪   fact.
- **Irrelevant Citation**: A citation that provides
↪   information NOT needed to support any GT Atomic
↪   Evidence or answer the question.

**Severity Levels**:

**0 (Clean - No Issues)**
- ALL citations are unique and relevant.
- Every citation contributes distinct, necessary
↪   information.
- No redundancy, no irrelevance.

**1 (Minor Issues)**
- A small portion of citations are redundant or irrelevant.
- 1-2 problematic citations, OR slight overlap between
↪   citations.
- Roughly <25% of citations are problematic.

**2 (Moderate Issues)**
- A noticeable portion of citations are redundant or
↪   irrelevant.
```

```
      - Multiple problematic citations (3-5), OR significant
↪   redundancy where key facts are repeated.
      - Roughly 25-50% of citations are problematic.

**3 (Severe Issues)**
- A large portion or majority of citations are redundant or
↪   irrelevant.
- Many problematic citations (5+), OR heavy redundancy with
↪   massive duplication.
- Roughly >50% of citations are problematic.

**Evaluation Guide**:
- Count total Model Citations: N
- Count redundant citations: R
- Count irrelevant citations: I
- Calculate proportion: (R + I) / N
- Map to severity: <25% → 1, 25-50% → 2, >50% → 3, 0% → 0

## Important Notes
- For Coverage: Only count a GT item as covered if the
↪   specific information is clearly present.
- For Severity: Base your judgment on the proportion of
↪   problematic citations.
- If Model Citations is empty/null, set covered_count=0 and
↪   redundancy_severity=0.

## Output Format
You must output your answer in a valid **JSON object**. Do
↪   not output any other text or explanations outside the
↪   JSON.

**JSON Schema:**
```json
{
  "covered_count": <integer>,
  "redundancy_severity": 0 | 1 | 2 | 3
}
```
```

E AWA-RL Rollout Cases

E.1 Correctly Answered

The following case demonstrates how the AWA-RL trained model performs step-by-step planning, reasoning, searching, and verification to arrive at the correct answer for a complex multi-hop question from the MuSiQue validation set.

> ***What happened to the Curonians who lived in the area where Erich Zakowski was born?***
> ***Reference Answer:*** *expelled by the Soviet Union*

```
<think>We need to answer: "What happened to the
↪   Curonians who lived in the area where Erich
↪   Zakowski was born?" Need to find Erich
↪   Zakowski birthplace, then find Curonians in that
↪   area, what happened to them. Likely about the
↪   Curonians (an ancient Baltic tribe) living in the
↪   region of Lithuania/Poland? Need to see if Erich
↪   Zakowski born in Curonian territory historically.
↪   Let's search.</think>

<tool_call>
{'name': 'wikipedia_search', 'arguments': {'query':
↪   'Erich Zakowski birthplace', 'top_n': 5}}
</tool_call><|im_end|>
<|im_start|>user
<tool_response>[
  {
    "doc_id": "1-1",
    "content": "\"Erich Zakowski\"\nErich Zakowski
↪   Erich Zakowski (born 25 November 1934 in East
↪   Prussia) is a German master mechanic, and the
↪   founder and longtime head of the Zakspeed
↪   racing team. After the Second World War,
↪   Zakowski fled from Prussia with his mother and
↪   four siblings initially to Dortmund then
↪   Hamburg and finally the family settled in
↪   Niederzissen. Zakowski graduated in Andernach
↪   as an apprentice auto mechanic, and passed his
↪   master exam. He founded his own garage in
↪   Niederzissen, which was the location of the
↪   Zakspeed racing operation, starting in 1968.
↪   In 1968, under the name \"\"Zakowski
↪   Niederzissen tuning\"\", he started using a
↪   Ford"
  },
  {
    "doc_id": "1-2",
    "content": "\"Erich Zakowski\"\nEscort for the
↪   Eifel race on the Nürburgring. In the 1970s
↪   and 1980s, under the direction of Erich
↪   Zakowski, Zakspeed established itself in
↪   various racing series, (especially in sports
↪   car racing). Zakspeed entered the Formula 1
↪   series in 1985. In 1990, after five years of
↪   racing, Zakowski retired active leadership of
↪   the team and handed it to his son Peter. Erich
↪   Zakowski Erich Zakowski (born 25 November 1934
↪   in East Prussia) is a German master mechanic,
↪   and the founder and longtime head of the
↪   Zakspeed racing team. After the Second World
↪   War, Zakowski fled from Prussia with his
↪   mother and"
  },
  {
    "doc_id": "1-3",
```

```
    "content": "\"Henry Jarecki\"\nHenry Jarecki Dr.
↪    Henry George Jarecki (born April 15, 1933) is
↪    a German American academic, psychiatrist,
↪    entrepreneur, producer and philanthropist.
↪    Henry Jarecki was born into a Jewish family in
↪    Stettin, Germany, (now Szczecin, Poland), the
↪    son of Max Jarecki, a physician, and Gerda
↪    Kunstmann, the scion of a shipping family. As
↪    a child, he fled Nazi Germany with his family
↪    for the United Kingdom and subsequently the
↪    United States.His wealthy family was able to
↪    transfer their wealth from Germany. Jarecki
↪    graduated from the Medical Faculty at
↪    Heidelberg University in 1957, and
↪    subsequently spent more than a decade as an
↪    academic,"
    },
    {
      "doc_id": "1-4",
      "content": "\"Zdzisław Zakrzewski\"\nZdzisław
↪    Zakrzewski Zdzisław Zakrzewski, of the
↪    Jastrzębiec coat of arms (11 November 1919 in
↪    Lwów – 21 March 2013 in Hayward, California)
↪    was a Polish-American optical engineer,
↪    philanthropist, banker, a veteran of Poland's
↪    defensive struggle in September 1939, and a
↪    social and political activist. Zdzisław
↪    Zakrzewski graduated from the Classical
↪    Gymnasium of St. Jadwiga and studied
↪    engineering at the Lwów Polytechnic Institute.
↪    He was an altar boy, a boy scout, an activist
↪    of the Lwów chapter of the All-Polish Youth
↪    and the \"\"Brotherly Aid\"\" Association, as
↪    well as a member of the \"\"Ikaria\"\" Student
↪    Fraternity. In September 1939, after the"
    },
    {
      "doc_id": "1-5",
      "content": "\"Erich Reich\"\nErich Reich Sir Erich
↪    Arieh Reich (born 1935, Vienna, Austria) is an
↪    Austrian-born entrepreneur based in London,
↪    who through his charity challenges company
↪    Classic Tours has inspired over 42,000 people
↪    to raise £60million for 300+ UK charities.
↪    Reich was born in 1935. In 1938, he was one of
↪    the children of 5,000 families deported by
↪    Nazi Germany to Poland. Under the
↪    Kindertransport agreement, he arrived in the
↪    United Kingdom, aged 4, in August 1939, one of
↪    10,000 children. He never saw his parents
↪    again, who were murdered in Auschwitz.
↪    Initially placed with a foster family in
↪    Dorking, Surrey, he moved"
    }
  ]</tool_response><|im_end|>
<|im_start|>assistant
<think>Erich Zakowski born in East Prussia. East
↪ Prussia historically includes Curonian territory.
↪ The Curonians were an ancient Baltic tribe living
↪ in the area of present-day Kaliningrad Oblast,
↪ Russia, and also parts of Lithuania. What happened
↪ to them? They were assimilated or disappeared; the
↪ region became German, then after WWII, the Germans
↪ expelled, area became Soviet, Curonian ethnic
↪ group extinct. Need source about Curonians and
↪ what happened to them. Let's search.</think>

<tool_call>
{'name': 'wikipedia_search', 'arguments': {'query':
↪ 'Curonians fate', 'top_n': 5}}
</tool_call><|im_end|>
<|im_start|>user
<tool_response>[
  {
    "doc_id": "2-1",
```

```
    "content": "Curonians\nCuronians The Curonians or
↪    Kurs (Curonian: \"\"Kursi\"\"; ; ; ; ; ; ; )
↪    were a Baltic tribe living on the shores of
↪    the Baltic Sea in what are now the western
↪    parts of Latvia and Lithuania from the 5th to
↪    the 16th centuries, when they merged with
↪    other Baltic tribes. They gave their name to
↪    the region of Courland (\"\"Kurzeme\"\"), and
↪    they spoke the Old Curonian language. Curonian
↪    lands were conquered by the Livonian Order in
↪    1266 and they eventually merged with other
↪    Baltic tribes participating in the
↪    ethnogenesis of Lithuanians and Latvians.
↪    Direct descendants of the Curonians include"
    },
    {
      "doc_id": "2-2",
      "content": "Curonians\npart of Samogitian ethnic
↪    self-identification. On the Latvian side
↪    during the Livonian War, the descendants of
↪    the Curonian nobility, although downgraded to
↪    peasant status, fought the Russians, as Johann
↪    Renner's chronicle reports: The Curonian
↪    language became extinct by the 16th century.
↪    Bishop Rimbert of Bremen (lived before 888 AD)
↪    in his life of St. Ansgar, Vita Ansgarii
↪    described the territory inhabited by the
↪    Curonians (\"\"Cori\"\") and gave the names of
↪    the administrative districts or lands
↪    (\"\"civitates\"\"): Curonians The Curonians
↪    or Kurs (Curonian: \"\"Kursi\"\"; ; ; ; ; ; ;
↪    ) were a Baltic tribe living on the shores of
↪    the"
    },
    {
      "doc_id": "2-3",
      "content": "\"Curonian Lagoon\"\n(); the southern
↪    part of the Spit and the Lagoon remained in
↪    Germany until 1945. This border is now the
↪    border between Lithuania and Russia, as after
↪    World War II, the southern end of the Spit and
↪    the German area south of the river – the part
↪    of East Prussia with the city Königsberg in
↪    Sambia – became part an exclave of Russia
↪    called Kaliningrad Oblast. While today the
↪    Kursenieki, also known as Kuršininkai, are a
↪    nearly extinct Baltic ethnic group living
↪    along the Curonian Spit, in 1649 Kuršininkai
↪    settlement spanned from Memel (Klaipėda) to
↪    Danzig (Gdańsk). The Kuršininkai were"
    },
    {
      "doc_id": "2-4",
      "content": "Curonians\nthe Kursenieki of the
↪    Curonian Spit and the so-called Curonian Kings
↪    of Courland. The ethnic origin of the
↪    Curonians has been disputed in the past. Until
↪    the middle of the 20th century, they were
↪    usually considered a Finnic tribe akin to the
↪    Livonians. This was traditionally the
↪    consensus of Estonian historians, while
↪    Latvian historians regarded the Curonians as
↪    Baltic. Since the 20th century, most sources
↪    refer to the Curonians as a Baltic tribe. Some
↪    researchers place the Curonians in the eastern
↪    Baltic group. However, others hold that the
↪    Curonians were related to Old Prussians who
↪    belonged in the western Baltic"
    },
    {
      "doc_id": "2-5",
```

        "content": "Curonians\nwas finally subdued in 1266,
↪   when the whole of Courland was partitioned
↪   between the Livonian Order and the Archbishop
↪   of Riga. The Curonian nobles, among them 40
↪   clans of the descendants of the Curonian kings,
↪   who lived in the town of Kuldīga, preserved
↪   personal freedom and some of their privileges.
↪   Southern Curonians from Megowa, Pilsaten and
↪   Ceclis lands gradually assimilated into the
↪   nascent Lithuanian nation and ceased to be
↪   known as a distinct ethnos by the 16th century.
↪   An intense period of Samogitian-Curonian
↪   bilingualism is posited because a Curonian
↪   linguistic substratum is evident in the
↪   Northern Samogitian dialect, an important"
      }
]</tool_response><|im_end|>
<|im_start|>assistant
<think>We need to answer: "What happened to the
↪ Curonians who lived in the area where Erich
↪ Zakowski was born?" So we need to state that they
↪ merged with other Baltic tribes, their language
↪ extinct, eventually became part of Lithuanian/
↪ Latvian ethnogenesis; they were conquered by the
↪ Livonian Order in 1266, eventually assimilated.
↪ Provide citation from doc 2-1 that says they
↪ merged with other Baltic tribes, their name given
↪ to Courland. Also need to link Zakowski birthplace
↪ East Prussia was Curonian area. Need source that
↪ East Prussia included Curonian territory. Might
↪ need to search "East Prussia Curonians".</think>

<tool_call>
{'name': 'wikipedia_search', 'arguments': {'query':
↪ 'East Prussia Curonians', 'top_n': 5}}
</tool_call><|im_end|>
<|im_start|>user
<tool_response>[
  {
    "doc_id": "3-1",
    "content": "Curonians\nthe Kursenieki of the
↪   Curonian Spit and the so-called Curonian Kings
↪   of Courland. The ethnic origin of the
↪   Curonians has been disputed in the past. Until
↪   the middle of the 20th century, they were
↪   usually considered a Finnic tribe akin to the
↪   Livonians. This was traditionally the
↪   consensus of Estonian historians, while
↪   Latvian historians regarded the Curonians as
↪   Baltic. Since the 20th century, most sources
↪   refer to the Curonians as a Baltic tribe. Some
↪   researchers place the Curonians in the eastern
↪   Baltic group. However, others hold that the
↪   Curonians were related to Old Prussians who
↪   belonged in the western Baltic"
  },
  {
    "doc_id": "3-2",
    "content": "Kursenieki\nreturn to Kursenieki of
↪   property confiscated after World War II.
↪   Curonians are one of the Baltic tribes. Their
↪   culture, religion and architecture are similar
↪   to those found in Germany and Sweden.
↪   Curonians are related with Lithuanians and
↪   Latvians. The Kursenieki were predominantly
↪   Lutheran, like most former inhabitants of East
↪   Prussia, although some ancient pagan customs
↪   were preserved. Most Kursenieki were bilingual
↪   or even trilingual: the Curonian language was
↪   used within the family and while fishing,
↪   German was used in everyday communication, and
↪   the language of church services was German and
↪   Lithuanian. The Kursenieki were primarily
↪   fishermen. Some elements of cuisine"
  },
  {
    "doc_id": "3-3",

        "content": "\"East Prussia\"\nand Prussian
↪   Lithuanians decreased over time due to the
↪   process of Germanization. The Polish-speaking
↪   population concentrated in the south of the
↪   province (Masuria and Warmia) and all German
↪   geographic atlases at the start of 20th
↪   century showed the southern part of East
↪   Prussia as Polish with the number of Poles
↪   estimated at the time to be 300,000.
↪   Kursenieki inhabited the areas around the
↪   Curonian lagoon, while Lithuanian-speaking
↪   Prussians concentrated in the northeast in
↪   (Lithuania Minor). The Old Prussian ethnic
↪   group became completely Germanized over time
↪   and the Old Prussian language died out in the
↪   18th century. At the beginning of"
  },
  {
    "doc_id": "3-4",
    "content": "\"East Prussia\"\nWhile many fled from
↪   the Red Army during the evacuation of East
↪   Prussia, Curonians that remained behind were
↪   subsequently expelled by the Soviet Union.
↪   Only 219 lived along the Curonian Spit in 1955.
↪   Many had German names such as Fritz or Hans, a
↪   cause for anti-German discrimination. The
↪   Soviet authorities considered the Curonians
↪   fascists. Because of this discrimination, many
↪   immigrated to West Germany in 1958, where the
↪   majority of Curonians now live. After the
↪   expulsion of the German population ethnic
↪   Russians, Belarusians, and Ukrainians were
↪   settled in the northern part. In the Soviet
↪   part of the region, a policy of"
  },
  {
    "doc_id": "3-5",
    "content": "Kursenieki\nKursenieki The Kursenieki
↪   (, – 'Curonians'; ; – 'Prussian Curonians')
↪   are a nearly extinct Baltic ethnic group
↪   living along the Curonian Spit.
↪   \"\"Kuršininkai\"\" refers only to inhabitants
↪   of Lithuania and former East Prussia that
↪   speak a dialect of Latvian. Some autochthonous
↪   inhabitants of Šventoji in Lithuania call
↪   themselves \"\"kuršininkai\"\" as well.
↪   Kursenieki are often confused with the extinct
↪   Curonian Baltic tribe, as neighbouring ethnic
↪   groups called Kuršininkai/Kursenieki as
↪   \"\"Curonians\"\": in German, Latvian and
↪   Lithuanian, Kursenieki and the Curonian tribes
↪   are known by the same terms (\"\"Kuren\"\",
↪   \"\"kurši\"\" and \"\"kuršiai\"\"
↪   respectively). In scientific Lithuanian
↪   literature, the name \"\"kuršininkai\"\" is
↪   used to"
  }
]</tool_response><|im_end|>
<|im_start|>assistant
<think>Doc 3-4 seems to describe what happened to the
↪ Curonians remaining in East Prussia: they were
↪ expelled by Soviet Union, considered fascists,
↪ many immigrated to West Germany. That addresses
↪ the question: "What happened to the Curonians who
↪ lived in the area where Erich Zakowski was born?"
↪ So answer: They were expelled by the Soviet Union
↪ after WWII, considered fascists, and many
↪ immigrated to West Germany. Provide citations: doc
↪ 1-1 for Zakowski birthplace East Prussia, doc 3-4
↪ for Curonians' fate, doc 2-1 for Curonians
↪ background (optional). Need to also show that
↪ Curonians lived in that area historically. Doc 3-3
↪ says "Kursenieki inhabited the areas around the
↪ Curonian lagoon, while Lithuanian-speaking
↪ Prussians concentrated in the northeast in
↪ (Lithuania Minor)." That ties Curonians to East
↪ Prussia. Use doc 3-3.

Thus answer: They were expelled by the Soviet Union
↪ and considered fascists, leading to their
↪ diaspora, with many moving to West Germany.
↪ Provide rationale.

Let's capture citations:</think>

```
- Doc 1-1: Erich Zakowski born in East Prussia.
- Doc 3-3: Kursenieki (Curonians) inhabited areas
↪   around Curonian lagoon in East Prussia.
- Doc 3-4: Curonian (Kursenieki) people expelled by
↪   Soviet Union, considered fascists, many immigrated
↪   to West Germany after 1955.

Now produce final answer.</think>

<answer>
```json
{
  "answer": "They were expelled by the Soviet Union
↪   and treated as fascists, leading most to
↪   immigrate to West Germany.",
  "rationale": "Erich Zakowski was born in East
↪   Prussia, the historic region where the Curonian
↪   (Kursenieki) tribe lived along the Curonian
↪   lagoon. After World War II the remaining
↪   Curonians were expelled by the Soviets and many
↪   later moved to West Germany.",
  "citations": ["1-1", "3-3", "3-4"]
}
```
</answer><|im_end|>
```

E.2 Well-Justified Abstention

The following case demonstrates how the AWA-RL trained model performs multiple rounds of searching and determines that a question is unanswerable. It then provides a principled abstention, supported by a clear explanation and the necessary citations. The question is also sampled from the MuSiQue validation set.

> ***How many miles of highways are in the city where the Yongle emperor greeted the person to whom the edict was addressed?***
> ***Reference Answer:*** *140 mi*

```
<think>We need to parse the question.

"How many miles of highways are in the city where the
↪   Yongle emperor greeted the person to whom the
↪   edict was addressed?"

We need to identify:

- The Yongle emperor greeted the person to whom the
↪   edict was addressed. So we need to know which city
↪   that event took place in. Then find how many miles
↪   of highways are in that city.

Thus we need to locate: "the Yongle emperor greeted
↪   the person to whom the edict was addressed".
↪   Likely referencing a historical event: Yongle
↪   Emperor (Zhu Di) of Ming dynasty, known for
↪   sending expeditions, issuing edicts. "Edict" maybe
↪   a "Zheng He" expedition? He greeted person maybe
↪   "the King of Java" or "the King of Ceylon"? Edict
↪   addressed to someone.

We need to search. Let's search Wikipedia for Yongle
↪   emperor greeted person edict.</think>

<tool_call>
{'name': 'wikipedia_search', 'arguments': {'query':
↪   'Yongle emperor greeted the person to whom the
↪   edict was addressed', 'top_n': 5}}
</tool_call><|im_end|>
<|im_start|>user
<tool_response>[
  {
    "doc_id": "1-1",
```

```
    "content": "\"Yongle Emperor\"\nwho intended to
↪   invade China, relations between the Ming
↪   Empire and Shakhrukh's state in Persia and
↪   Transoxania state considerably improved, and
↪   the states exchanged large official
↪   delegations on a number of occasions. Both the
↪   Ming Empire's envoy to Samarkand and Herat,
↪   Chen Cheng, and his counterpart, Ghiyasu'd-Din
↪   Naqqah, recorded detailed accounts of their
↪   visits to each other's states. One of the
↪   Yongle Emperor's consorts was a Jurchen
↪   princess, which resulted in many of the
↪   eunuchs serving him being of Jurchen origin,
↪   notably Yishiha. The Yongle Emperor instituted
↪   a Ming governor on Luzon during Zheng He's
↪   voyages and appointed Ko-ch'a-lao;"
},
{
  "doc_id": "1-2",
  "content": "\"Zhou Youde\"\nZhou Youde Zhou Youde
↪   (also romanised as Chou Yu-te; ; died 1680),
↪   courtesy name Yichu (), was a Chinese official
↪   active in the early Qing dynasty as governor
↪   of various provinces. As Viceroy of Liangguang,
↪   he contributed significantly towards repealing
↪   the Great Evacuation edict, together with Wang
↪   Lairen. Widely venerated as a respectable
↪   civil servant, or a \"\"benevolent
↪   official\"\", Zhou was deified after his death
↪   in 1680 and shrines bearing his image were
↪   established throughout China. Zhou Youde was
↪   born in the late Ming period. He enrolled in
↪   the Hongwen Institution in around 1644 and
↪   studied prose-editing and poetry,"
},
{
  "doc_id": "1-3",
  "content": "\"Xu Wen\"\nTang emissary delivered
↪   Emperor Zhuangzong's communique as an
↪   \"\"edict\"\" (i.e., treating Wu as a
↪   subordinate), Wu officials refused to receive
↪   it. Emperor Zhuangzong, not yet wanting to
↪   break with Wu, instead resent his communique
↪   as a \"\"letter\"\" (i.e., treating Wu as an
↪   equal state) that started with the greeting
↪   of, \"\"The letter of the emperor of the great
↪   Tang to the lord of Wu.\"\" Wu's return
↪   communique started with the greeting of,
↪   \"\"The respectful letter of the lord of the
↪   great Wu to the emperor of the great Tang,\"\"
↪   to show respect and yet equality. (Yan's
↪   predictions would come true"
},
{
  "doc_id": "1-4",
  "content": "Yeongeunmun\nroofed with blue tiles
↪   and had \"\"Yeongjomun\"\" (literally gate of
↪   welcoming imperial decrees) written on the
↪   front tables. In 1539 it was renamed to
↪   \"\"Yeongeunmun\"\" because the name of
↪   \"\"Yeongjomun\"\" was accused by the Ming
↪   dynasty ambassador Xue Tingchong. He claimed
↪   that since the imperial envoys carried
↪   imperial orders , imperial decrees, and
↪   imperial gifts, it was inappropriate to
↪   mention only imperial decree. The tablet was
↪   written by Zhu Zhifan, who came to Joseon as an
↪   ambassador in 1606. As a result of the Treaty
↪   of Shimonoseki (1895) which ended the First
↪   Sino-Japanese War, Qing China recognized"
},
{
  "doc_id": "1-5",
```

```
        "content": "\"Sino-Tibetan relations during the
    ↪   Ming dynasty\"\n1398-1402), the Yongle Emperor
    ↪   was aided by the Buddhist monk Yao Guangxiao,
    ↪   and like his father, the Hongwu Emperor, the
    ↪   Yongle Emperor was \"\"well-disposed towards
    ↪   Buddhism\"\", claims Rossabi. On March 10,
    ↪   1403, the Yongle Emperor invited Deshin
    ↪   Shekpa, 5th Karmapa Lama (1384-1415), to his
    ↪   court, even though the fourth Karmapa had
    ↪   rejected the invitation of the Hongwu Emperor.
    ↪   A Tibetan translation in the 16th century
    ↪   preserves the letter of the Yongle Emperor,
    ↪   which the Association for Asian Studies notes
    ↪   is polite and complimentary towards the
    ↪   Karmapa. The letter of invitation reads, In
    ↪   order to seek out the Karmapa, the Yongle"
    }
]</tool_response><|im_end|>
<|im_start|>assistant
<think>Result 1-5 mentions Yongle Emperor invited
↪   Deshin Shekpa, 5th Karmapa Lama. Edict? The person
↪   to whom the edict was addressed? The edict maybe
↪   the invitation letter to the Karmapa. So the city
↪   where the Yongle emperor greeted the person (the
↪   Karmapa Lama) - where did he greet? He invited him
↪   to his court, maybe at the capital, Beijing. But
↪   they might have met at the "court" in Beijing.
↪   Need to verify.

Open doc 1-5.</think>

<tool_call>
{'name': 'wikipedia_search', 'arguments': {'query':
↪   'Yongle Emperor greeted Deshin Shekpa city
↪   meeting', 'top_n': 5}}
</tool_call><|im_end|>
<|im_start|>user
<tool_response>[
  {
    "doc_id": "2-1",
    "content": "\"Yongle Emperor\"\nhad many of the
    ↪   best scholars chosen as candidates and took
    ↪   great care in choosing them, even creating
    ↪   terms by which he hired people. He was also
    ↪   concerned about the degeneration of Buddhism
    ↪   in China. Tibetan Buddhism was patronised by
    ↪   Yongle. In 1403, the Yongle Emperor sent
    ↪   messages, gifts, and envoys to Tibet inviting
    ↪   Deshin Shekpa, the fifth Gyalwa Karmapa of the
    ↪   Kagyu school of Tibetan Buddhism, to visit the
    ↪   imperial capital - apparently after having a
    ↪   vision of the bodhisattva Avalokitesvara.
    ↪   After a long journey, Deshin Shekpa arrived in
    ↪   Nanjing on 10 April 1407 riding on an elephant
    ↪   towards"
  },
  {
    "doc_id": "2-2",
    "content": "\"Deshin Shekpa, 5th Karmapa
    ↪   Lama\"\nbecause Emperor Zhu Di, the Yongle
    ↪   Emperor, (1402-1424) had a vision of
    ↪   Avalokitesvara. He also required religious
    ↪   ceremonies to be held for his deceased parents.
    ↪   After a long journey beginning in 1403, he
    ↪   arrived in Nanjing, the then capital on April
    ↪   10, 1407 on an elephant, at the imperial
    ↪   palace, where tens of thousands of monks
    ↪   greeted him. He convinced the emperor that
    ↪   there were different Buddhist branches for
    ↪   different people and that does not mean that
    ↪   one branch is better than the other. The
    ↪   Karmapa was very well received during his
    ↪   visit to the capital and a number of"
  },
  {
    "doc_id": "2-3",
```

```
        "content": "\"Yongle Emperor\"\nthe imperial
    ↪   palace, where tens of thousands of monks
    ↪   greeted him. Deshin Shekpa convinced the
    ↪   Yongle Emperor that there were different
    ↪   religions for different people, which does not
    ↪   mean that one is better than the others. The
    ↪   Karmapa was very well received during his
    ↪   visit and a number of miraculous occurrences
    ↪   were reported. He also performed ceremonies
    ↪   for the imperial family. The emperor presented
    ↪   him with 700 measures of silver objects and
    ↪   bestowed the title of 'Precious Religious King,
    ↪   Great Loving One of the West, Mighty Buddha of
    ↪   Peace'. Aside from the religious matter, the
    ↪   Yongle Emperor wished to establish"
  },
  {
    "doc_id": "2-4",
    "content": "\"Yongle Emperor\"\nan alliance with
    ↪   the Karmapa similar to the one the 13th- and
    ↪   14th-century Yuan khans had established with
    ↪   the Sakyapa. He apparently offered to send
    ↪   armies to unify Tibet under the Karmapa but
    ↪   Deshin Shekpa demurred, as parts of Tibet were
    ↪   still firmly controlled by partisans of the
    ↪   former Yuan dynasty. Deshin Shekpa left
    ↪   Nanjing on 17 May 1408. In 1410, he returned
    ↪   to Tsurphu where he had his monastery rebuilt
    ↪   following severe damage from an earthquake.
    ↪   When it was time for him to choose an heir,
    ↪   the Yongle Emperor wanted to choose his second
    ↪   son, Zhu Gaoxu. Zhu Gaoxu"
  },
  {
    "doc_id": "2-5",
    "content": "\"Sino-Tibetan relations during the
    ↪   Ming dynasty\"\n1398-1402), the Yongle Emperor
    ↪   was aided by the Buddhist monk Yao Guangxiao,
    ↪   and like his father, the Hongwu Emperor, the
    ↪   Yongle Emperor was \"\"well-disposed towards
    ↪   Buddhism\"\", claims Rossabi. On March 10,
    ↪   1403, the Yongle Emperor invited Deshin
    ↪   Shekpa, 5th Karmapa Lama (1384-1415), to his
    ↪   court, even though the fourth Karmapa had
    ↪   rejected the invitation of the Hongwu Emperor.
    ↪   A Tibetan translation in the 16th century
    ↪   preserves the letter of the Yongle Emperor,
    ↪   which the Association for Asian Studies notes
    ↪   is polite and complimentary towards the
    ↪   Karmapa. The letter of invitation reads, In
    ↪   order to seek out the Karmapa, the Yongle"
  }
]</tool_response><|im_end|>
<|im_start|>assistant
<think>Thus the city is Nanjing (then imperial
↪   capital). The question: "How many miles of
↪   highways are in the city where the Yongle emperor
↪   greeted the person to whom the edict was
↪   addressed?" So we need to find "highways miles"
↪   statistic for Nanjing.

Search for "Nanjing highways miles".</think>

<tool_call>
{'name': 'wikipedia_search', 'arguments': {'query':
↪   'Nanjing highways mileage', 'top_n': 5}}
</tool_call><|im_end|>
<|im_start|>user
<tool_response>[
  {
    "doc_id": "3-1",
```

16

```
      "content": "Nanjing\nopened for public service in
   ↪  2011. As an important regional hub in the
   ↪  Yangtze River Delta, Nanjing is well-connected
   ↪  by over 60 state and provincial highways to
   ↪  all parts of China. Express highways such as
   ↪  Hu-Ning, Ning-He, Ning-Hang enable commuters
   ↪  to travel to Shanghai, Hefei, Hangzhou, and
   ↪  other important cities quickly and
   ↪  conveniently. Inside the city of Nanjing,
   ↪  there are of highways, with a highway coverage
   ↪  density of 3.38 kilometers per hundred square
   ↪  kilometers (5.44 mi/100 sq mi). The total road
   ↪  coverage density of the city is 112.56
   ↪  kilometers per hundred square kilometers
   ↪  (181.15 mi/100 sq mi). The two artery"
  },
  {
    "doc_id": "3-2",
    "content": "\"Shanghai-Nanjing
   ↪  Expressway\"\nShanghai-Nanjing Expressway The
   ↪  Shanghai-Nanjing Expressway () is a modern,
   ↪  enclosed, four-lane, two-way highway. Each
   ↪  lane is wide, and the highway's roadbed is
   ↪  wide. There is a dividing strip in the center
   ↪  of the highway and a emergency parking area on
   ↪  each side of the highway. The speed limit is .
   ↪  It is in length. It runs from Zhenru, Shanghai
   ↪  to Maqun, Nanjing via Anting, Kunshan, Suzhou,
   ↪  Shuofang (), Wuxi, Changzhou, Danyang,
   ↪  Zhenjiang and Jurong. The Shanghai section is
   ↪  in length, and the Jiangsu section is long.
   ↪  The Zhenjiang section (a branch highway) is
   ↪  long. In Shanghai, the highway is coterminous"
  },
  {
    "doc_id": "3-3",
    "content": "Nanjing\nroads in Nanjing are
   ↪  Zhongshan Road and Hanzhong. The two roads
   ↪  cross in the city center, Xinjiekou.
   ↪  Expressways: National Highway (GXXX): The city
   ↪  also boasts an efficient network of public
   ↪  transportation, which mainly consists of bus,
   ↪  taxi and metro systems. The bus network, which
   ↪  is currently run by three companies since
   ↪  2011, provides more than 370 routes covering
   ↪  all parts of the city and suburban areas. At
   ↪  present, the Nanjing Metro system has a grand
   ↪  total of of route and 173 stations across 10
   ↪  lines. They are Line 1, Line 2, Line 3, Line 4,
   ↪  Line 10, Line S1, Line"
  },
  {
    "doc_id": "3-4",
    "content": "\"Nanjing Road\"\nfranchised stores
   ↪  were also set up at that time. On 23 August
   ↪  1937 a bomb was dropped on Nanjing Road by a
   ↪  Chinese plane in an attempt to lighten its
   ↪  load while being pursued by Japanese planes.
   ↪  The bomb hit two department stores, killing
   ↪  612 people and injuring another 482. In 2000,
   ↪  as a part of the development plan held by the
   ↪  local government, Nanjing Road was renovated
   ↪  to be a characteristic pedestrian street. The
   ↪  width is about 28 meters and the total length
   ↪  is 1,200 meters, which extends from Middle
   ↪  He'nan Road to Middle Xizang Road. In 2007,
   ↪  the"
  },
  {
    "doc_id": "3-5",
```

```
      "content": "Nanjing\nS3, Line S7, Line S8 and Line
   ↪  S9. The city is planning to complete a 17-line
   ↪  Metro and light-rail system by 2030. The
   ↪  expansion of the Metro network will greatly
   ↪  facilitate the intracity transportation and
   ↪  reduce the currently heavy traffic congestion.
   ↪  Nanjing's airport, Lukou International
   ↪  Airport, serves both national and
   ↪  international flights. In 2013, Nanjing
   ↪  airport handled 15,011,792 passengers and
   ↪  255,788.6 tonnes of freight. The airport
   ↪  currently has 85 routes to national and
   ↪  international destinations, which include
   ↪  Japan, Korea, Thailand, Malaysia, Singapore,
   ↪  United States and Germany. The airport is
   ↪  connected by a 29-kilometer (18 mi) highway
   ↪  directly to the city"
  }
]</tool_response><|im_end|>
<|im_start|>assistant
<think>Doc 3-1 says: "Inside the city of Nanjing,
   ↪  there are of highways". The content cut off; we
   ↪  need the exact number. Let's open more lines
   ↪  maybe? The snippet truncated. Could be missing due
   ↪  to formatting. Might need to rely on known data: I
   ↪  recall that Nanjing has about 600 km of highways?
   ↪  Actually 60 state and provincial highways. The doc
   ↪  says "over 60 state and provincial highways". Not
   ↪  miles though.

But the question asks "How many miles of highways are
   ↪  in the city". Might refer to "highways miles" as
   ↪  in "length of highways within the city" maybe in
   ↪  the Wikipedia article "Nanjing" includes "total
   ↪  length of expressways" maybe 250 km? Let's open
   ↪  the Nanjing Wikipedia page directly.</think>

<tool_call>
{'name': 'wikipedia_search', 'arguments': {'query':
   ↪  'Nanjing city highways total length km', 'top_n':
   ↪  5}}
</tool_call><|im_end|>
<|im_start|>user
<tool_response>[
  {
    "doc_id": "4-1",
    "content": "Nanjing\nopened for public service in
   ↪  2011. As an important regional hub in the
   ↪  Yangtze River Delta, Nanjing is well-connected
   ↪  by over 60 state and provincial highways to
   ↪  all parts of China. Express highways such as
   ↪  Hu-Ning, Ning-He, Ning-Hang enable commuters
   ↪  to travel to Shanghai, Hefei, Hangzhou, and
   ↪  other important cities quickly and
   ↪  conveniently. Inside the city of Nanjing,
   ↪  there are of highways, with a highway coverage
   ↪  density of 3.38 kilometers per hundred square
   ↪  kilometers (5.44 mi/100 sq mi). The total road
   ↪  coverage density of the city is 112.56
   ↪  kilometers per hundred square kilometers
   ↪  (181.15 mi/100 sq mi). The two artery"
  },
  {
    "doc_id": "4-2",
    "content": "\"Shanghai-Nanjing
   ↪  Expressway\"\nShanghai-Nanjing Expressway The
   ↪  Shanghai-Nanjing Expressway () is a modern,
   ↪  enclosed, four-lane, two-way highway. Each
   ↪  lane is wide, and the highway's roadbed is
   ↪  wide. There is a dividing strip in the center
   ↪  of the highway and a emergency parking area on
   ↪  each side of the highway. The speed limit is .
   ↪  It is in length. It runs from Zhenru, Shanghai
   ↪  to Maqun, Nanjing via Anting, Kunshan, Suzhou,
   ↪  Shuofang (), Wuxi, Changzhou, Danyang,
   ↪  Zhenjiang and Jurong. The Shanghai section is
   ↪  in length, and the Jiangsu section is long.
   ↪  The Zhenjiang section (a branch highway) is
   ↪  long. In Shanghai, the highway is coterminous"
  },
  {
    "doc_id": "4-3",
```

```
      "content": "Nanjing\nroads in Nanjing are
↪    Zhongshan Road and Hanzhong. The two roads
↪    cross in the city center, Xinjiekou.
↪    Expressways: National Highway (GXXX): The city
↪    also boasts an efficient network of public
↪    transportation, which mainly consists of bus,
↪    taxi and metro systems. The bus network, which
↪    is currently run by three companies since
↪    2011, provides more than 370 routes covering
↪    all parts of the city and suburban areas. At
↪    present, the Nanjing Metro system has a grand
↪    total of of route and 173 stations across 10
↪    lines. They are Line 1, Line 2, Line 3, Line 4,
↪    Line 10, Line S1, Line"
    },
    {
      "doc_id": "4-4",
      "content": "\"Nanjing Road\"\nfranchised stores
↪    were also set up at that time. On 23 August
↪    1937 a bomb was dropped on Nanjing Road by a
↪    Chinese plane in an attempt to lighten its
↪    load while being pursued by Japanese planes.
↪    The bomb hit two department stores, killing
↪    612 people and injuring another 482. In 2000,
↪    as a part of the development plan held by the
↪    local government, Nanjing Road was renovated
↪    to be a characteristic pedestrian street. The
↪    width is about 28 meters and the total length
↪    is 1,200 meters, which extends from Middle
↪    He'nan Road to Middle Xizang Road. In 2007,
↪    the"
    },
    {
      "doc_id": "4-5",
      "content": "Nanjing\nS3, Line S7, Line S8 and Line
↪    S9. The city is planning to complete a 17-line
↪    Metro and light-rail system by 2030. The
↪    expansion of the Metro network will greatly
↪    facilitate the intracity transportation and
↪    reduce the currently heavy traffic congestion.
↪    Nanjing's airport, Lukou International
↪    Airport, serves both national and
↪    international flights. In 2013, Nanjing
↪    airport handled 15,011,792 passengers and
↪    255,788.6 tonnes of freight. The airport
↪    currently has 85 routes to national and
↪    international destinations, which include
↪    Japan, Korea, Thailand, Malaysia, Singapore,
↪    United States and Germany. The airport is
↪    connected by a 29-kilometer (18 mi) highway
↪    directly to the city"
    }
]</tool_response><|im_end|>
```

<|im_start|>assistant
<think>The doc still missing the number. Possibly the
↪   article uses placeholder. Could be "Inside the
↪   city of Nanjing, there are 338 km of highways".
↪   Not sure.

But the question asks "How many miles of highways are
↪   in the city". We could answer with the number of
↪   miles (converted from km). If we have km, we can
↪   compute miles (1 km = 0.621371 mi). So maybe
↪   answer is about 380 miles.

Better to find a reliable source: maybe "Nanjing has
↪   338 km (210 mi) of highways". Let's search web but
↪   limited to Wikipedia. Could be in "List of cities
↪   by highway density". However we can rely on doc
↪   3-1 which says "highway coverage density of 3.38
↪   kilometers per hundred square kilometers (5.44
↪   mi/100 sq mi)". Not total length.

Alternative: maybe the city is not Nanjing but Beijing
↪   (since Yongle Emperor moved capital to Beijing).
↪   He greeted the person (maybe the envoys) at the
↪   "Imperial Court in Beijing". Edict to "all
↪   subjects". But the city's highways mileage may be
↪   easier to find: e.g., "Beijing has 800 miles of
↪   highways". Not sure.

Let's verify Yongle Emperor greeting person to whom
↪   the edict was addressed. Maybe referencing "the
↪   Yongle Emperor issued an edict to the Kingdom of
↪   Malacca; he greeted the envoy there." Another
↪   angle: The Yongle Emperor sent a "edict" (imperial
↪   decree) to "the King of Annam" (Vietnam). He
↪   greeted the person (the Vietnamese envoy) at the
↪   capital Beijing. The city would be Beijing. Need
↪   to confirm.

Search "Yongle emperor edict to Kingdom of
↪   Malacca".</think>

<tool_call>
{'name': 'wikipedia_search', 'arguments': {'query':
↪   'Yongle Emperor edict to the Kingdom of Malacca',
↪   'top_n': 5}}
</tool_call><|im_end|>
<|im_start|>user
<tool_response>[

    {
      "doc_id": "5-1",
      "content": "\"Parameswara (king)\"\ncentre of
↪   trade and commerce began to spread all over
↪   the eastern part of the world and reached as
↪   far as China. The Yongle Emperor of the Ming
↪   dynasty, who reigned from 1402 till 1424, sent
↪   his envoy known as Yin Qing to Malacca in 1405.
↪   Yin Qing's visit opened the way for the
↪   establishment of friendly relations between
↪   Malacca and China. Chinese merchants began
↪   calling at the port of Malacca, joining other
↪   foreign traders notably the Javanese, Indians,
↪   Chinese, and Burmese who came to establish
↪   their trading bases and settle in Malacca,
↪   soaring its population to 2000 during
↪   Parameswara's"
    },
    {
      "doc_id": "5-2",
      "content": "\"Parameswara (king)\"\nreign. In
↪   1411, Parameswara, his wife, his son, and a
↪   royal party of 540 people left for China with
↪   Admiral Zheng He to pay homage to the Yongle
↪   Emperor. Yongle praised Parameswara and
↪   acknowledged him as the rightful ruler of
↪   Malacca. He then presented Parameswara with a
↪   seal, silk and a yellow umbrella as symbols of
↪   royalty and also a letter appointing
↪   Parameswara as the ruler of Malacca. Malacca
↪   was then recognised as a kingdom by the
↪   Emperor of China. The envoy returned to
↪   Malacca together with a fleet led by Zheng He.
↪   The Chinese chronicles mention that in 1414,"
    },
    {
      "doc_id": "5-3",
      "content": "\"Malacca Sultanate\"\ntreasury and
↪   supply were stored. The growth of Malacca
↪   coincided with the rising power of Ayuthaya in
↪   the north. The growing ambitions of the
↪   kingdom against its neighbours and Malay
↪   Peninsula had alarmed the ruler of Malacca. In
↪   a preemptive measure, the king headed a royal
↪   visit to China in 1418 to raise his concerns
↪   about the threat. Yongle responded in October
↪   1419 by sending his envoy to warn the Siamese
↪   ruler. Relationship between the China and
↪   Malacca were further strengthened by several
↪   envoys to China, led by the Malaccan princes
↪   in the years 1420, 1421 and 1423. Due to"
    },
    {
      "doc_id": "5-4",

```
      "content": "\"Malacca Sultanate\"\nMalacca,
   ↪    Parameswara initiated the development of the
   ↪    place and laid the foundation of a trade port.
   ↪    The indigenous inhabitants of the straits, the
   ↪    Orang Laut, were employed to patrol the
   ↪    adjacent sea areas, to repel other petty
   ↪    pirates, and to direct traders to Malacca.
   ↪    Within years, news about Malacca becoming a
   ↪    centre of trade and commerce began to spread
   ↪    all over the eastern part of the world. In
   ↪    1405, Yongle Emperor of Ming Dynasty (r.
   ↪    1402-1424) sent his envoy headed by Yin Qing
   ↪    to Malacca. Yin Qing's visit opened the way
   ↪    for the establishment of friendly relations
   ↪    between Malacca and"
   },
   {
      "doc_id": "5-5",
      "content": "\"Yongle Emperor\"\nXu Chailao) to
   ↪    that position in 1405. China also had vassals
   ↪    among the leaders in the archipelago. China
   ↪    attained ascendancy in trade with the area in
   ↪    the Yongle Emperor's reign. The local rulers
   ↪    on Luzon were \"\"confirmed\"\" by the
   ↪    governor or \"\"high officer\"\" appointed by
   ↪    the Yongle Emperor. States in Luzon, Sulu
   ↪    (under King Paduka Pahala), Sumatra, and
   ↪    Brunei all established diplomatic relations
   ↪    with the Ming Empire and exchanged envoys and
   ↪    sent tribute to the Yongle Emperor. The Yongle
   ↪    Emperor exchanged ambassadors with Shahrukh
   ↪    Mirza, sending Chen Cheng to Samarkand and
   ↪    Herat, and Shahrukh sent Ghiyāth al-dīn
   ↪    Naqqāsh to Beijing."
   }
]</tool_response><|im_end|>
<|im_start|>assistant
<think>But the question: "the city where the Yongle
↪   emperor greeted the person to whom the edict was
↪   addressed". Edict was addressed to Parameswara
↪   (King of Malacca) maybe? The emperor greeted the
↪   person (Parameswara) at his court in Beijing?
↪   Actually Parameswara traveled to China to pay
↪   homage; he met Yongle Emperor in Beijing. So city
↪   is Beijing.

Now we need "How many miles of highways are in the
↪   city" for Beijing. Let's search "Beijing highways
↪   miles".</think>

<tool_call>
{'name': 'wikipedia_search', 'arguments': {'query':
↪   'Beijing highways mileage', 'top_n': 5}}
</tool_call><|im_end|>
<|im_start|>user
<tool_response>[
   {
      "doc_id": "6-1",
      "content": "Beijing\ntraffic. The Fengtai Railway
   ↪    Station has been closed for renovation. In
   ↪    outlying suburbs and counties of Beijing,
   ↪    there are over 40 railway stations. From
   ↪    Beijing, direct passenger train service is
   ↪    available to most large cities in China.
   ↪    International train service is available to
   ↪    Mongolia, Russia, Vietnam and North Korea.
   ↪    Passenger trains in China are numbered
   ↪    according to their direction in relation to
   ↪    Beijing. Beijing is connected by road links to
   ↪    all parts of China as part of the National
   ↪    Trunk Road Network. Nine expressways of China
   ↪    serve Beijing, as do eleven China National
   ↪    Highways. Beijing's urban transport is
   ↪    dependent upon"
   },
   {
      "doc_id": "6-2",
```

```
      "content": "\"Expressways of Beijing\"\nbeen
   ↪    abandoned as of Yanjiao, Hebei. It is a short
   ↪    and rather old expressway. Route: Beiguan
   ↪    Roundabout - E. 6th Ring Road - Baimiao -
   ↪    Yanjiao - China National Highway 102 Speed
   ↪    Limit: throughout Tolls: As of E. 6th Ring
   ↪    Road, heading east The Jingshen Expressway to
   ↪    Shenyang runs for 658 kilometres and is one of
   ↪    the longest expressways to leave Beijing.
   ↪    Route: Sifang Bridge (E. 4th Ring Road) -
   ↪    Wufang Bridge (E. 5th Ring Road) - Bailu Toll
   ↪    Gate - E. 6th Ring Road - Xianghe (Hebei) -
   ↪    Baodi (Tianjin) - Yutian - Lulong - Beidaihe
   ↪    Area - Shanhaiguan"
   },
   {
      "doc_id": "6-3",
      "content": "\"Beijing Bus\"\nBeijing Bus Public
   ↪    bus service in Beijing is the among the most
   ↪    extensive, widely used and affordable form of
   ↪    public transportation in urban and suburban
   ↪    districts of the city. In 2015, the entire
   ↪    network consisted of 876 routes with a fleet
   ↪    of 24,347 buses and trolleybuses carried 3.98
   ↪    billion passengers annually. Trolleybuses run
   ↪    on over 29 routes including 6, 38, 42, 65,
   ↪    101-112, 114-118, 124, 128, 301, BRT 1-3. Many
   ↪    of these trolleybus routes are located inside
   ↪    the Third Ring Road but some, such as 301 and
   ↪    BRT 1-3, do extend as far out as the Fifth
   ↪    Ring Road. Since"
   },
   {
      "doc_id": "6-4",
      "content": "\"Beijing Subway\"\nBeijing Subway The
   ↪    Beijing Subway is a rapid transit rail network
   ↪    that serves the urban and suburban districts
   ↪    of Beijing municipality. The subway is the
   ↪    world's busiest in annual ridership, with 3.78
   ↪    billion trips delivered in 2017, averaging
   ↪    10.35 million per day, with peak single-day
   ↪    ridership reaching 13.49 million. The subway
   ↪    network has 22 lines, 370 stations and (if not
   ↪    counting Xijiao line, the result is ) of route
   ↪    length in operation, and is the second longest
   ↪    subway system in the world after the Shanghai
   ↪    Metro. The Beijing Subway opened in 1969 and
   ↪    is the oldest metro system in mainland"
   },
   {
      "doc_id": "6-5",
      "content": "\"China National
   ↪    Highways\"\n\"National Highway Network
   ↪    Planning (2013 - 2030)\"\", which will bring
   ↪    the total number of highways to 119, with 81
   ↪    connecting highways between them. The total
   ↪    mileage will be increased to , with increased
   ↪    focus on the western and less developed
   ↪    regions. Although an accepted speed limit on
   ↪    China National Highways is 100 km/h, it is
   ↪    common to see cars pass other by in well in
   ↪    excess of 100 km/h. The lack of speed
   ↪    detection cameras on some routes, lack of a
   ↪    posted speed limit outside of localities and
   ↪    tremendous distances of road mileage, means
   ↪    that enforcing this speed limit is"
   }
]</tool_response><|im_end|>
<|im_start|>assistant
<think>The doc does not give explicit miles.
```

```
Maybe easier: The city could be "Nanjing" as the
↪  imperial capital where Yongle greeted the Karmapa
↪  (person maybe not edict). Edict was the invitation
↪  (the emperor sent message). So the person
↪  addressed to whom the edict was addressed would be
↪  Deshin Shekpa, the Karmapa Lama. The Yongle
↪  emperor greeted Deshin Shekpa in Nanjing (the
↪  city). So answer: "Inside the city of Nanjing,
↪  there are 338 km of highways" which is about 210
↪  miles. Provide citation doc 3-1 (or 4-1) which
↪  says "3.38 kilometers per hundred square
↪  kilometers (5.44 mi/100 sq mi)" but not total
↪  length. However we could compute that total
↪  highways maybe 338 km = 210 miles. Might be
↪  approximate.

But we need explicit miles number. Could be "over 60
↪  state and provincial highways" which is not a
↪  length but count. Not miles.

Thus maybe answer: "not enough information". Because
↪  we cannot get a precise miles figure.

Thus we should answer "not enough information".
↪  Provide rationale: we identified city (Nanjing)
↪  but the Wikipedia excerpt does not give a specific
↪  length in miles for highways.

Thus final answer: not enough information.

Let's verify that we have citation for city
↪  identification: doc 2-1 shows Yongle Emperor
↪  invited Deshin Shekpa to imperial capital, which
↪  was Nanjing. Also doc 3-1 shows highways info
↪  about Nanjing.

Thus we can answer not enough info.

</think>

<answer>
```json
{
  "answer": "not enough information",
  "rationale": "The Yongle Emperor's greeting to the
  ↪  person addressed in the edict (the 5th Karmapa
  ↪  Lama Deshin Shekpa) took place in Nanjing, as
  ↪  the emperor invited him to the imperial capital.
  ↪  However, the Wikipedia excerpt for Nanjing
  ↪  provides the highway coverage density (3.38
  ↪  km/100 km²) and the total number of state and
  ↪  provincial highways (over 60), but it does not
  ↪  specify a total length in miles for the highways
  ↪  within the city. Without a precise mileage
  ↪  figure, the question cannot be answered
  ↪  definitively.",
  "citations": ["2-1", "3-1"]
}
```

</answer><|im_end|>
```

F   Full Experimental Results

The complete aggregated results across all configurations are summarized in Table 4. Additionally, the detailed results for MuSiQue, 2WikiMultihopQA, and HotpotQA can be found in Table 5, Table 6, and Table 7, respectively.

Paradigm	Setting / Initialization	Ratio (%)	r_{ref}	γ	Acc	Refuse	Prec	RA-F1
Data-driven Baselines	SFT with refusal trajectories	0	-	-	0.530	0.000	0.530	0.530
		10	-	-	0.525	0.109	0.593	0.555
		20	-	-	0.512	0.131	0.595	0.548
		30	-	-	0.505	0.107	0.570	0.534
	RL from scratch (Unanswerable)	0	-	-	0.472	0.005	0.474	0.473
		10	-	-	0.483	0.060	0.510	0.496
		20	-	-	0.425	0.293	0.578	0.487
		30	-	-	0.305	0.522	0.588	0.394
	Cold-start RL (Unanswerable)	0	-	-	0.544	0.002	0.545	0.545
		10	-	-	0.545	0.001	0.545	0.545
		20	-	-	0.551	0.004	0.553	0.552
		30	-	-	0.557	0.018	0.567	0.562
Static Reward Baselines	RL from scratch (r_{ref})	-	0.00	-	0.493	0.017	0.500	0.496
		-	0.05	-	0.000	0.999	0.000	0.000
		-	0.10	-	0.000	0.999	0.000	0.000
		-	0.20	-	0.000	0.921	0.000	0.000
	Cold-start RL (r_{ref})	-	0.00	-	0.552	0.012	0.559	0.556
		-	0.20	-	0.488	0.239	0.649	0.553
		-	0.40	-	0.469	0.338	0.708	0.561
		-	0.60	-	0.438	0.421	0.750	0.550
		-	0.80	-	0.426	0.441	0.747	0.540
AWA-RL (Ours)	RL from scratch (γ)	-	-	1.000	0.322	0.360	0.475	0.381
		-	-	0.500	0.381	0.395	0.605	0.459
		-	-	0.250	0.441	0.269	0.581	0.499
		-	-	0.200	0.459	0.246	0.591	**0.515**
		-	-	0.125	0.487	0.104	0.537	0.511
		-	-	0.000	0.493	0.017	0.500	0.496
	Cold-start RL (γ)	-	-	1.000	0.458	0.383	0.738	0.561
		-	-	0.500	0.484	0.306	0.699	0.568
		-	-	0.250	0.509	0.225	0.664	0.573
		-	-	0.200	0.529	0.192	0.662	**0.585**
		-	-	0.125	0.545	0.125	0.628	0.582
		-	-	0.000	0.552	0.012	0.559	0.556

Table 4: Comprehensive experimental results across all training paradigms, settings, and hyperparameters. We report Accuracy (Acc), Refusal Rate (Refuse), Precision (Prec), and Reliability-Aware F1 (RA-F1). The best performing configurations for our proposed AWA-RL in both from-scratch and cold-start settings are highlighted in bold. Dashes (-) indicate that a parameter is not applicable to the specific setting.

Paradigm	Setting / Initialization	Ratio (%)	r_{ref}	γ	Acc	Refuse	Prec	RA-F1
Data-driven Baselines	SFT with refusal trajectories	0	-	-	0.377	0.000	0.377	0.377
		10	-	-	0.371	0.058	0.394	0.382
		20	-	-	0.367	0.066	0.393	0.380
		30	-	-	0.362	0.050	0.381	0.371
	RL from scratch (Unanswerable)	0	-	-	0.274	0.010	0.277	0.275
		10	-	-	0.272	0.096	0.301	0.286
		20	-	-	0.213	0.471	0.403	0.279
		30	-	-	0.094	0.751	0.378	0.151
	Cold-start RL (Unanswerable)	0	-	-	0.378	0.001	0.378	0.378
		10	-	-	0.373	0.000	0.373	0.373
		20	-	-	0.367	0.003	0.368	0.368
		30	-	-	0.373	0.017	0.379	0.376
Static Reward Baselines	RL from scratch (r_{ref})	-	0.00	-	0.279	0.025	0.286	0.283
		-	0.05	-	0.000	1.000	0.000	0.000
		-	0.10	-	0.000	0.999	0.000	0.000
		-	0.20	-	0.000	0.927	0.000	0.000
	Cold-start RL (r_{ref})	-	0.00	-	0.392	0.003	0.393	0.393
		-	0.20	-	0.339	0.195	0.421	0.376
		-	0.40	-	0.324	0.364	0.509	0.396
		-	0.60	-	0.304	0.483	0.588	0.401
		-	0.80	-	0.281	0.507	0.570	0.376
AWA-RL (Ours)	RL from scratch (γ)	-	-	1.000	0.121	0.550	0.269	0.167
		-	-	0.500	0.167	0.642	0.466	0.246
		-	-	0.250	0.212	0.437	0.377	0.271
		-	-	0.200	0.246	0.387	0.401	**0.305**
		-	-	0.125	0.278	0.155	0.329	0.301
		-	-	0.000	0.279	0.025	0.286	0.283
	Cold-start RL (γ)	-	-	1.000	0.321	0.433	0.566	0.410
		-	-	0.500	0.345	0.307	0.498	0.408
		-	-	0.250	0.378	0.179	0.460	0.415
		-	-	0.200	0.395	0.137	0.458	**0.424**
		-	-	0.125	0.395	0.076	0.427	0.411
		-	-	0.000	0.392	0.003	0.393	0.393

Table 5: Detailed experimental results on the **MuSiQue** dataset across all training paradigms and hyperparameters. We report Accuracy (Acc), Refusal Rate (Refuse), Precision (Prec), and Reliability-Aware F1 (RA-F1). The best performing configurations for AWA-RL in both from-scratch and cold-start settings are highlighted in bold. Dashes (-) indicate not applicable.

Paradigm	Setting / Initialization	Ratio (%)	r_{ref}	γ	Acc	Refuse	Prec	RA-F1
Data-driven Baselines	SFT with refusal trajectories	0	-	-	0.515	0.000	0.515	0.515
		10	-	-	0.512	0.228	0.663	0.578
		20	-	-	0.490	0.268	0.669	0.566
		30	-	-	0.489	0.232	0.637	0.553
	RL from scratch (Unanswerable)	0	-	-	0.521	0.003	0.523	0.522
		10	-	-	0.534	0.044	0.559	0.546
		20	-	-	0.482	0.222	0.620	0.542
		30	-	-	0.369	0.449	0.670	0.476
	Cold-start RL (Unanswerable)	0	-	-	0.595	0.004	0.597	0.596
		10	-	-	0.596	0.002	0.597	0.597
		20	-	-	0.610	0.007	0.614	0.612
		30	-	-	0.611	0.033	0.632	0.621
Static Reward Baselines	RL from scratch (r_{ref})	-	0.00	-	0.563	0.013	0.570	0.567
		-	0.05	-	0.000	0.999	0.000	0.000
		-	0.10	-	0.000	0.999	0.000	0.000
		-	0.20	-	0.000	0.895	0.000	0.000
	Cold-start RL (r_{ref})	-	0.00	-	0.591	0.030	0.609	0.600
		-	0.20	-	0.467	0.400	0.778	0.584
		-	0.40	-	0.457	0.447	0.826	0.589
		-	0.60	-	0.425	0.497	0.845	0.566
		-	0.80	-	0.420	0.509	0.835	0.559
AWA-RL (Ours)	RL from scratch (γ)	-	-	1.000	0.402	0.223	0.517	0.452
		-	-	0.500	0.462	0.233	0.602	0.523
		-	-	0.250	0.533	0.155	0.631	0.578
		-	-	0.200	0.551	0.163	0.658	**0.600**
		-	-	0.125	0.559	0.074	0.604	0.580
		-	-	0.000	0.563	0.013	0.570	0.567
	Cold-start RL (γ)	-	-	1.000	0.439	0.476	0.838	0.576
		-	-	0.500	0.465	0.429	0.814	0.592
		-	-	0.250	0.480	0.380	0.774	0.593
		-	-	0.200	0.508	0.341	0.771	0.612
		-	-	0.125	0.545	0.244	0.721	**0.621**
		-	-	0.000	0.591	0.030	0.609	0.600

Table 6: Detailed experimental results on the **2Wiki** dataset across all training paradigms and hyperparameters. We report Accuracy (Acc), Refusal Rate (Refuse), Precision (Prec), and Reliability-Aware F1 (RA-F1). The best performing configurations for AWA-RL in both from-scratch and cold-start settings are highlighted in bold. Dashes (-) indicate not applicable.

Paradigm	Setting / Initialization	Ratio (%)	r_{ref}	γ	Acc	Refuse	Prec	RA-F1
Data-driven Baselines	SFT with refusal trajectories	0	-	-	0.697	0.000	0.697	0.697
		10	-	-	0.692	0.041	0.722	0.706
		20	-	-	0.679	0.059	0.722	0.700
		30	-	-	0.664	0.040	0.692	0.678
	RL from scratch (Unanswerable)	0	-	-	0.620	0.002	0.621	0.621
		10	-	-	0.644	0.040	0.671	0.657
		20	-	-	0.580	0.185	0.712	0.639
		30	-	-	0.453	0.367	0.716	0.555
	Cold-start RL (Unanswerable)	0	-	-	0.660	0.000	0.660	0.660
		10	-	-	0.665	0.000	0.665	0.665
		20	-	-	0.676	0.002	0.677	0.677
		30	-	-	0.688	0.003	0.690	0.689
Static Reward Baselines	RL from scratch (r_{ref})	-	0.00	-	0.636	0.012	0.644	0.640
		-	0.05	-	0.000	0.999	0.000	0.000
		-	0.10	-	0.000	0.999	0.000	0.000
		-	0.20	-	0.000	0.942	0.000	0.000
	Cold-start RL (r_{ref})	-	0.00	-	0.674	0.003	0.676	0.675
		-	0.20	-	0.657	0.121	0.747	0.699
		-	0.40	-	0.627	0.203	0.787	0.698
		-	0.60	-	0.586	0.283	0.817	0.683
		-	0.80	-	0.578	0.308	0.835	0.683
AWA-RL (Ours)	RL from scratch (γ)	-	-	1.000	0.443	0.306	0.638	0.523
		-	-	0.500	0.514	0.311	0.746	0.609
		-	-	0.250	0.578	0.214	0.735	0.647
		-	-	0.200	0.579	0.187	0.712	0.639
		-	-	0.125	0.624	0.082	0.680	**0.651**
		-	-	0.000	0.636	0.012	0.644	0.640
	Cold-start RL (γ)	-	-	1.000	0.614	0.241	0.809	0.698
		-	-	0.500	0.641	0.182	0.784	0.705
		-	-	0.250	0.669	0.116	0.757	0.710
		-	-	0.200	0.684	0.097	0.757	**0.719**
		-	-	0.125	0.694	0.056	0.735	0.714
		-	-	0.000	0.674	0.003	0.676	0.675

Table 7: Detailed experimental results on the **HotpotQA** dataset across all training paradigms and hyperparameters. We report Accuracy (Acc), Refusal Rate (Refuse), Precision (Prec), and Reliability-Aware F1 (RA-F1). The best performing configurations for AWA-RL in both from-scratch and cold-start settings are highlighted in bold. Dashes (-) indicate not applicable.