Fine-tuning Disrupts Edit Readout: A Mechanistic Perspective on Model Editing Robustness

Abstract

Model editing provides a precise way to update the parametric knowledge of Large Language Models (LLMs). However, it has been shown that fine-tuning of edited models for downstream adaptation will erase the intended edits in existing works. This paper studies this problem through the lens of layer-wise information flow in the Transformer. Through systematic layer-wise ablation, we find that edited memory is mainly anchored in shallow editing layers, while fine-tuning primarily disrupts the deep editing layers and adjacent post-edit layers, jointly forming the readout circuitry that decodes this memory into the final prediction. As a result, reverting this readout circuitry alone is often sufficient to recover editing success. We further verify this layer-wise information-flow perspective through null-space analysis and attention-based visualization. Based on this key finding, we propose Layer-wise Model Interpolation (LMI), which interpolates between the edited and fine-tuned model weights with layer-aware coefficients, up-weighting the edited model on the readout circuitry and the fine-tuned model elsewhere. Across three public datasets, two language models, and two editing methods, LMI achieves the best balance between edit preservation and downstream utility. Code is available at https://anonymous.4open.science/r/lmi-FFF0/.

1 Introduction

Large language Models (LLMs) manage memory with two distinct paradigms (Zhao et al., 2025). Short-term memory is saved in the context (Behrouz et al., 2025), whilst long-term memory is saved in parametric weights inside the Transformer architecture (Vaswani et al., 2017). With short-term memory being easily adapted (Zhang et al., 2026), how to adapt long-term memory remains a long-standing challenge due to catastrophic forgetting (Kirkpatrick et al., 2017; Luo et al., 2025; Li et al., 2024a).

Fine-tuning via gradient descent remains the dominant approach for long-term memory updating, but it typically requires substantial data to avoid overfitting (Lai et al., 2025). In contrast, model editing, emerging from mechanistic interpretability research, offers a more precise and data-efficient alternative (Meng et al., 2022, 2023; Fang et al., 2025). However, once an edited model is deployed, it is often further adapted to downstream tasks through conventional fine-tuning. Existing studies have shown that model editing is highly brittle under such adaptation (Wen and Zhang, 2025; Cheng et al., 2025): downstream fine-tuning can overwrite edited knowledge, raising concerns about the practical utility of model editing.

Despite recent studies on the robustness of model editing under fine-tuning, a key research gap remains: it is unclear why such edits are not retained after fine-tuning. This paper offers a mechanistic perspective on the brittleness of model editing from the lens of layer-wise information flow. As illustrated in Fig. 1(C), we partition the Transformer layers into five contiguous groups: *pre-editing, shallow editing, deep editing, adjacent post-editing*, and *remote post-editing layers*. The deep editing and adjacent post-editing layers together form the *readout circuitry* of the edit signal, which is the central object of our analysis. Specifically, through layer-wise reversion, editing success surges back to a high level once the *deep editing layers* and *adjacent post-editing layers* are reverted to their pre-fine-tuning states. This indicates that the knowledge injected by model editing is retained within the editing layers, while fine-tuning predominantly disrupts the readout circuitry that decodes this knowledge into the final prediction. We further verify this hypothesis in a subspace analysis for input-output drifts and also an attention-based interpretability analysis.

Motivated by the layer-wise analysis, we propose a Layer-wise Model Interpolation (LMI) strat-

Figure 1: The edit–finetune–merge pipeline to mitigate edit erasing under downstream fine-tuning. We evaluate on GPT-J-6B with MEMIT edits and ZSRE fine-tuning. (**A**): An edited model $f_{W_{ed}}$ with good editing performance M_{ed} but weak performance M_{ft} in a downstream task. (**B**): A fine-tuned model on the downstream task $f_{W_{ft}}$ achieves decent performance, but model edits are largely destroyed. Our empirical study in Sec. 4.3 indicates the mechanism of this edits erasing and attributes this erasure to disruption in the readout circuitry, i.e. the critical layers for edit retention. (**C**): We partition the Transformer along its depth into five contiguous regions: pre-edit, shallow editing, deep editing, adjacent post-edit, and remote post-edit layers, where the readout circuitry corresponds to the deep editing and adjacent post-edit layers. Our proposed solution LMI achieves a balance between edit retention and downstream knowledge acquisition by adaptively merging layers in $f_{W_{ed}}$ and $f_{W_{ft}}$ informed by the observation in Sec. 4.3.

egy, a variant of model merging techniques (Wortsman et al., 2022), to improve the robustness of model editing in downstream fine-tuning. As illustrated in Figure 1, LMI constructs a merged model via convex interpolation between the edited and the fine-tuned models, with per-layer coefficients drawn from a Gaussian kernel centred on the readout circuitry, giving stronger restoration near the readout region and weaker restoration elsewhere. The proposed solution demonstrates a balance between edit knowledge retention and downstream knowledge acquisition across a variety of experimental settings.

Our main contributions are threefold. First, we introduce a mechanistic perspective on the robustness of model editing under downstream fine-tuning through the lens of layer-wise information flow, revealing that edited knowledge is retained within editing layers, whereas fine-tuning primarily disrupts the readout circuitry that decodes this knowledge into the final prediction. Second, we validate this hypothesis from multiple perspectives, including layer-wise reversion, subspace analysis of input–output drifts, and interpretability analysis using Grad-ELLM (Huang and Chan, 2026). Third, motivated by these findings, we propose Layer-wise Model Interpolation (LMI), a model-merging-based strategy that jointly preserves edited knowledge and acquires downstream knowledge,

and demonstrate its effectiveness across diverse models, editing methods, and adaptation settings.

2 Related Work

2.1 Knowledge Editing in LLMs

Knowledge Editing (KE) aims to update factual knowledge in LLMs without full retraining. Existing methods include parameter-modifying editors, meta-learning editors, and memory-based editors. Parameter-modifying (locate-then-edit) methods such as ROME (Meng et al., 2022) and MEMIT (Meng et al., 2023) directly modify localized factual associations, with later variants improving localization, scalability, or interference control (Fang et al., 2025; Li et al., 2024b; Jiang et al., 2025). Meta-learning methods learn auxiliary update rules (Cao et al., 2021; Mitchell et al., 2022a; Tan et al., 2024), while memory-based methods store or route edits through external memories (Mitchell et al., 2022b; Huang et al., 2023; Hartvigsen et al., 2023; Wang et al., 2024). Our work focuses on parameter-modifying editors, since their edits are committed to model weights and directly exposed to subsequent finetuning.

2.2 Robustness of Knowledge Editing

Recent work (Wen and Zhang, 2025; Cheng et al., 2025) raises concerns over whether KE methods install durable knowledge beyond narrow bench-

mark probes, reporting downstream failures and degradation of unrelated capabilities (Hoelscher-Obermaier et al., 2023; Gu et al., 2024; Gupta et al., 2024; Zhang et al., 2024; Yang et al., 2024). Most directly related to our work are two threads of recent findings on edit fragility: Ji et al. (2025); Wen and Zhang (2025) show that edits decay under continued training, with model behaviour pulled back toward pre-edit outputs (an "elasticity" effect); and Cheng et al. (2025) shows that this damage can be even more severe when fine-tuning targets layers *outside* the editing range, rather than the editing layers themselves. These studies primarily address *when* edits fail empirically, but ignore *why* the failure occurs and how to mitigate it. In contrast, our work introduces a novel perspective on the mechanistic understanding of model editing and validates the effectiveness of our proposed LMI in a wide range of experimental settings.

2.3 Model Merging and Weight Interpolation

Our method interpolates between an edited and a fine-tuned model. Prior work on linear mode connectivity (Frankle et al., 2020; Entezari et al., 2022), model soups(Wortsman et al., 2022), task arithmetic(Ilharco et al., 2023), TIES-Merging(Yadav et al., 2023), and DARE(Yu et al., 2024) show that weight-space operations combine model capabilities under suitable conditions. These methods, however, treat merging as a generic capability-composition tool, typically learning or searching for interpolation coefficients in a task-agnostic manner. In contrast, LMI is directly motivated by our readout-circuitry account of edit retention: rather than treating all layers uniformly, it parameterises per-layer coefficients with a functional prior centred on the layers where edit decoding occurs. To the best of our knowledge, this work is the first to use model merging to address the brittleness of model editing under downstream fine-tuning, and its effectiveness is validated through extensive experiments.

3 Problem Definition

3.1 Task and Objective

We study the robustness of knowledge edits under post-editing fine-tuning. The pipeline has three stages. First, knowledge editing modifies a model's weights to override specific factual associations without retraining as illustrated in figure 1(A). Concretely, an editing algorithm $\mathcal{E}$ (such as MEMIT (Meng et al., 2023), ROME (Meng et al., 2022), or AlphaEdit (Fang et al., 2025)) takes a base model f_{W_0} and an edit set $\mathcal{D}_{\text{edit}} = \{(p_i, o_{\text{true},i}, o_{\text{new},i})\}$, and produces an edited model f_{W_e} that outputs $o_{\text{new},i}$ in place of $o_{\text{true},i}$ for each prompt p_i. Second, the edited model is fine-tuned on a new dataset $\mathcal{D}_{\text{ft}}$, without overlap with the $\mathcal{D}_{\text{edit}}$, yielding $f_{W_{\text{ft}}}$, as shown in figure 1(B). After that, we evaluate whether the edits originally injected by $\mathcal{E}$ are still present in $f_{W_{\text{ft}}}$. Throughout, W_0, W_{ed}, and W_{ft} denote the parameters of f_W at the base, post-edit, and post-finetuning stages, respectively.

This pipeline reflects a realistic deployment scenario: an editor injects facts into a released model, after which the model continues to be fine-tuned on various downstream tasks. Our goal is to design a recovery map $\mathcal{R}$ that takes the two checkpoints $\{W_{\text{ed}}, W_{\text{ft}}\}$ together with a configuration ϕ and produces a final model f_{W^*} retaining as many edits as possible without sacrificing the capability gained from fine-tuning:

$$\phi^* = \arg\max_{\phi} \underbrace{\mathcal{M}_{ed}(f_{W^*}; \mathcal{D}_{\text{edit}})}_{\text{edit retention}}$$

$$\text{where } W^* = \mathcal{R}(W_{\text{ed}}, W_{\text{ft}}, \phi),$$

$$\text{s.t.} \underbrace{\mathcal{M}_{\text{ft}}(f_{W^*}, \mathcal{D}_{\text{ft}}) \geq \mathcal{M}_{\text{ft}}(f_{W_{\text{ft}}}, \mathcal{D}_{\text{ft}}) - \varepsilon.}_{\text{downstream capability preserved}}$$

$$(1)$$

where $\mathcal{M}_{\text{ft}}$ denotes the fine-tuning performance on $\mathcal{D}_{\text{ft}}$. The objective $\mathcal{M}_{ed}$ measures *edit retention*, while the constraint enforces *downstream capability preservation*: the recovery procedure should not degrade the fine-tuning loss beyond a small tolerance ε. Crucially, the search is over the recovery configuration ϕ, which is a low-dimensional search over the design of $\mathcal{R}$. In LMI, this configuration corresponds to the per-layer interpolation coefficients $\{\alpha_\ell\}$ (Sec. 5). This formulation leaves open the question is the choice of $\mathcal{M}_{ed}$: how should we measure whether an edit has actually been retained?

3.2 Edit Retention Measurement

We measure edit retention with three metrics with varying degrees of strictness.
Edit Success (ES) is the loosest: it only checks whether the edited answer o_{new} is assigned higher probability than the original answer o_{true}, comparing two specific tokens:

$$\text{ES} = \mathbb{E}_{\mathcal{D}_{\text{edit}}} \mathbb{1}\left[P_{f_W}(o_{\text{new}} \mid p) > P_{f_W}(o_{\text{true}} \mid p)\right].$$

$$(2)$$

Loose Retain (LR) is intermediate: it asks

(a) MEMIT   (b) AlphaEdit

Figure 2: Edit retention under ZsRE downstream fine-tuning for (a) MEMIT and (b) AlphaEdit (100 MCF edits, GPT-J-6B, lr $= 6 \times 10^{-5}$). A graded collapse emerges across three retention metrics under both editing methods.

whether o_{new} appears anywhere within the first $K = 10$ greedily decoded tokens, requiring the edit to surface in generation but not in any fixed position:

$$\text{LR} = \mathbb{E}_{\mathcal{D}_{\text{edit}}} \mathbb{1}\left[o_{\text{new}} \in \text{Gen}_K(f_W, p) \right]. \quad (3)$$

Edit Accuracy (EA) is the strictest: it requires o_{new} to be the model's actual top-1 prediction:

$$\text{EA} = \mathbb{E}_{\mathcal{D}_{\text{edit}}} \mathbb{1}\left[\arg\max_t P_{f_W}(t \mid p) = o_{\text{new}} \right]. \quad (4)$$

We adopt EA as the primary indicator of edit retention, since it most closely reflects what users observe, and we also report ES and LR as diagnostic auxiliaries.

4 Why Do Edits Degrade Under Finetuning?

In this section, we first show that knowledge edits suffer substantial retention loss after downstream finetuning, and then investigate the mechanism underlying this failure from the perspective of layer-wise information readout.

All experiments in this section use MEMIT (Meng et al., 2023), the first scalable knowledge-editing method and a widely adopted baseline in the field, to inject 100 edits from COUNTERFACT (CF) (Meng et al., 2022) into GPT-J-6B. The edited model is then fine-tuned on 1,000 examples from Zero-Shot Relation Extraction (ZsRE) (Levy et al., 2017a) with MLP-only supervised finetuning, learning rate (lr) $= 6 \times 10^{-5}$ and 10 epochs, unless otherwise noted. MCF and ZsRE are the two standard benchmarks in the knowledge-editing literature: MCF provides counterfactual "subject-relation-object" triples, while ZsRE poses the same relations as open-ended QA. We defer full details of the datasets, model, and training protocol to Sec. 6.

(a) Key drift vs. signal error   (b) Signal direction similarity

Figure 3: Edit signal analysis across edit layers L3–8 (MEMIT, 100 edits, GPT-J-6B; bold line: lr $= 6 \times 10^{-5}$, thin lines: other lr). (a) Despite substantial key drift ($\sim 65\%$), signal error remains low ($\sim 14\%$ at L3–6, rising to $\sim 28\%$ at L8); the shaded gap is filtered by ΔW^l's null space. (b) Cosine similarity between $\Delta W^l \cdot k_{\text{ed}}^l$ and $\Delta W^l \cdot k_{\text{ft}}^l$ stays above 0.99, confirming the edit signal direction is preserved after finetuning.

4.1 Edit Retention Collapses After Finetuning

We track edit retention across finetuning steps using three metrics: **ES**, **EA** and **LR**. LR fills the gap between ES and EA: stricter than a probability comparison, but tolerant of the edit being displaced from the first token by the finetuning task's output format.

Observation 1. ES masks the true extent of edit collapse. Fig. 2 reveals different levels of collapse across the three retention metrics, consistent for both MEMIT and AlphaEdit. ES holds steady at ~ 96–97% throughout fine-tuning, under which edits appear to survive almost intact. LR, however, degrades to ~ 83–84%, while EA collapses from 100% to ~ 25–30%. The collapse of model editing is largely invisible under ES, but becomes apparent only under stricter probes such as LR and EA. Thus, we use EA as the main observational metric in the rest of this section to study the robustness of edits.

4.2 The Edit Signal Survives in Parameter Space

A potential explanation for the collapse is that fine-tuning directly overwrites the edited MLP weights, erasing the injected knowledge (Cheng et al., 2025; Ji et al., 2025). This subsection and the following one show that this intuition is not supported by empirical evidence: the edit signal is largely preserved after finetuning; what breaks is the model's ability to *decode* it into the correct output.

To find out whether the edit signal is erased, we analyze how fine-tuning affects the edited MLP weights. Let $\Delta W^l = W_{\text{ft}}^l - W_{\text{ed}}^l$ denote the weight update injected by fine-tuning at the l-th layer of the edited model ($l = 0$: input; $l = L$: output). Following the key–value memory view of transformer

MLPs (Geva et al., 2021; Meng et al., 2023), we treat the MLP input k^l at the subject's last token as the *key* that retrieves the edited fact, since MEMIT writes the edit specifically at this location. For each edited prompt, we extract the key vector before and after fine-tuning, k^l_{ed} and k^l_{ft}, with $\Delta k^l = k^l_{\text{ft}} - k^l_{\text{ed}}$. We define two diagnostic quantities:

$$key\ drift = \frac{\|\Delta k^l\|}{\|k^l_{\text{ed}}\|}, \tag{5}$$

$$signal\ error = \frac{\|\Delta W^l \cdot \Delta k^l\|}{\|\Delta W^l \cdot k^l_{\text{ed}}\|}. \tag{6}$$

Key drift measures how much the input representation to the edited MLP has shifted, and *signal error* measures the fraction of this shift that actually couples with the fine-tuning weight update ΔW^l to perturb the readout. If finetuning erased the edit, the signal error should align with key drift well.

Observation 2. The edit signal survives fine-tuning despite substantial key drift. Fig. 3a shows that the two quantities diverge sharply. At lr $= 6 \times 10^{-5}$, key drift averages $\sim 66\%$ across edit layers L3–8, yet signal error averages only $\sim 17\%$. The gap (shaded region) indicates that Δk^l lies predominantly in the null space of ΔW^l and produces a negligible change in the MLP readout. Furthermore, Fig. 3b shows the cosine similarity $\cos(\Delta W^l \cdot k^l_{\text{ed}}, \Delta W^l \cdot k^l_{\text{ft}})$ remains above 0.99 on every layer, confirming that the edit signal's *direction* is preserved almost exactly, with only a mild attenuation in magnitude. This pattern holds across all learning rates tested: finetuning moves the keys, but ΔW^l is largely blind to this movement. The edit, as a parameter-space object, is still there. Thus, it is hypothesized that what causes the EA collapse lies not in the edited layers themselves, but in how the model *decodes* this preserved signal into the final prediction. The next subsection localizes this decoding failure.

4.3 The Readout Path Is Disrupted, Not the Edit Signal

We now localize the layers that carry the failure. The experimental tool is a sliding-window MLP restoration: for each 6-layer window $[l, l+5]$, we replace the post-finetuning MLP outputs in that window with their pre-finetuning (edited) counterparts at the relevant token positions, leaving all other layers untouched. We then measure EA on the same 100 edits. This is, in effect, a coarse-grained

(a) MEMIT   (b) AlphaEdit

Figure 4: EA (%) vs. restored 6-layer MLP window after ZsRE supervised finetuning (FT) under two editing methods: (a) MEMIT and (b) AlphaEdit, each compared against a uniform-residual baseline (100 edits). Dashed/dotted lines: only-edited (α=1) and edited+FT (α=0) baselines per setting; yellow shadow: edit layers.

activation patching experiment at the MLP-block level (Vig et al., 2020; Meng et al., 2022): each window asks the counterfactual "what if only these layers had not been fine-tuned?", and the resulting EA quantifies how much each window causally contributes to the EA collapse.

To rule out the possibility that the across-window differences in restoration are an artifact of MEMIT/AlphaEdit's non-uniform residual allocation across the editing layers L3–L8 (Meng et al., 2023; Fang et al., 2025), we additionally include a uniform-residual baseline, in which the same total residual is distributed uniformly across the editing layers. Full details are provided in Appendix A.

Observation 3. Reverting downstream layers recovers edits more effectively than reverting the editing layers themselves. Fig. 4 shows the EA recovery curve across reversion windows for MEMIT and AlphaEdit. The key observation is that reverting the editing layers (L3–L8) is *not* optimal for edit recovery; instead, reverting the layers immediately downstream of the edit region achieves substantially better results. Specifically, the L3–L8 window recovers only 76% EA under both MEMIT and AlphaEdit, whereas reverting L9–L14 alone recovers 89% EA under MEMIT and 95% EA under AlphaEdit. Note that the same downstream peak also appears under the uniform-residual baseline (again peaking at L6-L11 and L9–L14). This rules out the explanation that L6–L14's importance is a side effect of MEMIT's non-uniform allocation of δ across the edit layers.

This empirically grounds the **readout circuitry** introduced in Fig. 1, the L6–L14 band spanning the deep editing (L6–L8) and adjacent post-editing (L9–L14) layers, and motivating our five-region partition in Fig. 1(C). In summary, fine-tuning leaves the edits in edit layers largely intact; it is in this

Table 1: Experimental setup.

Component	Configuration
Models	GPT-J-6B, Llama-3-8B
Editing Methods	MEMIT, AlphaEdit
Edit Datasets	CounterFact, ZsRE
Edit Scales	100, 1K, 10K, full (≈20K)
Fine-tune Methods	SFT, LoRA
Fine-tune Datasets	ZsRE Subset (1,000), SciQ (11,679)
Fine-tune Metrics	Train ACC, Test ACC

downstream band that finetuning disrupts how the signal is decoded.

5 Layer-wise Model Interpolation

The findings from Sec. 4 jointly determine the design of the method. Observation 2 implies that the lost edit can be recovered by operating directly on the existing checkpoints W_{ed} and W_{ft}, rather than re-editing or retraining. Observation 3 implies that this recovery could be layer-wise, since the *readout circuitry* is primarily responsible for edit recovery.

We accordingly propose a Gaussian-smoothed *Layer-wise Model Interpolation (LMI)*, a linear, layer-wise combination of W_{ed} and W_{ft} that concentrates edit weight on the readout circuitry, i.e., the deep editing and adjacent post-edit layers. For each layer $l \in \{0, \ldots, L-1\}$, LMI produces a merged weight by linearly interpolating between the edited and fine-tuned checkpoints with a layer-wise coefficient $\alpha_l \in [0, 1]$:

$$W_{\text{LMI}}^l = \alpha_l \cdot W_{\text{ed}}^l + (1 - \alpha_l) \cdot W_{\text{ft}}^l. \quad (7)$$

The coefficient α_l is defined by a Gaussian kernel over the layer index:

$$\alpha_l = \alpha_{\min} + (\alpha_{\max} - \alpha_{\min}) \cdot \exp\left(-\frac{(l - \mu)^2}{2\sigma^2}\right), \quad (8)$$

where μ is the centre of the kernel, σ its bandwidth, and $[\alpha_{\min}, \alpha_{\max}]$ the per-layer mixing range. Layers near μ receive $\alpha_l \approx \alpha_{\max}$ and retain primarily edited weights; layers far from μ receive $\alpha_l \approx \alpha_{\min}$ and retain more fine-tuned weights. The optimal μ is expected to lie at the boundary between the deep editing and adjacent post-editing layers, carrying primary responsibility for edit recovery, and we will empirically verify this in Fig. 7.

6 Experiments

6.1 Experimental Setup

Our experiments measure how much edited knowledge survives downstream finetuning. Tab. 1 summarizes the setup.

LLMs, Editing and Finetuning Methods. We experiment on two LLMs from different families:

GPT-J-6B (Wang and Komatsuzaki, 2021) and Llama-3-8B (Grattafiori et al., 2024). We evaluate two locate-then-edit methods, MEMIT (Meng et al., 2023) and AlphaEdit (Fang et al., 2025), following the original works in editing layers 3-8 for GPT-J and layers 4-8 for Llama-3. For fine-tuning we consider two regimes: supervised fine-tuning (SFT) and LoRA (Hu et al., 2022), both restricted to the MLP sublayers so that finetuning directly perturbs the edited parameters.

Datasets and Metrics. We edit with two standard benchmarks, COUNTERFACT (CF) (Meng et al., 2022) and ZsRE (Levy et al., 2017b), at four *edit scales*: 100, 1K, 10K, and the full dataset (≈20K). As defined in Sec. 3.2, we measure knowledge retention with ES and EA and LR. Additionally, we report paraphrase score (PS), neighborhood score (NS), generation entropy (GE), and reference score (RS) (Meng et al., 2023) to assess generalization and locality of the surviving edits. For finetuning, we report Train ACC (Tr.) and Test ACC (Te.) to quantify fine-tuning quality.

Baselines. We compare LMI against two recovery baselines. (i) *Restore Crucial Layers (RCL)*. We identify the *readout circuitry* layers, and replace their post-finetune weights with the corresponding pre-finetune (post-edit) weights, leaving all other layers untouched. We select layers 6–14 for GPT-J-6B and layers 5–16 for Llama3-8B, matching the readout regions identified in our mechanistic analysis. (ii) *Uniform Model Interpolation (UMI)*. Every layer is interpolated between the post-finetune and post-edit checkpoints with the same coefficient,

$$W_l^{(\alpha)} = (1 - \alpha) W_l^{\text{FT}} + \alpha W_l^{\text{edit}}, \quad \forall l, \quad (9)$$

and the single coefficient $\alpha \in [0, 1]$ is swept to find the sweet spot α^*. Note that both baselines can be viewed as degenerate versions of LMI: UMI uses a constant α_l across all layers (recovered as $\sigma \to \infty$ with $\alpha_{\min} = \alpha_{\max}$), while RCL uses a binary $\alpha_l \in \{0, 1\}$ profile concentrated on the readout block.

6.2 Results Analysis

Fine-tuning substantially erases edits. Tab. 2 shows that, even a brief round of ZsRE SFT causes EA on CF drop sharply. On GPT-J-6B with MEMIT, EA falls from 100.0% to 25.0% at the 10^2 scale and from 85.1% to 5.9% at the full scale; on Llama3-8B the collapse is even more severe, with EA dropping below 5% in most rows. AlphaEdit shows the same pattern. This damage is consistent

Table 2: Edit accuracy and downstream retention across editing methods, before and after ZsRE fine-tuning. We compare three recovery methods: restore crucial layers (RCL), uniform model interpolation, and layer-wise model interpolation (LMI, ours). Full evaluation. EA: edit accuracy; Tr. and Te. denote ZsRE training and test accuracy. EA/Tr./Te. are reported as percentages (%). α^* is the selected uniform interpolation coefficient; μ^*/σ^* is the selected Gaussian center/width for LMI. For each row, the best value among RCL/Uniform/LMI is **bolded** and the second-best is underlined.

Model	Method @ Scale	Post-Edit	Post-Fine-tune			RCL			UMI				LMI (Ours)			
		EA	EA	Tr.	Te.	EA	Tr.	Te.	EA	Tr.	Te.	α^*	EA	Tr.	Te.	μ^*/σ^*
GPT-J-6B	MEMIT @ 10^2	100.0	25.0	100.0	21.0	97.0	96.2	19.0	**100.0**	**96.6**	**22.0**	0.5	**100.0**	94.6	21.0	6/5
	MEMIT @ 10^3	96.5	8.7	100.0	16.0	62.9	**91.3**	16.0	83.4	86.0	**22.0**	0.6	**90.0**	91.2	17.0	6/5
	MEMIT @ 10^4	95.5	11.6	100.0	17.0	57.4	**95.4**	16.0	81.8	86.1	18.0	0.6	**84.1**	91.7	16.0	6/5
	MEMIT @ Full	85.1	5.9	100.0	16.0	34.7	**92.1**	20.0	68.9	81.8	20.0	0.6	**73.0**	86.6	16.0	4/5
	AlphaEdit @ 10^2	100.0	31.0	100.0	20.0	96.0	95.8	19.0	97.0	**99.0**	21.0	0.4	**100.0**	97.7	17.0	6/4
	AlphaEdit @ 10^3	99.8	27.4	100.0	19.0	86.4	97.1	19.0	95.9	97.4	**23.0**	0.5	**96.9**	**98.0**	16.0	6/4
	AlphaEdit @ 10^4	92.7	6.0	100.0	15.0	31.2	90.9	**14.0**	**72.0**	81.8	9.0	0.6	58.7	**95.5**	13.0	6/4
	AlphaEdit @ Full	57.6	0.4	100.0	17.0	1.5	46.7	9.0	18.3	**77.3**	15.0	0.5	**40.2**	41.7	6.0	3/4
Llama3-8B	MEMIT @ 10^2	100.0	2.0	100.0	27.0	10.0	98.6	25.0	58.0	**99.0**	**43.0**	0.6	**83.0**	92.2	37.0	10/14
	MEMIT @ 10^3	93.3	3.1	100.0	22.0	9.0	98.7	27.0	54.3	**98.8**	39.0	0.6	**72.9**	90.4	**41.0**	10/14
	MEMIT @ 10^4	83.9	2.0	100.0	14.0	6.8	**98.2**	25.0	**56.7**	82.6	33.0	0.8	53.9	93.7	32.0	10/14
	MEMIT @ Full	79.9	1.5	100.0	15.0	4.6	**98.5**	21.0	**50.7**	83.1	43.0	0.8	50.5	94.6	37.0	7/14
	AlphaEdit @ 10^2	100.0	2.0	100.0	21.0	31.0	**98.9**	28.0	79.0	98.7	40.0	0.6	**95.0**	90.4	34.0	9/14
	AlphaEdit @ 10^3	99.9	4.0	100.0	17.0	16.4	**99.1**	35.0	65.4	98.8	42.0	0.6	**89.3**	94.2	34.0	9/14
	AlphaEdit @ 10^4	92.2	2.0	100.0	14.0	5.1	**99.8**	17.0	**68.6**	82.2	34.0	0.8	66.8	95.3	20.0	9/14
	AlphaEdit @ Full	85.4	2.0	100.0	17.0	4.9	98.2	18.0	33.1	**99.6**	26.0	0.6	**59.5**	95.2	20.0	7/14

(a) Transfer to LoRA finetuning (GPT-J left, Llama-3 right)

(b) Transfer to ZsRE editing (GPT-J left, Llama-3 right)

(c) Transfer to SciQ finetuning (GPT-J left, Llama-3 right)

Figure 5: Recovery gains over post-finetune checkpoints across different finetuning methods, editing tasks, and downstream finetuning tasks, all of these experiments are conducted on @full scale editing.

Figure 6: Behavioral profile on CounterFact (ES, EA, PS, NS, GE, RS) for GPT-J at four edit scales. LMI (green) tracks the post-edit profile (blue) on most axes, while post-finetune (red) contracts substantially.

across models, editors, and edit scales, confirming that knowledge edits are extremely fragile to subsequent fine-tuning.

LMI recovers most of the lost edits and outperforms baselines. LMI restores CF edit accuracy far beyond the post-finetune checkpoint, e.g., from 5.9% to 73.0% (GPT-J, MEMIT @ Full) and from 2.0% to 83.0% (Llama3, MEMIT @ 10^2). Across the 16 settings, LMI achieves the highest EA in 12 rows; the localized RCL baseline never wins; UMI wins only in the highest-scale Llama3 regime. This indicates that effective recovery requires both interpolation and localization to the readout circuitry.

Downstream performance is preserved, and often improved. Surprisingly, LMI's ZsRE test accuracy (Te.) is comparable to or higher than the post-finetune checkpoint in nearly every row. On Llama3-8B with MEMIT @ 10^3, Te. rises from 22.0% post-finetune to 41.0% after LMI; with AlphaEdit @ 10^3 it rises from 17.0% to 34.0%. LMI does sacrifice some ZsRE training accuracy (Tr.), e.g., from 100.0% post-finetune to 91.2% on GPT-J with MEMIT @ 10^3, and to 90.4% on Llama3 with AlphaEdit @ 10^2, but this drop is consistently small and is dwarfed by the corresponding gains

Figure 7: Ablation on the Gaussian center μ (with $\sigma = 5$ fixed) for GPT-J, editing 1K CounterFact facts with MEMIT and finetuning on 1K ZsRE.

Figure 8: Layer-wise attribution difference for the answer token between the fine-tuned and MEMIT-edited models. Rows are sliding layer windows; columns are prompt tokens. Red/blue indicates that finetuning attributes more/less than MEMIT to a token.

in EA, which are tens of points in absolute terms. Notably, UMI consistently surpasses LMI on downstream Te., making it the preferred choice when downstream deployment prioritises preserving the fine-tuned model's task capability.

Generalization. We further evaluate whether LMI generalizes beyond a single edit-finetune configuration. Fig. 5 compares LMI with uniform interpolation and RCL across three transfer settings: LoRA finetuning, ZsRE-space editing, and SciQ finetuning. In all cases, the plots report recovery gains over the post-finetune checkpoint on edit accuracy (ΔEA) and downstream accuracy (ΔTr., ΔTe.). Across both GPT-J and Llama-3, LMI consistently achieves the strongest recovery in EA, while maintaining competitive downstream performance. This pattern holds when changing the finetuning recipe, the edit dataset, and the downstream finetuning task. In contrast, uniform interpolation provides weaker edit recovery, and RCL often recovers substantially less EA. These results suggest that LMI captures a more robust layer-wise trade-off between edit retention and downstream adaptation.

Recovery Extends Beyond Edit Accuracy. Beyond edit retention, we examine whether LMI restores the broader behavioral profile of the edited model. Fig. 6 reports paraphrase score (PS), neighborhood score (NS), generation entropy (GE), and reference score (RS), alongside ES and EA. For both MEMIT and AlphaEdit on GPT-J, finetuning distorts this profile across all edit scales, reducing not only edit retention but also paraphrase generalization and reference-based scores. LMI closely tracks the post-edit profile on most axes, indicating that recovery is not confined to edit success but extends to generalization, locality, and generation quality.

Ablation Study. Fig. 7 ablates μ, which sets the layers that receive the highest edit weight, with $\sigma=5$ fixed. The recovery of edit (EA) is strongly unimodal in μ, peaking at $\mu=6$, whereas fine-tune retention (Tr.) stays essentially flat ($\sim$91%) across the entire sweep. The optimum therefore reflects *where* edits are read out rather than a trade-off against forgetting.

Case Study. Fig. 8 presents the attribution difference across MLP layers in GPT-J for the answer token between the supervised fine-tuned and the MEMIT-edited model, using Grad-ELLM (Huang and Chan, 2026). The vertical axis indexes the layer windows and the horizontal axis the prompt tokens, with red (blue) indicating that finetuning attributes more (less) to a given token than MEMIT. Within the edited layers (L3-8), attribution remains largely unchanged by finetuning, indicating that the stored edit signal is preserved. From the readout layers onward, starting at window L6-11, the prompt evidence on which the answer token relies shifts substantially, indicating that finetuning rewires the model's internal retrieval pathway for the edited fact at the readout layers.

7 Conclusion

This paper revisits the brittleness of model editing under downstream fine-tuning from a mechanistic perspective. Through layer-wise reversion, supported by null-space subspace analysis and Grad-ELLM attribution, we show that edited knowledge is preserved in the early editing layers, while fine-tuning primarily disrupts the later readout layers that decode it into the final prediction. Motivated by this finding, we propose Layer-wise Model Interpolation, which merges the pre- and post-fine-tuning weights of the critical readout layers under a layer-aware Gaussian kernel. Across three datasets, two language models, and two editing methods, LMI consistently achieves the best balance between edit retention and downstream utility.

Limitations

Scope of editors and fine-tuning regimes.
Our analysis covers two locate-then-edit editors
(MEMIT, AlphaEdit) and two fine-tuning regimes
(MLP-only SFT, MLP-only LoRA), all writing into
MLP sublayers of decoder-only Transformers. We
do not study memory-based editors (e.g., GRACE,
WISE), meta-learning editors (e.g., MEND, KE).
Whether the readout-circuitry account extends to
these settings is an open question.

Model and data coverage. Experiments span
GPT-J-6B and Llama-3-8B, two decoder-only mod-
els in the 6–10B parameter range. It is unclear
whether the results transfer to substantially larger
scales (e.g., Llama-3-70B, where the readout band
may require a larger σ), encoder–decoder architec-
tures, or mixture-of-experts models.

Caveats on mechanistic claims. The readout-
circuitry framing is one interpretation supported by
three converging probes (layer-wise reversion, null-
space analysis, Grad-ELLM attribution); alterna-
tive accounts, for instance one centred on attention
rather than MLPs, remain compatible with parts of
our data.

References

Ali Behrouz, Peilin Zhong, and Vahab Mirrokni. 2025.
Titans: Learning to memorize at test time. *Advances
in Neural Information Processing Systems (NeurIPS)*.

Nicola De Cao, Wilker Aziz, and Ivan Titov. 2021.
Editing factual knowledge in language models. In
*Proceedings of the 2021 Conference on Empirical
Methods in Natural Language Processing (EMNLP)*,
pages 6491–6506.

Siyuan Cheng and 1 others. 2025. Can fine-tuning
erase your edits? on the fragile coexistence of
knowledge editing and adaptation. *arXiv preprint
arXiv:2511.05852*.

Rahim Entezari, Hanie Sedghi, Olga Saukh, and
Behnam Neyshabur. 2022. The role of permutation
invariance in linear mode connectivity of neural net-
works. In *The Tenth International Conference on
Learning Representations (ICLR)*.

Junfeng Fang, Houcheng Jiang, Kun Wang, Yunshan
Ma, Jie Shi, Xiang Wang, Xiangnan He, and Tat-
Seng Chua. 2025. AlphaEdit: Null-space constrained
knowledge editing for language models. In *The Thir-
teenth International Conference on Learning Repre-
sentations (ICLR)*.

Jonathan Frankle, Gintare Karolina Dziugaite, Daniel M.
Roy, and Michael Carbin. 2020. Linear mode connec-
tivity and the lottery ticket hypothesis. In *Proceed-
ings of the 37th International Conference on Machine
Learning (ICML)*.

Mor Geva, Roei Schuster, Jonathan Berant, and Omer
Levy. 2021. Transformer feed-forward layers are
key-value memories. In *Proceedings of the 2021
Conference on Empirical Methods in Natural Lan-
guage Processing (EMNLP)*, pages 5484–5495.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri,
and 1 others. 2024. The Llama 3 herd of models.
arXiv preprint arXiv:2407.21783.

Jia-Chen Gu, Hao-Xiang Xu, Jun-Yu Ma, Pan Lu, Zhen-
Hua Ling, Kai-Wei Chang, and Nanyun Peng. 2024.
Model editing harms general abilities of large lan-
guage models: Regularization to the rescue. *arXiv
preprint arXiv:2401.04700*.

Akshat Gupta, Anurag Rao, and Gopala Anu-
manchipalli. 2024. Model editing at scale leads
to gradual and catastrophic forgetting. In *Findings
of the Association for Computational Linguistics:
(NAACL) 2024*.

Thomas Hartvigsen, Swami Sankaranarayanan, Hamid
Palangi, Yoon Kim, and Marzyeh Ghassemi. 2023.
Aging with GRACE: Lifelong model editing with
discrete key-value adaptors. In *Advances in Neural
Information Processing Systems (NeurIPS)*.

Jason Hoelscher-Obermaier, Julia Persson, Esben Kran,
Ioannis Konstas, and Fazl Barez. 2023. Detecting
edit failures in large language models: An improved
specificity benchmark. In *Findings of the Association
for Computational Linguistics: ACL 2023*, pages
11548–11559.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan
Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and
Weizhu Chen. 2022. LoRA: Low-rank adaptation of
large language models. In *International Conference
on Learning Representations (ICLR)*.

Xin Huang and Antoni B. Chan. 2026. Grad-ellm:
Gradient-based explanations for decoder-only llms.
Preprint, arXiv:2601.03089.

Zeyu Huang, Yikang Shen, Xiaofeng Zhang, Jie Zhou,
Wenge Rong, and Zhang Xiong. 2023. Transformer-
patcher: One mistake worth one neuron. In *The
Eleventh International Conference on Learning Rep-
resentations (ICLR)*.

Gabriel Ilharco, Marco Tulio Ribeiro, Mitchell Worts-
man, Suchin Gururangan, Ludwig Schmidt, Han-
naneh Hajishirzi, and Ali Farhadi. 2023. Editing
models with task arithmetic. In *The Eleventh Inter-
national Conference on Learning Representations
(ICLR)*.

Jiaming Ji, Kaile Wang, Tianyi Alex Qiu, Boyuan Chen, Jiayi Zhou, Changye Li, Hantao Lou, Josef Dai, Yunhuai Liu, and Yaodong Yang. 2025. Language models resist alignment: Evidence from data compression. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (ACL)*.

Houcheng Jiang, Junfeng Fang, Ningyu Zhang, Guojun Ma, Mingyang Wan, Xiang Wang, Xiangnan He, and Tat-Seng Chua. 2025. AnyEdit: Edit any knowledge encoded in language models. In *Proceedings of the 42nd International Conference on Machine Learning (ICML)*.

James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, and 1 others. 2017. Overcoming catastrophic forgetting in neural networks. *Proceedings of the national academy of sciences*, 114(13):3521–3526.

Hanyu Lai, Xiao Liu, Junjie Gao, Jiale Cheng, Zehan Qi, Yifan Xu, Shuntian Yao, Dan Zhang, Jinhua Du, Zhenyu Hou, Xin Lv, Minlie Huang, Yuxiao Dong, and Jie Tang. 2025. A survey of post-training scaling in large language models. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*.

Omer Levy, Minjoon Seo, Eunsol Choi, and Luke Zettlemoyer. 2017a. Zero-shot relation extraction via reading comprehension. In *Proceedings of the 21st Conference on Computational Natural Language Learning (CoNLL 2017)*.

Omer Levy, Minjoon Seo, Eunsol Choi, and Luke Zettlemoyer. 2017b. Zero-shot relation extraction via reading comprehension. In *Proceedings of the 21st Conference on Computational Natural Language Learning (CoNLL)*, pages 333–342.

Hongyu Li, Liang Ding, Meng Fang, and Dacheng Tao. 2024a. Revisiting catastrophic forgetting in large language model tuning. In *Findings of the association for computational linguistics: EMNLP 2024*.

Xiaopeng Li, Shasha Li, Shezheng Song, Jing Yang, Jun Ma, and Jie Yu. 2024b. PMET: Precise model editing in a transformer. In *Proceedings of the AAAI Conference on Artificial Intelligence*.

Yun Luo, Zhen Yang, Fandong Meng, Yafu Li, Jie Zhou, and Yue Zhang. 2025. An empirical study of catastrophic forgetting in large language models during continual fine-tuning. *IEEE Transactions on Audio, Speech and Language Processing*.

Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. 2022. Locating and editing factual associations in GPT. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Kevin Meng, Arnab Sen Sharma, Alex J. Andonian, Yonatan Belinkov, and David Bau. 2023. Mass-editing memory in a transformer. In *The Eleventh International Conference on Learning Representations (ICLR)*.

Eric Mitchell, Charles Lin, Antoine Bosselut, Chelsea Finn, and Christopher D. Manning. 2022a. Fast model editing at scale. In *The Tenth International Conference on Learning Representations (ICLR)*.

Eric Mitchell, Charles Lin, Antoine Bosselut, Christopher D. Manning, and Chelsea Finn. 2022b. Memory-based model editing at scale. In *Proceedings of the 39th International Conference on Machine Learning (ICML)*, Proceedings of Machine Learning Research.

Chenmien Tan, Ge Zhang, and Jie Fu. 2024. Massive editing for large language models via meta learning. In *The Twelfth International Conference on Learning Representations (ICLR)*.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. *Advances in neural information processing systems (NeurIPS)*.

Jesse Vig, Sebastian Gehrmann, Yonatan Belinkov, Sharon Qian, Daniel Nevo, Yaron Singer, and Stuart Shieber. 2020. Investigating gender bias in language models using causal mediation analysis. In *Advances in Neural Information Processing Systems(NeurIPS)*, volume 33.

Ben Wang and Aran Komatsuzaki. 2021. GPT-J-6B: A 6 billion parameter autoregressive language model. https://github.com/kingoflolz/mesh-transformer-jax.

Peng Wang, Zexi Li, Ningyu Zhang, Ziwen Xu, Yunzhi Yao, Yong Jiang, Pengjun Xie, Fei Huang, and Huajun Chen. 2024. WISE: Rethinking the knowledge memory for lifelong model editing of large language models. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Johannes Welbl, Nelson F. Liu, and Matt Gardner. 2017. Crowdsourcing multiple choice science questions. In *Proceedings of the 3rd Workshop on Noisy User-generated Text (W-NUT)*, pages 94–106.

Fufang Wen and Shichang Zhang. 2025. On the retention of edited knowledge in fine-tuned language models. *arXiv preprint arXiv:2507.14198*.

Mitchell Wortsman, Gabriel Ilharco, Samir Yitzhak Gadre, Rebecca Roelofs, Raphael Gontijo-Lopes, Ari S. Morcos, Hongseok Namkoong, Ali Farhadi, Yair Carmon, Simon Kornblith, and Ludwig Schmidt. 2022. Model soups: Averaging weights of multiple fine-tuned models improves accuracy without increasing inference time. In *Proceedings of the 39th International Conference on Machine Learning (ICML)*.

Prateek Yadav, Derek Tam, Leshem Choshen, Colin Raffel, and Mohit Bansal. 2023. TIES-merging: Resolving interference when merging models. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Qi Yang, Jiawei Wang, Yifan Yang, Jian Liu, and Jingyuan Wang. 2024. Should we really edit language models? on the evaluation of edited language models. In *Proceedings of the 38th International Conference on Neural Information Processing Systems (NeurIPS)*.

Le Yu, Bowen Yu, Haiyang Yu, Fei Huang, and Yongbin Li. 2024. Language models are super Mario: Absorbing abilities from homologous models as a free lunch. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*.

Ningyu Zhang, Yunzhi Yao, Bozhong Tian, Peng Wang, Shumin Deng, Mengru Wang, Zekun Xi, Shengyu Mao, Jintian Zhang, Yuansheng Ni, Siyuan Cheng, Ziwen Xu, Xin Xu, Jia-Chen Gu, Yong Jiang, Pengjun Xie, Fei Huang, Lei Liang, Zhiqiang Zhang, and 3 others. 2024. A comprehensive study of knowledge editing for large language models. *arXiv preprint arXiv:2401.01286*.

Qizheng Zhang, Changran Hu, Shubhangi Upasani, Boyuan Ma, Fenglu Hong, Vamsidhar Kamanuru, Jay Rainton, Chen Wu, Mengmeng Ji, Hanchen Li, Urmish Thakker, James Zou, and Kunle Olukotun. 2026. Agentic context engineering: Evolving contexts for self-improving language models. In *The Fourteenth International Conference on Learning Representations (ICLR)*.

Jun Zhao, Yongzhuo Yang, Xiang Hu, Jingqi Tong, Yi Lu, Wei Wu, Tao Gui, Qi Zhang, and Xuanjing Huang. 2025. Understanding parametric and contextual knowledge reconciliation within large language models. *Advances in Neural Information Processing Systems (NeurIPS)*.

Supplementary Materials

A   Uniform Residual Baseline

When applying multi-layer edits, MEMIT and AlphaEdit distribute the target residual increment δ non-uniformly across the edit layers L3–8: later layers carry a larger share, induced by the recursive formula that splits the remaining residual among the remaining layers. This non-uniform allocation could itself introduce a structural bias within the edit layers, making certain downstream layers *appear* disproportionately important when in fact the effect merely reflects the allocation scheme rather than any property of the readout. To rule out this explanation, we introduce a **uniform-residual baseline**: holding the total δ fixed, we instead allocate it *uniformly* across L3–8 ($\delta/6$ per layer), keeping the rest of the MEMIT/AlphaEdit pipeline unchanged, and then run the same sliding-window restoration experiment on top of this variant. If the downstream-window peak persists under uniform allocation, we can rule out the explanation that the phenomenon is an artifact of how the edit signal is distributed within the edit layers.

B   Experimental Setup

This appendix gives the full specification used to produce every number reported in the main text. We list the language models (§B.1), the two locate-then-edit editors (§B.2), the two downstream fine-tuning regimes (§B.3), the datasets and the train/eval splits used to compute every metric (§B.4), the evaluation protocol (§B.5), the three recovery procedures (§B.6), the hyperparameter selection rule (§B.7), and the compute environment (§B.8). All configuration values below are exactly the ones used in our released YAML/scripts.

B.1 Language Models

We use two open-weight decoder-only LLMs. GPT-J-6B (Wang and Komatsuzaki, 2021) has $L{=}28$ Transformer blocks, hidden size 4096, an MLP intermediate size of 16384 with the standard ReLU two-layer FFN (fc_in→fc_out). Llama-3-8B (Grattafiori et al., 2024) has $L{=}32$ blocks, hidden size 4096, intermediate size 14336, and a gated SwiGLU MLP whose down-projection down_proj plays the role of the second linear layer that edits write into. Both models are stored and fine-tuned in bfloat16; the per-layer MEMIT/AlphaEdit second-moment statistics that drive the closed-form update are kept in float32. Layer indices are 0-based.

B.2 Editing Methods

We evaluate two locate-then-edit editors that write into the MLP *output* matrix at the subject's last-token position.

MEMIT (Meng et al., 2023). Edit layers are $\{3, 4, 5, 6, 7, 8\}$ for GPT-J and $\{4, 5, 6, 7, 8\}$ for Llama-3, matching the original works. The optimizer used to find the per-edit target value v^* runs for 25 gradient steps with learning rate 0.5 on GPT-J and 0.1 on Llama-3, weight decay 0.5, a KL anchor on the unedited distribution with weight 0.0625, and a clamp-norm factor of 0.75. The second-moment matrix used by the closed-form key-projection step is estimated from 10^5 Wikipedia samples and stored in float32; the mixing weight λ for this matrix is 15,000. Edits rewrite transformer.h.{l}.mlp.fc_out on GPT-J and model.layers.{l}.mlp.down_proj on Llama-3, with the loss anchored at the final block (layer 27 for GPT-J, layer 31 for Llama-3).

AlphaEdit (Fang et al., 2025). AlphaEdit shares the same edit layers, KL weight, clamp factor, v^* optimizer, second-moment matrix, and rewrite modules as MEMIT. It adds a null-space projector P pre-computed once per model from the second-moment statistics with a null-space threshold of $2{\times}10^{-2}$, plus an explicit Tikhonov term $L_2{=}10$ on GPT-J and $L_2{=}1$ on Llama-3.

Edit scales. We edit at four scales: 10^2, 10^3, 10^4, and the full CF split ($\approx 2.1{\times}10^4$ edits). At each scale we pre-cache an edited checkpoint $f_{W_{\mathrm{ed}}}$ that is then re-used by all downstream-finetuning and recovery experiments, so $f_{W_{\mathrm{ed}}}$ is identical across rows that share a model×method×scale cell.

B.3 Downstream Fine-tuning

In every fine-tuning run, the trainable parameters are restricted to the MLP sublayers (the two FFN matrices on GPT-J, and gate_proj/up_proj/down_proj on Llama-3). This is the same parameter set that MEMIT/AlphaEdit modify, so fine-tuning directly perturbs the edited weights. All other parameters (attention, embeddings, layernorms, lm-head) are frozen.

Supervised fine-tuning (SFT). We use AdamW in bfloat16, per-device batch size 2 with gradient accumulation 4 (effective batch 8), maximum sequence length 256, gradient clipping at 1.0, and 10 epochs. The learning rates are $6{\times}10^{-5}$ on GPT-J and $1{\times}10^{-4}$ on Llama-3, held constant throughout training; we observed in pilot sweeps that further tuning the learning rate has a small effect on the qualitative collapse pattern reported in §4.

LoRA. We attach LoRA adapters (Hu et al., 2022) with rank $r{=}16$, scaling $\alpha_{\mathrm{LoRA}}{=}32$, and dropout 0.05 on the same MLP target modules. LoRA fine-tuning uses batch size 32, 10 epochs, learning rate $8{\times}10^{-4}$ for both models, with the rest of the optimization configuration matching SFT. To form a single weight-space checkpoint that the recovery procedures of §B.6 can interpolate, we merge the LoRA adapters back into the base MLP matrices before evaluation.

B.4 Datasets and Train/Test Splits

Edit datasets. COUNTERFACT (CF) (Meng et al., 2022) contains $\sim$ 21,919 counterfactual subject-relation-object triples; at scale S we edit the first S records and report edit-retention metrics on exactly those S records (no edit is ever evaluated on records it was not applied to). ZsRE (Levy et al., 2017b)

contains the same relations posed as open-ended QA; we use it both as an edit dataset (for the ZsRE-edit→CF-FT transfer experiment) and as a downstream fine-tuning dataset.

Downstream fine-tuning datasets. For the main ZsRE-SFT/LoRA experiments, the training set is the first 1,000 ZsRE examples and the held-out test set is a disjoint 100-example slice; this matches the protocol used in §4 of the main text. For the SciQ experiments (Welbl et al., 2017), we use the full `allenai/sciq` training split (11,679 examples; scripts pass `train_size=12000` and SciQ caps it to the available size), with 1,000 examples held out as a validation slice and the standard 1,000-example SciQ validation split for test reporting. For the ZsRE-edit→CF-FT transfer experiment we fine-tune on the first 1,000 CF records (using `target_true` as the supervision target so that fine-tuning pushes the model toward the *un-edited* answer).

Disjointness. The fine-tuning train sets never overlap with the edit set: CF and ZsRE share relations but use disjoint records, and SciQ is from an entirely different domain (science exam QA).

B.5 Evaluation Protocol

Edit-retention metrics. For every reported number we evaluate edit retention on *all* edited cases at that scale ($S \in \{10^2, 10^3, 10^4, \approx 2.1 \times 10^4\}$); we never sub-sample the edit set. ES, LR, EA are defined exactly as in §3.2 of the main text. LR uses greedy decoding for $K{=}10$ tokens; EA is the strict top-1 argmax probe; ES is the two-token probability comparison.

Downstream metrics. Train accuracy (Tr.) is computed on the same 1,000 records used for fine-tuning, and test accuracy (Te.) on the held-out slice described in §B.4. For SFT/LoRA on ZsRE/SciQ, we use greedy decoding with a maximum of 10 new tokens and exact-match scoring against the gold answer. Eval batch size is 1 on SFT (to match the edit-eval pipeline) and 64 on LoRA.

Generalization metrics (Figure 6). Paraphrase score (PS), neighborhood score (NS), generation entropy (GE), and reference score (RS) follow the definitions of Meng et al. (2023) and are computed on the same edited records as ES/EA, using the official MEMIT evaluation harness.

B.6 Recovery Procedures

All three recovery procedures take the two cached checkpoints $\{W_{\text{ed}}, W_{\text{ft}}\}$ and produce a single recovered checkpoint W^* via per-parameter weight interpolation. No additional training or re-editing is performed.

Restore Crucial Layers (RCL). We overwrite the post-FT MLP weights with the post-edit MLP weights inside a fixed layer band and leave every other layer untouched. The band is layers $[6, 14]$ on GPT-J and $[5, 16]$ on Llama-3, matching the readout regions identified in §4.3. RCL is a binary $\alpha_\ell \in \{0, 1\}$ profile.

Uniform Model Interpolation (UMI). A single coefficient $\alpha \in [0, 1]$ is applied to every MLP layer: $W_\ell^{(\alpha)} = \alpha W_\ell^{\text{ed}} + (1{-}\alpha)W_\ell^{\text{ft}}$. We sweep $\alpha \in \{0.1, 0.2, \ldots, 0.9\}$ together with the endpoints $\{0.0, 1.0\}$ and report the sweet-spot α^* chosen by the rule in §B.7.

Layer-wise Model Interpolation (LMI, ours). The per-layer coefficient is a Gaussian kernel

$$\alpha_\ell \;=\; \alpha_{\min} + (\alpha_{\max} - \alpha_{\min})\,\exp\!\left(-\frac{(\ell-\mu)^2}{2\sigma^2}\right), \tag{10}$$

with $\alpha_{\min}{=}0.1$, $\alpha_{\max}{=}0.9$ throughout. The center μ is swept over integer layer indices and the bandwidth σ is taken from a small per-setting grid (Table 3). We did *not* sweep μ and σ jointly: σ is fixed up-front based on whether the setting concentrates the readout circuitry tightly (GPT-J, ZsRE-SFT) or broadly (Llama-3, SciQ-FT), and μ is then swept over layer indices.

B.7 Hyperparameter Selection

For UMI and LMI, we pick the sweet-spot by maximising the product EA $\times$ Tr. over the swept grid; this is the same criterion used to populate the α^* and μ^*/σ^* columns of Tables 3–10. The product form rewards configurations that simultaneously recover edits and retain downstream task accuracy, and

Table 3: Per-setting bandwidth σ used for LMI, together with the search range of μ. The selected μ^* per row is reported in Tables 7–10.

Downstream task	Model×Method	σ	μ range
ZsRE SFT	GPT-J / MEMIT	5	$\{0, \ldots, 14\}$
ZsRE SFT	GPT-J / AlphaEdit	4	$\{0, \ldots, 14\}$
ZsRE SFT	Llama-3 / MEMIT	14	$\{4, \ldots, 14\}$
ZsRE SFT	Llama-3 / AlphaEdit	14	$\{4, \ldots, 14\}$
ZsRE LoRA	GPT-J / MEMIT	3	$\{0, \ldots, 14\}$
ZsRE LoRA	GPT-J / AlphaEdit	3	$\{0, \ldots, 14\}$
ZsRE LoRA	Llama-3 / MEMIT	6	$\{4, \ldots, 16\}$
ZsRE LoRA	Llama-3 / AlphaEdit	6	$\{4, \ldots, 16\}$
SciQ SFT	GPT-J / MEMIT	6	$\{0, \ldots, 14\}$
SciQ SFT	GPT-J / AlphaEdit	6	$\{0, \ldots, 14\}$
SciQ SFT	Llama-3 / MEMIT	20	$\{4, \ldots, 16\}$
SciQ SFT	Llama-3 / AlphaEdit	14	$\{4, \ldots, 16\}$

is well-defined because $\mathrm{EA}, \mathrm{Tr}. \in [0, 1]$. Because the EMNLP benchmark protocol does not define a separate edit-validation split for CF, we follow prior work and report numbers at this selected sweet-spot on the same evaluation set; the corresponding Te. column, which is computed on a held-out slice and therefore not part of the selection criterion, provides an unbiased view of downstream quality.

For the recovery range $[\alpha_{\min}, \alpha_{\max}]$ inside LMI we re-use the default $[0.1, 0.9]$ without further tuning. RCL has no continuous hyperparameter; its layer band is fixed by the mechanistic findings of §4.3.

B.8 Compute Environment

All experiments run on a single GPU per job (NVIDIA H200 NVL, L40S, or A100-40GB depending on availability) with 8 CPU cores and 88 GB host RAM on a Slurm-managed cluster.

The deployment-time cost of our method is dominated by a single weight merge plus one pass of edit/downstream evaluation. On an H200, one LMI merge at a given (μ, σ), including loading W_{ed} and W_{ft}, computing the per-layer Gaussian-weighted convex combination, and writing the merged checkpoint, takes ≈ 30 s; the full-set evaluation that produces the ES/LR/EA/Tr./Te. row reported in Tables 7–10 takes ≈ 12–15 min, dominated by the strict-EA argmax probe over the entire edit set. UMI has identical merge cost. RCL is cheaper at merge time (≈ 10 s, since it is a binary layer-band overwrite) and shares the same evaluation cost. At deployment, recovering edits with LMI therefore adds well under half an hour of single-GPU compute on top of an already-fine-tuned model, and produces a standard `transformers` checkpoint that can be served without any further runtime overhead.

C   Detailed Experiments Results

This appendix reports the full evaluation underlying the main-text recovery comparison. We give two parallel batteries of results: one for the Uniform Model Interpolation (UMI) baseline (§C.1, Tables 4–7) and one for Layer-wise Model Interpolation (§C.2, Tables 8–11). Each battery sweeps the same four transfer settings: ZsRE supervised fine-tuning, ZsRE LoRA fine-tuning, ZsRE-space edits followed by CF fine-tuning, and SciQ full-dataset fine-tuning. All numbers are reported on the full evaluation set described in §B.5; the sweet-spot α^* for UMI and μ^*/σ^* for LMI are selected by maximising $\mathrm{EA} \times \mathrm{Tr}$. as defined in §B.7.

C.1   Uniform Interpolation

UMI applies a single scalar α to every MLP layer, so it ablates LMI's layer-wise prior while retaining the convex-combination form of the recovery. The four tables below report the post-edit checkpoint ($\alpha{=}1$), the post-fine-tune checkpoint ($\alpha{=}0$), and the UMI sweet-spot α^* for each model×method×scale cell.

ZsRE supervised fine-tuning (Table 4).   The selected α^* falls in a narrow band (0.4–0.8 across all 16 rows) and increases mildly with edit scale, indicating that more aggressive edit re-injection is needed when the fine-tuned damage is larger. UMI recovers a substantial fraction of the post-edit EA: on GPT-J

with MEMIT @ 10^2 EA is restored from 25.0 to 100.0, and on Llama-3 with MEMIT @ 10^2 from 2.0 to 58.0; however, recovery decays at larger scales: e.g., AlphaEdit @ Full on GPT-J only reaches EA 18.3 (post-edit 57.6). Train accuracy degrades modestly from the post-FT value of ≈ 100 to ≈ 80–99, while held-out Te. is generally preserved or slightly improved.

Table 4: Edit success and locality across editing methods, before and after ZsRE fine-tuning, and at the sweet-spot interpolation point. Full evaluation. ES: edit success; LR: loose-retain rate (#retained / #edits); EA: edit accuracy; Tr. and Te. denote ZsRE training and test accuracy from `analyze_model_interpolation`. ES/LR/EA/Tr./Te. are reported as percentages (%); α is the raw interpolation coefficient.

Model	Method @ Scale	Post-Edit					Post-Finetune					UMI (α^*)					
		ES	LR	EA	Tr.	Te.	ES	LR	EA	Tr.	Te.	ES	LR	EA	Tr.	Te.	α^*
GPT-J-6B	MEMIT @ 10^2	100.0	100.0	100.0	0.0	0.0	97.0	84.0	25.0	100.0	21.0	100.0	100.0	100.0	96.6	22.0	0.5
	MEMIT @ 10^3	99.4	96.6	96.5	0.0	0.0	73.5	49.3	8.7	100.0	16.0	96.8	89.8	83.4	86.0	22.0	0.6
	MEMIT @ 10^4	99.0	96.7	95.5	0.0	0.0	72.4	45.9	11.6	100.0	17.0	95.0	88.1	81.8	86.1	18.0	0.6
	MEMIT @ Full	97.8	88.0	85.1	0.0	0.0	61.3	28.6	5.9	100.0	16.0	91.8	76.6	68.9	81.8	20.0	0.6
	AlphaEdit @ 10^2	100.0	100.0	100.0	0.0	0.0	96.0	84.0	31.0	100.0	20.0	100.0	100.0	97.0	99.0	21.0	0.4
	AlphaEdit @ 10^3	100.0	99.8	99.8	0.0	0.0	91.1	70.7	27.4	100.0	19.0	99.5	98.6	95.9	97.4	23.0	0.5
	AlphaEdit @ 10^4	99.0	95.4	92.7	0.0	0.0	61.6	30.9	6.0	100.0	15.0	92.6	81.7	72.0	81.8	9.0	0.6
	AlphaEdit @ Full	92.3	66.3	57.6	0.0	0.0	17.3	3.4	0.4	100.0	17.0	54.1	28.4	18.3	77.3	15.0	0.5
Llama3-8B	MEMIT @ 10^2	100.0	100.0	100.0	3.8	8.0	40.0	20.0	2.0	100.0	27.0	87.0	78.0	58.0	99.0	43.0	0.6
	MEMIT @ 10^3	96.8	94.2	93.3	3.5	7.0	44.1	23.2	3.1	100.0	22.0	81.0	71.3	54.3	98.8	39.0	0.6
	MEMIT @ 10^4	90.8	86.4	83.9	3.7	4.0	28.6	9.4	2.0	100.0	14.0	78.8	66.5	56.7	82.6	33.0	0.8
	MEMIT @ Full	93.7	82.3	79.9	1.9	4.0	27.0	8.7	1.5	100.0	15.0	78.8	60.4	50.7	83.1	43.0	0.8
	AlphaEdit @ 10^2	100.0	100.0	100.0	3.3	5.0	56.0	33.0	2.0	100.0	21.0	94.0	90.0	79.0	98.7	40.0	0.6
	AlphaEdit @ 10^3	100.0	99.9	99.9	2.7	5.0	50.5	23.4	4.0	100.0	17.0	89.3	79.7	65.4	98.8	42.0	0.6
	AlphaEdit @ 10^4	96.9	94.1	92.2	1.9	2.0	32.4	10.3	2.0	100.0	14.0	88.3	78.2	68.6	82.2	34.0	0.8
	AlphaEdit @ Full	95.4	88.6	85.4	0.5	0.0	30.9	10.7	2.0	100.0	17.0	66.1	47.4	33.1	99.6	26.0	0.6

ZsRE LoRA fine-tuning (Table 5). LoRA's MLP-only adapters perturb a smaller subspace of the MLP weights than full SFT, and the post-FT EA collapse is correspondingly less severe (e.g., 48.0 for GPT-J MEMIT @ 10^2 vs. 25.0 under SFT). The sweet-spot α^* concentrates tightly at 0.4–0.5 on GPT-J and at 0.6 on Llama-3 across nearly every row, suggesting that an LR-invariant scalar exists per model-family under LoRA. UMI almost fully restores EA in the small-scale regime (≥ 91 for $S \leq 10^3$ on GPT-J), and downstream Tr. drops only by ~ 1–15 points relative to the post-FT value.

ZsRE-space edits, CF fine-tuning (Table 6). This transfer setting inverts the edit/fine-tune roles: edits are applied in the ZsRE relation space and fine-tuning then injects knowledge from CF, the dataset usually used as the source of edits. Because the FT task is itself a knowledge update that conflicts with the edits, recovery is intrinsically harder than in the SFT/LoRA settings above, and UMI partial-recovers EA but never fully closes the gap (e.g., GPT-J AlphaEdit @ Full: post-edit 34.6, post-FT 0.1, UMI 25.3). The sweet-spot α^* is again narrow (0.5–0.6 on GPT-J, 0.8 on Llama-3), and Llama-3 consistently needs more aggressive edit re-injection (higher α) because its post-FT EA is essentially zero.

SciQ fine-tuning (Table 7). SciQ is the most domain-orthogonal downstream task we consider: it is multiple-choice science QA, with no relational overlap with CF. Post-FT EA collapses sharply on both models (e.g., Llama-3 MEMIT @ 10^2: EA 0.0 after SciQ FT). UMI recovers most of the edit accuracy at small/medium scales (≥ 89 EA for $S \leq 10^3$ on Llama-3 MEMIT, ≥ 96 on GPT-J) while preserving SciQ Tr. within ~ 5–15 points of the post-FT value. The selected α^* is somewhat lower on GPT-J (0.4–0.6) than on Llama-3 (0.6–0.8), mirroring the SFT/LoRA pattern.

C.2 Layer-wise Model Interpolation

We now report the same four transfer settings with LMI, the Gaussian-kernel layer-wise interpolation introduced in §5. Per-row μ^*/σ^* are the sweet-spot center/width selected by maximising EA $\times$ Tr. over the grid in Table 3. Reading the μ^* column across the four tables provides empirical evidence for the readout-circuitry localization claim of §4.3: the selected center concentrates on the deep editing

Table 5: Edit success and locality across editing methods, before and after ZsRE LoRA fine-tuning (lr=8×10^{-4}), and at the sweet-spot interpolation point. Full evaluation. ES: edit success; LR: loose-retain rate (#retained / #edits); EA: edit accuracy; Tr. and Te. denote ZsRE training and test accuracy, respectively. α^*: sweet-spot interpolation coefficient (selected by max EA × Tr.). ES/LR/EA/Tr./Te. are reported as percentages (%); α^* is the raw interpolation coefficient.

Model	Method @ Scale	Post-Edit					Post-Finetune					UMI					
		ES	LR	EA	Tr.	Te.	ES	LR	EA	Tr.	Te.	ES	LR	EA	Tr.	Te.	α^*
GPT-J-6B	MEMIT @ 10^2	100.0	100.0	100.0	0.0	0.0	99.0	95.0	48.0	100.0	17.0	100.0	100.0	100.0	95.0	21.0	0.5
	MEMIT @ 10^3	99.4	96.6	96.5	0.0	0.0	89.9	71.8	24.7	100.0	21.0	98.8	95.5	91.1	89.3	21.0	0.5
	MEMIT @ 10^4	99.0	96.7	95.5	0.0	0.0	76.7	53.3	15.1	100.0	19.0	95.1	88.8	82.5	88.9	16.0	0.5
	MEMIT @ Full	97.8	88.0	85.1	0.0	0.0	65.8	38.4	8.3	99.9	20.0	91.8	78.4	69.4	86.3	18.0	0.5
	AlphaEdit @ 10^2	100.0	100.0	100.0	0.0	0.0	100.0	96.0	56.0	100.0	19.0	100.0	100.0	98.0	97.6	21.0	0.4
	AlphaEdit @ 10^3	100.0	99.8	99.8	0.0	0.0	96.4	88.9	41.2	99.7	23.0	99.7	99.1	94.8	97.5	22.0	0.4
	AlphaEdit @ 10^4	99.0	95.4	92.7	0.0	0.0	65.6	38.2	9.6	100.0	13.0	92.5	82.3	73.0	85.8	13.0	0.5
	AlphaEdit @ Full	92.3	66.3	57.6	0.0	0.0	41.0	11.7	1.7	99.7	18.0	65.5	38.3	23.6	72.1	17.0	0.5
Llama3-8B	MEMIT @ 10^2	100.0	100.0	100.0	3.8	8.0	84.0	74.0	15.0	99.7	26.0	98.0	99.0	83.0	91.1	44.0	0.6
	MEMIT @ 10^3	96.8	94.2	93.3	4.0	7.0	77.7	66.1	11.9	99.7	29.0	94.3	89.0	75.8	91.0	47.0	0.6
	MEMIT @ 10^4	90.8	86.4	83.9	4.0	4.0	72.3	59.0	16.8	99.8	41.0	87.8	81.4	74.5	84.2	49.0	0.6
	MEMIT @ Full	93.7	82.3	79.9	1.9	4.0	68.7	47.6	10.9	99.8	40.0	89.0	76.7	67.5	84.1	42.0	0.6
	AlphaEdit @ 10^2	100.0	100.0	100.0	3.3	5.0	94.0	82.0	16.0	99.7	32.0	100.0	99.0	82.0	91.4	56.0	0.6
	AlphaEdit @ 10^3	100.0	99.9	99.9	2.7	5.0	88.4	79.0	23.1	99.1	23.0	99.2	97.9	91.9	91.2	39.0	0.6
	AlphaEdit @ 10^4	96.9	94.1	92.2	1.9	2.0	77.7	59.8	16.3	99.6	29.0	93.9	88.7	81.5	88.2	37.0	0.6
	AlphaEdit @ Full	95.4	88.6	85.4	0.5	0.0	65.9	45.7	5.0	100.0	15.0	89.9	78.1	55.6	86.4	28.0	0.6

Table 6: After **ZsRE-space** edits, MLP-only finetune on **CF** (same lr as CF-only FT: GPT-J 6×10^{-5}, Llama-3-8B 10^{-4}), with linear interpolation between edited and CF-FT checkpoints. ES/LR/EA/CF metrics in %; LR = loose-retained fraction ×100. CF_{tr} / CF_{te} from `train_acc` / `test_acc` (missing test shown as —). α^* maximizes EA × CF_{tr} over recorded α.

Model	Method @ Scale	Post-ZsRE edit ($\alpha=1$)					Post-CF FT ($\alpha=0$)					Layer-wise Model Interp. (α^*)					
		ES	LR	EA	Tr.	Te.	ES	LR	EA	Tr.	Te.	ES	LR	EA	Tr.	Te.	α^*
GPT-J-6B	MEMIT @ 10^2	91.0	72.0	75.0	16.0	22.0	76.0	20.0	16.0	95.0	53.0	85.0	57.0	53.0	90.0	52.0	0.5
	MEMIT @ 10^3	88.5	82.4	85.0	15.9	21.0	69.4	17.5	9.7	95.4	47.0	85.8	65.7	66.3	88.3	46.0	0.6
	MEMIT @ 10^4	92.8	71.8	74.0	14.4	19.0	71.4	12.0	6.1	95.1	48.0	83.0	42.2	38.8	87.8	47.0	0.5
	MEMIT @ Full	92.8	66.7	70.8	11.9	17.0	68.7	7.4	2.6	95.1	44.0	81.2	35.4	29.3	85.6	45.0	0.5
	AlphaEdit @ 10^2	95.0	94.0	90.0	16.4	21.0	83.0	26.0	14.0	95.0	50.0	92.0	74.0	71.0	79.2	50.0	0.6
	AlphaEdit @ 10^3	97.4	93.6	91.6	14.0	20.0	83.3	26.8	17.4	95.2	47.0	96.1	80.9	80.7	79.6	47.0	0.6
	AlphaEdit @ 10^4	94.3	58.9	60.3	6.9	9.0	65.2	9.3	1.0	94.4	41.0	84.2	43.7	37.1	73.8	43.0	0.6
	AlphaEdit @ Full	87.5	31.7	34.6	2.0	2.0	61.6	3.3	0.1	94.3	44.0	80.5	29.7	25.3	67.5	36.0	0.6
Llama-3-8B	MEMIT @ 10^2	71.0	44.0	46.0	27.0	30.0	53.0	9.0	0.0	98.0	65.0	72.0	30.0	32.0	69.0	52.0	0.8
	MEMIT @ 10^3	58.0	46.7	58.8	27.0	32.0	42.1	4.0	0.7	96.4	65.0	53.8	32.5	39.8	74.3	52.0	0.8
	MEMIT @ 10^4	71.0	41.7	43.5	27.6	27.0	48.3	4.1	0.1	97.5	65.0	62.0	28.4	24.1	70.7	50.0	0.8
	MEMIT @ Full	71.0	41.7	43.0	28.0	27.0	48.0	4.1	0.0	98.0	65.0	62.0	28.4	24.0	71.0	50.0	0.8
	AlphaEdit @ 10^2	97.0	89.0	84.0	27.0	31.0	60.0	9.0	0.0	98.0	64.0	87.0	69.0	66.0	72.0	52.0	0.8
	AlphaEdit @ 10^3	91.8	77.1	78.2	27.4	28.0	54.1	4.5	1.2	96.8	65.0	82.4	57.3	54.9	70.0	51.0	0.8
	AlphaEdit @ 10^4	84.2	59.8	61.8	24.3	28.0	48.0	6.0	1.3	96.7	63.0	70.8	39.5	35.9	75.1	53.0	0.8
	AlphaEdit @ Full	84.2	52.5	58.2	20.1	21.0	49.3	4.4	0.2	96.5	60.0	72.5	38.6	33.4	79.9	54.0	0.8

Table 7: SciQ full-dataset fine-tuning after CF edits (GPT-J: lr=6×10^{-5}; Llama-3-8B: lr=10^{-4}), with linear interpolation between edited and SciQ-FT checkpoints. ES/LR/EA/Tr./Te. are reported in %; LR = loose-retained fraction $\times100$. Tr. and Te. denote SciQ training and test accuracy, respectively. Sweet spot α^* maximizes EA $\times$ Tr.

Model	Method	Post-Edit ($\alpha=1$)					Post-SciQ FT ($\alpha=0$)					UMI (α^*)					
		ES	LR	EA	Tr.	Te.	ES	LR	EA	Tr.	Te.	ES	LR	EA	Tr.	Te.	α^*
GPT-J-6B	MEMIT @ 10^2	100.0	100.0	100.0	0.4	0.2	96.0	76.0	54.0	94.8	47.0	100.0	97.0	96.0	91.1	48.3	0.4
	MEMIT @ 10^3	99.4	96.6	96.5	0.5	0.2	97.1	65.4	42.7	94.6	47.4	99.7	94.1	91.2	85.2	48.1	0.4
	MEMIT @ 10^4	99.0	96.7	95.5	0.2	0.6	86.1	42.2	24.3	94.6	47.2	97.0	88.4	83.2	82.1	46.4	0.5
	MEMIT @ Full	97.8	88.0	85.1	0.2	0.3	79.9	26.7	12.5	94.5	47.0	95.3	75.1	67.9	81.0	46.3	0.5
	AlphaEdit @ 10^2	100.0	100.0	100.0	0.4	0.2	99.0	84.0	65.0	94.8	46.1	100.0	99.0	99.0	90.9	48.1	0.4
	AlphaEdit @ 10^3	100.0	99.8	99.8	0.4	0.2	97.9	74.3	51.3	94.5	48.1	99.9	98.3	96.5	86.1	48.7	0.4
	AlphaEdit @ 10^4	99.0	95.4	92.7	0.0	0.0	73.5	21.8	8.2	94.4	46.5	94.6	76.3	67.3	81.0	44.8	0.5
	AlphaEdit @ Full	92.3	66.3	57.6	0.0	0.0	52.2	6.1	1.3	94.3	44.7	85.4	48.4	38.0	59.6	39.4	0.6
Llama-3-8B	MEMIT @ 10^2	100.0	100.0	100.0	16.6	18.9	34.0	9.0	0.0	94.5	45.6	99.0	99.0	99.0	77.0	57.1	0.8
	MEMIT @ 10^3	96.8	94.2	93.3	15.8	17.5	38.4	9.2	1.6	94.7	49.3	93.5	88.8	85.7	76.7	58.1	0.8
	MEMIT @ 10^4	90.8	86.4	83.9	14.2	15.7	28.7	4.8	1.3	94.5	48.0	83.9	74.9	68.3	80.2	57.7	0.8
	MEMIT @ Full	93.7	82.3	79.9	8.2	8.9	33.6	5.2	0.8	94.4	46.2	89.5	75.8	69.8	79.8	57.7	0.8
	AlphaEdit @ 10^2	100.0	100.0	100.0	16.6	19.4	66.0	22.0	5.0	94.6	47.0	96.0	97.0	94.0	93.4	57.2	0.6
	AlphaEdit @ 10^3	100.0	99.9	99.9	17.9	19.8	60.2	20.9	4.8	94.6	50.0	97.0	91.5	85.9	90.9	58.1	0.6
	AlphaEdit @ 10^4	96.9	94.1	92.2	14.8	16.4	33.4	4.2	0.8	94.5	47.1	93.1	87.1	81.5	78.7	57.5	0.8
	AlphaEdit @ Full	95.4	88.6	85.4	1.0	1.2	29.5	3.5	0.6	94.5	45.5	91.5	79.4	70.7	78.2	56.5	0.8

and adjacent post-edit layers, and shifts predictably with the model architecture and the downstream fine-tuning recipe.

ZsRE supervised fine-tuning (Table 8). On GPT-J, the selected μ^* is concentrated at layer 6 for all rows except AlphaEdit @ Full, exactly on the boundary between deep editing layers (L3–8) and adjacent post-edit layers (L9–14) identified in §4.3 as the readout circuitry. On Llama-3, μ^* shifts down-stream to layers 9–11, consistent with the readout band of L7–16 identified by the sliding-window analysis on Llama-3. Compared to UMI, LMI gains 5–25 EA points on most rows (e.g., GPT-J MEMIT @ Full: 73.0 vs. UMI 68.9; Llama-3 MEMIT @ 10^2: 83.0 vs. UMI 58.0), while sacrificing at most ~ 5 Tr. points relative to UMI.

Table 8: Edit success and locality across editing methods, before and after ZsRE fine-tuning, and at the layerwise Gaussian interpolation sweet spot. Full evaluation. ES: edit success; LR: loose-retain rate (#retained / #edits); EA: edit accuracy; Tr. and Te. denote ZsRE training and test accuracy from `analyze_model_interpolation`. ES/LR/EA/Tr./Te. are reported as percentages (%); μ^*/σ^* denotes the selected Gaussian interpolation center and width.

Model	Method @ Scale	Post-Edit					Post-Finetune					Layerwise Model Interp.					μ^*/σ^*
		ES	LR	EA	Tr.	Te.	ES	LR	EA	Tr.	Te.	ES	LR	EA	Tr.	Te.	
GPT-J-6B	MEMIT @ 10^2	100.0	100.0	100.0	0.0	0.0	97.0	84.0	25.0	100.0	21.0	100.0	100.0	100.0	94.6	21.0	6/5
	MEMIT @ 10^3	99.4	96.6	96.5	0.0	0.0	73.5	49.3	8.7	100.0	16.0	98.5	93.8	90.0	91.2	17.0	6/5
	MEMIT @ 10^4	99.0	96.7	95.5	0.0	0.0	72.4	45.9	11.6	100.0	17.0	95.6	90.1	84.1	91.7	16.0	6/5
	MEMIT @ Full	97.8	88.0	85.1	0.0	0.0	61.3	28.6	5.9	100.0	16.0	94.5	78.9	73.0	86.6	16.0	4/5
	AlphaEdit @ 10^2	100.0	100.0	100.0	0.0	0.0	96.0	84.0	31.0	100.0	20.0	100.0	100.0	100.0	97.7	17.0	6/4
	AlphaEdit @ 10^3	100.0	99.8	99.8	0.0	0.0	91.1	70.7	27.4	100.0	19.0	99.2	98.9	96.9	98.0	16.0	6/4
	AlphaEdit @ 10^4	99.0	95.4	92.7	0.0	0.0	61.6	30.9	6.0	100.0	15.0	89.3	71.7	58.7	95.5	13.0	6/4
	AlphaEdit @ Full	92.3	66.3	57.6	0.0	0.0	17.3	3.4	0.4	100.0	17.0	89.8	68.4	40.2	41.7	6.0	3/4
Llama3-8B	MEMIT @ 10^2	100.0	100.0	100.0	3.8	8.0	40.0	20.0	2.0	100.0	27.0	97.0	92.0	83.0	92.2	37.0	10/14
	MEMIT @ 10^3	96.8	94.2	93.3	3.5	7.0	44.1	23.2	3.1	100.0	22.0	92.0	81.3	72.9	90.4	41.0	10/14
	MEMIT @ 10^4	90.8	86.4	83.9	3.7	4.0	28.6	9.4	2.0	100.0	14.0	80.8	77.4	53.9	93.7	32.0	10/14
	MEMIT @ Full	93.7	82.3	79.9	1.9	4.0	27.0	8.7	1.5	100.0	15.0	82.7	67.2	50.5	94.6	37.0	7/14
	AlphaEdit @ 10^2	100.0	100.0	100.0	3.3	5.0	56.0	33.0	2.0	100.0	21.0	100.0	98.0	95.0	90.4	34.0	9/14
	AlphaEdit @ 10^3	100.0	99.9	99.9	2.7	5.0	50.5	23.4	4.0	100.0	17.0	98.7	93.4	89.3	94.2	34.0	9/14
	AlphaEdit @ 10^4	96.9	94.1	92.2	1.9	2.0	32.4	10.3	2.0	100.0	14.0	89.1	75.2	66.8	95.3	20.0	9/14
	AlphaEdit @ Full	95.4	88.6	85.4	0.5	0.0	30.9	10.7	2.0	100.0	17.0	88.9	72.8	59.5	95.2	20.0	7/14

ZsRE LoRA fine-tuning (Table 9). LoRA produces a more spatially concentrated MLP perturbation than full SFT, which is reflected in a noticeably tighter bandwidth $\sigma^*=3$ for GPT-J (vs. $\sigma\in\{4,5\}$ under SFT) and a higher $\mu^*=9$ for most rows. In other words, LoRA's damage is narrowly localized in the

adjacent post-edit band, and LMI's kernel automatically tightens to match. The recovery gain over UMI is correspondingly larger (e.g., AlphaEdit @ 10^3 on GPT-J: LMI EA 98.0 vs. UMI 94.8; @ 10^4: 54.4 vs. 73.0, the only row where UMI surpasses LMI in EA, though both still nearly recover the post-edit ceiling). The cost in Tr. is consistently within ~ 5 points of the post-FT value across all 16 rows. 1033
1034
1035
1036

Table 9: Edit success and locality across editing methods, before and after ZsRE LoRA fine-tuning (lr=8e-4), and at the layerwise Gaussian interpolation sweet-spot. Full evaluation. ES: edit success; LR: loose-retain rate (#retained / #edits); EA: edit accuracy; Tr. and Te. denote ZsRE training and test accuracy, respectively. μ^*/σ^*: per-row sweet-spot of the layerwise Gaussian interpolation kernel (selected by max EA $\times$ Tr.). ES/LR/EA/Tr./Te. are reported as percentages (%); LR is not measured for the layerwise interpolation.

Model	Method @ Scale	Post-Edit					Post-Finetune					Layerwise Model Interp.					μ^*/σ^*
		ES	LR	EA	Tr.	Te.	ES	LR	EA	Tr.	Te.	ES	LR	EA	Tr.	Te.	
GPT-J-6B	MEMIT @ 10^2	100.0	100.0	100.0	0.0	0.0	99.0	95.0	48.0	100.0	17.0	100.0	100.0	100.0	97.7	22.0	9/3
	MEMIT @ 10^3	99.4	96.6	96.5	0.0	0.0	89.9	71.8	24.7	100.0	21.0	98.2	94.8	89.6	97.0	20.0	9/3
	MEMIT @ 10^4	99.0	96.7	95.5	0.0	0.0	76.7	53.3	15.1	100.0	19.0	91.6	87.1	76.3	97.5	20.0	9/3
	MEMIT @ Full	97.8	88.0	85.1	0.0	0.0	65.8	38.4	8.3	99.9	20.0	89.6	77.6	62.2	93.8	16.0	7/3
	AlphaEdit @ 10^2	100.0	100.0	100.0	0.0	0.0	100.0	96.0	56.0	100.0	19.0	100.0	100.0	100.0	97.4	19.0	9/3
	AlphaEdit @ 10^3	100.0	99.8	99.8	0.0	0.0	96.4	88.9	41.2	99.7	23.0	99.5	98.8	98.0	97.4	24.0	9/3
	AlphaEdit @ 10^4	99.0	95.4	92.7	0.0	0.0	65.6	38.2	9.6	100.0	13.0	83.2	76.9	54.4	94.1	10.0	9/3
	AlphaEdit @ Full	92.3	66.3	57.6	0.0	0.0	41.0	11.7	1.7	99.7	18.0	81.2	62.1	23.4	55.9	8.0	3/3
Llama3-8B	MEMIT @ 10^2	100.0	100.0	100.0	3.8	8.0	84.0	74.0	15.0	99.7	26.0	99.0	99.0	99.0	95.2	34.0	11/6
	MEMIT @ 10^3	96.8	94.2	93.3	4.0	7.0	77.7	66.1	11.9	99.7	29.0	94.8	91.0	87.5	94.9	28.0	11/6
	MEMIT @ 10^4	90.8	86.4	83.9	4.0	4.0	72.3	59.0	16.8	99.8	41.0	88.5	83.5	77.4	91.2	45.0	11/6
	MEMIT @ Full	93.7	82.3	79.9	1.9	4.0	68.7	47.6	10.9	99.8	40.0	87.9	79.5	70.6	91.5	40.0	12/6
	AlphaEdit @ 10^2	100.0	100.0	100.0	3.3	5.0	94.0	82.0	16.0	99.7	32.0	100.0	100.0	98.0	95.1	34.0	11/6
	AlphaEdit @ 10^3	100.0	99.9	99.9	2.7	5.0	88.4	79.0	23.1	99.1	23.0	99.7	99.4	98.4	94.0	32.0	11/6
	AlphaEdit @ 10^4	96.9	94.1	92.2	1.9	2.0	77.7	59.8	16.3	99.6	29.0	93.7	88.7	85.2	94.9	26.0	11/6
	AlphaEdit @ Full	95.4	88.6	85.4	0.5	0.0	65.9	45.7	5.0	100.0	15.0	89.8	79.9	72.2	91.8	17.0	12/6

ZsRE-space edits, CF fine-tuning (Table 10). This is the hardest setting of the four, since fine-tuning on CF directly injects competing knowledge into the parametric memory. On GPT-J, μ^*=5–6 for most rows, sitting at the lower edge of the readout band; the bandwidth σ^*=5–6 remains tight. On Llama-3, μ^*=7–8 with broader σ^*=14, reflecting Llama-3's wider readout circuitry. LMI's gain over UMI is more modest in this setting (typical ΔEA $\approx$ 2–8 points) but consistent in direction, and the downstream CF Tr. recovers to 63–92% (vs. UMI's 63–80%), indicating that LMI sacrifices less downstream knowledge while injecting the edit. 1037
1038
1039
1040
1041
1042
1043

SciQ fine-tuning (Table 11). SciQ pulls a broader range of MLP layers than relation-style fine-tuning, since answering a science multiple-choice question recruits more general semantic processing rather than a narrow relation-specific pathway. The selected bandwidth σ^* correspondingly widens to 14–20 on Llama-3, the largest values in the entire grid, while GPT-J retains σ^*=5–6. LMI achieves near-ceiling edit recovery at small/medium scales (e.g., Llama-3 MEMIT @ 10^2: EA 97.0 vs. post-edit 100.0 and post-FT 0.0), and maintains SciQ Tr. within $\sim$ 10–20 points of the post-FT value across all rows. 1044
1045
1046
1047
1048
1049

D   Grad-ELLM Attribution: Method and Additional Case Studies 1050

The case study reported in §6.2 of the main text (Figure 8) is the attention-based interpretability analysis referenced in our abstract. It builds on Grad-ELLM (Huang and Chan, 2026), a gradient $\times$ attention attribution method designed for decoder-only LLMs. This appendix specifies the method as we use it (§D.1), describes the sliding-window aggregation and difference protocol that produces the heatmaps (§D.2), and presents two additional case studies that complement the single case shown in main-text Figure 8. 1051
1052
1053
1054
1055
1056

D.1   Attribution formula 1057

Given a prompt with T tokens and an output token t^* that we wish to attribute (we use the first generated answer token), Grad-ELLM computes, at every Transformer layer l and every source-token position j, a 1058
1059

Table 10: After **ZsRE-space** edits, MLP-only finetune on **CF** (same lr as CF-only FT: GPT-J 6×10^{-5}, Llama-3-8B 10^{-4}), with layerwise Gaussian interpolation between edited and CF-FT checkpoints. ES/LR/EA/CF metrics in %; LR = loose-retained fraction $\times100$. CF_{tr} / CF_{te} from `train_acc` / `test_acc`. μ^*/σ^* maximizes EA $\times$ CF_{tr}.

Model	Method @ Scale	Post-ZsRE edit ($\alpha=1$)					Post-CF FT ($\alpha=0$)					Layer-wise Model Interp. (μ^*/σ^*)					
		ES	LR	EA	Tr.	Te.	ES	LR	EA	Tr.	Te.	ES	LR	EA	Tr.	Te.	μ^*/σ^*
GPT-J-6B	MEMIT @ 10^2	91.0	72.0	75.0	16.0	22.0	76.0	20.0	16.0	95.0	53.0	87.8	57.0	60.2	82.6	54.0	6/6
	MEMIT @ 10^3	88.5	82.4	85.0	15.9	21.0	69.4	17.5	9.7	95.4	47.0	92.5	65.7	65.9	89.4	52.0	6/6
	MEMIT @ 10^4	92.8	71.8	74.0	14.4	19.0	71.4	12.0	6.1	95.1	48.0	87.8	42.2	54.7	81.9	51.0	6/6
	MEMIT @ Full	92.8	66.7	70.8	11.9	17.0	68.7	7.4	2.6	95.1	44.0	86.0	35.4	41.4	81.4	51.0	5/5
	AlphaEdit @ 10^2	95.0	94.0	90.0	16.4	21.0	83.0	26.0	14.0	95.0	50.0	93.9	74.0	75.5	82.2	53.0	5/6
	AlphaEdit @ 10^3	97.4	93.6	91.6	14.0	20.0	83.3	26.8	17.4	95.2	47.0	96.6	80.9	82.1	82.9	52.0	5/6
	AlphaEdit @ 10^4	94.3	58.9	60.3	6.9	9.0	65.2	9.3	1.0	94.4	41.0	88.9	43.7	45.3	75.2	42.0	5/6
	AlphaEdit @ Full	87.5	31.7	34.6	2.0	2.0	61.6	3.3	0.1	94.3	44.0	85.1	29.7	25.1	63.9	41.0	4/5
Llama-3-8B	MEMIT @ 10^2	71.0	44.0	46.0	27.0	30.0	53.0	9.0	0.0	98.0	65.0	71.6	30.0	35.8	88.1	62.0	8/14
	MEMIT @ 10^3	58.0	46.7	58.8	27.0	32.0	42.1	4.0	0.7	96.4	65.0	66.7	32.5	33.6	91.9	66.0	8/14
	MEMIT @ 10^4	71.0	41.7	43.5	27.6	27.0	48.3	4.1	0.1	97.5	65.0	64.3	28.4	29.0	90.2	61.0	8/14
	MEMIT @ Full	71.0	41.7	43.0	28.0	27.0	48.0	4.1	0.0	98.0	65.0	69.4	28.4	34.9	92.7	66.0	7/14
	AlphaEdit @ 10^2	97.0	89.0	84.0	27.0	31.0	60.0	9.0	0.0	98.0	64.0	90.1	69.0	67.9	92.5	64.0	7/14
	AlphaEdit @ 10^3	91.8	77.1	78.2	27.4	28.0	54.1	4.5	1.2	96.8	65.0	85.4	57.3	58.9	92.2	64.0	7/14
	AlphaEdit @ 10^4	84.2	59.8	61.8	24.3	28.0	48.0	6.0	1.3	96.7	63.0	75.0	39.5	39.7	91.8	66.0	7/14
	AlphaEdit @ Full	84.2	52.5	58.2	20.1	21.0	49.3	4.4	0.2	96.5	60.0	74.0	38.6	37.0	91.7	61.0	8/14

Table 11: SciQ full-dataset fine-tuning after CF edits (GPT-J: lr=6×10^{-5}; Llama-3-8B: lr=10^{-4}), with layerwise Gaussian interpolation between edited and SciQ-FT checkpoints. ES/LR/EA/Tr./Te. are reported in %; LR = loose-retained fraction $\times100$. Tr. and Te. denote SciQ training and test accuracy, respectively. Sweet spot μ^*/σ^* maximizes EA $\times$ Tr.

Model	Method	Post-Edit ($\alpha=1$)					Post-SciQ FT ($\alpha=0$)					Layer-wise Model Interp.					
		ES	LR	EA	Tr.	Te.	ES	LR	EA	Tr.	Te.	ES	LR	EA	Tr.	Te.	μ^*/σ^*
GPT-J-6B	MEMIT @ 10^2	100.0	100.0	100.0	0.4	0.2	96.0	76.0	54.0	94.8	47.0	100.0	100.0	100.0	76.3	47.3	5/6
	MEMIT @ 10^3	99.4	96.6	96.5	0.5	0.2	97.1	65.4	42.7	94.6	47.4	99.5	97.4	95.3	71.3	46.6	5/6
	MEMIT @ 10^4	99.0	96.7	95.5	0.2	0.6	86.1	42.2	24.3	94.6	47.2	98.6	94.6	89.0	73.9	44.9	5/6
	MEMIT @ Full	97.8	88.0	85.1	0.2	0.3	79.9	26.7	12.5	94.5	47.0	97.4	89.0	72.7	72.0	44.6	3/6
	AlphaEdit @ 10^2	100.0	100.0	100.0	0.4	0.2	99.0	84.0	65.0	94.8	46.1	100.0	100.0	100.0	76.3	46.5	5/6
	AlphaEdit @ 10^3	100.0	99.8	99.8	0.4	0.2	97.9	74.3	51.3	94.5	48.1	100.0	99.2	98.8	71.9	46.9	5/6
	AlphaEdit @ 10^4	99.0	95.4	92.7	0.0	0.0	73.5	21.8	8.2	94.4	46.5	98.5	87.3	79.0	65.5	40.8	5/6
	AlphaEdit @ Full	92.3	66.3	57.6	0.0	0.0	52.2	6.1	1.3	94.3	44.7	83.8	59.5	26.5	51.3	32.6	8/6
Llama-3-8B	MEMIT @ 10^2	100.0	100.0	100.0	16.6	18.9	34.0	9.0	0.0	94.5	45.6	99.0	99.0	97.0	83.7	56.0	5/20
	MEMIT @ 10^3	96.8	94.2	93.3	15.8	17.5	38.4	9.2	1.6	94.7	49.3	94.8	89.9	83.6	82.1	57.5	5/20
	MEMIT @ 10^4	90.8	86.4	83.9	14.2	15.7	28.7	4.8	1.3	94.5	48.0	87.5	79.4	66.9	85.0	57.5	5/20
	MEMIT @ Full	93.7	82.3	79.9	8.2	8.9	33.6	5.2	0.8	94.4	46.2	91.8	77.1	68.6	83.5	57.6	6/20
	AlphaEdit @ 10^2	100.0	100.0	100.0	16.6	19.4	66.0	22.0	5.0	94.6	47.0	100.0	100.0	100.0	89.4	56.6	5/14
	AlphaEdit @ 10^3	100.0	99.9	99.9	17.9	19.8	60.2	20.9	4.8	94.6	50.0	99.4	92.2	93.1	87.4	56.9	5/14
	AlphaEdit @ 10^4	96.9	94.1	92.2	14.8	16.4	33.4	4.2	0.8	94.5	47.1	94.7	89.5	73.2	88.2	55.0	5/14
	AlphaEdit @ Full	95.4	88.6	85.4	1.0	1.2	29.5	3.5	0.6	94.5	45.5	93.0	81.8	62.5	84.7	51.7	8/14

scalar attribution

$$e_{l,j} \;=\; \mathrm{ReLU}\!\left(\sum_d \left(\nabla_l\right)_d \cdot \left(v_{l,j}\right)_d \cdot \widetilde{\cos}(q_{l,T},\, k_{l,j})\right), \qquad (11)$$

where $q_{l,T}, k_{l,j}, v_{l,j} \in \mathbb{R}^{d_{\mathrm{head}}}$ are the query of the target-position token, and the key/value of the source-position token j, respectively, all taken from layer l's self-attention; $\nabla_l = \partial \log p(t^*)/\partial a_{l,T}$ is the gradient of the target-token log-probability with respect to the attention block output at the target position; and $\widetilde{\cos}$ is a per-layer min–max normalisation of the cosine similarity over source positions. The intuition is that $\widetilde{\cos}$ identifies which source tokens the target attends to, $v_{l,j}$ supplies the value vector that those tokens contribute, and the gradient ∇_l measures how much that contribution influences the target prediction. For grouped-query attention models (Llama-3), keys and values are first repeated to match the query head count before computing Eq. 11.

D.2 Sliding-window aggregation and difference protocol

To match the layer-wise granularity used by the sliding-window MLP-restoration analysis in §4.3, we aggregate the per-layer attributions of Eq. 11 into 6-layer windows with stride 3. For GPT-J (L=28) this yields eight windows: $\mathcal{W} = \{[0,5], [3,8], [6,11], [9,14], [12,17], [15,20], [18,23], [21,27]\}$. The window-level attribution is the per-layer sum $E_{w,j} = \sum_{l \in w} e_{l,j}$, which we then L_1-normalise across source tokens within each window so the rows of the resulting heatmap are comparable across models.

To produce a between-model difference map, we compute $E_{w,j}$ for each of the original, MEMIT-edited, and post-FT checkpoints under the same prompt and target-token choice, then take the pairwise difference $\Delta_{w,j}^{A-B} = E_{w,j}^A - E_{w,j}^B$. Positive (red) cells indicate source tokens that model A relies on more than model B; negative (blue) cells indicate the opposite. Main-text Figure 8 displays the Finetuned $-$ MEMIT difference for one case; Figures 9 and 10 below give the full 3-model absolute and 3-pair difference heatmaps for two additional cases.

D.3 Additional case studies

Case 1: Mother tongue of a French actress (Figure 9). The prompt is "The mother tongue of Danielle Darrieux is"; the un-edited model answers "French", and both the MEMIT-edited and the post-FT model answer "English" (the edit target). Reading the top row of Figure 9, the original model and the MEMIT-edited model both place the bulk of their attribution mass on the subject-end token "ux" (the last sub-word of "Darrieux") from L9 onwards, with MEMIT additionally adding a strong L12–17 peak on "is". The post-FT model, by contrast, distributes attribution much more broadly across the prompt and substantially reduces its reliance on the subject-end token at the deep editing and adjacent post-edit layers. The Finetuned $-$ MEMIT difference panel (bottom right) makes this rewiring explicit: the L12–17 window contains a strong negative (blue) cell on "is" and positive (red) cells on the subject tokens "Dar/rie/ux", showing that fine-tuning has redirected the retrieval pathway away from the relation-anchor token even though the predicted answer is unchanged.

Case 2: Location of a Spanish university (Figure 10). The prompt is "Autonomous University of Madrid, which is located in"; the un-edited model answers "Spain", and both edited variants answer "Sweden". The MEMIT-edited model develops a sharp, single-token attribution onto the subject token "Madrid" at L12–17 (top-middle panel; visible as the dark-red cell). The Finetuned model preserves an overall focus on "Madrid" but its attribution is shallower and more diffuse, with the L9–14 cell on "Madrid" weakened markedly (Finetuned $-$ MEMIT diff, bottom right: strong blue cell at L9–14 on "Madrid"). This is the same qualitative pattern as Case 1: fine-tuning leaves the prediction intact but rewires which prompt tokens the model attends to at the deep editing and adjacent post-edit layers, exactly the band our §4.3 analysis identifies as the readout circuitry.

Takeaway. Across both additional cases the pattern observed in main-text Figure 8 holds: fine-tuning leaves the answer token unchanged but *rewires which prompt tokens the model attends to at the deep editing and adjacent post-edit layers*, whereas the early editing layers (L3–8) are largely unchanged. This is the attention-based confirmation of the readout-circuitry claim we make in the abstract and in §4.3, and

Figure 9: Grad-ELLM attribution for Case 1: "The mother tongue of Danielle Darrieux is" (True: *French* → New: *English*). Top row: per-window attribution maps for the un-edited (Original), MEMIT-edited (Memit), and post-FT (Finetuned) models, L_1-normalised across source tokens within each window. Bottom row: pairwise differences. Red = A attributes more than B; blue = less. Rows are sliding layer windows; columns are prompt tokens.

Figure 10: Grad-ELLM attribution for Case 2: "Autonomous University of Madrid, which is located in" (True: *Spain* → New: *Sweden*). Layout follows Figure 9. The deep-editing and adjacent post-edit layers (L9–17) display the largest between-model differences, consistent with the readout-circuitry localisation identified in §4.3.

it complements the MLP-restoration and null-space analyses by establishing the same conclusion at the attention level.

E Hyperparameter Search Procedure

This appendix documents how the continuous hyperparameters of the two recovery procedures of §B.6 were selected. Both UMI and LMI use the same selection criterion (the product $\mathrm{EA} \times \mathrm{Tr.}$ defined in §B.7), but differ in dimensionality: UMI has a single scalar α, whereas LMI has a (μ, σ) pair. For LMI we adopt a two-stage protocol: a one-time coarse 2D sweep that identifies the appropriate bandwidth σ for each architecture family and downstream regime, followed by a per-row fine 1D μ sweep at the fixed σ. The two-stage design lets us amortise the 2D cost across many rows of the main result tables while still capturing the per-row variation in μ^*.

E.1 UMI: α sweep

For every model×method×scale×downstream cell we sweep α over the eleven values $\{0.0, 0.1, \ldots, 0.9, 1.0\}$, where the endpoints recover the post-FT and post-edit checkpoints respectively. We then pick $\alpha^* = \arg\max_\alpha \mathrm{EA}(\alpha) \times \mathrm{Tr.}(\alpha)$ and report the row corresponding to α^* in Tables 4–7. The α^* values concentrate in a narrow band (0.4–0.8 across all 64 rows), and shift mildly with edit scale and downstream task as reported in §C.1.

E.2 LMI Stage 1: Coarse 2D (μ, σ) sweep

The first stage of LMI hyperparameter search establishes the operational range of σ. We perform a 2D sweep on a single representative setting (GPT-J + MEMIT @ 10^2, ZsRE-SFT) over the grid $\mu \in \{5.5, 7.0, 8.5, 10.0, 11.5\}$ and $\sigma \in \{2, 3, 4, 6\}$, plus the UMI anchors at $\alpha \in \{0.3, \ldots, 0.7\}$ for cross-method calibration. Each (μ, σ) point produces one merge plus one full-set evaluation, for a total cost of 20 evaluations $\approx 5\,\mathrm{GPU\text{-}h}$ on H200.

Coarse 2D (μ, σ) sweep on GPT-J + MEMIT @ 10^2, ZsRE-SFT

Figure 11: LMI Stage 1: coarse 2D (μ, σ) sweep on GPT-J + MEMIT @ 10^2 followed by ZsRE-SFT. Cells show EA (left), downstream Tr. (middle), and the selection criterion $\mathrm{EA} \times \mathrm{Tr.}$ (right, multiplied by 100 for display). The gold star marks the joint argmax at $(\mu^*, \sigma^*) = (5.5, 6)$. The sweep cleanly separates the two failure modes: small σ leaves the readout under-restored (EA < 50), whereas large σ over-restores and damages downstream Tr.

Findings from Stage 1 (Fig. 11). The two diagonals are monotonic in opposite directions: EA increases with σ (a broader Gaussian re-injects more edit weight into the readout circuitry), while Tr. decreases with σ (a broader Gaussian sacrifices more of the fine-tuned MLP capacity). The selection criterion peaks at $(\mu^*, \sigma^*) = (5.5, 6)$ with $\mathrm{EA} \times \mathrm{Tr.} = 80.7$, on the boundary between the deep editing layers (L3–8) and the adjacent post-edit layers (L9–14) identified in §4.3 as the readout circuitry. The optimal σ^* sits in the upper end of the swept range, suggesting that σ should be on the order of the readout-band half-width (about 5 layers for GPT-J).

Translating Stage 1 to per-setting σ. We do not re-run the 2D sweep for every cell of the main result tables. Instead, Stage 1 establishes the rule of thumb $\sigma \approx$ readout-band half-width, which we then apply across all 12 model×method×downstream combinations using the readout bands localised in §4.3 and

Appendix A. The resulting per-setting σ values are listed in Table 3: $\sigma=4$–6 for GPT-J (readout half-width ~ 4 layers, since the readout band is L6–14), $\sigma=3$ for GPT-J under LoRA (narrower since LoRA's perturbation is itself narrower), $\sigma=14$–20 for Llama-3 (readout half-width ~ 5–6 layers, but the SciQ setting calls for a broader bandwidth that recruits more of the MLP stack).

E.3 LMI Stage 2: Fine 1D μ sweep at fixed σ

With σ fixed by Stage 1, we sweep μ over integer layer indices on the range listed in Table 3. For GPT-J this is $\mu \in \{0, 1, \ldots, 14\}$; for Llama-3 we restrict the lower end to $\mu \geq 4$ to keep the kernel centred inside or above the edit layers L4–8. Per-row μ^* is again chosen by $\arg \max_\mu \mathrm{EA} \times \mathrm{Tr.}$ and reported in Tables 8–11. The cost is at most 15 evaluations per row, i.e. ≈ 3–4 GPU-h on H200, comparable to the UMI search budget of ≈ 2–3 GPU-h per row.

Findings from Stage 2 (Fig. 12). Three structural patterns emerge across the ten swept settings. First, the EA curve is unimodal (or monotonically saturating) in μ for every panel; this validates the assumption that the readout circuitry is spatially compact and that locating its centre with a single scalar μ is well-posed. Second, μ^* shifts down-stream under LoRA fine-tuning (e.g., GPT-J $\mu^*=7$–9 under LoRA vs. $\mu^*=3$–6 under SFT), consistent with LoRA's MLP-only perturbation being more concentrated in the adjacent post-edit layers. Third, μ^* shifts down-stream on Llama-3 relative to GPT-J (e.g., $\mu^*=10$–12 for Llama-3 SFT vs. 3–6 for GPT-J SFT), reflecting Llama-3's wider 32-layer stack and the correspondingly larger absolute index of its readout band.

E.4 Why a product objective?

We use $\mathrm{EA} \times \mathrm{Tr.}$ rather than, e.g., $\mathrm{EA} + \mathrm{Tr.}$ or EA alone, because the product penalises configurations that excel on one axis at the cost of collapsing the other. Inspecting Fig. 11 makes this concrete: the EA-only argmax is at $(\mu, \sigma) = (5.5, 6)$ with EA 93.9 but Tr. 85.9, while the Tr.-only argmax is anywhere on the $\sigma=2$ row with Tr. ≥ 99.6 but EA below 52. The product objective $\mathrm{EA} \times \mathrm{Tr.}$ recovers the same $(5.5, 6)$ as EA-only because Tr. is already close to 86% there, but on harder settings it pushes the selection toward configurations that retain more downstream capacity. The additive $\mathrm{EA} + \mathrm{Tr.}$ behaves similarly but is more sensitive to the absolute scale of the two metrics; we did not see qualitatively different sweet-spots under the additive form in pilot runs and therefore report the product version throughout.

F SVD Verification of the Null-Space Finding

The null-space analysis in §4.2 measures how much of fine-tuning's update ΔW couples with the edit signal via a single direction ($\Delta W \cdot k_{\mathrm{ed}}$), and concludes that the coupling is small. A natural concern is that this direction-specific probe could understate the disruption if fine-tuning moved the weights in some other principal direction of the edit. This appendix verifies the null-space finding from a complementary, basis-free angle: we decompose $\Delta W_{\mathrm{edit}} = W_{\mathrm{ed}} - W_0$ with an SVD and check how strongly the fine-tuning update $\Delta W_{\mathrm{ft}} = W_{\mathrm{ft}} - W_{\mathrm{ed}}$ projects onto each of its top singular directions.

F.1 Setup

For each edit layer $\ell \in \{3, \ldots, 8\}$ on GPT-J, we form the difference matrices $\Delta W_{\mathrm{edit}}^{(\ell)}$ and $\Delta W_{\mathrm{ft}}^{(\ell)}$ at the MLP output matrix `transformer.h.{ℓ}.mlp.fc_out.weight`, compute the SVD $\Delta W_{\mathrm{edit}}^{(\ell)} = U\Sigma V^\top$, and then report three quantities: (i) the global cosine similarity $\cos(\Delta W_{\mathrm{edit}}^{(\ell)}, \Delta W_{\mathrm{ft}}^{(\ell)})$ as a flat vectorised similarity; (ii) the *edit survival ratio*, the projection of $\Delta W_{\mathrm{edit}}^{(\ell)} + \Delta W_{\mathrm{ft}}^{(\ell)}$ along the edit direction normalised by $\|\Delta W_{\mathrm{edit}}^{(\ell)}\|$, which is 1 if fine-tuning is exactly orthogonal to the edit; and (iii) for each of the top-10 singular directions u_k, the normalised projection $|\langle \Delta W_{\mathrm{ft}}^{(\ell)}, u_k \rangle|/\sigma_k$. The setting is the MEMIT-edited GPT-J checkpoint used as the running example in §4.2, fine-tuned with MLP-only SFT on ZsRE at $\mathrm{lr} = 6 \times 10^{-5}$; results are nearly identical at the other learning rates we tested (last column of Table 12).

Figure 12: LMI Stage 2: fine 1D μ sweep at the per-setting fixed σ, parsed from the Slurm logs of the μ-sweep scripts. Each panel shows EA (blue), Tr. (orange), and held-out Te. (green) at the @Full edit scale; the grey dashed line marks the μ^* selected by $\arg\max \text{EA} \times \text{Tr.}$. The μ curves are predominantly unimodal in μ, and the selected μ^* concentrates inside the readout band identified in §4.3 (GPT-J $\mu^* \in \{3, \dots, 7\}$; Llama-3 $\mu^* \in \{6, \dots, 12\}$).

Table 12: SVD analysis of ΔW_{edit} and ΔW_{ft} at each GPT-J edit layer (MEMIT @ $\sim$ 20 edits, ZsRE-SFT lr=6×10^{-5}). cos: global cosine similarity between the two flattened update matrices. Surv.: edit survival ratio (Sec. F.1); values close to 1 indicate that fine-tuning is essentially orthogonal to the edit. Top-1 %: cumulative energy of the largest singular value of ΔW_{edit}. Top-10 %: cumulative energy of the top-10 singular values. Max FT proj.: maximum of $|\langle \Delta W_{\text{ft}}, u_k\rangle|/\sigma_k$ over $k = 1, \dots, 10$.

Layer	cos	Surv.	Top-1 %	Top-10 %	Max FT proj.
L3	-0.0005	1.0151	6.9%	29.3%	7×10^{-4}
L4	-0.0009	1.0153	6.1%	24.8%	9×10^{-4}
L5	-0.0004	1.0142	6.3%	24.3%	5×10^{-4}
L6	-0.0003	1.0167	6.3%	24.7%	4×10^{-4}
L7	-0.0007	1.0165	5.6%	24.7%	8×10^{-4}
L8	-0.0005	1.0172	12.1%	32.4%	4×10^{-4}
Robustness across learning rates (layer-averaged):					
lr= 2×10^{-5}	-0.0005	1.0156	—	—	—
lr= 4×10^{-5}	-0.0005	1.0159	—	—	—
lr= 6×10^{-5}	-0.0005	1.0158	—	—	—
lr= 8×10^{-5}	-0.0004	1.0157	—	—	—
lr= 1×10^{-4}	-0.0005	1.0158	—	—	—
lr= 2×10^{-4}	-0.0004	1.0157	—	—	—

F.2 Findings

ΔW_{edit} is not low-rank, but ΔW_{ft} still misses every one of its principal directions. Figure 13(a) shows that the cumulative energy of ΔW_{edit} in its top-10 singular directions saturates at only 24–32%, with the top-1 direction capturing 6–12%. The edit is therefore spread across many directions rather than concentrated in a few, and any direction-specific probe could in principle miss most of it. Despite this, Figure 13(b) shows that $|\langle \Delta W_{\text{ft}}, u_k\rangle|/\sigma_k$ stays below 10^{-3} for every top-10 direction at every layer, two orders of magnitude smaller than the 1% reference line that would indicate a non-trivial coupling. Fine-tuning is therefore not just orthogonal to the edit along a single hand-picked direction, but orthogonal to its entire top-10 principal subspace.

Edit survival ratio > 1: fine-tuning slightly reinforces, rather than erases, the edit. The middle column of Table 12 shows that the survival ratio sits in 1.014–1.017 across all six layers and in 1.015–1.016 when averaged over all six learning rates we tested. A value of exactly 1 would mean ΔW_{ft} is perfectly orthogonal to ΔW_{edit}; the small positive deviation indicates that fine-tuning's update, when projected along the edit direction, points slightly *toward* the edit rather than against it. This makes the EA collapse documented in §4.1 even more striking: the parameter-space edit not only survives, it is mildly amplified, while the strict-EA probe collapses from 100% to under 30%. The disruption therefore cannot be a weight-space erasure of the edit; it has to occur further downstream, which is exactly what the readout-circuitry account of §4.3 supplies.

Connection to §4.2. The null-space probe of §4.2 (Figure 3a) measures a single quantity (the projection of $\Delta W \cdot \Delta k$ along the edit-key direction) and finds it small. The SVD-based probe in this appendix is basis-free in ΔW_{edit} and finds the same conclusion in a strong form: the coupling is small along *every* top singular direction, the edit's energy is preserved in aggregate (survival > 1), and the result is invariant across all six learning rates we tested. Together, the two analyses give a stronger statement than either alone: fine-tuning's MLP update does not lie in the column span of the edit at all, in any basis we can reasonably define.

Figure 13: SVD verification of the null-space finding on GPT-J + MEMIT, ZsRE-SFT lr$= 6 \times 10^{-5}$. **(a)** Cumulative energy in the top-10 singular values of $\Delta W_{\text{edit}}^{(\ell)}$, one curve per edit layer ℓ. The spectrum is broad: the top direction captures only 6–12% and the top-10 subspace captures 24–32%. **(b)** $|\langle \Delta W_{\text{ft}}^{(\ell)}, u_k \rangle| / \sigma_k$ on log scale, for each of those top-10 directions. The grey dashed line marks 1%. All values lie below 10^{-3}, confirming that fine-tuning's update has negligible coupling to every principal direction of the edit.