NEURO-SYMBOLIC PROCEDURAL PLANNING WITH COMMONSENSE PROMPTING

ABSTRACT

Procedural planning aims to implement complex high-level goals by decomposition into sequential simpler low-level steps. Although procedural planning is a basic skill set for humans in daily life, it remains a challenge for large language models (LLMs) that lack a deep understanding of the cause-effect relations in procedures. Previous methods require manual exemplars to acquire procedural planning knowledge from LLMs in the zero-shot setting. However, such elicited pre-trained knowledge in LLMs induces spurious correlations between goals and steps, which impair the model generalization to unseen tasks. In contrast, this paper proposes a neuro-symbolic procedural **PLAN**ner (PLAN) that elicits procedural planning knowledge from the LLMs with commonsense-infused prompting. To mitigate spurious goal-step correlations, we use symbolic program executors on the latent procedural representations to formalize prompts from commonsense knowledge bases as a causal intervention toward the Structural Causal Model. Both automatic and human evaluations on WikiHow and RobotHow show the superiority of PLAN on procedural planning without further training or manual exemplars.

1 INTRODUCTION

How to make a cup of coffee? As humans, we can easily identify the procedure with the commonsense reasoning ability we acquire. However, can we endow machines with the same ability to sketch out a sequential plan list? Procedural planning (Pearson, 1996; Huang et al.; Lyu et al., 2021; Wu et al., 2022; Zhang et al., 2020a;b) is a task that aims to decompose a specific task into a sequence of temporally extended steps (Figure 1). Such ability is a necessity for a wide range of downstream applications, such as household robots (Ahn et al., 2022; Blukis et al., 2021; Min et al., 2022; Padmakumar et al., 2022; Shridhar et al., 2020) and conversational assistants (Budzianowski et al., 2018; Ding et al., 2022; Eric et al., 2017; Ilievski et al., 2018; Yang et al., 2022).

Existing formalization of the procedural planning task can mainly be categorized as 1) sequential choice making (Lyu et al., 2021; Wu et al., 2022; Zhang et al., 2020a;b), which reasons about the next step from the options given, the task, and previous steps; 2) conditioned generation (Huang et al.; Ahn et al., 2022), which generates the plans composing of temporal-extended steps to implement the task. We study the procedural planning task as the conditioned generation problem since it do not require a skillfully annotated dataset and is close to real-world scenarios. Previous approaches require manual exemplars (Wei et al., 2022; Huang et al.) to acquire such procedural knowledge in the zero-shot setting. However, it is impossible to cover the ever-changing task setups and the flexible dependency relations between internal steps. In fact, the biased data may cause the model to learn spurious correlations and hinder the model from generalizing to counterfactual tasks. Thus we take a step back and rethink how humans conduct procedural planning. Studies in cognitive science state that humans rely on past experience (Duncker & Lees, 1945; Knoblich et al., 1999; Smith, 1995; Zhang et al., 2019) and chunking mechanisms (Gobet et al., 2001; Miller, 1956) to solve novel and complex problems.

Such generalizable planning ability in complex tasks, if not using exemplars, can be achieved by learning the causal-effect relations among the goals and steps in the procedure. Thus we first devise a Structural Causal Model (SCM) (Peters et al., 2017) (Figure 2) for procedural planning and show that pre-trained knowledge (D) in LLMs confounds language models to make biased decisions toward an unreasonable action. Since the confounder is unobservable, intervention techniques such as backdoor

Figure 1: Two independant procedural planning task examples from RobotHow and WikiHow. PLAN construct commonsense-infused prompt from external knowledge (e.g., ConceptNet) to elicit procedural planning ability of the Large Language Models (LLMs) without training or exemplars.

adjustment (Hu & Li, 2021; Weber et al., 2020; Yue et al., 2020) are not applicable in our SCM. Instead, we build a mediator and implement it as a commonsense-infused prompt. Through the mediator, we can identify causal effects among goals and steps by investigating the indirect effect from the goals, which is essentially the frontdoor adjustment in causality (Pearl, 2009).

In addition, reasoning the logical order of the plan is a critical ability in procedural planning. For example, switching on TV happens before sitting on the sofa and watching TV, but switching on TV is interchangeable with grabbing the remote control. However, directly incorporating the graph structure external commonsense knowledge into language models cannot maximally elicit commonsense reasoning ability for order. Thus we apply a symbolic program (Mao et al., 2019; Yi et al., 2018) to construct such commonsense-infused prompt from external resource that attends to the high-level goals and maintains the procedural structure. More specifically, we parse the goal into an entity to retrieve the subgraph that represents the common knowledge related to the entity, including the prerequisite event, subsequent event, location, usage, etc. Finally, we semantically translate the knowledge to the admissible knowledge and aggregate with the task as commonsense-infused prompts to elicit procedural planning ability from LLMs.

We conduct experiments on two datasets that involve completing daily household goals, RobotHow (Puig et al., 2018) and WikiHow (Koupaee & Wang, 2018). Furthermore, we devise 3 families of automatic intervention methods to construct a counterfactual dataset based on the original dataset. PLAN surpasses powerful baselines (Chain of Thoughts (Wei et al., 2022) and Zero-shot Planner (Huang et al.)) by large margins on both the original and the counterfactual samples. Our major contributions in this work can be summarized as:

- We propose a neuro-symbolic model using commonsense-infused prompting to tackle the procedural planning task without annotated exemplars or further training.
- We develop the first causal framework for procedural planning by 1) defining a temporally extended Structural Causal Model and 2) resolving spurious correlation between high-level goals and low-level steps via frontdoor adjustment with a prompt-based mediator.
- Extensive evaluation results show the superiority of PLAN in reasoning the cause-effect relations among goals and steps and achieving promising procedural planning ability.

2   EXTERNAL KNOWLEDGE MATTERS IN PROCEDURAL PLANNING

As depicted in Figure 1, the procedural planning requires generating the Plan (e.g., *Step 1:* Walk to the living room.) conditioned on the Task (e.g., Watch TV). We describe the problem definition below and then show why external knowledge matters in procedural planning through the lens of causality and how we elicit procedural ability from the Large Language Models (LLMs).

2.1   PROBLEM DEFINITION

Given the high-level task T (e.g. watch television in the living room) sampled from a task domain D_T (e.g. RobotHow), a procedural planner aims to decompose it into lower-level time-extended

(a) Full temporal causal graph   (b) SCM at step i

Figure 2: **Structural Causal Model (SCM) for Procedural Planning.** (a) The full temporal causal graph. T denotes the task query, and S_i is the sub-goal step at timestep i. D is the unobservable confounding variable introduced by the LLMs. P_i denotes the mediating variables we construct to mitigate the spurious correlation. (b) The SCM at timestep i. Without causal intervention, the model produces a sub-goal step "find television" due to the spurious correlation between "television" and "living room" caused by the confounding variable D. With our causal intervention, the constructed mediating variable P_i (Section 3.1) can block the backdoor paths for $T \rightarrow S_i$ and $S_{i-1} \rightarrow S_i$ (opened by D) and generate the causal sub-goal "find book" precisely (Section 3.2).

steps $\mathbf{S} = \{s_1, ..., s_t | s \in \bar{S}\}$. Depending on the task domain D_T, the agent and the environment have certain action set A and the object set O respectively. Each step s in $\bar{S}$ is constrained as the admissible composition of $a \in A$ and $o \in O$. The procedural plan $\mathbf{S}$ is generated as $\mathbb{P}(S_t | T, S_{0:t-1})$.

2.2 A Causal Look at Procedure Planning with LLMs

We seek to empower the LLMs with the ability to reason cause-effect relations in procedural planning. Thus, we devise a causal framework by first defining a Structural Causal Model (SCM) of procedural planning in Figure 2. The SCM describes the temporal dynamics and procedural cause-effect relationship. Our causal assumption in SCM indicates that there is a backdoor path from task to step, which must be blocked with frontdoor adjustment. Therefore, we model the input prompt as a mediator which is created from external knowledge. More specifically, we define our Full Temporal Causal Graph as in Figure 2a, which is an unrolled Structural Causal Model (SCM) for sequential decision making. Our goal is to identify the causal effect between attended task T and plan procedures $\mathbf{S} = \{S_1, S_2, \ldots\}$ from LLMs. Initially, there are direct paths $T \rightarrow S_i$ and $S_k \rightarrow S_i, k < i$ because S_i relies on the LLM attended task entities and previous accomplished steps. D is an unobserved confounder from learned knowledge during pre-training. D builds a backdoor path between T and S_i and misguides the LLM to attend on false entities to generate the next step (see Fig. 2b). Note that D is unobservable as we directly adopt the LLM without knowing the pre-training data. To mitigate the spurious correlation, we then introduce a mediator P_i for each S_i as shown in Figure 2a to achieve our frontdoor adjustment by injecting external knowledge into LLMs in a neuro-symbolic approach. We describe the implementation of such frontdoor adjustment in Section 3.1.

3 Our Approach

Though LLMs have strong general language intelligence, they still perform poorly in reasoning the cause-effect relations in procedural plans due to a lack of daily life experience. We propose to elicit the unbiased procedural planning knowledge from the LLMs using the created commonsense-infused Prompt P as $\mathbb{P}(S_t | T, S_{0:t-1}, P)$. Figure 3 and Algorithm 1 depict how PLAN tackles the procedural planning in a five-stage manner. We illustrate the commonsense-infused prompt construction (the first three stages) in Section 3.1 and planning with LLMs (the last stage) in Section 3.2.

3.1 Commonsense-infused Prompt Construction

Inspired by the above causal analysis, we propose to construct commonsense-infused Prompt P that reveals the cause-effect relations among the goals and steps during procedural planning.

Figure 3: **The Overview of Procedural Planning.** Our five-stage pipeline includes: 1) semantically parsing the task T into entity set T_E to retrieve subgraph G_s from the external knowledge base G. 2) formalize procedural prompt P_G and then translate into the admissible one $\hat{P}_G$. 3) aggregate task, previous steps and P_G as final commonsense-infused prompt P. (Section 3.1) 4) and 5) generating and translating time-extended procedural plan until triggering the termination condition. (Section 3.2)

Stage1: Task-Relevant Knowledge Subgraph Sampling First, we investigate the causal effect $T \to P_i$ and $S_{i-1} \to P_i$ (Figure 2). Note that in the path $T \to D \to S_i \leftarrow P_i$, S_i is a collider that blocks the association between D and P_i. Since there is no backdoor path for $T \to P_i$ and similarly for $S_{i-1} \to P_i$, we simply have the conditional probability after applying *do*-operators:

$$\mathbb{P}(P_i = p | do(T)) = \mathbb{P}(P_i = p | T), \quad \mathbb{P}(P_i = p | do(S_{i-1})) = \mathbb{P}(P_i = p | S_{i-1}) \tag{1}$$

We achieve the *do*-operation in a prompting way by modifying the input so that the model can attend on the correct entities. We extract the entities from the task name, and retrieve a three-hop graph from an external knowledge base. The graph can be verbalized and applied as a prompt so that the LLM attends on the correct entities to plan S_1. As for the implementation, the high-level task name T is Semantically Parsed into the Entity Set T_E with the named entity information to extract the representative nodes from the graph. We use NLTK to tokenize and `pos_tag` the task text. Then we use the noun (e.g. television), noun phrases (e.g. remote control), and verb phrases (e.g. watch television) as the entity node. Each entity $e \in T_E$ is used as a query for sampling the local subgraph $G_e \subseteq \mathcal{N}_e \times \mathcal{R}_s \times \mathcal{N}_e$ from the external knowledge base $G \subseteq \mathcal{N} \times \mathcal{R} \times \mathcal{N}$ (e.g., ConceptNet (Speer et al., 2017)), where $\mathcal{N}$ and $\mathcal{R}$ represent the number of concept nodes and commonsense relations respectively. When extracting the Task-relevant Subgraph G_s from the External Knowledge Base G, we keep the triplets with relation type in household domain (e.g., `AtLocation`, `UsedFor`) and filter out ones in the linguistic domain (e.g., `DistinctFrom`, `DerivedFrom`) for the procedural planning task. $\mathcal{N}_e$ is maintained in a set of top-k task-relevant nodes using the weight of each R_e, which is adapted using the edge-wise invariance module illustrated in the next paragraph. G_s is a composite of the $\{G_e, e \in E\}$, representing the task-relevant external knowledge.

Stage2: Edge-Wise Adaption and Symbolic Structuring Second, we need to find the causal effect for $P_i \to S_i$. Since the path $P_i \leftarrow T \leftarrow D \to S_i$ contains a backdoor from P_i to S_i, we cannot rely on the conditional probability. Instead, we add intervention on P_i by applying the *do*-operator to cut off $D \to T$:

$$\mathbb{P}(S_i | do(P_i = p)) = \sum_{t,s} \mathbb{P}(S_i | p, T = t, S_{i-1} = s) \mathbb{P}(T = t, S_{i-1} = s)$$
$$= \sum_{t,s} \mathbb{P}(S_i | p, T = t, S_{i-1} = s) \mathbb{P}(S_{i-1} = s | T = t) \mathbb{P}(T = t) \tag{2}$$

The retrieved entity-centered graph has multiple edges representing various relationships with other actions/entities. Therefore, the summation over intervened T can be achieved by incorporating these edges into the prompt. For instance, "living room" can be "walked to" and "used for reading" while "book" can locate in "living room" and "bedroom". Similarly, we extrapolate over the edges for $i - 1$ hops to aggregate the intervened S_i, i.e. $P(S_{i-1} = s | T = t)$. Directly ranking the retrieved nodes N_e with the pre-computed weight in the external knowledge base will result in

---

Algorithm 1 Neuro-Symbolic Procedural Planning using Commonsense-Infused Prompting

---

Require:
    Task Sample T, Admissible Step Set S, External Knowledge Graph G;
    Language Model for Generation LM_G and Translation LM_T, Symbolic Rule Set R;
Ensure:
  1: Zero-shot Inference for Temporal-extended Procedural Plan $S_T = s_1, ..., s_t$;
  2: [Stage1] Semantically parse T into entity set T_E;
  3: Retrieve commonsense subgraph G_s from G for each $e \in T_E$;
  4: [Stage2] Construct procedural prompt P_G based on G_s using Symbolic Rule Set R;
  5: Translate P_G in Admissible Knowledge Prompt $\hat{P}_G = LM_T(P_G)$;
  6: [Stage3] Aggregate Prompt $P \leftarrow [T; S_{0:t-1}; \hat{P}_G]$;
  7: **for** each timestep t **do**
  8:    [Stage4] and [Stage5] $s_t = LM_T(LM_G(P_t))$;
  9:    Update Procedural Plan $S_T \leftarrow s_t$;
10: **end for**

---

spurious correlation. Such retrieved local subgraphs tend to capture the task-invariant concept nodes as the causal factors. To mitigate this, we propose to adapt the weight of each triplet (**Edge-wise Adaption**). The adaptive weight is the addition of the original edge weight and the cosine similarity between the tail node embedding n_{tail} and the task embedding v_{task}. The embeddings are projected from the node text and task name using the sentence-transformer (Reimers & Gurevych, 2019). To better track the utilized external knowledge during inference, we construct the task-dependent commonsense prompt with a symbolic program executor (**Symbolic Structuring**) guided by the relation type of each triplet in G_s with the adapted edge weight beyond threshold θ_e. Specifically, the executor acquires the neural information of each natural language node and executes the sequential mapping program by sampling the operation Op from the Symbolic Rule Set R according to the edge relation type. For instance, the *AtLocation* edge samples the operation `Op_AtLocation` from R, which takes the commonsense relation of the triplet from G_s as the parameters to query the procedural concept output given the natural language meaning of the linked nodes (e.g., go to the location of `Start_Node_Of`(r_e) in this case). Similarly, `Op_UsedFor` may refer to "go to find `End_Node_Of`(r_e) and use it for `Start_Node_Of`(r_e)". And operators `Op_HasSubevent` and `Op_HasPrerequisite` will recursively navigate the subgraph G_e. After navigating the subgraph, we linearize the transformed triplets as the Procedural Prompt P_G, which is then translated to Admissible Knowledge Prompt $\hat{P}_G$ by the Translation Language Model LM_T.

Stage3: Temporally-Extended Aggregation To acquire temporal order in procedure, we obtain the Prompt P at timestep t with the aggregation of task T, history steps $S_{0:t-1}$ and current external knowledge $\hat{P}_G$. The underlying causal mechanism is a combination of Eq. 1 and Eq. 2:

$$\mathbb{P}(S_i|do(T), do(S_{i-1})) = \sum_p \mathbb{P}(S_i|do(P_i = p))\mathbb{P}(p|do(T), do(S_i))$$

$$= \sum_p \mathbb{P}(p|T) \sum_{t,s} \mathbb{P}(S_i|p, T = t, S_{i-1} = s)\mathbb{P}(T = t, S_{i-1} = s) \quad (3)$$

The adjustment and marginalization in Eq. 3 is achieved in the input space by forming the Procedural Prompt P_G that allows the LLM to attend on the causal entities instead of the highly correlated ones for the next step generation. The LLM can reason over the most relevant edges to link the concepts with the task entities as a context. The prompts from knowledge bases are independent of the pre-training data distribution so that P_i is independent of D and satisfies the frontdoor criterion. Please refer to Appendix A for more details on the simplification of our causal temporal graph.

3.2 PROCEDURAL PLANNING WITH LLMS

Stage4: Semantic Generation The external knowledge is further concatenated with the high-level goal (task name) as the initial prompt. The initial prompt contains limited semantics and executability, but still contains external knowledge and structure that help leverage the reasoning ability of the large language models. Given the prompt, the language model Generation $LM_G \in \{P_{AR}, P_{AE}\}$ (e.g.,

GPT3, BART) generates the next sentence, and the most confident prediction is then appended to previous prompts. The Termination Condition is either reaching the max step t or the matching score is below threshold θ. The joint probabilities of auto-regressive (P_{AR}) and auto-encoder (P_{AE}) model is factorized as:

$$\mathbb{P}_{AR}(x) = \prod_{i=1}^{n} p(s_n|\hat{P_G}, s_{1:n-1}, T), \quad \mathbb{P}_{AE}(x) = \prod_{i=1}^{n} p(s_n|\hat{P_G}, \{s_{1:n-1}, [MASK]\}, T) \quad (4)$$

where $\hat{P_G}$ represent the commonsense knowledge and T represent the task name.

Stage5: Admissible Step Translation To ensure that the generated procedural plans could ground to the specific task domain (e.g. RobotHow, WikiHow), we should avoid producing the steps that are inadmissible (e.g. Toast the table). In other words, the generated steps should be fully constrained to the admissible composite of action and object in a certain task domain. Thus previous works ((Huang et al.; Ahn et al., 2022)) have explored using the model (which is LM_T in our case) to score a step selected from a fixed set of available options, instead of directly sampling from the output distributions of the language model (which is LM_G in our case). Specifically, we match the generated step by LM_G to the most similar admissible step in the embedding space encoded by the Translation Language Model LM_T. Following (Huang et al.), we utilize a Sentence-Transformer (Reimers & Gurevych, 2019) to calculate the cosine similarity:

$$\mathbb{P}(s_i|x) = LM_T(LM_G(x)), \text{where } s_i = \{k|k \in [a, o], a \in A, o \in O\} \quad (5)$$

which translates $LM_G(x)$ into the admissible step $s_i \in S$ that is the closest in the embedding space measured by the cosine similarity. A and O represent the action set and object set respectively.

3.3 Counterfactual Procedural Data Construction

To investigate the counterfactual reasoning ability of the procedural planning models, we design three families of intervention methods: 1) **Initial Configuration**: intervene in the initial configuration, such as the location for implementing the task. 2) **Intermediate Step**, randomly selecting the step from the program as an additional constraint the task name for implementing the task. 3) **Final Goal**, intervene the task goal as the composite of another randomly sampled task. Table 6 in Appendix summarizes the category, description. The counterfactual dataset construction details and post-intervention examples are provided in Appendix B.2.

4 Experiments

4.1 Procedural Planning Setup

Datasets We conduct zero-shot experiments on two datasets with procedural information, WikiHow[1] (collected following (Koupaee & Wang, 2018)) and RobotHow (Puig et al., 2018) without training. **WikiHow** is a large-scale text summarization dataset that is constructed from a human-written knowledge base, involving procedural tasks that spans various topics. We utilize "how to" title as the task names and the summarized headlines as the steps. **RobotHow** is a large knowledge base of common household tasks collected in the VirtualHome (Puig et al., 2018) simulator. The dataset contains the programs with high-level task names and low-level steps. D_T is composed of 292 and 2000 distinct tasks from RobotHow and WikiHow respectively. In RobotHow, A is of size 42 and O is of size 195. In WikiHow, A is of size 1161 and O is of size 13873. Human evaluations use randomly sampled 50 task examples for each dataset. Automatic evaluations use 150 and 1000 task examples randomly sampled from RobotHow and WikiHow respectively. Please refer to Appendix B.1 and Appendix B.2 for dataset details.

Baselines We compare our approach with three vanilla generative pre-trained language models (BART, GPT2, and GPT3) and two powerful generation baselines (Zero-shot Planner (Huang et al.) noted as "LLMaP" and Chain of Thought (Wei et al., 2022) noted as "Chain"). More method and configuration details of the models can be found in Appendix B.3 and Appendix B.4.

Metrics We ask human annotators on the Amazon Mechanical Turk platform to rate model performance on two aspects: 1) `Coverage`: depicts which set of steps can better complete the target task

---

[1]https://www.wikihow.com

Dataset	Model$_{base}$	Original-Coverage			Original-Order			Counterfactual-Coverage			Counterfactual-Order		
		Win(↑)	Tie	Lose(↓)	Win(↑)	Tie	Lose(↓)	Win(↑)	Tie	Lose(↓)	Win(↑)	Tie	Lose(↓)
RobotHow	BART (Lewis et al., 2020)	**46.67**	31.33	22.00	**50.00**	22.67	27.33	**42.00**	22.67	35.33	**50.00**	18.67	31.33
	GPT2 (Radford et al.)	**42.67**	22.00	35.33	**44.00**	18.67	37.33	**56.67**	11.33	32.00	**45.33**	16.00	38.67
	GPT3 (Brown et al., 2020)	**50.00**	23.33	26.67	**53.33**	23.33	23.33	**54.67**	16.67	28.67	**56.00**	15.33	28.67
WikiHow	BART (Lewis et al., 2020)	**56.67**	12.67	30.67	**69.33**	10.00	20.67	**50.00**	26.67	23.33	**46.00**	21.33	32.67
	GPT2 (Radford et al.)	**48.00**	16.00	36.00	**49.33**	11.33	39.33	**46.67**	16.67	36.67	**44.67**	19.33	36.00
	GPT3 (Brown et al., 2020)	**75.17**	10.74	14.09	**72.67**	8.67	18.67	**44.00**	22.67	33.33	**48.67**	25.33	26.00

Table 1: Percentages of procedural planning results of PLAN that are better than, tied with, or worse than Planner (Huang et al.), in coverage and order metrics under original and counterfactual setting.

Architecture	Model	RobotHow				WikiHow			
		Original		Counterfactual		Original		Counterfactual	
		Coverage	Order	Coverage	Order	Coverage	Order	Coverage	Order
BART (Lewis et al., 2020)	Chain (Wei et al., 2022)	2.99	2.80	2.71	2.76	2.88	3.42	3.34	2.97
	LLMaP (Huang et al.)	3.06	2.84	2.96	2.82	2.78	3.35	3.46	3.02
	PLAN (Ours)	**3.16**	**3.10**	**3.07**	**2.98**	**3.05**	**3.47**	**3.62**	**3.18**
GPT2 (Radford et al.)	Chain (Wei et al., 2022)	2.43	2.28	3.12	2.88	2.97	3.44	3.60	3.01
	LLMaP (Huang et al.)	3.09	2.94	2.93	**2.90**	3.20	3.53	3.63	3.24
	PLAN (Ours)	**3.12**	**2.99**	**3.43**	2.88	**3.67**	**3.69**	**3.81**	**3.31**
GPT3 (Brown et al., 2020)	Chain (Wei et al., 2022)	3.26	3.18	3.45	3.58	3.29	3.46	3.70	3.71
	LLMaP (Huang et al.)	3.50	3.56	3.56	3.53	3.21	3.27	3.77	3.71
	PLAN (Ours)	**3.72**	**3.70**	**3.67**	**3.56**	**3.72**	**3.82**	**3.85**	**3.75**

Table 2: Averaged 5-point Likert scale human evaluations on "coverage" and "order" aspects.

(captures semantic completeness). 2) `Order`: depicts which sequence covers more steps that are necessary to complete the target task (captures sequential order correctness). In addition, we use Sentence-BLEU (S-BLEU) (Papineni et al., 2002), BERTScore (Zhang* et al., 2020), ROUGE-1 (Lin, 2004) and Word Mover's Distance (WMD) (Kusner et al., 2015) as automatic evaluation metrics. These metrics are used to compute the semantic scores between the annotated programs and the predictions. Details of the crowdsourcing human evaluation can be found in Appendix C.1.

4.2 HUMAN EVALUATION RESULTS WITH COVERAGE AND ORDER METRIC

Each example is rated by 3 crowdsourcing annotators. For the **Win-Lose Comparison**, we ask the human rater to choose between ours and the baseline LLMaP (Huang et al.). Averaged results reported in Table 1 show that our PLAN is more frequently rated as better for both coverage and order metrics, outperforming baselines over the winning ratio by 21% in coverage and 26% in order, across two datasets. We report the average results of **Human Ratings** with 5-point Likert scale in Table 2. The consistent performance boost of PLAN indicates the superiority of injecting external commonsense knowledge into the procedural planning task. The performance drop of LLMaP and Chain in the counterfactual setting indicates the vulnerability of fixed holdout knowledge and the pre-defined manual exemplars in causal procedural planning. Please refer to Appendix C.1 for the crowdsourcing human evaluation interface details. Table 5 shows two examples for **Qualitative Comparison**. More examples can be found in Appendix D.

4.3 AUTOMATICALLY MEASURING THE PROCEDURAL PLANNING

Main Results Table 3 summarizes The automatic evaluation results. PLAN achieves the best results regardless of the architecture of the language model architecture, either autoregressive or autoencoder based. The performance gain of "LLMaP" over "Chain" may probably be due to direct exposure to the holdout task from the dataset. While the "Chain" baseline still outperforms the vanilla baseline that only takes the high-level task name as the prompt. Note that the annotated program is not the only solution, thus these automatic metrics provide limited absolute performance information. Details for the correlation between automatic metrics and human evaluation can be found in Section 4.5.

Effects of Edge-wise Adaption and Symbolic Program Execution We build the variant "w/o Adaption", which maintains the top-k task-specific nodes ranked by the original weight in the external knowledge graph G without adaption. And we build a variant "w/o Symbolic" that directly takes the extracted concept nodes from external knowledge base as prompt. As shown in Table 3, these two variants experience consistent performance drop, demonstrating the importance of adaption and

Model	RobotHow				WikiHow			
	S-BLEU	WMD	BERT-f1	ROUGE-f1	S-BLEU	WMD	BERT-f1	ROUGE-f1
BART Lewis et al. (2020)	0.069	0.923	0.870	0.442	0.083	0.937	0.836	0.379
BART + Chain (Wei et al., 2022)	0.079	0.913	0.862	0.448	0.095	0.939	0.782	0.377
BART + LLMaP (Huang et al.)	0.094	0.940	0.870	0.467	0.131	0.950	0.816	0.371
BART + PLAN (Ours)	**0.110**	**0.951**	**0.890**	**0.528**	**0.142**	**0.958**	0.833	**0.400**
w/o Adaption	0.104	0.929	0.886	0.492	0.132	0.952	0.824	0.398
w/o Symbolic	0.062	0.858	0.835	0.392	0.087	0.939	0.828	0.386
GPT2 (Radford et al.)	0.056	0.891	0.846	0.356	0.051	0.925	0.826	0.345
GPT2 + Chain (Wei et al., 2022)	0.079	0.906	0.861	0.405	0.124	0.937	0.817	0.352
GPT2 + LLMaP (Huang et al.)	0.115	0.931	0.885	0.481	0.115	0.957	0.833	0.363
GPT2 + PLAN (Ours)	**0.148**	**0.945**	**0.898**	**0.547**	**0.133**	**0.971**	**0.835**	**0.373**
w/o Adaption	0.142	0.944	0.896	0.542	0.123	0.965	0.830	0.360
w/o Symbolic	0.143	0.942	0.895	0.538	0.121	0.967	0.829	0.357
GPT3 (Brown et al., 2020)	0.072	0.882	0.855	0.416	0.077	0.936	0.832	0.366
GPT3 + Chain (Wei et al., 2022)	0.089	0.905	0.860	0.471	0.094	0.943	0.839	0.471
GPT3 + LLMaP (Huang et al.)	0.123	0.931	0.894	0.539	0.116	0.946	0.842	0.401
GPT3 + PLAN (Ours)	**0.155**	**0.939**	**0.902**	**0.561**	**0.155**	**0.961**	**0.849**	**0.433**
w/o Adaption	0.139	0.923	0.887	0.517	0.144	0.955	0.830	0.420
w/o Symbolic	0.135	0.933	0.898	0.536	0.140	0.959	0.843	0.414

Table 3: Automatic evaluation results on the Original RobotHow and WikiHow. Metrics are computed between the annotated programs and the predictions.

Model	Initial Configuration				Intermediate Step				Final Goal			
	S-BLEU	WMD	BERT-f1	ROUGE-f1	S-BLEU	WMD	BERT-f1	ROUGE-f1	S-BLEU	WMD	BERT-f1	ROUGE-f1
Chain (Wei et al., 2022)	0.125	0.906	0.875	0.518	0.136	0.926	0.892	0.550	0.063	0.918	0.857	0.467
LLMaP (Huang et al.)	0.148	0.929	0.887	0.566	0.141	0.886	0.902	0.547	0.070	0.928	0.868	0.490
PLAN (Ours)	**0.169**	**0.934**	**0.897**	**0.570**	**0.183**	**0.953**	**0.913**	**0.590**	**0.082**	**0.934**	**0.873**	**0.493**

Table 4: Automatic evaluation results on the Counterfactual RobotHow with language model GPT2.

symbolic components. We conduct the paired-t test (p¡0.05) statistics results over the variant "w/o Symbolic" and "w/o Adaption". Compared with the full model PLAN, the variants have experienced a statistically significant performance drop. Especially on BERTScore-f1, the p-value is $8.884e - 13$ and $1.4e - 8$ respectively. This further confirms the importance of the modules.

Effects of the Large Language Model Architecture To investigate the effects of the pre-trained language model architecture, we use GPT2 and GPT3 as our autoregressive architecture and BART (Lewis et al., 2020) as our autoencoder architecture. The autoregressive architecture achieves better results than the autoencoder one. Since the pre-training objective of autoregressive-based GPT is to predict the next token given the previous input tokens. We assume the performance gain of GPT is due to a smaller gap between the objective of their pre-training and the procedural planning task.

Level of Complexity We show report results that use the test set which is separated into several buckets according to the number of steps in the procedural planning task. The step number reflects the difficulty of the task. In Table 8 and Table 9 in Appendix C.2, we show that the averaged performance gain of PLAN over the baselines are consistent or more significant in more complicated procedural planning settings. This indicates the superiority of PLAN in solving long-horizon tasks.

4.4 RESULTS ON COUNTERFACTUAL TASK SAMPLES

We apply *Initial Configuration*, *Intermediate Step*, *Final Goal* intervention methods on RobotHow and *Intermediate Step* on WikiHow. Counterfactual setting results for human evaluation are summarized in Table 1 and Table 2. PLAN consistently outperforms baselines by a large margin and experiences a much smaller performance drop compared with the powerful baselines when switching to the counterfactual setting. We assume it's due to the biased knowledge of the holdout examples and manual exemplars utilized in the baselines, which are vulnerable to counterfactual samples. Automatic evaluation results on counterfactual RobotHow are summarized in Table 4. Aligned with human evaluations, PLAN achieves the best performance. The overall poor performance in *the Final Goal* category indicates the challenge for long-horizon and composite procedural planning tasks. While the overall better performance in the *Intermediate Step* category benefits from the intermediate guidance.

Dataset	Task	Model	Steps
RobotHow	Toast Bread	Chain	Step 1: Walk to kitchen. Step 2: Put bowl on oven. Step 3: Switch off oven. Step 4: Open oven. Step 5: Grab bowl. Step 6: Put bowl in oven.
		LLMaP	Step 1: Put bread in oven. Step 2: Put food bread in oven. Step 3: Put food bread on table.
		PLAN	Step 1: Walk to kitchen counter. Step 2: Pull bread slice. Step 3: Put bread slice on toaster. Step 4: Switch on toaster. Step 5: Look at toaster. Step 6: Turn to toaster.
WikiHow	How to Take Care of a Pet	Chain	Step 1: Take care of your pets. Step 2: Scroll to the end of the text file.
		LLMaP	Step 1: Make sure your pet always has enough food and water. Step 2: Be sure to feed your dog at least three times a day. . . . Step 4: Give your dog fruits and vegetables as snacks. . . .
		PLAN	Step 1: Research the type of pet, so you can make sure the pet fits into your environment and lifestyle. . . . Step 4: Watch your pet's diet carefully. Step 5: Monitor your pet for illness and injury. . . .

Table 5: Showcases of procedural steps predicted by different models with GPT2 as the base LLM.

4.5 CORRELATION BETWEEN AUTOMATIC AND HUMAN EVALUATION

We evaluate segment-level **Pearson Correlation** between human and automatic metrics. We observe that BERTScore has a moderate correlation to the human coverage score and WMD has a moderate correlation to the human order score, with 23.3% and 32.3% respectively. Similar to the prior findings (Xu et al., 2021), n-gram-based metrics (Sentence-BLEU and ROUGE) have a relatively weaker correlation to the human coverage score, with a Pearson correlation of 16.4% and 21.1%. Overall, our automatic and human evaluation scores are consistent with the main claim of this paper. However, human evaluation is still irreplaceable for procedural planning at the current stage.

5 RELATED WORK

Procedural Planning Learning to generate procedural plan (Zhang et al., 2020b; Chang et al., 2020; Huang et al.) is important for embodied agentTellex et al. (2011); Jansen (2020); Ahn et al. (2022) and conversational assistants (Ilievski et al., 2018; Yang et al., 2022). Previous work views procedural script learning as a structured form of commonsense knowledge Gupta et al. (2004); Regneri et al. (2010); Wanzare et al. (2016), while more recent work strengthens its association with the changing environments for executable action planning Puig et al. (2018); Shridhar et al. (2020). Our method tackles the problem by utilizing commonsense-infused prompts via a neuro-symbolic approach (Mao et al., 2019; Nye et al., 2021; Yi et al., 2018) for zero-shot procedural planning.

Causality for Language Generation The integration of causality and machine learning has been an intriguing topic for many problems Pearl (2009); Schölkopf (2022). Previous studies focusing on causal inference for natural language understanding Chen et al. (2020); Keith et al. (2020); Wood-Doughty et al. (2018) and generating counterfactual text representations Feder et al. (2021). Weber et al. (2020) proposes an intervention method for script learning. However, their method cannot be directly applied to procedural generation. The generated plan in our case has a formal structure and our method is based on mediation analysis VanderWeele (2015) and causal intervention Pearl (2009); Peters et al. (2017).

Prompt for Large Language Model There is an emerging interest in using prompts to extract knowledge from large language models Chen et al. (2022); Le Scao & Rush (2021); Su et al. (2022); Ye et al. (2022); Zhou et al. (2022). Cao et al. (2022) treats the prompt as a cause of the task-specific predictor and investigates biases in prompt-based probing evaluations. Chain of thought Wei et al. (2022) discovers that LLM can perform better on reasoning tasks when the prompt is designed as a series of short sentences that mimic the reasoning process of humans.

6 CONCLUSION AND FUTURE WORK

Procedural planning is a newly emerged research area of great importance to various applications, such as household robots and virtual assistants. We propose a neuro-symbolic procedural **PLAN**ner (PLAN) with commonsense-infused prompts elicited from the external knowledge base to solve the procedural planning problem in a zero-shot manner. Experiments show the effectiveness of our proposed PLAN on both automatic and human evaluation results. Extending neuro-symbolic procedural planning to handle the long-horizon composite tasks and provide effective automatic evaluation metrics are important directions for future work.

7 ETHICAL STATEMENT

Given the limited diversified cultural background of the dataset we are using from RobotHow and WikiHow, we assume our results may be biased toward a single cultural background. For instance, given the task "make breakfeast", it should take multi-culture into consideration to generate the procedural plans.

8 REPRODUCIBILITY STATEMENT

We provide more data samples and qualitative samples in supplemental materials. In addition, we provide our code implementation at https://anonymous.4open.science/r/PLANNER-7B24 to reproduce our experiments. The `Preprocess` folder provides the utils to construct the data. The `Evaluation` folder provides the code for automatic and human evaluation tools. The `Planning` folder contains the main code for our approach and reproduced planners for procedural planning. The `Visualization` folder provides the code we use to visualize in the environment.

REFERENCES

Michael Ahn, Anthony Brohan, Noah Brown, Yevgen Chebotar, Omar Cortes, Byron David, Chelsea Finn, Keerthana Gopalakrishnan, Karol Hausman, Alex Herzog, et al. Do as i can, not as i say: Grounding language in robotic affordances. *arXiv preprint arXiv:2204.01691*, 2022.

Valts Blukis, Chris Paxton, Dieter Fox, Animesh Garg, and Yoav Artzi. A persistent spatial semantic representation for high-level natural language instruction execution. In *CoRL*, 2021.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 1877–1901. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/1457c0d6bfcb4967418bfb8ac142f64a-Paper.pdf.

Paweł Budzianowski, Tsung-Hsien Wen, Bo-Hsiang Tseng, Iñigo Casanueva, Stefan Ultes, Osman Ramadan, and Milica Gasic. Multiwoz - a large-scale multi-domain wizard-of-oz dataset for task-oriented dialogue modelling. In *EMNLP*, 2018.

Boxi Cao, Hongyu Lin, Xianpei Han, Fangchao Liu, and Le Sun. Can prompt probe pretrained language models? understanding the invisible risks from a causal view. *ACL*, 2022.

Chien-Yi Chang, De-An Huang, Danfei Xu, Ehsan Adeli, Li Fei-Fei, and Juan Carlos Niebles. Procedure planning in instructional videos. In *Computer Vision – ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part XI*, pp. 334–350, Berlin, Heidelberg, 2020. Springer-Verlag. ISBN 978-3-030-58620-1. doi: 10.1007/978-3-030-58621-8_20. URL https://doi.org/10.1007/978-3-030-58621-8_20.

Wenqing Chen, Jidong Tian, Liqiang Xiao, Hao He, and Yaohui Jin. Exploring logically dependent multi-task learning with causal inference. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 2213–2225, 2020.

Xiang Chen, Ningyu Zhang, Xin Xie, Shumin Deng, Yunzhi Yao, Chuanqi Tan, Fei Huang, Luo Si, and Huajun Chen. Knowprompt: Knowledge-aware prompt-tuning with synergistic optimization for relation extraction. In *Proceedings of the ACM Web Conference 2022*, pp. 2778–2788, 2022.

Bosheng Ding, Junjie Hu, Lidong Bing, Sharifah Aljunied Mahani, Shafiq R. Joty, Luo Si, and Chunyan Miao. Globalwoz: Globalizing multiwoz to develop multilingual task-oriented dialogue systems. 2022.

Karl Duncker and Lynne S Lees. On problem-solving. *Psychological monographs*, 58(5):i, 1945.

Mihail Eric, Lakshmi Krishnan, Francois Charette, and Christopher D. Manning. Key-value retrieval networks for task-oriented dialogue. In *Proceedings of the 18th Annual SIGdial Meeting on Discourse and Dialogue*, pp. 37–49, Saarbrücken, Germany, August 2017. Association for Computational Linguistics. doi: 10.18653/v1/W17-5506. URL `https://aclanthology.org/W17-5506`.

Amir Feder, Nadav Oved, Uri Shalit, and Roi Reichart. Causalm: Causal model explanation through counterfactual language models. *Computational Linguistics*, 47(2):333–386, 2021.

Fernand Gobet, Peter C.R. Lane, Steve Croker, Peter C-H. Cheng, Gary Jones, Iain Oliver, and Julian M. Pine. Chunking mechanisms in human learning. *Trends in Cognitive Sciences*, 5(6):236–243, 2001. ISSN 1364-6613. doi: https://doi.org/10.1016/S1364-6613(00)01662-4. URL `https://www.sciencedirect.com/science/article/pii/S1364661300016624`.

Rakesh Gupta, Mykel J Kochenderfer, Deborah Mcguinness, and George Ferguson. Common sense data acquisition for indoor mobile robots. In *AAAI*, pp. 605–610, 2004.

Zhiting Hu and Li Erran Li. A causal lens for controllable text generation. *Advances in Neural Information Processing Systems*, 34, 2021.

Wenlong Huang, Pieter Abbeel, Deepak Pathak, and Igor Mordatch. Language models as zero-shot planners: Extracting actionable knowledge for embodied agents gpt-2 1.5b. URL `https://huangwl18.github.io/language-planner`.

Vladimir Ilievski, Claudiu Cristian Musat, Andreea Hossmann, and Michael Baeriswyl. Goal-oriented chatbot dialog management bootstrapping with transfer learning. In *IJCAI*, 2018.

Peter Jansen. Visually-grounded planning without vision: Language models infer detailed plans from high-level instructions. In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pp. 4412–4417, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.findings-emnlp.395. URL `https://aclanthology.org/2020.findings-emnlp.395`.

Katherine Keith, David Jensen, and Brendan O'Connor. Text and causal inference: A review of using text to remove confounding from causal estimates. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 5332–5344, 2020.

Giinther Knoblich, Stellan Ohlsson, Hilde Haider, and Detlef Rhenius. Constraint relaxation and chunk decomposition in insight problem solving. *Journal of Experimental Psychology: Learning, Memory and Cognition*, 25:1534–1555, 1999.

Mahnaz Koupaee and William Yang Wang. Wikihow: A large scale text summarization dataset. *ArXiv*, abs/1810.09305, 2018.

Matt Kusner, Yu Sun, Nicholas Kolkin, and Kilian Weinberger. From word embeddings to document distances. In Francis Bach and David Blei (eds.), *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pp. 957–966, Lille, France, 07–09 Jul 2015. PMLR. URL `https://proceedings.mlr.press/v37/kusnerb15.html`.

Teven Le Scao and Alexander M Rush. How many data points is a prompt worth? In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 2627–2636, 2021.

Mike Lewis, Yinhan Liu, Naman Goyal, Marjan Ghazvininejad, Abdelrahman Mohamed, Omer Levy, Veselin Stoyanov, and Luke Zettlemoyer. BART: Denoising sequence-to-sequence pre-training for natural language generation, translation, and comprehension. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 7871–7880, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.703. URL `https://aclanthology.org/2020.acl-main.703`.

Chin-Yew Lin. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pp. 74–81, Barcelona, Spain, July 2004. Association for Computational Linguistics. URL `https://aclanthology.org/W04-1013`.

Qing Lyu, Li Zhang, and Chris Callison-Burch. Goal-oriented script construction. In *Proceedings of the 14th International Conference on Natural Language Generation*, pp. 184–200, 2021.

Jiayuan Mao, Chuang Gan, Pushmeet Kohli, Joshua B. Tenenbaum, and Jiajun Wu. The Neuro-Symbolic Concept Learner: Interpreting Scenes, Words, and Sentences From Natural Supervision. In *International Conference on Learning Representations*, 2019. URL `https://openreview.net/forum?id=rJgMlhRctm`.

George A. Miller. The magical number seven plus or minus two: some limits on our capacity for processing information. *Psychological review*, 63 2:81–97, 1956.

So Yeon Min, Devendra Singh Chaplot, Pradeep Ravikumar, Yonatan Bisk, and Ruslan Salakhutdinov. Film: Following instructions in language with modular methods. 2022.

Maxwell Nye, Michael Tessler, Josh Tenenbaum, and Brenden M Lake. Improving coherence and consistency in neural sequence models with dual-system, neuro-symbolic reasoning. *Advances in Neural Information Processing Systems*, 34, 2021.

Aishwarya Padmakumar, Jesse Thomason, Ayush Shrivastava, Patrick Lange, Anjali Narayan-Chen, Spandana Gella, Robinson Piramuthu, Gokhan Tur, and Dilek Hakkani-Tür. Teach: Task-driven embodied agents that chat. In *AAAI 2022*, 2022. URL `https://www.amazon.science/publications/teach-task-driven-embodied-agents-that-chat`.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics*, pp. 311–318, Philadelphia, Pennsylvania, USA, July 2002. Association for Computational Linguistics. doi: 10.3115/1073083.1073135. URL `https://aclanthology.org/P02-1040`.

Judea Pearl. Causal diagrams for empirical research. *Biometrika*, 82(4):669–688, 1995.

Judea Pearl. *Causality*. Cambridge university press, 2009.

Douglas J. Pearson. Learning procedural planning knowledge in complex environments. In *AAAI/IAAI, Vol. 2*, 1996.

Jonas Peters, Dominik Janzing, and Bernhard Schölkopf. *Elements of causal inference: foundations and learning algorithms*. The MIT Press, 2017.

Xavier Puig, Kevin Ra, Marko Boben, Jiaman Li, Tingwu Wang, Sanja Fidler, and Antonio Torralba. Virtualhome: Simulating household activities via programs. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 8494–8502, 2018.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. URL `https://github.com/codelucas/newspaper`.

Michaela Regneri, Alexander Koller, and Manfred Pinkal. Learning script knowledge with web experiments. In *Proceedings of the 48th Annual Meeting of the Association for Computational Linguistics*, pp. 979–988, 2010.

Nils Reimers and Iryna Gurevych. Sentence-BERT: Sentence embeddings using Siamese BERT-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 3982–3992, Hong Kong, China, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1410. URL `https://aclanthology.org/D19-1410`.

Bernhard Schölkopf. Causality for machine learning. In *Probabilistic and Causal Inference: The Works of Judea Pearl*, pp. 765–804. 2022.

Mohit Shridhar, Jesse Thomason, Daniel Gordon, Yonatan Bisk, Winson Han, Roozbeh Mottaghi, Luke Zettlemoyer, and Dieter Fox. Alfred: A benchmark for interpreting grounded instructions for everyday tasks. *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 10737–10746, 2020.

Steven M. Smith. Getting into and out of mental ruts: A theory of fixation, incubation, and insight. 1995.

Robyn Speer, Joshua Chin, and Catherine Havasi. Conceptnet 5.5: An open multilingual graph of general knowledge. In *Proceedings of the Thirty-First AAAI Conference on Artificial Intelligence*, AAAI'17, pp. 4444–4451. AAAI Press, 2017.

Yusheng Su, Xiaozhi Wang, Yujia Qin, Chi-Min Chan, Yankai Lin, Huadong Wang, Kaiyue Wen, Zhiyuan Liu, Peng Li, Juanzi Li, Lei Hou, Maosong Sun, and Jie Zhou. On transferability of prompt tuning for natural language processing. In *Annual Conference of the North American Chapter of the Association for Computational Linguistics (NAACL)*, 2022.

Stefanie Tellex, Thomas Kollar, Steven Dickerson, Matthew Walter, Ashis Banerjee, Seth Teller, and Nicholas Roy. Understanding natural language commands for robotic navigation and mobile manipulation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 25, pp. 1507–1514, 2011.

Tyler VanderWeele. *Explanation in causal inference: methods for mediation and interaction*. Oxford University Press, 2015.

Lilian DA Wanzare, Alessandra Zarcone, Stefan Thater, and Manfred Pinkal. A crowdsourced database of event sequence descriptions for the acquisition of high-quality script knowledge. In *Proceedings of the Tenth International Conference on Language Resources and Evaluation (LREC'16)*, pp. 3494–3501, 2016.

Noah Weber, Rachel Rudinger, and Benjamin Van Durme. Causal inference of script knowledge. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 7583–7596, 2020.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Ed Chi, Quoc Le, and Denny Zhou. Chain of thought prompting elicits reasoning in large language models. 1 2022. URL `http://arxiv.org/abs/2201.11903`.

Zach Wood-Doughty, Ilya Shpitser, and Mark Dredze. Challenges of using text classifiers for causal inference. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing. Conference on Empirical Methods in Natural Language Processing*, volume 2018, pp. 4586. NIH Public Access, 2018.

Te-Lin Wu, Alexander Spangher, Pegah Alipoormolabashi, Marjorie Freedman, Ralph M. Weischedel, and Nanyun Peng. Understanding multimodal procedural knowledge by sequencing multimodal instructional manuals. In *ACL*, 2022.

Wenda Xu, Michael Saxon, Misha Sra, and William Yang Wang. Self-supervised knowledge assimilation for expert-layman text style transfer. In *AAAI*, 2021.

Shiquan Yang, Rui Zhang, Sarah Monazam Erfani, and Jey Han Lau. An interpretable neuro-symbolic reasoning framework for task-oriented dialogue generation. 2022.

Hongbin Ye, Ningyu Zhang, Shumin Deng, Xiang Chen, Hui Chen, Feiyu Xiong, Xi Chen, and Huajun Chen. Ontology-enhanced prompt-tuning for few-shot learning. *WWW*, 2022.

Kexin Yi, Jiajun Wu, Chuang Gan, Antonio Torralba, Pushmeet Kohli, and Joshua B. Tenenbaum. Neural-symbolic vqa: Disentangling reasoning from vision and language understanding. In *NeurIPS*, 2018.

Zhongqi Yue, Hanwang Zhang, Qianru Sun, and Xian-Sheng Hua. Interventional few-shot learning. *Advances in neural information processing systems*, 33:2734–2746, 2020.

Li Zhang, Qing Lyu, and Chris Callison-Burch. Intent detection with wikihow. In *Proceedings of the 1st Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics and the 10th International Joint Conference on Natural Language Processing*, pp. 328–333, 2020a.

Li Zhang, Qing Lyu, and Chris Callison-Burch. Reasoning about goals, steps, and temporal ordering with wikihow. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 4630–4639, 2020b.

Tianyi Zhang*, Varsha Kishore*, Felix Wu*, Kilian Q. Weinberger, and Yoav Artzi. Bertscore: Evaluating text generation with bert. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=SkeHuCVFDr`.

Zhonglu Zhang, Yu Luo, Chaolun Wang, Christopher M. Warren, Qianfeng Xia, Qiang Xing, Bihua Cao, Yi Lei, and Hong Li. Identification and transformation difficulty in problem solving: Electrophysiological evidence from chunk decomposition. *Biological Psychology*, 143:10–21, 2019.

Kaiyang Zhou, Jingkang Yang, Chen Change Loy, and Ziwei Liu. Conditional prompt learning for vision-language models. In *CVPR*, 2022.

A SCM THEORETICAL DETAILS

A.1 CAUSAL PRELIMINARIES

The Structural Causal Model (SCM) is a directed acyclic graph (DAG) to describe the causal relationships within a system Pearl (2009). In this paper, we refer to the unrolled SCM along the time dimension as the full temporal causal graph, while the rolled-up version is also called the causal summary graph Peters et al. (2017). In an SCM, if the variable D is a cause of both T and S_i, then it is called a **confounder**. A confounder opens up a backdoor path and causes a spurious correlation between T and S_i. The **backdoor path** is defined as the remaining path between T and S_i when all the arrows pointing out of T are removed. Therefore, $T \leftarrow D \rightarrow S_i$ is a backdoor path. For our SCM with mediator P_i shown in Figure 4c (same as Figure 2b) from the main paper, there is no backdoor path between T and $\{P_i, S_{i-1}\}$ because only $D \rightarrow T$ is left after removing outgoing arrows of T. On the other hand, there is a backdoor path between P_i and S_i, i.e. $P_i \leftarrow T \leftarrow D \rightarrow S_i$ so that P_i indirectly affect the observation of S_i through $\{T, S_{i-1}\}$ and D.

To identify the true causal effect between X and Y, we aim to estimate the conditional $\mathbb{P}(Y|do(X))$ after intervention with the *do*-operator. The *do*-operator is to break the backdoor path by setting X to a fixed value independent of Z. Then the path $Z \rightarrow X$ can be removed to eliminate the backdoor paths. In practice, the backdoor adjustment and frontdoor adjustment are two fundamental methods to implement interventions and obtain the conditional $\mathbb{P}(Y|do(X))$.

Clarity of the Definition As a language prompt, P_i inherit the content from P_{i-1} and thus can be detached from steps before S_{i-1} for simplicity.

Causal Intervention There are two types of operation to control the confounding bias: the *backdoor adjustment* and the *frontdoor adjustment* (Pearl, 2009). The backdoor adjustment is intractable in our case because it requires the prior distribution of the confounding variables. On the other hand, we can construct an input prompt as a mediator P_i for $T \rightarrow S_i$ and $S_{i-1} \rightarrow S_i$. Then the frontdoor adjustment applies a two-step *do*-operation to mitigate bias by investigating $P \rightarrow S_i$ (Pearl, 2009). Specifically, we construct the prompt mediator P_i using techniques illustrated in Section 2.2.

A.2 THE BACKDOOR ADJUSTMENT

The backdoor adjustment is one way to realize the intervention $do(T = t)$ by considering the conditional probability over the existing data distribution with observed confounder D. It calculates the average causal effects by considering all stratums of the dataset:

$$\mathbb{P}(S_i|do(T)) = \sum_d \mathbb{P}(S_i|T, D = d)\mathbb{P}(D = d) \tag{6}$$

However, for LLMs, the pretraining data is usually unobservable and has been transformed as knowledge incorporated into the hidden space. Therefore, we are not able to directly apply the backdoor adjustment.

A.3 THE FRONTDOOR ADJUSTMENT

The frontdoor adjustment is another technique to apply intervention by introducing a mediator P_i when the confounder is unobservable. As is explained in Section 2.2 from the main paper, the frontdoor adjustment is equivalent to two consecutive *do*-operation on task T and prompt P_i. We first investigate the generation of S_1 and then expand it to S_t.

Timestep $i = 1$ As is shown in Figure 4a, since there is no preceding steps, the first step generation involves D, T and P_1 only. Similar to the proof in Section 2.2 from the main paper, we have:

$$P(S_1|do(T)) = \sum_p P(S_1|do(P_1 = p))P(p|do(T))$$
$$= \sum_p P(p|T) \sum_t P(S_i|p, T = t)P(T = t) \tag{7}$$

By adding intervention to T, we make the value of $do(T = t)$ independent of the confounder D at the beginning. The backdoor path through $D \rightarrow T$ is eliminated as a result.

(a) SCM at timestep $i = 1$

(b) The SCM and three backdoor paths at timestep $i > 1$

(c) Equivalent SCM at timestep $i > 1$ after eliminating P_{i-1}

Figure 4: **The Frontdoor Adjustment for Causal Procedural Planner.** (a) the structural causal model at timestamp $i = 1$. T denotes the task name and S_1 denotes the step at timestep 1. D is the unobservable confounding variable introduced by the pre-training data. P_1 denotes the mediating variables we construct to mitigate the spurious correlation at timestep 1. (b) D opens up backdoor paths for $T \to S_i$, $P_{i-1} \to S_i$ and $S_{i-1} \to S_i$ which can be blocked by introducing P_i. path 1 and path 2 share the same path $D \to T$. Intervention on T blocks $D \to T$ and the backdoor path 2. Intervention on S_{i-1} blocks $D \to S_{i-1}$ and the backdoor path 3. (c) the structural causal model at timestamp $i > 1$ after simplification based on Equation 13-17.

Timestep $i > 1$ As is shown in Figure 2a from the main paper, we model the mediator P_1 as an effect of three variables, T, P_{i-1} and S_{i-1}. The first step of our frontdoor adjustment is to apply the *do*-operator on the three variables and observe the change in P_i as explained in Section 2.2 from the main paper. Since there are no backdoor paths between P_i and these variables, we have the probability after intervention equal to the conditional probability without intervention:

$$\mathbb{P}(P_i = p | do(T)) = \mathbb{P}(P_i = p | T) \tag{8}$$
$$\mathbb{P}(P_i = p | do(P_{i-1})) = \mathbb{P}(P_i = p | P_{i-1}) \tag{9}$$
$$\mathbb{P}(P_i = p | do(S_{i-1})) = \mathbb{P}(P_i = p | S_{i-1}) \tag{10}$$

The second step is to apply *do*-operator on P_i and then identify the causal effect as:

$$\mathbb{P}(S_i | do(P_i)) = \sum_{t,p',s} \Big(\mathbb{P}(S_i | P_i, T = t, P_{i-1} = p', S_{i-1} = s) \\ \mathbb{P}(T = t, P_{i-1} = p', S_{i-1} = s) \Big) \tag{11}$$

Combining Equation8-10 and Equation 11, we have the frontdoor adjustment. Note that there are three backdoor paths from each of the variables T, P_{i-1}, and S_{i-1}, as is shown in Figure 4b (drawn in blue, red and purple). More importantly, the one through T, i.e. $P_i \leftarrow T \leftarrow D \to S_i$ (the blue path in Figure 4b) and the one through P_{i-1}, i.e. $P_i \leftarrow P_{i-1} \leftarrow T \leftarrow D \to S_i$ (the red path in Figure 4b) shares the same subpath. The intervention on the task T breaks the backdoor paths for both T and P_{i-1}. Therefore, we have our frontdoor adjustment as

$$\mathbb{P}(S_i | do(S_{i-1}), do(P_{i-1}), do(T)) \tag{12}$$
$$= \sum_p \mathbb{P}(S_i | do(P_i = p)) \mathbb{P}(p | do(S_{i-1}), do(P_{i-1}), do(T)) \tag{13}$$
$$= \sum_p \mathbb{P}(S_i | do(P_i = p)) \mathbb{P}(p | do(S_{i-1}), P_{i-1}, do(T)) \tag{14}$$
$$= \sum_p \mathbb{P}(S_i | do(P_i = p)) \mathbb{P}(p | do(S_{i-1}), do(T)) \tag{15}$$
$$= \sum_p \mathbb{P}(p | S_{i-1}, T) \sum_{s,t} \mathbb{P}(S_i | p, S_{i-1} = s, T = t) \mathbb{P}(S_{i-1} = s, T = t) \tag{16}$$
$$= \mathbb{P}(S_i | do(S_{i-1}), do(T)) \tag{17}$$

We have Equation 14 because of the intervention on T and **Rule 2** (Pearl, 1995), Equation 15 because of **Rule 1** (Pearl, 1995). We end up with Equation 15-17 which is shown as Equation 3 in Section 2.2 from the main paper.

B   IMPLEMENTATION DETAILS

B.1   ORIGINAL DATASET DETAILS

RobotHow This dataset is Attribution-NonCommercial-ShareAlike 4.0 International Creative Commons License. We evaluate the inference of 150 tasks by random selection from the dataset. Each program contains the task name, task description and steps. We use the task name and sequence of steps as our input and output references. Each step is a composition of `[Action]`, `[Object]` and `[Number]`. For example, the sequence of steps of the task "Watch TV" are: 1. [Walk] ¡TELEVISION¿ (1) 2. [SwitchOn] ¡TELEVISION¿ (1) 3. [Walk] ¡SOFA¿ (1) 4. [Sit] ¡SOFA¿ (1) 5. [Watch] ¡TELEVISION¿ (1).

WikiHow This dataset is under an Attribution-Noncommercial-Share Alike 3.0 Creative Commons License. And the text content is free to modify, republish and share. We evaluate the inference of 1000 tasks by random selection from the dataset. The admissible action space and interaction object space are more complex than the programs in RobotHow. And there is no fixed "[Action] ¡Object¿ (Number)" form of each step. For each article, it contains the title, the bold headlines and text. We utilize the title and headlines as our task name and steps respectively.

External Knowledge Base For the external knowledge base, we utilize ConceptNet to leverage commonsense reasoning ability to help ground language generation in goal-guided procedural text generation. ConceptNet (Speer et al., 2017) captures commonsense knowledge explicitly with triplets of (*head node*, *relation*, *end node*). It contains $799,273$ nodes and $2,487,810$ edges that represent both symmetric and asymmetric relations. Specifically, the core relations we utilized are *Synonym*, *AtLocation*, *CapableOf*, *Causes*, *CausesDesire*, *HasPrerequisite*, *HasSubevent*, and *UsedFor*. Since we are looking at the commonsense knowledge in house-holding tasks, so we filter out the relations (/r/DistinctFrom, /r/DerivedFrom, /r/SymbolOf, /r/EtymologicallyRelatedTo, /r/EtymologicallyDerivedFrom) that are related to the linguistic.

B.2   COUNTERFACTUAL DATASET AND EXPERIMENT DETAILS

Category	Description	Example
Initial Configuration	Constrain the environment configuration, e.g. location	Watch TV in bedroom
Intermediate Step	Constrain the way to finish the task	Work (Find Computer)
Final Goal	Change the final effect of the task by composition	Watch youtube and Put away jackets

Table 6: **Three Types of Counterfactual Procedural Planning.** Three types of methods, including initial configuration, intermediate step, and final goal are applied to intervene the original procedural data.

Table 7 show the examples that compare the original program and the counterfactual program of each intervention method are also provided. Specifically, for **Initial Configuration**, we randomly append the location to a given task name to constrain the location of completing the task. The steps are prepended with the initial step "walk to ¡Location¿". For **Intermediate Step**, we randomly sampled a step from the task-specific program and append it to the task name to constrain the way to implement a given task. For **Final Goal**, we randomly combine two tasks by combining both the task names and the programs to construct a set of long-horizon composite tasks.

We conduct counterfactual experiments by applying randomly selected intervention methods over RobotHow. And we only apply the Intermediate Step intervention method over WikiHow due to the loose configuration requirement and the long text of the WikiHow contents. Note that the performance gain of PLAN under the counterfactual setting mainly comes from the additional guidance of the task introduced from the Intermediate Step intervention method. However, the baselines mostly experience performance drops due to the limited annotated exemplars. PLAN consistently outperforms baselines by a large margin, indicating its superiority under the counterfactual setting.

Category	Original Program	Counterfactual Program
Initial Configuration	Task: Watch TV
Step 1: Find remote control.Step 2: Grab remote control.
Step 3: Find television.Step 4: Switch on television.
Step 5: Turn to television.Step 6: Watch television.
Step 7: Switch off television.
Step 8: Put back remote control	Task: Watch TV in bedroom
Step 1: Walk to bedroom Step 2: Find remote control.
Step 3: Grab remote control.Step 4: Find television.
Step 5: Switch on television.Step 6: Turn to television.
Step 7: Watch television.Step 8: Switch off television.
Step 9: Put back remote control
Intermediate Step	Task: Work
Step 1: Walk to home office.Step 2: Walk to chair.
Step 3: Find chair.Step 4: Sit on chair.
Step 5: Find computer.Step 6: Switch on computer.
Step 7: Turn to computer.Step 8: Look at computer	Task: Work (Find Computer)
Step 1: Walk to home office.Step 2: Walk to chair.
Step 3: Find chair.Step 4: Sit on chair.
Step 5: Find computer.Step 6: Switch on computer.
Step 7: Turn to computer.Step 8: Look at computer
Final Goal	Task1: Turn light off
Step 1: Walk to bedroom Step 2: Walk to light
Step 3: Switch off light
Task2: Clean
Step 1: Walk to home office Step 2: Walk to rag
Step 3: Find rag Step 4: Grab rag
Step 5: Walk to desk Step 6: Find computer
Step 7: Wipe computer Step 8: Wipe desk
Step 9: Put back rag	Task: Turn light off and Clean
Step 1: Walk to bedroom Step 2: Walk to light
Step 3: Switch off light
Step 4: Walk to home office
Step 5: Walk to rag Step 6: Find rag
Step 7: Grab rag Step 8: Walk to desk
Step 9: Find computer Step 10: Wipe computer
Step 11: Wipe desk Step 12: Put back rag

Table 7: **Comparison between Standard and Counterfactual Procedural Planning.** Three types of methods, including initial configuration, intermediate step, and final goal are applied to intervene the original procedural data.

B.3 METHOD DETAILS

Baselines LLMaP propose a procedure to extract temporally extended plans from large pre-trained language models. Chain explores manually creating exemplars that mimic the reasoning process and uses them to prompt large language models for reasoning tasks. To compare with Chain on the procedural planning task, we manually generate exemplars that contain the chain of thought for 1% of the inference task programs. Note that for the BART language model, we use BART-large version. And we use the 1.5 billion parameter GPT-2 (aka gpt2-xl). For the translation model LM_T, we use sentence-transformers (RoBERTa-large). All these models are released by HuggingFace. In addition, our experiments with GPT3 (davinci) use OpenAI API (May, 2022).

External Knowledge Graph Conceptnet5 define a set of 34 relations ([2]). Within the relations we consider in the procedural planning task, the averaged sampling time of subgraph sampling is 0.03576 milliseconds per task program.

B.4 HYPERPARAMETER SEARCH

We perform a hyperparameter search for all evaluated methods. The confidence threshold θ, which terminate the generation when below it, is searched in $\{0, 0.5, 0.55, 0.6, 0.65, 0.7, 0.75, 0.8\}$. The steps horizon, which constrains the maximal number of procedural planning steps, is searched in $\{10, 20, 40\}$. The number of hops for retrieving the subgraph from the external knowledge base is searched in $\{1, 2, 3\}$. The ratio of maximal concepts to the length of the task name is searched in $\{1, 2, 3\}$. The cosine similarity threshold for keeping the task-specific concept is searched in $\{0.4, 0.6, 0.8\}$. The edge weight threshold θ_e is searched in $\{0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8\}$. The top-$k$ task-specific nodes value is searched in $\{1, 5, 10, 15, 20, 25, 50, 100\}$.

The configurations used in the experiments are: θ=0.7, 20 step horizon, 3 hops, 3 ratio of concepts to task length, cosine similarity threshold 0.4, θ_e=0.6 and k=10.

B.5 COMPUTATION AND RESOURCES

We use one single NVIDIA A100 GPU Server for all the experiments. Since there is no training in our zero-shot settings, the computation is only used for the inference stage of the experiments.

---

[2]https://github.com/commonsense/conceptnet5/wiki/Relations

C   Evaluation Details

C.1   Crowdsourcing Human Evaluation

We conduct all the human evaluations (rating and win-lose comparison) on Amazon Mechanical Turk platform. Each example is rated by 3 annotators. We ask Amazon Mechanical Turk workers, for every assignment, to evaluate the quality of the provided low-level steps given the high-level task description. For the **Win-Lose Comparison**, they were asked to choose one from the two provided model generated results by *1:the first one is better*, *2:equal* and *3:the second one is better*. For the **Human Ratings**, they were asked to score each sample with 5-point Likert scale. This process does not involve collecting any personal information. And we manually check no offensive content is produced by the models.

The assignment layout templates for workers are shown in Figure 6 and Figure 5. Specifically, we evaluate randomly selected 50 task examples from each dataset (RobotHow and WikiHow) under all the settings (standard and counterfactual). We only collect the examples that the workers read the instructions carefully by checking whether they give 1 score for the empty program as a sanity check. The hourly wage paid to participants is estimated $9. And the total amount spent on participant compensation is $1296. The details of the Human Intelligence Tasks process are described in the following sections.

C.1.1   Win-Lose Comparison

During the process of Human Intelligence Tasks, the workers are shown the following instructions: *Read the given task and the sequence of steps, determine which set of steps can better complete the target task. In other words, can the task be decomposed into these steps? Please consider the sequential order of the steps.*

Then the program to be evaluated is provided as:

Question Task: Study

Sequence 1:: Step 1: Walk to textbook Step 2: Read book Step 3: Walk to book

Sequence 2:: Step 1: Walk to home office Step 2: Find desk

Finally, the workers are asked to score the program by following the instructions below: *Select an option: 1 - Sequence 1 is better; 2 - Tie; 3 - Sequence 2 is better*

The above example is to evaluate the order metric, for the coverage metric, the same process are conducted, except for the instructions are: *Read the given task and the sequence of steps, and determine which sequence covers more steps that are necessary to complete the target task. Please ignore the sequential order of the steps.*

C.1.2   Human Ratings

Similar as the Win-Lose Comparison Human Intelligence Tasks, the workers are shown the following instructions: *For every question below, determine whether the task can be completed in any reasonable scenario using the provided steps (Please consider the sequential order of the steps.). You could directly give the lowest score (1) for the empty steps. In other words, can the task be decomposed into these steps? (Please consider the sequential order of the steps.)*

Then the program to be evaluated is provided as:

Question Task: Write an email

Sequence of Steps: Step 1: Walk to home office Step 2: Walk to computer Step 3: Find computer Step 4: Turn to computer Step 5: Look at computer Step 6: Walk to computer Step 7: Find chair Step 8: Sit on chair Step 9: Find keyboard Step 10: Grab keyboard Step 11: Find mouse Step 12: Grab mouse Step 13: Type on keyboard

Finally, the workers are asked to score the program by following the instructions below: *Use the slider below to indicate how much you agree with the following statement (1 = Strongly disagree, 5 = Strongly agree). If "sequence of steps" are blank, please directly choose 1 (lowest score). The*

Figure 5: Amazon Mechanical Turk Platform. Questions Layout for Human Raters for Win-Tie-Lose Comparison.

task can be completed in any reasonable scenario using the provided steps. `[SLIDER PROVIDED HERE]`

The above example is to evaluate the order metric, for the coverage metric, the same process is conducted, except for the instructions are: *For every question below, determine whether the task can be completed in any reasonable scenario using the provided steps (Please ignore the sequential order of the steps.). You could directly give the lowest score (1) for the empty steps. In other words, can the task be decomposed into these steps? (Please ignore the sequential order of the steps.)*

C.2 MORE RESULTS

Significance Test   We provide paired-t test (p¡0.05) statistics results for Table 2. On RobotHow, our PLAN significantly outperforms all baselines on Original-Order(BART) and Counterfactual-Coverage(GPT2). On WikiHow, our PLAN significantly outperforms all baselines on Original-Coverage(BART, GPT2), Counterfactual-Coverage(BART, GPT2), and Counterfactual-Order(BART). For the coverage metric under the counterfactual setting, the human-provided program is not significantly better than our PLAN.

Figure 6: Amazon Mechanical Turk Platform. Questions Layout for Human Raters for 5 Point Likert Scale.

Results on GPT-3   In addition, we conduct experiments with GPT-3 (davinci version) using OpenAI API. We showcase the comparison in Table 10.

Model	RobotHow								
	Step Bucket	S-BLEU	WMD	BERT-f1	ROUGE-f1	Coverage	Order	Step Avg.	Time Cost (ms)
BART + Chain (Wei et al., 2022)	(0,10]	0.073	0.915	0.863	0.432	2.947	2.760	6.600	3.330
	(10,20]	0.049	0.909	0.857	0.442	2.921	2.825	13.714	3.820
BART + LLMaP (Huang et al.)	(0,10]	0.076	0.941	0.867	0.450	2.973	2.760	6.600	3.298
	(10,20]	0.028	0.931	0.853	0.393	3.095	2.889	13.714	3.866
BART + PLAN	(0,10]	0.099	0.955	0.894	0.532	3.187	3.013	6.600	3.272
	(10,20]	0.041	0.935	0.869	0.437	3.079	3.206	13.714	4.022
GPT2 + Chain (Wei et al., 2022)	(0,10]	0.076	0.891	0.856	0.395	2.453	2.147	6.600	3.370
	(10,20]	0.057	0.877	0.845	0.359	2.365	2.476	13.714	3.804
GPT2 + LLMaP (Huang et al.)	(0,10]	0.112	0.942	0.894	0.486	3.147	2.987	6.600	3.212
	(10,20]	0.064	0.906	0.859	0.394	2.921	2.73	13.714	3.875
GPT2 + PLAN	(0,10]	0.167	0.940	0.901	0.554	3.173	2.813	6.600	3.344
	(10,20]	0.101	0.924	0.882	0.480	2.984	3.063	13.714	3.954
GPT3 + Chain (Wei et al., 2022)	(0,10]	0.086	0.920	0.878	0.445	3.568	3.459	6.838	3.215
	(10,20]	0.112	0.931	0.884	0.499	3.562	3.469	13.688	3.988
GPT3 + LLMaP (Huang et al.)	(0,10]	0.132	0.951	0.911	0.544	3.811	3.486	6.838	3.144
	(10,20]	0.139	0.939	0.894	0.502	3.531	3.625	13.688	3.964
GPT3 + PLAN	(0,10]	0.171	0.961	0.918	0.574	3.459	3.568	6.838	3.379
	(10,20]	0.167	0.953	0.916	0.578	3.750	3.688	13.688	4.134

Table 8: Evaluation results on the Original RobotHow by separating test set into several Step Bucket.

Model	WikiHow								
	Step Bucket	S-BLEU	WMD	BERT-f1	ROUGE-f1	Coverage	Order	Step Avg.	Time Cost (ms)
BART + Chain (Wei et al., 2022)	(0,10]	0.053	0.919	0.789	0.356	2.969	3.521	6.156	8.233
	(10,20]	0.032	0.921	0.784	0.294	2.644	3.311	14.467	7.349
BART + LLMaP (Huang et al.)	(0,10]	0.068	0.934	0.814	0.353	2.802	3.438	6.156	8.289
	(10,20]	0.032	0.924	0.794	0.293	2.600	3.178	14.467	7.487
BART + PLAN	(0,10]	0.108	0.939	0.834	0.431	3.083	3.594	6.156	8.341
	(10,20]	0.059	0.927	0.812	0.372	2.978	3.244	14.467	7.829
GPT3 + Chain (Wei et al., 2022)	(0,10]	0.107	0.928	0.817	0.353	3.031	3.438	6.156	8.367
	(10,20]	0.077	0.933	0.812	0.328	2.733	3.422	14.467	7.585
GPT3 + LLMaP (Huang et al.)	(0,10]	0.111	0.946	0.831	0.36	3.292	3.625	6.156	8.218
	(10,20]	0.066	0.955	0.829	0.342	2.978	3.378	14.467	7.583
GPT3 + PLAN	(0,10]	0.136	0.961	0.856	0.416	3.645	4.0	6.677	8.213
	(10,20]	0.127	0.961	0.868	0.458	3.68	3.2	13.6	7.632
GPT3 + Chain (Wei et al., 2022)	(0,10]	0.123	0.954	0.837	0.432	3.655	3.517	6.0	8.424
	(10,20]	0.121	0.949	0.856	0.465	3.421	3.684	15.526	7.775
GPT3 + LLMaP (Huang et al.)	(0,10]	0.146	0.956	0.865	0.514	3.652	3.739	6.565	7.953
	(10,20]	0.099	0.951	0.849	0.452	3.375	3.312	15.0	7.247
GPT3 + PLAN	(0,10]	0.203	0.969	0.861	0.506	3.31	3.643	5.81	8.101
	(10,20]	0.185	0.967	0.855	0.466	3.714	3.333	15.095	7.506

Table 9: Evaluation results on the Original WikiHow by separating test set into several Step Bucket.

D QUALITATIVE EXAMPLES

More qualitative examples that are randomly selected are provided. Table 11 show random samples on the original dataset. Table 12 show random samples on the counterfactual datasets with the Intermediate Step intervention method. And Table 13 shows random samples on the counterfactual RobotHow with the Initial Configuration and Final Goal intervention methods.

Model	Program
	RobotHow Task: Write an Email
Human	Step 1: Walk to home office. Step 2: Walk to computer. Step 3: Find computer. Step 4: Turn to computer. Step 5: Look at computer. Step 6: Walk to computer. Step 7: Find chair. Step 8: Sit on chair. Step 9: Find keyboard. Step 10: Grab keyboard. Step 11: Find mouse. Step 12: Grab mouse. Step 13: Type on keyboard
LLMaP	Step 1: Switch on computer.
PLAN	Step 1: point at mail. Step 2: put envelope on printer.Step 3: put notes on printer.
	WikiHow Task: How to Become an Art Investor
Human	Step 1: Start with some experience or interest in art. Step 2: Understand the difference between art collectors, art investors and art speculators. Step 3: Figure out what you are willing to pay for art, before going to an auction house. Step 4: Pay attention to what schools of art are selling well, and which are down. Step 5: Focus art investments on fine art paintings, rather than decorative art. Step 6: Reach out to trusted auction houses and dealers when you are looking to buy art. Step 7: Buy your investment art when you feel confident of its worth, its price and its ability to grow in value. Step 8: Study how art is properly stored. Step 9: Have your art investments appraised occasionally.Step 10: Consider renting out your art investments. Step 11: Understand that selling an art investment can take time.
LLMaP	Step 1: Reach out to trusted auction houses and dealers when you are looking to buy art.
PLAN	Step 1: figure out what you are willing to pay for art, before going to an auction house. Step 2: consider renting out your art investments. Step 3: buy your investment art when you feel confident of its worth, its price and its ability to grow in value.

Table 10: Showcases of procedural steps predicted by different models with GPT3 as the base LLM.

Model	Program
	RobotHow Task: Play Games
Human	Step 1: Walk to bedroom.Step 2: Walk to video game console.
Step 3: Find video game console.Step 4: Walk to video game console.
Step 5: Switch on video game console.Step 6: Find television.
Step 7: Switch on television.Step 8: Find video game controller.
Step 9: Grab video game controller.Step 10: Find chair.
Step 11: Walk to chair.Step 12: Sit on chair
Chain	Step 1: Put chef knife on water glass.Step 2: Find sink.
LLMaP	Step 1: Walk to bedroom.Step 2: Walk to video game console.
Step 3: Find video game console
PLAN	Step 1: Walk to video game controller.Step 2: Find video game controller.
Step 3: Switch on video game controller.Step 4: Find tv.Step 5: Switch on tv.
	WikiHow Task: How to Be an Organized Artist
Human	Step 1: Keep related supplies in the same area.,.
Step 2: Make an effort to clean a dedicated workspace after every session.,.
Step 3: Place loose supplies in large, clearly visible containers.,.
Step 4: Use clotheslines and clips to hang sketches, photos, and reference material.,.
Step 5: Use every inch of the room for storage, especially vertical space.,.
Step 6: Use chalkboard paint to make space for drafting ideas right on the walls.,.
Step 7: Purchase a label maker to make your organization strategy semi-permanent.,.
Step 8: Make a habit of throwing out old, excess, or useless stuff each month.
Chain	Step 1: Feel for a dense, kinky coat.
Step 2: Look for rounded ears with crimped inner hairs.
LLMaP	Step 1: Make sure that all money has been covered on both end.
Step 2: Check your bill and banking statements regularly.to ensure that your bills are
getting paid as they should be, you should check all statements that you receive.
Step 3: Keep track of your expenses.Step 4: Keep track of your income.
PLAN	Step 1: Prioritize your goals for the workshop.Step 2: Prepare to create your neopoprealist mural.
Step 3: Organize your computer-based materials.Step 4: Have a clear plan.
Step 5: Work on being the best you.
Step 6: Paint patterns with brushes of suitable size for the particular portion of work you are painting.
Step 7: Put together a schedule and chart.
Step 8: Buy your investment art when you feel confident of its worth, its price and its ability to grow
in value.
Step 9: Make a clean brea.
Step 10: First, you will need to make sure you have all of the materials listed below.
	WikiHow Task: How to Use Saddle Soap
Human	Step 1: Read the manufacturer's directions., Step 2: Avoid lye heavy products.,
Step 3: Make your own saddle soap.
Chain	Step 1: Give her a safe space.Step 2: Let him exercise.
Step 3: Be kind to him.Step 4: Offer him a treat.
LLMaP	Step 1: Dip a damp cloth in the saddle soap.
Step 2: Dampen several cloths and work them into a lather with the saddle soap.
Step 3: Dip a cloth into the mixture.Step 4: Rub the product on with a cloth.
Step 5: Clean the grime off with the cloth.Step 6: Dampen a cloth with water.
Step 7: Rub a damp microfiber cloth over the surface.Step 8: Use a damp cloth to wipe once again.
Step 9: Dampen a towel with lukewarm water.Step 10: Wipe the area clean with a damp towel.
Step 11: Soak a towel in warm water.
PLAN	Step 1: Brush your horse.Step 2: Clean the saddle.
Step 3: Start by using the first cloth to rub down the leather, making sure you remove any built
up grass and dirt.
Step 4: Rub the leather down so you remove most of the oil and wax.
Step 5: Wipe off excess oil.Step 6: Rinse the leather.
Step 7: Clean any other leather tack items (martingale, breastplate, draw reins, cruppers, etc.

Table 11: Showcases of procedural steps predicted by different models with GPT2 as the base LLM.

Model	Program
	RobotHow Intermediate Step
Turking (Find computer.).
Human	Step 1: Walk to home office.
Step 2: Walk to desk.
Step 3: Find chair.
Step 4: Sit on chair.
Step 5: Find computer.
Step 6: Switch on computer
Chain	Step 1: Switch on computer.
Step 2: Switch off computer.
LLMaP	Step 1: find computer.
PLAN	Step 1: Walk to chair.
Step 2: Turn to computer.
Step 3: Look at computer.
Step 4: Switch off computer.
Step 5: Switch on computer.
	WikiHow Intermediate Step
Task: How to Become an Art Investor (Figure out what you are willing to pay for art, before going to an auction house.).
Human	Step 1: Start with some experience or interest in art.,.
Step 2: Understand the difference between art collectors, art investors and art speculators.,.
Step 3: Figure out what you are willing to pay for art, before going to an auction house.,.
Step 4: Pay attention to what schools of art are selling well, and which are down.,.
Step 5: Focus art investments on fine art paintings, rather than decorative art.,.
Step 6: Reach out to trusted auction houses and dealers when you are looking to buy art.,.
Step 7: Buy your investment art when you feel confident of its worth, its price and its ability to grow in value.,.
Step 8: Study how art is properly stored.,.
Step 9: Have your art investments appraised occasionally.,.
Step 10: Consider renting out your art investments.,.
Step 11: Understand that selling an art investment can take time.
Chain	Step 1: See art being sold directly by artists by clicking on the "direct from the artist" link.
Step 2: Look at the price.
Step 3: Look at the writer's website.
Step 4: Create a portfolio of your work.
Step 5: Look at price again.
LLMaP	Step 1: Create a sketch in the neopoprealist manner of the future mural on a small piece of paper 8"x10" using the black ink pen.
Step 2: Prepare to create your neopoprealist mural.
Step 3: Prepare your paint.
Step 4: Begin your project with a design.
Step 5: Produce a scaled down version of your finished mural.
Step 6: Prepare the wall to be painted.
Step 7: Allow the background and base coats to dry.
Step 8: Draw the lines, then fill the appeared section with different repetitive patterns (examine the images above).
Step 9: Paint patterns with brushes of suitable size for the particular portion of work you are painting.
Step 10: Clean up the lines and shapes as needed.
Step 11: Seal the mural if needed.
Step 12: Be inspired and it will help you succee.
Step 13: This is where you get to be the most creative.
PLAN	Step 1: Figure out what you are willing to pay for art, before going to an auction house.
Step 2: Sell your art online.
Step 3: Go to the auction house.
Step 4: Buy it.
Step 5: Install the first floor.,repeat steps 1-4 to add more floor.
Step 6: Enter in the second round values.
Step 7: Get the 3-carat diamond.
Step 8: Know the four cs of diamonds.
Step 9: Find a reputable diamond appraiser in your area.

Table 12: Showcases of procedural steps predicted by different models with GPT2 as the base LLM under counterfactual setting (Intermediate Step).

Model	Program
	RobotHow Initial Configuration
Task: Play games in dining room.
Human	Step 1: Walk to dining room.Step 2: Walk to video game console.
Step 3: Find video game console.Step 4: Walk to video game console.
Step 5: Switch on video game console.Step 6: Find television.
Step 7: Switch on television.Step 8: Find video game controller.
Step 9: Grab video game controller.Step 10: Find chair.
Step 11: Walk to chair.Step 12: Sit on chairTask: Play games in dining room.
Step 1: Walk to video game controller.Step 2: Put video game controller on diningtable.
Step 3: Put boardgame on kitchen table.Step 4: Put boardgame on diningtable.
Chain	Step 1: Walk to dining room.Step 2: Walk to sauce pan.
Step 3: Pour bottle water into dish bowl.Step 4: Walk to water.
Step 5: Walk to carrot.Step 6: Walk to food salt.
LLMaP	Step 1: Walk to kitchen.Step 2: Walk to food food.Step 3: Walk to dining room.
PLAN	Step 1: walk to dining room.Step 2: find diningtable.Step 3: walk to board game.
Step 4: put video game controller on diningtable.Step 5: put food snack on diningtable.
Step 6: put board game on diningtable.
Step 7: put boardgame on diningtable.Step 8: put board game on kitchen table.
Step 9: find video game console.Step 10: put glass on board game.
Step 11: grab video game controller.Step 12: put glass on boardgame.
	RobotHow Final Goal
Task: Turn light off and clean
Human	Step 1: Walk to bedroom.Step 2: Walk to light.Step 3: Switch off light.
Step 1: Walk to home office.Step 2: Walk to rag.Step 3: Find rag.
Step 4: Grab rag.Step 5: Walk to desk.Step 6: Find computer.
Step 7: Wipe computer.Step 8: Wipe desk.Step 9: Put back rag.
Chain	Step 1: Walk to kitchen.Step 2: Walk to cooking pot.Step 3: Walk to water.
Step 4: Walk to dishwasher.
LLMaP	Step 1: Put light bulb on bowl.Step 2: Switch off light bulb.Step 3: Switch on light.
PLAN	Step 1: plug out lighting.Step 2: put cleaning solution on desk.
Step 3: find dish soap.Step 4: scrub light switch.
Step 5: wipe lighting.

Table 13: Showcases of procedural steps predicted by different models with GPT2 as the base LLM under counterfactual setting (Initial Configuration, Final Goal).

E DISCUSSION

E.1 LIMITATIONS

Though pointing out a direction to prompt out actionable knowledge in large-scale pre-trained language models with external commonsense knowledge, the limitations of reasoning long-horizon procedural plan still exist. Existing datasets for procedural planning like WikiHow and RobotHow are all monolingual supporting only English goals and plans. In the future, it is important to expand these datasets or having novel datasets that support multiple languages used across the world. The inherent difference between these languages may also result in different planning strategies in granularity or abstraction levels, which is potentially challenging. In addition, the long-horizon and complex composite tasks still remain challenging for the existing procedural planners.

E.2 ETHICAL CONSIDERATIONS

We hope to debias the procedural planning to avoid misleading either humans or robots with daily life instructions, which may result in unsafe situations. The cultural bias behind these datasets can be a critical issue for future work. As the ground truth planning steps usually reflect the culture shared by the English-speaking group, other cultures may have a completely different practical consideration that leads to different orders of these steps or even novel steps that are failed to be proposed by the LLMs we utilized in this paper. In the future, we will consider the cultural bias as a proxy variable so that we could adjust the implicit knowledge from LLM or commonsense from external sources according to different needs of cultural backgrounds.