A Picture is Worth A Thousand Numbers:
Enabling LLMs Reason about Time Series via Visualization

Abstract

Large language models (LLMs), with demonstrated reasoning abilities across multiple domains, are largely underexplored for time-series reasoning (TsR), which is ubiquitous in the real world. In this work, we propose `TimerBed`, the first comprehensive testbed for evaluating LLMs' TsR performances. Specifically, `TimerBed` includes stratified reasoning patterns with real-world tasks, comprehensive combinations of LLMs and reasoning strategies, and various supervised models as comparison anchors. We conduct extensive experiments with `TimerBed` and verify the initial failures of LLMs in TsR, evidenced by the ineffectiveness of zero shot (ZST) and performance degradation of few-shot in-context learning (ICL). Further, we identify one possible root cause: the numerical modeling of data. To address this, we propose a prompt-based solution, `VL-Time`, using visualization-modeled data and language-guided reasoning. Experimental results demonstrate that `VL-Time` enables multimodal LLMs to be effective ZST and powerful ICL reasoners for time series, achieving up to a 400% relative improvement in performance and 99% reduction in token costs.

1 Introduction

With the recent surge in large language models (LLMs), their reasoning abilities have exhibited powerful performance with unique interpretability across multiple domains, including logic, mathematics, and symbolic reasoning (Wei et al., 2022; Kojima et al., 2022; Achiam et al., 2023; Dubey et al., 2024; Yang et al., 2024). As a type of data widely present in the real world, time series records the dynamic evolution of data over time. Time-series reasoning (TsR) has extensive real-world applications, such as pathological diagnosis (Dingwell and Cusumano, 2000), marine biological monitoring (Baumgartner and Mussoline, 2011), and human activity recognition (Yang et al., 2015). There-fore, in this paper, we aim to **explore the question: "Can LLMs handle time-series reasoning? If not, how to enable them?"**

However, this question remains largely underexplored. The **first key obstacle is "How to effectively evaluate LLMs' TsR abilities?"**. Existing works face limitations at every component:

(1) Task and Data. (a) Unstructured task design: Existing TsR evaluations (Merrill et al., 2024; Chow et al., 2024) simply mix multiple tasks without any taxonomy for reasoning patterns, making it challenging to understand LLMs' TsR limitations. (b) Synthetic data. Due to the challenges of curating suitable datasets, existing TsR works (Merrill et al., 2024) use synthetic data, failing to effectively reflect real-world validity.

(2) LLMs and Prompts: (a) Outdated LLMs: Evaluations (Merrill et al., 2024), still using Llama of March 2023, have limited reference value for current research due to the rapid development of LLMs. (b) Prompt selection: Current TsR evaluations (Merrill et al., 2024; Chow et al., 2024) only adopt zero-shot prompting to assess LLMs for TsR, which fails to reveal their actual effectiveness.

(3) Comparison Anchors: Existing TsR works either lack comparison anchors (Chow et al., 2024), only comparing different LLMs, thus failing to quantify success, or adopt human-level performance as a reference (Merrill et al., 2024), which is costly and difficult to scale to other datasets.

To address these issues, we propose `TimerBed`, the first comprehensive test**Bed** for evaluating LLMs **r**easoning about **Time** series. Using `TimerBed`, we conduct extensive experiments to assess LLMs' TsR effectiveness, test several current beliefs about LLMs, and discuss possible causes of their failures in TsR. Inspired by these insights, we further propose a prompt-based solution called `VL-Time`, which uses visualization to model data and language to guide reasoning, thereby unlocking multimodal LLMs' abilities for TsR. Our main

contributions are summarized as follows:

- We propose `TimerBed`, the first comprehensive testbed for evaluating LLMs for TsR. `TimerBed` introduces stratified reasoning patterns with curated real-world tasks, comprehensive combinations of advanced LLMs and reasoning strategies, and comparison anchors using diverse supervised models.
- We conduct extensive evaluations with `TimerBed` to provide insights and identify a root cause of LLMs' initial failures in TsR: the directly numerical modeling of data.
- We propose a prompt-based solution, named `VL-Time`, to address this issue for multimodal LLMs, using visualization-modeled data and language-guided reasoning.
- Experimental results show that `VL-Time` enables multimodal LLMs as effective zero-shot and powerful few-shot reasoners for time series. Specifically, `VL-Time` requires fewer than six samples per class to consistently outperform all supervised methods in deterministic reasonings and half of them in probabilistic reasonings. Compared to directly numerical modeling, `VL-Time` achieves an **average improvement of 140%, up to 433%**, only requiring **about 0.9% of the token cost**.

`TimerBed` is now anonymously available[1]. Additional related works are in Appendix A and limitations are in Section 8

2 Testbed for LLMs Reasoning about Time Series

As discussed in Section 1, existing evaluation efforts have limitations at every component of benchmarking. To address the question of *"How to evaluate and understand the actual TsR capabilities of LLMs?"*, we present **`TimerBed`**, a testbed for evaluating LLM reasoning time series, as shown in Figure 1. We further detail `TimerBed`'s components by reasoning patterns with tasks, LLMs and reasoning strategies, and comparison anchors.

2.1 Stratified Reasoning Patterns with Curated Real-world Tasks

Inspired by the classic reasoning problem taxonomy(Jaeger, 1994; Dechter, 2022), we stratify TsR tasks into three patterns of increasing difficulty: simple deterministic reasoning, complex determin-

istic reasoning, and probabilistic reasoning. Specifically, "Simple" and "Complex" are defined based on whether multiple factors need to be integrated for reasoning. "Deterministic" and "Probabilistic" are based on whether the relationship between input and output is deterministic. We practically distinguish them by the method of data annotation, i.e., whether labeled by human experts or directly derived from data. The former ensures a definite reasoning path from the input data to the answer, whereas the latter involves potential instability, such as the influence of unobserved variables. To the best of our knowledge, this is the first stratified evaluation framework for LLMs's TsR capability, supporting a progressive analysis.

We further aligned two real-world tasks with each pattern for an effective evaluation. Following existing works on benchmarking LLMs' reasoning abilities(Kojima et al., 2022; Wei et al., 2022; Sprague et al., 2024), we standardized the organization of datasets in a classification task format. These datasets cover multiple domains (biology, healthcare, electricity, physics, and nature), various task types (binary and multi-class classification, fine-grained and coarse-grained classification), and multiple data types (univariate and multivariate, varying size, precision, value ranges and sequence lengths), thus enable a comprehensive evaluation. Moreover, we curate the corresponding informative textual information, including descriptions of tasks, data and labels, which are crucial for LLMs to perform reasoning tasks. Details for each reasoning pattern and corresponding tasks are as follows:

Simple Deterministic Reasoning. This pattern is relatively simple due to the one-to-one correspondence between the features and the class. We introduce two real-world tasks: north atlantic Right Whale Calls detection (RCW)[2] and Transient Electromagnetic Event classification (TEE)[3]. In both datasets, each class is clearly defined by a feature, and the labels are annotated by humans based on input variables, guaranteeing simple deterministic reasoning. The details are as follows:

The RCW task contains audio recordings used to identify right whale calls amidst oceanic environmental noise. In this task, a short, rising "whoop" sound serves as both a necessary and sufficient con-

---

Figure 1: Overview of the proposed `TimerBed`. `TimerBed` designs three patterns of TsR tasks of increasing difficulty: simple or complex deterministic reasoning and probabilistic reasoning. For each reasoning pattern, `TimerBed` matches two real-world tasks and presents an example in the figure. `TimerBed` covers 4 types of LLMs with the corresponding most advanced models and three reasoning strategies for comprehensive evaluation. `TimerBed` adopts 8 supervised time-series models and random guessing as anchors to quantify the success of LLMs for TsR.

dition for identifying a right whale call. The TEE task is sourced from the FORTE satellite, which employs optical and radio frequency instruments to detect transient electromagnetic events associated with lightning. Each event type corresponds to a specific physical phenomenon. For example, the "CG Positive" event type is characterized by a positive charge discharge from cloud to ground, manifested in the power density time series as a distinct radiation spike followed by several hundred microseconds of noise.

Complex Deterministic Reasoning. This pattern is more difficult due to the many-to-one relationship between features and classes. We introduce two real-world tasks: Electrocardiogram (ECG) Record Diagnosis and Electromyogram (EMG) Signal Diagnosis. These tasks originate from medical scenarios, where the labels are annotated by doctors via integrating multiple features from time-series signals, ensuring both complexity and determinism. The details are as follows:

The ECG task[4] contains single-lead ECG recordings that measure four different cardiac arrhyth-

mias: normal sinus rhythm, atrial fibrillation, other alternative rhythms, and unclassifiable conditions due to excessive noise. Each category requires integrating multiple factors for inference. For example, the "atrial fibrillation" category is characterized by four known features: irregular RR intervals, absence of P waves, presence of f waves, and baseline fluctuations. The EMG task[5] comprises recordings of muscle responses to neural stimulation, used for diagnosing muscular dystrophies and neuropathies. Specifically, it includes single-channel EMG recordings classified into three types: healthy, neuropathy, and myopathy. This task also requires comprehensive assessment. For instance, the neuropathy category displays three known characteristic features: fibrillations and positive sharp waves, high-amplitude and long-duration motor unit action potentials, and polyphasic waveforms.

Probabilistic Reasoning Probabilistic reasoning is challenging due to the unstable relationship from features and classes, but common in real-world applications(Liu et al., 2021; Zhang et al., 2022). We introduce two real-world tasks: Human Activity Recognition (HAR) and Computer Type Usage

---

[4]https://physionet.org/content/challenge-2017/1.0.0/

[5]https://physionet.org/content/emgdb/1.0.0/

classification (CTU). The probabilistic reasoning is ensured by: (1) labels collected automatically; (2) data gathered from multiple users, whose behavioral habits significantly impact the results but remain unobserved. Details are as follows:

The HAR task [6] uses wearable sensors on a smartphone to record six daily activities: walking, walking upstairs, walking downstairs, sitting, standing, and lying down. We utilize the three channels representing body linear accelerations. This dataset was collected from 30 users, whose individual behavior characteristics are crucial for reasoning but remain unobserved. The CTU task[7] aims to infer computer types (desktop or laptop) based on consumer behavior in 24-hour electricity usage. This dataset was collected from 251 users, whose individual behavior characteristics are also crucial for reasoning but remain unobserved.

More details of datasets are in Appendix C.

2.2 Comprehensive Combination of LLMs and Reasoning Strategies

Considering the rapid development of LLMs, TimerBed explores a comprehensive evaluation by combining various types of LLMs and reasoning strategies. Specifically, TimerBed covers four types of LLMs, including open-source unimodal models with the corresponding advanced LLMs: Qwen2.5-72B[8] for open-source unimodal LLMs, Qwen2-VL-72B[9] for open-source multimodal LLMs, GPT-4[10] for closed-source unimodal models, and GPT-4o[11] for closed-source multimodal LLMs. The open-source or closed-source nature determines development methods, while unimodal or multimodal models affect their adaptations to the underexplored time-series modality. For reasoning strategies, we consider three widely used approaches: zero shot (ZST) (Kojima et al., 2022), zero-shot chain of thought (CoT) (Wei et al., 2022), and few-shot in-context learning (ICL) (Brown et al., 2020).

2.3 Anchors for Quantifying Success

Considering the differences in reasoning patterns and task difficulty, it is necessary to use anchors to

---

[6] https://archive.ics.uci.edu/dataset/240/human+activity+recognition+using+smartphones
[7] https://www.timeseriesclassification.com/description.php?Dataset=Computers
[8] https://qwenlm.github.io/blog/qwen2.5/
[9] https://github.com/QwenLM/Qwen-VL
[10] https://openai.com/index/gpt-4/
[11] https://platform.openai.com/docs/models

---

quantify the success of LLMs. We include random guessing and nine supervised time-series models as basic and strong anchors, respectively. Specifically, the supervised time-series models cover both time and frequency domain with three main architectures including transformer-based, CNN-based, and MLP-based, detailed in Appendix F.

Figure 2: Normalized Results of Zero-shot Time-series Reasoning. The accuracy is normalized by random guessing. Detailed original results are in Table 3. LLMs consistently show near-random performance with ZST.

Figure 3: Normalized Results of Chain-of-Thought and Few-shot In-Context-Learning Time-series Reasoning. The accuracy is normalized by random guessing. Detailed original results are in Table 3. CoT shows marginal improvement and ICL brings degradation.

3 Evaluations and Insights

3.1 Evaluation Setups

We model time-series data as numerical series to feed into LLMs, following existing works of prompting LLMs for time-series analysis (Xue and Salim, 2023; Gruver et al., 2024; Liu et al., 2024a; Dong et al., 2024). We applied format instructions, including mandatory descriptions of tasks, data, and options, as well as optional instructions, such as CoT's "Please solve this problem step by step." For ICL strategies that require context, we randomly sampled examples from the original training

set to construct the demo set and selected the number of demos per category from [1, 2, 3, 4, 5] as a standard few-shot setting following Jiang et al.. Details of prompts are in Appendix D. We empirically set the temperature of LLMs to 0 to ensure reproducibility. Accuracy is used as the evaluation metric, where a higher value indicates better performance. We run each setting three times and report the average. More details are in Appendix E

3.2 Results and Insights

We conduct evaluations with `TimerBed` with the aforementioned setups to answer the question: ***"What is the effectiveness of LLMs for TsR under different reasoning patterns and strategies?"*** We have the following observations:

Different Reasoning Patterns: Usually Near-Random Performance with ZST. We visualize ZST results in Figure 2, normalized by random guessing's accuracy. Detailed original results are in Table 3. We observe that for all LLMs, their ZST performances across different reasoning patterns are Ineffective, usually close to or sometimes worse than random guessing. This finding contradicts the prevailing conclusion that LLMs are general effective ZST reasoners (Kojima et al., 2022), especially with informative instructions for LLMs.

Different Reasoning Strategies: CoT > ZST > ICL. We visualize the results under different reasoning strategies in Figure 3, normalized by the performance of random guessing. Detailed original results are in Table 3.

Across LLMs, we find that CoT consistently outperforms ZST for TsR, validating the rationality of our reasoning tasks, which is consistent with the prevailing conclusion that CoT is primarily effective for reasoning tasks(Sprague et al., 2024).

However, the few-shot ICL strategy for TsR often results in performance degradation, which contradicts the prevailing conclusion that LLMs' performance can generally benefit from few-shot ICL(Brown et al., 2020).

Additionally, we observe that multimodal LLMs generally performed worse than unimodal LLMs, consistent with the existing conclusion about potential degradation of language capabilities in multimodal LLMs(Lu et al., 2024).

4 Anomalies Analysis

Further, we attempt to answer ***"What causes the failures of LLMs for TsR?"***. Focusing on the two aforementioned anomalies, we verify that a primary root cause is the numerical modeling for time-series data of existing works (Xue and Salim, 2023; Gruver et al., 2024; Liu et al., 2024a; Dong et al., 2024), detailed as follows:

Numerical Modeled Data → Difficulty of Feature Extraction → Ineffectiveness of ZST. We begin by checking the feature extraction plans of LLMs. Via prompts, we present verbalized feature extraction plan of every LLM for different TsR tasks in Appendix G. We notice that these plans are similar to each other and, in most cases, are reasonable. This indicates that LLMs possess at least some effective domain knowledge for zero-shot TsR. However, we also notice that most of these planned features are difficult to extract from numerical time series, which can be categorized into the following four types:

(1) Pictorial Features: For example, features like "mitral valve shape" for the ECG task or "paired appearance" for the TEE task are challenging because numerical time series are too specific.

(2) Time-Related Features: Examples include the "0.12 to 0.20 seconds PR interval" for the ECG task and the "noise persisting for several hundred microseconds" for the TEE task. Numerical time series data naturally lose aligned time stamps, and their lengths, frequently exceeding 1000 steps, further hinder LLMs from accurately tracking time.

(3) Cross-Dimension Features: For example, "simultaneous changes in X, Y, and Z-axis accelerations" for the HAR task. Numerical time series, which involves concatenating multiple variable series, naturally loses temporal alignment, thus hindering the extraction of cross-dimension features.

(4) Frequency-Domain Features: Such as the "rising trend in frequency" for the RCW task, visualized in Figure 9. Numerical series need transformations like Fast Fourier Transform(Brigham, 1988) to expose frequency-domain features, which LLMs cannot handle implicitly.

Numerical Modeled Data → Excessive Length of Context → Performance Degradation in ICL. The tokenization of LLMs is not optimized for numerical series, leading to an excessive context length. Specifically, one time-series sample typically consists of hundreds of time steps, where each time step (a numerical value) often requires more than 12 tokens. Token cost for each dataset is detailed in Table 5. For example, in the RCW dataset, one time-series sample requires up to 60K input

Figure 4: Comparison of existing numerical modeling solution, denoted as "Traditional Solution", and proposed `VL-Time` for prompting LLM reasoning about time series. The key difference is that `VL-Time` replaces numerical modeling with visualization modeling for time-series data, which enhances feature perception and reduce context length. `VL-Time` further adopts a two-stage framework with planning then solving.

tokens using GPT-4o. This inefficient tokenization further leads to the performance degradation in ICL due to: (1) Long Context Handling Difficulty. With multiple examples included in the context, ICL significantly increasing token length and the difficulty for LLMs' understanding(Liu et al., 2024b). (2) Limited Examples Coverage: The number of time-series examples that can be included in the context is quite limited. For instance, in the RCW dataset, even with a powerful 128K context length of LLMs, only one example can be included, while there are two classes. This leads to biased information and harms performances.

5 Proposed Solution

This section aims to answer the question: *"How to address the original failure of LLMs in TsR?"* by focusing on the two anomalies mentioned above.

High-Level Idea. Our high-level idea is to **replace existing numerical modeling with visualization-based modeling** of time-series data. The rationale for why visualization is key to addressing the feature extraction and context length issues is as follows:

(1) Visualization empowers feature extraction. First, visualization naturally reveals pictorial features. Second, visualization can directly reflect time-related features by indicating time stamps using axis indices. Additionally, visualization naturally aligns different variables and uses color and legends to annotate them, thus clearly denoting cross-dimension features. Finally, frequency-domain features can be effectively represented through frequency-domain visualization.

(2) Visualization is compressive. Compared to numerical modeling, where token usage is proportional to the data precision and sequence length, visualization serves as an effective compression method. By adjusting the image size, visualization can effectively control token count while largely preserving information. For example, on the RCW task, a time-series sample using numerical modeling requires 60,000 tokens, while visual modeling only requires 85 tokens, based on GPT-4o.

Framework and Details Shown in Figure 4, we propose a prompt-based solution, named **VL-Time**, which empower arbitrary multimodal LLMs to reason **Time** series by data modeling via **V**isualization and task reasoning guided by **L**anguage. Specifically, **VL-Time** follows a 'plan-then-solve' framework (Wang et al., 2023), split into two stages to prompt multimodal LLMs for TsR.

1st Stage: Planning. In the first dialogue, VL-Time prompts LLMs makes two key decisions based on the task description: (a) choosing between time-domain or frequency-domain visualization, and (b) proposing the planned features. To ensure effective feature extraction, our visualization designs include time stamps on the x-axis, semantic labels on the y-axis, and different colors and textual legends for each variable or frequency. Figure 10 and 9 show examples of our visualization. Please note that for each task, the planning stage only needs to be run once, while shared across samples.

2nd Stage: Solving. The second dialogue uses format instructions to prompt multimodal LLMs for completing TsR. Here, the "Image", which is the visualization of time-series data, and the hints, which guide attention for feature perception, come from the first planning stage.

6 Experiments

This section aims to answer the question:*"How well can* `VL-Time` *unlock multimodal LLMs' reasoning ability for time series?"*

Table:

Reasoning Pattern		Simple Deterministic		Complex Deterministic		Probabilistic	
Reasoning Task (6)		RCW	TEE	ECG	EMG	CTU	HAR
Metric		ACC(%)	ACC(%)	ACC(%)	ACC(%)	ACC(%)	ACC(%)
Random Guessing		50.00	14.29	25.00	33.33	50.00	16.67
Supervised Time-series Models (8)	Transformer	64.12	59.52	25.00	86.67	59.20	87.26
	Autoformer	62.59	26.19	23.95	46.67	**67.20**	75.04
	Informer	75.51	59.52	22.39	66.66	**67.20**	85.83
	FEDformer	76.59	42.86	26.40	73.33	51.60	**89.88**
	PatchTST	82.11	57.14	24.82	60.00	64.00	79.60
	iTransformer	76.92	21.43	24.48	46.67	46.40	89.49
	TimesNet	80.23	61.90	26.20	73.33	64.00	88.65
	Dlinear	56.96	47.63	23.61	46.67	52.40	48.97
Zero-shot LLMs	GPT-4o (numeric)	50.00	21.43	25.00	33.33	45.45	29.17
	GPT-4o (VL-Time)	70.02	24.88	26.33	33.33	50.71	37.50
	Improvement	+40.04%	+16.10%	+5.32 %	+0.00%	+11.57%	+28.56%
	Win Supervised	3/8	1/8	7/8	0/8	1/8	0/8
Few-shot ICL LLMs	GPT-4o (numeric)	50.00	35.71	31.25	33.33	50.00	12.50
	GPT-4o (VL-Time)	**91.03**	**64.29**	**43.75**	**91.67**	63.64	66.67
	Improvement	+82.06%	+80.03%	+40.00%	+175.04%	+27.28%	+433.36%
	Win Supervised	8/8	8/8	8/8	8/8	4/8	4/8

Table 1: Performance comparison on `TimerBed`: (1) `VL-Time` enables GPT-4o to perform effective zero-shot TsR, with up to 40% relative improvement and consistently outperforming random guessing on 6/6 tasks. (2) `VL-Time` enables GPT-4o to achieve powerful few-shot TsR, with up to 433% relative improvements, surprisingly surpassing 8/8 supervised models in simple and complex deterministic TsR, and matching their performances in probabilistic TsR. Here, few-shot refers to less than six examples per class. We bold the best result for each task.

6.1 Performance Comparison

We conduct experiments using `TimerBed`, following the same experimental setup as in Section 3.2. We use GPT-4o as the representative by default, with other LLMs in Section 6.3. To avoid confusion, we use GPT-4o (numeric) to denote existing numerical modeling solution evaluated in Section 3.2. We use the low resolution option of GPT-4o API. For supervised models, we retained each dataset's original train-test split or used an 8:2 split of the original training set when the test set lacked available labels. As shown in Table 1, we make the following observations:

`VL-Time` enables multimodal LLMs as effective zero-shot time-series reasoners. First, `VL-Time` significantly improves GPT-4o's performance by an average of 17% and up to 40%. Additionally, `VL-Time` allows GPT-4o to surpass random guessing on all 6/6 tasks and outperform part of supervised models on 4/6 tasks. Compared to GPT-4o (numeric)'s random-level performance, `VL-Time` achieves a breakthrough for zero-shot TsR.

`VL-Time` enables multimodal LLMs as powerful few-shot in-context time-series reasoners. First, `VL-Time` boosts GPT-4o's performance by an impressive average of 140% and up to 433%. Besides, `VL-Time` enables GPT-4o to outperform all supervised time-series models on 4/4 tasks with simple and complex deterministic reasoning patterns. Moreover, `VL-Time` even matches the performance of supervised models (surpassing half of them) on 2/2 tasks with probabilistic reasoning patterns. Recall that probabilistic reasoning demands more data to capture uncertainty. However, `VL-Time` remarkably enables multimodal LLMs to achieve strong performance with fewer than six examples per class, demonstrating unique data efficiency.

Cost Comparison. `VL-Time` introduces no additional training cost, only requires running the planning stage once per task, and maintains the same output format as traditional prompts. The cost difference mainly comes from the modeling approach: visual modeling in `VL-Time` and numerical modeling in traditional prompts. Thus, we present the input token cost and count per sample in Table 4 and 5, with "gpt-4o-2024-08-06" endpoint. Results show that `VL-Time` significantly reduces token count and costs, requiring only **about 9‰ of numerical modeling's cost**.

In conclusion, `VL-Time` significantly unlocks multimodal LLMs' TsR capabilities by addressing the two observed anomalies in Section 3.2 and largely reduces token cost.

6.2 Ablation Studies

We choose the RCW and HAR tasks to conduct ablation study of the proposed `VL-Time`. We apply the zero-shot setting to reduce evaluation bias.

Figure 5: Ablation Study of VL-Time. The planning stage and visualization designs, including the textual legend and timestamps, are all validated as effective.

Effectiveness of the Planning Stage. As shown in Figure 5, the planning stage proves effective: (1) VL-Time\Planning performs close to random on RCW, highlighting the importance of planning for time- or frequency-domain visualizations, especially since RCW relies on frequency features. (2) For HAR, a time-domain task, VL-Time\Planning also shows performance degradation, confirming that feature hints from the planning stage effectively guide the solving stage

Effectiveness of the Visualization Design. We focus on two key designs: the textual legend and timestamps, corresponding to two ablation versions, VL-Time\Legend and VL-Time\TimeStamps, respectively. The visualizations for RCW and HAR are shown in Figure 9 and 10. Specifically, RCW uses legends to align colors with decibel levels, while HAR uses legends to map curves with x, y, and z axes of acceleration. As shown in Figure 5, two visualization designs prove effective: (1) VL-Time\Legend shows a significant performance drop, particularly for HAR, where identifying the x, y, and z axes is crucial for activity recognition. (2) VL-Time\TimeStamps shows consistent performance degradation, indicating that capturing temporal semantics is helpful.

6.3 Exploratory Studies

Data Efficiency in ICL. To thoroughly analyze the ICL capabilities unlocked by VL-Time, we conduct experiments by varying the number of examples in the context. As shown in Figure 6, we have the following observations: (1) VL-Time demonstrates high data efficiency, typically achieving strong performance with just 4 examples per class. (2) VL-Time consistently benefits from ICL, compared to the performance degradation of traditional solutions, as detailed in Section 3.2.

Multimodal LLMs Selection. We analyze the impact of LLM selection to answer three questions:

Figure 6: Results of VL-Time empowered data efficiency in ICL. Typically, VL-Time requires only 4 examples per class in ICL to achieve strong performance.

Figure 7: Results of LLMs selection with ICL. We label the improvements of VL-Time over the numerical modeling at the top of bars. Figure 8 further shows the zero-shot results. We observe the consistent effectiveness of VL-Time, the importance of model scale, and the gap between open- and closed-source models.

(1) Is VL-Time effective across different LLMs? (2) How does model size affect TsR performance? (3) What is the gap between open-source and closed-source models? To explore these, we use two additional multimodal LLMs: GPT-4o-mini for Question (2) and Qwen2-VL-72B for Question (3). As shown in Figure 7, we conclude the following: (1) VL-Time is effective across multimodal LLMs. (2) LLM's TsR capability still scales with its size. (2) State-of-the-art open-source multimodal LLMs still lag behind closed-source models on TsR tasks.

7 Conclusion

We explore the area of LLMs reasoning about time series. We present the first comprehensive evaluation suite, conduct extensive evaluations, and verify the initial failures. We identify numerical modeling of data as one possible key issue and further propose a prompt-based solution with visualization modeling. Experiments show that this solution enables multimodal LLMs as effective zero-shot and powerful in-context-learning reasoners about time series, and significantly reduces token costs.

8 Limitations

According to the three levels of causality proposed by Pearl and Mackenzie, this paper focuses on reasoning problems at the basic "Correlation" level. For problems at the further "Intervention" and "Counterfactual" levels, we look forward to future work, especially in addressing the lack of suitable datasets.

Besides, all reasoning tasks in this work are formalized as classification tasks, as the relationship between performance in other forms of time series analysis tasks and reasoning ability is currently unclear. Specifically, time-series forecasting (Kamarthi et al.) and imputation (Du et al., 2024) tasks involve generating specific numerical series, but it is unclear whether the causal relationships between inputs and outputs can support reasoning for such specific numerical series. For example, when forecasting future series of influenza infections, any event occurring in the future window, such as a disease outbreak, would affect the specific numbers but can not be included in the input. We anticipate future work to further discuss how to reasonably evaluate reasoning performance with other time-series analysis task formats.

Moreover, this work focuses on a prompt-based solution to unlock the ability of multimodal LLMs to reason about time series. We expect our evaluation suite, insights, and solution to inspire subsequent fine-tuning-based solutions, especially those that empower both unimodal and multimodal LLMs.

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Mark F Baumgartner and Sarah E Mussoline. 2011. A generalized baleen whale call detection and classification system. *The Journal of the Acoustical Society of America*, 129(5):2889–2902.

EO Brigham. 1988. The fast fourier transform and its applications.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020. Language models are few-shot learners. In *Proceedings of the 34th International Conference on Neural Information Processing Systems*, NIPS '20, Red Hook, NY, USA. Curran Associates Inc.

Winnie Chow, Lauren Gardiner, Haraldur T Hallgrímsson, Maxwell A Xu, and Shirley You Ren. 2024. Towards time series reasoning with llms. *arXiv preprint arXiv:2409.11376*.

Rina Dechter. 2022. *Reasoning with probabilistic and deterministic graphical models: Exact algorithms*. Springer Nature.

Jonathan B Dingwell and Joseph P Cusumano. 2000. Nonlinear time series analysis of normal and pathological human walking. *Chaos: An Interdisciplinary Journal of Nonlinear Science*, 10(4):848–863.

Manqing Dong, Hao Huang, and Longbing Cao. 2024. Can llms serve as time series anomaly detectors? *arXiv preprint arXiv:2408.03475*.

Wenjie Du, Jun Wang, Linglong Qian, Yiyuan Yang, Fanxing Liu, Zepu Wang, Zina Ibrahim, Haoxin Liu, Zhiyuan Zhao, Yingjie Zhou, et al. 2024. Tsi-bench: Benchmarking time series imputation. *arXiv preprint arXiv:2406.12747*.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, et al. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Nate Gruver, Marc Finzi, Shikai Qiu, and Andrew G Wilson. 2024. Large language models are zero-shot time series forecasters. *Advances in Neural Information Processing Systems*, 36.

Manfred Jaeger. 1994. Probabilistic reasoning in terminological logics. In *Principles of Knowledge Representation and Reasoning*, pages 305–316. Elsevier.

Yixing Jiang, Jeremy Irvin, Ji Hun Wang, Muhammad Ahmed Chaudhry, Jonathan H Chen, and Andrew Y Ng. 2024. Many-shot in-context learning in multimodal foundation models. *arXiv preprint arXiv:2405.09798*.

Harshavardhan Kamarthi, Lingkai Kong, Zhiyuan Zhao, Chao Zhang, B Aditya Prakash, et al. Time-series forecasting for out-of-distribution generalization using invariant learning. In *Forty-first International Conference on Machine Learning*.

Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. 2022. Large language models are zero-shot reasoners. *Advances in neural information processing systems*, 35:22199–22213.

Haoxin Liu, Zhiyuan Zhao, Jindong Wang, Harshavard-han Kamarthi, and B. Aditya Prakash. 2024a. Lst-prompt: Large language models as zero-shot time series forecasters by long-short-term prompting. In *Findings of the Association for Computational Linguistics, ACL 2024, Bangkok, Thailand and virtual meeting, August 11-16, 2024*, pages 7832–7840. Association for Computational Linguistics.

Jiashuo Liu, Zheyan Shen, Yue He, Xingxuan Zhang, Renzhe Xu, Han Yu, and Peng Cui. 2021. Towards out-of-distribution generalization: A survey. *arXiv preprint arXiv:2108.13624*.

Nelson F Liu, Kevin Lin, John Hewitt, Ashwin Paran-jape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. 2024b. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics*, 12:157–173.

Yong Liu, Tengge Hu, Haoran Zhang, Haixu Wu, Shiyu Wang, Lintao Ma, and Mingsheng Long. 2024c. itransformer: Inverted transformers are effective for time series forecasting. In *The Twelfth International Conference on Learning Representations*.

Haoyu Lu, Wen Liu, Bo Zhang, Bingxuan Wang, Kai Dong, Bo Liu, Jingxiang Sun, Tongzheng Ren, Zhu-oshu Li, Yaofeng Sun, et al. 2024. Deepseek-vl: towards real-world vision-language understanding. *arXiv preprint arXiv:2403.05525*.

Mike A Merrill, Mingtian Tan, Vinayak Gupta, Tom Hartvigsen, and Tim Althoff. 2024. Language mod-els still struggle to zero-shot reason about time series. *arXiv preprint arXiv:2404.11757*.

Yuqi Nie, Nam H Nguyen, Phanwadee Sinthong, and Jayant Kalagnanam. 2023. A time series is worth 64 words: Long-term forecasting with transformers. In *The Eleventh International Conference on Learning Representations*.

Judea Pearl and Dana Mackenzie. 2018. *The book of why: the new science of cause and effect*. Basic books.

Zayne Sprague, Fangcong Yin, Juan Diego Rodriguez, Dongwei Jiang, Manya Wadhwa, Prasann Singhal, Xinyu Zhao, Xi Ye, Kyle Mahowald, and Greg Dur-rett. 2024. To cot or not to cot? chain-of-thought helps mainly on math and symbolic reasoning. *arXiv preprint arXiv:2409.12183*.

A Vaswani. 2017. Attention is all you need. *Advances in Neural Information Processing Systems*.

Lei Wang, Wanyu Xu, Yihuai Lan, Zhiqiang Hu, Yunshi Lan, Roy Ka-Wei Lee, and Ee-Peng Lim. 2023. Plan-and-solve prompting: Improving zero-shot chain-of-thought reasoning by large language models. In *Pro-ceedings of the 61st Annual Meeting of the Associa-tion for Computational Linguistics (Volume 1: Long Papers)*, pages 2609–2634, Toronto, Canada. Associ-ation for Computational Linguistics.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. 2022. Chain-of-thought prompting elicits rea-soning in large language models. *Advances in neural information processing systems*, 35:24824–24837.

Haixu Wu, Tengge Hu, Yong Liu, Hang Zhou, Jianmin Wang, and Mingsheng Long. 2023. Timesnet: Tem-poral 2d-variation modeling for general time series analysis. In *The Eleventh International Conference on Learning Representations*.

Haixu Wu, Jiehui Xu, Jianmin Wang, and Mingsheng Long. 2021. Autoformer: Decomposition transform-ers with auto-correlation for long-term series fore-casting. *Advances in neural information processing systems*, 34:22419–22430.

Hao Xue and Flora D Salim. 2023. Promptcast: A new prompt-based learning paradigm for time series forecasting. *IEEE Transactions on Knowledge and Data Engineering*.

An Yang, Beichen Zhang, Binyuan Hui, Bofei Gao, Bowen Yu, Chengpeng Li, Dayiheng Liu, Jianhong Tu, Jingren Zhou, Junyang Lin, et al. 2024. Qwen2. 5-math technical report: Toward mathematical ex-pert model via self-improvement. *arXiv preprint arXiv:2409.12122*.

Jianbo Yang, Minh Nhut Nguyen, Phyo Phyo San, Xi-aoli Li, and Shonali Krishnaswamy. 2015. Deep convolutional neural networks on multichannel time series for human activity recognition. In *Ijcai*, vol-ume 15, pages 3995–4001. Buenos Aires, Argentina.

Shukang Yin, Chaoyou Fu, Sirui Zhao, Ke Li, Xing Sun, Tong Xu, and Enhong Chen. 2023. A survey on multimodal large language models. *arXiv preprint arXiv:2306.13549*.

Ailing Zeng, Muxi Chen, Lei Zhang, and Qiang Xu. 2023. Are transformers effective for time series fore-casting? In *Proceedings of the AAAI conference on artificial intelligence*, volume 37, pages 11121–11128.

Xingxuan Zhang, Jiansheng Li, Wenjing Chu, Junjia Hai, Renzhe Xu, Yuqing Yang, Shikai Guan, Ji-azheng Xu, and Peng Cui. 2024. On the out-of-distribution generalization of multimodal large lan-guage models. *arXiv preprint arXiv:2402.06599*.

Xingxuan Zhang, Linjun Zhou, Renzhe Xu, Peng Cui, Zheyan Shen, and Haoxin Liu. 2022. Towards unsu-pervised domain generalization. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4910–4920.

Haoyi Zhou, Shanghang Zhang, Jieqi Peng, Shuai Zhang, Jianxin Li, Hui Xiong, and Wancai Zhang. 2021. Informer: Beyond efficient transformer for long sequence time-series forecasting. In *Proceed-ings of the AAAI conference on artificial intelligence*, volume 35, pages 11106–11115.

Tian Zhou, Ziqing Ma, Qingsong Wen, Xue Wang, Liang Sun, and Rong Jin. 2022. Fedformer: Frequency enhanced decomposed transformer for long-term series forecasting. In *International conference on machine learning*, pages 27268–27286. PMLR.

A Additional Related Works

First, we introduce related works on modeling time series data for LLMs. Existing studies (Xue and Salim, 2023; Gruver et al., 2024; Liu et al., 2024a; Dong et al., 2024) on prompting LLMs for time series analysis mainly model time series numerically as textual inputs to LLMs. This approach is somewhat limited by the fact that LLMs at that time only had textual capabilities. In the context of the rapid development of multimodal capabilities in recent LLMs (Yin et al., 2023; Zhang et al., 2024), our proposed solution aims to unlock the reasoning abilities of multimodal LLMs for time series.

Next, we discuss related works on LLMs reasoning about time series. Recently, Merrill et al. pointed out that LLMs still struggle with zero-shot reasoning about time series. Our concurrent work (Chow et al., 2024) also confirms this viewpoint. From an evaluation perspective, our contribution lies in providing a more progressive, comprehensive, and up-to-date evaluation suite, addressing their limitations in various components, detailed in Section 1. From a conclusion perspective: (1) We more thoroughly verify the initial failures across reasoning patterns, advanced and diverse LLMs, and reasoning strategies, detailed in Section 3. (2) However, our proposed method resolves these failures and enables LLMs as effective zero-shot and powerful in-context learning reasoners about time series. This is due to the visualization designs, the "plan then solve" framework, and the crucial few-shot in-context learning reasoning strategies, which are ignored by these works, as verified in Section 6. (3) Additionally, we point out current limitations and future research directions—namely, that LLMs still cannot surpass all supervised models in probabilistic reasoning, detailed in Table 1.

B Detailed Evaluation Results

Detailed Evaluation Results are provided in Table 3.

C Details of Datasets

Dataset statistics are provided in Table 2.

D Details of Prompts

D.1 Prompt used for Zero-Shot Setting

```
prompt = ""

prompt += f"""{TimeSeries_Number}.
Given the time series data above,
answer the following question
using the specified format.
    Question: {task_description}
    Choices: {str(class_desprtion)}
  Please respond with the following format:
   ---BEGIN FORMAT TEMPLATE---
  Answer Choice: [Your Answer Choice Here]
   ---END FORMAT TEMPLATE---
  Do not deviate from the above format.
  Repeat the format template for the answer."""
```

D.2 Prompt used for Zero-Shot Chain-of-Thought Setting

```
prompt = ""
prompt += f"""{TimeSeries_Number}.
Given the time series data above,
answer the following question
using the specified format.
    Question: {task_description}
    Choices: {str(class_desprtion)}
  Please solve this problem step by step.
  Please respond with the following format:
   ---BEGIN FORMAT TEMPLATE---
  Answer Choice: [Your Answer Choice Here]
   ---END FORMAT TEMPLATE---
  Do not deviate from the above format.
  Repeat the format template for the answer."""
```

D.3 Prompt used for Few-shot In-Context Learning Setting

```
prompt = ""
for demo in demo_examples:
    prompt += f"""{TimeSeries_Number}.
    Given the time series data above,
    answer the following question
    using the specified format.
    Question: {task_description}
    Choices: {str(class_desprtion)}
    Answer Choice: {demo.answer}
    """
prompt += f"""{TimeSeries_Number}.
Given the time series data above,
answer the following question
using the specified format.
    Question: {task_description}
    Choices: {str(class_desprtion)}
  Please solve this problem step by step.
  Please respond with the following format:
    ---BEGIN FORMAT TEMPLATE---
  Answer Choice: [Your Answer Choice Here]
    ---END FORMAT TEMPLATE---
  Do not deviate from the above format.
  Repeat the format template for the answer."""
```

D.4 Details of Task Description

D.4.1 RCW

Play the role of a marine biology expert: is there a right whale calls in the record?

D.4.2 TEE

Based on the power density time series data and select the transient electromagnetic event that best matches. The FORTE satellite detects transient electromagnetic events associated with lightning using a suite of optical and radio-frequency (RF) instruments. There are 7 event types. CG Positive Initial Return Stroke: A positive charge is lowered from a cloud to the ground. The characteristic feature of this type of event in the power density time series is a sharp turn-on of radiation, followed by a few hundreds of microseconds of noise; IR Negative Initial Return Stroke: A negative charge is lowered from a cloud to ground. The power waveform slowly ramps up to a level known as an attachment point, where a large surge current causes the VHF power to 'spike'. This attachment is followed by an exponentially shaped decline in the waveform.; SR Subsequent Negative Return Stroke: A negative charge is lowered from a cloud to ground. As the name implies, subsequent return strokes come after initial return strokes. Note that subsequent positive return strokes don't exist. I Impulsive Event: Typically an intra-cloud event characterized by a sudden peak in the waveform. I2 Impulsive Event Pair: Another intra-cloud event characterized by sudden peaks in the waveform that come in closely separated pairs. These are also called TIPPs (Trans-Ionospheric Pulse Pairs). KM Gradual Intra-Cloud Stroke: An intra-cloud event which increases in power more gradually than an impulsive event. O Off-record: 800 microseconds was not enough to fully capture the lightning event.

D.4.3 ECG

As a cardiologist, you are tasked with classifying a patient's heart condition based on single-lead ECG recordings.

D.4.4 EMG

As an Electromyograms (EMG) analysis expert, you are tasked with determining the type of the subject based on the EMG record.

D.4.5 CTU

Play as a computer energy consumption analysis expert, please correctly determine whether this computer is a desktop or a laptop based on the 24-hour power consumption data.

D.4.6 HAR

As a human activity recognition expert, you are tasked with determining the type of activity performed by the subject based on the accelerometer record series along the x, y, and z axes over time.

E More Details of Setup

For the Qwen model, we utilize four NVIDIA A100 80GB servers. To prevent biases caused by class imbalance, We perform sampling for a balanced class distribution following Jiang et al.. We use the API service provided by OpenAI for GPT-4o and GPT-4. The specific endpoint for for GPT-4o is "gpt-4o-2024-08-06", for GPT-4 is "gpt-4-1106-preview", To prevent models from abstaining (which is common in ICL setting with numerical modeling but rarely for our VL-Time), we rerun the query until an answer is provided.

F Included Eight Supervised Time-Series Models

- **Transformer**(Vaswani, 2017), a classic sequence-to-sequence model basing on multi-

head attention mechanism.

- **Informer**(Zhou et al., 2021), an advanced Transformer designed to tackle long-term modeling problem with sparse attention layers and self-attention distilling.

- **Autoformer**(Wu et al., 2021), a Transformer-based model that keeps encoder-decoder structure but alters attention computations by auto-correlation mechanism in order to benefit long-term modeling.

- **FEDformer**(Zhou et al., 2022), a Transformer that explicitly use Fourier decomposition results to enhance long-term modeling ability.

- **PatchTST**(Nie et al., 2023), a transformer-based models using segmentation of time series and channel-independence design.

- **iTransformer**(Liu et al., 2024c), a inverted Transformer that tokenizes multivariate time-series upon each timestamps.

- **DLinear**(Zeng et al., 2023), a linear model that performs modeling by a direct regression upon historical time series with a one-layer linear model.

- **TimesNet**(Wu et al., 2023), a temporal 2D-variation modeling for general yime series analysis.

G   Verbalized Feature Extraction Plans

G.1   RCW

G.1.1   Prompt

Given the task: Play the role of a marine biology expert: is there a right whale calls in the record? Please tell me what features or patterns do you plan to extract from input data to correctly complete this task?

G.1.2   GPT-4

To determine if there are right whale calls in a recording while playing the role of a marine biology expert, several key features and patterns can be extracted from the audio data. Here's a plan to approach this task:

Frequency Analysis: Right whale calls typically fall within specific frequency ranges, often between 50 Hz to 500 Hz. Analyzing the frequency content of the audio can help identify segments where these calls might occur.

Temporal Patterns: Right whale calls have distinctive durations and temporal patterns. For example, up-calls usually last about one second and rise in frequency. Identifying these patterns can help differentiate right whale calls from other sounds.

Energy and Power: Examining the energy or power of the audio signal over time can help to detect calls, as vocalizations tend to have higher energy levels compared to background noise.

Spectral Characteristics: Spectrogram analysis can be very useful. Right whale calls exhibit specific shapes on spectrograms, such as the curved shape of up-calls. Machine learning models can be trained to recognize these shapes.

Harmonic Patterns: Whale calls often consist of harmonic series where multiple harmonics of a fundamental frequency are present. Detecting these can help confirm the presence of whale calls.

Temporal Consistency: Repeated patterns over time could indicate the presence of biological sources (like whales) as opposed to random noise or other transient sounds.

Machine Learning Classification: After extracting features, employing a classifier such as a Support Vector Machine (SVM) or a neural network that has been trained on labeled examples of right whale calls and other sounds can automate the detection process.

Audio Quality Assessment: Ensuring the recording's quality and clarity can aid in more accurate

analysis, considering factors like signal-to-noise ratio and possible interference.

By combining these methods, the task of detecting right whale calls in recordings can be approached systematically and effectively.

G.1.3 GPT-4o

To detect right whale calls in a sound recording, the following features and patterns are essential for accurate analysis. I will approach this task systematically, as it typically involves bioacoustic signal processing. Below are the key features and patterns I would focus on:

1. Spectral Features (Frequency Domain) Spectrogram Analysis: Visual representation of frequencies over time to identify characteristic call patterns. Peak Frequency: Right whale calls often occur between 50-300 Hz. Band Energy Ratios: Measure energy distribution within specific frequency bands of interest. Mel-Frequency Cepstral Coefficients (MFCCs): Captures timbral features, useful for bioacoustic identification. 2. Temporal Features (Time Domain) Duration of Calls: Right whale calls typically last 0.5 - 1.5 seconds. Temporal Gaps: Identifying rhythmic patterns or repetitions of the same call type. Zero-Crossing Rate: Number of times the signal crosses the zero amplitude axis, useful for characterizing specific call types. 3. Call Types and Patterns Upcalls: A rising frequency contour starting around 50 Hz and ending at 150-200 Hz (most common call type for North Atlantic right whales). Gunshots: Brief, broadband pulses that are associated with social behavior or communication. Chirps: Shorter calls with a rapid change in frequency. Harmonics: Identify overtones accompanying the primary frequency of calls. 4. Acoustic Context Features Ambient Noise: Identify and filter background noise like boat engines, wind, or waves to focus on whale vocalizations. Signal-to-Noise Ratio (SNR): Assess how clearly the whale calls are distinguishable from background noise. Call Repetition Patterns: Determine if calls appear in sequence or clusters, which is typical in some behavioral contexts. 5. Geospatial and Seasonal Context (if metadata is available) Time of Day / Season: Right whales exhibit seasonal calling behavior—more frequent calls during migration and breeding seasons. Location and Habitat Information: Helps determine if the recording region overlaps with known whale migration routes or habitats. 6. Feature Engineering and Post-processing Techniques Smoothing and Filtering: Applying band-pass filters to isolate frequencies relevant to whale calls. Dynamic Time Warping (DTW): Useful for matching whale call templates to observed audio signals. Call Classification Models: Using supervised machine learning or deep learning models (e.g., Convolutional Neural Networks) trained on annotated whale call data. By extracting and analyzing these features, I can determine the presence of right whale calls within a recording. The focus will be on identifying the upcall pattern, as it is the most diagnostic feature for right whales, but other patterns like gunshots and chirps will also be investigated to ensure comprehensive detection.

G.1.4 Qwen2.5-72B

Certainly! To determine whether a recording contains right whale calls, we need to analyze the acoustic characteristics of the audio data. Here's a detailed breakdown of the features and patterns I would extract from the input data:

1. Frequency Analysis Dominant Frequency Range: Right whales typically produce low-frequency vocalizations, often in the range of 50-200 Hz. Analyzing the frequency spectrum to identify dominant frequencies within this range can help confirm the presence of right whale calls. Spectral Peaks: Look for distinct peaks in the frequency spectrum that correspond to known right whale call frequencies. 2. Temporal Analysis Duration: Right whale calls can vary in duration but are generally between 0.5 and 2 seconds. Measuring the duration of potential calls can help filter out non-whale sounds. Inter-Call Intervals: The intervals between successive calls can also be a useful feature. Right whales often produce calls at regular intervals, which can be characteristic of their vocal behavior. 3. Amplitude Modulation Envelope Shape: Analyze the amplitude envelope of the sound to identify patterns typical of right whale calls. These calls often have a distinctive rise and fall in amplitude. Peak Amplitude: Identify the peak amplitude of the sound and compare it to known thresholds for right whale calls. 4. Spectral Features Spectral Centroid: This is the center of mass of the spectrum and can help distinguish between different types of sounds. Right whale calls tend to have a lower spectral centroid compared to other marine sounds. Spectral Bandwidth: Measure the width of the frequency band where most of the energy is concentrated. Right whale calls often have a relatively narrow bandwidth. 5. Mel-Frequency Cepstral Coefficients (MFCCs) MFCCs:

These coefficients capture the shape of the spectral envelope and are widely used in speech and bioacoustic analysis. Extracting MFCCs from the audio can help in identifying the unique spectral patterns of right whale calls. 6. Waveform Analysis Zero-Crossing Rate: The rate at which the waveform crosses the zero axis can provide information about the texture of the sound. Right whale calls often have a specific zero-crossing rate. Energy Distribution: Analyze the energy distribution over time to identify segments with high energy that could correspond to whale calls. 7. Machine Learning and Pattern Recognition Feature Vectors: Combine the above features into a feature vector for each segment of the audio. Classification Models: Train machine learning models (e.g., Support Vector Machines, Neural Networks) on labeled data to classify segments as either containing right whale calls or not. 8. Contextual Analysis Environmental Noise: Consider the ambient noise level and other marine sounds that might interfere with the detection of right whale calls. Geographic and Temporal Context: Use metadata such as location and time of recording to cross-reference with known right whale habitats and migration patterns. By extracting and analyzing these features, we can effectively determine whether a given audio recording contains right whale calls. This approach combines both traditional signal processing techniques and modern machine learning methods to ensure accurate identification.

G.1.5   Qwen2-VL-72B

To determine if there are right whale calls in a given audio record, I would extract the following features or patterns from the input data:

Spectrogram: A spectrogram is a visual representation of the spectrum of frequencies in a sound as they vary with time. By analyzing the spectrogram of the audio record, I can identify the frequency range and duration of the calls, which can help me distinguish right whale calls from other sounds. Pitch: Right whale calls have a distinct pitch that is typically between 20 and 30 Hz. By analyzing the pitch of the audio record, I can determine if there are any sounds that fall within this range. Duration: Right whale calls typically last between 1 and 10 seconds. By analyzing the duration of the sounds in the audio record, I can identify any sounds that fall within this range. Intensity: Right whale calls are typically loud and can be heard over long distances. By analyzing the intensity of the sounds in the audio record, I can determine if there are any sounds that are loud enough to be right whale calls. Repetition: Right whale calls are often repeated in a specific pattern. By analyzing the repetition of the sounds in the audio record, I can determine if there are any sounds that follow a pattern that is consistent with right whale calls. By analyzing these features and patterns, I can determine if there are any right whale calls in the audio record.

G.2   TEE

G.2.1   Prompt

Given the task: Based on the power density time series data and select the transient electromagnetic event that best matches. The FORTE satellite detects transient electromagnetic events associated with lightning using a suite of optical and radio-frequency (RF) instruments. There are 7 event types. CG Positive Initial Return Stroke: A positive charge is lowered from a cloud to the ground. The characteristic feature of this type of event in the power density time series is a sharp turn-on of radiation, followed by a few hundreds of microseconds of noise; IR Negative Initial Return Stroke: A negative charge is lowered from a cloud to ground. The power waveform slowly ramps up to a level known as an attachment point, where a large surge current causes the VHF power to 'spike'. This attachment is followed by an exponentially shaped decline in the waveform.; SR Subsequent Negative Return Stroke: A negative charge is lowered from a cloud to ground. As the name implies, subsequent return strokes come after initial return strokes. Note that subsequent positive return strokes don't exist. I Impulsive Event: Typically an intra-cloud event characterized by a sudden peak in the waveform. I2 Impulsive Event Pair: Another intra-cloud event characterized by sudden peaks in the waveform that come in closely separated pairs. These are also called TIPPs (Trans-Ionospheric Pulse Pairs). KM Gradual Intra-Cloud Stroke: An intra-cloud event which increases in power more gradually than an impulsive event. O Off-record: 800 microseconds was not enough to fully capture the lightning event. Please tell me what features or patterns do you plan to extract from input data to correctly complete this task?

G.2.2   GPT-4

To successfully classify transient electromagnetic events based on power density time series data from the FORTE satellite, you would analyze specific

features from the time series that correspond to the unique characteristics of each event type. Here are the key features and patterns to focus on for each of the seven event types:

CG Positive Initial Return Stroke:

Sharp Onset of Radiation: Look for a very quick rise in power density at the beginning of the event. Short Duration Noise: After the sharp onset, expect a period of noisy signal lasting a few hundred microseconds. IR Negative Initial Return Stroke:

Slow Ramp-Up: The power density will increase gradually until it reaches a specific threshold. Spike at Attachment Point: After the slow ramp-up, look for a significant spike in the power density. Exponential Decline: Post-spike, the waveform should show an exponentially shaped decline. SR Subsequent Negative Return Stroke:

Multiple Peaks: Since these strokes occur after the initial return strokes, identify multiple peaks that might follow initial peaks in a given timeframe. Characteristics Similar to IR Negative: Each subsequent return stroke might mirror the slow ramp-up and sharp spike, though typically less pronounced than the initial stroke. I Impulsive Event:

Sudden Peak: Look for a sudden, sharp peak in the power density without prior gradual increase or subsequent pairs of peaks. I2 Impulsive Event Pair:

Paired Peaks: Identify closely spaced pairs of sharp peaks. Consistency in Time Interval: The time interval between the paired peaks should be consistent across events classified as TIPPs. KM Gradual Intra-Cloud Stroke:

Gradual Increase in Power: Unlike impulsive events, these will show a more gradual rise in power density. Sustained High Power Levels: The power might stay elevated for a longer period compared to other intra-cloud events. O Off-record:

Incomplete Waveform: Look for waveforms that seem to cut off or end abruptly without resolving normally within the 800-microsecond timeframe. To automate the classification process and improve accuracy, you can implement a series of steps:

Preprocessing: Apply noise reduction and normalization techniques to clean the data for more precise analysis. Feature Extraction: Develop algorithms to extract the above features from the time series data. This might include detecting peaks, analyzing the rate of rise and fall in power density, and measuring durations and intervals. Classification Model: Use machine learning techniques such as decision trees, support vector machines,

or neural networks to classify events based on the extracted features. Training the model with labeled examples of each event type will be crucial. Validation and Testing: Continuously validate the model with new data and adjust parameters to handle variations in signal characteristics or noise levels. By focusing on these features and employing robust data processing and machine learning techniques, you can effectively classify the types of transient electromagnetic events detected by the FORTE satellite.

G.2.3 GPT-4o

To correctly classify transient electromagnetic events detected by the FORTE satellite using the power density time series, I will extract the following features and patterns from the data:

1. Onset Shape and Slope (Turn-On Pattern) Feature: Detect the rate of power increase at the start of the event. Reason: CG Positive Initial Return Stroke: Sharp, sudden increase in power. IR Negative Initial Return Stroke: Gradual ramp-up to an attachment point, followed by a sudden spike. 2. Noise Characteristics (Post-Onset) Feature: Identify high-frequency noise following the event onset. Reason: CG Positive Initial Return Stroke: Hundreds of microseconds of noise following the sharp turn-on. IR Negative Initial Return Stroke: Less noise following the attachment point. 3. Peak Power Amplitude and Timing Feature: Measure the peak power and the time to reach the peak. Reason: I Impulsive Event: Single, sharp peak. I2 Impulsive Event Pair (TIPPs): Two closely spaced peaks of similar amplitude. SR Subsequent Negative Return Stroke: Peak power smaller than the initial stroke, coming after an initial event. 4. Power Decay Pattern (Post-Peak) Feature: Examine the post-peak decay shape (exponential or not). Reason: IR Negative Initial Return Stroke: Exponential decline following the surge. KM Gradual Intra-Cloud Stroke: Power decays gradually over time without a sharp drop. 5. Duration of the Event Feature: Calculate the total event duration (from onset to the end of the waveform). Reason: O Off-Record: The event continues beyond the 800-microsecond recording window. Other Events: Fit within the 800-microsecond window. 6. Number of Peaks and Time Separation Between Peaks Feature: Identify the number of distinct peaks and measure time intervals between them. Reason: I2 Impulsive Event Pair (TIPPs): Two closely spaced peaks. I Impulsive Event: Single peak without sub-

sequent pulses. SR Subsequent Negative Return Stroke: A second peak occurring after the initial return stroke. 7. Power Level at Attachment Point (For IR Events) Feature: Detect the power level at the attachment point for initial return strokes. Reason: IR Negative Initial Return Stroke: The power ramps up gradually and hits an attachment point before spiking. 8. Pattern in Power Increase (Gradual vs. Sudden) Feature: Classify the pattern of power increase (impulsive or gradual). Reason: KM Gradual Intra-Cloud Stroke: Gradual increase in power compared to impulsive events. I Impulsive Event: Sudden increase in power. These features will help in differentiating between the seven event types by matching the time series patterns against the characteristic behaviors described.

G.2.4 Qwen2.5-72B

To accurately classify transient electromagnetic events based on the power density time series data from the FORTE satellite, several key features and patterns should be extracted and analyzed. Here's a detailed breakdown of what to look for in each event type:

1. CG Positive Initial Return Stroke Sharp Turn-On: Look for a sudden and significant increase in power density over a very short period (a few microseconds). Noise Duration: After the sharp turn-on, there should be a period of noise lasting a few hundred microseconds. 2. IR Negative Initial Return Stroke Ramp-Up: Identify a gradual increase in power density leading to an attachment point. Spiking: At the attachment point, there should be a sharp spike in the power waveform. Exponential Decline: Following the spike, the power should decline exponentially. 3. SR Subsequent Negative Return Stroke Sudden Peak: Look for a sudden and significant increase in power density, similar to the initial return stroke but typically less intense. Timing: Consider the timing relative to the initial return stroke, as subsequent strokes often occur shortly after the initial one. 4. I Impulsive Event Sudden Peak: Identify a sudden and sharp peak in the power waveform. Duration: The peak should be relatively short-lived, typically a few microseconds. 5. I2 Impulsive Event Pair (TIPPs) Paired Peaks: Look for two closely spaced peaks in the power waveform. Separation: The separation between the peaks should be very short, typically a few microseconds. 6. KM Gradual Intra-Cloud Stroke Gradual Increase: Identify a gradual and sustained increase in power density

over a longer period compared to impulsive events. Smooth Transition: The transition from low to high power should be smooth without sharp spikes. 7. O Off-record Duration Exceeding 800 microseconds: If the event lasts longer than 800 microseconds, it is classified as off-record. Feature Extraction Techniques: Time Domain Analysis: Peak Detection: Use algorithms to detect peaks in the power density waveform. Rise Time: Measure the time it takes for the power to rise from a baseline to a peak. Fall Time: Measure the time it takes for the power to fall from a peak back to a baseline. Noise Analysis: Analyze the noise characteristics following a sharp turn-on. Frequency Domain Analysis: Spectral Analysis: Perform Fourier Transform to analyze the frequency components of the waveform. Bandwidth: Determine the bandwidth of the signal, which can help distinguish between different types of events. Statistical Analysis: Mean and Variance: Calculate the mean and variance of the power density over different segments of the waveform. Skewness and Kurtosis: These higher-order statistics can provide insights into the shape of the waveform. Machine Learning: Feature Engineering: Combine the above features into a feature vector. Classification Models: Train machine learning models (e.g., Random Forest, Support Vector Machines, Neural Networks) to classify the events based on the extracted features. By carefully extracting and analyzing these features, you can effectively classify the transient electromagnetic events detected by the FORTE satellite.

G.2.5 Qwen2-VL-72B

To correctly complete this task, I plan to extract the following features or patterns from the input data:

Sharp turn-on of radiation: This feature is characteristic of a positive initial return stroke (CG Positive Initial Return Stroke). I will look for a sudden increase in power density at the beginning of the time series data. Exponentially shaped decline: This feature is characteristic of a negative initial return stroke (IR Negative Initial Return Stroke). I will look for a slow increase in power density followed by a sudden spike and then a gradual decline in the waveform. Subsequent negative return stroke: This feature is characteristic of a subsequent negative return stroke (SR Subsequent Negative Return Stroke). I will look for a negative charge being lowered from a cloud to the ground after an initial return stroke. Sudden peak in the waveform: This feature is characteristic

of an impulsive event (I Impulsive Event). I will look for a sudden increase in power density in the time series data. Closely separated pairs of sudden peaks: This feature is characteristic of an impulsive event pair (I2 Impulsive Event Pair). I will look for two closely separated peaks in the time series data. Gradual increase in power: This feature is characteristic of a gradual intra-cloud stroke (KM Gradual Intra-Cloud Stroke). I will look for a gradual increase in power density in the time series data. Off-record event: This feature is characteristic of an off-record event (O Off-record). I will look for a lightning event that was not fully captured within the 800 microseconds of the time series data.

G.3 ECG

G.3.1 Prompt

Given the task: As a cardiologist, you are tasked with classifying a patient's heart condition based on single-lead ECG recordings. Please tell me what features or patterns do you plan to extract from input data to correctly complete this task?

G.3.2 GPT-4

To classify a patient's heart condition based on single-lead ECG recordings effectively, various features and patterns can be extracted from the ECG signal to facilitate accurate diagnosis. Here are some key features and patterns typically considered:

Heart Rate: The average heart rate can be calculated by detecting the intervals between R-peaks (RR intervals) in the ECG signal. Variations in heart rate can indicate conditions like tachycardia or bradycardia.

RR Intervals: Analyzing the variability of RR intervals helps in assessing the autonomic nervous system's control over the heart, indicating potential arrhythmias or other heart conditions.

P-Wave Analysis: The presence, size, shape, and duration of the P-wave, which represents atrial depolarization, are important. Abnormalities in P-waves can indicate atrial enlargement or atrial arrhythmias.

QRS Complex: The duration, amplitude, and morphology of the QRS complex, which represents ventricular depolarization, are crucial. Changes can indicate ventricular hypertrophy, bundle branch blocks, or other ventricular disorders.

ST Segment: The level and shape of the ST segment can indicate ischemia or myocardial infarction. Elevation or depression of this segment is particularly significant in diagnosing these conditions.

T-Wave Analysis: Alterations in T-wave morphology can be indicative of electrolyte imbalances, ischemia, or myocardial infarction.

QT Interval: Measuring the duration of the QT interval, which represents the total time for ventricular depolarization and repolarization, is important. Prolonged or shortened QT intervals can lead to arrhythmias.

Signal Quality: Assessing the quality of the ECG signal to detect noise, artifacts, or missing segments which could affect the analysis.

Advanced Signal Processing Features:

Spectral Analysis: Frequency components of the ECG can provide insights into periodic oscillations of the heart rhythm, identifying arrhythmic conditions. Wavelet Transform: This helps in detecting transient features and non-stationary changes in the ECG signal. Machine Learning Features:

Feature Engineering: Creating composite features like heart rate variability, RR interval statistics (mean, median, range, standard deviation), and counts of arrhythmic beats. Time-Series Analysis: Applying algorithms to detect trends, patterns, and outliers over time. Statistical Features: These include calculating the mean, variance, skewness, and kurtosis of the intervals and amplitudes, providing a statistical summary that may indicate underlying pathologies.

These features can be extracted using various signal processing techniques and then used as inputs into classification models or algorithms to determine specific heart conditions. By analyzing these aspects of the ECG, a cardiologist can effectively classify different types of heart conditions with higher accuracy.

G.3.3 GPT-4o

To classify a patient's heart condition based on single-lead ECG recordings, the following key features and patterns can be extracted:

1. Time-Domain Features Heart Rate (HR):

Average beats per minute (bpm) over the recording. Heart rate variability (HRV) to assess autonomic function. R-R Interval:

Interval between successive R-peaks, essential for rhythm assessment. P, QRS, and T Wave Duration:

Abnormal durations may indicate conduction delays (e.g., bundle branch block). PR Interval:

Prolonged PR intervals could indicate first-degree heart block. QT and Corrected QT Interval (QTc):

Long QT may indicate risk for arrhythmias. QRS Complex Morphology:

Shape or width of the QRS complex provides insight into ventricular conduction. Frequency-Domain Features Power Spectral Density (PSD):

Analysis of frequency components to detect anomalies in heart rhythms (e.g., tachyarrhythmia). LF/HF Ratio:

Low-Frequency (LF) and High-Frequency (HF) ratio reflects autonomic nervous system balance. Morphological Features Amplitude of P, QRS, and T Waves:

Useful to detect hypertrophy, ischemia, or electrolyte imbalances. ST-Segment Deviation:

Elevated or depressed ST-segment indicates ischemia or myocardial infarction. Presence of U-Waves:

Might indicate hypokalemia or repolarization abnormalities. Rhythm Patterns and Waveforms Detection of Arrhythmias:

Identification of atrial fibrillation (AF), ventricular tachycardia (VT), or bradycardia. Atrial and Ventricular Premature Contractions:

Isolated ectopic beats that may suggest arrhythmogenic risks. Regularity of Beats:

Distinguishing between sinus rhythm, AF, and other irregular rhythms. Nonlinear and Statistical Features Poincaré Plots:

Used to visualize HRV patterns and detect arrhythmias. Entropy (e.g., Approximate and Sample Entropy):

Measures signal complexity, with reduced entropy indicating abnormal rhythms. Fractal Dimension:

Provides insight into the complexity of ECG signals, useful for arrhythmia detection. Wavelet Transform Features Wavelet Coefficients:

Helps in time-frequency analysis to detect transient events like arrhythmias or ischemia. Multiscale Analysis:

Captures changes in the ECG signal across different scales, useful for feature extraction from noisy signals. Machine Learning or Deep Learning Based Features (if applicable) Learned Features from CNN or RNN Models:

Automatically extracted patterns that represent ECG morphology and rhythm. Latent Features from Autoencoders:

Captures compressed representations of the signal for efficient classification. By extracting these features, both traditional cardiologists and machine learning models can perform accurate heart condition classification based on ECG recordings, improving the diagnostic process and patient outcomes.

G.3.4 Qwen2.5-72B

To classify a patient's heart condition based on single-lead ECG recordings as a cardiologist, several key features and patterns need to be extracted from the ECG data. These features can help in diagnosing various cardiac conditions such as arrhythmias, ischemia, and myocardial infarction. Here are the primary features and patterns to consider:

Heart Rate (HR): Mean Heart Rate: Average beats per minute (BPM). Heart Rate Variability (HRV): Variations in the time interval between heartbeats. QRS Complex: Amplitude: The height of the QRS complex. Duration: The width of the QRS complex. Morphology: Shape and pattern of the QRS complex, which can indicate bundle branch blocks or ventricular hypertrophy. P Wave: Amplitude: Height of the P wave. Duration: Width of the P wave. Morphology: Shape and pattern of the P wave, which can indicate atrial enlargement or atrial fibrillation. T Wave: Amplitude: Height of the T wave. Duration: Width of the T wave. Morphology: Shape and pattern of the T wave, which can indicate ischemia or electrolyte imbalances. ST Segment: Elevation or Depression: Changes in the ST segment can indicate myocardial ischemia or infarction. Morphology: Shape of the ST segment, including upsloping, downsloping, or flat patterns. PR Interval: Duration: Time from the onset of the P wave to the onset of the QRS complex. Variability: Changes in the PR interval can indicate conduction abnormalities. QT Interval: Duration: Time from the onset of the Q wave to the end of the T wave. Corrected QT (QTc): Adjusted for heart rate to account for variations in heart rate. RR Interval: Duration: Time between successive R waves. Variability: Changes in RR intervals can indicate arrhythmias. Rhythm Analysis: Regular vs. Irregular: Consistency of the R-R intervals. Rate: Whether the heart rate is normal, bradycardic, or tachycardic. Pattern: Specific patterns such as atrial fibrillation, atrial flutter, or ventricular tachycardia. Waveform Analysis: Presence of Abnormal Waves: Such as U waves, epsilon waves, or delta waves. Abnormal Patterns: Such as J-point ele-

vation, Osborn waves, or T-wave inversions. Frequency Domain Analysis: Power Spectral Density (PSD): Distribution of power over different frequency bands. Dominant Frequencies: Frequencies with the highest power. Time-Frequency Analysis: Spectral Analysis: Techniques like Fourier Transform or Wavelet Transform to analyze both time and frequency components. Bispectral Analysis: Higher-order spectral analysis to detect nonlinear interactions. Machine Learning Features: Feature Engineering: Creating new features from raw ECG data, such as statistical measures, derivatives, and integrals. Feature Selection: Using techniques like PCA (Principal Component Analysis) or LASSO (Least Absolute Shrinkage and Selection Operator) to select the most relevant features. By extracting and analyzing these features, you can effectively classify a patient's heart condition and provide an accurate diagnosis. Each feature provides a piece of the puzzle, and together they form a comprehensive picture of the patient's cardiac health.

G.3.5 Qwen2-VL-72B

To classify a patient's heart condition based on single-lead ECG recordings, I would extract the following features or patterns from the input data:

Heart rate: The number of heartbeats per minute can provide important information about the patient's heart condition. Rhythm: The regularity of the heartbeats can indicate whether the patient has a normal or abnormal heart rhythm. P wave: The P wave represents atrial depolarization and can provide information about the patient's atrial activity. QRS complex: The QRS complex represents ventricular depolarization and can provide information about the patient's ventricular activity. ST segment: The ST segment represents the period between the end of ventricular depolarization and the beginning of ventricular repolarization and can provide information about the patient's myocardial ischemia. T wave: The T wave represents ventricular repolarization and can provide information about the patient's ventricular repolarization. QT interval: The QT interval represents the time between the start of ventricular depolarization and the end of ventricular repolarization and can provide information about the patient's ventricular repolarization. PR interval: The PR interval represents the time between the start of atrial depolarization and the start of ventricular depolarization and can provide information about the patient's atrioventricular conduction. QRS duration: The QRS duration

represents the time it takes for the ventricles to depolarize and can provide information about the patient's ventricular conduction. Axis: The axis represents the direction of the electrical activity of the heart and can provide information about the patient's heart position and orientation. By analyzing these features or patterns, I can classify the patient's heart condition based on the single-lead ECG recordings.

G.4 EMG

G.4.1 Prompt

Given the task: As an Electromyograms (EMG) analysis expert, you are tasked with determining the type of the subject based on the EMG record. Please tell me what features or patterns do you plan to extract from input data to correctly complete this task?

G.4.2 GPT-4

As an Electromyograms (EMG) analysis expert tasked with determining the type of subject based on the EMG record, the following features and patterns would be essential to extract from the input data to facilitate accurate classification:

Signal Amplitude: The peak amplitude of the EMG signal provides information on muscle activity level, which can vary significantly between different types of subjects, such as athletes vs. non-athletes, or among different medical conditions.

Mean Absolute Value (MAV): This feature represents the average of the absolute values of the EMG signal. It is useful for estimating the overall muscle activation over time.

Variance: The variance of the EMG signal can help in assessing the signal's power and muscle fatigue, which may differentiate between subject types based on their endurance and muscle condition.

Root Mean Square (RMS): This is a measure of the signal's power, reflecting muscle force and fatigue. It's particularly useful in continuous monitoring of muscle activity.

Zero Crossing Rate (ZCR): This measures the rate at which the signal changes from positive to negative and vice versa, indicating muscle fiber recruitment patterns and firing rates.

Waveform Length: The cumulative length of the waveform over time, reflecting the complexity of the muscle activation pattern. It can indicate the contractile characteristics of different muscle groups.

Frequency Domain Features:

Median Frequency (MDF): This frequency divides the spectrum into two regions with equal power; it shifts downwards as muscles fatigue. Mean Frequency (MNF): This is the average frequency weighted by the amplitude, used to assess muscle fatigue and fiber composition. Power Spectral Density (PSD): Analysis of the distribution of power across various frequency bands can indicate the type of muscle activity and its intensity. Entropy: This measures the complexity or randomness of the EMG signal, useful for distinguishing between controlled and uncontrolled muscle activity.

Higher Order Statistics (HOS): Skewness and kurtosis of the EMG signal provide insights into the symmetry and peakiness of the distribution, which can vary with different types of muscle activation.

Autoregressive Model Coefficients: Parameters from fitting an autoregressive model to the EMG signal can help in characterizing the muscle activity and can be used as features for classification.

Signal Decomposition:

Wavelet Transform: Decomposing the signal into wavelets to capture both frequency and location information about muscle activity. Empirical Mode Decomposition (EMD): This non-linear and non-stationary signal analysis technique can adaptively decompose an EMG signal into intrinsic mode functions (IMFs), revealing hidden patterns. Pattern Recognition: Detecting specific patterns of muscle activation that are characteristic of certain actions or types of subjects, using sequence modeling or neural networks.

These features can be extracted using advanced signal processing techniques and subsequently used in machine learning models to classify different types of subjects based on their EMG records. The choice of features and model depends on the specificity of the subjects being classified and the quality and type of EMG data available.

G.4.3 GPT-4o

Time-Domain Features Mean Absolute Value (MAV):

Average of the absolute EMG signal, reflecting muscle contraction intensity. Root Mean Square (RMS):

Indicates the power of the signal and reflects muscle contraction strength. Zero Crossing Rate (ZCR):

The number of times the signal changes sign, related to muscle activation and fatigue. Slope Sign Changes (SSC):

Number of slope changes in the signal, which identifies muscle state changes. Waveform Length (WL):

Cumulative length of the signal waveform, representing complexity and activity. Integrated EMG (IEMG):

Summed absolute values of the EMG signal, used to measure muscle workload over time. Frequency-Domain Features Mean Frequency (MNF):

Average frequency content of the signal, which decreases during muscle fatigue. Median Frequency (MDF):

Frequency at which the power spectrum is divided into two equal halves, commonly used for fatigue detection. Power Spectral Density (PSD):

Quantifies the power across different frequency bands, helping to identify fatigue or abnormal muscle states. Band Power (BP):

Signal energy in specific frequency bands (e.g., 10-500 Hz for EMG). Spectral Moments:

Useful for characterizing the distribution of spectral content across the frequency spectrum. Time-Frequency and Nonlinear Features Short-Time Fourier Transform (STFT):

Analyzes how the frequency components of the signal change over time. Wavelet Transform:

Provides multi-scale analysis to capture transient muscle activations and fatigue patterns. Entropy Measures:

Sample Entropy, Approximate Entropy: Measures the signal complexity, with reduced entropy indicating fatigue or pathology. Fractal Dimension:

Assesses signal irregularity, with higher values indicating more complex muscle activation patterns. Muscle Activation Features Onset and Offset Detection:

Time points when a muscle starts or stops contracting, useful for activity detection. Co-activation Patterns:

Correlation between different muscle groups, helping in understanding coordination and motor control. Muscle Synergy Analysis:

Identifying groups of muscles activated together to perform specific tasks. Fatigue and Pathology Detection Features Decrease in MNF and MDF Over Time:

Indicators of muscle fatigue as spectral content shifts to lower frequencies. Increase in Signal Amplitude and Variability:

Pathological conditions may exhibit irregular or spastic muscle activity. Motor Unit Action Potential (MUAP) Features:

MUAP size, shape, and firing rates provide insights into motor unit recruitment and muscle health. Statistical Features Skewness and Kurtosis:

Indicates asymmetry and peakedness of the signal distribution, respectively. Variance and Standard Deviation:

Reflects the variability in muscle activity, useful for fatigue and abnormality detection. Cross-Correlation:

Measures synchronization between signals from different muscles. Machine Learning or Deep Learning Features (if applicable) Learned Features from CNN, RNN, or LSTM Models:

Automatically extracted patterns representing complex muscle activity and fatigue states. Latent Features from Autoencoders:

Compressed representations for efficient subject classification. By extracting these features from the EMG signal, both traditional analysis and machine learning models can accurately classify the subject type, providing insights into muscle performance, fatigue, or pathology.

G.4.4 Qwen2.5-72B

To determine the type of the subject based on Electromyogram (EMG) records, several key features and patterns can be extracted from the EMG data. These features help in distinguishing between different types of muscle activities, which can be indicative of various conditions or states of the subject. Here are some of the most important features and patterns to consider:

Amplitude: Mean Amplitude: The average amplitude of the EMG signal over a period of time. Peak Amplitude: The maximum amplitude reached during the recording. Frequency: Power Spectrum Density (PSD): Analyzing the frequency content of the EMG signal can provide insights into the muscle's activation patterns. Median Frequency (MDF): The frequency below which 50Mean Frequency (MNF): The average frequency of the power spectrum. Time-Domain Features: Root Mean Square (RMS): A measure of the magnitude of the EMG signal over a period of time. Zero Crossings (ZC): The number of times the EMG signal crosses the zero line. Waveform Length (WL): The cumulative length of the EMG signal over a period of time. Slope Sign Changes (SSC): The number of times the slope of the EMG sig-

nal changes sign. Frequency-Domain Features: Fast Fourier Transform (FFT): Converts the time-domain signal into its frequency components. Band Power: The power in specific frequency bands (e.g., low, medium, high). Non-Linear Features: Sample Entropy (SampEn): Measures the complexity and regularity of the EMG signal. Approximate Entropy (ApEn): Another measure of signal complexity and regularity. Motor Unit Action Potential (MUAP) Analysis: MUAP Shape and Size: Characteristics of individual motor unit action potentials. Firing Rate: The rate at which motor units are activated. Spectral Moments: First Spectral Moment (F1): The mean frequency. Second Spectral Moment (F2): The variance of the frequency distribution. Time-Frequency Analysis: Short-Time Fourier Transform (STFT): Provides a time-varying spectral representation of the EMG signal. Wavelet Transform: Analyzes the signal in both time and frequency domains, useful for non-stationary signals. Statistical Features: Skewness: Measures the asymmetry of the signal distribution. Kurtosis: Measures the "tailedness" of the signal distribution. Muscle Fatigue Indicators: Fatigue Index (FI): The rate of change of the median frequency over time, indicating muscle fatigue. Spectral Shift: Changes in the frequency content of the EMG signal as the muscle fatigues. By extracting these features, you can build a comprehensive profile of the EMG signal, which can then be used to classify the type of the subject. For example, different muscle conditions (e.g., healthy vs. pathological), different levels of muscle activity (e.g., rest vs. contraction), or different types of movements (e.g., voluntary vs. involuntary) can be distinguished based on these features. Machine learning algorithms can be trained on these features to automate the classification process.

G.4.5 Qwen2-VL-72B

As an EMG analysis expert, I would extract the following features or patterns from the input data to determine the type of the subject:

Frequency content: The frequency content of the EMG signal can provide information about the type of muscle activity. For example, low-frequency components may indicate slow muscle contractions, while high-frequency components may indicate fast muscle contractions. Amplitude: The amplitude of the EMG signal can provide information about the strength of the muscle contraction. Higher amplitudes may indicate stronger muscle contractions.

Duration: The duration of the EMG signal can provide information about the duration of the muscle contraction. Longer durations may indicate sustained muscle contractions. Shape: The shape of the EMG signal can provide information about the type of muscle activity. For example, a burst of activity followed by a period of inactivity may indicate a twitch, while a sustained period of activity may indicate a tetanus. Coherence: The coherence between different EMG signals can provide information about the coordination of muscle activity. High coherence may indicate coordinated muscle activity, while low coherence may indicate uncoordinated muscle activity. Power spectral density: The power spectral density of the EMG signal can provide information about the distribution of power across different frequency bands. This can be used to identify specific muscle groups or types of muscle activity. By analyzing these features or patterns, I can determine the type of the subject based on the EMG record.

G.5 CTU

G.5.1 Prompt

Given the task: Play as a computer energy consumption analysis expert, please correctly determine whether this computer is a desktop or a laptop based on the 24-hour power consumption data. Please tell me what features or patterns do you plan to extract from input data to correctly complete this task?

G.5.2 GPT-4

To differentiate between a desktop and a laptop based on 24-hour power consumption data, you would focus on extracting and analyzing specific features or patterns that can indicate the type of device based on its energy usage profile. Here are several key features and patterns you might consider:

Total Daily Power Consumption:

Laptops typically consume less power than desktops due to their more energy-efficient components. Calculating the total power used over a 24-hour period could give an initial indication of the device type. Power Consumption Patterns Over Time:

Analyze hourly or segment-wise power consumption. Laptops might show a more uniform consumption pattern, especially if they're left on but are in sleep or hibernate modes. Desktops might show a starker contrast between high consumption during active use and low consumption

when turned off or in sleep mode. Frequency and Duration of Power Spikes:

Desktops might exhibit higher power spikes during usage due to more powerful processors and peripherals compared to laptops. Observing how often and how long these spikes occur can be indicative. Minimum Power Consumption Levels:

The minimum power levels (especially during inactive periods like nighttime) can be telling. Desktops might completely turn off (very low or zero consumption) or remain on higher consumption levels due to connected devices, whereas laptops typically have lower baseline consumption levels due to battery optimization features. Presence of Battery Charging Patterns:

If data shows periodic drops and rises in power consumption that could correspond to a battery charging cycle, it's likely a laptop. Desktops would not show this pattern unless a UPS or similar device is connected, which is less common. Variability in Power Consumption:

Analyzing the variability and standard deviation in power usage over 24 hours can help distinguish between the two. Laptops generally have less variability in power consumption, while desktops might have greater fluctuations due to different modes of operation (idle, full power, sleep mode). Response to Day and Night Cycles:

Depending on the usage patterns, if the device shows a significant reduction in power usage during typical sleeping hours, it might suggest a laptop which is often put into sleep mode automatically. Desktops might not show this pattern distinctly if they are left on for processes like downloads, updates, or backups during off-hours. By analyzing these features and considering the context in which the device is used (e.g., home, office), you can infer with reasonable accuracy whether the device is a desktop or a laptop. Statistical and machine learning models can be applied to these features to automate the classification process, especially if you have a labeled dataset to train such models.

G.5.3 GPT-4o

To determine whether a computer is a desktop or a laptop based on its 24-hour power consumption data, I will extract the following features and patterns:

1. Base Power Consumption (Idle Usage) Feature: Identify the minimum power level when the computer is idle. Reason: Desktops typically have higher idle consumption due to larger components

(e.g., GPUs, cooling systems). Laptops generally consume lower power at idle. 2. Power Consumption Peaks and Variability Feature: Extract peak power usage and how frequently peaks occur throughout the day. Reason: Desktops often have higher peak power consumption during intensive tasks (e.g., gaming, rendering). Laptops may exhibit more frequent but lower peaks, depending on workload. 3. Usage Patterns (On-Off Cycles) Feature: Identify the duration and frequency of usage periods vs. idle or sleep periods. Reason: Laptops tend to have more off/sleep cycles due to battery-saving features, while desktops often remain on for extended periods, especially if connected to UPS or used as servers. 4. Power Spikes During Start-Up (Boot Time) Feature: Detect significant power increases indicating a system boot. Reason: Laptops may exhibit small, brief spikes during start-up, while desktops might have more noticeable power jumps due to larger components. 5. Battery-Induced Cycles (Power Drops) Feature: Look for repeating low power levels or abrupt power drops corresponding to battery-saving modes (if the system is unplugged). Reason: Only laptops have battery discharge patterns, leading to identifiable low-power modes (like Sleep or Hibernate). 6. Cooling System Patterns (Fan Activity) Feature: Identify fan activity or cooling-induced power surges. Reason: Desktops typically have stronger fans or liquid cooling systems, leading to regular power surges when temperatures rise. Laptops have smaller fans, with less significant fluctuations. 7. Day-Night Power Trends (User Behavior) Feature: Observe power usage during the night and early morning hours. Reason: Desktops are sometimes left on overnight for background processes (e.g., downloads, backups), while laptops are more likely to enter sleep mode overnight. 8. Power Consumption Range Feature: Compute the range of power consumption (Max - Min) throughout the day. Reason: Desktops generally exhibit a broader power range (e.g., 50-200W or higher). Laptops have a narrower range (e.g., 5-50W). These features and patterns will allow us to distinguish between desktop and laptop behaviors effectively. With proper statistical or machine learning models, these extracted features can be combined for a final classification.

G.5.4 Qwen2.5-72B

To determine whether a computer is a desktop or a laptop based on 24-hour power consumption data, I would focus on several key features and patterns that typically differentiate the two types of computers. Here's how I would approach the analysis:

1. Average Power Consumption Desktops generally have higher average power consumption compared to laptops because they have more powerful components and larger power supplies. Laptops are designed for portability and efficiency, so their average power consumption is typically lower. 2. Peak Power Consumption Desktops can have very high peak power consumption, especially during resource-intensive tasks like gaming, video rendering, or running multiple applications simultaneously. Laptops have more limited peak power consumption due to their smaller form factor and battery constraints. 3. Power Consumption Variability Desktops often show more variability in power consumption throughout the day, as they are more likely to be used for a wide range of tasks with varying power demands. Laptops tend to have more consistent power consumption, especially when running on battery power, but can show variability when plugged in and performing intensive tasks. 4. Idle Power Consumption Desktops usually have a higher idle power consumption because they have more components (e.g., multiple fans, larger power supplies) that consume power even when the system is not under load. Laptops have lower idle power consumption due to their energy-efficient design and power-saving features. 5. Power Consumption Patterns During Sleep or Hibernate Desktops may not enter deep sleep or hibernate states as frequently as laptops, leading to higher power consumption even when not in use. Laptops are more likely to enter low-power states (sleep or hibernate) to conserve battery, resulting in very low power consumption during these periods. 6. Daily Usage Patterns Desktops are often left on for extended periods, even overnight, leading to a more continuous power consumption pattern. Laptops are more likely to be turned off or put into sleep mode when not in use, resulting in more frequent drops in power consumption. 7. Battery Cycles (if applicable) If the data includes information about battery cycles, this can be a clear indicator: Laptops will show battery charge and discharge cycles. Desktops do not have batteries, so there will be no such cycles. 8. Time of Day Analysis Desktops might show higher power consumption during typical working hours (9 AM to 5 PM) and lower consumption during nighttime. Laptops might show more varied usage patterns, including evening and late-night usage, depending

on the user's habits. Example Analysis Steps: Calculate Average Power Consumption: Compute the mean power consumption over the 24-hour period. Identify Peak Power Consumption: Find the highest power consumption value and note the time it occurs. Analyze Power Consumption Variability: Calculate the standard deviation of power consumption to understand how much it fluctuates. Examine Idle Power Consumption: Look at the lowest power consumption values to estimate idle power. Check for Low-Power States: Identify periods of very low power consumption (e.g., <10W) that might indicate sleep or hibernate states. Review Daily Usage Patterns: Plot the power consumption over the 24-hour period to visualize usage patterns and identify any regular cycles. By combining these features and patterns, you can make an informed decision about whether the computer is a desktop or a laptop.

G.5.5   Qwen2-VL-72B

To determine whether a computer is a desktop or a laptop based on 24-hour power consumption data, I would extract the following features or patterns from the input data:

Average power consumption: I would calculate the average power consumption of the computer over the 24-hour period. Desktop computers typically consume more power than laptops, so a higher average power consumption would suggest that the computer is a desktop. Power consumption during peak hours: I would also look at the power consumption during peak hours, such as during the day when the computer is in use. Desktop computers tend to have higher power consumption during peak hours, while laptops may have lower power consumption during these times. Power consumption during idle periods: I would also examine the power consumption during idle periods, such as overnight when the computer is not in use. Desktop computers may have higher power consumption during idle periods due to their larger size and more powerful components, while laptops may have lower power consumption during these times. Power consumption spikes: I would look for any power consumption spikes in the data, which could indicate that the computer is performing a power-intensive task. Desktop computers may have more frequent and larger power consumption spikes due to their more powerful components, while laptops may have fewer and smaller spikes. By analyzing these features and patterns in the power consump-

tion data, I would be able to determine whether the computer is a desktop or a laptop.

G.6   HAR

G.6.1   Prompt

Given the task: As a human activity recognition expert, you are tasked with determining the type of activity performed by the subject based on the accelerometer record series along the x, y, and z axes over time . Please tell me what features or patterns do you plan to extract from input data to correctly complete this task?

G.6.2   GPT-4

For the task of human activity recognition based on accelerometer data along the x, y, and z axes, the extraction of relevant features is crucial for accurately classifying the type of activity. Here are some typical features and patterns you might consider extracting from the accelerometer data:

Statistical Features:

Mean: Average value of acceleration for each axis. Standard Deviation: Measure of the amount of variation or dispersion in the acceleration values. Variance: Squared deviation of each point from the mean, indicating the spread of the acceleration data. Median: The middle value of the data which divides the probability distribution into two equal halves. Range: Difference between the maximum and minimum values in the acceleration data. Interquartile Range (IQR): Measures the statistical dispersion as the difference between 25th and 75th percentiles. Time-domain Features:

Root Mean Square (RMS): Indicates the magnitude of acceleration, computed as the square root of the average of the squares of the values. Zero Crossing Rate (ZCR): Number of times the signal changes from positive to negative and vice versa, which can indicate the frequency of the activity. Signal Magnitude Area (SMA): Integration of the magnitude of the acceleration over a window, giving a sense of the energy expenditure. Time between Peaks: Interval time between local maxima in the acceleration data. Frequency-domain Features:

Fast Fourier Transform (FFT): Transforming the data from time domain to frequency domain to analyze the frequency components. Power Spectral Density (PSD): Indicates the power present in various frequency components. Spectral Entropy: Measures the regularity and complexity of the frequency distribution. Peak Frequency: The

frequency with the maximum power, indicating the dominant frequency of movement. Correlation-based Features:

Correlation between Axes: Measures how related the movements in different axes are, which can indicate coordinated motion patterns. Geometrical Features:

Angles between Axes: Can help in understanding the orientation of the body in space. Magnitude of Acceleration Vector: Calculated as the square root of the sum of the squares of x, y, and z components. It provides a holistic view of the acceleration independent of the direction. Entropy-based Features:

Signal Entropy: Indicates the unpredictability or complexity of the acceleration signal. By extracting these features from the accelerometer data, you can capture a comprehensive profile of the movements, which can then be fed into a machine learning model to classify different types of human activities such as walking, running, sitting, standing, etc.

G.6.3 GPT-4o

To determine the type of activity performed by a subject using accelerometer data, I would focus on extracting both statistical features and domain-specific patterns that capture relevant aspects of the movements. Below is a structured approach to the features I plan to extract:

1. Time-Domain Features These features capture statistical properties directly from the raw time series data along the x, y, and z axes:

Mean: Average value of the accelerometer data for each axis. Standard Deviation (STD): Measures variability in the signal. Variance: Quantifies how much the data varies. Min, Max, and Range: Captures the spread of the data values. Skewness: Measures the asymmetry of the data distribution. Kurtosis: Measures the "tailedness" of the data distribution. Signal Magnitude Area (SMA):

Energy: Sum of squared values for each axis divided by the series length. Root Mean Square (RMS): Useful to measure overall signal intensity. 2. Frequency-Domain Features Using Fourier Transform (or Wavelet Transform) to analyze the signal in the frequency domain helps identify periodic activities (e.g., walking, running).

Spectral Entropy: Measures randomness in the frequency spectrum. Dominant Frequency: The frequency with the highest magnitude. Power Spectral Density (PSD): Helps measure power in various frequency bands. Peak Frequencies and Their Amplitudes: To identify key frequencies related to the activity. 3. Time-Frequency Features Using short-time Fourier transform (STFT) or wavelet decomposition to extract:

Wavelet coefficients: Capture both time-localized frequency content. Instantaneous frequency: Measures how frequency content changes over time. 4. Magnitude and Orientation Features Some activities are better identified through the magnitude or orientation of movement:

Acceleration Magnitude: Magnitude

Mean and Variance of Magnitude: Stability of the signal magnitude over time. Tilt Angles: Angles between the gravity vector and each axis. Roll and Pitch Angles: Describe the subject's orientation. 5. Temporal and Statistical Patterns These features capture the dynamics of the signal over time.

Zero Crossing Rate: Counts the number of times the signal crosses zero, indicating changes in direction. Autocorrelation: Measures similarity of the signal with a delayed version of itself. Number of Peaks: Useful for repetitive activities like walking or jogging. Signal Peaks and Valleys: Identify critical motion events. 6. Segment-Level Features Segmenting the data into windows (e.g., sliding windows of 1-3 seconds) ensures more granular feature extraction.

Features within sliding windows: Mean, STD, etc., within each window. Window Overlap: To smooth transitions between activities. 7. Cross-Axis Features These features capture interactions between the x, y, and z axes:

Correlation between axes: Helps detect synchronized movements along different directions. Covariance between axes: Measures joint variability of axes. 8. Activity-Specific Patterns Gait Cycle Detection: For walking and running patterns. Step Detection: Counting steps to differentiate walking from running. Stationarity Detection: Helps identify stationary periods, such as sitting or standing. 9. Feature Engineering with Domain Knowledge Tilt thresholding: To detect specific postures like sitting, lying down, or standing. Jerk computation: Time derivative of acceleration to detect sudden changes (e.g., jumping). This diverse set of features—statistical, frequency-based, temporal, and activity-specific—helps build a robust model capable of accurately classifying activities such as walking, running, sitting, standing, and more complex activities.

G.6.4 Qwen2.5-72B

To accurately determine the type of activity performed by a subject based on accelerometer data, it's crucial to extract meaningful features that can capture the essence of the movements. Here are some key features and patterns you might consider extracting from the accelerometer record series along the x, y, and z axes:

1. Statistical Features Mean: The average value of the acceleration in each axis. Standard Deviation: Measures the variability or spread of the acceleration values. Variance: Another measure of the spread of the data. Maximum and Minimum Values: The highest and lowest values of acceleration in each axis. Range: The difference between the maximum and minimum values. Median: The middle value of the sorted acceleration data. Interquartile Range (IQR): The range between the first quartile (25th percentile) and the third quartile (75th percentile). 2. Frequency Domain Features Fast Fourier Transform (FFT): Converts the time-domain signal into the frequency domain to identify dominant frequencies. Spectral Energy: The total energy in the frequency domain. Spectral Entropy: Measures the disorder or randomness in the frequency domain. Spectral Centroid: The center of mass of the spectrum. Spectral Roll-off: The frequency below which a certain percentage (e.g., 853. Time-Domain Features Zero Crossing Rate: The rate at which the signal crosses zero. Mean Absolute Value (MAV): The average of the absolute values of the acceleration. Root Mean Square (RMS): The square root of the mean of the squared values of the acceleration. Signal Magnitude Area (SMA): The sum of the absolute values of the acceleration in all three axes. Jerk: The rate of change of acceleration, calculated as the difference between consecutive acceleration values. 4. Correlation and Covariance Cross-Correlation: Measures the similarity between the acceleration signals in different axes. Covariance: Measures how much two signals vary together. 5. Temporal Patterns Auto-correlation: Measures the correlation of the signal with a delayed copy of itself. Lag: The time delay at which the autocorrelation is maximized. Peak Detection: Identifies the peaks in the acceleration signal, which can be indicative of specific activities. 6. Energy Features Total Energy: The sum of the squared values of the acceleration. Band Energy: The energy in specific frequency bands. 7. Complexity and Entropy Sample Entropy: Measures the complexity of the signal. Approximate Entropy: Another measure of signal complexity. 8. Shape Features Skewness: Measures the asymmetry of the distribution of the acceleration values. Kurtosis: Measures the "tailedness" of the distribution. 9. Activity-Specific Features Step Count: For walking or running, the number of steps can be a useful feature. Stride Length: The distance covered in one step. Cadence: The number of steps per minute. 10. Machine Learning Features Principal Component Analysis (PCA): Reduces the dimensionality of the data while retaining most of the variance. Feature Selection: Techniques like mutual information, chi-squared test, or recursive feature elimination can help select the most relevant features. Example Feature Extraction Process: Preprocessing: Filtering: Apply low-pass or band-pass filters to remove noise. Segmentation: Divide the continuous data into fixed-length windows (e.g., 2 seconds). Feature Calculation: For each window, compute the statistical, frequency, time-domain, and other features mentioned above. Feature Normalization: Normalize the features to ensure they are on a similar scale, which can improve the performance of machine learning models. Model Training: Use the extracted features to train a machine learning model (e.g., Random Forest, SVM, Neural Networks) to classify the activities. By carefully selecting and combining these features, you can build a robust model for human activity recognition using accelerometer data.

G.6.5 Qwen2-VL-72B

To determine the type of activity performed by the subject based on the accelerometer record series along the x, y, and z axes over time, I would extract the following features or patterns from the input data:

Mean and standard deviation of the acceleration values along each axis: These features can help identify the overall movement and intensity of the activity. Frequency domain features: I would perform a Fourier transform on the acceleration data to extract frequency domain features such as the dominant frequency, frequency bandwidth, and spectral entropy. These features can help identify the periodicity and complexity of the activity. Time domain features: I would extract time domain features such as the root mean square (RMS), zero crossing rate, and autocorrelation. These features can help identify the smoothness and regularity of the activity. Activity-specific features: Depending

on the type of activity being performed, I would extract activity-specific features such as the number of steps taken, the duration of the activity, and the intensity of the activity. Contextual features: I would also consider contextual features such as the location of the subject, the time of day, and the duration of the activity. These features can help identify the context in which the activity is being performed. By combining these features, I can create a comprehensive representation of the activity being performed and use machine learning algorithms to classify the activity accurately.

Dataset	Number of Variable	Length of Series	Number of Class	Number of Samples
RCW	1	4000	2	30,000
TEE	1	319	7	143
ECG	1	1500	4	43,673
EMG	1	1500	3	205
CTU	1	720	2	500
HAR	3	206	6	10,299

Table 2: Dataset Statistics.

Task		RCW	TEE	ECG	EMG	CTU	HAR
Metric		ACC(%)	ACC(%)	ACC(%)	ACC(%)	ACC(%)	ACC(%)
Random Guessing		50.00	14.29	25.00	33.33	50.00	16.67
Qwen2.5-72B	ZST	50.00	21.43	25.00	33.33	40.91	29.17
	CoT	50.00	25.00	30.77	33.33	45.45	29.17
	ICL	50.00	21.43	12.50	33.33	54.55	25.00
Qwen2-VL-72B	ZST	50.00	14.29	25.00	33.33	38.89	20.83
	CoT	50.00	17.86	25.00	33.33	45.45	20.83
	ICL	50.00	17.86	25.00	16.67	54.55	29.17
GPT-4	ZST	50.00	14.29	25.00	33.33	40.91	25.00
	CoT	50.00	21.43	25.00	33.33	45.45	29.17
	ICL	50.00	17.86	18.75	41.67	45.45	12.50
GPT-4o	ZST	50.00	10.71	25.00	33.33	22.73	12.50
	CoT	50.00	14.29	31.25	55.56	54.55	16.67
	ICL	50.00	35.71	31.25	33.33	50.00	12.50

Table 3: Detailed Results of Time-series Reasoning without Normalization.

	Cost for Traditional Method Per Sample	Cost for Proposed Method Per Sample
RCW	0.15$	0.000213$
TEE	0.0112$	0.000213$
ECG	0.0638$	0.000213$
EMG	0.0638$	0.000213$
CTU	0.027$	0.000213$
HAR	0.0185$	0.000213$

Table 4: Results of Cost Comparison based on GPT-4o. Our method defaults to using the low resolution option of GPT-4o API, ensuring a fixed cost for different data.

	Token Per Sample for Numerical Modeling	Token Per Sample for Proposed Solution
RCW	60,000	85
TEE	4,466	85
ECG	25,500	85
EMG	25,500	85
CTU	10,800	85
HAR	7,416	85

Table 5: Details of Token Usage Comparison based on GPT-4o. Our method defaults to using low resolution option of GPT-4o API, ensuring a fixed toke sage for different data.

Figure 8: Studies of multimodal LLM selection under zero-shot settings. We label the improvements of VL-Time over the original solution at the top of the bars

Figure 9: Frequency-Domain Visualization Demo of RCW Task.

Figure 10: Time-Domain Visualization Demo of HAR Task.