What can 5.17 billion regression fits tell us about artificial models of the human visual system?

Abstract

Rapid simultaneous advances in machine vision and cognitive neuroimaging present an unparalleled opportunity to assess the current state of artificial models of the human visual system. Here, we perform a large-scale benchmarking analysis of 72 modern deep neural network models to characterize with robust statistical power how differences in architecture and training task contribute to the prediction of human fMRI activity across 16 distinct regions of the human visual system. We find: one, that even stark architectural differences (e.g. the absence of convolution in transformers and MLP-mixers) have very little consequence in emergent fits to brain data; two, that differences in task have clear effects–with categorization and self-supervised models showing relatively stronger brain predictivity across the board; three, that feature reweighting leads to substantial improvements in brain predictivity, without overfitting – yielding model-to-brain regression weights that generalize at the same level of predictivity to brain responses over 1000s of new images. Broadly, this work presents a lay-of-the-land for the emergent correspondences between the feature spaces of modern deep neural network models and the representational structure inherent to the human visual system.

1 Introduction

The pace of progress in computer vision poses a practical challenge for neuroscientists seeking to assess state-of-the-art models in their ability to explain visual representation and behavior. New high-performing models are released on a near-daily basis, and recent innovations (e.g. in self-supervised learning [1, 2]) have created myriad new opportunities for productive synergy between the fields of biological and machine vision. As such, methods for comparing the brain-predictivity of artificial models using a predefined analysis pipeline ("neural benchmarking") are critical in helping discern the algorithmic innovations that may be meaningful with respect to the study of brain function.

Existing public neural benchmarking datasets have been limited to mouse and primate neurophysiology (3, 4). Recent advances in the scale and quality of human neuroimaging datasets (5–7) now present an opportunity to rigorously assess the state of deep neural network modeling as applied to the human visual system.

Here we present a large-scale benchmark of dozens of state-of-the-art deep neural network models in their prediction of human brain activity across the visual hierarchy. Aiming for coverage, our survey attempts to document the current trends in how well different kinds of models, varying in both task and architecture, learn features with brain-like response signatures. Our results complement prior work examining different model predictivities (8–10), but at a significantly larger scale, and

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

incorporating a set of more modern models not yet fully accounted for in the benchmarking literature (e.g. self-supervised models and vision transformers).

2   Methods

As the target of our neural benchmark, we use the Natural Scenes Dataset (NSD, [5]), a recent fMRI dataset representing the most extensive sampling of visual responses in individual participants to date (30,000 stimuli viewed per subject; 73,000 unique images total). Here we analyze only a small fraction of this dataset, focusing on responses to 1,000 COCO stimuli that were shown to 4 subjects at least 3 times, in a subset of ROIs along the visual hierarchy. We compare these responses with the responses of 72 modern DNNs that vary in task and architecture (see Appendix for details).

We employ two methods for mapping the activations of model features within a layer to regions of the brain – classical representational similarity analysis (RSA, [11]) and voxelwise-encoding (re-weighted) RSA (12). Classical RSA considers all of the features from a given model layer equally in computing the image-wise representational dissimilarity matrix (RDM), which is directly compared with a given neural RDM. This method requires a fully-emergent match in population-level geometry between a neural ROI and the full set of units in a model layer.

Voxelwise encoding RSA (veRSA), on the other hand, takes advantage of feature reweighting to identify different model subspaces that correspond to the variance in different brain regions (13). To implement voxel-wise encoding RSA, we use an efficient high-throughput model-fitting procedure, first applying leave-one-out cross-validated ridge regression to map between a given model feature space and the observed univariate activity pattern of each voxel; once we've collected a set of predictions for the patterns of activity for each voxel in a given ROI, we compute an RDM from these predictions and compare that RDM to the RDM in the brain. This re-weighted RSA procedure requires massive parallelization, and entails performing a total of around 5.17 billion regression fits (calculated by multiplying the total number of model layers we analyze by the total number of voxels under consideration from the brain dataset). To assuage concerns of overfitting, we validate the robustness of our fitted regressions by testing their generalizability to 1000 independent images entirely removed from the training procedure.

3   Results

3.1   Hierarchical Correspondence

As a first step and sanity check, we ask: Does the seminal finding that the information processing hierarchies in deep nets recapitulate the information processing hierarchy in the human visual system (14–16) hold at scale and across a significantly diverse population of models? The answer is a resounding affirmative (**Figure 1**): Using a purely data-driven aggregation procedure, we show that the relative depth of the best-fitting model layer for each ROI seems to re-capitulate the human visual hierarchy (e.g. early visual areas, followed by category-selective regions). This hierarchical convergence holds even when breaking down the models by broad, divergent classes of architecture.

3.2   Architecture Variation

How do models with different architectures compare in their ability to predict the structure of human brain responses across the visual system? Our particular survey of models, chosen deliberately to reflect the diversity of modern object recognition (ImageNet-trained) architectures, allows for numerous subdivisions, but perhaps the most prominent is between convolutional architectures (e.g. VGG, ResNet, MobileNet, $n = 24$), vision transformers (e.g. Visformer, DeIT, $n = 13$) and MLP-mixers (e.g. ResMLP, gMixer, $n = 5$). The latter two of these are more recent advents of computer vision, and are defined by the lack of a convolutional inductive bias – once considered a cornerstone of the link between biological and machine vision. Comparisons between these architectures (across both classical RSA and voxel-encoding RSA) are shown in Figure 2.

Figure 1: *(A) Visualization of selected regions-of-interest on a flattened hemisphere. (B) Emergent hierarchical correspondence between the most predictive model layer and the hypothesized information processing hierarchy of the visual system. Regions along the x-axis are ordered by the average depth of the best predicting layer (across all models). Data are also broken down by the architectural distinctions of ConvNets, MLP-Mixers, and Transformers. Each point is the best performing layer from a given model, averaged over subjects.*

To test for differences in predictivity, we use nonparametric ANOVAs. Without reweighting (classical RSA), there is a significant difference across ConvNets, MLP-Mixers, and Transformers ($\chi^2_{\text{Kruskal-Wallis}}(2) = 10.14, p_{\text{Holm}} = 0.02, \widehat{\varepsilon}^2_{\text{ordinal}} = 0.27, CI_{95\%}[0.09, 0.49]$) in early visual areas, driven by a significant pairwise advantage of ConvNets over Transformers. With reweighting (veRSA), this difference disappears. Without reweighting, there is no significant difference between architectures in higher-level cortical areas. With reweighting, there is a difference ($\chi^2_{\text{Kruskal-Wallis}}(2) = 10.59, p_{\text{Holm}} = 0.02, \widehat{\varepsilon}^2_{\text{ordinal}} = 0.26, CI_{95\%}[0.09, 0.56]$), driven this time by the pairwise superiority of both ConvNets and MLP-Mixers over Transformers.

Behind these apparently significant effects is the numerical reality that the raw effect sizes in both cases is effectively negligible – less than $r_{\text{Pearson}} = 0.01$ and $r_{\text{Pearson}} = 0.02$, respectively. As such, the most striking effect here is not that of architecture, but of mapping method, which substantially augments the predictive power of every model in our survey (with average gains of $r_{\text{Pearson}} = 0.160, CI_{95\%}[0.152, 0.166]$ across model and ROI). In the most notable case, models in EBA experience average gains of $r_{\text{Pearson}} = 0.265$. These improvements dwarf any difference attributable to architecture, and underscore an important point: despite dramatic differences in the design and algorithmic inductive biases of ConvNets, MLP-Mixers, and Transformers, there is little consequence on the resulting brain predictivity (regardless of mapping method).

3.3 Task Variation

How does brain predictivity vary as a function of task? For a window into this question we consider the 24 models from the Taskonomy project (17). These models share the same base architecture (ResNet-50) and visual diet, but are trained on 1 of 24 popular computer vision tasks. These tasks are organized into 4 different categories (2D, 3D, Semantic and Geometric) according to what the authors of the Taskonomy project call the models' 'transfer affinity' – the degree to which a model trained on one task supports transfer learning to another. The prediction levels of these models for both classical and voxel-wise encoding RSA are shown in Figure 3.

Without reweighting, there is considerable variability across ROI in the tasks that are most predictive of the brain, but the differences between the best task and the second-best task is minimal in most cases. In V2, for example, a 2D task (edge detection) is the most predictive of the tasks at $r_{\text{Pearson}} = 0.226$, but is closely followed by a 3D task (Keypoints) at $r_{\text{Pearson}} = 0.220$.

Figure 2: *Architecture variations. Model fits are shown along the y-axis, for early visual areas (top row) and category-selective areas (bottom row), for classical RSA (left) and voxel-wise encoding RSA (right). The gray boxes indicate an intersubject reference point (the average pairwise correlation of individual subject RDMs). Each dot is the best performing layer from a single model, with trained models in large circular points, and untrained counterparts in small diamonds.*

As in the case of architecture, feature reweighting (veRSA) leads to uniform improvement across models. Strikingly, however, object and scene classification gain disproportionately. The gains for object recognition are so substantial that it becomes the single most predictive task for all brain areas, often dominating by an impressively large margin, with a mean gain over the next best task (apart from scene classification) of $r_{\text{Pearson}} = 0.127, CI_{95\%}[0.122, 0.131])$ across all ROIs.

While these results point strongly to an advantage of category supervision in the formation of neurally predictive representation (at least in the case of veRSA), the self-supervised models (absent from Taskonomy) in our survey allow us to delve more deeply into whether the classification objective is the key driver of neural predictivity, or whether category-supervised models derive their advantage from the set of invariances that they learn in service of classification.

The predictive power of our self-supervised models strongly suggest the latter: regardless of mapping method, self-supervised models (especially recent contrastive ResNet-50 models such as SimCLR and BarlowTwins) tend to show a small but statistically significant advantage over a (recently revamped) category-supervised ResNet-50 [18]. For example, averaging across brain ROIs, SimCLR eeks out a mean gain of $r_{\text{Pearson}} = 0.013, CI_{95\%}[0.0106, 0.0192]$ in weighted RSA and a gain of $r_{\text{Pearson}} = 0.006, CI_{95\%}[0.002, 0.008]$ in classical RSA. While these results should not be interpreted as indicating superiority of self-supervision over category-supervision, they do indicate *parity* in prediction levels – a win for ethological plausibility (12, 19).

3.4 Generalization Tests

The sheer quantity of regression fits required to summarize the predictive performance of our model set, and the vast number of dimensions relative to data points, may raise concern: is this deep encoding pipeline massively overfitting, in spite of our cross-validation procedures? Or, are the estimates we derive truly a reasonable approximation (given the linking assumptions inherent in the analysis) of a given model's brain predictivity?

Figure 3: *Effect of task on model-brain predictivity. (A) 24 Taskonomy models with a ResNet-50 architecture, grouped into 4 categories (2D, 3D, Geometric, or Semantic). An untrained (randomly-initialized) model, for comparison. The correlation between the model features and brain responses for early visual areas (top) and category-selective regions (bottom) is plotted, using classical RSA in (B) and reweighted RSA in (C). Gray box plots indicate the range of inter-subject RDM correlations using classical RSA.*

To address this concern, we conducted a separate generalization test for each model, in which we selected the best performing layer (according to the original LOOCV score from our regression procedure) per subject, per ROI. For these layers, we then use reweighted RSA to compare brain and model feature spaces using a set of 1000 entirely held-out test images per subject. These images were never referenced or incorporated during training, and prediction scores on these images thus provide a measure of "pure" generalization.

Even with this more stringent test, we found little-to-no drop in accuracy in predicting brain representation evoked by the 1000 unique test images per fMRI subject. When aggregating across subjects, models, and ROI, for example, the mean decrease in score on the unseen images was less than 1% ($r_{\text{Pearson}} = 0.0095, CI_{95\%}[0.00422, 0.0153]$). By adding a mere 103 million regression fits to our initial total of 5.17 billion, then, we can thus confirm definitively that our encoding models generalize to previously-unseen data. (A more detailed figure showing generalization across specific subjects and ROIs is shown in the Appendix.)

4 Discussion

So what can we learn about the human visual system from 5.17 billion regression fits? Broadly, it seems, there are two sets of answers, one more pessimistic, one more optimistic. On the side of pessimism, the lack of variation across architecture suggests that massive innovations in computer vision may often yield little to no change in our ability to predict the representational structure of biological vision, disrupting what was once prophesied to become a glorious feedback loop between

neuroscientific insight and engineering innovation. What's more, the frequent variability in interpretation across mapping method seems a potential pitfall if not accounted for with greater vigilance and attention to theoretical commitment. On the side of optimism, it appears that more general, algorithmic correspondences between DNNs and brains (especially in terms of the information processing hierarchy) persist in spite of an increasingly rapid shift away from biological plausibility in engineering. In opposite direction of this shift is a promising move *towards* ethological plausibility – many cutting-edge models no longer rely on learning targets humans almost certainly do not share (e.g. full category supervision). Not coincidentally, these models appear to be competitive predictors of brain activity.

Current models are still far from capturing the kaleidoscopic complexity of biological visual systems. Our goal in pursuing this large-scale benchmark is not to discern the "best" model of vision, but rather to clarify what kinds of things are and are not important for building next-generation perceptual models that will push our understanding of human vision further.

References

[1] Jure Zbontar, Li Jing, Ishan Misra, Yann LeCun, and Stéphane Deny. Barlow twins: Self-supervised learning via redundancy reduction. *arXiv preprint arXiv:2103.03230*, 2021.

[2] Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre H Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Daniel Guo, Mohammad Gheshlaghi Azar, et al. Bootstrap your own latent: A new approach to self-supervised learning. *arXiv preprint arXiv:2006.07733*, 2020.

[3] Martin Schrimpf, Jonas Kubilius, Ha Hong, Najib J. Majaj, Rishi Rajalingham, Elias B. Issa, Kohitij Kar, Pouya Bashivan, Jonathan Prescott-Roy, Franziska Geiger, Kailyn Schmidt, Daniel L. K. Yamins, and James J. DiCarlo. Brain-score: Which artificial neural network for object recognition is most brain-like? *bioRxiv preprint*, 2018.

[4] Colin Conwell, David Mayo, Michael A. Buice, Boris Katz, George A. Alvarez, and Andrei Barbu. Neural regression, representational similarity, model zoology & neural taskonomy at scale in rodent visual cortex. *bioRxiv*, 2021. doi: 10.1101/2021.06.18.448431. URL https://www.biorxiv.org/content/early/2021/06/18/2021.06.18.448431.

[5] Emily Jean Allen, Ghislain St-Yves, Yihan Wu, Jesse L Breedlove, Logan T Dowdle, Bradley Caron, Franco Pestilli, Ian Charest, J Benjamin Hutchinson, Thomas Naselaris, et al. A massive 7t fmri dataset to bridge cognitive and computational neuroscience. *bioRxiv*, 2021.

[6] Nadine Chang, John A Pyles, Austin Marcus, Abhinav Gupta, Michael J Tarr, and Elissa M Aminoff. Bold5000, a public fmri dataset while viewing 5000 visual images. *Scientific data*, 6 (1):1–18, 2019.

[7] Oliver Contier, Martin N Hebart, Adam H Dickter, Lina Teichmann, Alexis Kidder, Anna Corriveau, Charles Zheng, Maryam Vaziri-Pashkam, and Charles Baker. Things-fmri/meg: A large-scale multimodal neuroimaging dataset of responses to natural object images. *Journal of Vision*, 21(9):2633–2633, 2021.

[8] Seyed-Mahdi Khaligh-Razavi and Nikolaus Kriegeskorte. Deep supervised, but not unsupervised, models may explain it cortical representation. *PLoS computational biology*, 10(11), 2014.

[9] Katherine R Storrs, Tim C Kietzmann, Alexander Walther, Johannes Mehrer, and Nikolaus Kriegeskorte. Diverse deep neural networks all predict human inferior temporal cortex well, after training and fitting. *Journal of Cognitive Neuroscience*, 33(10):2044–2064, 2021.

[10] Aria Wang, Michael Tarr, and Leila Wehbe. Neural taskonomy: Inferring the similarity of task-derived representations from brain activity. In *Advances in Neural Information Processing Systems*, pages 15475–15485, 2019.

[11] Nikolaus Kriegeskorte, Marieke Mur, and Peter A Bandettini. Representational similarity analysis-connecting the branches of systems neuroscience. *Frontiers in systems neuroscience*, 2:4, 2008.

[12] Talia Konkle and George A Alvarez. Beyond category-supervision: instance-level contrastive learning models predict human visual system responses to objects. *bioRxiv*, 2021.

[13] Philipp Kaniuth and Martin N Hebart. Feature-reweighted rsa: A method for improving the fit between computational models, brains, and behavior. *bioRxiv*, 2021.

[14] Daniel LK Yamins, Ha Hong, Charles F Cadieu, Ethan A Solomon, Darren Seibert, and James J DiCarlo. Performance-optimized hierarchical models predict neural responses in higher visual cortex. *Proceedings of the National Academy of Sciences*, 111(23):8619–8624, 2014.

[15] Umut Güçlü and Marcel AJ van Gerven. Deep neural networks reveal a gradient in the complexity of neural representations across the ventral stream. *Journal of Neuroscience*, 35 (27):10005–10014, 2015.

[16] Umut Güçlü and Marcel AJ van Gerven. Increasingly complex representations of natural movies across the dorsal stream are shared between subjects. *NeuroImage*, 145:329–336, 2017.

[17] Amir R Zamir, Alexander Sax, William Shen, Leonidas J Guibas, Jitendra Malik, and Silvio Savarese. Taskonomy: Disentangling task transfer learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3712–3722, 2018.

[18] Ross Wightman, Hugo Touvron, and Hervé Jégou. Resnet strikes back: An improved training procedure in timm. *arXiv preprint arXiv:2110.00476*, 2021.

[19] Chengxu Zhuang, Siming Yan, Aran Nayebi, Martin Schrimpf, Michael C Frank, James J DiCarlo, and Daniel LK Yamins. Unsupervised neural network models of the ventral visual stream. *Proceedings of the National Academy of Sciences*, 118(3), 2021.

[20] Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *European conference on computer vision*, pages 740–755. Springer, 2014.

[21] Jacob S Prince, John A Pyles, Michael J Tarr, and Kendrick N Kay. Glmsingle: a turnkey solution for accurate single-trial fmri response estimates. *Journal of Vision*, 21(9):2831–2831, 2021.

[22] Leyla Tarhan and Talia Konkle. Reliability-based voxel selection. *NeuroImage*, 207:116350, 2020.

[23] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems 32*, pages 8024–8035. Curran Associates, Inc., 2019. URL http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf.

[24] Ross Wightman. Pytorch image models. https://github.com/rwightman/pytorch-image-models, 2019.

[25] Priya Goyal, Quentin Duval, Jeremy Reizenstein, Matthew Leavitt, Min Xu, Benjamin Lefaudeux, Mannat Singh, Vinicius Reis, Mathilde Caron, Piotr Bojanowski, Armand Joulin, and Ishan Misra. Vissl. https://github.com/facebookresearch/vissl, 2021.

[26] Alexander Sax, Bradley Emi, Amir R. Zamir, Leonidas J. Guibas, Silvio Savarese, and Jitendra Malik. Mid-level visual representations improve generalization and sample efficiency for learning visuomotor policies. 2018.

[27] Alexander Sax, Jeffrey O Zhang, Bradley Emi, Amir Zamir, Silvio Savarese, Leonidas Guibas, and Jitendra Malik. Learning to navigate using mid-level visual priors. *arXiv preprint arXiv:1912.11121*, 2019.

[28] Ping Li, Trevor J Hastie, and Kenneth W Church. Very sparse random projections. In *Proceedings of the 12th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 287–296, 2006.

[29] Nikolaus Kriegeskorte, Marieke Mur, Douglas A Ruff, Roozbeh Kiani, Jerzy Bodurka, Hossein Esteky, Keiji Tanaka, and Peter A Bandettini. Matching categorical object representations in inferior temporal cortex of man and monkey. *Neuron*, 60(6):1126–1141, 2008.

[30] Aran Nayebi, Nathan CL Kong, Chengxu Zhuang, Justin L Gardner, Anthony M Norcia, and Daniel LK Yamins. Unsupervised models of mouse visual cortex. *bioRxiv*, 2021.

A   Appendix

A.1   Human Brain Data

The Natural Scenes Dataset (NSD) is the largest effort to date to measure human brain responses with functional magneic resonance imaging (fMRI), reflecting measurements of 73,000 unique stimuli from the Microsoft Common Objects in Context (COCO) dataset ([20]) at high resolution (7T field strength, $1.33s$ TR, $1.8mm^3$ voxel size). In the present work, we analyze only a small fraction of this dataset, focusing on responses to images that enable direct comparison between data from different subjects. That is, we focus on the 1000 COCO stimuli that overlapped between subjects (the "shared1000" images), and limit analyses to the 4 subjects (subjs 01, 02, 05, 07) for whom all 3 image repetitions are available for the shared1000. For the generalization tests, we also select a random unique set of 1000 images for each subject; these were not included in the "shared1000." All responses were estimated using a custom GLM toolbox ("GLMsingle" [21]), which was applied during the preprocessing of NSD time-series data, featuring optimized denoising and regularization procedures, to accurately measure changes in neural activity in response to each experimental stimulus.

We focus our analyses to voxels within a set of predefined functional ROIs that span the visual hierarchy (see [5] for details on the procedures used to define the ROIs). Further, to maximize SNR of the target data, we implement a reliability-based voxel selection procedure [22] that isolates regions of the brain containing stable structure in their responses. To compute the split-half reliability a given voxel, we use 1,000 images from each subject (independent from the shared1000, and from all images included in our main analyses and generalization tests), and take the average correlation in univariate response profiles over each pair of available image repetitions (e.g. $mean(r(rep1, rep2), r(rep2, rep3), r(rep1, rep3))$). ROI voxels exceeding a reliability threshold of Pearson $r = 0.1$ were included in subsequent analyses. These procedures yield a matrix of dimension (images, voxels, repetitions) for each subject's ROI, and we average over the 3 repetitions to yield the final ROI data input into our neural benchmarking pipeline.

A.2   Candidate Deep Neural Network Models

In total, we survey a set of 72 distinct models (110 including the randomly-initialized versions of certain of these models). These models are sourced from four different repositories: the Torchvision (PyTorch) model zoo [23]; the pytorch-image-models (timm) library [24]; the VISSL (self-supervised) model zoo [25]; and the Taskonomy (visualpriors) project [17, 26, 27]. The first two of these repositories offer pretrained versions of a large number of object recognition models with varying architectures: including (classic and modern) convolutional networks, vision transformers, and MLP-mixers. For each of these 'ImageNet' (object recognition) models, we include one trained and one randomly initialized variant (using the initialization scheme the model authors recommended) so as to assess the impact of ImageNet training on brain prediction, and as a sanity check. The self-supervised models are mainly variants on a popular convolutional architecture (ResNet-50), though do include some transformers (the 'DINO' models). The Taskonomy models consist of a core encoder-decoder architecture trained on 24 different common computer vision tasks, ranging from autoencoding to edge detection. These models are engineered in such a way that only the architecture of the decoder

varies across task, allowing us to assess (after detaching the encoder) what effect different kinds of training has on predictive power, independent of model design.

A.3 Benchmarking Pipeline

Feature Extraction For each of our deep neural network models, we extract features in response to each of our probe stimuli at each distinct layer of the network. Importantly, we define a layer here as a distinct computational (sub)operation. This means, for example, that we treat convolution and the rectified nonlinearity that follows it as two distinct feature maps. This is especially relevant in the case of transformers, where the features inherent to the key - query - value computation of the attention maps often differ substantially. At the end of our feature extraction procedure, we have for each model and each model layer, a matrix of features of the dimensions *number of images x number of flattened features from a given layer*.

Classical RSA (cRSA) As a first method of mapping deep neural network responses to voxel responses, we use classical RSA, a nonparametric mapping method that quantifies the *emergent* similarity of the 'representational geometry' between two feature spaces, regardless of origin. To compute this metric, we construct representational dissimilarity matrices (RDMs) using the pairwise correlation distance (1 - Pearson's r) between the responses of a given neural ROI (image by voxel) or a given model layer (image by unit) for all images being considered. We then compare these RDMs by taking a second-order correlation (Pearson's r) between the flattened upper-triangular portion of each. This ultimately yields a matrix of correlation scores of dimension: (number of subjects x number of ROIs x number of model layers x number of models). Classical RSA reflects the extent to which the representational structure in each model layer naturally recapitulates the representational structure in a visual cortical ROI, without alteration or feature reweighting.

Voxelwise Encoding RSA The following procedure yields the billions of regression fits we reference in the title. The pipeline works as follows: first, we fit a regression for *each voxel* as a weighted combination of model layer features. Given that the number of features in a layer sometimes number in the millions, we employ sparse random projection [28] as a dimensionality-reduction procedure, and then use ridge regression as a linear model to relate the model feature space to each voxel's tuning function. Then, we use the voxel-encoding models to generate predicted activation profiles to the complete set of held-out images, and correlate the subsequent predicted representational similarity structure to that of the brain. For additional detail, see Section A.4.

We emphasize that this method contrasts with popular practices in primate and mouse benchmarking, which treat predictivity of unit-level univariate response profiles as the key measure. However, fMRI affords more systematic spatial sampling over the cortex. Thus, for the present analysis, rather than taking the aggregate of single voxel fits as our key measure, we choose to treat the population representational geometry over each ROI as our critical target for prediction. This multi-voxel similarity structure provides different kinds of information about the format of population-level coding than do individual units. (29).

Noise Ceilings and Reference Metrics

While powerful in the quantity and diversity of its images, the number of repetitions in image presentation (3 per image) in the NSD dataset leaves little room to estimate a noise ceiling per voxel with standard split-half reliability methods. Thus, as a reference metric for how well our models are doing overall, we use inter-subject predictivity: a measure of how well the brain of one human predicts the brain of another. Here, we took the average pairwise correlation of the individual subject RDMs in a given ROI. For a more in-depth discussion of ceilings and reference points, as well as experimental alternatives, see Section A.5.

A.4 Voxelwise Encoding RSA In-Depth

To predict the activity profile of each voxel, we first use Sparse Random Projection (SRP) [28] to project the model features generated in response to our 1000 probe images into a lower-dimensional

space. We use a dimensionality of 5960 projections–a number we chose *a priori* using the Johnson-Lindenstrauss lemma, which mathematically guarantees the preservation of pairwise distances in a given space of operations (with a minimal distortion defined by a hyperparameter epsilon, which we leave in all cases at the scikit-learn default of 0.1). We then perform a leave-one-out cross-validated (LOOCV) ridge regression (cross-validating over images) to map these projections to the responses of our voxels, obtaining a vector of predicted voxel responses that we then correlate with the true voxel responses to obtain a score per voxel per model layer. [1]

This leave-one-out cross-validation is performed in a single matrix operation often referred to as generalized cross-validation, and is numerically equivalent to iterative leave-one-out, but is effectively instantaneous. We iterate this regression procedure until we have a score for all voxels and all model layers. No hyperparameter selection was performed over the course of the benchmarking, apart from a minimal, exploratory grid search for a lambda parameter (of values: $1e1, 1e2, 1e3, 1e4, 1e5, 1e6, 1e7$) on an AlexNet model (which we subsequently excluded from the main analysis). Thus, all feature spaces were projected to 5960 sparse random projections, and all regressions were run with a lambda penalty of $1e5$.

Rather than taking single-voxel fits as our key measure, we consider the geometry of the population across the larger region of interest as a critical target for prediction. To do so, we use the predicted responses from our voxel-wise encoding method to generate predicted representational dissimilarity matrices. The logic behind this procedure is effectively to dispense with or otherwise transform irrelevant features from the network via reweighting, such that new images are cast into a weighted subspace of the original feature space. The representational geometry of this subspace serves as the comparison to the brain. At the end of this procedure, we obtain a matrix of correlation scores of dimension (number of subjects x number of ROIs x number of model layers x number of models).

A.5 Intersubject Predictivity and the Noise Ceiling

In general, the purpose of a noise ceiling is to estimate (at the level of an individual unit of prediction) how reliable the response in that unit is across time. This metric allows us to then quantify how well our response data at one point predicts our response data at another. One example such measure relevant to fMRI is the Spearman-Brown-corrected split-half reliability of a voxel response over sequential presentations of the same stimuli. However, this method tends to underestimate true voxel reliability in regimes with few presentations.

The alternative we have provided here – the pairwise inter-subject representational similarity reference – is straightforward in its calculation, and computationally equivalent to the procedure for benchmarking the models with classical RSA (which is to say, that subject RDMs and model RDMs were computed in the exact same way, and compared using the same correlation metric).

As a reference point for weighted RSA, however, this threshold is perhaps a bit misleading – since only the models benefit from the reweighting. One possible alternative, similar to work done recently in the neural network modeling of mouse visual cortex [30], is to directly incorporate the neural activity of human brains into a regression procedure wherein the regressand is the neural activity of a target subject and the regressors are the neural activities of other subjects. This procedure has the advantage of equating the set of computational (sub)operations that map model feature spaces to the brain, and of providing similarly intuitive targets that undergird inferences over how much of the variance in a target biological system we can capture with a system that is decidedly not biological.

As a preliminary test of *reweighted* inter-subject predictivity, we consider another version of the pairwise metric above, predicting single subjects using data from other single subjects. For each pair of subjects, in which one is the target and the other is the contrast, we iterate over ROIs, gathering all voxels from the contrast's ROI to serve as regressors in the prediction of activity in each of the

---

[1]Note that after the SRP procedure there is no longer an interpretable mapping between individual model features and brain voxels; nonetheless, we have confirmed empirically that SRP procedure yields similar brain predictivity compared to a control analysis using AlexNet, a model whose feature map dimensionality is sufficiently low to run our encoding procedure without SRP.

Figure 4: *Generalization scores across subject and ROI. Each point in red is the LOOCV score for a given model over the 1000 training images; each point in blue is the generalization to 1000 unseen images never incorporated into the training procedure.*

target's ROI voxels. We repeat this procedure until we have predicted all voxels in a given target subject with all possible contrast subjects. The mapping procedure in this case is exactly the same as it was for the mapping of models, controlled even to the hyperparemeter: we project the ROI voxel activity from the contrast subject to 5960 sparse random projections, and regress these subjects to the target voxel with a ridge regression set to a lambda penalty of $1e5$.

While this method equates each computational (sub)operation between model and human, the intersubject predictivity threshold it establishes is even lower than the version without reweighting. One reason for this may be that the brain activity from a single subject does not provide a sufficient breadth of variance to benefit from the reweighting. As a first pass at rectifying this issue, we devised a new measure, predicting each voxel from the *concatenated* activity of all voxels from all other subjects in the target ROI, effectively creating a multi-human reference. While we are continuing to assess, conceptually, whether such a reference point may be useful, the estimates it produces for individual subjects are indeed far higher than the estimates of either the unweighted individual subject-to-subject comparison or the corresponding weighted comparison, and is in most cases far higher than the observed levels of model prediction. Figure 5 shows a comparison between the different kinds of human reference points we compute.

A.6 Generalization Scores across Subject + ROI

Figure 4 shows the generalization scores across individual subjects and individual ROIs.

A.7 Compute Required

We used a single machine with 8 Nvidia RTX 3090 GPUs, 755gb of RAM, and 96 CPUs. GPUs were used only for extracting model activations, and could (without major slowdown) be removed from the analytic pipeline. Dimensionality reduction and regression computations were CPU and RAM intensive. Replicating all of our results would take approximately two weeks on a similar machine.

Figure 5: *A plot demonstrating different kinds of human reference points. Points in black are model scores from the voxelwise-encoding RSA method (a method that involves reweighting). The colored bands are the 95% confidence interval on a given reference metric. Reweighting the neural activity of multiple subjects to predict a single target subject (in blue) is the one reference point that reweighted models do not consistently outperform.*