# Model Obfuscation for Securing Deployed Neural Networks

## Abstract

More and more edge devices and mobile apps are leveraging deep learning (DL) capabilities. Deploying such models on devices – referred to as on-device models – rather than as remote cloud-hosted services, has gained popularity as it avoids transmitting user's data off of the device and for high response time. However, on-device models can be easily attacked, as they can be accessed by unpacking corresponding apps and the model is fully exposed to attackers. Recent studies show that adversaries can easily generate white-box-like attacks for an on-device model or even inverse its training data. To protect on-device models from white-box attacks, we propose a novel technique called *model obfuscation*. Specifically, model obfuscation hides and obfuscates the key information – structure, parameters and attributes – of models by *renaming*, *parameter encapsulation*, *neural structure obfuscation*, *shortcut injection*, and *extra layer injection*. We have developed a prototype tool *ModelObfuscator* to automatically obfuscate on-device TFLite models. Our experiments show that this proposed approach can dramatically improve model security by significantly increasing the difficulty of extracting models' inner information, without increasing the latency of DL models. Our proposed on-device model obfuscation has the potential to be a fundamental technique for on-device model deployment. Our prototype tool is publicly available at
https://github.com/AnonymousAuthor000/Code2536.

## 1 Introduction

Numerous edge and mobile devices are leveraging deep learning (DL) capabilities. Though DL models can be deployed on a cloud platform, data transmission between mobile devices and the cloud may compromise user privacy and suffer from severe latency and throughput issues. To achieve high-level security, users' personal data should not be sent outside the device. To achieve high throughput and response time, especially for a large number of devices, on-device DL models are needed. The capabilities of newer mobile devices and some edge devices keep increasing, with more powerful systems on a chip (SoCs) and a large amount of memory, making them suitable for running on-device models. Indeed, many intelligent applications have already been deployed on devices (Xu et al., 2019) and have already benefited millions of users.

Unfortunately, it has been shown that DL models can be easily compromised by adversarial attacks, membership attacks, model inversion attacks, *etc*. (Szegedy et al., 2013; Chen et al., 2017b; Shafahi et al., 2018; Shokri et al., 2017; Fang et al., 2020). Since on-device models are directly hosted on mobile devices, adversaries can easily unpack the mobile apps to locate the models for exploitation. Such on-device models are thus facing more serious security threats (Huang et al., 2021; Li et al., 2021). In addition, deploying DL models may cause intellectual property leakage (Sun et al., 2021).

According to our observation, existing defense methods to protect the on-device models can be categorized into three different types: (1) trustworthy learning algorithms, (2) input processing, and (3) detection. First, trustworthy learning trains models at training time via adversarial training (Tramèr et al., 2017; Shafahi et al., 2019; Wong et al., 2020), or robust learning systems (Blanchard et al., 2017) or *etc*. Second, input processing eliminates the effect of attacks by transforming the adversarial inputs into benign ones. For instance, input restoration (Liao et al., 2018; Zhou et al., 2021) and randomization (Dhillon et al., 2018; Xie et al., 2017) are used to defend against adversarial attacks. The third kind of defense first distinguishes adversarial and clean inputs (*e.g.*, via local intrinsic

dimensionality (Ma et al., 2018)) and then disables the adversarial ones. In addition, watermarking methods can be used to against intellectual property leak (Yang et al., 2019; Fan et al., 2019; Lukas et al., 2019). The above existing defense techniques assume that adversary already gets access to target models or surrogate models to craft adversarial inputs. Hence, they are called as **reactive** defences. Unfortunately, reactive defences cannot prevent attackers from generating white-box attacks by directly inspecting model's information or using a surrogate model. To further secure deployed models, besides reactive defenses, we argue there is a need for designing **proactive** methods.

Applying *proactive defense* to hide the key information of deployed models has three main advantages. First, proactive defense disallows the transformation from a non-differentiable to a differentiable model. Specifically, conducting white-box attacks requires backward propagation, while deployed on-device models just provide the forward inference functionality (non-differentiable). Attackers could attack the non-differentiable model (*e.g.*, TFLite model) by first transforming it to a differentiable one and then conducting white-box attacks (developers, 2022). Proactive defense could disallow such transformation. Second, existing work (Zhou et al., 2020) shows that surrogate models that have a similar structure to the target model can improve the performance of black-box attacks. The proactive defense prevents attackers from finding a similar surrogate model to attack. Third, the proactive defense could help protect the intellectual property in an app. By hiding model's key information, proactive defense can prevent others from stealing or fine-tuning the models.

In this paper, we propose a novel **proactive** model protection approach based on model obfuscation, which obfuscates the key information of on-device DL models. Given a trained model and its underlying DL library (*e.g.*, PyTorch, TensorFlow, TFLite and etc.), an end2end prototype tool, *ModelObfuscator*, is developed to generate the obfuscated on-device model and corresponding DL library. Specifically, *ModelObfuscator* first extracts the information of the target model and locates the source code in the library used by its layers. Then, it obfuscates the information of the models and builds a customized DL library that is compatible with the obfuscated model. To achieve this, we design five obfuscation methods, including: (1) *renaming*, (2) *parameter encapsulation*, (3) *neural structure obfuscation*, (4) *random shortcut injection*, and (5) *random extra layer injection*. These obfuscation methods significantly increase the difficulty of parsing the information of the model. The model obfuscation can prevent adversaries from reconstruct the model to conduct white-box-like attacks, identifying the structure of the model to find a similar surrogate model to generate black-box attacks. In addition, adversaries also hard to transfer the trained weights and structure of models to steal intellectual property. Experiments on 10 different models show that *ModelObfuscator* can against state-of-the-art model parsing and attack tools with a negligible time overhead and 20% storage overhead. Our contributions in this work include:

- We propose the first model obfuscation framework to hide the key information of deployed DL models. It can prevent adversaries from generating white-box attacks, finding a similar surrogate model to generate effective black-box attacks, and stealing the knowledge of on-device models. It is a proactive method to protect the on-device models.

- We design five obfuscation strategies for protecting on-device models and provide an end2end prototype tool, *ModelObfuscator*. This tool automatically obfuscates the model and builds a compatible DL software library. The tool is open-source available.

- We provide a taxonomy and comparison of different obfuscation methods in terms of effectiveness and overhead, to guide model owners in choosing appropriate defense strategies.

## 2 RELATED WORK

**Adversarial Attacks:** Depending on the knowledge required by the adversary, adversarial attacks can be categorized into white-box attacks such as gradient-based attacks (Croce & Hein, 2020; Goodfellow et al., 2015; Kurakin et al., 2017; Papernot et al., 2016; Moosavi-Dezfooli et al., 2016; Madry et al., 2018; Moosavi-Dezfooli et al., 2017), and black-box attacks such as query-based attacks (Chen et al., 2017a; Ilyas et al., 2018a;b; Guo et al., 2019; Brendel et al., 2017; Cheng et al., 2018; Chen et al., 2020; Mopuri et al., 2018). For the gradient-based attack, FGSM (Goodfellow et al., 2015) and its iterative version BIM (Kurakin et al., 2017) compute the sign of the gradient direction to construct the perturbation. DeepFool (Moosavi-Dezfooli et al., 2016) is designed to optimize the direction for crossing the decision boundary, while C&W (Carlini & Wagner, 2017) introduced a way to craft with minimal $\ell_p$ norm perturbations distance. For query-based attacks,

Figure 1: The working process of our *ModelObfuscator* on-device DL model obfuscation tool.

Boundary Attack (Brendel et al., 2017) and HopSkipJump (Chen et al., 2020) estimate the gradients based on zeroth-order optimization methods. White-box attacks have full access to the model structure and its parameters. In black-box attacks, only partial information about the model is available. Goodfellow *et al.*, (Goodfellow et al., 2015) show that adversarial examples have transferability, meaning that adversarial examples generated by surrogate models (Papernot et al., 2017; Zhou et al., 2020) can be used to fool the target model. Therefore, for adversarial attacks on devices, Huang *et al.*, (Huang et al., 2021) and Cao *et al.*, (Cao et al., 2021) evaluated the robustness of mobile models by applying the existing attacks generated from surrogate models.

**Defences**   Prior studies such as adversarial training (Tramèr et al., 2017; Shafahi et al., 2019; Wong et al., 2020) proposed a training scheme to secure the DL models. While some other papers focus on eliminating the effect of the attacks. For instance, they use input restoration (Liao et al., 2018; Zhou et al., 2021) and randomization (Dhillon et al., 2018; Xie et al., 2017) to defend against adversarial attacks. In addition, attack detection is also a promising technique to distinguish the harmful inputs (Ma et al., 2018). For defending against model extraction and intellectual property leakage, watermarking methods are proposed to detect intellectual property stealing (Yang et al., 2019; Fan et al., 2019; Lukas et al., 2019). These works are reactive defences for deployed model.

**Code obfuscation:**   Many code obfuscation methods are motivated by protecting intellectual property and defence against reverse engineering (Collberg & Thomborson, 2002). They provide complex obfuscating algorithms for programs like JAVA code (Collberg et al., 1997; 1998), including robust methods for high-level languages (Wang, 2001) and machine code level (Wroblewski, 2002) obfuscation. Code obfuscation is a well-developed technique to secure the source code. However, we cannot simply apply code obfuscation to prevent reverse engineering for on-device DL models. On-device models are usually developed using common open-source DL libraries like TensorFlow Lite. Key model information is stored in a model file that needs to be compatible with the DL framework. In this work, inspired by code obfuscation, we propose to obfuscate the information at model level and then produce a compatible DL library for the obfuscated model.

## 3  METHODOLOGY

We chose the TensorFlow Lite (TFLite) platform to demonstrate our model obfuscation approach. TFLite is currently the most commonly used on-device DL platform. The steps to produce TFLite models are shown in the top half of Figure 1. Usually, DL developers use TensorFlow application programming interfaces (APIs) to define and train the TensorFlow (TF) model. The trained TF model is then compiled to a TFLite model. Note that TFLite has different implementations with TF, their operators (*i.e.*, layers) may not be compatible [1]. Therefore, the TFLite library will check the compatibility during compilation. Once the compatibility check passed, the compiled TFLite model can run on devices using the TFLite library. Hence, the problem of obfuscating TFLite models is to design obfuscation strategies and make the obfuscated model compatible with the TFLite library.

We analyzed the current mainstream DL platforms (*i.e.*, TensorFlow and PyTorch) and identified the following two main findings. First, these platforms are open-source and provide a set of tools to build

---

[1]https://www.tensorflow.org/lite/guide/ops_compatibility

the library (*e.g.*, TFLite library) from the source code. Second, they officially support customized operators (*e.g.*, neural layers). Specifically, on top of these DL platforms, users could implement customized layers in C/C++ and compile customized layers to executing files (`.so` file in TensorFlow). Then, users can use these customized layers via high-level Python interfaces. Those features enable us to design obfuscation techniques to obfuscate model and DL library code together. The bottom half of Figure 1 shows the overview of our model obfuscation framework. Specifically, *ModelObfuscator* has three main steps: (1) model parsing, (2) model obfuscation, and (3) model assembling & library recompilation. In the following subsections, we detail our proposed *ModelObfuscator*.

## 3.1 MODEL PARSING

The first step of *ModelObfuscator* model obfuscation is to parse the deployed model to extract its key information. *ModelObfuscator* first extracts the structure information of each layer, including the name of layers (*e.g.*, `Conv2D`) and model structures (including model's input, output, layer ID and *etc.*). The extracted structure information are depicted using a data structure as shown in the right example. Then, *ModelObfuscator* will extract the parameter of each layer. Moreover, *ModelObfuscator*

| Minimal model structure |
|---|
| {
    "Layer name": "Conv2D",
    "Input": [0],
    "Output": [1],
    "ID": 0,
}
... |

will identify the source code used by each layer by referring to the underlying libraries. The identified source code includes relevant packages or functions of the TFLite layers.

## 3.2 MODEL OBFUSCATION

After getting the model information and corresponding source codes, *ModelObfuscator* will obfuscate the model as well as the source codes. *ModelObfuscator* uses five obfuscation strategies: *renaming*, *parameter encapsulation*, *neural structure obfuscation*, *shortcut injection*, and *extra layer injection*.

| Obfuscated minimal model structure |
|---|
| {
    "Layer name": "Tbuszp",
    "Input": [0],
    "Output": [1],
    "ID": 0,
}
... |

| Source code registration (C/C++ code) |
|---|
| TfLiteRegistration* Register_Conv2D()
↓
TfLiteRegistration* Register_Tbuszp() |

***Renaming*** The most straightforward obfuscation strategy is the renaming of a layer. Usually, the layer's name contains important information, which is the function of this layer. For instance, "Conv2D" indicates a 2D convolution layer. Such information is useful for adversaries to reconstruct the model to generate white-box attacks or to obtain a similar surrogate model to conduct effective black-box attacks. To hide such important information, we randomly change each model layer's name. On the right is an example of an obfuscated `Conv2D` layer. *ModelObfuscator* automatically replaces the real name with the random meaningless string `Tbuszp`. Meanwhile, *ModelObfuscator* creates a copy of `Conv2D`'s source code and replaces the layer name (*i.e.*, `Conv2D`) in the source code with `Tbuszp`. Note that we modify the duplicate of `Conv2D` in case the modification affects other parts of the TFLite library. After adding modified source codes into the TFLite project, the recompiled TFLite library will recognize obfuscated layers as custom layers and correctly execute them at runtime.

***Parameter encapsulation*** Existing TFLite models have two main assets: model structure and parameters. The parameter can be obtained in the training period. Given an input, a TFLite model will compute the results using the input tensor and parameters that are stored in the model file. As we discussed above, parameter exposure is very dangerous. An adversary could use the parameter information to perform many kinds of white-box attacks, *e.g.*, adversarial attacks and model inversion attacks. Besides, an adversary can guess the function of this layer according to the shape of the parameter, because different layers have different numbers of parameters (*e.g.*, two in the convolution layer) and different shapes of parameters (*e.g.*, $(3, 3, 64)$ in the convolution layer).

To hide key model parameter information, we instead encapsulate parameters into their corresponding generated custom source codes of the obfuscated layer. For example, for a simple one-layer feed-forward neural network, the output can be computed by $Y = \theta(W^T X + b)$, where $X$, $W$, and $b$ is input tensor, parameter of the layer, and bias, respectively. $\theta$ is the activation for neural nodes. For *ModelObfuscator* obfuscation, the network layer can be disguised as $Y = g(X)$, where $g$ is an unknown function. We then implement the correct computation (*i.e.*, $g$) in the generated

Figure 2: Neural structure obfuscation for a simple feed-forward neural network.

Figure 3: Example of shortcut injection and extra layer injection for the TFLite model extract from a real-world app. (a) part of the original model. (b) the corresponding obfuscated model. This visualization is generated by Netron (Roeder, 2017).

custom TFLite source code, which we then obfuscate. At runtime, function $g$ will be invoked to achieve the computation from $\boldsymbol{X}$ to $\boldsymbol{Y}$. Now an adversary is unable to extract the key parameter information from our obfuscated model. Furthermore, the implementation of $g$ can be obfuscated using transitional and well-proven code obfuscation strategies (Collberg & Thomborson, 2002). After compiling the modified TFLite, adversaries will find it very hard to identify key model parameters by reverse engineering the compiled library.

***Neural structure obfuscation*** Just obfuscating layer names and parameters is not enough, since an adversary may still infer the function of each layer according to the model structure. For instance, Figure 2(a) presents the structure of the neural network, where the input, hidden and output layers include four, two, and one node, respectively. Attacker could search for a surrogate model according to the neural architecture. To solve this problem, *ModelObfuscator* uses *neural structure obfuscation* to obfuscated neural architecture with the goal of confusing the adversary. We propose two strategies for network structure obfuscation: *random* and *align-to-largest*. Given a model with output shapes $\boldsymbol{s} = (s_0, \cdots, s_n)$, where $s_n$ refers to the number of dimensions for the $n$-th channel, the random strategy generate a random shape $\mathbf{r} = (\mathrm{r}_0, \cdots, \mathrm{r}_n)$ of the output for each layer. Figure 2(b) shows an obfuscated model of Figure 2(a) using random strategy. Second, the align-to-largest strategy finds the largest output shape $\boldsymbol{s}'$ and then fill the output shapes of other layers to the size of $\boldsymbol{s}'$. Figure 2(c) shows such an obfuscated model, where the output shapes of each layer are filled up to $(4)$. Note that this will not affect the performance of models because the modified TFLite library will not compute the output using the provided neural structure information.

***Shortcut injection & extra layer injection*** Neural structure obfuscation changes the network structure by inserting new nodes, but the spatial relationships of original layers remain the same. Therefore, even with the above three obfuscation strategies, the adversary can still infer node information by analyzing the spatial relationships of runtime data (*e.g.*, actual input-output values of each node). To further obfuscate the model structure, hence, *ModelObfuscator* applies two more strategies: shortcut and extra layer injection. The injected shortcut and extra layers would destroy the original spatial relationships of TFLite models.

To automatically inject random shortcuts, *ModelObfuscator* first randomly select a shortcut pair $(\mathrm{r}_1, \mathrm{r}_2)$. The outputs of $\mathrm{r}_1$-th layer are then added to the input list of $\mathrm{r}_2$-th layer. For example, the blue solid line in Figure 3(b) is a shortcut inserted into the model extracted from a fruit recognition app, which connects the 2-nd convolution layer and the 5-th convolution layer. Second, to inject extra layers, just like the shortcut injection, *ModelObfuscator* randomly picks a layer pair $(\mathrm{r}'_1, \mathrm{r}'_2)$.

Table 1: The obfuscation error of the proposed model obfuscation method. 'Error': the output difference between the original model and the obfuscated model.

| | ① | ② | ③ | ④ | ⑤ | ⑥ | ⑦ | ⑧ | ⑨ | ⑩ | **Average** |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Error | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |

The input of the extra layer is the output node list of $r'_1$-th layer, and its output is added to the input list of $r'_2$-th layer. For instance, an extra layer `Ypxumu` (as shown in the red dotted line in Figure 3(b)) is injected between the 2-nd and 3-rd convolution layers.

Note that the injected shortcut and layers will not affect the prediction results of the deployed model because the modified TFLite library will ignore the obfuscation part (*e.g.*, `Ypxumu` layers) in model inference. Specifically, the extra layer $Y = f(X)$ just needs to create the output with a specific shape to confuse the adversary. In addition, extra layer injection will not significantly increase the latency of on-device models because the extra layer does not need much computational resources.

***Combine five obfuscation strategies*** The proposed five obfuscation strategies are applied to the target model sequentially. Figure 3 show an example, where Figure 3(a) is the original model, while Figure 3(b) shows the final obfuscated model. The structure and parameters of the obfuscated model are quite different from that of the original model, which will make the obfuscated model hard to attack. To prevent an adversary from parsing the obfuscated model through reverse engineering the modified TFLite library and customized layers, we use code obfuscation strategies, a well-developed technology to make the code unreadable and unable to be reverse engineered (Appendix B). The combination of model and code obfuscation would hide the key information of models.

### 3.3 MODEL ASSEMBLING AND LIBRARY RECOMPILATION

After obtaining the obfuscated model and modified TFLite source codes, *ModelObfuscator* assembles the new obfuscated model using the obfuscated model structure and then recompiles the modified TFLite library to support the newly generated obfuscated model.

## 4 EVALUATION

### 4.1 EXPERIMENTAL SETTING

**Dataset** To evaluate *ModelObfuscator*'s performance on models with various structures for multiple tasks, we collected 10 TFLite models including a fruit recognition model, a skin cancer diagnosis model, MobileNet (Howard et al., 2017), MNASNet (Tan et al., 2019), SqueezeNet (Iandola et al., 2016), EfficientNet (Tan & Le, 2019), MiDaS (Ranftl et al., 2020), Inception-ResNetV2, PoseNet (Kendall et al., 2015), and SSD (Liu et al., 2016), which are referred to as model ① - ⑩, respectively. The fruit recognition and skin cancer diagnosis model were collected from Android apps (see the provided code repository). The other models were collected from the TensorFlow Hub [2].

**Experimental Environment** *ModelObfuscator* is evaluated on a workstation with Intel(R) Xeon(R) W-2175 2.50GHz CPU, 32GB RAM, and Ubuntu 20.04.1 operating system.

### 4.2 EFFECTIVENESS OF *ModelObfuscator*

We first evaluate the effectiveness of *ModelObfuscator*. Ideally, *ModelObfuscator* should not affect the prediction accuracy of the original models, while providing sufficient defense against model attacks. To this end, we apply all five proposed obfuscation strategies to each model and compare the prediction results based on 1,000 randomly generated inputs. The obfuscation error is calculated as $||y-y'||_2$, where $y$ and $y'$ is the output of original models and obfuscated models, respectively. Note that the number of extra layers and shortcuts is set to 30 in *shortcut injection & extra layer injection*. Table 1 demonstrates that *ModelObfuscator* **model obfuscation strategies have no impact on the prediction results of the original models**.

To show the effectiveness of *ModelObfuscator* in hiding the model's key information, we try to extract the information of obfuscated models using five well-known model conversion/parsing tools.

---

[2]`https://tfhub.dev/`

Table 2: The success number of existing tools in extracting model information with each obfuscation strategy. '*Basic obfuscation*': *renaming + parameter encapsulation*.

|  | TF-ONNX | TFLite2ONNX | TFLite2TF | TFLite-tools | App Attack |
|---|---|---|---|---|---|
| Original | 10 | 9 | 9 | 10 | 8 |
| *Renaming* | 0 | 0 | 0 | 0 | 8 |
| *Parameter encapsulation* | 0 | 0 | 0 | 0 | 2 |
| *Neural structure* | 0 | 0 | 0 | 0 | 8 |
| *Shortcut injection* | 0 | 0 | 0 | 0 | 8 |
| *Extra layer injection* | 0 | 0 | 0 | 0 | 8 |
| *Basic obfuscation* | 0 | 0 | 0 | 0 | 0 |

The tools include TF-ONNX (Developers, 2022) TFLite2ONNX (Wang, 2021), TFLite2TF (Hyodo, 2022), TFLite-tools (Liberis, 2022), and Smart App Attack (Huang & Chen, 2022), which is proposed to attack the on-device models. In this experiment, we apply the basic obfuscation strategies *renaming* and *parameter encapsulation* on the original models. For model conversion tools, if they can successfully convert the model format, we consider it a success case for extracting the model information. If *ModelObfuscator* method is effective, these tools cannot work on the models. For the app attacking method, if it can correctly identify the model that has the same model structure with the on-device model on TensorFlow Hub, we consider it a success case. If *ModelObfuscator* is effective, this tool should not be able to identify the surrogate model on TensorFlow Hub. As shown in Table 2, **two basic obfuscation strategies can prevent all existing model extraction tools from parsing the deployed TFLite model**. Besides, parameter encapsulation could prevent App Attack from finding surrogate models on 6 models. When combining renaming and *Parameter encapsulation*, the App Attack on all the models can be prevented. However, except for *parameter encapsulation*, applying other strategies separately does not confuse the App Attack, because App Attack can identify the same model through the parameter comparison.

Figure 4: Visualization of structure obfuscation for LeNet. (a) original data flow of LeNet (b) obfuscated model with one shortcut and extra layer (c) obfuscated model with three shortcuts and three extra layers. Red dotted line and red dotted block represent injected shortcut and extra layer.

As we discussed above, adversaries may infer the functionality of each layer by analyzing the structure and data flows of the model. To demonstrate the capability of *ModelObfuscator* in obfuscating the model structure and data flows, we show a visualization of LeNet (LeCun et al., 1998) before and after applying *Shortcut injection & extra layer injection*. The visualization of model structure and data flows before and after obfuscation are shown in Figure 4. As can be seen, **it is difficult to recognize the shortcut or extra layer without prior knowledge of the model structure**. When a large number (*e.g.*, more than 30) of shortcuts and extra layers is used to obfuscate the TFLite, the structure of the obfuscated model will become extremely unreadable (Figure 7). Therefore, the *shortcut* and *extra layer injection* are effective in making it extremely difficult for an adversary to understand the model structure.

### 4.3 EFFICIENCY OF *ModelObfuscator*

We evaluate the efficiency of *ModelObfuscator* obfuscation strategies by demonstrating the runtime overhead of each model in our dataset. Specifically, we report both the time overhead and memory overhead of the proposed obfuscation method under various settings based on 1,000 randomly generated instances. The results of time and memory overhead are shown in Table 3 and

Table 3: Time overhead (seconds per 1000 inputs) of the original model and obfuscated model. We use five obfuscation strategies. '$(n_1, n_2)$': obfuscated models with $n_1$ shortcuts and $n_2$ extra layers.

| | ① | ② | ③ | ④ | ⑤ | ⑥ | ⑦ | ⑧ | ⑨ | ⑩ | **Average** |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Original | 30.3 | 98.5 | 62.1 | 72.5 | 33.4 | 81.2 | 346.6 | 247.4 | 130.4 | 231.2 | **133.4** |
| (0, 0) | 30.4 | 98.7 | 61.1 | 70.4 | 33.5 | 82.3 | 346.4 | 247.0 | 130.7 | 232.1 | **133.3** |
| (30, 0) | 30.7 | 97.9 | 62.3 | 72.7 | 33.1 | 82.0 | 346.9 | 247.1 | 130.2 | 231.0 | **133.4** |
| (0, 10) | 30.2 | 98.6 | 61.1 | 74.1 | 34.9 | 82.3 | 346.7 | 251.5 | 130.9 | 231.6 | **134.2** |
| (0, 20) | 30.6 | 98.3 | 63.3 | 74.1 | 36.8 | 81.3 | 348.2 | 247.1 | 130.5 | 231.3 | **134.2** |
| (0, 30) | 30.4 | 98.5 | 63.2 | 74.6 | 34.5 | 82.8 | 349.0 | 251.9 | 130.4 | 236.7 | **135.2** |

Table 4: Overhead of the model obfuscation on random access memory (RAM) cost (Mb per model). We use five obfuscation strategies. To eliminate the influence of other processes on the test machine, we show the increment of RAM usage for the model inference.

| | ① | ② | ③ | ④ | ⑤ | ⑥ | ⑦ | ⑧ | ⑨ | ⑩ | **Average** |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Original | 18.8 | 49.5 | 33.1 | 46.5 | 41.3 | 51.9 | 241.1 | 373.8 | 39.4 | 97.8 | **99.3** |
| (0, 0) | 18.9 | 53.3 | 33.1 | 49.9 | 45.5 | 56.8 | 244.8 | 381.2 | 40.6 | 99.8 | **102.4** |
| (30, 0) | 18.7 | 51.4 | 32.6 | 49.5 | 46.0 | 55.8 | 244.6 | 381.6 | 40.3 | 100.2 | **102.0** |
| (0, 10) | 25.9 | 58.8 | 42.5 | 53.6 | 49.2 | 69.5 | 248.1 | 386.7 | 55.0 | 107.5 | **109.7** |
| (0, 20) | 30.0 | 67.3 | 50.4 | 56.7 | 56.0 | 66.2 | 253.1 | 387.7 | 66.9 | 112.0 | **114.6** |
| (0, 30) | 35.9 | 81.9 | 55.2 | 57.3 | 71.6 | 73.0 | 267.7 | 397.3 | 73.4 | 123.8 | **123.71** |

Table 4, respectively. '$(n_1, n_2)$' in the table indicates the the number of shortcuts ($n_1$) and number of extra layers ($n_2$) applied, where $(0, 0)$ indicates only the basic obfuscations (*i.e.*, renaming, parameter encapsulation) and neural structure are involved. We also include the time and memory consumption of the original models as the baseline. As shown in Table 3, even though extra layers are injected into the obfuscated model, ***ModelObfuscator* obfuscated models incur a negligible time overhead** (*i.e.*, approximately 1% on average for the most time-consuming obfuscation). The differences between using various obfuscation settings are also not significant. Because the *parameter encapsulation* will remove some data processing steps in the source code of APIs, the basic obfuscation ('(0,0)' in Table 3) may reduce the latency of TFLite models.

The memory overhead for *ModelObfuscator* obfuscated models is shown in Table 4. To eliminate the impact of different memory optimization methods, we use peak RAM usage where the model preserves all intermediate tensors. It can be seen that the other obfuscation strategies do not affect memory usage except for the *extra layer injection*. Memory usage increases when the number of extra layers increases. Therefore, a trade-off between the complexity of the obfuscation and the memory overhead is worth considering when choosing the obfuscation strategy. Nevertheless, we argue that even with the most complex settings in our experiment, which provide sufficient protection to the original model, **the memory overhead is acceptable (approximately 20%)**.

Table 5: Size change (Mb) of the TFLite library and models after the obfuscation. The size of the obfuscated model is reduced to a few Kb. The original library size is 191.5 Mb. '+' and '-' refer to the increase and decrease, respectively.

| | ① | ② | ③ | ④ | ⑤ | ⑥ | ⑦ | ⑧ | ⑨ | ⑩ |
|---|---|---|---|---|---|---|---|---|---|---|
| library-all | +8.7 | +31.9 | +19.6 | +38.7 | +8.8 | +40.6 | +126.1 | +231.8 | +9.7 | +52.1 |
| model | -5.5 | -16.9 | -10.3 | -17.5 | -5.0 | -18.6 | -66.3 | -121.1 | -5.0 | -27.5 |
| total | +3.2 | +15.0 | +9.3 | +21.2 | +3.8 | +22.0 | +59.8 | +110.7 | +4.7 | +24.4 |
| library-renaming | +8.7 | +31.9 | +19.6 | +38.7 | +8.8 | +40.6 | +126.1 | +231.7 | +9.7 | +52.1 |

Considering that the models are deployed on mobile devices that have limited storage space, we also present the size differences of the modified TFLite software library and the obfuscated models. Note that the size change is caused by creating additional `.so` files to support the inference of the obfuscated layer. Hence, the size difference will be the same with different implementations (*e.g.*, Python, Java). Table5 shows the size change to the TFLite software library and the TFLite models after applying *ModelObfuscator* obfuscation strategies. We use all obfuscation strategies in this experiment and the number of injecting shortcuts and extra layers is 30. Our results show that **the library size change is mainly caused by the *renaming* method**, because it will create a new API for the renamed layer in TFLite library. In addition, the *extra layer injection* will also increase the

Figure 5: Taxonomy of model obfuscation methods.

size of library because it will create the new API to support the extra layer. As the extra layer just has simple function, the affect of the *extra layer injection* is negligible. Our obfuscation strategies **significantly reduce the size of the TFLite model file** because it only keeps the obfuscated minimal structure information. However, **the size of the TFLite library is significantly increased**, and increases the size of the application deployed on the mobile device.

## 5 DISCUSSION

**Taxonomy of model obfuscation methods**   In this paper, we proposed five different model obfuscation strategies. Figure 5 shows a preliminary taxonomy of the different model obfuscation methods and the best practice for model deployment. First, developers can use the *renaming* and *parameter encapsulation* to prevent most model parsing or reverse engineering tools from extracting the information of the deployed model. In the scenarios that computational costs are critical, developers can use the *neural structure obfuscation* and *shortcut injection*, as they do not introduce additional overhead. For structure obfuscation, developers can use *neural structure obfuscation*, *shortcut injection*, and *extra layer injection*. These three methods can significantly increase the difficulty of understanding the data flow of the deployed models. In addition, developers can use *renaming* and *neural structure obfuscation* to disguise the deployed model, which can mislead the adversary into choosing the wrong architecture to produce a surrogate model. If the size of the app package is critical (e.g., deploying the model on devices with limited storage), developers need to carefully consider the trade-off between the number of obfuscated layers leveraging *extra layer injection* with *renaming*. The reason is that if *renaming* is used to create a different obfuscated layer for every layer, *ModelObfuscator* will need to create the corresponding APIs in the TFLite library to support the obfuscated layers, hence increasing the size of the library.

**Limitations**   Although the proposed model obfuscation does not introduce significant computational overhead, our method does have a limitation, *i.e.*, the size increase of the modified TFLite library. This is because we need to provide support for the new obfuscations made. For a huge network like a 1000-layer network deployed model (although it is not practical for on-device deployment considering current device capacity), the size of the modified TFLite library will significantly increase if we rename every layer. As a result, the app package also increases as the modified TFLite library will also need to be deployed on the device.

## 6 CONCLUSION

In this work, we analyzed the risk of deep learning models deployed on mobile devices. Adversaries can extract information from the deployed model to perform white-box attacks, identify surrogate models for black-box attacks, or steal its intellectual property. To this end, we proposed a model obfuscation framework to secure the deployment of DL models. Model obfuscation is a proactive defense to protect the deployed model. We utilized five obfuscation methods to obfuscate the information of the deployed model, *i.e.*, *renaming*, *parameter encapsulation*, *neural node obfuscation*, *shortcut injection*, and *extra layer injection*. We developed a prototype tool *ModelObfuscator* to automatically obfuscate a TFLite model and produce a modified TFLite library that is compatible with the obfuscated model. Experiments show that our method is effective in resisting the model parsing tools without performance sacrifice. Considering the negligible extra resources required, and the extra security it achieves, we believe that model obfuscation has the potential to be a fundamental step for on-device model deployment in the future. We hope DL frameworks like TensorFlow can officially support this technology. Moreover, optimizing model obfuscation to avoid overhead is worthwhile to be explored.

REFERENCES

Peva Blanchard, El Mahdi El Mhamdi, Rachid Guerraoui, and Julien Stainer. Machine learning with adversaries: Byzantine tolerant gradient descent. *Advances in Neural Information Processing Systems*, 30, 2017.

Wieland Brendel, Jonas Rauber, and Matthias Bethge. Decision-based adversarial attacks: Reliable attacks against black-box machine learning models. *arXiv preprint arXiv:1712.04248*, 2017.

Hongchen Cao, Shuai Li, Yuming Zhou, Ming Fan, Xuejiao Zhao, and Yutian Tang. Towards black-box attacks on deep learning apps. *arXiv preprint arXiv:2107.12732*, 2021.

Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks. In *2017 IEEE Symposium on Security and Privacy (SP)*, pp. 39–57. IEEE, 2017.

Jianbo Chen, Michael I Jordan, and Martin J Wainwright. Hopskipjumpattack: A query-efficient decision-based attack. In *2020 ieee symposium on security and privacy (sp)*, pp. 1277–1294. IEEE, 2020.

Pin-Yu Chen, Huan Zhang, Yash Sharma, Jinfeng Yi, and Cho-Jui Hsieh. Zoo: Zeroth order optimization based black-box attacks to deep neural networks without training substitute models. In *Proceedings of the 10th ACM Workshop on Artificial Intelligence and Security*, pp. 15–26. ACM, 2017a.

Xinyun Chen, Chang Liu, Bo Li, Kimberly Lu, and Dawn Song. Targeted backdoor attacks on deep learning systems using data poisoning. *arXiv preprint arXiv:1712.05526*, 2017b.

Minhao Cheng, Thong Le, Pin-Yu Chen, Jinfeng Yi, Huan Zhang, and Cho-Jui Hsieh. Query-efficient hard-label black-box attack: An optimization-based approach. *arXiv preprint arXiv:1807.04457*, 2018.

Christian Collberg, Clark Thomborson, and Douglas Low. A taxonomy of obfuscating transformations, 1997.

Christian Collberg, Clark Thomborson, and Douglas Low. Manufacturing cheap, resilient, and stealthy opaque constructs. In *Proceedings of the 25th ACM SIGPLAN-SIGACT symposium on Principles of programming languages*, pp. 184–196, 1998.

Christian S. Collberg and Clark Thomborson. Watermarking, tamper-proofing, and obfuscation-tools for software protection. *IEEE Transactions on software engineering*, 28(8):735–746, 2002.

Francesco Croce and Matthias Hein. Reliable evaluation of adversarial robustness with an ensemble of diverse parameter-free attacks. In *International conference on machine learning*, pp. 2206–2216. PMLR, 2020.

Developers. tf2onnx - Convert TensorFlow, Keras, Tensorflow.js and Tflite models to ONN, August 2022. URL https://github.com/onnx/tensorflow-onnx.

ONNX developers. Onnx. https://github.com/onnx/onnx, 2022. Version: 1.12.0.

Guneet S Dhillon, Kamyar Azizzadenesheli, Zachary C Lipton, Jeremy Bernstein, Jean Kossaifi, Aran Khanna, and Anima Anandkumar. Stochastic activation pruning for robust adversarial defense. *arXiv preprint arXiv:1803.01442*, 2018.

Lixin Fan, Kam Woh Ng, and Chee Seng Chan. Rethinking deep neural network ownership verification: Embedding passports to defeat ambiguity attacks. *Advances in neural information processing systems*, 32, 2019.

Minghong Fang, Xiaoyu Cao, Jinyuan Jia, and Neil Gong. Local model poisoning attacks to {Byzantine-Robust} federated learning. In *29th USENIX Security Symposium (USENIX Security 20)*, pp. 1605–1622, 2020.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *ICLR*, 2015.

Chuan Guo, Jacob Gardner, Yurong You, Andrew Gordon Wilson, and Kilian Weinberger. Simple black-box adversarial attacks. In *International Conference on Machine Learning*, pp. 2484–2493, 2019.

Andrew G Howard, Menglong Zhu, Bo Chen, Dmitry Kalenichenko, Weijun Wang, Tobias Weyand, Marco Andreetto, and Hartwig Adam. Mobilenets: Efficient convolutional neural networks for mobile vision applications. *arXiv preprint arXiv:1704.04861*, 2017.

Yujin Huang and Chunyang Chen. Smart app attack: Hacking deep learning models in android apps. *IEEE Transactions on Information Forensics and Security*, 17:1827–1840, 2022.

Yujin Huang, Han Hu, and Chunyang Chen. Robustness of on-device models: Adversarial attack to deep learning models on android apps. In *2021 IEEE/ACM 43rd International Conference on Software Engineering: Software Engineering in Practice (ICSE-SEIP)*, pp. 101–110. IEEE, 2021.

Katsuya Hyodo. tflite2tensorflow, 2022. URL `https://github.com/PINTO0309/tflite2tensorflow`.

Forrest N Iandola, Song Han, Matthew W Moskewicz, Khalid Ashraf, William J Dally, and Kurt Keutzer. Squeezenet: Alexnet-level accuracy with 50x fewer parameters and¡ 0.5 mb model size. *arXiv preprint arXiv:1602.07360*, 2016.

Andrew Ilyas, Logan Engstrom, Anish Athalye, and Jessy Lin. Black-box adversarial attacks with limited queries and information. In *ICML*, pp. 2142–2151, 2018a.

Andrew Ilyas, Logan Engstrom, and Aleksander Madry. Prior convictions: Black-box adversarial attacks with bandits and priors. *arXiv preprint arXiv:1807.07978*, 2018b.

Alex Kendall, Matthew Grimes, and Roberto Cipolla. Posenet: A convolutional network for real-time 6-dof camera relocalization. In *Proceedings of the IEEE international conference on computer vision*, pp. 2938–2946, 2015.

Alexey Kurakin, Ian Goodfellow, and Samy Bengio. Adversarial examples in the physical world. *International Conference on Learning Representations (ICLR)*, 2017.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Yuanchun Li, Jiayi Hua, Haoyu Wang, Chunyang Chen, and Yunxin Liu. Deeppayload: Black-box backdoor attack on deep learning models through neural payload injection. In *2021 IEEE/ACM 43rd International Conference on Software Engineering (ICSE)*, pp. 263–274. IEEE, 2021.

Fangzhou Liao, Ming Liang, Yinpeng Dong, Tianyu Pang, Xiaolin Hu, and Jun Zhu. Defense against adversarial attacks using high-level representation guided denoiser. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1778–1787, 2018.

Edgar Liberis. tflite-tools, February 2022. URL `https://github.com/eliberis/tflite-tools`.

Wei Liu, Dragomir Anguelov, Dumitru Erhan, Christian Szegedy, Scott Reed, Cheng-Yang Fu, and Alexander C Berg. Ssd: Single shot multibox detector. In *European conference on computer vision*, pp. 21–37. Springer, 2016.

Nils Lukas, Yuxuan Zhang, and Florian Kerschbaum. Deep neural network fingerprinting by conferrable adversarial examples. *arXiv preprint arXiv:1912.00888*, 2019.

Xingjun Ma, Bo Li, Yisen Wang, Sarah M Erfani, Sudanthi Wijewickrema, Grant Schoenebeck, Dawn Song, Michael E Houle, and James Bailey. Characterizing adversarial subspaces using local intrinsic dimensionality. *arXiv preprint arXiv:1801.02613*, 2018.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *International Conference on Learning Representations(ICLR)*, 2018. URL `https://openreview.net/forum?id=rJzIBfZAb`.

Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, and Pascal Frossard. Deepfool: a simple and accurate method to fool deep neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2574–2582, 2016.

Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, Omar Fawzi, and Pascal Frossard. Universal adversarial perturbations. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1765–1773, 2017.

Konda Reddy Mopuri, Phani Krishna Uppala, and R Venkatesh Babu. Ask, acquire, and attack: Data-free uap generation using class impressions. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 19–34, 2018.

Nicolas Papernot, Patrick McDaniel, Somesh Jha, Matt Fredrikson, Z Berkay Celik, and Ananthram Swami. The limitations of deep learning in adversarial settings. In *2016 IEEE European Symposium on Security and Privacy (EuroS&P)*, pp. 372–387. IEEE, 2016.

Nicolas Papernot, Patrick McDaniel, Ian Goodfellow, Somesh Jha, Z Berkay Celik, and Ananthram Swami. Practical black-box attacks against machine learning. In *Proceedings of the 2017 ACM on Asia conference on computer and communications security*, pp. 506–519, 2017.

René Ranftl, Katrin Lasinger, David Hafner, Konrad Schindler, and Vladlen Koltun. Towards robust monocular depth estimation: Mixing datasets for zero-shot cross-dataset transfer. *IEEE transactions on pattern analysis and machine intelligence*, 2020.

Lutz Roeder. Netron, Visualizer for neural network, deep learning, and machine learning models, December 2017. URL `https://doi.org/10.5281/zenodo.7109451`. If you use Netron in your research, please cite it using these metadata.

Ali Shafahi, W Ronny Huang, Mahyar Najibi, Octavian Suciu, Christoph Studer, Tudor Dumitras, and Tom Goldstein. Poison frogs! targeted clean-label poisoning attacks on neural networks. *Advances in neural information processing systems*, 31, 2018.

Ali Shafahi, Mahyar Najibi, Mohammad Amin Ghiasi, Zheng Xu, John Dickerson, Christoph Studer, Larry S Davis, Gavin Taylor, and Tom Goldstein. Adversarial training for free! *Advances in Neural Information Processing Systems*, 32, 2019.

Reza Shokri, Marco Stronati, Congzheng Song, and Vitaly Shmatikov. Membership inference attacks against machine learning models. In *2017 IEEE symposium on security and privacy (SP)*, pp. 3–18. IEEE, 2017.

Zhichuang Sun, Ruimin Sun, Long Lu, and Alan Mislove. Mind your weight (s): A large-scale study on insufficient machine learning model protection in mobile apps. In *30th USENIX Security Symposium (USENIX Security 21)*, pp. 1955–1972, 2021.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *International conference on machine learning*, pp. 6105–6114. PMLR, 2019.

Mingxing Tan, Bo Chen, Ruoming Pang, Vijay Vasudevan, Mark Sandler, Andrew Howard, and Quoc V Le. Mnasnet: Platform-aware neural architecture search for mobile. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 2820–2828, 2019.

Florian Tramèr, Alexey Kurakin, Nicolas Papernot, Ian Goodfellow, Dan Boneh, and Patrick McDaniel. Ensemble adversarial training: Attacks and defenses. *arXiv preprint arXiv:1705.07204*, 2017.

Chenxi Wang. *A security architecture for survivability mechanisms*. University of Virginia, 2001.

Zhenhua Wang. tflite2onnx - Convert TensorFlow Lite models to ONNX, August 2021. URL `https://github.com/jackwish/tflite2onnx`.

Eric Wong, Leslie Rice, and J Zico Kolter. Fast is better than free: Revisiting adversarial training. *arXiv preprint arXiv:2001.03994*, 2020.

Gregory Wroblewski. General method of program code obfuscation. 2002.

Cihang Xie, Jianyu Wang, Zhishuai Zhang, Zhou Ren, and Alan Yuille. Mitigating adversarial effects through randomization. *arXiv preprint arXiv:1711.01991*, 2017.

Mengwei Xu, Jiawei Liu, Yuanqiang Liu, Felix Xiaozhu Lin, Yunxin Liu, and Xuanzhe Liu. A first look at deep learning apps on smartphones. In *The World Wide Web Conference*, pp. 2125–2136, 2019.

Ziqi Yang, Hung Dang, and Ee-Chien Chang. Effectiveness of distillation attack and countermeasure on neural network watermarking. *arXiv preprint arXiv:1906.06046*, 2019.

Dawei Zhou, Tongliang Liu, Bo Han, Nannan Wang, Chunlei Peng, and Xinbo Gao. Towards defending against adversarial examples via attack-invariant features. In *International Conference on Machine Learning*, pp. 12835–12845. PMLR, 2021.

Mingyi Zhou, Jing Wu, Yipeng Liu, Shuaicheng Liu, and Ce Zhu. Dast: Data-free substitute training for adversarial attacks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 234–243, 2020.

## A APPENDIX - THE VISUALIZATION OF THE MODEL OBFUSCATION

Figure 6: The visualization of the original SqueezeNet model. It is plotted by Netron (Roeder, 2017).

Figure 7: The visualization of the obfuscated SqueezeNet model with all obfuscation strategies. This figure is plotted by Netron (Roeder, 2017). The number of injected shortcuts and extra layers is 30. The obfuscated model can run on the modified TFLite library. The computational time and memory overhead of model obfuscation for this model can be found in Figure 3 and 4. The size change can be found in Figure 5.

## B    APPENDIX - EXAMPLE OF CODE OBFUSCATION

The following code is the 'Eval' function of the modified source code to support the `Concatenation` layer. It will finally call the 'EvalImpl' function, which is the detailed implementation for the forward inference.

```
template <KernelType kernel_type>
TfLiteStatus Eval(TfLiteContext* context, TfLiteNode* node) {
  // auto* params =
  //     reinterpret_cast<TfLiteConcatenationParams*>(node->builtin_data);
  // int axis = params->axis;
  TfLiteTensor* output;
  TF_LITE_ENSURE_OK(context, GetOutputSafe(context, node, 0, &output));
  if (IsConstantOrPersistentTensor(output)) {
    // Output is computed in Prepare.
    return kTfLiteOk;
  }
  if (axis < 0) axis += output->dims->size;

  return EvalImpl<kernel_type>(context, node, axis, output);
}
```

After obfuscating the simple code by some simple obfuscation method (*e.g.*, comments removal, functions and variables renaming, whitespaces removal. We use an open-source tool to implement it [3]), the code will become the following form:

```
template<lpurqacghdzw uowpojpkaqnn>TfLiteStatus ojmfjdqxlkrj(TfLiteContext
*zsflmtabfslq,TfLiteNode*node){gqgyxfwmpoax*output;TF_LITE_ENSURE_OK(
zsflmtabfslq,GetOutputSafe(zsflmtabfslq,node,0,&output));if(
IsConstantOrPersistentTensor(output)){return    tsciszklzszy;}if(
dwzzpibyhyhk<0)dwzzpibyhyhk+=output->dims->size;return
tizpeextacqk<uowpojpkaqnn>(zsflmtabfslq,node,dwzzpibyhyhk,output);}
```

---

[3] https://github.com/whoward3/C-Code-Obfuscator

Note that this is just a simple example. For the case when the original model is a 30-layer neural network, it will create more than 10 thousand lines of code for supporting the obfuscated model, and then add the code to the TFLite project to compile a modified TFLite library. If adversaries use the reverse engineering method to extract the source code of the obfuscated layer, ideally they can get the above obfuscated code. But the code will be extremely difficult to read. This is the reason why we think developers can use code obfuscation to resist further reverse engineering for the source code of the modified TFLite library.