LEARNING BASIC INTERPRETABLE FACTORS FROM TEMPORAL SIGNALS VIA PHYSICAL SYMMETRY

ABSTRACT

We have recently seen great progress in learning interpretable music representations, ranging from basic factors, such as pitch and timbre, to high-level concepts, such as chord, texture and melody contour. However, most methods rely heavily on music domain knowledge and it remains an open question how to learn interpretable and disentangled representations using inductive biases that are more general. In this study, we use *physical symmetry* as a self-consistency constraint on the latent space. Specifically, it requires the prior model that characterises the dynamics of the latent states to be *equivariant* with respect to a certain group transformation (say, translation and rotation). We show that our model can learn *linear* pitch factor (that agrees with human music perception) as well as pitch-timbre disentanglement from unlabelled monophonic music audio. In addition, the same methodology can be applied to computer vision, learning the 3D Cartesian space as well as space-colour disentanglement from a simple moving object shot by a single fixed camera. Furthermore, applying physical symmetry to the prior model naturally leads to *representation augmentation*, a new learning technique which helps improve sample efficiency.

1 INTRODUCTION

Interpretable representation-learning models have achieved great progress for various types of time-series data. Taking the *music* domain as an example, tailored deep generative models (Ji et al., 2020) have been developed to learn pitch, timbre, melody contour, chord progression, accompaniment texture, etc. However, most models still rely heavily on domain-specific knowledge. For example, to use pitch scales or instrument labels for pitch-timbre disentanglement (Luo et al., 2020; 2019; Engel et al., 2020; Lin et al., 2021; Esling et al., 2018), and to use chords and self-supervised rhythm labels for learning higher-level representations (Akama, 2019; Yang et al., 2019; Wang et al., 2020; Wei & Xia, 2021). Such an approach is very different from human learning; even without formal music training, one can at least perceive basic factors such as pitch and timbre from the experience of listening to music. In other words, it remains an open question how to learn interpretable and disentangled music representations using inductive biases that are more general. We see a similar issue in other domains. For instance, various computer-vision models (McCarthy & Ahmed, 2020; Trevithick & Yang, 2021; Mescheder et al., 2019; Riegler et al., 2017) can learn 3D representations of human faces or a particular scene by incorporating domain knowledge (e.g., labelling of meshes and voxels, 3D-specific setups such as multi-cameras, 3D convolution, etc.) but it remains a non-trivial task to trace the 3D location of a simple moving object from monocular videos in a self-supervised fashion.

In this study, we explore to use *physical symmetry* (i.e., symmetry of physical laws) as a weak self-consistency constraint for the learned latent z space. As indicated in Figure 1, this general inductive bias requires that after a certain transformation S (e.g., translation or rotation) in the latent space, the learned prior model R, which can be regarded as the induced physical law describing the temporal flow of the latent states, should output equivariant predictions. Formally, $z_{t+1} = R(z_t)$ if and only if $z_{t+1}^S = R(z_t^S)$, where $z^S = S(z)$. In other words, R and S are commutable operations for z, i.e., $R(S(z)) = S(R(z))$. Note that this approach is fundamentally different from most existing symmetry-informed models (Bronstein et al., 2021), in which the symmetry property is used to constrain the encoder or the decoder.

Figure 1: Physical symmetry, the fundamental inductive bias of this study.

Specifically, we design **s**elf-supervised learning with **p**hysics **s**ymmetry (**SPS**), a method that adopts an encoder-decoder framework to learn the latent states and use a vanilla RNN with physical symmetry as the prior model. We show that with the right symmetry assumptions, our model learns *linear* pitch factors that agree with human music perception from monophonic music audio, without any knowledge about pitch scales, signal-level harmonics and spectral regularities, or external labelling. If we further assume a global invariant latent code, the model can learn pitch-timbre disentanglement without instrument labelling. Moreover, we show that the same methodology can be applied to the computer vision domain, learning 3D Cartesian space as well as space-colour disentanglement from monocular videos of a bouncing ball shot from a fixed perspective.

2 INTUITION

The idea of using physical symmetry for representation learning comes from modern physics. In classical physics, scientists usually first induce physical laws from observations and then discover symmetry properties of the law. (E.g., Newton's law of gravitation, which was induced from planetary orbits, is symmetric with respect to Galilean transformation.) In contrast, in modern physics, scientists often start from a symmetry assumption, based on which they derive the corresponding law and predict the properties (representations) of fundamental particles. (E.g., general relativity was developed based on a firm assumption of symmetry with respect to Lorentz transformation).

Analogously, we use physical symmetry as an inductive bias of our machine learning model, which helps us learn a regularised prior and an interpretable latent space. In other words, if it is a belief of many physicists that symmetry in physical law is a main design principle of nature, we regard symmetry in physical law as a major useful inductive bias of the representation learner.

The introduction of physical symmetry to the learned prior model naturally leads to **representation augmentation**, a novel learning technique which helps improve sample efficiency. As indicated in Figure 1, representation augmentation means to "imagine" new z_t^S as the training sample of the prior model R. Representation augmentation can be regarded as a regularisation of the prior model, since it requires the prediction of the z sequence to be *equivariant* with respect to a certain group transformation of S. It also constrains the encoder and decoder *indirectly through the prior model* since the network is trained in an end-to-end fashion.

3 METHODOLOGY

Our goal is to learn a disentangled and interpretable representation z_i of each high-dimensional data sample x_i from time-series observations $\mathbf{x}_{1:T}$. **The disentanglement of z_i is at two levels. First**, z_i is divided into two factors: $z_{i,s}$ and $z_{i,c}$, where $z_{i,s}$ is the style factor remaining unchanged over the temporal flow and $z_{i,c}$ is the content representation that changes over time. **More importantly**, we aim to further disentangle the content factor using physical symmetry such that *each* dimension of $z_{i,c}$ is interpretable and consistent with human perception.

We focus on two specific problems in this paper. The primary problem is to learn *pitch* and *timbre* factors of music notes from monophonic music audio, where each x_i is a spectrogram of a note. Ideally, $z_{i,c}$ is a 1D content factor representing the pitch and $z_{i,s}$ is a style factor representing the timbre. The secondary problem is to learn *3D Cartesian location* and *colour* factors of a simple moving object (a bouncing ball) from its trajectory shot by a fixed, single camera. In this case, each x_i is an image. Ideally, $z_{i,c}$ is learned to be a 3D content factor representing the location and $z_{i,s}$

represents the colour. For both problems, we use physical symmetry to learn the representations in a self-supervised manner with no other inductive biases (such as contrastive loss and mutual information) or training tricks (such as batch normalisation and dropout).

3.1 MODEL

Figure 2 shows our model design. It includes: 1) an encoder E and three weight-sharing decoders D, represented by the green trapezoids, 2) two weight-sharing prior models R, represented by the red squares, 3) a group transformation S and its inverse operation S^{-1}, represented by the blue squares, and 4) a random-pooling operation P, represented by the yellow circle. We use a CNN to implement E, its deconvolutional counterpart for D and an RNN for R.

During the training process, the temporal data input $\mathbf{x}_{1:T}$ is first fed into the encoder E to obtain the corresponding representation $\mathbf{z}_{1:T}$. $\mathbf{z}_{1:T}$ is then split into two parts: the style factor $\mathbf{z}_{1:T,s}$ and the content factor $\mathbf{z}_{1:T,c}$. The style factor $\mathbf{z}_{1:T,s}$ is passed through the random-pooling module P, where one sub-element $z_{\tau,s}$ is randomly picked. The content factor $\mathbf{z}_{1:T,c}$ is fed into *three* branches. In the first branch (the green line), $\mathbf{z}_{1:T,c}$ is combined with $z_{\tau,s}$ by concatenating each sub-element $z_{i,c}$ with $z_{\tau,s}$, and fed to the decoder D to reconstruct $\mathbf{x}'_{1:T}$. In the second branch (the orange line), $\mathbf{z}_{1:T,c}$ is passed through the prior model R to predict its next step, $\hat{\mathbf{z}}_{2:T+1,c}$, which is then combined with $z_{\tau,s}$ to reconstruct $\hat{\mathbf{x}}_{2:T+1}$. In the third branch (the blue line), we sequentially transform $\mathbf{z}_{1:T,c}$ with S, pass it through R, and transform it back using the inverse transformation S^{-1} to predict another version of the next step $\tilde{\mathbf{z}}_{2:T+1,c}$, which is finally combined with $z_{\tau,s}$ to reconstruct $\tilde{\mathbf{x}}_{2:T+1}$. We get three outputs from the model: $\mathbf{x}'_{1:T}$, $\hat{\mathbf{x}}_{2:T+1}$ and $\tilde{\mathbf{x}}_{2:T+1}$.

The underlying idea of physical symmetry is that the dynamics of latent content factor and its transformed version *follow the same physical law* characterised by R. Therefore, $\tilde{\mathbf{z}}$ and $\hat{\mathbf{z}}$ should be close to each other and so are $\tilde{\mathbf{x}}$ and $\hat{\mathbf{x}}$, assuming S is a proper transformation. This self-consistency constraint helps the network learn a more regularised latent space. In addition, $z_{\tau,s}$ further helps disentangle the style factor by assuming an invariant style over the course of each time-series sequence.

Figure 2: An overview of our model. The temporal data input $\mathbf{x}_{1:T}$ is fed into the encoder E to obtain the corresponding representation $\mathbf{z}_{1:T}$, which is then split into two parts: the style factor $\mathbf{z}_{1:T,s}$ and the content factor $\mathbf{z}_{1:T,c}$. The style factor is passed through the random-pooling layer P, where a sub-element $z_{\tau,s}$ is randomly selected; the content factor is fed into three different branches and combined with $z_{\tau,s}$ to reconstruct three outputs respectively: $\mathbf{x}'_{1:T}$, $\hat{\mathbf{x}}_{2:T+1}$ and $\tilde{\mathbf{x}}_{2:T+1}$.

3.2 TRAINING OBJECTIVE

The total loss contains four terms: reconstruction loss $\mathcal{L}_{\text{rec}}$, prior prediction loss $\mathcal{L}_{\text{prior}}$, symmetry-based loss $\mathcal{L}_{\text{sym}}$, and KL divergence loss $\mathcal{L}_{\text{KLD}}$. Formally,

$$\mathcal{L} = \mathcal{L}_{\text{rec}} + \lambda_1 \mathcal{L}_{\text{prior}} + \lambda_2 \mathcal{L}_{\text{sym}} + \lambda_3 \mathcal{L}_{\text{KLD}}, \tag{1}$$

where λ_1, λ_2 and λ_3 are weighting parameters. By referring to the notations in section 3.1,

$$\mathcal{L}_{\text{rec}} = \mathcal{L}_{\text{BCE}}(\mathbf{x}'_{1:T}, \mathbf{x}_{1:T}) + \mathcal{L}_{\text{BCE}}(\hat{\mathbf{x}}_{2:T}, \mathbf{x}_{2:T}) + \mathcal{L}_{\text{BCE}}(\tilde{\mathbf{x}}_{2:T}, \mathbf{x}_{2:T}), \tag{2}$$

$$\mathcal{L}_{\text{prior}} = \ell_2(\hat{\mathbf{z}}_{2:T,c}, \mathbf{z}_{2:T,c}), \tag{3}$$

$$\mathcal{L}_{\text{sym}} = \ell_2(\tilde{\mathbf{z}}_{2:T,c}, \hat{\mathbf{z}}_{2:T,c}) + \ell_2(\tilde{\mathbf{z}}_{2:T,c}, \mathbf{z}_{2:T,c}). \tag{4}$$

Lastly, the $\mathcal{L}_{\text{KLD}}$ is the Kulback-Leibler divergence loss between the posterior distribution of z_i and a standard Gaussian.

3.3 SYMMETRY-BASED REPRESENTATION AUGMENTATION

We name S with *representation augmentation* since it creates extra fake sequences of z (i.e., imaginary experience based on a group assumption) to help train the prior. In practice, we apply K different transformations S to $\mathbf{z}_{1:T-1,c}$ to generate K fake sequences. Thus, the two terms of symmetry-based loss can be specified as:

$$\ell_2(\tilde{\mathbf{z}}_{2:T,c}, \mathbf{z}_{2:T,c}) = \frac{1}{K} \sum_{k=1}^{K} \ell_2(S_k^{-1}(R(S_k(\mathbf{z}_{1:T-1,c}))), \mathbf{z}_{2:T,c}), \tag{5}$$

$$\ell_2(\tilde{\mathbf{z}}_{2:T,c}, \hat{\mathbf{z}}_{2:T,c}) = \frac{1}{K} \sum_{k=1}^{K} \ell_2(S_k^{-1}(R(S_k(\mathbf{z}_{1:T-1,c}))), \hat{\mathbf{z}}_{2:T,c}), \tag{6}$$

where the lower case k denotes the index of a specific transformation and we refer to K as the *augmentation factor*. Likewise, the last term of reconstruction loss can be specified as:

$$\mathcal{L}_{\text{BCE}}(\tilde{\mathbf{x}}_{2:T}, \mathbf{x}_{2:T}) = \frac{1}{K} \sum_{k=1}^{K} \mathcal{L}_{\text{BCE}}(D(S_k^{-1}(R(S_k(\mathbf{z}_{1:T-1,c}))), z_{\tau,s}), \mathbf{x}_{2:T}). \tag{7}$$

Each transformation S applied to each sequence $\mathbf{z}_{1:T,c}$ belongs to a certain group, and different groups are used for different problems. For the music problem, we assume the content factor be to 1D and use random $S \in G \cong (\mathbb{R}, +)$. In other words, we add or subtract the content factor by a random scalar. As for the video problem, we assume the content factor be to 3D and use random $S \in G \cong (\mathbb{R}^2, +) \times \text{SO}(2)$. In other words, random rotation and shift are applied on two dimensions of the 3D content factor.

4 RESULTS

We run experiments on two problems. In section 4.1, we present the results of learning pitch and timbre factors from monophonic music audios. In section 4.2, we present the results of learning 3D location and colour factors from monocular videos of a bouncing ball shot from a fixed perspective. For both problems, we use a representation augmentation factor of $K = 4$. The focus in this section is to see whether the learned latent space of content is interpretable (isomorphic to human perception), and whether the content-style disentanglement is successful.

4.1 LEARNING PITCH AND TIMBRE FACTORS FROM MUSIC AUDIO

4.1.1 DATASET

We synthesise a dataset that contains around 2400 audio clips, each containing 15 notes in major scales with the first half ascending and the second half descending. We vary the starting pitch such that every MIDI pitch in the range C2 to C7 is present in the dataset. For each note sequence, we synthesise it using 53 different instruments, yielding 53 audio clips. Specifically, two soundfonts are used: FluidR3_GM (Wen, 2013) for the train set and GeneralUser GS v1.471 (Chris, 2017) for the test set. The pitch ranges for different instruments vary, so we limit each instrument to its common pitch range.

4.1.2 RESULTS ON INTERPRETABLE PITCH SPACE

Figure 3 shows that the pitch factor learned by our model has a linear relation with the true pitch. Here, we use z_{pitch} as the synonym of z_c to denote the content factor. The plot shows the mappings of two tasks and four models. In the embedding task (the first row), x-axis is the true pitch and

Figure 3: A visualisation of the the mapping between the 1D content factor and the true pitch. A linear, noiseless mapping is ideal.

y-axis is embedded z_{pitch}. In the synthesis task (the second row), x-axis is z_{pitch} and y-axis is the detected pitch (by YIN algorithm, a standard pitch-estimation method by De Cheveigné & Kawahara (2002)) of decoded (synthesised) notes. The fours models involved are: 1) our model, 2) our model without symmetry (i.e., no representation augmentation during training), 3) an β-VAE trained to reconstruct single-note spectrograms from a single instrument (banjo), and 4) SPICE (Gfeller et al., 2020), a SOTA unsupervised pitch estimator *with strong domain knowledge on how pitch linearity is reflected in log-frequency spectrograms*. As the figure shows, without explicit knowledge of pitch, our model learns a more interpretable pitch factor than β-VAE, and the result is comparable to SPICE.

4.1.3   RESULTS ON PITCH-TIMBRE DISENTANGLEMENT

We evaluate the content-style disentanglement using factor-wise data augmentation following Yang et al. (2019). Namely, we change (i.e., augment) the instrument (i.e., style) of notes while keeping their pitch, and then measure the effects on the encoded z_c and z_s. Ideally, the change of z_s should be much more significant than z_c. Here, we compare three approaches: 1) our model, 2) our model without splitting for z_s (i.e., our model without the dashed black path shown in Figure 2) but fed z_s together with z_c into the prior model, and 3) GMVAE (Luo et al., 2019), a domain-specific pitch-timbre disentanglement model trained with *explicit pitch labels*.

Figure 4: Comparisons for Δz_c and Δz_s for different instruments against accordion, with pitch kept constant at MIDI pitch D3.

Figure 4 presents the changes in normalised z_c and z_s measured by L2 distance when we change the instrument of an anchor note whose pitch is D3 and synthesised by accordion. Table 1 provides a more quantitative version by aggregating all possible instrument combinations and all different pitch pairs. Both results show that our model produces a smaller relative change in z_c under timbre augmentation, demonstrating a successful pitch-timbre disentanglement outperforming both the ablation and baseline. Note that for the ablation model, z_c varies heavily under timbre augmentation, seemingly containing timbre information. This result indicates that the design of an invariant style factor over the temporal flow is necessary to achieve good disentanglement.

Table 1: Mean ratios of z_c and z_s changes under timbre augmentation across all possible instrument combinations under different constant pitches.

Methods	$\|\|\Delta z_c\|\|_2/\|\|\Delta z_s\|\|_2 \downarrow$
Ours w/o z_s splitting	2.20
GMVAE (Baseline)	0.67
SPS (Ours)	**0.49**

4.2 Learning location and colour factors from videos of a moving object

4.2.1 Dataset

We run physical simulations of a bouncing ball in a 3D space and generate 4096 trajectories. The ball is affected by gravity and the bouncing force. A fixed camera records a 20-frame video of each 4-second simulation to obtain one trajectory (see Figure 5). The ball's size, gravity, and proportion of energy loss per bounce are constant across all trajectories. The ball's colour, initial position, and initial velocity are randomly sampled.

Figure 5: Two example trajectories from the bouncing ball dataset.

4.2.2 Result on interpretable 3D representation

Figure 6: Latent space traversal on different models. The i-th row denotes the generation results of changing z_i while keeping $z_{\neq i} = 0$.

Figure 6 illustrates the interpretability of learned content factor using latent space traversal. Each row varies only one dimension of the learned 3D content factor, keeping the other two dimensions at zero. Figure 6(a) shows the results of our model. We clearly observe that: i) *increasing z_1 (the first dimension of z_c) moves the ball from left to right, increasing z_2 moves the ball from bottom to top, and increasing z_3 moves the ball from far to near.* Figure 6(b) is the ablation model without physical

symmetry, and (c) shows the result of our baseline model β-VAE, which is trained to reconstruct static images of a single colour (green). Neither (b) nor (c) learns an interpretable latent space.

Table 2: Linear fits between the true location and the learned location factor.

Method	x axis MSE $\downarrow$	y axis MSE $\downarrow$	z axis MSE $\downarrow$	MSE $\downarrow$
β-VAE (Baseline)	0.37	0.76	0.73	0.62
Ours w/o Symmetry	0.35	0.72	0.68	0.58
SPS (Ours)	**0.11**	**0.06**	**0.09**	**0.09**

Table 2 quantitatively evaluates the linearity of the learned location factor. We fit a linear regression from z_c to the true 3D location over the test set and then compute the Mean Square Errors (MSEs). A smaller MSE indicates a better fit. All three methods (as used in Figure 6) are evaluated on a single-colour (green) test set. Results show that our model achieves the best linearity in the learned latent factors, which aligns with our observations in Figure 6.

4.2.3 RESULT ON SPACE-COLOUR DISENTANGLEMENT

Similar to section 4.1.3, we evaluate the space-colour disentanglement by augmenting the colour (i.e., style) of the bouncing balls while keeping their locations, and then measure the effects on the encoded z_c and z_s. Again, a good disentanglement should lead to a change in z_s much more significant than z_c. Here, we compare two approaches: 1) our model and 2) our model ablating splitting for z_s. The ablation model follows the same configuration as in section 4.1.3. A subtle difference is that the ablation model does not differently constrain z_2 (corresponding to the y-axis) than z_s. To ensure a meaningful comparison, under colour augmentation, we consider z_2 to be a part of z_s of the ablation model and a part of z_c of the complete model.

Figure 7: Comparisons for Δz_c and Δz_s for different colours against a white ball, with location kept constant at (0, 1, 5).

Table 3: Mean ratios of z_c and z_s changes under colour augmentation across sampled colour combinations under different constant locations.

Methods	$\lVert\Delta z_c\rVert_2/\lVert\Delta z_s\rVert_2$ $\downarrow$
Ours w/o z_s splitting	1.62
SPS (Ours)	**0.54**

Figure 7 presents the changes in normalised z_c and z_s measured by L2 distance when we change the instrument of an anchor ball whose location is (0, 1, 5) and rendered using white colour. Table 3 provides a more quantitative version by aggregating sampled colour combinations and location pairs. Both results show that our model produces a smaller relative change in z_c under timbre augmentation, demonstrating a successful pitch-timbre disentanglement outperforming the ablation model. Note that for the ablation model, z_c varies heavily under colour augmentation. This result agrees

with section 4.1.3 and again indicates that the design of an invariant style factor helps with disentanglement.

5   ANALYSIS

To better understand how representation augmentation leads to an interpretable content factor, we train a simplified version of our model with no style factor on the videos of a single-colour (green) bouncing ball. We choose the vision problem since a 3D content manifests a more obvious difference when physical symmetry is applied.

5.1   REPRESENTATION AUGMENTATION IMPROVES SAMPLE EFFICIENCY

Figure 8 shows that *a larger factor of representation augmentation leads to lower linear projection loss* (the measurement introduced in section 4.2.2) of the learned 3D representation. Here, K is the augmentation factor, and $K = 0$ means the model is trained without physical symmetry. The comparative study is conducted on 4 training set sizes (256, 512, 1024 and 2048), in which each box plot shows the results of 10 experiments trained with a fixed K and random initialisation. We observe that a larger K leads to better results and compensates for the lack of training data. For example, the loss trained on 256 samples with $K = 4$ is comparable to the loss trained on 1024 samples with $K = 0$, and the loss trained on 512 samples with $K = 4$ is even lower than the loss trained on 2048 samples with $K = 0$. In other words, when $K = 0$, increasing the number of training samples beyond a certain point does not further shrink the error, but increasing K still helps.

Figure 8: Linear projection MSE for different representation augmentation factors (K) and training set sizes.

5.2   REPRESENTATION AUGMENTATION IMPROVES DISENTANGLEMENT

Figure 9 visualises the latent space during different stages of model training, and we see that a larger K leads to a better disentanglement in an earlier stage of training. The horizontal axis shows the training epoch. Three experiments with different K values ($\times 0, \times 4, \times 16$) are stacked vertically. Each experiment is trained twice with random initialisation. Each subplot shows the orthogonal projection of the z_c space onto the plane spanned by z_1 and z_3, therefore hiding most of the y-axis (i.e. ball height) wherever disentanglement is successful. During training, the role of physical symmetry is to "straighten" the encoded grid and a larger K yields a stronger effect.

6   RELATED WORK

The idea of using a predictive model for better self-supervised learning has been well established (Oord et al., 2018; Chung et al., 2015; LeCun, 2022). In terms of model architecture, our model belongs to the family of disentangled sequential autoencoders (Bai et al., 2021; Hsu et al., 2017; Vowels et al., 2021; Yingzhen & Mandt, 2018; Zhu et al., 2020). It is very similar to VRNN (Chung et al., 2015) if we remove the global invariant part from the overall network. In addition, our model can be seen as a variation of joint-embedding predictive architecture (JEPA) in LeCun (2022) if we

Figure 9: A visualisation of the learned latent space against training epoch.

eliminate the reconstruction losses on the observation. In fact, we see the network topology of a model as the "hardware" and see the learning strategy (e.g., contrastive method, regularised method, or a mixed one), as "software". The main contribution of this study lies in the learning strategy — to use physical symmetry to limit the capacity of the latent space, and to use representation augmentation to increase sample efficiency.

The notion of "symmetry" and the use of symmetry for disentanglement are also not new in representation learning (Higgins et al., 2018; Bronstein et al., 2021). Most symmetric-based methods care about the relation between observation x and latent z (Sanghi, 2020; Quessard et al., 2020; Dupont et al., 2020; Huang et al., 2021). E.g., when a certain transformation is applied to x, z should simply keep invariant or follow a same/similar transformation. Such an assumption inevitably requires some knowledge in the domain of x. In contrast, the physical symmetry used in this study focuses solely on the dynamics of z, and therefore we only have to make assumptions about the underlying group transformation in the latent space. We see two most relevant works in the field of reinforcement learning (Mondal et al., 2022; Dupont et al., 2020), which applied an equivariant assumption very similar to the physical symmetry used in this paper. The major differences are twofold. First, to disentangle the basic factors, our method requires no interactions with the environment. Second, our method is much more concise; it needs no other tailored components or other inductive biases such as symmetric embeddings network and contrastive loss used in Dupont et al. (2020) or MDP homomorphism applied in Mondal et al. (2022).

7 CONCLUSION

In this paper, we propose a methodology that uses physical symmetry to learn disentangled and interpretable representations from time-series data. Experiments show that physical symmetry effectively regularises the latent space by enforcing the prior model to be equivariant with respect to group transformations. Under a proper group assumption, our method learns an interpretable 1D pitch factor (that agrees with human music perception) as well as a good pitch-timbre disentanglement from music audios without any labels of pitches or instruments. We also show that with the same method, we can learn an interpretable 3D Cartesian location factor as well as a good location-colour disentanglement from monocular videos of bouncing ball shot from a fixed perspective. In addition, a new training technique, representation augmentation, is developed to couple with physical symmetry. Analysis shows that representation augmentation leads to better sample efficiency and representation disentanglement.

REPRODUCIBILITY STATEMENT

The source code for training and testing the models, as well as generating the figures and tables, is publicly available at https://github.com/double-blind-75098/Learning-basic-interpretable-factors-from-temporal-signals-via-physical-symmetry.

ACKNOWLEDGMENTS

Redacted for review.

REFERENCES

Taketo Akama. Controlling symbolic music generation based on concept learning from domain knowledge. In Arthur Flexer, Geoffroy Peeters, Julián Urbano, and Anja Volk (eds.), *Proceedings of the 20th International Society for Music Information Retrieval Conference, ISMIR 2019*, pp. 816–823, 2019. URL http://archives.ismir.net/ismir2019/paper/000100.pdf.

Junwen Bai, Weiran Wang, and Carla P Gomes. Contrastively disentangled sequential variational autoencoder. *Advances in Neural Information Processing Systems*, 34:10105–10118, 2021.

Samy Bengio, Oriol Vinyals, Navdeep Jaitly, and Noam Shazeer. Scheduled sampling for sequence prediction with recurrent neural networks. *Advances in neural information processing systems*, 28, 2015.

Michael M Bronstein, Joan Bruna, Taco Cohen, and Petar Veličković. Geometric deep learning: Grids, groups, graphs, geodesics, and gauges. *arXiv preprint arXiv:2104.13478*, 2021.

Collins Chris. GeneralUser GS, 2017. URL https://schristiancollins.com/generaluser.php.

Junyoung Chung, Kyle Kastner, Laurent Dinh, Kratarth Goel, Aaron C Courville, and Yoshua Bengio. A recurrent latent variable model for sequential data. In C. Cortes, N. Lawrence, D. Lee, M. Sugiyama, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 28. Curran Associates, Inc., 2015. URL https://proceedings.neurips.cc/paper/2015/file/b618c3210e934362ac261db280128c22-Paper.pdf.

Alain De Cheveigné and Hideki Kawahara. Yin, a fundamental frequency estimator for speech and music. *The Journal of the Acoustical Society of America*, 111(4):1917–1930, 2002.

Emilien Dupont, Miguel Bautista Martin, Alex Colburn, Aditya Sankar, Josh Susskind, and Qi Shan. Equivariant neural rendering. In *International Conference on Machine Learning*, pp. 2761–2770. PMLR, 2020.

Jesse Engel, Rigel Swavely, Lamtharn Hanoi Hantrakul, Adam Roberts, and Curtis Hawthorne. Self-supervised pitch detection by inverse audio synthesis. In *ICML 2020 Workshop on Self-supervision in Audio and Speech*, 2020. URL https://openreview.net/forum?id=RlVTYWhsky7.

Philippe Esling, Axel Chemla-Romeu-Santos, and Adrien Bitton. Bridging audio analysis, perception and synthesis with perceptually-regularized variational timbre spaces. In *Proceedings of the 19th International Society for Music Information Retrieval Conference, ISMIR 2018*, pp. 175–181, 2018.

Beat Gfeller, Christian Frank, Dominik Roblek, Matt Sharifi, Marco Tagliasacchi, and Mihajlo Velimirović. Spice: Self-supervised pitch estimation. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 28:1118–1128, 2020.

Irina Higgins, David Amos, David Pfau, Sebastien Racaniere, Loic Matthey, Danilo Rezende, and Alexander Lerchner. Towards a definition of disentangled representations. *arXiv preprint arXiv:1812.02230*, 2018.

Wei-Ning Hsu, Yu Zhang, and James Glass. Unsupervised learning of disentangled and interpretable representations from sequential data. *Advances in neural information processing systems*, 30, 2017.

Siyuan Huang, Yichen Xie, Song-Chun Zhu, and Yixin Zhu. Spatio-temporal self-supervised representation learning for 3d point clouds. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 6535–6545, 2021.

Shulei Ji, Jing Luo, and Xinyu Yang. A comprehensive survey on deep music generation: Multi-level representations, algorithms, evaluations, and future directions. *arXiv preprint arXiv:2011.06801*, 2020.

Yann LeCun. A path towards autonomous machine intelligence. *preprint posted on openreview*, 2022.

Liwei Lin, Gus Xia, Qiuqiang Kong, and Junyan Jiang. A unified model for zero-shot music source separation, transcription and synthesis. In Jin Ha Lee, Alexander Lerch, Zhiyao Duan, Juhan Nam, Preeti Rao, Peter van Kranenburg, and Ajay Srinivasamurthy (eds.), *Proceedings of the 22nd International Society for Music Information Retrieval Conference, ISMIR 2021*, pp. 381–388, 2021. ISBN 978-1-7327299-0-2. URL https://archives.ismir.net/ismir2021/paper/000047.pdf.

Yin-Jyun Luo, Kat Agres, and Dorien Herremans. Learning disentangled representations of timbre and pitch for musical instrument sounds using gaussian mixture variational autoencoders. *Proceedings of the 20th International Society for Music Information Retrieval Conference, ISMIR 2019*, 2019.

Yin-Jyun Luo, Kin Wai Cheuk, Tomoyasu Nakano, Masataka Goto, and Dorien Herremans. Unsupervised disentanglement of pitch and timbre for isolated musical instrument sounds. In *Proceedings of the 21st International Society for Music Information Retrieval Conference, ISMIR 2020*, pp. 700–707, 2020.

Ollie McCarthy and Zohaib Ahmed. Hooligan: Robust, high quality neural vocoding. *arXiv preprint arXiv:2008.02493*, 2020.

Lars Mescheder, Michael Oechsle, Michael Niemeyer, Sebastian Nowozin, and Andreas Geiger. Occupancy networks: Learning 3d reconstruction in function space. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 4460–4470, 2019.

Arnab Kumar Mondal, Vineet Jain, Kaleem Siddiqi, and Siamak Ravanbakhsh. Eqr: Equivariant representations for data-efficient reinforcement learning. In *International Conference on Machine Learning*, pp. 15908–15926. PMLR, 2022.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

Robin Quessard, Thomas Barrett, and William Clements. Learning disentangled representations and group structure of dynamical environments. *Advances in Neural Information Processing Systems*, 33:19727–19737, 2020.

Gernot Riegler, Ali Osman Ulusoy, and Andreas Geiger. Octnet: Learning deep 3d representations at high resolutions. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 3577–3586, 2017.

Aditya Sanghi. Info3d: Representation learning on 3d objects using mutual information maximization and contrastive learning. In *European Conference on Computer Vision*, pp. 626–642. Springer, 2020.

Alex Trevithick and Bo Yang. Grf: Learning a general radiance field for 3d representation and rendering. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 15182–15192, 2021.

Matthew J Vowels, Necati Cihan Camgoz, and Richard Bowden. Vdsm: Unsupervised video disentanglement with state-space modeling and deep mixtures of experts. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8176–8186, 2021.

Ziyu Wang, Dingsu Wang, Yixiao Zhang, and Gus Xia. Learning interpretable representation for controllable polyphonic music generation. In Julie Cumming, Jin Ha Lee, Brian McFee, Markus Schedl, Johanna Devaney, Cory McKay, Eva Zangerle, and Timothy de Reuse (eds.), *Proceedings of the 21th International Society for Music Information Retrieval Conference, ISMIR 2020*, pp. 662–669, 2020. ISBN 978-0-9813537-1-5. URL `http://archives.ismir.net/ismir2020/paper/000094.pdf`.

Shiqi Wei and Gus Xia. Learning long-term music representations via hierarchical contextual constraints. In Jin Ha Lee, Alexander Lerch, Zhiyao Duan, Juhan Nam, Preeti Rao, Peter van Kranenburg, and Ajay Srinivasamurthy (eds.), *Proceedings of the 22nd International Society for Music Information Retrieval Conference, ISMIR 2021*, pp. 738–745, 2021. ISBN 978-1-7327299-0-2. URL `https://archives.ismir.net/ismir2021/paper/000092.pdf`.

Frank Wen. The fluid release 3 general-MIDI soundfont, 2013. URL `https://member.keymusician.com/Member/FluidR3_GM/index.html`.

Ruihan Yang, Dingsu Wang, Ziyu Wang, Tianyao Chen, Junyan Jiang, and Gus Xia. Deep music analogy via latent representation disentanglement. In Arthur Flexer, Geoffroy Peeters, Julián Urbano, and Anja Volk (eds.), *Proceedings of the 20th International Society for Music Information Retrieval Conference, ISMIR 2019*, pp. 596–603, 2019. URL `http://archives.ismir.net/ismir2019/paper/000072.pdf`.

Li Yingzhen and Stephan Mandt. Disentangled sequential autoencoder. In *International Conference on Machine Learning*, pp. 5670–5679. PMLR, 2018.

Yizhe Zhu, Martin Renqiang Min, Asim Kadav, and Hans Peter Graf. S3vae: Self-supervised sequential vae for representation disentanglement and data generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6538–6547, 2020.

A APPENDIX

A.1 IMPLEMENTATION DETAILS

A.1.1 ARCHITECTURE DETAILS

Out models for both tasks share the following architecture. The encoder is composed of a 2D-CNN with ReLU activation connected by two parallel linear layers, one for estimating the mean and the other for the log-variance if VAE is used. Otherwise, we use only one linear layer outputting z. The prior model is a vanilla RNN of one layer with 256 hidden units and one linear layer projection head. The decoder consists of several linear layers followed by a set of 2D transposed convolution layers mirroring the CNN in the encoder. We apply the Sigmoid function to its output to produce the final output. We use no batch normalisation or dropout layers.

Minor variations exist between the models for the two tasks. In the audio task, we use three convolution layers in the encoder, with three linear and three 2D transposed convolution layers in the decoder. In the vision task, as the data is more complex, we use four convolution layers in the encoder, with four linear and four 2D transposed convolution layers in the decoder.

A.1.2 TRAINING DETAILS

For both tasks, we use the Adam optimiser with a learning rate gradually decreasing from 10^{-3} to 10^{-5} in about 150000 batch iterations. The training batch size is 32 across all of our experiments. For all VAE-based models we present, including SPS (ours), ours w/o symmetry, and β-VAE (baseline), we set β (i.e., λ_3 in Equation (1)) to 0.01, with $\lambda_1 = 1$ and $\lambda_2 = 2$. All BCE and SE loss functions are calculated in sum instead of mean. $K = 4$ for all SPS models except for those discussed in section 5 where we analyse the influence of different K.

The RNN predicts $z_{n+1:T,c}$ given the first n embeddings $z_{1:n,c}$. We choose $n = 3$ for the audio task and $n = 5$ for the vision task. We adopt scheduled sampling (Bengio et al., 2015) during the training stage, where we gradually reduce the guidance from teacher forcing. After around 50000 batch iterations, the RNN relies solely on the given $z_{n+1:T,c}$ and its predictions.

Audio-specific setups. We run STFT (with sample rate $= 16000/s$, window length $= 1024$, hop length $= 512$, and no padding) over each audio to obtain a spectrogram. We further convert its energy values into a logarithmic scale and normalise them to the range $[0, 1]$. We then slice the spectrogram into fifteen segments, each containing one note. The CNN encoder, in each timestep, takes one segment as input. In practice, we sample $S \sim \mathcal{U}([-1, 1])$.

Vision-specific setups. In practice, we randomly choose from $S_1 \in G_1 \cong (\mathbb{R}^2, +)$ and $S_2 \in G_2 \cong \mathrm{SO}(2)$ to augment the representation. Both of them apply to two dimensions of z_c. Under the constraints of symmetry these two dimensions represent the horizontal x-z plane. Similar to the audio setup, we sample $S_1 \sim \mathcal{U}([-1, 1]^2)$.

A.2 EXTRA RESULTS

A.2.1 MORE INSPECTIONS ON LATENT FACTORS

To supplement results presented in section 4.1.2, Figure 10 shows a more quantitative analysis, using R^2 as the metric to evaluate the linearity of the pitch against z_{pitch} mapping. Although SPICE produces rather linear mappings in Figure 3, it suffers from octave errors towards extreme pitches, hurting its R^2 performance.

Figure 10: We use R^2 to evaluate mapping linearity. A larger R^2 indicates a more interpretable latent space.

Figure 11 evaluates the learned colour factor of our model. Each pixel shows the colour of the ball synthesised by the decoder using different z coordinates. The ball colour is detected using naive saturation maxima. In the central subplot, the location factor $z_{1:3}$ stays at zeros while the colour factor $z_{4:5}$ is controlled by the subplot's x, y axes. As shown in the central subplot, our model (a) learns a natural 2D colour space. The surrounding subplots keep the colour factor $z_{4:5}$ unchanged, and the location factor $z_{1,3}$ is controlled by the subplot's x, y axes. A black cross marks the point where the entire $z_{1:5}$ is equal to the corresponding one in the central subplot. As is shown by the surrounding subplots, varying the location factor does not affect the colour produced by our model (a), so the disentanglement is successful. The luminosity changes because the scene is lit by a point light source, making the ball position affect the surface shadow. On the other hand, β-VAE (b) learns an uninterpretable colour factor.

Figure 11: The colour map of the synthesised ball experiment through latent space traversal.

A.2.2 MORE ON CONTENT-STYLE DISENTANGLEMENT

To supplement sections 4.1.3 and 4.2.3, we further quantify the results in the form of augmentation-based queries following Yang et al. (2019), regarding the intended split in z as ground truth and the dimensions with the largest variances from factor-wise augmentation as predictions. For example, under timbre augmentation under a given pitch for our model, if z_1 and z_3 are the two dimensions of z that produce the largest variances, we count one false positive (z_1), one false negative (z_2) and one true positive (z_3). The precision would be 0.67. Tables 4 and 5 show the precision scores of the three approaches against their corresponding random selection for the two tasks. The results are in line with our observation in the previous sections, with our model more likely to produce the largest changes in dimensions in z_c under content augmentation and that in z_s under style augmentation.

Table 4: Results on augmentation-based queries on the audio task. Precision, recall and F1 are the same since the number of predicted and ground-truth positives are identical. Note that random precisions for different approaches can be different as z_c and z_s are split differently.

Methods	Timbre augmentation		Pitch augmentation	
	Precision ↑	Random Precision	Precision ↑	Random Precision
Ours w/o z_s splitting	0.50	0.67	0.02	0.33
GMVAE (Baseline)	0.93	0.50	0.83	0.50
SPS (Ours)	0.98	0.67	0.82	0.33

Table 5: Results on augmentation-based queries on the visual task. Since the ablation model does not differently constrain z_2 (corresponding to the y-axis) than z_s, we consider z_c and z_s differently for the two approaches. Under colour augmentation, we consider z_2 to be a part of z_s for the ablation model and a part of z_c for the complete model. Under location augmentation, we consider z_2 to be a part of z_c for both models.

Methods	Colour augmentation		Location augmentation	
	Precision ↑	Random Precision	Precision ↑	Random Precision
Ours, w/o z_s splitting	0.64	0.60	0.36	0.40
SPS (Ours)	0.99	0.40	0.88	0.40

A.2.3 RECONSTRUCTION AND PRIOR PREDICTION

We investigate the video reconstruction and prediction capacities of our model and show that they are not harmed by adding symmetry constraints. We compare our model, our model ablating symmetry constraints, and a β-VAE trained solely for only image reconstruction. Table 6 and Table 7 respectively show the results of audio and vision tasks. For each task, we report per-pixel BCE of the reconstructed sequences from the original input frames (Self-recon) and from the RNN predictions (Pred-recon). We also include $\mathcal{L}_{\text{prior}}$, the MSE loss on the RNN-predicted $\hat{z}$ as defined in section 3.2. The results show that our model suffers little decrease in reconstruction and prediction performance while surpassing the ablation model in terms of $\mathcal{L}_{\text{prior}}$.

Table 6: Reconstruction and prediction results of the audio task.

Methods	Self-recon (BCE/Pixel) ↓	Pred-recon (BCE/Pixel) ↓	$\mathcal{L}_{\text{prior}}$ (MSE/z) ↓
Ours w/o Symmetry	0.0360	0.0363	0.0486
β-VAE (Baseline)	0.0359	N/A	N/A
SPS (Ours)	0.0356	0.0359	0.0418

Table 7: Reconstruction and prediction results of the video task.

Methods	Self-recon (BCE/Pixel) ↓	Pred-recon (BCE/Pixel) ↓	$\mathcal{L}_{\text{prior}}$ (MSE/z) ↓
Ours w/o Symmetry	0.6456	0.6464	0.132
β-VAE (Baseline)	0.6455	N/A	N/A
SPS (Ours)	0.6457	0.6464	0.0957

A.2.4 MORE ANALYSIS ON REPRESENTATION AUGMENTATION

To supplement the results in section 5, Figure 12 shows how representation augmentation jointly affect the linearity of the learned latent space and the reconstruction accuracy of $\hat{x}$. Similar to Figure 8, the experiment is conducted using different Ks, each with 10 trails. We see that representation augmentation does not sacrifice reconstruction but shrinks the linear projection loss in a consistent manner.

Figure 12: The effect of representation augmentation on linear projection and the reconstruction of $\hat{x}$.

A.3 SPS WITH AUTOENCODER (AE)

We also test our method on AE, i.e., a model with almost the same architecture but the latent representation is not variational. Although AE usually suffers from its unregularised latent distribution and cannot learn meaningful embeddings, we find that once regularised with physical symmetry AE turns out to learn interpretable latent representations. This section presents our preliminary findings.

Table 8 supplements Table 2 by adding AE to the comparison. The latent space learned by AE is less linear than that learned by VAE but still much better than the ablation and baseline methods.

Table 8: Linear fits between the true location and the learned location factor, comparing AE with VAE.

Method	x axis MSE $\downarrow$	y axis MSE $\downarrow$	z axis MSE $\downarrow$	MSE $\downarrow$
SPS-AE	0.17	0.23	0.24	0.21
SPS-VAE	**0.11**	**0.06**	**0.09**	**0.09**

We further evaluate AE's disentanglement performance following the methods in sections 4.1.3, 4.2.3 and A.2.2. Figure 13, Table 9 and Table 10 respectively supplement Figure 4, Table 1 and Table4. Figure 14, Table 11 and Table 12 supplement Figure 7, Table 3 and Table5. The AE variant of our model achieves comparable performance to the VAE in both pitch-timbre and space-colour disentanglement, even slightly surpassing VAE in several metrics. Our results show that symmetry-regularisation empowers AE to learn well-disentangled representations.

Figure 13: Comparisons for Δz_c and Δz_s for different instruments against accordion, with pitch kept constant at MIDI pitch D3.

Table 9: Mean ratios of z_c and z_s changes under timbre augmentation across all possible instrument combinations under different constant pitches. We compare the AE and VAE variants of our model.

Methods	$||\Delta z_c||_2/||\Delta z_s||_2 \downarrow$
SPS-AE	**0.48**
SPS-VAE	0.49

Figure 15 is plotted in the same way as Figure 9, showing how the true location-latent space mapping becomes gradually more disentangled and linear as training progresses. AEs, once symmetry-augmented, are able to learn a location factor of similar qualities to those of VAEs within the same number of epochs.

Table 10: Results on augmentation-based queries on the audio task.

Methods	Timbre augmentation		Pitch augmentation	
	Precision ↑	Random Precision	Precision ↑	Random Precision
SPS-AE	**0.99**	0.67	0.80	0.33
SPS-VAE	0.98	0.67	**0.82**	0.33

Figure 14: Comparisons for Δz_c and Δz_s for different colours against white, with location kept constant at (0, 1, 5).

Table 11: Mean ratios of z_c and z_s changes under colour augmentation across sampled colour combinations under different constant locations.

Methods	$||\Delta z_c||_2/||\Delta z_s||_2 \downarrow$
SPS-AE	**0.48**
SPS-VAE	0.54

Table 12: Results on augmentation-based queries on the visual task.

Methods	Colour augmentation		Location augmentation	
	Precision ↑	Random Precision	Precision ↑	Random Precision
SPS-AE	0.98	0.40	0.85	0.40
SPS-VAE	**0.99**	0.40	**0.88**	0.40

Figure 15: Comparing VAE and AE in terms of latent space regularisation during training.