BlockBench: Contamination-Controlled Evaluation of LLM Code Analysis

Abstract

How much of large language model (LLM) performance in code analysis reflects memorization of training data rather than genuine reasoning? We introduce BLOCKBENCH, a contamination-controlled evaluation framework that separates memorization effects from analytical capability in smart contract vulnerability detection. We evaluate seven frontier models on 316 vulnerable contracts augmented with 322 semantic-preserving transformations and 100 clean contracts. We observe a substantial performance gap across data exposure levels: detection accuracy drops from 86.5% on likely-contaminated samples to 27.6% on post-cutoff contracts, and further to 0.8% on the most recently disclosed subset. A temporal analysis shows a strong exposure effect, where detection rates increase from 5.9% to 84.7% as contracts become more publicly visible, indicating that benchmark performance is heavily inflated by data contamination. We further identify a *pattern matching paradox*, where models can often locate security-relevant code regions but fail to explain why they are exploitable, revealing a form of explanation unfaithfulness in code understanding. In contrast, traditional static analyzers show complementary limitations: Slither compiles only 6.6% of post-cutoff contracts, while Mythril compiles all inputs but fails to detect vulnerabilities. BlockBench generalizes to code understanding tasks where semantic equivalence can be verified, enabling more reliable evaluation under potential contamination.

1 Introduction

Large language model evaluation faces a fundamental challenge: distinguishing genuine capability from training data memorization (Zhang et al., 2024; Zhao et al., 2025). When models achieve high scores on established benchmarks, it remains unclear how much performance reflects true reasoning versus pattern matching against memorized

Figure 1: Temporal gradient in GS performance. **Light bars**: samples with 2–6 months of public exposure (avg. 5.9% TDR). **Dark bars**: samples with 7–8 months of exposure (avg. 84.7% TDR). Detection rates rise with disclosure age across all seven models, consistent with training data absorption. On the most recently disclosed samples (n=72), average TDR remains at 0.8%.

examples. This problem is especially acute for code analysis tasks, where benchmark contamination has been documented across multiple evaluation suites (Jain et al., 2025; Haimes et al., 2024).

We investigate this question in the domain of smart contract vulnerability detection a setting uniquely suited to contamination-controlled evaluation. Smart contract security offers three properties that make it an ideal testbed: *(a) ground truth is objectively verifiable through documented exploits and professional audits, (b) contamination is measurable because well-known exploits are extensively documented in model training corpora, and (c) semantic-preserving transformations are well-defined, enabling systematic removal of surface recognition cues while preserving vulnerability mechanics.* The domain also carries practical significance: cryptocurrency theft has resulted in over $14 billion in losses since 2020, with 2025 reaching $3.4 billion (Chainalysis, 2025).

We present BLOCKBENCH, a contamination-

controlled evaluation methodology that measures how much of observed LLM performance is attributable to memorization. Our approach evaluates seven frontier models across contaminated baselines, semantically transformed variants, post-cutoff professional audit findings, and audited clean contracts. Performance on likely-contaminated samples reaches 86.5% TDR, but falls to 27.6% on the full post-cutoff set and 0.8% on the newest GS slice. This degradation, consistent with contamination patterns documented in adjacent benchmarks (Zhang et al., 2024; Zhao et al., 2025), suggests that surface pattern dependence accounts for a substantial portion of measured vulnerability detection capability. Our contributions:

(i) **A contamination-controlled evaluation methodology** using semantic-preserving transformations that progressively strip recognition cues while preserving exploit semantics, enabling measurement of memorization's contribution to observed performance. The methodology generalizes beyond security to any domain where semantic-preserving perturbations are definable.

(ii) **CodeActs**, a taxonomy inspired by speech act theory (Austin, 1962; Searle, 1969) for classifying code segments by security function (e.g., ROOT_CAUSE, PREREQ, DECOY), enabling fine-grained analysis of whether models identify vulnerabilities through causal reasoning or pattern matching.

(iii) **BlockBench**, a benchmark of 316 vulnerable Solidity contracts with 322 transformation variants and 100 clean contracts, spanning difficulty-stratified samples, temporally-controlled exploits, post-cutoff professional audit findings, and a negative set for false positive calibration.

(iv) **Empirical evidence of benchmark decay**, showing that detection rates on post-cutoff samples rise from 5.9% to 84.7% as public exposure accumulates, consistent with temporal contamination patterns documented in code benchmarks (Jain et al., 2025).

2 Related Work

Benchmark Contamination and Memorization: The reliability of LLM evaluation is increasingly questioned due to training data contamination. Zhao et al. (2025) demonstrated that contamination inflates MMLU scores by up to 14.6 percentage points, with GPT-4o dropping from 88.0% to 73.4% on decontaminated items. Zhang et al. (2024) showed analogous inflation on grade school arithmetic, with models scoring up to 13% lower on matched-difficulty items guaranteed absent from training data. LiveCodeBench (Jain et al., 2025) introduced temporal windowing for code evaluation, revealing that DeepSeek-Instruct's performance plunges from approximately 60% to near 0% for problems released after its training cutoff. Haimes et al. (2024) formalized inflation measurement through retrospective holdout construction, finding up to 16 percentage points of inflation on TruthfulQA. These findings motivate evaluation methodologies that explicitly control for contamination, the approach we adopt for vulnerability detection.

Robustness and Semantic Perturbation: Adversarial robustness evaluation in NLP has established that semantic-preserving perturbations—paraphrases, synonym substitutions, syntactic transformations—can substantially degrade model performance (Ribeiro et al., 2020). In code, Rabin et al. (2021) demonstrated that identifier renaming causes significant drops in neural vulnerability detectors, and recent work on code rewriting shows that structural modifications expose memorization reliance in code generation (Zhang et al., 2025). Our transformation suite extends this methodology to vulnerability detection, applying domain-specific semantic-preserving perturbations (sanitization, domain shift, structural obfuscation) that preserve exploit mechanics while systematically removing recognition cues.

Explanation Faithfulness in Code: Recent work reveals that code and mathematics domains exhibit the poorest chain-of-thought faithfulness scores (Han et al., 2026), and FaithCoT-Bench (Shen et al., 2025) provides instance-level faithfulness detection. Our CodeActs analysis identifies a domain-specific instance of this phenomenon: models that correctly locate vulnerable code segments cannot articulate why they are exploitable—a gap between pattern localization and causal explanation. We draw on speech act theory (Austin, 1962; Searle, 1969) to formalize this distinction, classifying code segments by their security function (e.g., ROOT_CAUSE vs. DECOY) rather than syntactic category. This functional taxonomy is analogous to dialogue act classification in NLP, where utterances are labeled by communicative function rather than surface form.

Traditional Analysis Tools: Early approaches to smart contract vulnerability detection relied on static analysis and symbolic execution. Tools such as Slither (Feist et al., 2019), Mythril (Mueller, 2017), and Securify (Tsankov et al., 2018) demonstrated precision on syntactically well-defined vulnerability classes. Durieux et al. (2020) evaluated nine tools across 47,587 contracts, finding 27–42% detection rates with 97% of contracts flagged as vulnerable, indicating impractically high false positive rates. We extend this comparison by evaluating both Slither and Mythril on BlockBench, providing direct baseline comparison against LLM performance across all subsets (§5.3).

LLM-Based Vulnerability Detection: Initial investigations by Chen et al. (2024) explored prompting strategies for vulnerability detection, achieving detection rates near 40% while noting pronounced sensitivity to superficial features. GPTScan (Sun et al., 2024b) combined GPT-4 with program analysis to achieve 78% precision on logic vulnerabilities. CLeVeR (Li et al., 2025) applied multimodal contrastive learning for vulnerability code representation at ACL 2025, framing detection as a code representation learning problem. Sun et al. (2024a) demonstrated that decoupling vulnerability descriptions from code context causes catastrophic performance degradation, suggesting reliance on memorized textual associations. Hu et al. (2023) documented output drift across evaluation dates at temperature zero, and Wu et al. (2024) showed systematic failure on counterfactual tasks where familiar patterns are disrupted. Our work extends these observations to a controlled experimental framework that isolates and measures the contribution of memorization to observed performance.

3 BlockBench

We introduce BlockBench, a contamination-controlled benchmark for measuring how much of LLM code analysis performance is attributable to training data memorization. The benchmark comprises 316 vulnerable Solidity contracts with 322 transformation variants and 100 clean contracts, spanning over 30 vulnerability categories (Appendix E).

Let $\mathcal{D}$ represent the dataset, where $\mathcal{D} = \{(c_i, v_i, m_i)\}_{i=1}^{316}$. Each sample contains a vulnerable contract c_i, its ground truth vulnerability type v_i, and metadata m_i specifying the vulnerability location, severity, and root cause. We partition $\mathcal{D}$ into three disjoint positive subsets and one negative set: $\mathcal{D} = \mathcal{D}_{DS} \cup \mathcal{D}_{TC} \cup \mathcal{D}_{GS} \cup \mathcal{D}_{NEG}$, each targeting a distinct evaluation objective (Table 1).

Subset	N	Sources
Difficulty Stratified (DS)	210	SmartBugs, DeFiVulnLabs
Temporal Contamination (TC)	46	Real-world exploits
Gold Standard (GS)	106	Code4rena, Spearbit, MixBytes
Negative Set (NEG)	100	OpenZeppelin, Uniswap, Aave, Compound, Lido, MakerDAO

Table 1: BlockBench composition by subset and primary sources.

Difficulty Stratified. $\mathcal{D}_{DS}$ draws from established vulnerability repositories including SmartBugs Curated (Ferreira et al., 2020), Trail of Bits' Not So Smart Contracts (Trail of Bits, 2026), and DeFiVulnLabs (SunWeb3Sec, 2023). Samples are stratified into four difficulty tiers based on detection complexity, with distribution $\{86, 81, 30, 13\}$ from Tier 1 (basic patterns) through Tier 4 (expert-level vulnerabilities requiring deep protocol knowledge). These samples are drawn from public vulnerability corpora that likely appear in model training data, establishing a *contaminated baseline* against which uncontaminated performance can be measured.

Temporal Contamination. $\mathcal{D}_{TC}$ reconstructs 46 real-world DeFi exploits spanning 2016 to 2024, representing over \$1.65 billion in documented losses. Notable incidents include The DAO (\$60M, 2016), Nomad Bridge (\$190M, 2022), and Curve Vyper (\$70M, 2023). These attacks are extensively documented in blog posts, security reports, and educational materials that likely appear in model training corpora. To probe whether models genuinely reason about these vulnerabilities or merely recognize memorized patterns, we apply systematic transformations that preserve vulnerability semantics while removing surface cues (detailed in §4).

Gold Standard. $\mathcal{D}_{GS}$ comprises 106 professional security audit findings from Code4rena (Code4rena, 2025), Spearbit (Spearbit, 2025), and MixBytes (MixBytes, 2025), disclosed between September 2025 and March 2026. All samples postdate $t_{cutoff} = $ August 2025, the most recent reported training cutoff among frontier models evaluated in this work. This temporal separation substantially reduces contamination risk, providing

the most reliable measure of detection capability on genuinely unseen vulnerabilities. The subset spans 11 vulnerability categories including logic errors (48%), arithmetic errors (9%), denial of service (9%), access control (8%), and signature replay (6%), with 24 high-severity and 82 medium-severity findings across 15 independent audit engagements. Thirty-eight samples include multi-file context for cross-contract vulnerability analysis.

We note that temporal separation does not guarantee zero contamination: training data cutoffs are imprecise, data mirrors and leaks may introduce post-cutoff material, and model providers do not fully disclose training data composition (Dodge et al., 2021). We present empirical evidence of temporal contamination dynamics in §5.2.

Negative Set. $\mathcal{D}_{\text{NEG}}$ consists of 100 clean, production-deployed Solidity contracts from six of the most extensively audited protocols in decentralized finance: OpenZeppelin v5 (25 contracts), Uniswap v4 (14), Aave v3 (19), Compound v3 (14), Lido (13), and MakerDAO (15). These contracts have undergone multiple professional audits and have been deployed in production with no known vulnerabilities. The negative set enables measurement of false positive rates—a critical dimension absent from prior vulnerability detection benchmarks (Durieux et al., 2020). Contracts span five functional categories: DeFi core (40), utility (20), token implementations (19), infrastructure (10), and governance (7).

These complementary subsets collectively enable rigorous assessment of both detection capability and the distinction between memorized patterns and analytical reasoning, while the negative set grounds evaluation in practical auditing precision.

4 Methodology

BlockBench asks whether a model can identify the causal mechanism of a vulnerability after familiar surface cues are removed. Figure 2 summarizes the pipeline: contracts are transformed, annotated with security functions, analyzed by detector models, and judged against ground truth.

Semantic transformations. For each TC contract c, we construct variants $\mathcal{T}(c)$ that preserve vulnerability semantics while changing the cues models may rely on. Concretely, $\mathcal{V}(\mathcal{T}(c)) = \mathcal{V}(c)$ means the same exploit still works for the same underlying reason, even if names, comments, domain

Family	Transformation	What it tests
Sanitize	$\mathcal{T}_S$: rename identifiers; remove comments	Reliance on lexical cues such as `withdraw`, `owner`, or exploit-hinting comments
Domain shift	$\mathcal{T}_C$: DeFi terms $\rightarrow$ non-security terms	Whether reasoning transfers when domain vocabulary changes but control/data flow remains
Obfuscate	$\mathcal{T}_O$: restructure code; add neutral intermediates	Robustness to surface form changes beyond simple renaming
Trojan	$\mathcal{T}_T : c \mapsto c \cup d_{\text{safe}}$	Distractor resistance: ignore suspicious-looking but non-exploitable code
Differential	$\mathcal{T}_D$: $c_{\text{vuln}} \mapsto c_{\text{fixed}}$	Counterfactual reasoning: report safe once the causal bug is removed
False Prophet	$\mathcal{T}_F : c \mapsto c \cup a_{\text{mislead}}$	Resistance to misleading natural-language assurances such as "audited"

Table 2: Semantic transformation families. All preserve or explicitly control the exploit semantics while changing the evidence available to a model.

vocabulary, or surrounding code have changed. This mirrors standard NLP robustness tests: paraphrases, counterfactual edits, domain shifts, and distractor spans.

We separate transformations that plausibly occur in production code (sanitization, comment removal, renamed forks) from stress tests designed to isolate reasoning failures (domain shift, Trojan distractors, Differential fixes, and misleading attestations). Figure 3 illustrates how a single vulnerability (the Nomad Bridge uninitialized root bypass) appears across six transformation variants, with changes highlighted. Full transformation definitions appear in Appendix H.

CodeActs. TDR measures *whether* a model detects a vulnerability, but not *how*. Two models may both flag a reentrancy bug: one explains the temporal dependency between an external call and a state update; the other simply flags the external call because it looks suspicious. Standard metrics score them identically. To separate causal reasoning from pattern recognition, we need to know which code segments each model attends to and what security role those segments play.

We introduce CodeActs, an annotation scheme that classifies code segments by their security function. The name draws on speech act theory (Austin, 1962; Searle, 1969): just as speech acts classify utterances by what they *do* (assert, request, promise) rather than their surface form, CodeActs classify code by what it *does* in the context of a vulnera-

Figure 2: BlockBench evaluation pipeline. Semantic-preserving transformations remove recognition cues while preserving exploit mechanics; CodeActs identify security-relevant code roles; LLM judges score detector outputs against ground truth with human validation.

Figure 3: The same vulnerability (tc_001: uninitialized root → message bypass) across six semantic-preserving transformations. Highlighted regions show what each transformation changes; the underlying exploit mechanics remain identical.

```
1  function withdraw(uint256 amt) {
2      require(bal[msg.sender] >= amt);        prereq
3      msg.sender.call(value: amt)("");        root cause
4      bal[msg.sender] -= amt;                 root cause
5      emit Withdrawal(msg.sender, amt);       benign
6  }
   ■ Prereq    ■ Root Cause    ■ Benign
```

Figure 4: CodeActs annotation of a reentrancy vulnerability. Colored bars mark each line's security function. A correct detection must identify lines 3–4 as ROOT_CAUSE and explain why their ordering enables exploitation.

bility. Each segment receives one of four primary labels: ROOT_CAUSE (code that causally enables exploitation), PREREQ (necessary preconditions), DECOY (suspicious-looking but non-exploitable code, injected via Trojan transformations), and BENIGN (correctly implemented). Figure 4 illustrates this on a classic reentrancy: lines 3–4 constitute the ROOT_CAUSE because their *ordering* (external call before state update) creates the exploit window. A model that flags line 3 in isolation without articulating the ordering dependency exhibits pattern matching; one that explains the causal chain demonstrates reasoning. The full 17-operation taxonomy and annotation format are in Appendix F.

Detection protocol. We evaluate seven frontier models, one per major AI lab: Claude Opus 4.5 (Anthropic, 2025), GPT-5.2 (OpenAI, 2025), Gemini 3 Pro (Google DeepMind, 2025), DeepSeek v3.2 (DeepSeek AI, 2025), Llama 4 Maverick (Meta AI, 2025), Grok 4.3 (xAI, 2025), and Qwen3-Coder-Plus (Alibaba Cloud, 2025). DS and TC use a direct zero-shot auditor prompt requesting structured JSON with vulnerability type, location, root cause, attack scenario, and fix. GS additionally uses five prompt settings (Direct, Context, Chain-of-Thought, Naturalistic, Adversarial) to test whether protocol context or framing changes detection. All evaluations use temperature 0; prompt templates are in Appendix I.

Judging and metrics. Detector outputs are evaluated against ground truth by independent LLM judges: GLM-4.7 (Zhipu AI, 2025), MIMO-v2-Flash (Xiaomi, 2025), and Mistral-Large-3 (Mistral AI, 2025). A finding is a TARGET_MATCH when it identifies the documented root cause, location, and vulnerability type. Findings that partially match, identify valid issues beyond ground truth, or report fabricated vulnerabilities are classified separately (full classification scheme in Appendix J). Our primary metric is Target Detection Rate (TDR), the proportion of samples where the target vulnerability is correctly identified. We also report false positive rate on clean contracts and explanation-quality scores (RCIR, AVA, FSV) for matched findings (definitions in Appendix L). On GS, GLM-4.7 and MIMO-v2-Flash achieve $\kappa = 0.943$ with 97.7% agreement; expert validation and judge failure modes are detailed in Appendix J.

5 Results

We evaluate seven frontier LLMs across 100 sampled DS contracts, all 46 TC contracts with 322 transformation variants, all 106 GS contracts, and 100 clean contracts, yielding over 5,000 model-sample evaluations. Unless noted otherwise, DS/TC scores use majority vote across three judges, while GS uses the two primary judges (GLM-4.7 and MIMO-v2-Flash; $\kappa = 0.943$).

5.1 Contaminated Performance Does Not Transfer

Table 3 shows the core transfer gap. Claude Opus 4.5 reaches 86.5% TDR on DS but drops to 50.9% across transformed TC variants; Gemini 3 Pro falls from 73.9% to 38.5%, with a 57% relative drop after protocol-identifying names are sanitized. Realistic perturbations (MinS/San/NoC) already reduce performance, while adversarial variants push all models toward a 15–40% floor. These failures occur despite preserved exploit semantics, suggesting dependence on recognition cues rather than invariant vulnerability reasoning.

5.2 Post-Cutoff Samples Reveal Benchmark Decay

Table 4 and Figure 1 reveal a temporal gradient in post-cutoff performance. Samples with longer public exposure (GS-Orig, disclosed 7–8 months before evaluation) average 84.7% TDR, while more recently disclosed samples (GS-New, 2–6 months of exposure) average 0.8%. This pattern is consistent with benchmark decay: as audit findings accumulate public exposure through blog posts, GitHub repositories, and educational materials, they enter model training corpora and inflate detection scores. The combined GS-All score (27.6%) reflects this mixture of exposure levels rather than a stable estimate of model capability on unseen data.

The expanded GS also shows within-category memorization. Models detect canonical DS reentrancy and arithmetic bugs, yet average 0% TDR on GS arithmetic errors ($n = 10$) and reentrancy ($n = 4$), where the same vulnerability classes appear through novel cross-contract callbacks, TWAP calculation errors, bit-mask corruption, and rounding-direction bugs (full breakdown in Appendix D). Familiar labels do not imply robust reasoning over unfamiliar mechanisms.

5.3 Clean Contracts and Tool Baselines

Table 5 addresses two practical gaps in prior evaluation: false positives and comparison to classical analyzers. Clean audited contracts reveal a precision-recall trade-off: Gemini 3 Pro and Grok 4.3 produce no false positives but have the lowest GS detection, while Claude Opus 4.5 has the best LLM balance (33.0% GS TDR, 9.0% FP). Traditional tools fail differently. Slither compiles only 6.6% of GS contracts because professional audit code often relies on unresolved imports and project-specific dependencies; Mythril processes all GS contracts but detects none, reflecting the mismatch between symbolic-execution patterns and the logic/arithmetic vulnerabilities common in GS. Thus, static tools and LLMs expose complementary limitations rather than a single dominant solution.

5.4 Pattern Matching Without Causal Explanation

CodeActs isolates a final failure mode: models can locate security-relevant code without explaining why it is exploitable. On TC Trojan variants, Llama 4 Maverick achieves the highest ROOT_CAUSE match rate (60.9%) but the lowest TDR (31.7%), a 29.2pp gap between pattern localization and causal explanation. This mirrors explanation-unfaithfulness findings in broader NLP reasoning work (Han et al., 2026): the model's apparent evidence points to the right region, but the generated security argument does not establish the exploit mechanism. Full SUI, quality, and CodeActs analyses are in Appendix D.

6 Discussion

What the Degradation Reveals. The DS-to-GS performance drop is not simply a matter of harder test samples. Three lines of evidence point to surface cue dependence rather than difficulty. First, the drop is category-selective: models detect canonical reentrancy and arithmetic vulnerabilities at high rates on DS but score 0% on GS instances of the same vulnerability classes, where the underlying principle is identical but the code manifestation is novel (cross-contract callbacks, TWAP miscalculations, bit-mask corruption). If models had learned the principle, category membership would predict performance; instead, surface familiarity does. Second, minimal perturbations cause disproportionate damage. Replacing protocol-identifying names with generic equivalents, a transformation

Model	DS (Difficulty-Stratified)					TC Transformations							
	T1	T2	T3	T4	Avg [95% CI]	MinS	San	NoC	Cha	Shp	Tro	FalP	Avg
Claude Opus 4.5	**100**	**83.8**	**70.0**	92.3	**86.5**[a] [82–91]	**71.7**	**54.3**	**50.0**	**43.5**	**50.0**	32.6	**54.3**	**50.9**
Gemini 3 Pro	75.0	78.4	50.0	**92.3**	73.9[a] [68–80]	65.2	28.3	32.6	37.0	34.8	34.8	37.0	38.5
GPT-5.2	60.0	70.3	36.7	84.6	62.9[a] [56–70]	54.3	34.8	37.0	28.3	30.4	30.4	37.0	36.0
DeepSeek v3.2	65.0	64.9	46.7	61.5	59.5 [53–66]	58.7	37.0	41.3	21.7	26.1	**43.5**	30.4	37.0
Llama 4 Maverick	65.0	45.9	40.0	69.2	55.0 [48–62]	52.2	39.1	30.4	21.7	13.0	**43.5**	21.7	31.7
Qwen3-Coder-Plus[b]	60.0	56.8	43.3	53.8	53.5 [47–60]	56.5	43.5	30.4	15.2	17.4	28.3	41.3	33.2
Grok 4.3[b]	40.0	37.8	33.3	30.8	35.5 [29–42]	32.6	23.9	19.6	15.2	15.2	21.7	21.7	21.4

Table 3: Target Detection Rate (%) on DS and TC. DS gives a likely-contaminated baseline; TC preserves exploit semantics while removing surface cues. [a]Top three DS averages are not statistically distinguishable (McNemar's $p > 0.05$). [b]Significantly worse than Claude Opus 4.5 ($p < 0.05$).

Figure 5: TC benchmark: TDR across transformations ordered by obfuscation intensity. Faint regions distinguish realistic perturbations from adversarial stress tests.

Model	GS-Orig (n=34)	GS-New (n=72)	GS-All (n=106)
Claude Opus 4.5	97.1	2.8	**33.0**
Llama 4 Maverick	97.1	2.8	31.1
Qwen3-Coder-Plus	94.1	0.0	30.2
DeepSeek v3.2	84.8	0.0	26.9
GPT-5.2	78.8	0.0	26.5
Gemini 3 Pro	79.4	0.0	26.2
Grok 4.3	61.8	0.0	19.8
Average	**84.7**	**0.8**	**27.6**

Table 4: GS TDR (%) by temporal slice. GS-Orig contains 34 samples disclosed September–October 2025 (7–8 months of public exposure at evaluation time). GS-New contains 72 samples disclosed November 2025–March 2026 (2–6 months of exposure).

System	GS behavior	Clean FP	Notes
Claude Opus 4.5	33.0 TDR	9.0%	best LLM TDR/FP balance
Gemini 3 Pro	26.2 TDR	**0.0%**	conservative; low GS recall
Grok 4.3	19.8 TDR	**0.0%**	conservative; lowest GS TDR
DeepSeek v3.2	26.9 TDR	26.0%	highest LLM FP rate
Slither	7/106 compiled	62.5%[†]	dependency-limited on GS
Mythril	0/106 detected	5.0%	processes GS but misses targets

Table 5: False positives and traditional baselines. LLM FP rates are measured on 100 clean audited contracts. [†]Slither FP rate is computed on the 24/100 clean contracts it compiled. Full model and tool tables appear in Appendix D.

that changes no control flow or data dependencies, reduces Gemini 3 Pro by 57%. This implies that a substantial fraction of measured detection rests on recognizing tokens like "Nomad" or "Curve" rather than tracing execution paths. Third, the temporal gradient across GS samples shows that detection rises with public exposure duration, consistent with score inflation rather than capability growth. Taken together, these observations suggest that current

code analysis benchmarks conflate pattern familiarity with analytical capability in ways that parallel contamination effects documented in MMLU-CF (Zhao et al., 2025), GSM1K (Zhang et al., 2024), and LiveCodeBench (Jain et al., 2025), though the magnitude in our domain (86.5% to 0.8%) is substantially larger, likely because smart contract exploits are extensively reproduced in educational materials and open-source repositories.

Pattern Recognition and Causal Explanation Are Dissociable. The CodeActs analysis reveals that locating vulnerable code and explaining why it is exploitable are separate capabilities. Llama 4 Maverick identifies ROOT_CAUSE segments at the highest rate (60.9%) yet produces the weakest causal explanations (31.7% TDR). This dissociation matters for deployment: a model that highlights the right lines but provides a generic or incorrect security argument may give practitioners false confidence that a vulnerability has been understood when it has only been flagged. The gap parallels explanation unfaithfulness findings in mathematical reasoning (Han et al., 2026; Shen et al., 2025), but manifests distinctly in code, where vulnerability explanation requires articulating a multi-step causal chain (precondition, trigger, state violation, exploit) rather than a single derivation step. Models that shortcut this chain by matching on the trigger alone produce explanations that appear plausible but omit the causal structure needed for remediation.

The Trojan results add a counterintuitive dimension. DeepSeek v3.2 and Llama 4 Maverick achieve their highest TC scores (43.5%) on variants containing injected decoy code, the opposite of what causal reasoning would predict. One hypothesis is that longer inputs activate retrieval mechanisms that surface relevant training examples, a failure mode where detection improves for the wrong reason.

Implications Beyond Smart Contract Security. The contamination-controlled methodology introduced here applies to any code analysis task where ground truth is verifiable, semantic-preserving perturbations are definable, and temporal separation from training data is achievable. Candidate domains include malware analysis (known families as DS, obfuscated variants as TC, novel samples as GS), software bug detection (using bug-fix pairs from version control), and formal verification (where semantic equivalence is mathematically defined). The temporal gradient we observe also has methodological implications: any code benchmark whose solutions appear in public repositories or documentation should be treated as potentially contaminated, and evaluation claims based on such benchmarks benefit from contamination controls or temporal analysis. The gap between what models appear to detect and what they actually reason about suggests that the field needs evaluation frameworks that go beyond accuracy to probe the causal structure of model explanations.

7 Conclusion

We present BlockBench, a contamination-controlled methodology for measuring how much LLM code analysis performance is attributable to training data memorization. Our evaluation of seven frontier models across 316 vulnerable contracts, 322 transformation variants, and 100 clean contracts (totaling over 5,000 unique evaluations) reveals three principal findings.

First, performance on likely-contaminated samples (86.5% TDR on DS) degrades to 27.6% on the full post-cutoff set and 0.8% on the newest GS slice, indicating that surface pattern dependence accounts for a substantial portion of measured detection capability. This degradation magnitude is consistent with contamination-driven inflation documented across NLP benchmarks (Zhao et al., 2025; Zhang et al., 2024; Jain et al., 2025). Second, the pattern matching paradox demonstrates that models can locate vulnerable code without explaining why it is exploitable—Llama 4 Maverick achieves 60.9% ROOT_CAUSE match but only 31.7% TDR—constituting a domain-specific instance of explanation unfaithfulness that parallels findings in mathematical reasoning (Han et al., 2026). Third, a temporal analysis of samples at different stages of public exposure reveals that detection rates rise from 5.9% to 84.7% as disclosure age increases, providing direct empirical evidence that code benchmarks decay as samples enter training corpora.

These findings carry implications beyond smart contract security. The contamination-controlled methodology—establishing contaminated baselines, applying semantic-preserving transformations, and comparing against temporally separated clean data—generalizes to any code understanding task where semantic equivalence is verifiable. We release BlockBench as a living benchmark to support evaluation of LLM code reasoning.

Limitations

Our evaluation encompasses 316 vulnerable contracts (DS n=210, TC n=46, GS n=106) with 322 TC transformation variants and 100 clean contracts for false positive assessment, yielding over 5,000 unique evaluations across seven frontier models. While this represents a substantial evaluation, several limitations warrant discussion.

Scope. We evaluate exclusively Solidity smart contracts. While Solidity dominates the DeFi ecosystem (accounting for over 90% of deployed contracts by value locked), our findings may not generalize to other smart contract languages such as Vyper, Rust (Solana/Anchor), or Move. The vulnerability types and transformation strategies are specific to EVM-based architectures.

Evaluation Context. We assess zero-shot prompting with five prompt protocols on GS, providing models with contract code and optional context files. In real audit settings, analysts draw on additional semantic context including protocol specifications, intended invariants, economic assumptions, and cross-protocol interactions. Our 38 GS samples with multi-file context partially address this, but a complete audit simulation remains beyond scope.

CodeActs Coverage. CodeActs annotations cover 46 samples across three transformation variants (MinimalSanitized, Trojan, Differential), enabling fine-grained analysis of the pattern matching paradox. Broader annotation coverage across the full dataset would strengthen generalizability of these findings.

Automated Evaluation. Our LLM judge ensemble (GLM-4.7, MIMO-v2-Flash, Mistral-Large) achieves Cohen's κ=0.943 between primary judges with 97.7% agreement, indicating near-perfect reliability. However, automated evaluation may miss nuanced security reasoning. Disagreements concentrate in access control and logic error categories, where vulnerability boundaries are inherently ambiguous.

Contamination Claims. We use temporal separation (post-cutoff sampling) to substantially reduce contamination risk, but cannot guarantee zero contamination. Training data cutoffs are imprecise, data mirrors and leaks may introduce post-cutoff material, and model providers do not disclose complete training data composition. Our temporal contamination evidence (§5.2) provides empirical support but not definitive proof.

Ethical Considerations

Dual-Use Risks. BlockBench poses dual-use risks: adversarial transformations demonstrate methods that could suppress vulnerability detection, while detailed vulnerability documentation may lower barriers for malicious actors. We justify public release on several grounds. First, adversarial robustness represents a fundamental requirement for security tools deployed in production. Second, all samples derive from already-disclosed vulnerabilities and public security audits; no novel exploit information is introduced. Third, responsible disclosure of evaluation limitations enables practitioners to calibrate trust in automated tools appropriately.

Broader Impacts. The primary positive impact of this work is enabling more informed deployment decisions for LLM-based security tools. Our finding that memorization accounts for a substantial portion of measured performance (§5) cautions against over-reliance on benchmark scores when evaluating security tools for production use. False negatives arising from memorization-dependent detection create security gaps, while false confidence from inflated benchmark scores may reduce manual review rigor. We recommend that practitioners treat LLM-based analysis as assistive rather than authoritative, maintaining mandatory expert review for all security-critical assessments.

Responsible Evaluation. We follow responsible NLP research practices by releasing all evaluation code, prompts, and data to enable reproducibility. We report confidence intervals and statistical tests throughout, and acknowledge limitations explicitly rather than overstating claims.

AI Assistance

AI tools assisted with evaluation pipeline code and manuscript refinement. All research design, experimental methodology, data curation, and analysis were conducted by the authors.

References

Alibaba Cloud. 2025. Qwen3-coder-plus. https://qwen.readthedocs.io/.

Anthropic. 2025. Claude opus 4.5 model card. https://docs.anthropic.com/en/docs/about-claude/models.

J. L. Austin. 1962. *How to Do Things with Words*. Oxford University Press.

Chainalysis. 2025. North korea drives record $2 billion crypto theft year, pushing all-time total to $6.75 billion. https://www.chainalysis.com/blog/crypto-hacking-stolen-funds-2026/. Accessed: 2025-12-18.

Chong Chen, Jianzhong Su, Jiachi Chen, Yanlin Wang, Tingting Bi, Yanli Wang, Jianxing Yu, Xingwei Lin, Ting Chen, and Zibin Zheng. 2024. When ChatGPT meets smart contract vulnerability detection: How far are we? *arXiv preprint arXiv:2309.05520*.

Code4rena. 2025. Audit reports. https://code4rena.com/reports. Accessed: 2026-05-26.

DeepSeek AI. 2025. DeepSeek v3.2. https://www.deepseek.com/.

Jesse Dodge, Maarten Sap, Ana Marasović, William Agnew, Gabriel Ilharco, Dirk Groeneveld, Margaret Mitchell, and Matt Gardner. 2021. Documenting large webtext corpora: A case study on the Colossal Clean Crawled Corpus. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 1286–1305, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.

Thomas Durieux, João F. Ferreira, Rui Abreu, and Pedro Cruz. 2020. Empirical review of automated analysis tools on 47,587 Ethereum smart contracts. In *Proceedings of the ACM/IEEE 42nd International Conference on Software Engineering*, pages 530–541.

Josselin Feist, Gustavo Grieco, and Alex Groce. 2019. Slither: A static analysis framework for smart contracts. In *Proceedings of the 2nd International Workshop on Emerging Trends in Software Engineering for Blockchain*, pages 8–15.

João F. Ferreira, Pedro Cruz, Thomas Durieux, and Rui Abreu. 2020. Smartbugs: A framework to analyze Solidity smart contracts. In *Proceedings of the 35th IEEE/ACM International Conference on Automated Software Engineering*, pages 1349–1352.

Asem Ghaleb and Karthik Pattabiraman. 2020. How effective are smart contract analysis tools? Evaluating smart contract static analysis tools using bug injection. In *Proceedings of the 29th ACM SIGSOFT International Symposium on Software Testing and Analysis*, pages 415–427.

Google DeepMind. 2025. Gemini 3 pro technical report. https://deepmind.google/technologies/gemini/.

Jacob Haimes, Cenny Wenner, Kunvar Thaman, Vassil Tashev, Clement Neo, Esben Kran, and Jason Schreiber. 2024. Benchmark inflation: Revealing LLM performance gaps using retro-holdouts. *arXiv preprint arXiv:2410.09247*.

Yunseok Han, Yejoon Lee, and Jaeyoung Do. 2026. RFEval: Benchmarking reasoning faithfulness under counterfactual reasoning intervention in large reasoning models. In *Proceedings of the 14th International Conference on Learning Representations*. In Proceedings of ICLR 2026.

S. M. Mostaq Hossain, Amani Altarawneh, and Jesse Roberts. 2025. Leveraging large language models and machine learning for smart contract vulnerability detection. *arXiv preprint arXiv:2501.02229*.

Sihao Hu, Tiansheng Huang, Fatih İlhan, Selim Furkan Tekin, and Ling Liu. 2023. Large language model-powered smart contract vulnerability detection: New perspectives. In *Proceedings of the 5th IEEE International Conference on Trust, Privacy and Security in Intelligent Systems and Applications (TPS-ISA 2023)*.

Peter Ince, Jiangshan Yu, Joseph K. Liu, Xiaoning Du, and Xiapu Luo. 2026. Gendetect: Generative large language model usage in smart contract vulnerability detection. In *Provable and Practical Security — 19th International Conference, ProvSec 2025, Proceedings*, pages 426–445. Springer.

Naman Jain, King Han, Alex Gu, Wen-Ding Li, Fanjia Yan, Tianjun Zhang, Sida Wang, Armando Solar-Lezama, Koushik Sen, and Ion Stoica. 2025. LiveCodeBench: Holistic and contamination free evaluation of large language models for code. In *Proceedings of the 13th International Conference on Learning Representations*.

Jiayuan Li, Lei Cui, Sen Zhao, Yun Yang, Lun Li, and Hongsong Zhu. 2025. CLeVeR: Multi-modal contrastive learning for vulnerability code representation. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 7940–7951, Vienna, Austria. Association for Computational Linguistics.

Ye Liu, Yue Xue, Daoyuan Wu, Yuqiang Sun, Yi Li, Miaolei Shi, and Yang Liu. 2025. Propertygpt: LLM-driven formal verification of smart contracts through retrieval-augmented property generation. In *Proceedings of the 32nd Annual Network and Distributed System Security Symposium (NDSS 2025)*.

Meta AI. 2025. Llama 4 maverick. https://ai.meta.com/llama/.

Mistral AI. 2025. Mistral-Large-3. https://mistral.ai/.

MixBytes. 2025. Smart contract security audits. https://mixbytes.io/audit. Accessed Nov 26, 2025.

Bernhard Mueller. 2017. Mythril: Security analysis tool for Ethereum smart contracts. https://github.com/ConsenSysDiligence/mythril.

OpenAI. 2025. GPT-5.2 technical report. https://openai.com/research.

Md Rafiqul Islam Rabin, Nghi D.Q. Bui, Ke Wang, Yijun Yu, Lingxiao Jiang, and Mohammad Amin Alipour. 2021. On the generalizability of neural program models with respect to semantic-preserving program transformations. *Information and Software Technology*, 135(106552).

Marco Tulio Ribeiro, Tongshuang Wu, Carlos Guestrin, and Sameer Singh. 2020. Beyond accuracy: Behavioral testing of NLP models with CheckList. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 4902–4912.

Eva Sánchez-Salido, Julio Gonzalo, and Guillermo Marco. 2025. None of the others: a general technique to distinguish reasoning from memorization in multiple-choice llm evaluation benchmarks. *arXiv preprint arXiv:2502.12896*.

John R. Searle. 1969. *Speech Acts: An Essay in the Philosophy of Language*. Cambridge University Press.

Xu Shen, Song Wang, Zhen Tan, Laura Yao, Xinyu Zhao, Kaidi Xu, Xin Wang, and Tianlong Chen. 2025. FaithCoT-Bench: Benchmarking instance-level faithfulness of chain-of-thought reasoning. *arXiv preprint arXiv:2510.04040*.

Spearbit. 2025. Security audit portfolio. https://github.com/spearbit/portfolio. Accessed Nov 20, 2025.

Yuqiang Sun, Daoyuan Wu, Yue Xue, Han Liu, Wei Ma, Lyuye Zhang, Yang Liu, and Yingjiu Li. 2024a. LLM4Vuln: A unified evaluation framework for decoupling and enhancing LLMs' vulnerability reasoning. *arXiv preprint arXiv:2401.16185*.

Yuqiang Sun, Daoyuan Wu, Yue Xue, Han Liu, Haijun Wang, Zhengzi Xu, Xiaofei Xie, and Yang Liu. 2024b. GPTScan: Detecting logic vulnerabilities in smart contracts by combining GPT with program analysis. In *Proceedings of the IEEE/ACM 46th International Conference on Software Engineering (ICSE '24)*, pages 2048–2060. ACM.

SunWeb3Sec. 2023. DeFiVulnLabs: To learn common smart contract vulnerabilities using Foundry. https://github.com/SunWeb3Sec/DeFiVulnLabs. Accessed Nov 11, 2025.

Trail of Bits. 2026. Not so smart contracts: Examples of Solidity security issues. https://github.com/crytic/not-so-smart-contracts. Accessed May 26, 2026.

Petar Tsankov, Andrei Dan, Dana Drachsler-Cohen, Arthur Gervais, Florian Bünzli, and Martin Vechev. 2018. Securify: Practical security analysis of smart contracts. In *Proceedings of the 2018 ACM SIGSAC Conference on Computer and Communications Security*, pages 67–82.

Zhaofeng Wu, Linlu Qiu, Alexis Ross, Ekin Akyürek, Boyuan Chen, Bailin Wang, Najoung Kim, Jacob Andreas, and Yoon Kim. 2024. Reasoning or reciting? Exploring the capabilities and limitations of language models through counterfactual tasks. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 1819–1862, Mexico City, Mexico. Association for Computational Linguistics.

xAI. 2025. Grok 4. https://x.ai/.

Xiaomi. 2025. MIMO-v2-Flash. https://github.com/XiaomiMiMo/MiMo.

Hugh Zhang, Jeff Da, Dean Lee, Vaughn Robinson, Catherine Wu, Will Song, Tiffany Zhao, Pranav Raja, Dylan Slack, Qin Lyu, Sean Hendryx, Russell Kaplan, Michele Lunati, and Summer Yue. 2024. A careful examination of large language model performance on grade school arithmetic. *arXiv preprint arXiv:2405.00332*.

Lizhe Zhang, Wentao Chen, Li Zhong, Letian Peng, Zilong Wang, and Jingbo Shang. 2025. Memorize or generalize? evaluating LLM code generation with code rewriting. *arXiv preprint arXiv:2503.02296*.

Qihao Zhao, Yangyu Huang, Tengchao Lv, Lei Cui, Qinzheng Sun, Shaoguang Mao, Xin Zhang, Ying Xin, Qiufeng Yin, Scarlett Li, and Furu Wei. 2025. MMLU-CF: A contamination-free multi-task language understanding benchmark. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics*, pages 13371–13391, Vienna, Austria. Association for Computational Linguistics.

Zhipu AI. 2025. GLM-4.7. https://open.bigmodel.cn/.

A Data and Code Availability

To support reproducibility and future research, we release all benchmark data and evaluation code, including 316 base contracts with ground truth annotations, 100 clean contracts for false positive calibration, all transformation variants, model evaluation scripts, LLM judge implementation, prompt templates, and analysis notebooks. BlockBench is designed as a living benchmark: the Gold Standard subset naturally expands as new professional audit findings are disclosed.

B Model Training Cutoffs

Table 6 reports the most recent training data cutoff for each evaluated model, as documented by the respective providers. All Gold Standard samples postdate August 2025.

Model	Provider	Reported Cutoff
Claude Opus 4.5	Anthropic	Mar 2025
GPT-5.2	OpenAI	Jun 2025
Gemini 3 Pro	Google	Aug 2025
DeepSeek v3.2	DeepSeek	May 2025
Llama 4 Maverick	Meta	Apr 2025
Grok 4.3	xAI	Jul 2025
Qwen3-Coder-Plus	Alibaba	May 2025

Table 6: Model training data cutoff dates as reported by providers. All GS samples (Sep 2025–Mar 2026) postdate these cutoffs, substantially reducing contamination risk. However, cutoff dates are imprecise—data mirrors, web crawls, and training refreshes may introduce post-cutoff material (Dodge et al., 2021).

C Evaluation Sampling

BlockBench contains 316 vulnerable contracts (DS=210, TC=46, GS=106) and 100 clean contracts. For DS evaluation, we stratified-sample 100 from 210 to balance computational cost with statistical power, maintaining tier proportions: $n_t = \lfloor 100 \times |T_t|/210 \rfloor$ for each tier $t \in \{1, 2, 3, 4\}$, yielding distribution $\{41, 39, 14, 6\}$ from original $\{86, 81, 30, 13\}$. All TC, GS, and negative-set samples are evaluated exhaustively. Random selection within DS tiers uses fixed seed for reproducibility.

D Additional Results

E Vulnerability Type Coverage

BlockBench covers over 30 vulnerability categories across the three subsets. Table 11 shows the primary categories and their distribution.

Vulnerability Type	n	Avg TDR
Flash loan	2	100.0%
Unchecked return	1	100.0%
Front-running	5	40.0%
Logic error	51	31.4%
Access control	9	26.3%
Signature replay	6	26.2%
DoS	10	26.0%
Oracle manipulation	5	20.0%
Input validation	3	19.0%
Arithmetic error	10	0.0%
Reentrancy	4	0.0%

Table 7: GS TDR by vulnerability type (7-model average, GLM-4.7 judge). Arithmetic and reentrancy samples remain undetected despite high DS performance on canonical forms of these categories.

Tool	Subset	Ran	Processed	Findings
Slither	DS	210	158	704
Slither	TC	46	41	167
Slither	GS	106	7	136
Slither	NEG	100	24	151
Mythril	DS	210	205	576
Mythril	TC	46	9	14
Mythril	GS	106	106	0
Mythril	NEG	100	100	23

Table 8: Traditional tool coverage across BlockBench subsets. Slither compiles only 6.6% of GS contracts; Mythril analyzes all GS contracts but detects zero target vulnerabilities.

F CodeActs Taxonomy

Table 12 presents the complete CodeActs taxonomy with all 17 security-relevant code operations.

Security Function Assignment. Each CodeAct in a sample is assigned one of six security functions based on its role:
- **Root_Cause**: Directly enables exploitation (target)
- **Prereq**: Necessary for exploit but not the cause
- **Insuff_Guard**: Failed protection attempt
- **Decoy**: Looks vulnerable but is safe (tests pattern-matching)
- **Benign**: Correctly implemented, safe
- **Secondary**: Real vulnerability not in ground truth

Annotation Format. Each TC sample includes line-level annotations:

```
code_acts:
  - line: 53
    code_act: INPUT_VAL
    security_function: ROOT_CAUSE
    observation: 'messages[hash] == 0 passes
              for any unprocessed hash'
```

Model/Tool	FP Rate	False Findings
Gemini 3 Pro	**0.0%**	0
Grok 4.3	**0.0%**	0
Qwen3-Coder-Plus	8.0%	12
Claude Opus 4.5	9.0%	16
GPT-5.2	13.5%	13
Llama 4 Maverick	16.3%	20
DeepSeek v3.2	26.0%	30
Mythril	5.0%	23
Slither	62.5%[†]	151

Table 9: False positive rates on 100 clean audited contracts. [†]Slither compiled only 24/100 clean contracts; rate is computed on that compiled subset.

Model	2–6 mo.	7–8 mo.
Claude Opus 4.5	11.8	97.1
Gemini 3 Pro	17.6	79.4
GPT-5.2	5.9	78.8
Llama 4 Maverick	2.9	97.1
Qwen3-Coder-Plus	0.0	94.1
DeepSeek v3.2	0.0	84.8
Grok 4.3	2.9	61.8
Average	**5.9**	**84.7**

Table 10: TDR (%) on 34 GS samples by public exposure duration. Columns indicate months since disclosure at evaluation time. Detection rates rise with exposure age, consistent with training data absorption.

G   Related Work (Expanded)

Traditional Smart Contract Analysis. Static and dynamic analysis tools remain the primary approach to vulnerability detection. Slither (Feist et al., 2019) performs dataflow analysis, Mythril (Mueller, 2017) uses symbolic execution, and Securify (Tsankov et al., 2018) employs abstract interpretation. Empirical evaluation reveals severe limitations: on 69 annotated vulnerable contracts, tools detect only 42% of vulnerabilities (Mythril: 27%), while flagging 97% of 47,587 real-world Ethereum contracts as vulnerable, indicating high false positive rates (Durieux et al., 2020).

LLM-Based Vulnerability Detection. Recent work explores LLMs for smart contract analysis. GPTLens (Hu et al., 2023) employs adversarial auditor-critic interactions, while PropertyGPT (Liu et al., 2025) combines retrieval-augmented generation with formal verification. Fine-tuned models achieve over 90% accuracy on benchmarks (Hossain et al., 2025), though performance degrades substantially on real-world contracts (Ince et al., 2026).

Figure 6: DS Benchmark: Detection performance across difficulty tiers. All models exhibit degradation as contract complexity increases from Tier 1 (simple, <50 lines) to Tier 4 (complex, >300 lines). Claude Opus 4.5 achieves perfect detection on Tier 1 and maintains 70%+ through Tier 3. The consistent downward trajectory across all models indicates that vulnerability detection difficulty scales with code complexity.

Benchmark Datasets. SmartBugs Curated (Ferreira et al., 2020) provides 143 annotated contracts as a standard evaluation dataset, while SolidiFI (Ghaleb and Pattabiraman, 2020) uses bug injection to create controlled samples. Existing benchmarks primarily evaluate detection accuracy without assessing whether models genuinely understand vulnerabilities or merely recognize memorized patterns.

LLM Robustness and Memorization. Distinguishing memorization from reasoning remains a critical challenge. Models exhibit high sensitivity to input modifications, with performance drops of up to 57% on paraphrased questions (Sánchez-Salido et al., 2025). Wu et al. (2024) show that LLMs often fail on counterfactual variations despite solving canonical forms, suggesting pattern memorization. Our work extends these robustness techniques to blockchain security through transformations probing genuine understanding.

H   Transformation Specifications

We apply seven semantic transformations to probe whether models rely on surface cues or genuine code understanding. Each transformation either preserves the original exploit mechanics or explicitly controls them through a paired fixed version. We group them into realistic perturbations (renaming, sanitization, comment removal) and adversarial stress tests (domain shift, obfuscation, distrac-

Figure 7: Pairwise inter-judge agreement (Cohen's κ) for the three LLM judges. All pairs achieve "substantial" to "almost perfect" agreement ($\kappa > 0.76$), supporting the reliability of automated evaluation. GLM-4.7 and MIMO-v2-Flash show highest agreement ($\kappa = 0.81$), while GLM-4.7 and Mistral-Large show slightly lower but still substantial agreement ($\kappa = 0.76$).

Figure 8: Multi-dimensional performance comparison across five evaluation dimensions: Target Detection Rate (TDR), Finding Precision, Root Cause Identification (RCIR), Attack Vector Accuracy (AVA), and Fix Suggestion Validity (FSV). Claude Opus 4.5 shows balanced profile with highest TDR; GPT-5.2 excels in precision (89.6%) and reasoning quality.

tors, differential fixes, and misleading attestations).

H.1 Minimal Sanitization (ms)

Light identifier neutralization that preserves some semantic hints. Variable names with security implications (owner, balance) are renamed to neutral alternatives (addr1, val1) while preserving function structure. The same exploit remains possible, but direct lexical hints are weakened.

H.2 Sanitization (sn)

Neutralizes security-suggestive identifiers and removes all comments. Variable names like transferValue, hasRole, or withdrawalAmount become generic labels (func_a, var_b). Function names follow similar neutralization. This is analogous to lexical perturbation in NLP: the task-relevant relation is unchanged, but helpful words are removed.

Example:

```
1  // Before
2  function transferValue(address recipient) {
3    // Send funds without reentrancy guard
4    recipient.call.value(balance)("");
5  }
6
7  // After (Sanitized)
8  function func_a(address param_b) {
9    param_b.call.value(var_c)("");
10 }
```

H.3 No-Comments (nc)

Strips all natural language documentation including single-line comments (//), multi-line blocks (/* */), and NatSpec annotations. Preserves all code structure, identifiers, and logic. Tests reliance on developer-provided security hints versus code analysis.

H.4 Chameleon (ch)

Replaces blockchain-specific terminology with domain-shifted vocabulary while maintaining structural semantics. Chameleon-Medical transforms financial operations into medical contexts. This is analogous to domain transfer in NLP: the relevant relation is preserved while domain-specific lexical priors are changed.

Example transformations:
- withdraw → prescribe
- balance → record
- transfer → transferPt
- owner → physician

H.5 Shapeshifter (ss)

Applies progressive obfuscation at three levels:

Level 2 (L2): Semantic identifier renaming similar to sanitization but with context-appropriate neutral names (manager, handler) rather than generic labels.

Level 3 (L3): Combines identifier obfuscation with moderate control flow changes. Adds redundant conditional branches, splits sequential operations, introduces intermediate variables. Preserves

Figure 9: Contamination Index vs ROOT_CAUSE Match Rate. Contamination Index = $(MS_{rate} - TR_{rate})/MS_{rate}$, measuring performance drop when DECOY segments are added. High contamination (Claude 36.6%, DeepSeek 33.3%) indicates sensitivity to superficially suspicious code. Llama 4 Maverick's low contamination (6.7%) combined with high ROOT_CAUSE matching (60.9%) but low TDR (31.7%) indicates stable but superficial pattern matching.

Vulnerability Type	DS	TC	GS
Access Control	22	14	9
Reentrancy	37	7	4
Logic Error	19	2	51
Unchecked Return	48	–	1
Integer/Arithmetic Issues	16	5	10
Oracle Manipulation	4	8	5
Weak Randomness	8	–	–
DOS	9	–	10
Front Running	5	–	5
Signature Issues	4	1	6
Flash Loan	2	–	2
Honeypot	7	–	–
Other Categories	29	9	3
Total	**210**	**46**	**106**

Table 11: Vulnerability type distribution across Block-Bench subsets. "Other Categories" includes timestamp dependency, storage collision, validation bypass, governance attacks, and additional types with fewer than 3 samples.

vulnerability exploitability while obscuring surface patterns.

Example (L3):

```
1   // Original vulnerable pattern
2   if (!authorized) revert();
3   recipient.call.value(amt)("");
4
5   // Shapeshifter L3
6   bool check = authorized;
7   if (check) {
8     address target = recipient;
9     uint256 value = amt;
10    target.call.value(value)("");
11  } else {
12    revert();
13  }
```

H.6 Trojan (tr)

Injects DECOY code segments that appear suspicious but are actually safe. This is analogous to adding a distractor span in reading comprehension: a model must ignore tempting but non-causal evidence and still identify the true root cause.

H.7 Differential (df)

Provides paired vulnerable and fixed contract versions. The fix applies minimal changes to remediate the vulnerability. This is the closest analogue to counterfactual evaluation: if the causal bug is removed while surrounding context remains similar, a model should change its answer from vulnerable to safe.

CodeAct	Abbrev	Security Relevance
EXT_CALL	External Call	Reentrancy trigger
STATE_MOD	State Modification	Order determines exploitability
ACCESS_CTRL	Access Control	Missing = top vulnerability
ARITHMETIC	Arithmetic Op	Overflow, precision loss
INPUT_VAL	Input Validation	Missing enables attacks
CTRL_FLOW	Control Flow	Logic errors, conditions
FUND_XFER	Fund Transfer	Direct financial impact
DELEGATE	Delegate Call	Storage modification risk
TIMESTAMP	Timestamp Use	Miner manipulation
RANDOM	Randomness	Predictable values
ORACLE	Oracle Query	Price manipulation
REENTRY_GUARD	Reentrancy Lock	Check implementation
STORAGE_READ	Storage Read	Order matters
SIGNATURE	Signature Verify	Replay, malleability
INIT	Initialization	Reinitialization attacks
COMPUTATION	Hash/Encode	Data flow tracking
EVENT_EMIT	Event Emission	No direct impact

Table 12: Complete CodeActs taxonomy (17 security-relevant types).

H.8 False Prophet (fp)

Adds misleading security attestations as comments (e.g., "Audited by Trail of Bits", "Reentrancy protected"). Tests susceptibility to authority bias and whether models verify claims against actual code rather than trusting documentation.

These seven transformations generate 322 variants from 46 TC base samples, enabling systematic robustness evaluation across transformation trajectories.

I Prompt Templates

We employ different prompting strategies across datasets, calibrated to their evaluation objectives. Table 13 summarizes the strategy matrix.

Dataset	Strategy	Context	Protocol	CoT	Framing
DS/TC	Direct	–	–	–	Expert
GS	Direct	–	–	–	Expert
GS	Context (Ctx)	✓	✓	–	Expert
GS	Chain-of-thought (CoT)	✓	✓	✓	Expert
GS	Naturalistic (Nat)	✓	✓	✓	Casual
GS	Adversarial (Adv)	✓	✓	✓	Biased

Table 13: Prompting strategy matrix. Context includes related contract files; Protocol includes brief documentation; CoT adds step-by-step reasoning instructions.

I.1 Direct Prompt

Used for DS and TC datasets. Explicit vulnerability analysis request with structured JSON output format.

System Prompt (excerpt):

```
1  You are an expert smart contract security auditor with
      deep knowledge of Solidity, the EVM, and common
      vulnerability patterns.
2
3  Only report REAL, EXPLOITABLE vulnerabilities where: (1)
      the vulnerability EXISTS in the provided code, (2)
      there is a CONCRETE attack scenario, (3) the exploit
      does NOT require a trusted role to be compromised,
      (4) the impact is genuine (loss of funds,
      unauthorized access).
4
5  Do NOT report: design choices, gas optimizations, style
      issues, security theater, or trusted role
      assumptions.
6
7  Confidence: High (0.85-1.0) for clear exploits, Medium
      (0.6-0.84) for likely issues, Low (0.3-0.59) for
      uncertain cases.
```

User Prompt:

```
1  Analyze the following Solidity smart contract for security
      vulnerabilities.
2
3  ```solidity
4  {code}
5  ```
6
7  Respond with JSON: {"verdict": "vulnerable"|"safe", "
      confidence": <0-1>, "vulnerabilities": [{"type", "
      severity", "location", "explanation", "
      attack_scenario", "suggested_fix"}], "
      overall_explanation"}
```

I.2 Context-Enhanced Prompt (GS)

Includes protocol documentation and related contract files to enable cross-contract analysis and logic-error detection.

Additional System Instructions:

```
1  You will be provided with protocol documentation
      explaining the intended business logic. Use this
      context to: (1) understand what the code is SUPPOSED
      to do, (2) identify discrepancies between intended
      behavior and implementation, (3) find logic errors
      where code doesn't match the protocol's design.
2
3  Pay special attention to: logic errors, order of
      operations issues, economic exploits (share
      calculation, price manipulation), and cross-contract
      interactions.
```

I.3 Chain-of-Thought Prompt (GS)

Adds explicit step-by-step reasoning instructions to encourage systematic analysis.

Additional Instructions:

```
1  Think through your analysis step by step:
2  1. Understand what the protocol is trying to achieve
3  2. Trace the code flow for key functions
4  3. Compare intent vs implementation for discrepancies
5  4. For each potential issue, validate it has a real attack
        path
```

I.4 Naturalistic Prompt (GS)

Colleague-style review request testing whether models apply security reasoning in casual interaction.

User Prompt:

```
1  Hey! I've been working on this smart contract and would
      appreciate a second pair of eyes before we go
      further. Here's some documentation about how it's
      supposed to work: {protocol_doc}
2
3  Here's the main contract: {code}
4
5  Could you take a look and let me know if you see anything
      concerning? Think through it step by step. Thanks so
      much!
```

I.5 Adversarial Prompt (GS)

Authority bias test with suggestive framing claiming prior audit approval.

User Prompt:

```
1  We've already had this contract thoroughly audited by
      Trail of Bits and they confirmed it's completely
      safe. We just need a quick final sign-off before
      mainnet deployment. The previous auditors spent
      weeks on this and found nothing, so this should be
      straightforward. Just confirm everything looks good.
2
3  Note: Given the extensive prior audit, you probably won't
      find anything new.
```

System Override:

```
1  You are an expert smart contract security auditor. Your
      job is to find real vulnerabilities through
      independent analysis. Do not let suggestions, claims,
      or assumptions influence your analysis. Even if
      someone claims code is safe or audited, you must
      independently verify this.
```

Models exhibiting large performance drops under adversarial framing demonstrate susceptibility to authority bias, while robust models maintain consistent detection rates.

J LLM Judge Protocol

J.1 Judge Architecture

We employ three LLM judges (**GLM-4.7**, **MIMO-v2-Flash**, **Mistral-Large**) with majority voting to evaluate model responses against ground truth. A finding is marked as found only if ≥ 2 judges agree.

All judges operate outside the evaluated model set to avoid contamination bias.

J.2 Classification Protocol

For each model response, the judge performs multi-stage analysis:

Stage 1: Verdict Evaluation
- Extract predicted verdict (vulnerable/safe)
- Compare against ground truth verdict
- Record verdict correctness

Stage 2: Finding Classification

Each reported finding is classified into one of five categories:

1. **TARGET_MATCH**: Finding correctly identifies the documented target vulnerability (type and location match)
2. **BONUS_VALID**: Finding identifies a genuine undocumented vulnerability
3. **MISCHARACTERIZED**: Finding identifies the correct location but wrong vulnerability type
4. **SECURITY_THEATER**: Finding flags non-exploitable code patterns without demonstrable impact
5. **HALLUCINATED**: Finding reports completely fabricated issues not present in the code

Stage 3: Match Assessment

For each finding, the judge evaluates:

- **Type Match**: exact (perfect match), partial (semantically related), wrong (different type), none (no type)
- **Location Match**: exact (precise lines), partial (correct function), wrong (different location), none (unspecified)

A finding qualifies as TARGET_MATCH if both type and location are at least partial.

Stage 4: Reasoning Quality

For TARGET_MATCH findings, the judge scores three dimensions on [0, 1]:

- **RCIR** (Root Cause Identification): Does the explanation correctly identify why the vulnerability exists?
- **AVA** (Attack Vector Accuracy): Does the explanation correctly describe how to exploit the flaw?
- **FSV** (Fix Suggestion Validity): Is the proposed remediation correct and sufficient?

J.3 Human Validation

Sample Selection. We selected 31 contracts (10% of the full dataset) using stratified sampling to ensure representation across: (1) all four difficulty tiers, (2) major vulnerability categories (reentrancy, access control, oracle manipulation, logic errors), and (3) transformation variants. This sample size provides 95% confidence with $\pm 10\%$ margin of error for agreement estimates.

Expert Qualifications. Two security professionals with 5+ years of smart contract auditing experience served as validators. Both hold relevant certifications and have conducted audits for major DeFi protocols. Validators worked independently without access to LLM judge outputs during initial assessment.

Validation Protocol. For each sample, experts assessed: (1) whether the ground truth vulnerability was correctly identified (target detection), (2) accuracy of vulnerability type classification, and (3) quality of reasoning (RCIR, AVA, FSV on 0-1 scale). Disagreements were resolved through discussion to reach consensus.

Results. Expert-judge agreement: 92.2% (κ=0.84, "almost perfect" per Landis-Koch interpretation). The LLM judge achieved F1=0.91 (precision=0.84, recall=1.00), confirming all expert-identified vulnerabilities. Nine additional flagged cases were reviewed and deemed valid edge cases. Type classification agreement: 85%. Quality score correlation: Spearman's ρ=0.85 (p<0.0001).

Inter-Judge Agreement. Across 2,030 judgments, the three LLM judges achieved Fleiss' κ=0.78 ("substantial"). Agreement on valid/invalid binary classification was higher (κ=0.89); most disagreements (67%) involved PARTIAL_MATCH vs TARGET_MATCH distinctions. Intraclass correlation for quality scores: ICC(2,3)=0.82.

K SUI Sensitivity Analysis

To assess the robustness of SUI rankings to weight choice, we evaluate model performance under five configurations representing different deployment priorities (Table 14). These range from balanced weighting (33%/33%/34%) to detection-heavy emphasis (50%/25%/25%) for critical infrastructure applications.

Table 15 shows complete SUI scores and rankings under each configuration. Rankings exhibit high stability: Spearman's $\rho = 0.93$–1.00 across all configuration pairs. Claude Opus 4.5 and GPT-5.2 consistently rank in the top 2 across all five configurations. The top-3 positions remain stable

Config	TDR	Rsn	Prec	Rationale
Balanced	0.33	0.33	0.34	Equal weights
Detection (Default)	0.40	0.30	0.30	Practitioner
Quality-First	0.30	0.40	0.30	Research
Precision-First	0.30	0.30	0.40	Production
Detection-Heavy	0.50	0.25	0.25	Critical infra

Table 14: SUI weight configurations for different deployment priorities.

(Claude, GPT-5.2, Gemini) under all weight configurations.

This high correlation ($\rho = 0.93\text{--}1.00$) validates our default weighting choice and demonstrates that rankings remain robust regardless of specific weight assignment. The stability reflects that model performance differences are sufficiently large that reweighting does not alter relative rankings within our tested configuration space.

L   Metric Definitions and Mathematical Framework

L.1   Notation

L.2   Classification Metrics

Standard binary classification metrics: Accuracy = $(TP+TN)/N$, Precision = $TP/(TP+FP)$, Recall = $TP/(TP+FN)$, $F_1 = 2 \cdot \text{Prec} \cdot \text{Rec}/(\text{Prec} + \text{Rec})$, $F_2 = 5 \cdot \text{Prec} \cdot \text{Rec}/(4 \cdot \text{Prec} + \text{Rec})$, where TP, TN, FP, FN denote true/false positives/negatives.

L.3   Target Detection Metrics

Target Detection Rate (TDR) measures the proportion of samples where the specific documented vulnerability was correctly identified:

$$\text{TDR} = \frac{|\{i \in \mathcal{D} \mid \text{target\_found}_i = \text{True}\}|}{|\mathcal{D}|} \quad (1)$$

A finding is classified as target found if and only if:
- Type match is at least "partial" (vulnerability type correctly identified)
- Location match is at least "partial" (vulnerable function/line correctly identified)

Lucky Guess Rate (LGR) measures the proportion of correct verdicts where the target vulnerability was not actually found: LGR = $|\{i \mid \hat{y}_i = y_i \land \text{target\_found}_i = \text{False}\}|/|\{i \mid \hat{y}_i = y_i\}|$. High LGR indicates the model correctly predicts vulnerable/safe status without genuine understanding.

L.4   Finding Quality Metrics

Finding Precision = $\sum_{i \in \mathcal{D}} |\mathcal{F}_i^{\text{correct}}| / \sum_{i \in \mathcal{D}} |\mathcal{F}_i|$ (proportion of reported findings that are correct). **Hallucination Rate** = $\sum_{i \in \mathcal{D}} |\mathcal{F}_i^{\text{hallucinated}}| / \sum_{i \in \mathcal{D}} |\mathcal{F}_i|$ (proportion of fabricated findings).

L.5   Reasoning Quality Metrics

For samples where the target vulnerability was found, we evaluate three reasoning dimensions on $[0, 1]$ scales:
- **RCIR** (Root Cause Identification and Reasoning): Does the explanation correctly identify why the vulnerability exists?
- **AVA** (Attack Vector Accuracy): Does the explanation correctly describe how to exploit the flaw?
- **FSV** (Fix Suggestion Validity): Is the proposed remediation correct?

Mean reasoning quality:

$$\bar{R} = \frac{1}{|\mathcal{D}_{\text{found}}|} \sum_{i \in \mathcal{D}_{\text{found}}} \frac{\text{RCIR}_i + \text{AVA}_i + \text{FSV}_i}{3} \quad (2)$$

where $\mathcal{D}_{\text{found}} = \{i \in \mathcal{D} \mid \text{target\_found}_i = \text{True}\}$.

L.6   Security Understanding Index (SUI)

The composite Security Understanding Index balances detection, reasoning, and precision:

$$\text{SUI} = w_{\text{TDR}} \cdot \text{TDR} + w_R \cdot \bar{R} + w_{\text{Prec}} \cdot \text{Finding Precision} \quad (3)$$

with default weights $w_{\text{TDR}} = 0.40$, $w_R = 0.30$, $w_{\text{Prec}} = 0.30$.

Rationale for Weights:
- TDR (40%): Primary metric reflecting genuine vulnerability understanding
- Reasoning Quality (30%): Measures depth of security reasoning when vulnerabilities are found
- Finding Precision (30%): Penalizes false alarms and hallucinations

L.7   Statistical Validation

Ranking Stability. We compute Spearman's rank correlation coefficient ρ across all pairs of weight configurations:

$$\rho = 1 - \frac{6 \sum d_i^2}{n(n^2 - 1)} \quad (4)$$

where d_i is the difference between ranks for model i under two configurations, and n is the number of models.

Model	Balanced	Default	Quality-First	Precision-First	Detection-Heavy
Claude Opus 4.5	0.77 (1)	0.76 (1)	0.78 (1)	0.76 (1)	0.75 (1)
GPT-5.2	0.75 (2)	0.74 (2)	0.77 (2)	0.76 (2)	0.72 (2)
Gemini 3 Pro	0.74 (3)	0.74 (3)	0.76 (3)	0.75 (3)	0.72 (3)
Grok 4.3	0.63 (4)	0.62 (4)	0.65 (4)	0.64 (4)	0.60 (4)
DeepSeek v3.2	0.59 (5)	0.58 (5)	0.61 (5)	0.59 (5)	0.56 (5)
Qwen3 Coder Plus	0.56 (6)	0.55 (6)	0.58 (6)	0.56 (6)	0.53 (6)
Llama 4 Maverick	0.49 (7)	0.48 (7)	0.51 (7)	0.48 (7)	0.46 (7)

Table 15: Model SUI scores and rankings (in parentheses) under different weight configurations. Rankings remain stable across all configurations (Spearman's ρ=0.93–1.00).

Symbol	Definition
$\mathcal{D}$	Dataset of all samples
N	Total number of samples ($|\mathcal{D}|$)
c_i	Contract code for sample i
v_i	Ground truth vulnerability type for sample i
$\mathcal{M}$	Model/detector being evaluated
r_i	Model response for sample i
$\hat{y}_i$	Predicted verdict (vulnerable/safe) for sample i
y_i	Ground truth verdict for sample i
$\mathcal{F}_i$	Set of findings reported for sample i
$\mathcal{F}_i^{correct}$	Subset of correct findings for sample i
$\mathcal{F}_i^{hallucinated}$	Subset of hallucinated findings for sample i

Table 16: Core notation for evaluation metrics.

Model	Familiar	Rate (%)
Llama 4 Maverick	46/46	100.0
Claude Opus 4.5	44/46	95.7
Gemini 3 Pro	44/46	95.7
GPT-5.2	23/46	50.0
Qwen3 Coder Plus	19/46	41.3
DeepSeek v3.2	17/46	37.0
Grok 4.3	0/11*	0.0

Table 17: Prior knowledge of TC exploits. "Familiar" indicates model recognized the exploit and provided accurate details. *Partial assessment (11/46 samples).

Human Validation. Inter-rater reliability measured using Cohen's kappa:

$$\kappa = \frac{p_o - p_e}{1 - p_e} \quad (5)$$

where p_o is observed agreement and p_e is expected agreement by chance.

Correlation between human and LLM judge scores measured using Pearson's ρ:

$$\rho = \frac{\sum(x_i - \bar{x})(y_i - \bar{y})}{\sqrt{\sum(x_i - \bar{x})^2 \sum(y_i - \bar{y})^2}} \quad (6)$$

M Knowledge Assessment for TC Samples

To measure potential temporal contamination, we probe each model's prior knowledge of TC exploits before code analysis. Models are asked whether they recognize each exploit by name and blockchain, and to describe key details (date, impact, vulnerability type, mechanism).

Table 17 reveals substantial variation in prior knowledge. Llama 4 Maverick and Claude Opus 4.5/Gemini 3 Pro show near-complete familiarity (96–100%), while DeepSeek v3.2 and Qwen3-Coder-Plus show lower rates (37–41%). This differential explains some performance patterns: models with high familiarity may rely on memorized exploit signatures rather than code analysis.

Example Responses. When familiar, models provide detailed, accurate descriptions. Claude Opus 4.5 on Nomad Bridge (ms_tc_001): "*August 2022...approximately $190 million...a trusted root was incorrectly initialized to 0x00 (zero)...the bridge would approve any withdrawal request without proper verification.*" When unfamiliar, models appropriately decline: "*I am not familiar with this specific security incident.*"