DIFFUSION PROBABILISTIC FIELDS

ABSTRACT

Diffusion probabilistic models have quickly become a major approach for generative modeling of images, 3D geometry, video and other domains. However, to adapt diffusion generative modeling to these domains the denoising network needs to be carefully designed for each domain independently, oftentimes under the assumption that data lives in an Euclidean grid. In this paper we introduce Diffusion Probabilistic Fields (DPF), a diffusion model that can learn distributions over continuous functions defined over metric spaces, commonly known as *fields*. We extend the formulation of diffusion probabilistic models to deal with this field parametrization in an explicit way, enabling us to define and end-to-end learning algorithm that side-steps the requirement of representing fields with latent vectors as in previous approaches (Dupont et al., 2022a; Du et al., 2021). We empirically show that, while using the same denoising network, DPF effectively deals with different modalities like 2D images and 3D geometry, in addition to modeling distributions over fields defined on non-Euclidean metric spaces.

1 INTRODUCTION

Diffusion probabilistic modeling has quickly become a central approach for learning data distributions, obtaining impressive empirical results across multiple domains like images (Nichol & Dhariwal, 2021), videos (Ho et al., 2022) or even 3D geometry (Luo & Hu, 2021). In particular, Denoising Diffusion Probabilistic Models (often referred to as DDPMs or diffusion generative models) (Ho et al., 2020; Nichol & Dhariwal, 2021) and their continuous-time extension (Song et al., 2021b) both present a training objective that is more stable than precursors like generative adversarial nets (GANs) (Goodfellow et al., 2014) or energy-based models (EBMs) (Du et al., 2020). In addition, diffusion generative models have shown to empirically outperform GANs in the image domain (Dhariwal & Nichol, 2021) and to suffer less from mode-seeking pathologies during training (Kodali et al., 2017).

A diffusion generative model consists of three main components: the forward (or *diffusion*) process, the backward (or *inference*) process, and the denoising network (also referred to as the *score network*[1] due to its equivalence with denoising score-matching approaches Dickstein et al. (2015)). A substantial body of work has addressed different definitions of the forward and backward processes (Rissanen et al., 2022; Bansal et al., 2022; Song et al., 2021a), focusing on the image domain. However, there are two caveats with current diffusion models that remain open. The first one is that data is typically assumed to live on a discrete Euclidean grid (exceptions include work on molecules (Hoogeboom et al., 2022) and point clouds (Luo & Hu, 2021)). The second one is that the denoising network is heavily tuned for each specific data domain, with different network architectures used for images (Nichol & Dhariwal, 2021), video (Ho et al., 2022), or geometry (Luo & Hu, 2021).

In order to extend the success of diffusion generative models to the large number of diverse areas in science and engineering, a unification of the score formulation is required. Importantly, a unification enables use of the same score network across different data domains exhibiting different geometric structure without requiring data to live in or to be projected into a discrete Euclidean grid.

To achieve this, in this paper, we introduce the Diffusion Probabilistic Field (DPF). DPFs make progress towards the ambitious goal of unifying diffusion generative modeling across domains by learning distributions over continuous functions. For this, we take a functional view of the data, interpreting a data point $x \in \mathbb{R}^d$ as a function $f : \mathcal{M} \to \mathcal{Y}$ (Dupont et al., 2022a; Du et al., 2021).

---

[1]We use the terms score network/function and denoising network/function exchangeably in the paper.

The function f maps elements from a metric space $\mathcal{M}$ to a signal space $\mathcal{Y}$. This functional view of the data is commonly referred to as a *field* representation (Xie et al., 2022), which we use to refer to functions of this type. An illustration of this field interpretation is provided in Fig. 1. Using the image domain as an illustrative example we can see that one can either interpret images as multidimensional array $\boldsymbol{x}_i \in \mathbb{R}^{h \times w} \times \mathbb{R}^3$ or as field $f : \mathbb{R}^2 \to \mathbb{R}^3$ that maps 2D pixel coordinates to RGB values. This field view enables a unification of seemingly different data domains under the same parametrization. For instance, 3D geometry data is represented via $f : \mathbb{R}^3 \to \mathbb{R}$, and spherical signals become fields $f : \mathbb{S}^2 \to \mathbb{R}^d$.

In an effort to unify generative modeling across different data domains, field data representations have shown promise in three recent approaches: From data to functa (FDN) (Dupont et al., 2022a), GEnerative Manifold learning (GEM) (Du et al., 2021) and Generative Adversarial Stochastic Process (GASP) (Dupont et al., 2022b). The first two approaches adopt a latent field parametrization (Park et al., 2019), where a field network is parametrized via a Hypernetwork (Ha et al., 2017) that takes as input a trainable latent vector. During training, a latent vector for each field is optimized in an initial reconstruction stage (Park et al., 2019). In FDN (Dupont et al., 2022a) the authors then propose to learn the distribution of optimized latents in an independent second training stage, similar to the approach by Rombach et al. (2022); Vahdat et al. (2021). Du et al. (2021) define additional latent neighborhood regularizers during the reconstruction stage. Sampling is then performed in a non-parametric way: one chooses a random latent vector from the set of optimized latents and projects it into its local neighborhood before adding Gaussian noise. See Fig. 2 for a visual summary of the differences between FDN (Dupont et al., 2022a), GEM (Du et al., 2021) and our DPF. GASP (Dupont et al., 2022b) employs a GAN paradigm: the generator produces a field while the discriminator operates on discrete points from the field, and distinguishes input source, *i.e.*, either real or generated.

In contrast to prior work (Dupont et al., 2022a; Du et al., 2021; Dupont et al., 2022b), we formulate a *diffusion generative model* over functions in a *single-stage* approach. This permits efficient end-to-end training without relying on an initial reconstruction stage or without tweaking the adversarial game, which we empirically find to lead to compelling results. Our contributions are summarized as follows:

- We introduce the Diffusion Probabilistic Field (DPF) which extends the formulation of diffusion generative models to field representations.
- We formulate a probabilistic generative model over fields in a single-stage model using an explicit field parametrization, which differs from recent work (Dupont et al., 2022a; Du et al., 2021) and simplifies the training process by enabling end-to-end learning.
- We empirically demonstrate that DPF can successfully capture distributions over functions across different domains like images, 3D geometry and spherical data, outperforming recent work (Dupont et al., 2022a; Du et al., 2021; Dupont et al., 2022b).

2 BACKGROUND: DENOISING DIFFUSION PROBABILISTIC MODELS

Denoising Diffusion Probabilistic Models (DDPMs) belong to the broad family of latent variable models. We refer the reader to Everett (2013) for an in depth review. In short, to learn a parametric data distribution $p_\theta(\boldsymbol{x}_0)$ from an empirical distribution of finite samples $q(\boldsymbol{x}_0)$, DDPMs reverse a diffusion Markov Chain (*i.e.*, the forward diffusion process) that generates latents $\boldsymbol{x}_{1:T}$ by gradually adding Gaussian noise to the data $\boldsymbol{x}_0 \sim q(\boldsymbol{x}_0)$ for T time-steps as follows:

$$q(\boldsymbol{x}_t|\boldsymbol{x}_{t-1}) := \mathcal{N}\left(\boldsymbol{x}_{t-1}; \sqrt{\bar{\alpha}_t}\boldsymbol{x}_0, (1 - \bar{\alpha}_t)\mathbf{I}\right). \tag{1}$$

Here, $\bar{\alpha}_t$ is the cumulative product of fixed variances with a handcrafted scheduling up to time-step t. Ho et al. (2020) highlight two important observations that make training of DDPMs efficient: i) Eq. (1) adopts sampling in closed form for the forward diffusion process. ii) reversing the diffusion process is equivalent to learning a sequence of denoising (or score) networks ϵ_θ, with tied weights. Reparametrizing Eq. (1) as $\boldsymbol{x}_t = \sqrt{\bar{\alpha}_t}\boldsymbol{x}_0 + \sqrt{1 - \bar{\alpha}_t}\epsilon$ results in the "simple" DDPM loss

$$\mathcal{L}_\theta = \mathbb{E}_{t\sim[0,T],\boldsymbol{x}_0\sim q(\boldsymbol{x}_0),\epsilon\sim\mathcal{N}(0,\mathbf{I})}\left[\|\epsilon - \epsilon_\theta(\sqrt{\bar{\alpha}_t}\boldsymbol{x}_0 + \sqrt{1 - \bar{\alpha}_t}\epsilon, t)\|^2\right], \tag{2}$$

which makes learning of the data distribution $p_\theta(\boldsymbol{x}_0)$ both efficient and scalable.

Figure 1: The left panel shows the parametrization of each data domain as a field. For visualization purposes we use the color red to denote the input to the field function (*e.g.*, a metric space $\mathcal{M}$ where the field is defined). In the right panel we show the graphical model of DPF, a diffusion generative model to capture distributions over fields. In DPF the latent variables are fields $f_{1:T}$ that can be evaluated continuously. By taking a field parametrization of data we unify diffusion generative modeling across different domains (images, 3D shapes, spherical images) using the same score network implementation.

At inference time, we compute $\boldsymbol{x}_0 \sim p_\theta(\boldsymbol{x}_0)$ via ancestral sampling (Ho et al., 2020). Concretely, we start by sampling $\boldsymbol{x}_T \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$ and iteratively apply the score network ϵ_θ to denoise $\boldsymbol{x}_T$, thus reversing the diffusion Markov Chain to obtain $\boldsymbol{x}_0$. Sampling $\boldsymbol{x}_{t-1} \sim p_\theta(\boldsymbol{x}_{t-1}|\boldsymbol{x}_t)$ is equivalent to computing the update

$$\boldsymbol{x}_{t-1} = \frac{1}{\sqrt{\alpha_t}} \left(\boldsymbol{x}_t - \frac{1 - \alpha_t}{\sqrt{1 - \alpha_t}} \epsilon_\theta(\boldsymbol{x}_t, t) \right) + \mathbf{z}, \tag{3}$$

where at each inference step a stochastic component $\mathbf{z} \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$ is injected, resembling sampling via Langevin dynamics (Welling & Teh, 2011).

A central part of the learning objective in Eq. (2) is the score network ϵ_θ, which controls the marginal distribution $p_\theta(\boldsymbol{x}_{t-1}|\boldsymbol{x}_t)$. Notably, score networks are heavily tailored for each specific data domain. For example, in the image domain, score networks are based on a UNet (Ronneberger et al., 2015) with multiple self-attention blocks (Nichol & Dhariwal, 2021). In contrast, for 3D structures like molecules, score networks are based on graph neural nets (Hoogeboom et al., 2022). To unify the design of score networks across data domains, in this paper, we present the diffusion probabilistic field (DPF), which introduces a unified formulation of the score network that can be applied to multiple domains by representing data samples as fields.

3 DIFFUSION PROBABILISTIC FIELDS

A diffusion probabilistic field (DPF) is a diffusion generative model that captures distributions over fields. We are given observations in the form of an empirical distribution $q(f_0)$ over fields (living in an unknown field manifold) where a field $f_0 : \mathcal{M} \to \mathcal{Y}$ maps elements from a metric space $\mathcal{M}$ to a signal space $\mathcal{Y}$. For example, in the image domain an image can be defined as a field that maps 2D pixel coordinates to RGB values $f_0 : \mathbb{R}^2 \to \mathbb{R}^3$. In DPF the latent variables $f_{1:T}$ are fields that can be continuously evaluated. To tackle the problem of learning a diffusion generative model over fields we need to successfully deal with the infinite dimensional nature of the field representation in the forward process as well as in the score network and backward process.

We adopt an explicit field parametrization, where a field is characterized by a set of coordinate-signal pairs $\{(\boldsymbol{m}_c, \boldsymbol{y}_{(c,0)})\}$, $\boldsymbol{m}_c \in \mathcal{M}, \boldsymbol{y}_{(c,0)} \in \mathcal{Y}$, which we denote as *context pairs*. For clarity we row-wise stack context pairs and refer to the resulting matrix via $\mathbf{C}_0 = [\mathbf{M}_c, \mathbf{Y}_{(c,0)}]$. Here, $\mathbf{M}_c$ denotes the coordinate portion of all context pairs and $\mathbf{Y}_{(c,0)}$ denotes the signal portion of all context pairs at time $t = 0$. Note that the coordinate portion does not depend on the time-step by

Figure 2: In DPF we explicitly parameterize a field by a set of coordinate-signal pairs, or *context pairs*, as opposed to a latent vector z_0 as in FDN (Dupont et al., 2022a) or GEM (Du et al., 2021). This explicit field parametrization allows us to side-step the reconstruction training stage of prior approaches and instead *directly model the distribution of fields* rather than the distribution of latents that encode fields.

design.[2] This is a key difference with respect to FDN (Dupont et al., 2022a) or GEM (Du et al., 2021), both of which adopt a latent parametrization of fields, where a learnt field $\hat{f} : \Psi(z_0) \times \mathcal{M} \to \mathcal{Y}$ is parametrized by a latent weight vector z_0 through a hypernetwork model Ψ (Ha et al., 2017). Using a latent parametrization forces a reconstruction stage in which latents z_0 are first optimized to reconstruct their corresponding field (Park et al., 2019; Du et al., 2021) (*i.e.*, defining an empirical distribution of latents $q(z_0)$ living in an unknown latent manifold). A prior $p_\theta(z_0)$ over latents is then learnt *independently* in a second training stage (Dupont et al., 2022a). In contrast, our explicit field parametrization allows us to formulate a *score field network*, enabling DPF to directly model a distribution over fields, which results in improved performance (cf. Sect. 4). Fig. 2 depicts the differences between latent field parametrizations in FDN (Dupont et al., 2022a) and GEM (Du et al., 2021), and the explicit field parametrization in DPF.

Adopting an explicit field parametrization, we define the forward process for context pairs by diffusing the signal and keeping the coordinates fixed. Consequently the forward process for context pairs reads as follows:

$$\mathbf{C}_t = [\mathbf{M}_c, \mathbf{Y}_{(c,t)} = \sqrt{\bar{\alpha}_t}\mathbf{Y}_{(c,0)} + \sqrt{1 - \bar{\alpha}_t}\epsilon_c], \tag{4}$$

where $\epsilon_c \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$ is a noise vector of the appropriate size. We now turn to the task of formulating a score network for fields. By definition, the score network needs to take as input the context pairs (*i.e.*, the field parametrization), and needs to accept being evaluated continuously in $\mathcal{M}$ in order to be a field. We do this by using *query pairs* $\{m_q, y_{(q,0)}\}$. Equivalently to context pairs, we row-wise stack query pairs and denote the resulting matrix as $\mathbf{Q}_0 = [\mathbf{M}_q, \mathbf{Y}_{(q,0)}]$. Note that the forward diffusion process is equivalently defined for both context and query pairs:

$$\mathbf{Q}_t = [\mathbf{M}_q, \mathbf{Y}_{(q,t)} = \sqrt{\bar{\alpha}_t}\mathbf{Y}_{(q,0)} + \sqrt{1 - \bar{\alpha}_t}\epsilon_q], \tag{5}$$

---

[2]We assume the geometry of fields does not change.

Algorithm 1 Training

1: **repeat**
2:   $(\mathbf{C}_0, \mathbf{Q}_0) \sim \text{Uniform}(q(f_0))$
3:   $t \sim \text{Uniform}(\{1, \ldots, T\})$
4:   $\epsilon_c \sim \mathcal{N}(\mathbf{0}, \mathbf{I}), \epsilon_q \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$
5:   $\mathbf{C}_t = [\mathbf{M}_c, \sqrt{\bar{\alpha}_t}\mathbf{Y}_{(c,0)} + \sqrt{1 - \bar{\alpha}_t}\epsilon_c]$
6:   $\mathbf{Q}_t = [\mathbf{M}_q, \sqrt{\bar{\alpha}_t}\mathbf{Y}_{(q,0)} + \sqrt{1 - \bar{\alpha}_t}\epsilon_q]$
7:   Take gradient descent step on
    $\nabla_\theta \|\epsilon_Q - \epsilon_\theta(\mathbf{C}_t, t, \mathbf{Q}_t)\|^2$
8: **until** converged

Figure 3: **Left:** DPF training algorithm. **Right**: Visual depiction of a training iteration for a field in the image domain. See Sect. 3 for definitions.

Algorithm 2 Sampling

1: $\mathbf{Q}_T = [\mathbf{M}_q, \mathbf{Y}_{(q,t)} \sim \mathcal{N}(\mathbf{0}_q, \mathbf{I}_q)]$
2: $\mathbf{C}_T \subseteq \mathbf{Q}_T$ ▷ Random subset
3: **for** $t = T, \ldots, 1$ **do**
4:   $\boldsymbol{z} \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$ if $t > 1$, else $\boldsymbol{z} = \mathbf{0}$
5:   $\mathbf{Y}_{(q,t-1)} = \frac{1}{\sqrt{\alpha_t}}\left(\mathbf{Y}_{(q,t)} - \frac{1-\alpha_t}{\sqrt{1-\bar{\alpha}_t}}\epsilon_\theta(\mathbf{C}_t, t, \mathbf{Q}_t)\right) + \sigma_t\boldsymbol{z}$
6:   $\mathbf{Q}_{t-1} = [\mathbf{M}_q, \mathbf{Y}_{(q,t-1)}]$
7:   $\mathbf{C}_{t-1} \subseteq \mathbf{Q}_{t-1}$ ▷ Same subset as in step 2
8: **end for**
9: **return** f_0 evaluated at coordinates $\mathbf{M}_q$

Figure 4: **Left:** DPF sampling algorithm. **Right**: Visual depiction of the sampling process for a field in the image domain.

where $\epsilon_q \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$ is a noise vector of the appropriate size. However, the underlying field is solely defined by context pairs, and query pairs merely act as points on which to evaluate the score network. The resulting *score field* model is formulated as follows:

$$\epsilon_q = \epsilon_\theta(\mathbf{C}_t, t, \mathbf{Q}_t). \tag{6}$$

Using the explicit field characterization and the score field network in Eq. (6), we obtain the training and inference procedures in Alg. 1 and Alg. 2, respectively, which are accompanied by illustrative examples for a field representation of images. For training, we uniformly sample context and query pairs from $f_0 \sim \text{Uniform}(q(f_0))$ and only corrupt their signal using the forward process in Eq. (4) and Eq. (5). We then train the score field network given in Eq. (6) to denoise the signal in query pairs, given context pairs.

During sampling, to generate a field $f_0 \sim p_\theta(f_0)$ we first define query pairs $\mathbf{Q}_T = [\mathbf{M}_q, \mathbf{Y}_{(q,T)} \sim \mathcal{N}(\mathbf{0}, \mathbf{I})]$ on which the field will be evaluated. Note that the number of points on which the score field is evaluated during sampling has to be fixed (*e.g.*, to generate an image with $32 \times 32 = 2048$ pixels we define 2048 query pairs $\mathbf{Q}_T$ at time $t = T$). We then let context pairs be a random subset of the query pairs. We use the context pairs to denoise query pairs and follow ancestral sampling as in the vanilla DDPM (Ho et al., 2020).[3] Note that during inference the coordinates of the context and query pairs do not change, only their corresponding signal value. The result of sampling is given by $\mathbf{Q}_0$ which is the result of evaluating f_0 at coordinates $\mathbf{M}_q$.

---

[3]More efficient sampling approaches like DDIM (Song et al., 2021a) are trivially adapted to DPF.

CelebA-HQ 64^2	FID ↓	Precision ↑	Recall ↑
VAE (Kingma & Welling, 2014)	175.33	0.799	0.001
StyleGAN2 (Karras et al., 2020)	5.90	0.618	0.481
FDN (Dupont et al., 2022a)	40.40	0.577	0.397
GEM (Du et al., 2021)	30.42	0.642	0.502
GASP (Dupont et al., 2022b)	13.50	0.836	0.312
DPF (ours)	13.21	0.866	0.347

CIFAR-10 32^2	FID ↓	IS ↑
PixelIQN (Ostrovski et al., 2018)	49.46	5.29
NCSNv2 (Song & Ermon, 2020)	31.75	-
StyleGAN2 (Karras et al., 2020)	3.26	9.74
DDPM (Ho et al., 2020)	3.17	9.46
GEM (Du et al., 2021)	23.83	8.36
DPF (ours)	15.10	8.43

Table 1: **Quantitative evaluation of image generation** on CelebA-HQ (Karras et al., 2018). The middle bar separates domain-specific (*top*) from domain-agnostic approaches (*bottom*).

Table 2: **Quantitative evaluation of image generation** on CIFAR-10 (Krizhevsky, 2009).The middle bar separates domain-specific (*top*) from domain-agnostic approaches (*bottom*).

4 EXPERIMENTAL RESULTS

We present results on multiple domains: 2D image data, 3D geometry data, and spherical data. Across all domains we use the same score network architecture. We only adjust the dimensionality of the metric space $\mathcal{M}$ and the signal space $\mathcal{Y}$ as well as the network capacity (*i.e.*, number of layers, hidden units per layer, etc.) when needed. We implement the field score network ϵ_θ using a PerceiverIO architecture (Jaegle et al., 2022), an efficient transformer that enables us to scale the number of both context pairs and query pairs. Additional architecture hyperparameters and implementation details are provided in the appendix.

4.1 2D IMAGES

We present empirical results on two standard image benchmarks: CelebA-HQ (Karras et al., 2018) 64^2 and CIFAR-10 (Krizhevsky, 2009) 32^2. All image datasets are mapped to their field representation, where an image $x \in \mathbb{R}^{h \times w \times 3}$ is represented as a function $f : \mathbb{R}^2 \to \mathbb{R}^3$ defined by coordinate-RGB pairs. In Tab. 1 and Tab. 2 we compare DPF with FDN (Dupont et al., 2022a), GEM (Du et al., 2021), and GASP (Dupont et al., 2022b), which are domain-agnostic generative models that employ field representations. For completeness, we also report results for the domain-specific VAE (Kingma & Welling, 2014), StyleGAN2 (Karras et al., 2020) and DDPM (Ho et al., 2020). Similarly, on CIFAR-10 data we compare with multiple domain-specific methods including auto-regressive (Ostrovski et al., 2018) and score-based (Song & Ermon, 2020) approaches. We report Fréchet Inception Distance (FID) (Heusel et al., 2017), Inception Score (IS) (Salimans et al., 2016) and precision/recall metrics (Sajjadi et al., 2018) for different datasets.

We observe that DPF obtains compelling generative performance on both CelebA-HQ 64^2 and CIFAR-10 data. In particular, DPF outperforms recent approaches that aim to unify generative modeling across different data domains such as FDN (Dupont et al., 2022a) and GEM (Du et al., 2021). In particular, we observe that DPF obtains the best Precision score across all domain-agnostic approaches on CelebA-HQ 64^2 (Karras et al., 2018), as well as very competitive FID scores. One interesting finding is that GASP Dupont et al. (2022b) reports comparable FID score than DPF. However, when inspecting qualitative examples shown in Fig. 5 we observe GASP samples to contain artifacts typically obtained by adversarial approaches. In contrast, samples generated from DPF are more coherent and without artifacts. We believe the texture diversity caused by these artifacts to be the reason for the difference in FID scores between GASP and DPF (similar findings were discussed in (Dupont et al., 2022a)). Finally, when studying empirical results on CIFAR-10 shown in Tab. 2, we again see that DPF performs better than GEM (Du et al., 2021) both in terms of FID and IS.

Notably, we can observe a gap between domain-agnostic and the most recent domain-specific approaches such as StyleGAN2 (Karras et al., 2020) and DDPM (Ho et al., 2020). This gap is a result of two main factors. First, domain-specific approaches can incorporate design choices tailored to their domain in the score network (*i.e.*, translation equivariance in CNNs for images). Second, the training and inference settings are typically different for the domain-agnostic and domain-specific approaches reported in Tab. 1 and Tab. 2. To further study this issue we refer readers to Sect. A, where we compare the performance of DPF and DDPM (Ho et al., 2020) using the same training and evaluation settings.

Figure 5: **Qualitative comparison of different domain-agnostic approaches** on CelebA-HQ 64^2 (Karras et al., 2018). DPF generates diverse and globally consistent samples, without the background blurriness of two-stage approaches like FDN (Dupont et al., 2022a) and GEM (Du et al., 2021) that rely on an initial reconstruction step, or the artifacts of adversarial approaches like GASP (Dupont et al., 2022b). All the images in this figure have been generated by a model, *i.e.*, we do not directly reproduce images from the CelebA-HQ dataset (Karras et al., 2018).

Figure 6: **Qualitative comparison** of GEM (Du et al., 2021) and DPF on CIFAR-10 (Krizhevsky, 2009). DPF generates crisper samples than GEM (Du et al., 2021) while also better capturing the empirical distribution.

Finally, we show qualitative generation results for domain-agnostic approaches on CelebA-HQ 64^2 (Karras et al., 2018) and CIFAR-10 (Krizhevsky, 2009) in Fig. 5 and Fig. 6, respectively. We note that for CelebA-HQ, DPF generates diverse and globally consistent samples, without the blurriness (particularly in the backgrounds) observed in two-stage approaches (Dupont et al., 2022a; Du et al., 2021) that rely on an initial reconstruction step, or the artifacts of adversarial approaches (Dupont et al., 2022b). When evaluated on CIFAR-10 (Krizhevsky, 2009), we see that DPF generates crisper and more diverse results than GEM (Du et al., 2021).

4.2 3D GEOMETRY

We now turn to the task of modeling distributions over 3D objects and present results on the ShapeNet dataset (Chang et al., 2015). We follow the settings in GEM (Du et al., 2021) and train our model on ~ 35k ShapeNet objects, where each object is represented as a voxel grid at a 64^3 resolution. Each object is then represented as a function $f : \mathbb{R}^3 \rightarrow \mathbb{R}^1$. Following the settings of GEM (Du et al., 2021), we report coverage and MMD metrics (Achlioptas et al., 2018) computed from sampling 2048 points on the meshes obtained from the ground truth and generated voxel grids. We compare them using the Chamfer distance. In Tab. 3 we compare DPF performance with 3 baselines: Latent GAN (Chen & Zhang, 2019), FDN (Dupont et al., 2022a) and GEM (Du et al., 2021). We train DPF at 32^3 resolution. During sampling we evaluate 32^3 query pairs on the score field, then reshape the results to a 3D grid of 32^3 resolution and tri-linearly up-sample to the final 64^3 resolution for computing evaluation metrics.

ShapeNet 64^3	Coverage ↑	MMD ↓
Latent GAN (Chen & Zhang, 2019)	0.389	0.0017
FDN (Dupont et al., 2022a)	0.341	0.0021
GEM (Du et al., 2021)	0.409	0.0014
DPF (ours)	0.419	0.0016

Table 3: **Quantitative evaluation of 3D geometry generation** on ShapeNet (Chang et al., 2015). DPF outperforms prior approaches both in terms of Coverage and MMD metrics.

DPF outperforms both GEM (Du et al., 2021) and FDN (Dupont et al., 2022a) in learning the multimodal distribution of objects in ShapeNet, as shown by the coverage metric. In addition, while GEM (Du et al., 2021) performs better in terms of MMD, we do not observe this difference when visually comparing the generated samples shown in Fig. 7. We attribute this difference in MMD scores to the fact that MMD over-penalizes fine-grained geometry.

4.3 Data on $\mathbb{S}^2$

Straightforwardly, DPF can also learn fields that are not defined in the Euclidean plane. To demonstrate this, we show results on signals defined over the sphere. In particular, following Cohen et al. (2018), we use a stereographic projection to map image data onto the sphere. Hence, each resulting example is represented as a field $f_0 : \mathbb{S}^2 \to \mathbb{R}^d$. To uniformly sample points in $\mathbb{S}^2$ we use the Driscoll-Healy algorithm (Driscoll & Healy, 1994) and sample points at a resolution of 32^2 and 64^2 for spherical MNIST (LeCun et al., 1998) and AFHQ (Choi et al., 2020) data, respectively. In Fig. 8 we show the distribution of real examples for MNIST (LeCun et al., 1998) and AFHQ (Choi et al., 2020) images projected on the sphere as well as the samples generated by our DPF. Unsurprisingly, since DPF is agnostic to the geometry of the metric space $\mathcal{M}$, it can generate crisp and diverse samples for fields defined on the sphere.

5 Related Work

Generative modeling has advanced significantly in recent years. Early work on energy-based models (*e.g.*, restricted Boltzmann machines etc.) were able to accurately model images of digits but struggled to scale to larger and more diverse data. More recently, generative adversarial nets (GANs) and variational auto-encoders (VAEs) showed impressive improvements. While early variants showed promise, new GAN and VAE variants have been proposed to stabilize training and increase the perceptual quality of the results. To achieve this, different loss objectives have been studied (Goodfellow et al., 2014; Mao et al., 2017; Nowozin et al., 2016; Li et al., 2017a; Berthelot et al., 2017; Poole et al., 2016; Arjovsky et al., 2017; Gulrajani et al., 2017; Wu et al., 2019; Mroueh & Sercu, 2017; Mroueh et al., 2017; Jolicoeur-Martineau, 2018; Sun et al., 2020; Deshpande et al., 2019; 2018; Li et al., 2017b), new architectures have been devised (Radford et al., 2016; Donahue et al., 2017; Zhu et al., 2017; Brock et al., 2019; Karras et al., 2019; 2018), and a variety of normalization techniques have been proposed (Zhang et al., 2018; Miyato et al., 2018; Ioffe & Szegedy, 2015;

FDN (Dupont et al., 2022a)   GEM (Du et al., 2021)   DPF (ours)

Figure 7: **Qualitative comparison of different domain-agnostic approaches** on ShapeNet (Chang et al., 2015).

Real samples for spherical MNIST.   **Real samples** for spherical AFHQ.

DPF samples (ours).   DPF samples (ours).

Figure 8: **Qualitative comparison of empirical and generated samples** for spherical versions of MNIST and AFHQ (Choi et al., 2020).

Ba et al., 2016). Finally, methods have been discussed to produce more diverse samples (Lin et al., 2018; Xiao et al., 2018) and to improve convergence (Mazumdar et al., 2019; Yazıcı et al., 2019; Liu et al., 2017; Sanjabi et al., 2018). Even more recently, score-based and diffusion-based generative modeling has been introduced (Dickstein et al., 2015; Ho et al., 2020; Song et al., 2021b). While these methods are computationally more demanding, they have been shown to lead to remarkably compelling results (Nichol & Dhariwal, 2021). Recent advances have reduced computational needs, *e.g.*, by formulating diffusion in the latent space (Rombach et al., 2022; Vahdat et al., 2021), and demonstrated their applicability to many different data domains (Nichol & Dhariwal, 2021; Luo & Hu, 2021; Ho et al., 2022; Hoogeboom et al., 2022).

The field formulation of generative modeling developed for DPF is orthogonal to the body of work on Riemannian generative models (Bortoli et al., 2022; Gemici et al., 2016; Rozen et al., 2021). The goal in Riemannian generative modeling is to explicitly constraint the learned density to respect a particular Riemannian manifold structure. For example, a Riemannian generative model can learn a distribution of points $x \in \mathbb{S}^2$ on the 2D sphere $\mathbb{S}^2$, explicitly enforcing that any generated samples lie on the sphere. In contrast, DPF learns a generative model over a distribution of multiple samples of signals uniformly defined on the sphere, or any other metric space.

The DPF formulation also differs from the recently introduced FDN (Dupont et al., 2022a), GEM (Du et al., 2021) and GASP (Dupont et al., 2022b). The first two approaches adopt a latent field parametrization (Park et al., 2019). However, different from our work, the field network in FDN and GEM is parametrized via a hypernetwork (Ha et al., 2017) that takes as input a trainable latent vector. During training, a latent vector for each field is optimized in an initial auto-decoding stage (Park et al., 2019). Sampling is approached in a non-parametric way: a random latent vector is chosen from the set of optimized latents and subsequently projected into its local neighborhood before Gaussian noise is added. GASP (Dupont et al., 2022b) leverages a GAN whose generator produces field data whereas a point cloud discriminator operates on discretized data and aims to differentiate input source, *i.e.*, either real or generated. In comparison with concurrent work on neural Gaussian Processes (Dutordoir et al., 2022) we do not explicitly formulate a conditional inference problem (as typically done in GPs) and look at the more challenging task of learning an unconditional generative model over fields. We extensively test our hypothesis on complex field distributions for 2D images and 3D shapes, and on distribution of fields defined over non-Euclidean geometry.

6 CONCLUSION

In this paper we made progress towards modeling distributions over fields by introducing DPF. A diffusion probabilistic model that directly captures a distribution over fields without resorting to a initial reconstruction stage (Dupont et al., 2022a; Du et al., 2021) or tweaking unstable adversarial approaches (Dupont et al., 2022b). We show that DPF can capture distributions over fields in different domains without making any assumptions about the data. This enables us to use the same denoising architecture across domains obtaining satisfactory results. In addition, we show that DPF can be used to learn distributions over fields defined on non-Euclidean geometry.

7 ETHICAL STATEMENT

When considering ethical impact of generative models like DPF a few aspects that need attention are the use generative models for creating disingenuous data, *e.g.*, "DeepFakes" Mirsky & Lee (2021), training data leakage and privacy Tinsley et al. (2021), and amplification of the biases present in training data Jain et al. (2020). For an in-depth review of ethical considerations in generative modeling we refer the reader to Rostamzadeh et al. (2021). In addition, we want to highlight that any face images we show are generated from our model. We do not directly reproduce face images from any dataset.

8 REPRODUCIBILITY STATEMENT

We take great care in the reproducibility of our results. We provide links to the public implementations that can be used to replicate our results in Sect. A and Sect. B, as well as describing all training parameters in Tab. 6. All of the datasets we report results on are public and can be freely downloaded. Finally, we plan to release a public code repository upon paper decision.

REFERENCES

P. Achlioptas, P. Diamanti, I. Mitliagkas, and L. Guibas. Learning representations and generative models for 3d point clouds. In *ICML*, 2018.

M. Arjovsky, S. Chintala, and L. Bottou. Wasserstein gan. In *ICML*, 2017.

J. Ba, J. Kiros, and G. Hinton. Layer normalization. *arXiv*, 2016.

A. Bansal, E. Borgnia, H. Chu, J. Li, H. Kazemi, F. Huang, M. Goldblum, J. Geiping, and T. Goldstein. Cold diffusion: Inverting arbitrary image transforms without noise. *arXiv*, 2022.

D. Berthelot, T. Schumm, and L. Metz. Began: Boundary equilibrium generative adversarial networks. In *NeurIPS*, 2017.

V. Bortoli, E. Mathieu, M. Hutchinson, J. Thornton, Y. Teh, and A. Doucet. Riemannian score-based generative modeling. *arXiv*, 2022.

A. Brock, J. Donahue, and K. Simonyan. Large scale gan training for high fidelity natural image synthesis. In *ICLR*, 2019.

A. Chang, T. Funkhouser, L. Guibas, et al. Shapenet: An information-rich 3d model repository. *arXiv*, 2015.

Z. Chen and H. Zhang. Learning implicit fields for generative shape modeling. In *CVPR*, 2019.

Y. Choi, Y. Uh, J. Yoo, and J. Ha. Stargan v2: Diverse image synthesis for multiple domains. In *CVPR*, 2020.

T. Cohen, M. Geiger, J. Köhler, and M. Welling. Spherical cnns. In *ICLR*, 2018.

I. Deshpande, Z. Zhang, and A. G. Schwing. Generative Modeling using the Sliced Wasserstein Distance. In *CVPR*, 2018.

I. Deshpande, Y.-T. Hu, R. Sun, A. Pyrros, N. Siddiqui, S. Koyejo, Z. Zhao, D. Forsyth, and A. Schwing. Max-Sliced Wasserstein Distance and its use for GANs. In *CVPR*, 2019.

P. Dhariwal and A. Nichol. Diffusion models beat gans on image synthesis. In *NeurIPS*, 2021.

J. Dickstein, E. Weiss, N. Maheswaranathan, and S. Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics. In *ICML*, 2015.

J. Donahue, P. Krähenbühl, and T. Darrell. Adversarial feature learning. In *ICLR*, 2017.

J. Driscoll and D. Healy. Computing fourier transforms and convolutions on the 2-sphere. *Advances in applied mathematics*, 1994.

Y. Du, S. Li, and I. Mordatch. Compositional visual generation with energy based models. In *NeurIPS*, 2020.

Y. Du, K. Collins, J. Tenenbaum, and V. Sitzmann. Learning signal-agnostic manifolds of neural fields. In *NeurIPS*, 2021.

E. Dupont, H. Kim, S. Eslami, D. Rezende, and D. Rosenbaum. From data to functa: Your data point is a function and you should treat it like one. In *ICML*, 2022a.

E. Dupont, Y. Teh, and A. Doucet. Generative models as distributions of functions. In *AISTATS*, 2022b.

V. Dutordoir, A. Saul, Z. Ghahramani, and F. Simpson. Neural diffusion processes. *arXiv*, 2022.

B Everett. *An introduction to latent variable models*. Springer, 2013.

M. Gemici, D. Rezende, and S. Mohamed. Normalizing flows on riemannian manifolds. *arXiv*, 2016.

I. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio. Generative adversarial nets. In *NeurIPS*, 2014.

I. Gulrajani, F. Ahmed, M. Arjovsky, V. Dumoulin, and A. C Courville. Improved training of wasserstein gans. In *NeurIPS*, 2017.

D. Ha, A. Dai, and Q. Le. Hypernetworks. In *ICLR*, 2017.

M. Heusel, H. Ramsauer, T. Unterthiner, B. Nessler, and S. Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In *NeurIPS*, 2017.

J. Ho, A. Jain, and P. Abbeel. Denoising diffusion probabilistic models. In *NeurIPS*, 2020.

J. Ho, T. Salimans, A. Gritsenko, W. Chan, M. Norouzi, and D. J Fleet. Video diffusion models. In *ICLR*, 2022.

E. Hoogeboom, V. Satorras, C. Vignac, and M. Welling. Equivariant diffusion for molecule generation in 3d. In *ICML*, 2022.

S. Ioffe and C. Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *ICML*, 2015.

A. Jaegle, S. Borgeaud, J. Alayrac, et al. Perceiver io: A general architecture for structured inputs & outputs. In *ICLR*, 2022.

N. Jain, A. Olmo, S. Sengupta, L. Manikonda, and S. Kambhampati. Imperfect imaganation: Implications of gans exacerbating biases on facial data augmentation and snapchat selfie lenses. *CORR*, 2020.

A. Jolicoeur-Martineau. The relativistic discriminator: a key element missing from standard gan. In *ICLR*, 2018.

T. Karras, T. Aila, S. Laine, and J. Lehtinen. Progressive growing of gans for improved quality, stability, and variation. In *ICLR*, 2018.

T. Karras, S. Laine, and T. Aila. A style-based generator architecture for generative adversarial networks. In *CVPR*, 2019.

T. Karras, M. Aittala, J. Hellsten, S. Laine, J. Lehtinen, and T. Aila. Training generative adversarial networks with limited data. In *NeurIPS*, 2020.

D. Kingma and J. Ba. Adam: A method for stochastic optimization. In *ICLR*, 2015.

D. Kingma and M. Welling. Auto-encoding variational bayes. In *NeurIPS*, 2014.

N. Kodali, J. Abernethy, J. Hays, and Z. Kira. On convergence and stability of gans. *arXiv*, 2017.

A. Krizhevsky. Learning multiple layers of features from tiny images. Technical report, University of Toronto, 2009.

Y. LeCun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. In *Proceedings of the IEEE*, 1998.

C. Li, W. Chang, Y. Cheng, et al. Mmd gan: Towards deeper understanding of moment matching network. In *NeurIPS*, 2017a.

Y. Li, A. G. Schwing, K.-C. Wang, and R. Zemel. Dualing GANs. In *NeurIPS*, 2017b.

Z. Lin, A. Khetan, G. Fanti, et al. Pacgan: The power of two samples in generative adversarial networks. In *NeurIPS*, 2018.

S. Liu, O. Bousquet, and K. Chaudhuri. Approximation and convergence properties of generative adversarial learning. In *NeurIPS*, 2017.

S. Luo and W. Hu. Diffusion probabilistic models for 3d point cloud generation. In *CVPR*, 2021.

X. Mao, Q. Li, H. Xie, et al. Least Squares Generative Adversarial Networks. In *ICCV*, 2017.

E. Mazumdar, M. Jordan, and S. Sastry. On finding local nash equilibria (and only local nash equilibria) in zero-sum games. *arXiv*, 2019.

Y. Mirsky and W. Lee. The creation and detection of deepfakes: A survey. *CSUR*, 2021.

T. Miyato, T. Kataoka, M. Koyama, and Y. Yoshida. Spectral normalization for generative adversarial networks. In *ICLR*, 2018.

Y. Mroueh and T. Sercu. Fisher gan. In *NeurIPS*, 2017.

Y. Mroueh, T. Sercu, and V. Goel. Mcgan: Mean and covariance feature matching gan. In *ICML*, 2017.

A. Nichol and P. Dhariwal. Improved denoising diffusion probabilistic models. In *ICML*, 2021.

S. Nowozin, B. Cseke, and R. Tomioka. f-gan: Training generative neural samplers using variational divergence minimization. In *NeurIPS*, 2016.

G. Ostrovski, W. Dabney, and R. Munos. Autoregressive quantile networks for generative modeling. In *ICML*, 2018.

J. Park, P. Florence, J. Straub, R. Newcombe, and S. Lovegrove. Deepsdf: Learning continuous signed distance functions for shape representation. In *CVPR*, 2019.

B. Poole, A. Alemi, J. Dickstein, and A. Angelova. Improved generator objectives for gans. In *NIPS 2016 Workshop on Adversarial Training*, 2016.

A. Radford, L. Metz, and S. Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. In *ICLR*, 2016.

S. Rissanen, M. Heinonen, and A. Solin. Generative modelling with inverse heat dissipation. *arXiv*, 2022.

R. Rombach, A. Blattmann, D. Lorenz, P. Esser, and B. Ommer. High-resolution image synthesis with latent diffusion models. In *CVPR*, 2022.

O. Ronneberger, P. Fischer, and T. Brox. U-net: Convolutional networks for biomedical image segmentation. In *MICCAI*, 2015.

N. Rostamzadeh, E. Denton, and L. Petrini. Ethics and creativity in computer vision. *arXiv*, 2021.

N. Rozen, A. Grover, M. Nickel, and Y. Lipman. Moser flow: Divergence-based generative modeling on manifolds. In *NeurIPS*, 2021.

M. Sajjadi, O. Bachem, M. Lucic, O. Bousquet, and S. Gelly. Assessing generative models via precision and recall. In *NeurIPS*, 2018.

T. Salimans, I. Goodfellow, W. Zaremba, V. Cheung, A. Radford, and X. Chen. Improved techniques for training gans. In *NeurIPS*, 2016.

M. Sanjabi, J. Ba, M. Razaviyayn, and J. Lee. On the convergence and robustness of training gans with regularized optimal transport. In *NeurIPS*, 2018.

J. Song, C. Meng, and S. Ermon. Denoising diffusion implicit models. In *ICLR*, 2021a.

Y. Song and S. Ermon. Improved techniques for training score-based generative models. In *NeurIPS*, 2020.

Y. Song, J. Dickstein, D. P. Kingma, A. Kumar, S. Ermon, and B. Poole. Score-based generative modeling through stochastic differential equations. In *ICLR*, 2021b.

R. Sun, T. Fang, and A. Schwing. Towards a Better Global Loss Landscape of GANs. In *NeurIPS*, 2020.

P. Tinsley, A. Czajka, and P. Flynn. This face does not exist... but it might be yours! identity leakage in generative models. In *WACV*, 2021.

A. Vahdat, K. Kreis, and J. Kautz. Score-based generative modeling in latent space. In *NeurIPS*, 2021.

M. Welling and Y. Teh. Bayesian learning via stochastic gradient langevin dynamics. In *ICML*, 2011.

J. Wu, W. Huang, Z. nd Li, J. Thoma, D. Paudel, and L. Gool. Sliced wasserstein generative models. In *CVPR*, 2019.

C. Xiao, P. Zhong, and C. Zheng. Bourgan: Generative networks with metric embeddings. In *NeurIPS*, 2018.

Y. Xie, T. Takikawa, S. Saito, O. Litany, S. Yan, N. Khan, F. Tombari, J. Tompkin, V. Sitzmann, and S. Sridhar. Neural fields in visual computing and beyond. In *Computer Graphics Forum*, 2022.

Y. Yazıcı, C. Foo, and S. andothers Winkler. The unusual effectiveness of averaging in gan training. In *ICLR*, 2019.

F. Yu, A. Seff, Y. Zhang, et al. Lsun: Construction of a large-scale image dataset using deep learning with humans in the loop. *arXiv*, 2015.

S. Zhai, W. Talbott, N. Srivastava, C. Huang, H. Goh, R. Zhang, and J. Susskind. An attention free transformer. In *ICML*, 2022.

H. Zhang, I. Goodfellow, D. Metaxas, and A. Odena. Self-attention generative adversarial networks. In *ICML*, 2018.

J. Zhu, T. Park, P. Isola, and A. Efros. Unpaired image-to-image translation using cycle-consistent adversarial networks. In *ICCV*, 2017.

APPENDIX

In this supplementary material, we provide an ablation study (Sect. A), implementation details (Sect. B), additional experiments and visualizations (Sect. C), limitations and future work (Sect. D).

A   ABLATION

In this section we ablate the critical design choices and hyperparameters of DPF. We train all model variants on the CelebA-HQ 64^2 dataset (Karras et al., 2018).

Performance gap between DPF and DDPM (Ho et al., 2020). We aim to provide a fair comparison between DPF and DDPM (Ho et al., 2020). For this we use the implementation of the DDPM score network by Ho et al. (2020)[4] and train both DDPM and DPF with the same settings: batch size, learning rate schedule, number of epochs, etc. During inference we use ancestral sampling and perform 1000 denoising steps. In Tab. 4 we observe the gap between DDPM (Ho et al., 2020) (a domain-specific approach) and DPF to be much smaller than it is in Tab. 2. Furthermore, when we approximately equate the number of parameters of the score network in DDPM and our score field model (67.6M vs. 62.4M parameters), we find that DPF outperforms DDPM in both FID and recall metrics. We attribute this to the fact that DPF better captures globally consistent samples and long-range interactions. We show qualitative results generated by DDPM (Ho et al., 2020) and DPF in Fig. 9.

DDPM (Ho et al., 2020) (120M paramters)

DPF (ours, 62.4M paramters)

Figure 9: **Visualization of DDPM (Ho et al., 2020) and DPF results** on CelebA-HQ (Karras et al., 2018) dataset. All the images show in this figure are generated by a model, we do not directly reproduce images from the CelebA-HQ dataset (Karras et al., 2018)

Moreover, we are interested in understanding whether the major bottleneck for DPF is on encoding context pairs or decoding query pairs (*e.g.*, evaluating the field at query coordinates). To verify this, we design two ablation experiments. One experiment is to replace the DPF encoder with a UNet and the other one is to replace the DPF decoder with a UNet. We show quantitative results in Tab. 4. We observe that DPF with a UNet decoder achieves the best performance w.r.t. FID, precision and recall scores. These empirical results suggest that further improvements might be obtained by better decoding of query pairs in DPF.

Resolution-free generation. Importantly, DPF differs from classic DDPM (Ho et al., 2020) in that DPF generates fields that can be evaluated at continuous points using query pairs, *i.e.*, context pairs used during training differ from query pairs applied at inference. This enables DPF to learn continuous fields rather than naively memorizing discretized data samples. To verify this, we sample DPF at a different resolution than the one it was trained on. Specifically, we train DPF on CelebA-HQ (Karras et al., 2018) at a resolution of 64^2 while using 128^2 query pairs to generate high resolution images, as shown in Fig. 10. From Fig. 10, we observe that DPF can generate accurate high-resolution image fields given low-resolution context and query pairs during training. For context, we compare

---

[4]Code available at https://github.com/rosinality/denoising-diffusion-pytorch.

Org.   Ours   Nearest Bi-linear   Org.   Ours   Nearest Bi-linear

Figure 10: **Qualitative results of super-resolution image generation.** We generate images at 128^2 resolution *(row 1)* given 64^2 context points *(top left)*. We show zoom-in results *(row 2)*. We compare our results with nearest neighbor and bi-linear upsampling. All the images in this figure have been generated by a model, *i.e.*, we do not directly reproduce images from the CelebA-HQ dataset (Karras et al., 2018).

CelebA-HQ 64^2	# Params.	# Channel	FID ↓	Precision ↑	Recall ↑
DDPM (Ho et al., 2020)	120M	128	11.26	0.916	0.384
DDPM (Ho et al., 2020)	67.6M	96	24.93	0.927	0.213
DPF (ours)	62.4M	-	13.21	0.866	0.347
DPF (w/ a UNet encoder)	127M	128	20.79	0.916	0.323
DPF (w/ a UNet decoder)	62.5M	128	12.27	0.877	0.457

Table 4: **DDPM (Ho et al., 2020) vs. DPF under the same setting.** The DDPM models are implemented using a UNet architecture (Ronneberger et al., 2015) with a convolutional channel number of 128 *(row 1)* and 96 *(row 2)*, respectively. We also use a UNet architecture to replace either the encoder *(row 4)* or the decoder *(row 5)* of DPF.

our results with standard nearest neighbor or bi-linear upsampling. In Fig. 10, we show that our results enjoy comparable or higher quality w.r.t. texture details than the upsampled results.

DPF hyperparameters. We provide an ablation over different DPF hyperparameters. In Tab. 5 we study the effect of varying the number of context pairs used during training. In Tab. 6 we evaluate different PerceiverIO (Jaegle et al., 2022) hyperparameters. For the comparisons in Tab. 5 and Tab. 6 we train models for 180 epochs and compute FID metrics using $1k$ samples.

As we see in Tab. 5, decreasing the number of context pairs leads to a drop in FID scores. This is expected since a smaller number of context pairs reduces the fidelity at which the field is represented. Also noteworthy, we have not optimized score network hyper-parameters for a reduced number of context pairs, *i.e.*, they are selected only based on the performance of the model trained with the full set of context pairs.

The results reported in Tab. 6 show the effects of reducing the number of parameters in the PerceiverIO architecture, using different knobs. We observe: decreasing the capacity of the latents (either number of latents or their dimensionality) has a higher impact than decreasing the depth of the model (number of blocks in the encoder, decoder, or the number of self-attention layers in encoder blocks).

CelebA-HQ 64^2	FID
# context pairs = 1028 (50%)	103.86
# context pairs = 2048 (75%)	91.12
# context pairs = 4096 (100%)	74.89

Table 5: **Performance of DPF trained with different number of context pairs**. Context pairs are randomly samples during training. The FID score is evaluated after 180 epochs for $1k$ samples.

CelebA-HQ 64^2	# Params.	FID
# latents = 256	62.3M	93.54
# dim latents = 256	22.8M	96.63
# decoder blocks = 2	59.7M	77.29
# blocks = 6	35.4M	83.87
# S.A. block# = 1	43.5M	75.52
Base	62.4M	74.89

Table 6: **Performance of DPF with different PerceiverIO (Jaegle et al., 2022) hyperparameters.** The base hyperparameters we use in the experiments are: 512 latents with a dimensionality of 512, 12 encoder blocks with 2 self-attention modules and 4 decoder blocks. The FID score is evaluated after 180 epochs for $1k$ samples. For more details on hyperparameters and implementation details see Sect. B.

Figure 11: **Visualization of denoising process** from $t = 1000$ (*noise*) to $t = 0$ (*images*) on CelebA-HQ (Karras et al., 2018) (*left*) and CIFAR-10 (Krizhevsky, 2009) (*right*).

B IMPLEMENTATION DETAILS

We implement DPF using PerceiverIO (Jaegle et al., 2022), an efficient encoder-decode transformer architecture. Specifically, the encoder maps input arrays (*i.e.*, DPF context pairs) to arrays in the latent space via a cross-attention layer. Similarly the decoder maps latent arrays to output query arrays (*i.e.*, DPF query pairs) via cross-attention blocks. We refer readers to Jaegle et al. (2022) for details of PerceiverIO. For conditioning the score computation on the time-step t we simply concatenate a positional embedding representation of t to the context and query pairs. PerceiverIO settings for all experiments with quantitative evaluation are show in Tab. 6. In practice, the DPF encoder has 12 transformer blocks, each of which contains 1 cross-attention layer followed by 2 self-attention layers. Both cross-attention and self-attention layers have 4 attention heads. The latent array has a dimension of 512×512 for 64^2 resolution images and 1024×1024 for 32^2 resolution images. We use Fourier feature position encoding to represent coordinates and time steps with a frequency of 10 and 64, respectively. We use an Adam (Kingma & Ba, 2015) optimizer during training. We set the learning rate to $1e - 4$. We set the batch size to 16 for all image datasets. We use 8 A100 GPUs for all experiments. Finally, for PerceiverIO we use a modification of the public repository.[5]

C ADDITIONAL EXPERIMENTS

Visualization of denoising process. In Fig. 11 we visualize the denoising process over time from left to right on CelebA-HQ (Karras et al., 2018) and CIFAR-10 (Krizhevsky, 2009) data.

Visual results on additional image datasets. In Fig. 12 we show qualitative results of DPF on additional image datasets, including AHFQ (Choi et al., 2020), FFHQ (Karras et al., 2019) and LSUN church (Yu et al., 2015) data at 32×32 resolution. In Fig. 13 we show videos of generated fields over spherical geometry (view with Adobe Acrobat to see animations).

---

[5] https://huggingface.co/docs/transformers/model_doc/perceiver

Hyper-parameter	CelebA-HQ (Karras et al., 2018)	CIFAR-10 (Krizhevsky, 2009)	ShapeNet (Chang et al., 2015)
train res.	64^2	32^2	32^3
eval res.	64^2	32^2	64^3
#context pairs	4096	2048	32768
#query pairs	4096	2048	32768
#dim coordinates	2	2	3
#dim signal	3	3	1
#freq pos. embed	10	10	10
#freq pos. embed t	64	64	64
#latents	1024	512	512
#dim latents	1024	512	1024
#blocks	12	12	12
#dec blocks	1	1	1
#self attends per block	2	2	2
#self attention heads	4	4	4
#cross attention heads	4	4	4
batch size	128	128	16
lr	$1e-4$	$1e-4$	$1e-4$
epochs	1300	1300	1000

Table 7: Hyperparameters and settings for DPF on different datasets.

D   LIMITATIONS AND FUTURE WORK

While DPF makes progress toward learning distributions over fields, there exist some limitations and opportunities for future work. The first limitation is that a vanilla implementation of the score network as a transformer becomes computationally prohibitive even at low resolutions, due to the quadratic cost of computing attention over context and query pairs. To alleviate this issue, we leverage the PerceiverIO (Jaegle et al., 2022) architecture that scales linearly with the number of query and context pairs. To further address this, one possible direction of future work is to explore other efficient transformer architectures (Zhai et al., 2022). In addition, similar to DDPM (Ho et al., 2020), DPF iterates over all time steps during sampling to produce a field during inference, which is slower compared to GANs. Existing work accelerates sampling (Song et al., 2021a) trading-off sample quality and diversity. We highlight that improved inference approaches like (Song et al., 2021a) are trivially integrated with DPF.

AFHQ (Choi et al., 2020)

FFHQ (Karras et al., 2019)

LSUN Church (Yu et al., 2015)

Figure 12: **Additional results on image datasets**. We show generated results using DPF on AFHQ (Choi et al., 2020), FFHQ (Karras et al., 2019) and LSUN church (Yu et al., 2015) data at 32×32 resolution. Face images are generated from DPF, *i.e.*, we do not directly reproduce face images from FFHQ (Karras et al., 2019).

.

Figure 13: **Videos of generated spherical results.** View with Adobe Acrobat to see animations.