INTROSPECTIVE LEARNING : A TWO-STAGE APPROACH FOR INFERENCE IN NEURAL NETWORKS

ABSTRACT

In this paper, we advocate for two stages in a neural network's decision making process. The first is the existing feed-forward inference framework where patterns in given data are sensed and associated with previously learned patterns. The second stage is a slower reflection stage where we ask the network to reflect on its feed-forward decision by considering and evaluating all available choices. Together, we term the two stages as introspective learning. We use gradients of trained neural networks as a measurement of this reflection. We perceptually visualize the explanations from both stages to provide a visual grounding to introspection. For the application of recognition, we show that an introspective network is 4% more robust and 42% less prone to calibration errors when generalizing to noisy data. We also illustrate the value of introspective networks in downstream tasks that require generalizability and calibration including active learning and out-of-distribution detection. Finally, we ground the proposed machine introspection to human introspection in the application of image quality assessment.

1 INTRODUCTION

Introspection is the act of looking into one's own mind (Boring, 1953). Classical introspection has its roots in philosophy. Locke (1847), the founder of empiricism, held that all human ideas come from experience. This experience is a result of both sensation and reflection. By sensation, one receives passive information using the sensory systems of sight, sound, and touch. Reflection is the objective observation of our own mental operations. Consider the toy example in Fig. 1. Given an image x and an objective of recognizing x, we first sense some key features in the bird. These features include the color and shape of the body, feathers and beak. The features are chosen based on our existing notion of what is required to contrast between birds. We then associate these features with our existing knowledge of birds and make a coarse decision that x is a spoonbill. This is the sensing stage. Reflection involves questioning the coarse decision and asking why x cannot be a Flamingo, Crane, or Pig among other classes. If the answers are satisfactory, then an introspective decision that x is indeed a spoonbill is made. The observation of this reflection is introspection.

In this paper, we adopt this differentiation between sensing and reflection to advocate for two-stage neural network architectures for perception-based applications. We first ground introspection based on existing neural networks. For the application of recognition, a neural network $f(\cdot)$ is trained on a distribution $\mathcal{X}$ to classify data into N classes. The network learns notions about data samples when classifying them. These notions are stored as network weights W. Given a data sample x, $f(x)$ is a projection on the network weights. Let y_{feat} be the logits projected before the final fully connected layer. In the final fully connected layer $f_L(\cdot)$, the parameters W_L can be considered as N filters each of dimensionality $d_{L-1} \times 1$. The output of the network $\hat{y}$ is given by,

$$y_{feat} = f_{L-1}(x), \forall y \in \Re^{N \times 1},$$
$$\hat{y} = \arg\max(W_L^T y_{feat}), \forall W_L \in \Re^{d_{L-1} \times N}, f_{L-1}(x) \in \Re^{d_{L-1} \times 1}. \tag{1}$$

Hence, the class in which the sensed features maximally correlate with the stored notion is the output. Existing recognition network architectures including VGG (Simonyan & Zisserman, 2015), ResNet (He et al., 2016), and DenseNet (Huang et al., 2017) among others all sense and predict using Eq.1. Hence, in Fig. 1, the sensing stage is any existing architecture. We term this type of learning

Figure 1: Toy example of the introspection process: The visual explanations in the sensing stage is from Grad-CAM (Selvaraju et al., 2017) while the explanations in the reflection stage are our own. The written text is for illustrative purpose only.

as feed-forward learning. In this paper, we define the reflection stage in terms of neural networks. This involves 1) implicitly creating introspective questions, 2) Answering the posed questions as introspective features, 3) Creating a function $\mathcal{H}(\cdot)$ that combines all introspective features to provide a single decision. Note that the challenge is to implicitly extract features that answer introspective questions without explicitly training on said questions as is the norm in Visual Question Answering applications (Antol et al., 2015). We show that gradients w.r.t network parameters store notions about the difference between classes and can be used as introspective features.

We first describe the methodology of introspective feature extraction in Section 2. We then analyze $\mathcal{H}(\cdot)$ in Section. 3. We show that $\mathcal{H}(\cdot)$ as a simple multi-layer perceptron that introspects on $\hat{y}$ is more generalizable and calibrated compared to using the feed-forward network $f(\cdot)$. We empirically show these results for the application of recognition in Section 5. We then illustrate the benefits of our two-stage architecture in other downstream tasks including out-of-distribution detection, active learning and image quality assessment in Section 6.

2 INTROSPECTIVE FEATURES

In this section, we describe introspective features and visualize them as explanations. We then analyze their extraction procedure and provide a methodology to accelerate it.

Definition 2.1 (Introspection). *Given a network $f(\cdot)$, a datum x, and the network's prediction $f(x) = \hat{y}$, introspection in $f(\cdot)$ is the measurement of change induced in the network parameters when a label y_I is introduced as the label for x.*

This definition for introspection is in accordance with the sensing and reflection stages in Fig. 1. The network's prediction $\hat{y}$ is the output of the sensing stage and the change induced by an alternative label y_I is the network reflecting on its decision $\hat{y}$ as opposed to y_I. Combination of the two is introspection. Note that introspection can occur when $\hat{y}$ is contrasted against any trained label $y_I, I \in [1, N]$. For instance, in Fig. 1, the network is asked to reflect on its decision of spoonbill by considering other y_I that x can take - flamingo, crane, and pig.

Reflection is the empirical risk that the network has predicted x as $\hat{y}$ instead of y_I. Given the network parameters, this risk is measured through some loss function $J(y_I, \hat{y})$. y_I is a one-hot vector with a one at the I^{th} location. The change that is induced in the network is given by the gradient of $J(y_I, \hat{y})$ w.r.t the network parameters. In this paper, we introspect based on reflecting on all possible classes. For an N-class classifier, there are N possible introspective classes and hence N possible gradients each given by, $r_I = \nabla_W J(y_I, \hat{y}), I \in [1, N]$. Here, r_I are the introspective features. Since we introspect based on classes, we measure the change in network weights in the final fully connected layer. Hence the introspective features are given by,

$$r_I = \nabla_{W_L} J(y_I, \hat{y}), I \in [1, N], r_I \in \Re^{d_{L-1} \times N} \tag{2}$$

where W_L are the network weights for the final fully connected layer. Note that the final fully connected layer from Eq. 1 has a dimensionality of $\Re^{d_{L-1} \times N}$. For every x, Eq. 2 is applied N times

Figure 2: Introspective feature visualizations. The images in the leftmost column are the input x. The representative images are for illustrative purposes and are not used to extract features.

to obtain N separate r_I. We first visualize these features and provide a physical interpretation to the gradients before analyzing and accelerating time and space complexities.

Introspective Feature Visualization   We modify Grad-CAM (Selvaraju et al., 2017) to visualize r_j from Eq. 2. Grad-CAM visually justifies the decision made by $f(\cdot)$ by highlighting features that lead to $\hat{y}$. It does so by backpropagating the logit associated with the prediction, $\hat{y}$. The resulting gradients at every feature map are global average pooled and used as importance scores. The importance scores multiply the activations of the final convolutional layer and the resultant map is the Grad-CAM visualization. Hence, gradients highlight the activation areas that maximally lead to the prediction $\hat{y}$. In Fig. 1, given a spoonbill image x and a ImageNet-pretrained (Deng et al., 2009) VGG-16 network, the sensing visualization shown is Grad-CAM. Grad-CAM indicates that the pink and round body, and straight beak are the reasons for the decision. Instead of backpropagating the $\hat{y}$ logit, we backpropagate $J(y_I, \hat{y})$ in the Grad-CAM framework. The gradients represent introspective features and are used as importance scores. It can be seen that they visually highlight the explanations to '*Why $\hat{y}$, rather than y_I*'. In Fig. 1, the network highlights the neck of the spoonbill to indicate that since an S-shaped neck is not observed, x cannot be a flamingo. Similarly, the body of the spoonbill is highlighted when asked why x is not a crane since cranes have white feathers while spoonbills are pink. Two more examples are shown in Fig. 2. In the first row, a VGG-16 architecture is trained on Stanford Cars dataset (Krause et al., 2013). Given a Bugatti convertible image, Grad-CAM highlights the bonnet as the classifying factor. An introspective question of why it cannot be a bugatti coupe is answered by highlighting the open top of the convertible. The entire car is highlighted to differentiate the bugatti convertible from a Volvo. In the second row, we explore visual explanations in computed seismic images using LANDMASS dataset (Alaudah et al., 2018). A ResNet-18 architecture using the procedure from Shafiq et al. (2018) is trained. The dataset has four geological features as classes - faults, salt domes, horizons, and chaotic regions. Given a fault image in Fig. 2, Grad-CAM highlights the regions where the faults are clearly visible as fractures between rocks. However, these regions resemble salt domes as shown in the representative image. The introspective answer of why x is not predicted as a salt dome tracks a fault instead of highlighting a general region that also resembles a salt dome. Note that no representative images are required to obtain introspective visualizations. The gradients introspect based on notions of classes in network parameters.

2.1 Introspective Feature Extraction

Consider the introspective feature from Eq. 2. Assuming that forward and backward passes through $f(\cdot)$ are each of $\mathcal{O}(1)$ time complexity, the feed-forward prediction for a given x is $\mathcal{O}(1)$ time complex. Given that $f(\cdot)$ is trained to classify between N classes, extracting N introspective features require N backpropagations and hence is $\mathcal{O}(N)$ complex. Each r_I in Eq. 2 has a dimenisonality $d_{L-1} \times N$. Hence for N features, the space complexity is $\mathcal{O}(N^2 \times d_{L-1})$. Both the space and

time complexity render $r_I, I \in [1, N]$ prohibitive for practical applications. We first provide a methodology for reducing space complexity.

Consider the extraction process in Eq. 2. Each r_I is a $d_{L-1} \times N$ matrix. Expressing gradients in r_I separately w.r.t the different filters in W_L, we have a row-wise concatenated set of gradients given by,

$$r_I = [\nabla_{W_{L,1}} J(y_I, \hat{y}); \nabla_{W_{L,2}} J(y_I, \hat{y}); \nabla_{W_{L,3}} J(y_I, \hat{y}) \ldots \nabla_{W_{L,N}} J(y_I, \hat{y})] \tag{3}$$

where each $W_{L,j} \in \Re^{d_{L-1} \times 1}$ and $r_I \in \Re^{d_{L-1} \times N^2}$. For all data $x \in \mathcal{X}$ the following lemma holds:

Lemma 1. *Given a unique ordered pair $(x, \hat{y})$ and a trained network $f(\cdot)$, the gradients for a loss function $J(y_I, \hat{y})$ w.r.t classes are pairwise orthogonal, each class paired with the predicted class.*

Proof. Provided in Appendix A.1. $\square$

Lemma 1 states that backpropagating class y_I does not provide any information to $W_{L,j}, j \neq I$ and hence there is no need to use $\nabla_{W_{L,j}} J(y_j, \hat{y}), j \neq i$ as features when considering y_I. We make two assumptions in this proof. The first is that $(x, \hat{y})$ is a unique ordered pair, i.e an image x only has a single class associated with it. In other words, it implies that if x has a label y_I then $y_I \neq y_j$ as long as $I \neq j$ and $I \in [1, N]$. The second assumption is that $f(\cdot)$ is well-trained. In Appendix A.1, we provide the complete proof when $J(y_i, \hat{y})$ is the cross entropy loss. From Lemma 1, the introspective feature is only dependent on the predicted class $\hat{y}$ and the introspective class y_I making their span orthogonal to all other gradients. Hence

$$r_I = \nabla_{W_{L,I}} J(y_I, \hat{y}), I \in [1, N], r_I \in \Re^{d_{L-1} \times 1} \tag{4}$$

For N introspective features in Eq. 4, the space complexity of r_I reduces from $\mathcal{O}(d_{L-1} \times N^2)$ to $\mathcal{O}(d_{L-1} \times N)$. Note that the bottleneck in time complexity for N gradient extractions are the serial N backpropagations in Eq. 3. Building on Lemma 1, we present the following theorem.

Theorem 1. *Given a unique ordered pair $(x, \hat{y})$ and a trained network $f(\cdot)$, the gradients for a loss function $J(y_I, f(x)), I \in [1, N]$ w.r.t classes when y_I are N orthogonal one-hot vectors is equivalent to when y_I is a vector of all ones.*

Proof. Provided in Appendix A.2. $\square$

The proof follows Lemma 1. Theorem 1 states that backpropagating a vector of all ones ($\mathbf{1}_N$) is equivalent to backpropagating N one-hot vectors with ones at orthogonal positions. This reduces the time complexity from $\mathcal{O}(N)$ to a constant $\mathcal{O}(1)$ since we only require a single pass to backpropagate $\mathbf{1}_N$. Hence, our introspective feature is given by,

$$r_x = \nabla_{W_L} J(\mathbf{1}_N, \hat{y}), r_x \in \Re^{d_{L-1} \times N}, \mathbf{1}_N = 1^{N \times 1} \tag{5}$$

Note the LHS is now r_x instead of r_I from Eq. 4. The final introspective feature is a matrix of the same size as W_L extracted in $\mathcal{O}(1)$ with a space complexity of $\mathcal{O}(d_{L-1} \times N)$. r_x is vectorized and scaled between $[-1, 1]$ before being used in Sections 5 and 6 as introspective features.

3 INTROSPECTIVE NETWORK

From Fig. 1, $f(\cdot)$ is any existing trained network used to obtain introspective features r_x. It is trained to predict the ground truth y given any x. Let $f(\cdot)$ be trained using the mean squared error loss function. Based on the assumption that $\mathcal{H}(r_x) = \mathbb{E}(y|f(x))$ and hence expectation of $y - \mathcal{H}(r_x)$ is 0, the loss function can be decomposed as,

$$\mathbb{E}[(f(x) - y)^2] = \mathbb{E}[(f(x) - \mathcal{H}(r_x))^2)] + \mathbb{E}[(\mathcal{H}(r_x) - y)^2]. \tag{6}$$

Note that since the goal is to predict y given x, $\mathcal{H}(r_x) = \mathbb{E}(y|f(x))$ is a fair assumption to make. Substituting for $f(x)$ in Eq. 6, and using variance decomposition of y onto $f(x)$, we have,

$$\mathbb{E}[(\hat{y} - y)^2] = \text{Var}(\hat{y}) - \text{Var}(\mathcal{H}(r_x)) + \mathbb{E}[(\mathcal{H}(r_x) - y)^2]. \tag{7}$$

This decomposition is adopted from structured calibration techniques. A full derivation is presented in Kuleshov & Liang (2015). The first term $\text{Var}(\hat{y})$ is the the variance in the prediction from $f(\cdot)$. This term is the precision of $f(\cdot)$ and is low for a well trained network. The third term is the MSE function between the introspective network $\mathcal{H}(\cdot)$ and the ground truth. It is minimized while training the $\mathcal{H}(\cdot)$ network. The second term is the variance of the network $\mathcal{H}(\cdot)$ given features r_x. Note that minimizing Eq. 7 can occur by maximizing $\text{Var}(\mathcal{H}(r_x))$. However, $\text{Var}(\mathcal{H}(r_x))$ is also a part of the bias-variance decomposition in the third term which is minimized. This prevents *perpetual introspection*, i.e having networks that introspect consecutively, by creating a trade-off. We use a fisher vector interpretation to analyze $\text{Var}(\mathcal{H}(r_x))$. If $\mathcal{H}(\cdot)$ is a linear layer with parameters $W_\mathcal{H}$, the $\text{Var}(\mathcal{H}(r_x))$ term reduces to $W_\mathcal{H}^T W_\mathcal{H} \times \text{Var}(r_x) \propto \text{Tr}(r_x^T \Sigma^{-1} r_x)$ where Σ is the covariance matrix. Σ is a gaussian approximation for the shape of the manifold. Generalizing it to a higher dimensional manifold and replacing Σ with F, we have,

$$\text{Var}(\mathcal{H}(r_x)) = \text{Tr}(r_x^T F^{-1} r_x), \tag{8}$$

$$\text{Var}(\mathcal{H}(r_x)) = \sum_{j=1}^{N} r_j^T F^{-1} r_j. \tag{9}$$

The RHS of Eq. 9 is a sum of fisher vectors taken across all possible labels. The proof is provided in Appendix A.4. The fisher vector approximation is intuitive since from Jaakkola et al. (1999) who project data onto gradients and use them as features. A similar setup with the assumption of well-trained network is used in Cohn (1994) to estimate the manifold distances for new data in an online learning setup. More recently, the authors in Kwon et al. (2020) use gradients as fisher vectors in a generative setting for anomaly detection.

Estimation of $\mathcal{X}$ using $\mathcal{H}$ When a sample $x \in \mathcal{X}$ is provided to a network $f(\cdot)$ trained on $\mathcal{X}$, all $r_j, j \neq \hat{y}$ in Eq. 9 tend to 0. The RHS reduces to $r_{\hat{y}}^T F^{-1} r_{\hat{y}}$. $r_{\hat{y}}$ is a function of $f(x)$ only and hence adds no new information to the framework. The results of $\mathcal{H}(\cdot)$ remain the same as $f(\cdot)$. In other words, given a trained ResNet-18 on CIFAR-10, the results of feed-forward learning will be the same as introspective learning on CIFAR-10 testset.

Generalization to $\mathcal{X}'$ using $\mathcal{H}$ When a new samples $x' \notin \mathcal{X}$ is provided to a network $f(\cdot)$ trained on $\mathcal{X}$, a fisher vector based projection across labels is more descriptive compared to a feed-forward approach. The N gradients in Eq. 9 add new information based on how the network needs to change the manifold shape F to accomodate the introspective gradients. Hence, given a distorted version of CIFAR-10 testset, our proposed introspective learning generalizes with a higher accuracy while providing calibrated outputs from Eq. 7. We show these two claims in Section 5. The benefits of calibrated generalizability are further explored in downstream tasks like active learning and out-of-distribution detection in Section 6.

4 RELATED WORKS

Contrastive Explanations The proposed visualizations of introspective features are of the contrastive variety. They answer questions of the form *'Why $\hat{y}$, rather than y_I?'*, instead of causal questions of the form *'Why $\hat{y}$?'* as answered by Grad-CAM (Selvaraju et al., 2017). While a number of visual explanatory techniques attempt to answer causal questions, the literature on contrastive techniques is sparse. Dhurandhar et al. (2018) require a separate network and training to extract explanations while Prabhushankar et al. (2020) provide explanatory features that are not scalable.

Two-stage Networks The usage of two-stage approaches to inference in neural networks is not new. The authors in Chen et al. (2020b) propose SimCLR, a self-supervised framework where multiple data augmentation strategies are used to contrastively train an overhead MLP. The MLP provides features which are stored as a dictionary. This feature dictionary is used as a look-up table for new test data. The classical object detection technique of R-CNN (Girshick et al., 2014) uses separate feature extraction and detection stages for inference. In all these works, the extracted features are feed-forward activations. In this paper, we use gradients against all classes as features.

Augmentations and Robustness The considered r_x features from Eq. 5 can be considered as feature augmentations. Augmentations, including SimCLR, Augmix (Hendrycks et al., 2019), adversarial augmentation (Hendrycks & Dietterich, 2019), and noise augmentations (Vasiljevic et al.,

2016) have shown to increase robustness of neural networks. We use introspection on top of non-augmented (Section 5) and augmented (Section B.2) networks and show that our proposed two-stage framework increases the robustness to create generalizable and calibrated inferences which aids active learning and out-of-distribution (OOD) detection. The same framework that robustly recognizes images despite noise can also detect noise to make an out-of-distribution detection.

Human Introspection   There is no direct application that tests visual human introspection. In its absence, we choose the application of Full-Reference Image Quality Assessment (FR-IQA) to connect machine vision with human vision. The goal in FR-IQA is to objectively estimate the subjective quality of an image. Humans are shown a pristine image along with a distorted image and asked to score the quality of the distorted image (Sheikh et al., 2006). This requires reflection on the part of the observers. We take an existing algorithm (Temel et al., 2016) and show that introspecting on top of this IQA technique brings its assessed scores closer to human scores.

5   EXPERIMENTS

Across Sections 5 and 6, we use a 3-layered MLP with sigmoid activations as $\mathcal{H}$. The structure is presented in Appendix B.1. We first define generalization and calibration in the context of this paper.

Generalization   In this paper, without loss of consistency with related works, we say that the network trained on distribution $\mathcal{X}$ is generalizable if it predicts correctly on a shifted distribution $\mathcal{X}'$. The difference in data distributions can be because of data acquisition setups, environmental conditions, distortions among others. We use CIFAR-10 for $\mathcal{X}$ and two distortion datasets - CIFAR-10C (Hendrycks & Dietterich, 2019) and CIFAR-10-CURE (Temel et al., 2018) as $\mathcal{X}'$. Generalization is measured through performance accuracy.

Calibration   Given a data distribution $x \in \mathcal{X}$, belonging to any of $y \in [1, N]$, a neural network provides two outputs - the decision $\hat{y}$ and the confidence associated with $\hat{y}$, given by $\hat{p}$. Let p be the true probability empirically estimated as $p = \hat{p}_i, \forall i \in [1, M]$. Then calibration is given by (Guo et al., 2017),

$$\mathbb{P}(y = \hat{y}|p = \hat{p}) = p \tag{10}$$

Calibration measures the difference between the confidence levels and the prediction accuracy. To showcase calibration we use the metric of Expected Calibration Error (ECE) as described in (Guo et al., 2017). The network predictions are placed in 10 separate bins based on their prediction confidences. Ideally, the accuracy equals the mid-point of confidence bins. The difference between accuracy and mid-point of bins, across bins is measured by ECE. Lower the ECE, better calibrated is the network.

Datasets and networks   CIFAR-10C consists of $950,000$ images whose purpose is to evaluate the robustness of networks trained on original CIFAR-10 trainset. CIFAR-10C perturbs the CIFAR-10 testset using 19 distortions in 5 progressive levels. Hence, there are 95 separate $\mathcal{X}'$ distributions to test on with each $\mathcal{X}'$ consisting of 10000 images. Note that we are not using any distortions or data from CIFAR-10C as a validation split during training. The authors in Temel et al. (2018) provide realistic distortions that they used to benchmark real-world recognition applications including Amazon Rekognition and Microsoft Azure. We use these distortions to perturb the test set of CIFAR-10. There are 6 distortions, each with 5 progressive levels. Of these 6 distortions - Salt and Pepper, Over Exposure, and Under Exposure noises are new compared to CIFAR-10C. We train four ResNet architectures - ResNet-18, 34, 50, and 101 He et al. (2016). All four ResNets are evaluated as sensing networks $f(\cdot)$. The training procedure and hyperparameters are presented in Appendix B.1.

Testing on CIFAR-10 testset   The trained networks are tested on CIFAR-10 testset with accuracies 91.02%, 93.01%, 93.09%, and 93.11% respectively. Next we extract r_x on all training and testing images in CIFAR-10. $\mathcal{H}(\cdot)$ is trained using r_x from the trainset using the same procedure as $f(\cdot)$. When tested on r_x of the testset, the accuracy for ResNets-18,34,50,101 is 90.93%, 92.92%, 93.17%, and 93.03%. Note that this is similar to the feed-forward results. The average ECE of all feed-forward and introspective networks is 0.04. Hence, when the test distribution is the same as training distribution there is no change in performance.

Testing on CIFAR-10C and CIFAR-10-CURE   The results of all networks averaged across distortions in both the datasets are shown in Fig. 3. Note that in each case, there is a shift leftward and upward indicating that the performance improves while the calibration error decreases. In the larger CIFAR-10C dataset, the introspective ResNet-18 performs similar to ResNets-34 and 50 in

Figure 3: Scatter plot with performance accuracy vs expected calibration error. Ideally, networks are in top left. Introspectivity increases performance accuracy while decreasing calibration error.

Figure 4: (a) ResNet-18 on CIFAR-10C. (b) Expected calibration error across 5 challenge levels in brightness and saturate distortions. Note that both these distortions do not affect the performance of the network and their feed-forward accuracy is high. The improvement in accuracy is statistically insignificant. However, introspection decreases the ECE across challenge levels.

terms of accuracy while beating them both in calibration. A more fine-grained analysis is shown in Fig. 4 for ResNet-18. The blue bars in Fig. 4a) represent the feed-forward accuracy. The red bars are the introspective accuracy gains over the feed-forward accuracy. Among 7 of the 19 distortions, the accuracy gains are over 5%. In Appendix B.2.1 and Fig. 5, we see that the gains are higher when the distortions are higher. Introspection performs well on blur-like distortions while struggling with distortions that disrupt the lower level characteristics of the image like brightness, contrast, and saturate. This can be attributed to the fact that r_x are derived from the last layer of $f(\cdot)$ and are missing low-level statistics that are filtered out by network in the initial layers. However, in Fig. 4b), we show ECE for brightness and saturate distortions across all 5 distortion levels - higher the level, more is the distortion affecting $\mathcal{X}'$. It can be seen that while the ECE for feed-forward networks increases across levels, the ECE for introspective networks decrease. Hence, even when there are no accuracy gains to be had, introspection helps in calibration.

Table 1: Recognition accuracy of Active Learning strategies.

Methods	Architecture	Original Testset		Gaussian Noise	
		R-18	R-34	R-18	R-34
Entropy	Feed-Forward	0.365	0.358	0.244	0.249
	Introspective	0.365	0.359	**0.258**	**0.255**
Least Confidence	Feed-Forward	0.371	0.359	0.252	0.25
	Introspective	0.373	0.362	**0.264**	**0.26**
Margin	Feed-Forward	0.38	0.369	0.251	0.253
	Introspective	0.381	0.373	**0.265**	**0.263**
BALD	Feed-Forward	0.393	0.368	0.26	0.253
	Introspective	0.396	0.375	**0.273**	**0.263**
BADGE	Feed-Forward	0.388	0.37	0.25	0.247
	Introspective	0.39	0.37	**0.265**	**0.260**

Table 2: OOD techniques applied on feed-forward and introspective networks when the data is under adversarial attack.

Methods	OOD Datasets (Attack)	FPR (95% at TPR) ↓	Detection Error ↓	AUROC ↑
		Feed-Forward/Introspective		
MSP	Textures	99.98/**23.19**	45.9/**7.9**	30.4/**96.48**
	iSUN	98.63/**87.2**	46.71/**28.95**	46.44/**75.81**
	Places365	100/**83.59**	47.64/**26.46**	25.08/**79**
	LSUN	99.65/**87.64**	43.38/**26.31**	43.47/**78.4**
ODIN	Textures	99.95/**2.06**	47.7/**3.48**	37.5/**99.11**
	iSUN	96.8/**90.42**	44.77/**31.11**	53.88/**73.22**
	Places-365	99.97/**82.5**	47.12/**26.86**	32.69/**78.88**
	LSUN	98.6/**88.28**	40.51/**27.88**	56.7/ **77.25**

Plug-in results of Introspection Note that there are a number of techniques proposed to alleviate a neural network's robustness challenges against distortions. The authors in (Vasiljevic et al., 2016) show that finetuning VGG-16 using blurry training images increases the performance of classification under blurry conditions. (Temel et al., 2017) propose utilizing distorted virtual images to boost performance accuracy. The authors in (Hendrycks & Dietterich, 2019) use adversarial images to augment the training data. All these works require knowledge of distortion or large amounts of new data during training. Our proposed method can infer introspectively on top of any existing $f(\cdot)$ enhanced using existing methods. In Appendix B.2, we show performance on top of (Vasiljevic et al., 2016) and (Hendrycks & Dietterich, 2019) of 6.8% on Level 5 distortions. In Appendix B.3, we analyze SimCLR and show that introspecting on the self supervised features increases its CIFAR-10C performance by about 6% on ResNet-101. We introspect on top of Augmix (Hendrycks et al., 2019) and show that while recognition accuracy is the same, introspection reduces ECE of Augmix network by 43.33%. A number of ablation studies including analysis of structure of $\mathcal{H}$, loss function, distortion levels on performance accuracy and ECE are shown in Appendix B.4. Moreover, we examine introspection when $\mathcal{X}'$ is domain shifted data from Office (Saenko et al., 2010) dataset in Appendix B.6.

6 APPLICATIONS

In this section, we illustrate the advantages of introspective networks in two applications that are a function of both generalization and calibration - active learning and out-of-distribution detection. In both these applications, we show that the existing state-of-the-art methods perform better in their respective tasks and metrics if they were applied on $\mathcal{H}(\cdot)$ than on $f(\cdot)$. We then conclude by grounding the proposed introspection in neural nets with introspection in humans through image quality assessment.

Active Learning The goal in active learning is to decrease the test error in a model by choosing the *best* samples from a large pool of unlabeled data to annotate and train the model. A number of strategies are proposed to query the *best* samples. A full review of active learning and query strategies are given in Settles (2009). Existing active learning strategies define *best* samples to annotate as those samples that the model is most uncertain about. This uncertainty is quantified by either entropy (Wang & Shang, 2014), least confidence (Wang & Shang, 2014), maximum margin (Roth & Small, 2006), or through extracted features in BADGE Ash et al. (2019), and BALD (Gal et al., 2017). We show the results of ResNet-18 and 34 architecture in Table 1. Implementations of all query strategies in Table 1 are taken from the codebase of Ash et al. (2019) and reported as feed-forward results. Note that the query strategies act on $f(\cdot)$ to sample images at every round. In the introspective results, all query strategies sample using $\mathcal{H}(\cdot)$. The training and testing procedures strategies are the same as feed-forward from Ash et al. (2019). Doing so we find similar results as recognition - on the original testset the active learning results are the same while there is a gain across strategies on Gaussian noise testset from CIFAR-10C. Note that the results shown are averaged over 20 rounds with a query batch size of a 1000 and initial random choice - which were kept same for $f(\cdot)$ and $\mathcal{H}(\cdot)$ - of 100. Further details and plots are shown in Appendix B.8.

Out-of-distribution Detection The goal of Out-Of-Distribution (OOD) detection is to detect those samples that are drawn from a distribution $\mathcal{X}' \neq \mathcal{X}$ given a fully trained $f(\cdot)$. A number of techniques

are proposed to detect out-of-distribution samples. Hendrycks & Gimpel (2016) propose Maximum Softmax Probability (MSP) as a baseline method by creating a threshold function on the softmax output. Liang et al. (2017) propose ODIN and improved on MSP by calibrating the network's softmax probability using temperature scaling (Guo et al., 2017). In this paper, we illustrate the effectiveness of existing OOD methods when applied on $\mathcal{H}(\cdot)$ than if they were applied on the feed-forward $f(\cdot)$. The code for OOD detection techniques are taken from Chen et al. (2020a) along with all hyperparameters and the training regimen. The temperature scaling coefficient for ODIN is set to 1000. Note that we do not use additional temperature scaling on $\mathcal{H}(\cdot)$ to illustrate the effectiveness of our method. We use three established metrics to evaluate OOD detection - False Positive Rate (FPR) at 95% True Positive Rate (TPR), Detection error, and AUROC. Ideally, AUROC values for a given method is high while the other two metrics are low. We use CIFAR-10 as our in-distribution dataset and use four OOD datasets - iSUN (Xiao et al., 2010), Describable Textures Dataset (Cimpoi et al., 2014), Places 365 (Zhou et al., 2017), and LSUN (Yu et al., 2015). As in recognition and active learning, we consider two difficulty settings. The first is the vanilla case with the above-listed out-of-distribution datasets. The results are presented in Appendix B.9 and Table 11. The harder setting is when the datasets are all attacked with adversarial noise on top of being OOD. This setting is formalized in Chen et al. (2020a). We show these results in Table 2. In all cases in Table 2, introspection outperforms its feed-forward counterpart. In the vanilla setting, introspection is better than its feed-forward network in 15 of considered 24 metrics. This is inline with results from recognition and active learning where introspection generalizes better on $\mathcal{X}'$ compared to $\mathcal{X}$ testsets.

Image Quality Assessment (IQA) TID 2013 (Ponomarenko et al., 2015) and MULTI-LIVE (Jayaraman et al., 2012) are two IQA datasets with 3000 and 225 distorted images respectively in 5 and 4 progressively increasing levels of distortions. This setup is similar to CIFAR-10C. The goal is to objectively assess the subjective quality of the distorted images given the pristine image. Inline with existing techniques (Temel et al., 2016), we use five metrics to measure the similarity between the algorithmically predicted qualities and human qualities - outlier ratio (consistency), root mean square error (RMSE, accuracy), Pearson correlation (PRCC, linearity), Spearman correlation (SRCC, rank), and Kendall correlation (KRCC, rank). To do so, we use an existing IQA technique called UNIQUE (Temel et al., 2016) and introspect on top of it. The details of UNIQUE as well as related works and compared methods are presented in Appendix B.10. Since UNIQUE is an autoencoder architecture and since the pristine image is available, introspection can occur based on features and on earlier layers. The exact procedure is given in Appendix B.10 and is termed as Introspective-UNIQUE. The results are shown in Table 12. The proposed framework acts as a plug-in on top of UNIQUE. For instance, UNIQUE is the third best performing method in MULTI dataset in terms of RMSE, PLCC, SRCC, and KRCC. However, Introspective-UNIQUE improves the performance for these metrics by 1.315, 0.036, 0.020, and 0.023, respectively and achieves the best performance on all metrics.

7 DISCUSSION AND CONCLUSION

Limitations and future work The paper illustrates the benefits of utilizing the change in model parameters as a measure of model introspection. In Section 2.1, we analyze the time complexity and accelerate it to $\mathcal{O}(1)$. However, the space complexity is still dependent on N. The paper uses an MLP for $\mathcal{H}(\cdot)$ and constructs r_x by vectorizing extracted gradients. Hence, taking the dimensionality of the final feature layer from Eq. 1, the space complexity is $\mathcal{O}(N \times d^{L-1})$. For large datasets with large N, usage of r_x as a vector of concatenated gradients is prohibitive. Hence, a required future work is to provide a method of combining all N gradients without vectorization. Also, our implementation uses serial gradient extraction across images. This is non-ideal since the available GPU resources are not fully utilized. A parallel implementation with per-sample gradient extraction (Goodfellow, 2015) is a pertinent acceleration technique for the future.

Conclusion We introduce the concept of introspection in neural networks as two separate stages in a network's decision process - the first is making a quick assessment based on sensed patterns in data and the second is reflecting on that assessment based on all possible decisions that could have been taken and making a final decision based on this reflection. We show that doing so increases the generalization performance of neural networks as measured against distributionally shifted data while reducing the calibration error of neural networks. Existing state-of-the-art methods in downstream tasks like active learning and out-of-distribution detection perform better in an introspective setting compared to a feed-forward setting especially when the distributional difference is high.

8 ETHICS STATEMENT

The introspective explanations can serve to examine the intrinsic notions and biases that a network uses to categorize data since $\mathcal{H}(\cdot)$ obtains its introspective answers through $f(\cdot)$. However, any internal bias present in $f(\cdot)$ only gets strengthened in $\mathcal{H}(\cdot)$ through confirmation bias. The framework will benefit from a human intervention between $f(\cdot)$ and $\mathcal{H}(\cdot)$ in sensitive applications. One way would be to ask counterfactual questions by providing an established counterfactual and asking the network to reflect based on that. While the introspective framework will remain the same, the features will change. Such a confirmation bias is also present in humans. In his seminal book in 2011, Kahneman (2011) outlines two systems of thought and reasoning in humans - a fast and instinctive 'system 1' that heuristically associates sensed patterns followed by a more deliberate and slower 'system 2' that examines and analyzes the data in context of intrinsic notions. Our framework derives its intuition based on these two systems of reasoning.

9 REPRODUCIBILITY STATEMENT

The paper uses publicly available datasets to showcase the results. Our introspective learning framework is built on top of existing deep learning apparatus - including ResNet architectures (He et al., 2016) (inbuilt PyTorch architectures), CIFAR-10C data (Hendrycks & Dietterich, 2019) (source code at `https://zenodo.org/record/2535967#.YLpTF-1KhhE`), calibration ECE and MCE metrics (Guo et al., 2017) (source code at `https://github.com/markus93/NN_calibration`), out-of-distribution detection metrics, and codes for existing methods were adapted from (Chen et al., 2020a) (source code at `https://github.com/jfc43/robust-ood-detection`), active learning methods and their codes were adapted from (Ash et al., 2019) (source code at `https://github.com/JordanAsh/badge`), Grad-CAM was adapted from (Selvaraju et al., 2017) (code used is at `https://github.com/adityac94/Grad_CAM_plus_plus`). Our own codes will be released upon acceptance. The exact training hyperparameters for $f(\cdot)$ and $\mathcal{H}(\cdot)$, and all considered $\mathcal{H}(\cdot)$ architectures are shown in Appendix B.1. Extensive ablation studies on $\mathcal{H}(\cdot)$ are shown in B.4.

REFERENCES

Yazeed Alaudah, Motaz Alfarraj, and Ghassan AlRegib. Structure label prediction using similarity-based retrieval and weakly supervised label mapping. *Geophysics*, 84(1):V67–V79, 2018.

Stanislaw Antol, Aishwarya Agrawal, Jiasen Lu, Margaret Mitchell, Dhruv Batra, C Lawrence Zitnick, and Devi Parikh. Vqa: Visual question answering. In *Proceedings of the IEEE international conference on computer vision*, pp. 2425–2433, 2015.

Jordan T Ash, Chicheng Zhang, Akshay Krishnamurthy, John Langford, and Alekh Agarwal. Deep batch active learning by diverse, uncertain gradient lower bounds. *arXiv preprint arXiv:1906.03671*, 2019.

Edwin G Boring. A history of introspection. *Psychological bulletin*, 50(3):169, 1953.

Jiefeng Chen, Yixuan Li, Xi Wu, Yingyu Liang, and Somesh Jha. Robust out-of-distribution detection for neural networks. *arXiv preprint arXiv:2003.09711*, 2020a.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pp. 1597–1607. PMLR, 2020b.

M. Cimpoi, S. Maji, I. Kokkinos, S. Mohamed, , and A. Vedaldi. Describing textures in the wild. In *Proceedings of the IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2014.

David A Cohn. Neural network exploration using optimal experiment design. 1994.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Amit Dhurandhar, Pin-Yu Chen, Ronny Luss, Chun-Chen Tu, Paishun Ting, Karthikeyan Shanmugam, and Payel Das. Explanations based on the missing: Towards contrastive explanations with pertinent negatives. *arXiv preprint arXiv:1802.07623*, 2018.

Yarin Gal, Riashat Islam, and Zoubin Ghahramani. Deep bayesian active learning with image data. In *International Conference on Machine Learning*, pp. 1183–1192. PMLR, 2017.

Ross Girshick, Jeff Donahue, Trevor Darrell, and Jitendra Malik. Rich feature hierarchies for accurate object detection and semantic segmentation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 580–587, 2014.

Ian Goodfellow. Efficient per-example gradient computations. *arXiv preprint arXiv:1510.01799*, 2015.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q Weinberger. On calibration of modern neural networks. In *International Conference on Machine Learning*, pp. 1321–1330. PMLR, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. *arXiv preprint arXiv:1903.12261*, 2019.

Dan Hendrycks and Kevin Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. *arXiv preprint arXiv:1610.02136*, 2016.

Dan Hendrycks, Norman Mu, Ekin D Cubuk, Barret Zoph, Justin Gilmer, and Balaji Lakshminarayanan. Augmix: A simple data processing method to improve robustness and uncertainty. *arXiv preprint arXiv:1912.02781*, 2019.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4700–4708, 2017.

Tommi S Jaakkola, David Haussler, et al. Exploiting generative models in discriminative classifiers. *Advances in neural information processing systems*, pp. 487–493, 1999.

Dinesh Jayaraman, Anish Mittal, Anush K Moorthy, and Alan C Bovik. Objective quality assessment of multiply distorted images. In *2012 Conference record of the forty sixth asilomar conference on signals, systems and computers (ASILOMAR)*, pp. 1693–1697. IEEE, 2012.

Daniel Kahneman. *Thinking, fast and slow*. Macmillan, 2011.

Jonathan Krause, Michael Stark, Jia Deng, and Li Fei-Fei. 3d object representations for fine-grained categorization. In *4th International IEEE Workshop on 3D Representation and Recognition (3dRR-13)*, Sydney, Australia, 2013.

Volodymyr Kuleshov and Percy S Liang. Calibrated structured prediction. *Advances in Neural Information Processing Systems*, 28:3474–3482, 2015.

Gukyeong Kwon, Mohit Prabhushankar, Dogancan Temel, and Ghassan AlRegib. Backpropagated gradient representations for anomaly detection. In *European Conference on Computer Vision*, pp. 206–226. Springer, 2020.

Shiyu Liang, Yixuan Li, and Rayadurgam Srikant. Enhancing the reliability of out-of-distribution image detection in neural networks. *arXiv preprint arXiv:1706.02690*, 2017.

John Locke. *An essay concerning human understanding*. Kay & Troutman, 1847.

Xingchao Peng, Ben Usman, Neela Kaushik, Judy Hoffman, Dequan Wang, and Kate Saenko. Visda: The visual domain adaptation challenge. *arXiv preprint arXiv:1710.06924*, 2017.

N. Ponomarenko, O. Ieremeiev, V. Lukin, K. Egiazarian, and M. Carli. Modified image visual quality metrics for contrast change and mean shift accounting. In *Proc. CADSM*, pp. 305–311, 2011.

Nikolay Ponomarenko, Lina Jin, Oleg Ieremeiev, Vladimir Lukin, Karen Egiazarian, Jaakko Astola, Benoit Vozel, Kacem Chehdi, Marco Carli, Federica Battisti, et al. Image database tid2013: Peculiarities, results and perspectives. *Signal processing: Image communication*, 30:57–77, 2015.

Mohit Prabhushankar, Gukyeong Kwon, Dogancan Temel, and Ghassan AlRegib. Contrastive explanations in neural networks. In *2020 IEEE International Conference on Image Processing (ICIP)*, pp. 3289–3293. IEEE, 2020.

Dan Roth and Kevin Small. Margin-based active learning for structured output spaces. In *European Conference on Machine Learning*, pp. 413–424. Springer, 2006.

Kate Saenko, Brian Kulis, Mario Fritz, and Trevor Darrell. Adapting visual category models to new domains. In *European conference on computer vision*, pp. 213–226. Springer, 2010.

Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE international conference on computer vision*, pp. 618–626, 2017.

Burr Settles. Active learning literature survey. 2009.

Muhammad A Shafiq, Mohit Prabhushankar, Haibin Di, and Ghassan AlRegib. Towards understanding common features between natural and seismic images. In *SEG Technical Program Expanded Abstracts 2018*, pp. 2076–2080. Society of Exploration Geophysicists, 2018.

Hamid R Sheikh, Muhammad F Sabir, and Alan C Bovik. A statistical evaluation of recent full reference image quality assessment algorithms. *IEEE Transactions on image processing*, 15(11): 3440–3451, 2006.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. In *International Conference on Learning Representations*, 2015.

D. Temel and G. AlRegib. PerSIM: Multi-resolution image quality assessment in the perceptually uniform color domain. In *IEEE Int. Conf. Image Proc.*, pp. 1682–1686, 2015.

D. Temel and G. AlRegib. CSV: Image quality assessment based on color, structure, and visual system. *Sig. Proc.: Image Comm.*, 48:92 – 103, 2016. ISSN 0923-5965. doi: http://dx.doi.org/10.1016/j.image.2016.08.008. URL http://www.sciencedirect.com/science/article/pii/S0923596516301151.

D. Temel and G. AlRegib. Perceptual image quality assessment through spectral analysis of error representations. *Sig. Proc.: Image Comm.*, 2019.

Dogancan Temel, Mohit Prabhushankar, and Ghassan AlRegib. Unique: Unsupervised image quality estimation. *IEEE signal processing letters*, 23(10):1414–1418, 2016.

Dogancan Temel, Gukyeong Kwon, Mohit Prabhuhankar, and Ghassan AlRegib. CURE-TSR: Challenging unreal and real environments for traffic sign recognition. *Advances in Neural Information Processing Systems (NIPS) Machine Learning for Intelligent Transportations Systems Workshop*, 2017.

Dogancan Temel, Jinsol Lee, and Ghassan AlRegib. Cure-or: Challenging unreal and real environments for object recognition. In *2018 17th IEEE International Conference on Machine Learning and Applications (ICMLA)*, pp. 137–144. IEEE, 2018.

Igor Vasiljevic, Ayan Chakrabarti, and Gregory Shakhnarovich. Examining the impact of blur on recognition by convolutional networks. *arXiv preprint arXiv:1611.05760*, 2016.

Dan Wang and Yi Shang. A new active labeling method for deep learning. In *2014 International joint conference on neural networks (IJCNN)*, pp. 112–119. IEEE, 2014.

Z. Wang and Q. Li. Information content weighting for perceptual image quality assessment. *IEEE Trans. Image Proc.*, 20(5):1185–1198, 2011.

Jianxiong Xiao, James Hays, Krista A Ehinger, Aude Oliva, and Antonio Torralba. Sun database: Large-scale scene recognition from abbey to zoo. In *2010 IEEE computer society conference on computer vision and pattern recognition*, pp. 3485–3492. IEEE, 2010.

Fisher Yu, Ari Seff, Yinda Zhang, Shuran Song, Thomas Funkhouser, and Jianxiong Xiao. Lsun: Construction of a large-scale image dataset using deep learning with humans in the loop. *arXiv preprint arXiv:1506.03365*, 2015.

L. Zhang and H. Li. SR-SIM: A fast and high performance iqa index based on spectral residual. In *IEEE Int. Conf. Image Proc.*, pp. 1473–1476, 2012.

L. Zhang, L. Zhang, X. Mou, D. Zhang, et al. Fsim: a feature similarity index for image quality assessment. *IEEE Trans. Image Proc.*, 20(8):2378–2386, 2011.

Bolei Zhou, Agata Lapedriza, Aditya Khosla, Aude Oliva, and Antonio Torralba. Places: A 10 million image database for scene recognition. *IEEE transactions on pattern analysis and machine intelligence*, 40(6):1452–1464, 2017.

A APPENDIX : PROOFS

A.1 PROOF FOR LEMMA 1

We start by assuming $J(\cdot)$ is a cross-entropy loss. $J(y_I, \hat{y}), I \in [1, N]$ can also be written as,

$$J(y_I, \hat{y}) = -y_{\hat{y}} + \log \sum_{j=1}^{N} e^{y_j}, \text{ where } \hat{y} = f(x), \hat{y} \in \Re^{N \times 1}. \tag{11}$$

This definition is used in PyTorch to implement cross entropy. Here we assume that the predicted logit, i.e, the argument of the max value in the logits $\hat{y}$ is $y_{\hat{y}}$. While training, $y_{\hat{y}}$ is the true label. In this paper, we backpropagate any trained class I, as an introspective class. Hence, Eq. 11 can be rewritten as,

$$J(y_I, \hat{y}) = -y_I + \log \sum_{j=1}^{N} e^{y_j}, \text{ where } \hat{y} = f(x), \hat{y} \in \Re^{N \times 1}. \tag{12}$$

Approximating the exponent within the summation with its second order Taylor series expansion, we have,

$$J(y_I, \hat{y}) = -y_I + \log \sum_{j=1}^{N} \left(1 + y_j + \frac{y_j^2}{2}\right). \tag{13}$$

Note that for a well trained network $f()$, the logits of all but the predicted class are high. As noted before, the predicted logit is $y_{\hat{y}}$. Hence $\sum_{j=1}^{N} \frac{y_j^2}{2} = \frac{y_{\hat{y}}^2}{2}$. Substituting,

$$J(y_I, \hat{y}) = -y_I + \log(N) + \log(\sum_{j=1}^{N} y_j) + \log\left(\frac{y_{\hat{y}}^2}{2}\right). \tag{14}$$

The quantity in Eq. 14 is differentiated, hence nulling the effect of constant $\log(N)$. For a well trained network $f(\cdot)$, small changes in W do not adversely affect the sum of all logits $\sum_{j=1}^{N} y_j$. Hence approximating its gradient to 0 and discarding it, we can obtain $\nabla_W J(y_j, \hat{y})$ as a function of two logits, y_I and $y_{\hat{y}}$ given by,

$$\nabla_W J(y_I, \hat{y}) = -\nabla_W y_I + \nabla_W \log\left(\frac{y_{\hat{y}}^2}{2}\right). \tag{15}$$

y_I is a one-hot vector of dimensionality $N \times 1$ while ∇_W is a $d_{L-1} \times N$ matrix. The product extracts only the I^{th} filter in the W matrix in gradient calculations. Following the above logic for $y_{\hat{y}}$, we have,

$$\nabla_W J(y_I, \hat{y}) = -\nabla_{W,I} y_I + \nabla_{W,y_{\hat{y}}} g(y_{\hat{y}}), \tag{16}$$

where $g(\cdot)$ is some function of $y_{\hat{y}}$. Hence the gradient $r_I = \nabla_W J(y_I, \hat{y})$ lies in the span of the filter gradients of W_I and $W_{\hat{y}}$, making r_I orthogonal to all other filter gradient pairs. Hence proven.

Table 3: Structure of $\mathcal{H}(\cdot)$ and accuracies on CIFAR-10C as reported in the paper.

$f(\cdot)$	Part 1: Structure of $\mathcal{H}(\cdot)$ - All layers separated by sigmoid	Accuracy (%)
R-18,34	$640 \times 300 - 300 \times 100 - 100 \times 10$	71.4, 73.36
R-50, 101	$2560 \times 300 - 300 \times 100 - 100 \times 10$	75.2, 75.47

A.2 Proof for Theorem 1

The proof for Theorem 1 follows from Lemma 1. For any given data x, there are N possible introspections and hence N possible reflections. The LHS in Eq. 16 is summed across N losses. Since $y_j, j \in [1, N]$ are one-hot vectors, they are orthogonal and the first term in RHS is an addition across j. The second term in RHS is independent of j. Representing this in equation form, we have,

$$\sum_{j=1}^{N} \nabla_W J(y_j, \hat{y}) = -\sum_{j=1}^{N} \nabla_{W,j} y_j + N \times \nabla_{W,y_{\hat{y}}} g(y_{\hat{y}}). \tag{17}$$

The first term is added N times for N orthogonal y_I. Hence, the first term reduces to a sum of all gradients of j^{th} filters when backpropagating y_j. Removing the summation and replacing $y_j = \mathbf{1}_N$ or a vector of all ones in the LHS, we still have the same RHS given by,

$$\nabla_W J(\mathbf{1}_N, \hat{y}) = -\sum_{j=1}^{N} \nabla_{W,j} y_j + N \times \nabla_{W,y_{\hat{y}}} g(y_{\hat{y}}). \tag{18}$$

Equating the LHS from Eq. 17 and Eq. 18, we have the proof.

A.3 Tradeoff in Eq. 7

Eq. 7 suggests a trade-off between minimizing $\mathbb{E}[(\mathcal{H}(r_x) - y)^2]$, which is the cost function for training $\mathcal{H}(\cdot)$, and the variance of the network $\mathcal{H}(\cdot)$. Ideally, an optimal point exists that optimally minimizes the cost function of $\mathcal{H}(\cdot)$ while maximizing its variance. This also prevents decomposing $\mathcal{H}(\cdot)$ into $\mathcal{H}_1(\cdot)$ and $\mathcal{H}_2(\cdot)$ that further introspect on $\mathcal{H}(\dot{)}$. In this paper, we create a single introspective network $\mathcal{H}(\cdot)$. Hence, we do not comment further on the practical nature of the trade-off or perpetual introspection. It is currently beyond the scope of this work. In all experiments, we train $\mathcal{H}(\cdot)$ as any other network feed-forward network - by minimizing an empirical loss function given the ground truth.

A.4 Fisher Vector Interpretation

We make two claims before Eq. 9 both of which are well established. These include :

- **Variance of a linear function** For a linear function $y = W \times x + b$, the variance of y is given by $\text{Var}(Wx + b) = W^2 \text{Var}(x)$ if $\text{Var}(W) = 0$.
- **Variance of a linear function when W is estimated by gradient descent** Ignoring the bias b, and taking $y = Wx = x^T \Sigma^{-1} x^T (xW)$, we have $\text{Var}(Wx) = \sigma^2 \text{Tr}(x^T \Sigma^{-1} x)$.

Both these results lead to Eq. 8. Since $r_x \in \Re^{d_{L-1} \times N}$, the trace of the matrix given by $\text{Tr}(r_x^T F^{-1} r_x)$, is a sum of projections on individual weight gradients given by $\sum_{j=1}^{N} r_j^T F^{-1} r_j$ in the Fisher sense.

B Appendix : Additional Results

B.1 Structure of $\mathcal{H}(\cdot)$ and training details

In this section, we provide the structure of the proposed $\mathcal{H}(\cdot)$ architecture. Note that, from Eq. 1, the y_{feat} in feed-forward learning are processed through a linear layer. We process the introspective features r_x through an MLP $\mathcal{H}(\cdot)$, whose parameter structure is given in Table 3. Hence, we follow

Figure 5: Introspective performance gains over Feed-Forward networks of a) ResNets-18,34,50,101, b) Level-wise averaged results across ResNets-18,34,50,101

the same workflow as feed-forward networks in introspective learning. The feed-forward features $f_{L-1}(x)$ are passed through the last linear layer in $f(\cdot)$ to obtain the prediction $\hat{y}$. The introspective features are passed through an MLP to obtain the prediction $\tilde{y}$. The exact training procedure for $\mathcal{H}(\cdot)$ is presented below.

Training $f(\cdot)$ and Hyperparameters We train four ResNet architectures - ResNet-18, 34, 50, and 101 He et al. (2016). Note that we are not using any known techniques that promote either generalization (training on noisy data (Vasiljevic et al., 2016)) or calibration (Temperature scaling (Guo et al., 2017)). The networks are trained from scratch on CIFAR-10 dataset which consists of 50000 training images with 10 classes. The networks are trained for 200 epochs using SGD optimizer with momentum $= 0.9$ and weight decay $= 5e - 4$. The learning rate starts at 0.1 and is changed as $0.02, 0.004, 0.0008$ after epochs $60, 120,$ and 160 respectively. PyTorch in-built Random Horizontal Flip and standard CIFAR-10 normalization is used as preprocessing transforms.

Training $\mathcal{H}(\cdot)$ The structures of all MLPs are shown in Table 3. ResNet-18,34 trained on CIFAR-10 provide r_x of dimensionality 640×1. This is fed into $\mathcal{H}(\cdot)$ which is trained to produce a 10×1 output. Note that r_x from ResNet-50,101 are of dimensionality 2560×1 - due to larger dimension of $f_{L-1}()$. All MLPs are trained similar to $f(\cdot)$ - for 200 epochs, SGD optimizer, momentum $= 0.9$, weight decay $= 5e^{-3}$, learning rates of $0.1, 0.02, 0.004, 0.0008$ in epochs $1 - 60, 61 - 120, 121 - 160, 161 - 200$ respectively. For the larger 5-layered ResNet-50,101 networks in Table 8, dropout with 0.1 is used and the weight decay is reduced to $5e^{-4}$.

B.2 INTROSPECTIVE ACCURACY GAIN AND CALIBRATION ERROR STUDIES

In this section, we present additional recognition and calibration results. In Fig. 4a), we showed distortion-wise accuracy and the introspective gain for ResNet-18. In this section, we present level-wise and network-wise accuracies for all four considered ResNet architectures. We show that an introspective ResNet-18 matches a Feed-Forward ResNet-50 in terms of recognition performance. We then compare the results of ResNet-18 against existing techniques that promote robustness. We show that introspection is a plug-in approach that acts on top of existing methods and provides gain. We do the same for calibration experiments on CIFAR-10C where we provide level-wise distortion-wise graphs for Expected Calibration Error (ECE) similar to Fig. 4b).

B.2.1 LEVEL-WISE RECOGNITION ON CIFAR-10C

In Fig. 5b), the introspective performance gains for the four networks are categorized based on the distortion levels. All 19 categories of distortion on CIFAR-10C are averaged for each level and their respective feed-forward accuracy and introspective gains are shown. Note that the levels are progressively more distorted. Hence, level 1 distribution $\mathcal{X}'$ is similar to the training distribution $\mathcal{X}$ when compared to level 5 distributions. As the distortion level increases, the introspective gains also increase. This is similar to the results from Section 6. In both active learning and OOD applications

as $\mathcal{X}'$ deviates from $\mathcal{X}$, introspection performs better. In Fig. 5a), we show the distortion-wise and level-wise increase for each network. Note that, an Introspective ResNet-18 performs similarly to a Feed-Forward ResNet-50.

Table 4: Introspecting on top of existing robustness techniques.

Methods	Accuracy
ResNet-18	67.89%
Denoising	65.02%
Adversarial Train (Hendrycks & Dietterich, 2019)	68.02%
SimCLR (Chen et al., 2020b)	70.28%
Augment Noise (Vasiljevic et al., 2016)	76.86%
Augmix (Hendrycks et al., 2019)	89.85%
ResNet-18 + Introspection	71.4%
Denoising + Introspection	68.86%
Adversarial + Introspection	70.86%
SimCLR + Introspection	73.32%
Augment Noise + Introspection	77.98%
Augmix + Introspection	89.89% (ECE 43.33% ↓)

B.2.2 INTROSPECTION AS A PLUG-IN ON TOP OF EXISTING TECHNIQUES

Several techniques exist that boost the robustness of neural networks to distortions. These include training with noisy images (Vasiljevic et al., 2016), training with adversarial images (Hendrycks & Dietterich, 2019), and self-supervised methods like SimCLR (Chen et al., 2020b) that train by augmenting distortions. Another commonly used technique is to pre-process the noisy images to denoise them. All these techniques can be used to train $f(\cdot)$. Our proposed framework sits on top of any $f(\cdot)$. Hence, it can be used as a plug-in network. These results are shown in Table 4. Denoising 19 distortions is not a viable strategy assuming that the characteristics of the distortions are unknown. We use Non-Local Means denoising and the results obtained are lower than the feed-forward accuracy by almost 3%. However, introspecting on this model increases the results by 3.84%. We create untargeted adversarial images using I-FGSM attack with $\alpha = 0.01$ and use them to train a ResNet-18 architecture. In our experiments this did not increase the feed-forward accuracy. Introspecting on this network provides a gain of 2.84%. SimCLR Chen et al. (2020b) and introspection on SimCLR is discussed in Section B.3. In the final experimental setup of augmenting noise (Vasiljevic et al., 2016), we augment the training data of CIFAR-10 with six distortions - gaussian blur, salt and pepper, gaussian noise, overexposure, motion blur, and underexposure - to train a ResNet-18 network $f'(\cdot)$. We use the noise characteristics provided by (Temel et al., 2018) to randomly distort 500 CIFAR-10 training images by each of the six distortions. The original training set is augmented with the noisy data and trained. The results of the feed-forward $f'(\cdot)$ show a substantial increase in performance to 76.86%. This is about 9% increase from the original architecture. We show that introspecting on $f'(\cdot)$ provides a further gain in accuracy of 1.12%. Note that to train $\mathcal{H}(\cdot)$, we do not use the augmented data. We only use the original CIFAR-10 undistorted training set. The gain obtained is by introspecting on only the undistorted data, even though $f'(\cdot)$ contains knowledge of the distorted data. Hence, introspection is a plug-in approach that works on top of any network $f(\cdot)$ or enhanced network $f'(\cdot)$. Augmix (Hendrycks et al., 2019) is currently the best performing technique on CIFAR-10C. It creates multiple chains of augmentations to train the base WideResNet network. On CIFAR-10C, $f'(\cdot)$ obtains 89.85% recognition accuracy. We use $f'(\cdot)$ as our base sensing model and train an introspective MLP on $f'(\cdot)$. Note that we do not use any augmentations for training $\mathcal{H}(\cdot)$. Doing so, we obtain a statistically similar accuracy performance of 89.89%. However, the expected calibration error of the feed-forward $f'(\cdot)$ model decreases by 43.33% after introspection. Hence, when there is no accuracy gains to be had, introspection provides calibrated models.

Table 5: Expected Calibration Error and Maximum Calibrated Error for Feed-Forward vs Introspective Networks.

Architectures		ResNet-18	ResNet-34	ResNet-50	ResNet-101
ECE (↓)	$f(\cdot)$	0.14	0.18	0.13	0.16
	$\mathcal{H}(\cdot)$	**0.07**	**0.09**	**0.06**	**0.1**
MCE (↓)	$f(\cdot)$	0.27	0.34	0.27	0.32
	$\mathcal{H}(\cdot)$	**0.23**	**0.24**	**0.25**	**0.23**

Figure 6: ECE vs distortion levels across 12 separate distortions from CIFAR-10C for ResNet-18.

B.2.3 EXPECTED CALIBRATION ERROR (ECE)

In Fig. 4b), we show ECE for two distortion types - brightness and saturation across 5 distortion levels. In Fig. 6, we show results across five distortion levels for the first 12 distortions. The blue plot is the Feed-Forward ECE while the lower orange plot is its introspective counterpart. Apart from Level 5 contrast, intrsopective ResNet-18 is more calibrated than its feed-forward counterpart. This is in addition to the performance gains. The trend remains the same in the remaining distortions and among all considered networks. We average out ECE across 19 distortions and 5 challenge levels and provide ECE results for ResNets-18, 34, 50, 101 in Table 5. Lower the error, better is the architecture. The proposed introspective framework decreases the ECE of its feed-forward backbone by approximately 42%. An additional metric called Maximum Calibration Error (MCE) is also used for comparison. While ECE averages out the calibration difference in all bins (From Section 6), MCE takes the maximum error among all bins Guo et al. (2017). The introspective networks outperform their feed-forward backbones among all architectures when compared using ECE and MCE.

Table 6: SimCLR and its supervised and introspective variations tested on CIFAR-10C.

Methods	ResNet-18	ResNet-34	ResNet-50	ResNet-101
SimCLR Chen et al. (2020b)	70.28%	69.5%	67.32%	64.68%
SimCLR-MLP	72.79%	72.54%	70.37%	70.89%
SimCLR-Introspective (Proposed)	**73.32%**	**73.06%**	**71.28%**	**71.76%**

B.3 SIMCLR AND INTROSPECTION

SimCLR Chen et al. (2020b) is a self-supervised contrastive learning framework that is robust to noise distortions. The algorithm involves creating augmentations of existing data including blur, noise, rotations, and jitters. The network is made to contrast between all the augmentations of the image and other images in the batch. A separate network head $g(\cdot)$ is placed on top of the network to extract features and inference is made by creating a similarity matrix to a feature bank. Note that $g(\cdot)$ is a simple MLP. Our proposed framework is similar to SimCLR in that we extract features and use an MLP $\mathcal{H}(\cdot)$ to infer from these features. In Table 4, we show the results of Introspecting ResNets against SimCLR. However, this comparison is unfair since the features in SimCLR are trained in a self-supervised fashion. In this section, we train SimCLR for ResNets-18, 34, 50, 101 and train a new MLP $g(\cdot)$, not for extracting features, but to classify images. In other words, in Chen et al. (2020b), the authors create $g(\cdot)$ to be a 512×128 layer that extracts features. We train a network of the form

Table 7: Introspective Learning accuracies when r_x is extracted with different loss functions for ResNet-18 on CIFAR-10C.

Feed-Forward	MSE-M	CE	BCE	L1	L1-M	Smooth L1	Smooth L1-M	NLL	SoftMargin
67.89%	**71.4%**	69.47%	70.76%	70.12%	70.72%	70.42%	70.63%	70.93%	70.91%

$512 \times 128 - 128 \times 10$ that is trained to classify images. We then introspect on this $g(\cdot)$ to obtain r_x. Hence, our extracted features are a result of introspecting on self-supervision. Note that $g(\cdot)$ is now a fully supervised network. We pass CIFAR-10C through $g(\cdot)$ and name it SimCLR-MLP in Table 6. It is unsurprising that the fully-supervised SimCLR-MLP beats the self-supervised SimCLR across all four ResNets. The introspective network is called SimCLR-Introspective in Table 6. Note that there is less than 1% recognition performance increase across networks compared to SimCLR-MLP. Hence, the performance gains for introspecting on SimCLR-MLP is not as high as base ResNet architectures from Table 4. One hypothesis for this marginal increase is that the notions created within SimCLR-MLP are predominantly from the self-supervised features in SimCLR. These may not be amenable for the current framework of introspection that learns to contrast between classes and not between features within-classes.

B.4 ABLATION STUDIES

The feature generation process in Section 2 is dependent on the loss function $J(\hat{y}, y)$. In this section, we analyze the performance of our framework for commonly used loss functions and show that the introspective network outperforms its feed-forward counterpart under any choice of $J(\hat{y}, y)$. We also ascertain the effect of the size of the parameter set in $\mathcal{H}(\cdot)$ on performance accuracy.

B.4.1 EFFECT OF LOSS FUNCTIONS

We extract r_x using 9 loss functions and report the final distortion-wise level-wise averaged results Table 7. We do so for ResNet-18 and for the architecture of $\mathcal{H}(\cdot)$ shown in Table 3. The following loss functions are compared : CE is Cross Entropy, MSE is Mean Squared Error, L1 is Manhattan distance, Smooth L1 is the leaky extension of Manhattan distance, BCE is Binary Cross Entropy, and NLL is Negative Log Likelihood. Notice that the performance of r_x extracted using all loss functions exceed that of the feed-forward performance. The shown results of MSE, L1-M and Smooth L1-M are obtained by backpropagating a $\mathbf{1}_N$ from Theorem 1 vector multiplied by the average of all maximum logits M, in the training dataset. We use M instead of 1 because we want the network to be as confidant of the introspective label y_I as it is with the prediction label $\hat{y}$. Note that the results in Table 7 are for CIFAR-10C. MSE-M outperforms NLL loss by 0.37% in average accuracy and is used in our experiments.

B.4.2 EFFECT OF $\mathcal{H}(\cdot)$

We conduct ablation studies to empirically show the following : 1) the design of $\mathcal{H}(\cdot)$ does not significantly vary the introspective results, 2) the extra parameters in $\mathcal{H}(\cdot)$ are not the cause of increased performance accuracy.

How does changing the structure of $\mathcal{H}(\cdot)$ change the performance? We vary the architecture of $\mathcal{H}(\cdot)$ from a single linear layer to 4 layers in the first half of Table 8 for ResNet-18. The results in the first three cases are similar. A four layered network performs worse than $f(\cdot)$. However, changing the weight decay from $5e^{-3}$ to $5e^{-4}$ during training increases the results to above 70% but does not beat the smaller networks. For ResNet-18 architecture, the highest results are obtained when $\mathcal{H}(\cdot)$ is a 2-layered architecture but for the sake of uniformity, we use the results from a 3-layered network across all ResNet architectures.

Are the extra parameters in $\mathcal{H}(\cdot)$ the only cause for increase in performance accuracy? We show an ablations study of the effect of structure of $\mathcal{H}(\cdot)$ and $f(\cdot)$ on the introspective and feed-forward results in the second half of Table 3 on CIFAR-10-C dataset. The results are divided into four sections. In the first section, we show the performance of the original feed-forward network $f(\cdot)$, the performance when the final layer, $f_L(\cdot)$ is retrained using features y_{feat} from Eq. 1, and the

Table 8: Ablation studies for $\mathcal{H}(\cdot)$ on CIFAR-10C.

Part 1 : Varying the number of layers		
	Feed-Forward 64×10	67.89%
	640×10	71%
R-18	$640 \times 100 - 100 \times 10$	**71.57%**
	$640 \times 300 - 300 \times 100 - 100 \times 10$	71.4%
	$640 \times 400 - 400 \times 200 - 200 \times 100 - 100 \times 10$	66.1%
	Feed-Forward 64×10	71.8%
R-50	$2560 \times 300 - 300 \times 100 - 100 \times 10$	**75.2%**
	$2560 \times 1000 - 1000 \times 500 - 500 \times 300 - 300 \times 100 - 100 \times 10$	73%
Part 2 : Is the performance increase only because of a large $\mathcal{H}(\cdot)$?		
	Feed-Forward	67.89%
	$f_L(\cdot)$ 1 Layer : 64×10	67.86%
	$\mathcal{H}(\cdot)$ 1 Layer : 640×10	**71%**
	$f_L(\cdot)$ 3 Layers $64 \times 30 - 30 \times 20 - 20 \times 10$	63.61%
	$\mathcal{H}(\cdot)$ 3 Layers: $640 \times 300 - 300 \times 100 - 100 \times 10$	**71.4%**
R-18		
	$f_L(\cdot)$, 6200 parameters : $64 \times 50 - 50 \times 40 - 40 \times 20 - 20 \times 10$	66.85%
	$\mathcal{H}(\cdot)$, 6400 parameters : 640×10	**71%**
	Prediction on y_{feat} using 10-NN (No $f_L(\cdot)$)	66.31%
	Prediction on r_x using 10-NN (No $\mathcal{H}(\cdot)$)	**68.76%**

(a) (b) (c)

Figure 7: Introspective vs. Feed-Forward accuracy of ResNet-18 across training epochs on (a) CIFAR-10 original testset, (b) CIFAR-10C Motion Blur Testset on all 5 challenge levels, (c) CIFAR-10C Gaussian Noise Testset on all 5 challenge levels.

introspective network when $\mathcal{H}(\cdot)$ is a single layer. The second section shows the results when the features y_{feat} are used to train a three layered network $f_L(\cdot)$, and the introspective network is also three layered. Finally, in section 3, we try to equate the number of parameters for $f_L(\cdot)$ and $\mathcal{H}(\cdot)$. Note that in all cases, $f_L(\cdot)$ and $\mathcal{H}(\cdot)$ are trained in the same manner as detailed in Section B.1. $\mathcal{H}(\cdot)$ beats the performance of $f_L(\cdot)$ among all ablation studies. Finally, similar to SimCLR, we forego using an MLP and use 10-Nearest Neighbors on y_{feat} (64×1) and r_x (640×1) for predictions. Both results are worse-off than their MLP results but r_x outperforms y_{feat}.

B.5 INTROSPECTIVE ACCURACY ACROSS TRAINING EPOCHS

In Section 2, we make the assumption that $f(\cdot)$ is well trained to approximate r_x using Theorem 1. In Section 3, the Fisher Vector analysis works when the gradients form distances across the manifold in $f(\cdot)$ which occurs if $f(\cdot)$ is well trained. In this section we show that, practically, introspection performs as well as feed-forward accuracy across training epochs on CIFAR-10 testset and outperforms

Table 9: Performance of Proposed Introspective $\mathcal{H}(\cdot)$ vs Feed-Forward $f(\cdot)$ Learning under Domain Shift on Office dataset

Architectures		DSLR ↓ Amazon	DSLR ↓ Webcam	Amazon ↓ DSLR	Amazon ↓ Webcam	Webcam ↓ DSLR	Webcam ↓ Amazon
ResNet-18	$f(\cdot)$	39.1	78	62.9	59	89.8	42.2
(%)	$\mathcal{H}(\cdot)$	**47**	**90.7**	**67.3**	**63.9**	**96**	**44**
ResNet-34	$f(\cdot)$	41.8	83.3	**67.3**	60.1	90.6	41.7
(%)	$\mathcal{H}(\cdot)$	**46.4**	**89.8**	**67.3**	**63.9**	**97.8**	**43.3**
ResNet-50	$f(\cdot)$	-	-	67.3	62	92.4	33.4
(%)	$\mathcal{H}(\cdot)$	-	-	**78.1**	**68.4**	**97.8**	30.8
ResNet-101	$f(\cdot)$	-	-	62.9	59	89.8	31.77
(%)	$\mathcal{H}(\cdot)$	-	-	**76.5**	**67.3**	**92.4**	**33.6**

feed-forward accuracy on CIFAR-10C distortions. We show results on original testset, gaussian noise and motion blur testsets in Fig. 7.

Training, Testing, and Results in Fig. 7a   In this experimental setup, ResNet-18 is trained for 200 epochs. The model states at multiples of 3 epochs from 1 to 200 are stored. This provides 67 states of $f(\cdot)$ along its training process. Each $f(\cdot)$ is tested on CIFAR-10 testset and the recognition accuracy is plotted in blue in Fig. 7a). The introspective features r_x for all 67 states are extracted for the $50,000$ training samples. These r_x are used to train 67 separate $\mathcal{H}(\cdot)$ of structure provided in Table 3 with a similar training setup as in Section B.1. The r_x from the $10,000$ testing samples are extracted individually for each of the 67 $f(\cdot)$ states and tested. The results are plotted in red in Fig. 7a). Note the sharp spikes at epochs 60 and 120 where there is a change in the learning rate. Hence, when training and testing distributions are similar, introspective and feed-forward learning provides statistically similar performance across varying states of $f(\cdot)$.

Training, Testing, and Results in Fig. 7b, c   We now consider the case when a network $f(\cdot)$ is trained on distribution $\mathcal{X}$ and tested on $\mathcal{X}'$ from CIFAR-10C distortions. The 67 trained models of ResNet-18 are tested on two distortions from CIFAR-10C. From the results in Fig. 4, introspective learning achieves one of its highest performance gains in Gaussian noise, and an average increase in motion blur after epoch 200. The results in Fig. 7 indicate that after approximately 60 epochs, the feed-forward network has sufficiently sensed notions to reflect between classes. This is seen in the performance gains in both the motion blur and Gaussian noise experiments.

Table 10: Performance of Proposed Introspective $\mathcal{H}(\cdot)$ vs Feed-Forward $f(\cdot)$ Learning under Domain Shift on VisDA Dataset

ResNet-18	Plane	Cycle	Bus	Car	Horse	Knife	Bike	Person	Plant	Skate	Train	Truck	All
$f(\cdot)$ (%)	27.6	7.2	**38.1**	54.8	43.3	**4.2**	**72.7**	**8.3**	28.7	22.5	**87.2**	2.9	38.1
$\mathcal{H}(\cdot)$ (%)	**39.9**	**27.6**	19.6	**79.9**	**73.5**	2.7	46.6	6.5	**43.8**	**30**	73.6	**4.3**	**43.58**

B.6   DOMAIN ADAPTATION ON OFFICE DATASET

In Section 3, we claim that introspection helps a network to better classify distributions that it has not seen while training. In Section 5, we tested on 95 new distributions in CIFAR-10C and 30 new distributions in CIFAR-10-CURE. In this section, we evaluate the efficacy of introspection when there is a domian shift between training and testing data under changes in background, and camera acquisition setup among others. Specifically, the robust recognition performance of $\mathcal{H}(\cdot)$ is validated on Office Saenko et al. (2010) dataset using Top-1 accuracy. The Office dataset has 3 domains - images taken from either Webcam or DSLR, and extracted from Amazon website. Images can belong to any of 31 classes and they are of varying sizes - upto 1920×1080. Hence, results on Office shows the applicability of introspection on large resolution images. ImageNet pre-trained ResNet-18,34,50,101 He et al. (2016) architectures are used for $f(\cdot)$. The final layer is retrained using the source domain while the remaining two domains are for testing. The experimental setup, the same detailed in Section 5, is applied and the Top-1 accuracy is calculated. The results are summarized in

Figure 8: Introspective vs. Feed-Forward accuracy of ResNet-18 across training rounds for state-of-the-art techniques in an active learning setting. The query batch size per round is 1000. The trainset is CIFAR-10 and testset is Gaussian Noise from CIFAR-10C.

Table 9. In every instance, the top domain is $\mathcal{X}$ - the training distribution, and the bottom domain is $\mathcal{X}'$ - the testing distribution. Note that ResNet-50 and 101 failed to train on 498 images in DSLR source domain. The results of introspection exceed that of feed-forward learning in all but ResNet-50 when classifying between Webcam and Amazon domains.

B.7   DOMAIN ADAPTATION ON VIS-DA DATASET

Validation results on a synthetic-to-real domain shift dataset called VisDA Peng et al. (2017) are presented in Table 10. VisDA has 12 classes with about $152,000$ synthetic training images, and $55,000$ real validation images. The validation images are cropped images from MS-COCO. ResNet-18 architecture pretrained on ImageNet is finetuned on the synthetically generated training images from VisDA dataset fro 200 epochs. It is then tested on the validation images and the recognition performance is shown in Table 10 as feed-forward $f(\cdot)$ results. Introspective $\mathcal{H}(\cdot)$ results are obtained and shown when $f(\cdot)$ is ResNet-18. There is an overall improvement of 5.48% in terms of performance accuracy. However, the individual class accuracies leave room for improvement.

B.8   ACTIVE LEARNING

In Table 1, the mean recognition accuracies across the first 20 rounds of Active Learning experiments for commonly used query strategies are shown. We plot these recognition accuracies across for all five query strategies in Fig. 8. The x-axis is the round at which the performance is calculated. The calculated accuracy is plotted on the y-axis. The experiment starts with a random 100 images in round 1. Each strategy queries using either a round-wise sample trained $f(\cdot)$ or a round-wise sample trained $\mathcal{H}(\cdot)$. Note that at each round, the networks are retrained. This continues for 20 rounds. Both BALD Gal et al. (2017) and BADGE Ash et al. (2019) applied on $\mathcal{H}(\cdot)$ consistently beat its $f(\cdot)$ counterpart on every round. This is because both these methods rely on extracting features from the network as compared to the other three techniques that directly use the output logits from either $\mathcal{H}(\cdot)$ or $f(\cdot)$. Since the network is not well-trained at the initial stages - due to a dearth of training data - the introspective network is not as consistent as the feed-forward network among Entropy, Least Confidence, and Margin strategies. Nonetheless, $\mathcal{H}(\cdot)$ outperforms $f(\cdot)$ on average across all rounds.

Table 11: Out-of-distribution Detection of existing techniques compared between feed-forward and introspective networks.

Methods	OOD Datasets	FPR (95% at TPR) ↓	Detection Error ↓	AUROC ↑
		Feed-Forward/Introspective		
MSP Hendrycks & Gimpel (2016)	Textures	58.74/**19.66**	18.04/**7.49**	88.56/**97.79**
	SVHN	61.41/**51.27**	16.92/**15.67**	89.39/**91.2**
	Places365	58.04/**54.43**	17.01/**15.07**	89.39/**91.3**
	LSUN-C	**27.95**/27.5	**9.42**/10.29	**96.07**/95.73
ODIN Liang et al. (2017)	Textures	52.3/**9.31**	22.17/**6.12**	84.91/**91.9**
	SVHN	66.81/**48.52**	23.51/**15.86**	83.52/**91.07**
	Places-365	**42.21**/51.87	16.23/**15.71**	**91.06**/90.95
	LSUN-C	**6.59**/23.66	**5.54**/10.2	**98.74**/ 95.87

Table 12: Performance of Contrastive Features against Feed-Forward Features and other Image Quality Estimators. Top 2 results in each row are highlighted.

Database	PSNR HA	IW SSIM	SR SIM	FSIMc	Per SIM	CSV	SUM MER	Feed-Forward UNIQUE	Introspective UNIQUE
				Outlier Ratio (OR, ↓)					
MULTI	0.013	0.013	**0.000**	0.016	0.004	**0.000**	**0.000**	**0.000**	**0.000**
TID13	**0.615**	0.701	0.632	0.728	0.655	0.687	**0.620**	0.640	**0.620**
				Root Mean Square Error (RMSE, ↓)					
MULTI	11.320	10.049	8.686	10.794	9.898	9.895	**8.212**	9.258	**7.943**
TID13	0.652	0.688	0.619	0.687	0.643	0.647	0.630	**0.615**	**0.596**
				Pearson Linear Correlation Coefficient (PLCC, ↑)					
MULTI	0.801	0.847	0.888	0.821	0.852	0.852	**0.901**	0.872	**0.908**
	-1	-1	0	-1	-1	-1	-1	-1	
TID13	0.851	0.832	0.866	0.832	0.855	0.853	0.861	**0.869**	**0.877**
	-1	-1	0	-1	-1	-1	0	0	
				Spearman's Rank Correlation Coefficient (SRCC, ↑)					
MULTI	0.715	**0.884**	0.867	0.867	0.818	0.849	**0.884**	0.867	**0.887**
	-1	0	0	0	-1	-1	0	0	
TID13	0.847	0.778	0.807	0.851	0.854	0.846	0.856	**0.860**	**0.865**
	-1	-1	-1	-1	0	-1	0	0	
				Kendall's Rank Correlation Coefficient (KRCC)					
MULTI	0.532	**0.702**	0.678	0.677	0.624	0.655	0.698	0.679	**0.702**
	-1	0	0	0	-1	0	0	0	
TID13	0.666	0.598	0.641	0.667	**0.678**	0.654	0.667	0.667	**0.677**
	0	-1	-1	0	0	0	0	0	

B.9 OOD

Adversarial setting in Table 2 A datapoint z, is perturbed as $z + \epsilon$ and the goal of the detector is to classify $z \in \mathcal{X}$ or $z \in \mathcal{X}'$. This modality is proposed by the authors in Chen et al. (2020a) and we use their setup. PGD attack with perturbation 0.0014 is used. The same MSP and ODIN detectors from Table 2 are utilized. On 4 OOD datasets, both MSP and ODIN show a performance gain across all three metrics on $\mathcal{H}(\cdot)$ compared to $f(\cdot)$. Note that the results in Table 11 is for ResNet-18 architecture for the same $f(\cdot)$ and $\mathcal{H}(\cdot)$ used in other experiments including Fig. 3.

Vanilla setting in Table 11 In Table 11, we show the results of out-of-distribution detection when $\mathcal{X}$ is CIFAR-10 and $\mathcal{X}'$ are the four considered datasets. Note that among the four datasets, textures and SVHN are more out-of-distribution from CIFAR-10 than the natural image datasets of Places365 and LSUN. The results of the introspective network is highest on Textures DTD dataset.

B.10 IMAGE QUALITY ASSESSMENT

Related Works Multiple methods have been proposed to predict the subjective quality of images including PSNR-HA (Ponomarenko et al., 2011), IW-SSIM (Wang & Li, 2011), SR-SIM (Zhang & Li, 2012), FSIMc (Zhang et al., 2011), PERSIM (Temel & AlRegib, 2015), CSV (Temel & AlRegib, 2016), SUMMER (Temel & AlRegib, 2019), and UNIQUE (Temel et al., 2016). All these methods extract structure related hand-crafted features from both reference and distorted images and compare them to predict the quality. Recently, machine learning models have been proposed to directly extract features from images (Temel et al., 2016). Temel et al. (2016) propose UNIQUE that uses a sparse

autoencoder trained on ImageNet to extract features from both reference and distorted images. We use UNIQUE as our base network $f(\cdot)$.

Feed-Forward UNIQUE Temel et al. (2016) train a sparse autoencoder with a one layer encoder and decoder and a sigmoid non-linearity on $100,000$ patches of size $8 \times 8 \times 3$ extracted from ImageNet testset. The autoencoder is trained with MSE reconstruction loss. This network is our $f(\cdot)$. UNIQUE follows a full reference IQA workflow which assumes access to both reference and distorted images while estimating quality. The reference and distorted images are converted to YGCr color space and converted to $8 \times 8 \times 3$ patches. These patches are mean subtracted and ZCA whitened before being passed through the trained encoder. The activations of all reference patches in the latent space are extracted and concatenated. Activations lesser than a threshold of 0.025 are suppressed to 0. The choice of threshold 0.025 is made based on the sparsity coefficient used during training. Similar procedure is followed for distorted image patches. The suppressed and concatenated features of both the reference and distorted images are compared using Spearman correlation. The resultant is the feed-forward estimated quality of the distorted image.

Introspective-UNIQUE We use the architecture and the workflow from Temel et al. (2016) which is based on feed-forward learning to demonstrate the value of introspection. We replace the feed-forward features with the proposed introspective features. The loss in Eq. 5 for introspection is not between classes but between the image x and its reconstruction $\tilde{x}$ from the sparse autoencoder from Temel et al. (2016). For a reference image x, r_x is derived using $J(x, \tilde{x})$. Hence, gradients of r_x span the space of reconstruction noise. Since the need in IQA is to characterize distortions, we obtain r_x for reference images from the first layer and project both reference and distorted images onto r_x. These projections are compared using Spearman correlation to assign a quality estimate. In this setting, $\mathcal{H}(\cdot)$ is the projection operator and Spearman correlation. Hence, Introspective-UNIQUE broadens introspection in the following ways - 1) defining introspection on generative models, 2) using gradients in the earlier layers of a network.

Results We report the results of the proposed introspective model in comparison with commonly cited methods Table 12. We utilize MULTI-LIVE (MULTI) (Jayaraman et al., 2012) and TID2013 (Ponomarenko et al., 2015) datasets for evaluation. The performance is validated using outlier ratio (consistency), root mean square error (accuracy), Pearson correlation (linearity), Spearman correlation (rank), and Kendall correlation (rank). Arrows next to each metric in Table 12 indicate the desirability of a higher number ($\uparrow$) or a lower number($\downarrow$). Two best performing methods for each metric are highlighted. The proposed framework is always in the top two methods for both datasets in all evaluation metrics. In particular, it achieves the best performance for all the categories except in OR and KRCC in TID2013 dataset. The feed-forward model does not achieve the best performance for any of the metrics in MULTI dataset. However, the same network using introspective features significantly improves the performance and achieves the best performance on all metrics. For instance, the feed-forward model is the third best performing method in MULTI dataset in terms of RMSE, PLCC, SRCC, and KRCC. However, the introspective features improve the performance for those metrics by 1.315, 0.036, 0.020, and 0.023, respectively and achieve the best performance for all metrics. This further reinforces the plug-in capability of the proposed introspective inference.