LEARNING QUBO FORMS IN QUANTUM ANNEALING

ABSTRACT

Modern quantum annealers can find high-quality solutions to combinatorial optimisation objectives given as quadratic unconstrained binary optimisation (QUBO) problems. Unfortunately, obtaining suitable QUBO forms in computer vision remains challenging and currently requires problem-specific analytical derivations. Moreover, such explicit formulations impose tangible constraints on solution encodings. In stark contrast to prior work, this paper proposes to learn QUBO forms from data through gradient backpropagation instead of deriving them. As a result, the solution encodings can be chosen flexibly and compactly. Furthermore, our methodology is general and virtually independent of the specifics of the target problem type. We demonstrate the advantages of learnt QUBOs on the diverse problem types of graph matching, 2D point cloud alignment and 3D rotation estimation. Our results are competitive with the previous quantum state of the art while requiring much fewer logical and physical qubits, enabling our method to scale to larger problems. The code and the new dataset will be open-sourced.

1 INTRODUCTION

Hybrid computer vision methods that can be executed partially on a quantum computer (QC) are an emerging research area (Boyda et al., 2017; Cavallaro et al., 2020; Seelbach Benkner et al., 2021; Birdal et al., 2021). Compared to classical methods, such approaches promise to solve computationally demanding (*e.g.,* combinatorial) sub-problems faster, with improved scaling, and without relaxations that often lead to approximate solutions. As of now, quantum primacy has not yet been demonstrated in remotely practical usages of quantum computing. Still, all existing quantum computer vision (QCV) methods fundamentally assume that it will be achieved in the future. Thus, solving these suitable algorithmic parts on a gate-based QC or a quantum annealer has the potential to re-shape the field. However, reformulating them for execution on a QC is often non-trivial.

QCV continues building up momentum, fuelled by the accessibility of experimental quantum annealers (QA) allowing to solve practical ($\mathcal{NP}$-hard) optimisation problems. Existing QCV methods using QAs rely on analytically deriving QUBOs (both QUBO matrices and solution encodings) for a specific problem type, which is challenging, especially since solutions need to be encoded as binary vectors (Li & Ghosh, 2020; Seelbach Benkner et al., 2020; 2021; Birdal et al., 2021). This often leads to larger encodings than necessary, severely impacting scalability. QUBO derivations with neural networks have not yet been scrutinised in the QA literature.

In stark contrast to the existing state of the art, this paper proposes—for the first time—to learn QUBO forms from data for any problem type using the backpropagation algorithm; see Fig. 1 for an overview. Our framework captures, in the weights of a neural network, the entire manifold of QUBOs belonging to a problem type; it can produce the QUBO form for a given problem instance in a single forward pass. In other words, it can be interpreted as a meta-learning approach in the context of hybrid (quantum-classical) neural network training, in which the superordinate network is trained to instantiate the parameters of the QUBO form.

In particular, we show how a (combinatorial) quantum annealing solver can be integrated into a vanilla neural network as a custom layer and be used in the forward and backward passes, which may be useful in other contexts. To that end, we introduce a contrastive loss that circumvents the inherently discontinuous and non-differentiable nature of QUBO solvers. Our method is compatible with any QUBO solver at training and test time—we consider parallelised exhaustive search, simulated annealing, and quantum annealing. QUBO learning, *i.e.,* determining a function returning

Figure 1: We propose **QUBO learning**, a quantum-classical meta-learning algorithm that avoids analytical QUBO derivations by learning to regress QUBOs to solve problems of a given type. We first represent a problem instance as a vector $\mathbf{p}$ and then feed it into an MLP that regresses the entries of the QUBO matrix $\mathbf{A}$. We then initialise a quantum annealer with $\mathbf{A}$, and use quantum annealing to find a QUBO minimiser and extract it as the solution $\mathbf{x}^*$ to the problem instance. We define losses involving $\mathbf{x}^*$ that avoid backpropagation through the annealing, and backpropagate gradients through the MLP to train it. We demonstrate the generalisability of our method on such problems as graph matching, point set registration, and rotation estimation.

QUBO forms given a problem instance of some problem type as input, is a non-trivial and difficult task. Our paper makes several technical contributions to enable QUBO learning for computer vision:

1. A new neural meta-learning approach to obtain QUBO forms executable on modern QAs for computer-vision problems. While prior methods rely on analytical derivations, we learn QUBO forms from data.

2. A new training strategy for neural methods with backpropagation involving finding low-energy solutions to instantaneous (optimised) QUBO forms, independent of the solver.

3. Application of the new framework to several computer-vision problems with solutions encoded by permutations and discretised rigid transformations.

We show that our methodology is a standardised way of obtaining QUBOs independent of the target problem type. This paper focuses on three problem types already tackled by QCV methods relying on analytical QUBO derivations: graph matching and point set alignment (with and without known prior point matches in the 3D and 2D case, respectively). We emphasise that we do not claim to outperform existing specialised methods for these problem types or that QA is particularly well-suited for them. Rather, we show that this wide variety of problems can be tackled successfully and competitively by our general quantum approach already now, before quantum primacy. Thus, in the future, computer-vision methods may readily benefit from the (widely expected) speed-up of QC through an *easy* and *flexible* re-formulation of algorithmic parts as QUBOs, thanks to our proposed method. We run our experiments on D-Wave Advantage5.1 (Dattani et al., 2019), an experimental realisation of AQC with remote access. This paper assumes familiarity with the basics of quantum computing. For convenience, we summarise several relevant definitions in the appendix.

2 RELATED WORK

There are two main paradigms for quantum computing: *gate-based* QC (also called *circuit-based*) and adiabatic quantum computing (AQC). Our method uses quantum annealing, which is derived from AQC, and is *not* gate-based. The predominantly theoretical field of quantum machine learning (QML) investigates how quantum computations can be integrated in machine learning (Biamonte et al., 2016; Dunjko & Briegel, 2018; Sim et al., 2019; Havlíček et al., 2019; Du et al., 2020; Mariella & Simonetto, 2021; Kübler et al., 2021). Many QML methods assume circuit-based quantum computers and define a quantum variational layer, *i.e.,* a sequence of parametrised unitary transformations meant for execution on quantum hardware (Mitarai et al., 2018). QML methods are often optimised using variants of the backpropagation algorithm (McClean et al., 2018; Verdon et al., 2019; Beer et al., 2020). Quantum variational models were recently applied to combinatorial optimisation (Khairy et al., 2020) and reinforcement learning (Dunjko et al., 2016; Lockwood & Si, 2020). Instead of learning to regress parameters of unitary transformations for gate-based QC, we learn to regress QUBO forms for QA.

In contrast to circuit-based machines, quantum annealers can already solve various real-world problems formulated as QUBOs (Neukart et al., 2017; Teplukhin et al., 2019; Stollenwerk et al., 2019; Orus et al., 2019; Mato et al., 2021; Speziali et al., 2021). Hence, the last few years in quantum computer vision (QCV) are characterised by a rapid transition from theoretical considerations (Venegas-Andraca & Bose, 2003; Chin et al., 2020; Neven et al., 2008b;a) to practical algorithms leveraging quantum-mechanical effects of quantum computers, ranging from image retrieval and processing (Venegas-Andraca & Bose, 2003; Yan et al., 2016), classification (Boyda et al., 2017; Nguyen & Kenyon, 2019; Cavallaro et al., 2020; Willsch et al., 2020a; Dema et al., 2020) and object tracking (Li & Ghosh, 2020; Zaech et al., 2022), to problems on graphs (Zick et al., 2015; Seelbach Benkner et al., 2020; Mariella & Simonetto, 2021), consensus maximisation (Doan et al., 2022), shape alignment (Noormandipour & Wang, 2021; Seelbach Benkner et al., 2021) and ensuring cycle-consistency (Birdal et al., 2021).

Many of these methods are evaluated on real quantum hardware, as both circuit-based and quantum annealing machines can be accessed remotely (D-Wave Systems, 2022; Rigetti Computing, 2022).

We demonstrate the efficacy of our method on the applications of graph matching and point set alignment where we compare against recent quantum state-of-the-art methods Seelbach Benkner et al. (2020) and Golyanik & Theobalt (2020), respectively.

Another line of work in different domains concerns with learning the best adiabatic quantum algorithm. While Pastorello et al. (2021) and Pastorello & Blanzieri (2019) develop an algorithm inspired by tabu search, our method uses a neural network to output a coupling matrix. Orthogonal to our work, others train neural networks to solve problem-specific QUBOs (Gabor et al., 2020). QML on gate-based QC has been studied at length but machine learning with QA remains largely under-explored, with only a few exceptions (*e.g.,* linear regression (Date & Potok, 2021) and binary neural networks (Sasdelli & Chin, 2021)). In stark contrast to existing QCV methods with analytically derived QUBOs (Li & Ghosh, 2020; Seelbach Benkner et al., 2020; 2021; Birdal et al., 2021), our approach enables more flexible and compact solution encodings.

Our method is also related to recent non-quantum approaches that integrate combinatorial solvers into neural networks and back-propagate through them (Ferber et al., 2020; Rolínek et al., 2020; Vlastelica et al., 2020). They aim to improve combinatorial optimisation by seamlessly integrating deep learning and combinatorial building blocks as custom layers. In this respect, ours is the first work that uses a quantum QUBO solver in neural architectures.

3 QUBO LEARNING APPROACH

We present a new meta-learning approach for regressing quadratic unconstrained binary optimisation problems (QUBOs) suitable for modern quantum annealers (QA). While existing work analytically derives QUBOs for a certain problem type, we propose to instead *learn* a function that turns a problem instance into a QUBO to be solved by a QA. Specifically, we train a multi-layer perceptron (MLP) that takes a vectorised problem instance and regresses the QUBO weights such that the QUBO minimiser is the solution to the problem. Note that we only specify the bit encoding of the solution but let the network learn to derive QUBOs. Crucially, we show how training the MLP is possible despite quantum annealing (like any QUBO solver) being discontinuous and non-differentiable, see Fig. 1 for an overview.

3.1 QUBOS AND QUANTUM ANNEALING

Quantum annealing is a metaheuristic to solve $\mathcal{NP}$-hard problems of the form $\arg\min_{\mathbf{s}\in\{-1,1\}^n} \mathbf{s}^\top \mathbf{J}\mathbf{s} + \mathbf{b}^\top \mathbf{s}$, where $\mathbf{s}$ is a binary vector, $\mathbf{J} \in \mathbb{R}^{n \times n}$ is a matrix of *couplings*, and $\mathbf{b} \in \mathbb{R}^n$ contains *biases* (McGeoch, 2014). We can rewrite this as a QUBO: $\arg\min_{\mathbf{x}\in\{0,1\}^n} \mathbf{x}^\top \mathbf{A}\mathbf{x}$, by substituting $\mathbf{x} = \frac{1}{2}(\mathbf{s} + \mathbb{1}_n)$ and $\mathbf{A} = \frac{1}{4}\mathbf{J} + \frac{1}{2}(\mathbf{J}\mathbb{1}_n + \mathbb{1}_n^\top \mathbf{J}) + \frac{1}{2}\text{diag}(\mathbf{b})$.

In quantum annealing, the binary n-dimensional vector $\mathbf{x}$ describes the measurement outcomes of n qubits. Annealing starts out with an equal superposition quantum state of the qubits that assigns an equal probability to all possible binary states $\{0,1\}^n$. During the anneal, the couplings and biases of $\mathbf{A}$ are gradually imposed on the qubits. The adiabatic theorem (Born & Fock, 1928) implies that doing so sufficiently slow forces the qubits into a quantum state that assigns non-zero probability

only to binary states that minimise the QUBO (Farhi et al., 2001). We then only need to measure the qubits to determine their binary state, which is our solution $\mathbf{x}$. For a more detailed description of quantum annealing, we refer to prior computer-vision works (Seelbach Benkner et al., 2020; 2021; Golyanik & Theobalt, 2020; Li & Ghosh, 2020) and the appendix A.

3.2 NETWORK ARCHITECTURE AND LOSSES

In this section, we describe the network architecture that takes as input a problem instance and regresses a QUBO whose solution (*e.g.,* obtained via quantum annealing) solves the problem instance. For a given problem type, we require a problem description that is amenable to QUBO learning: A parametrisation of problem instances as real-valued vectors $\mathbf{p} \in \mathbb{R}^m$, and a parametrisation of solutions as binary vectors $\mathbf{x} \in \{0, 1\}^n$. Since we use supervised training, we additionally need a training set $\mathcal{D} = \{(\mathbf{p}_d, \hat{\mathbf{x}}_d)\}_{d=1}^D$ containing D problem instances $\mathbf{p}_d$ with ground-truth solutions $\hat{\mathbf{x}}_d$.

We use a multilayer perceptron (MLP) with L layers and H hidden dimensions, ReLU activations (except for the last layer, which uses sin like Sitzmann et al. (2020)), and concatenating skip connections from the input into odd-numbered layers (except for the first and last layers). The input to the network is a problem instance $\mathbf{p}$, and the output is a QUBO matrix $\mathbf{A}$: $\mathbf{A} = \mathrm{MLP}(\mathbf{p})$.

We could now use a dataset of problem instances and corresponding $\mathbf{A}$ to supervise the MLP directly. However, this requires specifying how $\mathbf{A}$ is to be derived for a certain instance, which comes with two downsides: (1) A problem-type-specific algorithm for analytically deriving instance-specific $\mathbf{A}$ needs to be designed to generate enough training data $\{(\mathbf{p}_d, \mathbf{A}_d)\}_{d=1}^D$, which is non-trivial, and (2) The binary parametrisation ($\mathbf{x}$) of the solution space depends on the algorithm, which can lead to more variables than intrinsically needed by the problem (e.g., if $\mathbf{x}$ needs to represent one of k numbers, a one-hot parametrisation would have length $n = k$, while a binary-encoding parametrisation would have length $n = \log k$). This is particularly problematic as contemporary quantum hardware only provides a limited number of qubits. We thus choose to not directly supervise $\mathbf{A}$ and instead supervise the solutions of the QUBO. This tackles both issues as it lets the network *learn* an algorithm that is *compatible* with the (potentially shorter) solution parametrisation. Our method is therefore easily applicable to new problem types, as we show in Secs. 3.4 and 3.5.

The regressed $\mathbf{A}$ defines a QUBO, which can be solved by any QUBO solver—we experiment with quantum annealing, simulated annealing and exhaustive search. But how can we, during training, backpropagate gradients from the solution binary vector $\mathbf{x}$ through the QUBO solver despite these solvers having zero gradients almost everywhere (Vlastelica et al., 2020)? We circumvent this issue by exploiting a contrastive loss (*cf.* (LeCun et al., 2006, Eq. (10))) as follows: We know the energy of the ground-truth solution $\hat{\mathbf{x}}$ of the problem instance, namely $\hat{\mathbf{x}}^\top \mathbf{A} \hat{\mathbf{x}}$. If the energy of the minimiser $\mathbf{x}^* = \mathbf{x}^*(\mathbf{A})$ of the current QUBO is lower, then $\mathbf{A}$ does not yet describe a QUBO that outputs the right solution. We, therefore, seek to push the energy of $\hat{\mathbf{x}}$ lower, while pulling the energy of the minimiser $\mathbf{x}^*$ up:

$$L_{\mathrm{gap}} = \hat{\mathbf{x}}^\top \mathbf{A} \hat{\mathbf{x}} - \mathbf{x}^{*\top} \mathbf{A} \mathbf{x}^*, \tag{1}$$

which has zero gradient if $\mathbf{x}^* = \hat{\mathbf{x}}$, as desired. L_{gap} avoids backpropagation through $\mathbf{x}^*$ and is even compatible with automatic differentiation. It yields the following update for an entry of $\mathbf{A}$, which can then be further backpropagated into the MLP via the chain rule:

$$\frac{\partial L_{\mathrm{gap}}(\mathbf{A})}{\partial \mathbf{A}_{i,j}} = 2\hat{\mathbf{x}}_i \hat{\mathbf{x}}_j - 2\mathbf{x}_i^* \mathbf{x}_j^* - 2\frac{\partial \mathbf{x}^*(\mathbf{A})}{\partial \mathbf{A}_{i,j}} \mathbf{A} \mathbf{x}^*, \tag{2}$$

where the last term comes from the dependency of $\mathbf{x}^*$ on $\mathbf{A}$ via the QUBO solver. While intuitively useful, we note that this term is zero "almost everywhere" (in the mathematical sense), and we hence ignore it as it provides almost no information. Note that this is a common approximation; *e.g.,* auto-differentiation frameworks backpropagate through $\max(\cdot)$ pooling in the same manner.

Unfortunately, L_{gap} alone would not prevent degenerate $\mathbf{A}$, which have multiple solutions, including undesirable ones. We, therefore, discourage such $\mathbf{A}$ that have more than one solution $\mathbf{x}^*$:

$$L_{\mathrm{unique}} = -|\hat{\mathbf{x}}^\top \mathbf{A} \hat{\mathbf{x}} - \mathbf{x}^{+\top} \mathbf{A} \mathbf{x}^+|, \tag{3}$$

where $\mathbf{x}^+$ is the $\mathbf{x}$ that minimises $\mathbf{x}^\top \mathbf{A} \mathbf{x}$ over $\{0, 1\}^n \setminus \{\mathbf{x}^*\}$, and $|\cdot|$ is the absolute value operator.

In addition to these data terms, we found it helpful to regularise the network by encouraging sparsity on all intermediate features of the MLP (Liu et al., 2015):

$$L_{\text{mlp}} = \sum_{\mathbf{f} \in \mathcal{F}} \frac{1}{|\mathbf{f}|} \|\mathbf{f}\|_1, \tag{4}$$

where $\mathcal{F}$ is the set of all network layer outputs (except for the last layer). The total loss then reads:

$$L = L_{\text{gap}} + \lambda_{\text{unique}} L_{\text{unique}} + \lambda_{\text{mlp}} L_{\text{mlp}}, \tag{5}$$

where we set $\lambda_{\text{mlp}} = 10^{-4}$ and $\lambda_{\text{unique}} = 10^{-3}$ regardless of problem type.

3.3 QUBOS ON D-WAVE

Given a QUBO problem generated by the MLP, we can use D-Wave to solve it. The annealer takes $\mathbf{A}$ as input, where $\mathbf{A}_{i,j} \in \mathbb{R}$ describes the direction and coupling strength between logical qubits i and j. However, each physical qubit in the annealer is only connected to a small subset of other physical qubits, which makes the regressed $\mathbf{A}$ not directly compatible with the annealer. We tackle this issue by manually pre-determining a sparse connectivity pattern of the physical qubits and then masking out the other entries of $\mathbf{A}$ before solving, such that the MLP focuses on only these sparse entries. For example, when $\mathbf{x} \in \mathbb{R}^n$ with $n = 8$, we can use D-Wave's Chimera architecture, which is made up of interconnected $\mathcal{K}_{4,4}$ unit cells (Dattani et al., 2019). ($\mathcal{K}_{4,4}$ is a complete bipartite graph with two sets of four qubits each.) Since $n = 8$, we can fit one problem instance into one unit cell, which allows us to anneal many problem instances in parallel by putting them in different unit cells. This speeds up training and saves expensive time on the quantum annealer. For larger problems with $n = 32$, we can use D-Wave's Pegasus architecture (Boothby et al., 2020), which has more interconnections (qubit couplings) between its $\mathcal{K}_{4,4}$ unit cells than Chimera. We use four such unit cells per problem instance, following D-Wave's pattern (Til). See Fig. 4b for an exemplary colour-coded qubit connectivity pattern of $\mathbf{A}$.

Given our full method, we next show how it can be applied to three problem types: graph matching, point set registration, and rotation estimation. We refer to the supplementary material for details.

3.4 GRAPH MATCHING

The goal of graph matching is to determine correspondences from k key points in two images or graphs, see Fig. 2 for an example of two matched graphs on the Willow dataset (Cho et al., 2013). This can be formalised as a quadratic assignment problem with a permutation matrix representing the matching (Seelbach Benkner et al., 2020): $\arg\min_{\mathbf{X} \in \mathbb{P}_k} \mathbf{x}^\top \mathbf{W} \mathbf{x}$, where $\mathbb{P}_k$ is the set of permutation matrices, $\mathbf{x} = \text{vec}(\mathbf{X}) \in \{0,1\}^{k^2}$ is the vectorised permutation matrix, and $\mathbf{W} \in \mathbb{R}^{k^2 \times k^2}$ contains pairwise weights. Unfortunately, the permutation constraint cannot be directly realised on the quantum annealer.

Instead, note that a permutation $P : [k] \to [k]$ is fully defined by the sequence $P(1), P(2), \ldots, P(k)$. Our method can use an efficient binary encoding for each entry of this sequence, using only $k \log k$ binary variables in total. Note that not all vectors $\mathbf{x} \in \{0,1\}^{k \log k}$ are valid permutations. As an optional post-processing step, we can perform a *projection* to the nearest permutation with respect to the Hamming distance in our binary encoding. Unless stated otherwise, we do not apply this post-processing.

(a) Source   (b) Target

Figure 2: Example matching on four keypoints in the Willow dataset (Cho et al., 2013). Corresponding points (the same colors) are found based on feature similarity.

In addition to the solution parametrisation, we also need to design the problem description $\mathbf{p}$. For real data, we use $\mathbf{p} = \text{vec}(\mathbf{W})$, where the diagonal contains cosine similarities between the feature vectors extracted with AlexNet (Krizhevsky et al., 2012) pretrained on ImageNet (Deng et al., 2009) of all key point pairs, and the off-diagonal follows the geometric term from (Torresani et al., 2008, Eq. (6)). For evaluation, we also introduce a synthetic dataset, *RandGraph*, where we use a matrix of random distances $\mathbf{D} \in \mathbb{R}^{k \times k}$ with entries $\mathbf{D}_{i,j} \in \mathcal{U}(0,1)$ to define $\mathbf{W}_{k \cdot i + P(i), k \cdot j + P(j)} = |\mathbf{D}_{i,j} - \mathbf{D}_{P(i),P(j)}|$. The MLP thus learns to compress the input matrix into a much smaller QUBO.

3.5 POINT SET REGISTRATION AND ROTATION ESTIMATION

In 2D point set registration, we are given two 2D point clouds with potentially different numbers of points and without correspondences, and we seek to find a rotation angle that best aligns them. We follow Golyanik & Theobalt (2020) and use the vectorised form of their input matrix to represent a problem instance. We parametrise the solution space of $\mathbf{x} \in \{0,1\}^9$ by splitting the output space $[0, \frac{1}{3}\pi]$ into 2^9 equally sized bins and consecutively indexing them with a 9-bit integer.

In 3D rotation estimation, we are given two 3D point clouds with known matches and seek to estimate the 3D rotation that best aligns them. We represent a problem instance by the vectorised covariance matrix of the two point clouds; 3D rotation is parametrised by Euler angles α, β, γ. We discretise each of the three angles into 2^5 bins, such that $\mathbf{x} \in \{0,1\}^{15}$.

4 EXPERIMENTAL EVALUATION

Data. For graph matching, we evaluate on the Willow object dataset (Cho et al., 2013), which contains labelled key points. We use k=4 randomly chosen key point pairs per image. Our training set comprises 5640 images, and our test set has 846 images. Both of the sets are obtained via pygmtools (ThinkLab, 2021). We also evaluate on our synthetic dataset *RandGraph* (see Sec. 3.4), with both k=4 and k=5.

For 2D point set registration, we evaluate on the 2D Shape Structure dataset (Carlier et al., 2016) which contains 2D silhouette images of real-world objects. We treat the silhouette outlines as 2D points. Our training set consists of 500 shapes from various classes, and our test set contains 50 shapes. For each shape, we apply 1000 (for train) or 100 (for test) different rotations of up to $60°$ and pick random pairs to generate problem instances.

For 3D rotation estimation, we evaluate on ModelNet10 (Wu et al., 2015), which contains CAD models of ten object categories, which consist of vertices and edges. We use the vertices as the point cloud for each shape. We use 300 shapes from various classes as our training set and test on 30 shapes from various classes. For each shape, we apply 1000 different 3D rotations with angle ranges $\alpha, \gamma \in [-\frac{1}{9}\pi, \frac{1}{9}\pi]$ and $\beta \in [-\frac{1}{18}\pi, \frac{1}{18}\pi]$, and pick random pairs to generate problem instances.

Comparisons. We compare to two baselines and, depending on the problem type, specialised methods. For all problem types, we demonstrate the power of using QUBOs by comparing to a *Diag* baseline that regresses a diagonal QUBO matrix $\mathbf{A}$ which allows to trivially solve the QUBO. While this baseline ablates the QUBO itself, we also consider a more natural neural network baseline, *Pure*, which regresses the binary solution directly by using no activation after the last layer and uses an ℓ_1-loss between this output and $\hat{\mathbf{x}}$ instead of L_{gap} and L_{unique}. At test time, we threshold the network output of Pure at 0 to obtain binary vectors. For our method, Diag, and Pure, we experiment with all combinations of $L \in \{3,5\}$ and $H \in \{32, 78\}$.

On graph matching for the Willow Dataset, we compare our result with the *Direct* baseline, where we directly solve the quadratic assignment problem from $\mathbf{W}$ with exhaustive search and which provides an upper bound for our method. We also compare against Quantum Graph Matching (QGM) (Seelbach Benkner et al., 2020), to which we pass our input matrices $\mathbf{W}$. For 2D point set registration, we compare against the analytic quantum method (AQM) (Golyanik & Theobalt, 2020), which is an upper bound for our method since we take its vectorised QUBO as input, and against the classical, specialised ICP method (Lu & Milios, 1997). On 3D rotation estimation, we use Procrustes as a classical method specialised to this problem type, which is thus an upper bound for the performance of our general method.

Metrics. We measure the results quality for graph matching by the percentage of correctly recovered permutation matrices (accuracy). For 2D point set registration and 3D rotation estimation, we know the ground-truth rotation and quantify the difference to the estimated rotation by their geodesic distance (angle) in the rotation groups $SO(2)$ and $SO(3)$, respectively.

QUBO Solvers. For graph matching, we follow Sec. 3.3 to make our regressed QUBOs compatible with the QA. Due to a restricted QA compute budget, we train and test with simulated annealing, unless stated otherwise. For the point-cloud experiments, we regress dense $\mathbf{A}$ and use our exhaustive-search implementation at train and test time, unless stated otherwise. When evaluating

on the QA, we rely on minor embeddings to make the regressed $\mathbf{A}$ compatible with the QA. Please refer to the appendix for details.

4.1 RESULTS

General Baselines. The quantitative results for graph matching, point set registration, and rotation estimation are reported in Table 1, 2, and 3, respectively. Across network sizes and all three problem types, the results show that having a full, $\mathcal{NP}$-hard QUBO (ours) instead of only a diagonal QUBO (Diag) is advantageous. We find that our method yields better results than Pure on both point set registration and rotation estimation, although Pure yields better results for graph matching.

Table 1: Comparison to general baselines on graph matching. We report the accuracy.

(a) RandGraph for $k=4$.

	Ours	Diag	Pure
$L=3, H=32$	9	8	**91**
$L=3, H=78$	30	18	**96**
$L=5, H=32$	11	11	**89**
$L=5, H=78$	49	43	**96**

(b) Willow object dataset (Cho et al., 2013) for $k=4$. Trained for 300 epochs with $L=5, H=78$.

Ours	Diag	Pure	Direct
69	53	90	**97**

Table 2: Comparison to general baselines on point set registration. We report the averages of the mean errors and its standard deviations over three runs.

	Ours	Diag	Pure
$L=3, H=32$	8.4 ± 0.8	11.1 ± 1.3	$\mathbf{8.2 \pm 1.2}$
$L=3, H=78$	$\mathbf{7.2 \pm 1.1}$	8.3 ± 0.7	9.3 ± 1.9
$L=5, H=32$	$\mathbf{8.6 \pm 0.5}$	10.9 ± 1.2	9.3 ± 1.9
$L=5, H=78$	$\mathbf{6.8 \pm 0.3}$	7.7 ± 0.5	11.3 ± 4.5

Table 3: Comparison to general baselines on rotation estimation. We report the averages of the mean errors and its standard deviations over three runs.

	Ours	Diag	Pure
$L=3, H=32$	5.9 ± 3.0	$\mathbf{5.4 \pm 1.0}$	7.9 ± 0.5
$L=3, H=78$	$\mathbf{4.1 \pm 0.5}$	5.0 ± 0.3	7.1 ± 0.1
$L=5, H=32$	$\mathbf{3.7 \pm 0.8}$	5.0 ± 0.4	16.2 ± 7.1
$L=5, H=78$	$\mathbf{3.4 \pm 0.4}$	4.7 ± 0.2	10.1 ± 1.8

Specialised Methods. For reference, we compare to several methods that are specialised to a certain problem type. Since our approach is general, they provide an upper bound for our performance.

We evaluate QGM (Seelbach Benkner et al., 2020) on some of our RandGraph instances. We confirm their finding that strongly enforcing permutation constraints eventually retrieves the right permutation as the sample with the lowest energy. However, using the analytical bound for the penalty term leads to a success probability (*i.e.,* the probability to get the best solution across anneals) smaller than random guessing due to experimental errors in the couplings. Additionally, we find that the QUBOs of our method are much smaller and better suited to be solved with a quantum annealer than those of QGM. For RandGraph with $k = 5$, our method needs 15 physical qubits while their baseline and row-wise methods need 89 qubits on average and a chain length of 4, and their *Inserted* method needs on average 39 qubits and a chain length of 3 on D-Wave Advantage. Thus, our success probability of 26% when evaluating on test data is orders of magnitude higher than *Inserted*'s 0.22% (best in QGM). This shows how our method improves over the quantum state of the art even though we merely focus on the solution with the smallest energy across anneals, while they actually focus on the success probabilities. We refer to the appendix D for a detailed evaluation. Table 1b confirms that *Direct* is an upper bound to our approach.

Table 8 contains quantitative results for 2D point set registration without noise. AQM slightly outperforms our method, which is to be expected since we take AQM's QUBO as input for our method and hence its performance is an upper bound for ours. Figure 3 contains a qualitative example of our method.

Figure 3: Test-time example inputs and outputs of our method trained for 2D point set registration.

As expected, quantitative results in Table 7 (with 0% incorrect correspondences) show that the classical, specialised Procrustes method performs better than our general method on 3D rotation estimation. Note that our method yields better results than Procrustes under test-time noise, as we discuss later in detail.

4.2 ABLATION

We ablate L_{unique} and L_{mlp} in Table 4. For graph matching, we use RandGraph with $k=4$. We find that removing either L_{unique} or L_{mlp} leads to mixed results on graph matching and worse results in almost all cases for points set registration and rotation estimation.

Table 4: Loss ablations. We report the accuracy for graph matching and the mean/median error otherwise.

	Graph Matching			Point Set Registration			Rotation Estimation		
	w/o L_{unique}	w/o L_{MLP}	Ours	w/o L_{unique}	w/o L_{MLP}	Ours	w/o L_{unique}	w/o L_{MLP}	Ours
$L=3, H=32$	7	**9**	9	17.8 / 12.0	18.6 / 13.4	**15.0 / 8.7**	5.1 / 5.0	3.4 / 3.0	**3.4 / 3.0**
$L=3, H=78$	**30**	29	**30**	15.5 / 8.0	21.8 / 17.0	**14.5 / 7.7**	**2.9 / 3.0**	4.6 / 5.0	4.2 / 4.0
$L=5, H=32$	**14**	6	11	18.1 / 11.7	19.0 / 7.7	**9.0 / 4.6**	3.4 / 3.0	2.5 / 2.0	**2.3 / 2.0**
$L=5, H=78$	46	**54**	49	18.3 / 11.7	**17.8 / 11.7**	18.5 / 7.7	3.7 / 4.0	4.1 / 4.0	**3.3 / 3.0**

4.3 EVALUATION ON D-WAVE

By design, our method is agnostic to the type of QUBO solver used. After training with exhaustive search, we compare how the performance on the test set differs under exhaustive search, SA, or QA. The results in Fig. 4a show that the exact solutions of exhaustive search only slightly outperform the less computationally expensive QA and SA. Furthermore, SA yields results very similar to QA.

(a) Errors on rotation estimation.   (b) Evolution of result and coupling matrix for graph matching.

Figure 4: (a) Histogram of errors on rotation estimation using exhaustive search (ES), quantum annealing (QA), and simulated annealing (SA) at test time. The maximum error on the x-axis would be 59 but no methods had higher errors than shown. (b) Evolution over different epochs of (top) the Hamming distance between predicted solutions and the ground truth, and (bottom) coupling matrix, when training graph matching. (top) The x-axis shows the Hamming distance. Blue indicates unprojected results and red after projection to a permutation. We only project after training.

Next, we compare the test-time results QA and SA obtain (after training with the same technique, QA and SA, respectively). See Table 5 for the results, both with and without projecting the final binary solution to a valid permutation encoding during post-processing. Training with QA delivers better results than with SA. We attribute this to a better second-best solution $\mathbf{x}^+$ used by L_{unique}. While SA yields solutions $\mathbf{x}^*$ that are comparable to QA, its second-

Table 5: RandGraph ($k=5$) with our method $L=5, H=78$ trained for 450 epochs (QA or SA).

	SA	QA
Before projection	10	**18**
After projection	24	**36**

best solutions are worse than QA's. We refer to the appendix for details. Unfortunately, real-world compute resources for training with QA remain limited, as of this writing. We, therefore, fall back on SA for larger-scale experiments in this work. However, Table 5 suggests that our results might improve noticeably on QA.

4.4 FURTHER ANALYSIS

Training. We visualise the evolution of the result quality and $\mathbf{A}$ for graph matching in Fig. 4b.

Varying Problem Difficulty. We provide a more detailed analysis of the performance of our method on point set registration for varying levels of difficulties. Table 6 shows that a larger input misalignment between the two point clouds worsens the results, as expected.

Table 6: Binned analysis on point set registration with $L{=}5$, $H{=}78$. We evaluate on point-cloud pairs with ground-truth angles uniformly sampled within the given intervals. We report the mean/median error in degrees.

angle interval	$0 - 1\frac{\pi}{18}$	$1\frac{\pi}{18} - 2\frac{\pi}{18}$	$2\frac{\pi}{18} - 3\frac{\pi}{18}$	$3\frac{\pi}{18} - 4\frac{\pi}{18}$	$4\frac{\pi}{18} - 5\frac{\pi}{18}$	$5\frac{\pi}{18} - 6\frac{\pi}{18}$
mean / median	4.0 / 1.9	5.1 / 2.6	6.4 / 3.0	7.9 / 3.8	7.9 / 3.8	8.4 / 4.0

Robustness to Noise. We investigate the robustness of our method and others against input noise at test time after training without noisy data. Specifically, we look at rotation estimation, where we randomly pick a fixed percentage of points and randomly permute their correspondences (among themselves). Table 7 contains results with varying amounts of incorrect correspondences. The result quality of our method barely degrades with increasing noise levels, even for 20% of incorrect correspondences. Our method already outperforms the classical Procrustes for even 1% of incorrect correspondences, even though Procrustes also starts from the covariance matrix. In fact, the advantage of our method grows with larger levels of noise. Our method also consistently performs better than the general baselines, which are themselves similarly robust to increasing noise levels.

Table 7: Robustness to varying amounts of incorrect test-time correspondences in rotation estimation. We report the mean/median error for $L{=}3$, $H{=}32$. The first column specifies the percentage of incorrect correspondences at test time.

%	**Ours**	Procrustes	Diag	Pure
0	3.9 / 4.0	**0.0 / 0.0**	5.6 / 6.0	8.1 / 8.0
1	**3.4 / 3.0**	5.8 / 3.0	5.7 / 6.0	8.2 / 8.0
5	**3.4 / 3.0**	25.7 / 13.0	6.0 / 6.0	8.2 / 8.0
10	**3.2 / 3.0**	43.8 / 21.0	6.2 / 6.0	8.2 / 8.0
15	**3.5 / 3.0**	64.7 / 58.0	6.2 / 6.0	8.2 / 8.0
20	**3.7 / 3.0**	75.3 / 79.0	5.8 / 6.0	8.2 / 8.0

We next look at our point set registration approach and others under input noise at test time, after training without noise. Here we add uniform noise to one point cloud, where the range of the noise is a percentage of the maximum extent of the point cloud. Table 8 contains results with varying level of additive uniform noise. ICP, an iterative approach, gives perfect results and thus outperforms the competing non-iterative approaches, with AQM in second place. Note that our method takes as input the vectorised QUBO that AQM solves and hence AQM constitutes an upper bound for the performance of our method. In addition, our general approach could, in principle, scale to 3D point set registration while AQM's solution parametrisation severely inhibits scaling to larger problems. Our method performs better than the general baselines.

Table 8: Robustness to varying amounts of uniform noise in point set registration. We report the mean/median error for $L{=}5$, $H{=}78$, and the number of required logical and physical qubits. The first column specifies the range of the added uniform noise in percent of the maximum extent of the point cloud. "†": uncoupled qubits.

%	**Ours**	Diag	Pure	AQM
0	5.8 / 3.5	7.3 / 4.7	6.8 / 5.9	**4.3 / 2.6**
5	6.4 / 3.3	7.0 / 5.2	7.0 / 6.1	**4.5 / 2.9**
10	6.5 / **3.3**	8.4 / 5.2	7.1 / 6.5	**5.6** / 3.8
15	7.2 / **3.5**	9.5 / 5.9	7.9 / 6.7	**5.6** / 3.8
20	10.3 / 5.4	11.6 / 6.6	8.2 / 6.8	**5.9 / 3.3**
Qubits	**9/14**	$(9/9)^\dagger$	n/a	21/∼55

5 DISCUSSION

Limitations and Future Work. As all learning-based approaches, our method can show lower performance on problem instances that fall significantly outside the training distribution. While our general method does not outperform classical methods specialised on certain problem types, we achieve performance on par with hand-crafted QUBO designs used in state-of-the-art methods in quantum computer vision. We achieve this while greatly reducing the effort required for new problem types. Although our focus is on a general design in this paper, our core idea of learning QUBOs can be specialised to any given problem type by designing a more specific network architecture and losses that capture priors for the problem type. For our point-cloud experiments, we rely on minor embeddings to transfer the regressed dense QUBOs to the QA. On existing hardware, large minor embeddings can worsen the result quality noticeably. However, in our case, we can embed a QUBO with 9 logical qubits into only 14 physical qubits.

Conclusions. This paper proposes learning to regress QUBO forms for a target problem type instead of deriving them analytically. We showed the generality of our method on diverse problem types. We believe our work significantly broadens the available toolbox for development and analysis of quantum computer vision methods and opens up numerous avenues for future research.

REFERENCES

Source code for dwave.system.composites.tiling. `https://docs.ocean.dwavesys.com/projects/system/en/stable/_modules/dwave/system/composites/tiling.html`. Accessed: 2022-02-09.

Tameem Albash and Daniel A Lidar. Adiabatic quantum computation. *Reviews of Modern Physics*, 90(1):015002, 2018.

Kerstin Beer, Dmytro Bondarenko, Terry Farrelly, Tobias J. Osborne, Robert Salzmann, Daniel Scheiermann, and Ramona Wolf. Training deep quantum neural networks. *Nature Communications*, 11(808), 2020.

Jacob Biamonte, Peter Wittek, Nicola Pancotti, Patrick Rebentrost, Nathan Wiebe, and Seth Lloyd. Quantum machine learning. *Nature*, 549, 11 2016.

Tolga Birdal, Vladislav Golyanik, Christian Theobalt, and Leonidas Guibas. Quantum permutation synchronization. In *Computer Vision and Pattern Recognition (CVPR)*, 2021.

Kelly Boothby, Paul Bunyk, Jack Raymond, and Aidan Roy. Next-Generation Topology of D-Wave Quantum Processors. *arXiv e-prints*, 2020.

Max Born and Vladimir Fock. Beweis des adiabatensatzes. *Zeitschrift für Physik*, 51(3):165–180, 1928.

Edward Boyda, Saikat Basu, Sangram Ganguly, Andrew Michaelis, Supratik Mukhopadhyay, and Ramakrishna R. Nemani. Deploying a quantum annealing processor to detect tree cover in aerial imagery of california. *PLoS ONE*, 12, 2017.

Jun Cai, William G. Macready, and Aidan Roy. A practical heuristic for finding graph minors. *arXiv e-prints*, 2014.

Axel Carlier, Kathryn Leonard, Stefanie Hahmann, Geraldine Morin, and Misha Collins. The 2d shape structure dataset: A user annotated open access database. *Computers & Graphics*, 58: 23–30, 2016.

Gabriele Cavallaro, Dennis Willsch, Madita Willsch, Kristel Michielsen, and Morris Riedel. Approaching remote sensing image classification with ensembles of support vector machines on the d-wave quantum annealer. In *IEEE International Geoscience and Remote Sensing Symposium (IGARSS)*, 2020.

Tat-Jun Chin, David Suter, Shin-Fang Ch'ng, and James Quach. Quantum robust fitting. In *Proceedings of the Asian Conference on Computer Vision (ACCV)*, November 2020.

Minsu Cho, Karteek Alahari, and Jean Ponce. Learning graphs to match. In *International Conference on Computer Vision*, pp. 25–32, 2013.

D-Wave Systems. Leap. `https://docs.dwavesys.com/docs/latest/leap.html`, 2022. online; accessed on the 24.01.2022.

D-Wave Systems, Inc. D-wave system documentation. `https://docs.dwavesys.com/docs/latest/c_gs_4.html`. online; accessed on 2022-03-06.

D-Wave Systems, Inc. dimod simulated annealing sampler. `https://test-projecttemplate-dimod.readthedocs.io/en/latest/reference/sampler_composites/samplers.html`, 2022a. online.

D-Wave Systems, Inc. dwave-neal. `https://github.com/dwavesystems/dwave-neal`, 2022b. online.

D-Wave Systems, Inc. D-wave ocean. `https://docs.ocean.dwavesys.com/en/stable`, 2022c. online.

Prasanna Date and Thomas Potok. Adiabatic quantum linear regression. *Scientific Reports*, 11, 2021.

Nike Dattani, Szilard Szalay, and Nick Chancellor. Pegasus: The second connectivity graph for large-scale quantum annealing hardware. *arXiv e-prints*, 2019.

B Dema, Junya ARAI, and Keitarou HORIKAWA. Support vector machine for multiclass classification using quantum annealers. 2020.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *Computer Vision and Pattern Recognition*, pp. 248–255. IEEE, 2009.

Anh-Dzung Doan, Michele Sasdelli, David Suter, and Tat-Jun Chin. A hybrid quantum-classical algorithm for robust fitting. In *Computer Vision and Pattern Recognition (CVPR)*, 2022.

Yuxuan Du, Min-Hsiu Hsieh, Tongliang Liu, and Dacheng Tao. Expressive power of parametrized quantum circuits. *Phys. Rev. Research*, 2:033125, 2020.

Vedran Dunjko and Hans J Briegel. Machine learning & artificial intelligence in the quantum domain: a review of recent progress. *Reports on Progress in Physics*, 81(7):074001, 2018.

Vedran Dunjko, Jacob M. Taylor, and Hans J. Briegel. Quantum-enhanced machine learning. *Phys. Rev. Lett.*, 117:130501, 2016.

Edward Farhi, Jeffrey Goldstone, Sam Gutmann, Joshua Lapan, Andrew Lundgren, and Daniel Preda. A quantum adiabatic evolution algorithm applied to random instances of an np-complete problem. *Science*, 292(5516):472–475, 2001.

Aaron Ferber, Bryan Wilder, Bistra Dilkina, and Milind Tambe. Mipaal: Mixed integer program as a layer. *AAAI Conference on Artificial Intelligence*, 34:1504–1511, 2020.

Thomas Gabor, Sebastian Feld, Hila Safi, Thomy Phan, and Claudia Linnhoff-Popien. Insights on training neural networks for qubo tasks. In *Proceedings of the IEEE/ACM 42nd International Conference on Software Engineering Workshops*, pp. 436–441, 2020.

Frank Gaitan and Lane Clark. Graph isomorphism and adiabatic quantum computing. *Phys. Rev. A*, 89:022342, Feb 2014. doi: 10.1103/PhysRevA.89.022342. URL https://link.aps.org/doi/10.1103/PhysRevA.89.022342.

Vladislav Golyanik and Christian Theobalt. A quantum computational approach to correspondence problems on point sets. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9182–9191, 2020.

Vojtěch Havlíček, Antonio D. Córcoles, Kristan Temme, Aram W. Harrow, Abhinav Kandala, Jerry M. Chow, and Jay M. Gambetta. Supervised learning with quantum-enhanced feature spaces. *Nature*, 567:209–212, 2019.

Sami Khairy, Ruslan Shaydulin, Lukasz Cincio, Yuri Alexeev, and Prasanna Balaprakash. Learning to optimize variational quantum circuits to solve combinatorial problems. In *AAAI Conference on Artificial Intelligence*, 2020.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In F. Pereira, C. J. C. Burges, L. Bottou, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems*, volume 25, 2012.

Jonas M. Kübler, Simon Buchholz, and Bernhard Schölkopf. The inductive bias of quantum kernels. In *Neural Information Processing Systems (NIPS)*, 2021.

Yann LeCun, Sumit Chopra, Raia Hadsell, Fu Jie Huang, and et al. A tutorial on energy-based learning. In *Predicting Structured Data*. MIT Press, 2006.

Junde Li and Swaroop Ghosh. Quantum-soft qubo suppression for accurate object detection. In *European Conference on Computer Vision (ECCV)*, 2020.

Baoyuan Liu, Min Wang, Hassan Foroosh, Marshall Tappen, and Marianna Pensky. Sparse convolutional neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 806–814, 2015.

Owen Lockwood and Mei Si. Reinforcement learning with quantum variational circuit. *AAAI Conference on Artificial Intelligence and Interactive Digital Entertainment (AIIDE)*, 16:245–251, 2020.

Feng Lu and Evangelos Milios. Robot pose estimation in unknown environments by matching 2d range scans. *Journal of Intelligent and Robotic systems*, 18(3):249–275, 1997.

Nicola Mariella and Andrea Simonetto. A Quantum Algorithm for the Sub-Graph Isomorphism Problem. *arXiv e-prints*, 2021.

Kevin Mato, Riccardo Mengoni, Daniele Ottaviani, and Gianluca Palermo. Quantum molecular unfolding. *arXiv e-prints*, 2021.

Jarrod R. McClean, Sergio Boixo, Vadim N. Smelyanskiy, Ryan Babbush, and Hartmut Neven. Barren plateaus in quantum neural network training landscapes. *Nature Communications*, 9(4812), 2018.

Catherine C. McGeoch. Adiabatic quantum computation and quantum annealing: Theory and practice. *Synthesis Lectures on Quantum Computing*, 5(2):1–93, 2014.

K. Mitarai, M. Negoro, M. Kitagawa, and K. Fujii. Quantum circuit learning. *Phys. Rev. A*, 98: 032309, 2018.

Florian Neukart, Gabriele Compostella, Christian Seidel, David von Dollen, Sheir Yarkoni, and Bob Parney. Traffic flow optimization using a quantum annealer. *Frontiers in ICT*, 4, 2017.

Hartmut Neven, Vasil S. Denchev, Geordie Rose, and William G. Macready. Training a binary classifier with the quantum adiabatic algorithm. *arXiv e-prints*, 2008a.

Hartmut Neven, Geordie Rose, and William G. Macready. Image recognition with an adiabatic quantum computer i. mapping to quadratic unconstrained binary optimization. *arXiv e-prints*, 2008b.

Nga T. T. Nguyen and Garrett T. Kenyon. Image classification using quantum inference on the d-wave 2x. *arXiv e-prints*, 2019.

Mohammadreza Noormandipour and Hanchen Wang. Matching point sets with quantum circuit learning. *arXiv e-prints*, 2102.06697, 2021.

Roman Orus, Samuel Mugel, and Enrique Lizaso. Forecasting financial crashes with quantum computing. *Physical Review A*, 99, 06 2019.

Davide Pastorello and Enrico Blanzieri. Quantum annealing learning search for solving qubo problems. *Quantum Information Processing*, 18(10):1–17, 2019.

Davide Pastorello, Enrico Blanzieri, and Valter Cavecchia. Learning adiabatic quantum algorithms over optimization problems. *Quantum Machine Intelligence*, 3(1):1–19, 2021.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8024–8035. Curran Associates, Inc., 2019. URL `http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf`.

Rigetti Computing. Rigetti quantum cloud services. `https://docs.rigetti.com/qcs/`, 2022. online; accessed on the 24.01.2022.

Michal Rolínek, Paul Swoboda, Dominik Zietlow, Anselm Paulus, Vít Musil, and Georg Martius. Deep graph matching via blackbox differentiation of combinatorial solvers. In *European Conference on Computer Vision (ECCV)*, pp. 407–424, 2020.

Michele Sasdelli and Tat-Jun Chin. Quantum annealing formulation for binary neural networks. *arXiv preprint arXiv:2107.02751*, 2021.

Marcel Seelbach Benkner, Vladislav Golyanik, Christian Theobalt, and Michael Moeller. Adiabatic quantum graph matching with permutation matrix constraints. In *International Conference on 3D Vision (3DV)*, 2020.

Marcel Seelbach Benkner, Zorah Lähner, Vladislav Golyanik, Christof Wunderlich, Christian Theobalt, and Michael Moeller. Q-match: Iterative shape matching via quantum annealing. In *International Conference on Computer Vision (ICCV)*, 2021.

Sukin Sim, Peter D. Johnson, and Alán Aspuru-Guzik. Expressibility and entangling capability of parameterized quantum circuits for hybrid quantum-classical algorithms. *Advanced Quantum Technologies*, 2(12):1900070, 2019.

Vincent Sitzmann, Julien N.P. Martel, Alexander W. Bergman, David B. Lindell, and Gordon Wetzstein. Implicit neural representations with periodic activation functions. In *Proc. NeurIPS*, 2020.

Stefano Speziali, Federico Bianchi, Andrea Marini, Lorenzo Menculini, Massimiliano Proietti, Loris Francesco Termite, Alberto Garinei, Marcello Marconi, and Andrea Delogu. Solving sensor placement problems in real water distribution networks using adiabatic quantum computation. *Quantum Computing and Engineering (QCE)*, 2021.

Tobias Stollenwerk, Elisabeth Lobe, and Martin Jung. Flight gate assignment with a quantum annealer. In *Quantum Technology and Optimization Problems*, 2019.

Alexander Teplukhin, Brian K. Kendrick, and Dmitri Babikov. Calculation of molecular vibrational spectra on a quantum annealer. *Journal of chemical theory and computation*, 2019.

ThinkLab. pygmtools. Shanghai Jiao Tong University. Github, 2021. URL https://github.com/Thinklab-SJTU/pygmtools.

Lorenzo Torresani, Vladimir Kolmogorov, and Carsten Rother. Feature correspondence via graph matching: Models and global optimization. In *European conference on computer vision*, pp. 596–609. Springer, 2008.

Salvador E. Venegas-Andraca and Sougato Bose. Storing, processing, and retrieving an image using quantum mechanics. In *Quantum Information and Computation*, volume 5105, pp. 137 – 147, 2003.

Guillaume Verdon, Jason Pye, and Michael Broughton. A universal training algorithm for quantum deep learning. In *APS March Meeting Abstracts*, 2019.

Marin Vlastelica, Anselm Paulus, Vít Musil, Georg Martius, and Michal Rolínek. Differentiation of blackbox combinatorial solvers. In *International Conference on Learning Representations (ICLR)*, 2020.

D. Willsch, M. Willsch, H. De Raedt, and K. Michielsen. Support vector machines on the d-wave quantum annealer. *Computer Physics Communications*, 248:107006, 2020a. ISSN 0010-4655. doi: https://doi.org/10.1016/j.cpc.2019.107006. URL https://www.sciencedirect.com/science/article/pii/S001046551930342X.

Dennis Willsch, Madita Willsch, H. A. De Raedt, and Kristel Michielsen. Support vector machines on the d-wave quantum annealer. *Comput. Phys. Commun.*, 248:107006, 2020b.

Zhirong Wu, Shuran Song, Aditya Khosla, Fisher Yu, Linguang Zhang, Xiaoou Tang, and Jianxiong Xiao. 3d shapenets: A deep representation for volumetric shapes. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1912–1920, 2015.

Fei Yan, Abdullah Iliyasu, and Salvador Venegas-Andraca. A survey of quantum image representations. *Quantum Information Processing*, 15, 1 2016.

Jan-Nico Zaech, Alexander Liniger, Martin Danelljan, Dengxin Dai, and Luc Van Gool. Adiabatic Quantum Computing for Multi Object Tracking. In *Computer Vision and Pattern Recognition (CVPR)*, 2022.

Kenneth M. Zick, Omar Shehab, and Matthew French. Experimental quantum annealing: case study involving the graph isomorphism problem. *Scientific reports*, 5(1), 2015.

APPENDIX

This appendix provides more details on adiabatic quantum computing in Sec. A. We provide training and implementation settings in Sec. B. Further details on the problem description for graph matching and a failure case are in Sec. C. Sec. D contains a deeper comparison with QGM (Seelbach Benkner et al., 2020) and Sec. E compares SA and QA. In Sec. F, we provide further quantitative and qualitative results on rotation estimation. Sec. G contains more details and experiments on point set registration.

Please note that the appendix also contains our new dataset RandGraph.

A ADDITIONAL QUANTUM COMPUTING BACKGROUND

A.1 ANNEALING IN DETAIL

As we have seen, quantum annealing is a metaheuristic to solve the $\mathcal{NP}$-hard Ising problem:

$$\underset{\mathbf{s}\in\{-1,1\}^n}{\arg\min} \ \mathbf{s}^\top \mathbf{J}\mathbf{s} + \mathbf{b}^\top \mathbf{s}, \tag{6}$$

where $\mathbf{s}$ is a binary vector, $\mathbf{J} \in \mathbb{R}^{n\times n}$ is a matrix of *couplings*, and $\mathbf{b} \in \mathbb{R}^n$ contains *biases* (McGeoch, 2014). Here, we give a brief overview how this fits in the framework of quantum mechanics. The D-Wave annealer uses Niobium loops as physical building blocks. The direction of the current flowing through these loops can be modeled as a qubit: it can be described as a two-dimensional, complex, normalized vector $|\psi\rangle \in \mathbb{C}^2$. In the so-called computational basis, the basis vectors then correspond to current flowing clock-wise or anti-clock-wise. After measuring the state, the system will collapse to either outcome. But if it is not measured, we can have any linear combination of the basis vectors. The coefficients of the linear combination give information of the probability what outcome occurs after the measurement (e.g. clock-wise or anti-clock-wise current).

The state space of $n \in \mathbb{N}$ qubits can be expressed with the tensor product $\bigotimes_{i=1}^{n} \mathbb{C}^2$ and is thus a 2^n-dimensional complex vector space. We need that many parameters because *entangled* states cannot be described separately. If the two states $|\psi\rangle, |\phi\rangle$ corresponding to different physical systems (for example two niobium loops, or two atoms) can be described independent from each other, the whole system is described by $|\psi\rangle \otimes |\phi\rangle$. Note that if every state could be decomposed this way, one would only need $2n$ parameters.

The evolution of these states over time can be described with the Schrödinger equation:

$$H|\psi\rangle = i\hbar \frac{\partial}{\partial t}|\psi\rangle, \tag{7}$$

where the Hamilton operator H is a Hermitian Matrix describing the possible energies of the system, i is the imaginary unit, $\hbar$ is a constant, and t denotes time. For adiabatic quantum computing, one needs a problem Hamiltonian H_P, where the eigenvector corresponding to the lowest eigenvalue corresponds to a solution of the particular Ising problem, and an initial Hamiltonian H_I with an easy-to-prepare ground state. The Adiabatic Theorem (Born & Fock, 1928) states that if we start with the ground state of H_I and take a sufficiently long time τ to gradually change from H_I to H_P, for example with:

$$H(t) = (1 - \frac{t}{\tau})H_I + \frac{t}{\tau}H_P, \tag{8}$$

then we end up in the ground state of H_P. From the ground state of H_P, we can deduce the solution of the particular Ising problem. To simulate this whole process classically can be difficult because we are dealing with $2^n \times 2^n$ matrices H_I and H_P, where n is the number of qubits. Exactly how difficult the classical simulation is depends on the exact form of the Hamiltonians used. Particularly promising for speed-ups are, for example, so-called non-stoquastic Hamiltonians (Albash & Lidar, 2018).

A.2 LOGICAL AND PHYSICAL QUBITS

The QUBO defines the couplings between two *logical* qubits i and j. Such a QUBO can contain couplings between any two qubits. However, in contemporary hardware realizations, each *physical* qubit is only connected to a few others (see Fig. 5a and Fig. 5b). In the main paper, we show how the QUBO matrix **A** can account for this sparse connectivity pattern by setting entries between logical qubits i and j to 0 if the physical qubits i and j have no connection. Still, D-Wave supports denser connectivity patterns than what is implied by the hardware: Multiple physical qubits can be chained together to represent a single logical qubit of **x** that has many connections. The physical qubits in the chain will then have strong couplings along the chain to encourage them to all end up in the same final state (either all 0 or all 1), respresenting the final state of the corresponding logical qubit. This is formalised as a minor embedding of the connectivity graph of the logical qubits into the connectivity graph of the physical qubits. The heuristic proposed in Cai et al. (2014) is popular to determine the minor embeddings in practice.

| (a) Chimera | (b) Pegasus |

Figure 5: Visualisation of qubit connectivities. (a) The connectivity pattern of the physical qubits in the Chimera architecture. The unit cells (green boxes) have fewer interconnections than on Pegasus. Image due to D-Wave (D-Wave Systems, Inc.). (b) The connectivity pattern of the physical qubits in the Pegasus architecture. Green, red, and yellow correspond to one problem instance each.

B IMPLEMENTATION DETAILS

Our code, which we will release, is implemented in Pytorch (Paszke et al., 2019). We use Adam (Kingma & Ba, 2014) with a learning rate of 0.001 for training. For graph matching on RandGraph with $k = 4$, we use a batch size of 141 and train for 150 epochs, which takes about 7 hours. For RandGraph $k = 5$, we use 450 epochs, which takes about 23 hours. For Willow, we train for 300 epochs, which takes about 14 hours. The baselines are trained for the same number of epochs. While Diag takes a comparable amount of time, the Pure baseline takes about 3 minutes to train. For the experiments with $k = 5$ we use 0.00001 as learning rate.

For the point cloud experiments, we use a batch size of 32 and train for 20 epochs, which takes about 4 hours. We train Pure and Diag with the same batch sizes and epochs. The training of the Diag baseline takes 4 hours as well and Pure is trained within 3 hours. When solving a QUBO on a QA, we anneal 100 times and pick the solution with the lowest energy. We access the QA via Leap 2 (D-

Wave Systems, 2022) using the Ocean SDK (D-Wave Systems, Inc., 2022c). When solving with SA, we use 100 iterations from the default neal simulated annealing sampler.

C GRAPH MATCHING

C.1 PROBLEM DESCRIPTION

Here, we describe the design of the problem description $\mathbf{p}$ for graph matching. We use $\mathbf{p} = \text{vec}(\mathbf{W})$, where the diagonal of $\mathbf{W}$ contains cosine similarities between the feature vectors extracted with AlexNet (Krizhevsky et al., 2012) pretrained on ImageNet (Deng et al., 2009) of all pairs of key points. The off-diagonal follows the geometric term described in (Eq (7)) from Torresani et al. (2008). In particular, we use the term $\mathbf{W}_{\text{geom}}$ from Eq. (7) from Torresani et al. (2008) with minus signs in the beginning and in the exponential, and set $\eta = 0.98$. The convex combination with $\mathbf{W}_{\text{Alex}}$, where the cosine similarities of the feature vectors are on the diagonal, is then:

$$\mathbf{W} = \tau\mathbf{W}_{\text{Alex}} + (1 - \tau)\mathbf{W}_{\text{geom}}. \tag{9}$$

We choose $\tau = 0.81$ and $\eta = 0.98$ such that the QAP coincides often with the ground-truth correspondences (see Table (1b) "Direct" from the main paper).

C.2 FAILURE CASE

We show a failure case of our method when applied to graph matching in Fig. 6. It occurs due to large differences in the observed appearance.

(a) Source (b) Matching

Figure 6: Failure case for graph matching. We visualise the ground truth of an image pair. Here, our method does not find the correct matching: Only the beak and neck are matched correctly, while the geometric information for the other key points differs too strongly.

D DETAILED COMPARISON WITH QGM (SEELBACH BENKNER ET AL., 2020)

Here, we compare our method with QGM (Seelbach Benkner et al., 2020) in detail. The focus of both works differs however. Their work focuses more on the probability distribution of the retrieved solutions. Our work is more concerned with incorporating the quantum annealer into the training pipeline. When training the neural network, L_{gap} uses the retrieved solution with the smallest energy across anneals, while they are also interested in the success probabilities, *i.e.* the probability to get the best solution across anneals.

The *individual* QUBOs that occur in our method are much easier to solve by the QA than a QUBO that would arise in Seelbach Benkner et al. (2020). To show this, we compute the average success probabilities of the various methods from Seelbach Benkner et al. (2020) over 141 instances of RandGraph with $k = 5$. The

Table 9: Averaged success probabilities from the various methods in Seelbach Benkner et al. (2020) over 141 problem instances on RandGraph with $k = 5$ in %.

Inserted	Baseline	Row-wise	Ours
0.22	0.07	0.07	**26**

results are in Table 9. We also apply our method
to these problem instances. We solve the resulting QUBO with QA and find the average probability to be 26% with a standard deviation of 18%, better than any method from Seelbach Benkner et al. (2020).

This difference is not surprising since we construct our method such that we only use trivial embeddings and do not need to apply the minorminer heuristic (Cai et al., 2014). Because of that, for RandGraph with $k = 5$, our method needs only 15 physical qubits while their baseline and row-wise methods need 89 qubits on average and a chain length of 4, and their *Inserted* method needs on average 39 qubits and a chain length of 3 on D-Wave Advantage. Note that a heuristic search for better penalty parameters as in Birdal et al. (2021) could give rise to better results for the methods from Seelbach Benkner et al. (2020) in Table 9. However, the corresponding embeddings would still be problematic. Directly using the binary encoding for permutations as in Gaitan & Clark (2014) requires additional qubits because the problem would a-priori not be quadratic anymore.

E   SOLUTION QUALITY OF SA AND QA

In the main paper, we show that training with QA yields better performance than training with SA. Here, we analyse the quality of the solutions found by both techniques further. Fig. 7 contains histograms that depict the output of the quantum annealer and the two different simulated annealing solvers from neal (D-Wave Systems, Inc., 2022b) and from dimod (D-Wave Systems, Inc., 2022a). In contrast to the solver from dimod, neal is highly optimized for performance and hence we used it for our experiments.

We focus our analysis on the number of sweeps in SA, *i.e.* the number of steps in the 'cooling' schedule. We observe that it has a large influence on the quality of the second-best solution.

| (a) SA 1000 sweeps | (b) SA 10 sweeps | (c) SA 2 sweeps | (d) Dimod | (e) QA |

Figure 7: Energy histograms of (ideally optimal) 1000 samples for SA (different number of sweeps and dimod) and QA on one instance of RandGraph with $k = 5$ after 450 epochs training.

Table 10 illustrate this by averaging the fraction of the second-best energies over 141 instances and analysing 1000 samples from different solvers. We see that the quantum annealer produces the second best samples with the lowest energies.

Note however that we do not claim that this is an intrinsic general advantage of QA over SA, but merely that in our setting, QA outperforms SA. Still, prior work (Willsch et al., 2020b) also reaches the conclusion that quantum annealing has a lot potential for finding good near-optimal solutions.

The dimod sampler also produces second-best solutions with low energy but is computationally very expensive. This may be because a lot of non-optimal solutions are produced compared to the implementation from neal.

Table 10: Second-best energies of SA relative (in %) to the second-best energies of QA. We report the mean and std over 141 instances. Higher is better.

SA Neal with 1000 sweeps	SA Neal with 10 sweeps	SA Dimod
94.2 ± 10.3	86.0 ± 19	99.8 ± 0.9

F   3D ROTATION ESTIMATION

F.1   THREE STAGES

We obtain improved results when exploiting the fact that we use three Euler angles. Specifically, this minimal prior knowledge about the problem type allows us so split the regression into three stages. We use one stage per angle, with one network per stage. The training setup is as follows. We feed the first network with problem instances where $\alpha, \beta, \gamma \neq 0$. The network then regresses α. We feed the second stage network with problem instances, where $\alpha = 0$ and $\beta, \gamma \neq 0$. Subsequently the network regresses β. Lastly we feed the third network with problem instances, where $\alpha, \beta = 0$ and $\gamma \neq 0$. Here it regresses γ. During test time, the first network determines α, which is then applied to the input. The updated input is re-encoded before the second stage, which outputs β. Finally, with α and β applied already, the third stages regresses γ. Fig. 8 shows how the three different networks regress the angles and how it affects the problem instance.

| (a) Initial problem instance | (b) Application of the α rotation | (c) Application of the α, β rotations | (d) Application of the α, β, γ rotations |

Figure 8: Visualisation of the different steps of the rotation-estimation pipeline. We show (blue) the original 3D point cloud and (red) the rotated point cloud. The green points are points of the red point cloud, where the correspondence is unknown. Here, 10% of the correspondences are unknown.

F.2   VARIANCE

To better judge the stability under different random seeds, we repeat the main experiment from the paper three times for our method and each baseline. In Table 11, we report the mean and std of the median in our experimental results. Here, similar to the results from the main paper, we outperform the Diag and Pure baselines in all but one setting.

Table 11: Comparison to general baselines on rotation estimation. We report the mean of the per-experiment *median* and std across experiments for three different random seeds.

	Ours	Diag	Pure
$L=3, H=32$	6.0 ± 3.6	$\mathbf{5.3 \pm 1.1}$	7.0 ± 1.0
$L=3, H=78$	$\mathbf{4.0 \pm 1.0}$	5.0 ± 0.0	7.0 ± 0.0
$L=5, H=32$	$\mathbf{3.7 \pm 1.2}$	5.0 ± 0.0	16.3 ± 7.2
$L=5, H=78$	$\mathbf{3.7 \pm 0.6}$	5.0 ± 0.0	9.0 ± 1.0

F.3   TRAINING ON NOISY DATA

Table 12 shows how our method performs on noise-free and noisy test data after training on noisy data. Curiously, the noisy training data appears to negatively affect the training of our method and its performance drops, while Diag improves and Pure remains unchanged.

F.4   QUALITATIVE COMPARISON ON NOISY TEST DATA

Fig. 9 visualises the difference of our solution after training on noise-free data and Procrustes' solution under noisy test data.

F.5   COMPARISON TO AQM (GOLYANIK & THEOBALT, 2020)

Our method can handle 3D rotation estimation with known correspondences. However, AQM (Golyanik & Theobalt, 2020) would require 81 densely connected logical qubits, which is not supported by the current quantum-hardware generations. We thus cannot compare against AQM for this problem setting and instead only compare to classical methods such as Procrustes.

Table 12: Robustness to varying amounts of incorrect test-time correspondences in rotation estimation. We report the mean/median error for $L{=}3$, $H{=}32$. The first column specifies the percentage of incorrect correspondences at test time.

(a) Training without any noise.

%	**Ours**	Procrustes	Diag	Pure
0	3.9 / 4.0	**0.0 / 0.0**	5.6 / 6.0	8.1 / 8.0
1	**3.4 / 3.0**	5.8 / 3.0	5.7 / 6.0	8.2 / 8.0
5	**3.4 / 3.0**	25.7 / 13.0	6.0 / 6.0	8.2 / 8.0
10	**3.2 / 3.0**	43.8 / 21.0	6.2 / 6.0	8.2 / 8.0
15	**3.5 / 3.0**	64.7 / 58.0	6.2 / 6.0	8.2 / 8.0
20	**3.7 / 3.0**	75.3 / 79.0	5.8 / 6.0	8.2 / 8.0

(b) Training with 10% incorrect correspondences.

%	**Ours**	Procrustes	Diag	Pure
0	4.4 / 4.0	**0.0 / 0.0**	4.6 / 5.0	8.1 / 8.0
1	**4.3 / 4.0**	5.8 / 3.0	5.1 / 5.0	8.3 / 8.0
5	**5.0 / 5.0**	25.7 / 13.0	5.1 / 5.0	8.2 / 8.0
10	**5.2 / 5.0**	43.8 / 21.0	5.2 / 5.0	8.2 / 8.0
15	5.2 / 5.0	64.7 / 58.0	**5.0 / 5.0**	8.2 / 8.0
20	5.6 / 6.0	75.3 / 79.0	**4.9 / 5.0**	8.2 / 8.0

(a) Initial problem setting   (b) Our solution   (c) Solution by Procrustes

Figure 9: Comparison of initial input rotation, our method and Procrustes. The initial 3D point cloud is blue and the rotated one is red, where the unknown correspondences are displayed in green. Here, 10% of the correspondences are unknown.

G 2D POINT SET REGISTRATION

G.1 SETTING DETAILS

We encode the point set registration instances similar to Golyanik & Theobalt (2020). As the correspondences for point set registration are not known, we use k-nearest neighbours to find possible correspondences. Our network is trained with three nearest neighbours.

G.2 VARIANCE

In Table 13, we report the median instead of the mean of Table 2. Here, we outperform the baselines in all cases. In nearly all setups, we outperform the baselines, and only for one case, we are on-par with the Pure baseline. Still, even in that case, our method performs more consistently as evidenced by its lower std. These experiments show that we consistently outperform the baselines and the performance is not dependent on the random seed.

Table 13: Comparison to general baselines on point set registration. We report the mean of the per-experiment *median* and std across experiments for three different random seeds.

	Ours	Diag	Pure
$L{=}3, H{=}32$	**4.8 ± 0.6**	6.8 ± 0.2	5.8 ± 0.9
$L{=}3, H{=}78$	**3.7 ± 0.3**	5.1 ± 0.4	4.8 ± 0.3
$L{=}5, H{=}32$	**4.6 ± 0.1**	7.1 ± 1.0	7.1 ± 1.6
$L{=}5, H{=}78$	**3.4 ± 0.1**	4.9 ± 0.0	7.9 ± 2.7

Table 14: Robustness to varying amounts of uniform noise. We report the mean/median error for $L{=}3$, $H{=}32$. The first column specifies the range of the added uniform noise in percent of the maximum extent of the point cloud.

%	**Ours**	Diag	Pure	AQM
0	*7.4 / 4.2*	11.3 / 7.0	7.8 / 6.6	**4.3 / 2.6**
5	*6.7 / 3.8*	11.7 / 7.3	8.0 / 6.8	**4.5 / 2.9**
10	*7.2 / 4.5*	12.2 / 6.8	8.6 / 7.0	**5.6 / 3.8**
15	*8.2 / 4.9*	12.6 / 6.8	9.7 / 8.0	**5.6 / 3.8**
20	*11.0 / 6.0*	13.9 / 8.2	14.3 / 10.4	**5.9 / 3.3**

G.3 NOISE

In addition to the experiments in the main paper that uses the largest architecture, we also test the noise resistance on the smallest network setup with $L = 3$, $H = 32$. The results are shown in Table 14. Here, while our method is better than the baselines, we do not outperform AQM. However, *by construction, AQM is an upper bound for our method as the matrix introduced in Golyanik & Theobalt (2020) is the same as our input into the network but it gets directly solved by the QA.*

G.4 QUALITATIVE ABLATION RESULTS

In addition to the quantitative loss ablation in the paper, we visualise the effect of the losses here. In Figure 10, the full loss results in a nearly ground-truth rotation. However, if we leave out L_{gap} or L_{MLP} during training, a significant reduction in rotational accuracy is visible.

| (a) Initial problem instance | (b) Ours with the full loss | (c) Ours without L_{MLP} | (d) Ours without L_{gap} |

Figure 10: Qualitative loss ablation results. We show the (blue) original point cloud and (red) rotated point cloud.

G.5 FAILURE CASE

We continue our analysis with failure cases. Results in the main paper show that an increasing input angle leads to a reduction of the accuracy of our regressed angle. This can be traced back to our problem-instance encoding as the authors of Golyanik & Theobalt (2020) mention that an increasing angle makes finding the right correspondences more error-prone. Therefore, an imperfect input encoding makes it is also more likely for us to regress the wrong angle.

Furthermore, nearly symmetrical shapes can be difficult, as most points can be nearly perfectly aligned even with wrong rotations. Fig. 11 contains such a failure case. The initial angle of this instance, $50.8°$, is relatively large for our setup, and the shape, which looks like the silhouette of a fish, is nearly rotationally symmetrical. In cases like this, our method has difficulties regressing the right rotation.

| (a) Initial problem instance | (b) Failing to regress correct rotation |

Figure 11: Example of a failure case in point set registration. We show (blue) the initial image as well as (red) the rotated image.