What Has Been Overlooked in Contrastive Source-Free Domain Adaptation: Leveraging Source-Informed Latent Augmentation within Neighborhood Context

Abstract

Source-free domain adaptation (SFDA) involves adapting a model originally trained using a labeled dataset (*source domain*) to perform effectively on an unlabeled dataset (*target domain*) without relying on any source data during adaptation. This adaptation is especially crucial when significant disparities in data distributions exist between the two domains and when there are privacy concerns regarding the source model's training data. The absence of access to source data during adaptation makes it challenging to analytically estimate the domain gap. To tackle this issue, various techniques have been proposed, such as unsupervised clustering, contrastive learning, and continual learning. In this paper, we first conduct an extensive theoretical analysis of SFDA based on contrastive learning, primarily because it has demonstrated superior performance compared to other techniques. Motivated by the obtained insights, we then introduce a straightforward yet highly effective latent augmentation method tailored for contrastive SFDA. This augmentation method leverages the dispersion of latent features within the neighborhood of the query sample, guided by the source pretrained model, to enhance the informativeness of positive keys. Our approach, based on a single InfoNCE-based contrastive loss, outperforms state-of-the-art SFDA methods on widely recognized benchmark datasets.

1 Introduction

Supervised learning has proven successful in mimicking human behaviors in situations such as manipulation Mnih et al. (2015), recognition Russakovsky et al. (2015), and understanding Fawzi et al. (2022), primarily due to its accessibility to vast amounts of labeled data. However, this success hinges upon the assumption that both the training and the test data originate from the same underlying probability distribution, which often does not hold in various real-world scenarios. Consequently, model performance tends to deteriorate when applied to novel (*target*) data domains – such as real-world images – whose underlying data distribution markedly deviates from that of the training (*source*) domain (e.g., computer-generated images). This divergence in data distribution is commonly referred to as *domain shift* Ben-David et al. (2010). Domain adaptation (DA) tackles the performance degradation that stems from the domain shift, by acquiring representations that remain invariant to such shifts Ganin & Lempitsky (2015).

Lately, a significant and practical challenge has emerged, known as *source-free domain adaptation* (SFDA). This challenge revolves around the goal of developing the domain-invariant representation without using any labeled source data during the adaptation. This shift in focus is motivated by real concerns related to training data privacy and intellectual property Liang et al. (2020); Yang et al. (2021b); Huang et al. (2021a); Zhang et al. (2022); Yang et al. (2022). The inability to access the source domain during adaptation adds complexity to the task of estimating the degree of domain shift, making it challenging to learn a shared representation that bridges divergent domains. In response to this, the concept of contrastive learning has attracted significant attention. In this approach, discriminative clustering plays a crucial role in defining the decision boundaries that guide the classification efforts, by utilizing these clustered groups. However,

Figure 1: t-SNE visualization of target features extracted by the source pre-trained encoder, revealing significant feature dispersion due to domain shift. However, nearby target samples still tend to share similar ground truths, motivating our in-depth exploration of contrastive clustering in SFDA.

in scenarios where labels are unavailable, the decision boundaries inferred from these clusters may not consistently align with the actual classification boundaries based on the target labels.

Existing contrastive SFDA methods can be categorized into two types of approaches, based on how they generate positive keys for contrastive learning, whether neighborhood-based or augmentation-based. The neighborhood-based approaches rely on transferring neighborhood information from the source to the target by initializing the model for target adaptation with a model pre-trained on the source domain Yang et al. (2022). However, as the adaptation progresses and the model undergoes unsupervised clustering, the significance of this source domain neighborhood information diminishes. Conversely, the augmentation-based approach establishes a source-like set with a distribution aligned with the source domain during pre-training for generating pseudo-labels. Subsequently, it employs contrastive learning with data augmentation to facilitate discriminative clustering during target adaptation Zhang et al. (2022). However, this method encounters two significant problems. Firstly, like pseudo-labeling-based SFDA, its performance can be negatively affected by the presence of noisy labels Liang et al. (2021a). Secondly, achieving an optimal tradeoff between distribution alignment and contrastive clustering is challenging, especially when the source data is inaccessible during target adaptation.

The present paper aims to offer a comprehensive insight into how various design choices for positive keys in contrastive SFDA can mitigate the performance degradation due to domain shift. Additionally, it explores an effective solution for generating more informative positive keys to enhance contrastive clustering when source data is not available during target adaptation. This understanding is grounded in empirical observations within the latent feature space, as illustrated in Figure 1. In this figure, we can observe that target features extracted from the source pre-trained encoder exhibit significant dispersion because of domain shift, leading to increased target classification errors. Despite this feature dispersion, it is worth noting that nearby target features often share the same ground truth labels. These two observations are elaborated upon as follows:

- **Observations on Target Feature Dispersion**: A domain shift induces a significant dispersion of target features, as extracted from the source pre-trained encoder (as clear when comparing the t-SNE plots for source data features and target data features). This dispersion reduces the discriminative quality of the associated features, consequently making it difficult to effectively classify samples within the target domain.

- **Observations on Neighborhood Informativeness**: Despite the reduced discriminability, which leads to the lack of well-defined target feature clusters extracted from the source pre-trained encoder, neighboring target features still tend to belong to the same ground truth class. This suggests that valuable information, *w.r.t* target ground truth, likely exists within the local vicinity of target features.

Motivated by these observations, we conduct a comprehensive analysis of the underlying principles of contrastive SFDA and explore aspects that have been overlooked in the existing contrastive SFDA frameworks. Subsequently, we introduce our Source-informed Latent Augmented Neighborhood (SiLAN) method, built upon the acquired theoretical insights. This involves applying Gaussian noise to the latent features of the neighborhood centroid of a target query sample, mirroring the source model's standard deviation of latent features from the neighboring target samples, to enhance positive key generation. This latent augmentation is consistently applied during the positive key generation process for each target query sample, combining the benefits of both neighborhood exploration and data augmentation. Aligning the standard deviation of the random noise with that determined by the source pre-trained model allows contrastive clustering to effectively leverage the dispersion of the neighbors' features, which is often regarded as potentially detrimental to the model's discriminability. Our empirical findings demonstrate that optimizing an InfoNCE-based contrastive loss Oord et al. (2018); Chen et al. (2020) alone, combined with our SiLAN augmentation method, yields state-of-the-art performance across a range of benchmark SFDA datasets.

In summary, our paper's contributions are outlined as follows:

- We hypothesize that domain shift causes significant dispersion in target features yet nearby points still tend to share similar labels, explaining the success of contrastive clustering in SFDA.

- Our theoretical analysis of contrastive SFDA reveals that three often-overlooked factors, associated with the aforementioned hypotheses, have significant implications for target classification performance.

- To address these three issues, we introduce SiLAN, a simple yet effective latent augmentation technique explicitly designed to improve contrastive SFDA.

- Experimental results support our theoretical findings, demonstrating that InfoNCE, when augmented with SiLAN, achieves state-of-the-art performance in SFDA.

2 Related Work

2.1 Source-Free Domain Adaptation

The existing methods for SFDA can be grouped into two categories: contrastive and non-contrastive. Non-contrastive methods rely on extra guidance, such as pseudo labels Liang et al. (2020; 2021b) or samples generated through adversarial learning Li et al. (2020), from the source pre-trained model during adaptation. However, this additional guidance can potentially have detrimental effects on target classification performance Li et al. (2020). In this paper, we focus on contrastive SFDA methods, which have shown better performance. Attracting and Dispersing (AaD) Yang et al. (2022) identifies nearby samples to a target query using neighborhood searching and directly uses their latent features as positive keys. Historical Contrastive Learning (HCL) Huang et al. (2021a) introduces an instance-wise loss to enhance data-augmentation-based contrastive learning for target adaptation. Divide and Contrast (DaC) Zhang et al. (2022) investigates contrastive clustering using augmented inputs, effectively applying it to SFDA. However, existing contrastive SFDA methods overlook the alignment of different domains during target adaptation. In contrast, our approach incorporates domain alignment into the contrastive clustering process, which is achieved while optimizing a single contrastive loss.

2.2 Latent Augmentation

Data augmentation can change the semantics of input samples by causing major shifts in the latent space Upchurch et al. (2017). These techniques also vary based on data modality. Conversely, augmenting in the latent space Cheung & Yeung (2020) offers diverse transformations with a lower risk of altering the semantics of queries and is not dependent on the data modality. Common latent augmentation techniques include interpolation, extrapolation, random translation, and adding Gaussian noise DeVries & Taylor (2017), which have been shown effectiveness in various fields such as computer vision Liu et al. (2018); Stutz et al. (2019), natural language processing Kumar et al. (2019), and graph representation learning Cheng et al. (2022). In this paper, we investigate using latent augmentation to address challenges in contrastive SFDA. Specifically, we tailor the variance of the random noise used in latent augmentation according to the feature cluster variances from the source pre-trained model. This key technical distinction differentiates our method from the existing latent augmentation approaches.

2.3 Contrastive Learning

Contrastive learning is an effective framework for training models to differentiate between samples, which is versatile, and suitable for both supervised learning Khosla et al. (2020) and self-supervised learning (SSL). Contrastive SSL methods utilize the InfoNCE-based loss to draw samples (positive keys) closer to a query sample if they are similar, and to push away samples (negative keys) that are dissimilar, all within a designated embedding space. These methods often require large batch sizes for an effective contrasting Chen et al. (2020), additional memory banks for momentum updates He et al. (2020), or additional negative sampling strategies Hu et al. (2021). In our study, we use an InfoNCE-based contrastive loss, applied to the output logit space, to address SFDA challenges.

3 Source-Free Domain Adaptation

In this section, we outline the problem setup for SFDA and explain the implementation of contrastive learning to solve it. We also define the concept of *neighborhood* in our study, a key element for our theoretical analysis and proposed method.

3.1 Problem Statement

In customized applications, users typically possess their own data and a model pre-trained on a large dataset such as ImageNet Russakovsky et al. (2015), but do not have access to the model's original training data. SFDA methods aim to address this by enabling the model to adapt to the new data domain (*target domain*) without needing access to the original training data domain (*source domain*).

Pre-training on a source domain We define a dataset from a source domain as $\mathcal{D}_S := \{(\mathbf{x}_{\mathbf{s}}^i, \mathbf{y}_{\mathbf{s}}^i)\}_{i=1}^N$ where $\mathbf{x}_{\mathbf{s}}^i$ denotes the i-th data sample from the source dataset, and $\mathbf{y}_{\mathbf{s}}^i$ is its corresponding class label. The objective of the pre-training stage is to derive a model $f_s := F_s \circ G_s$ (referred to as the *source model*) that minimizes the classification error on the source data $\epsilon_{\mathcal{D}_S}(f_s) := \sum_{i=1}^N \mathbb{P}[f_s(\mathbf{x}_s^i) \neq \mathbf{y}_s^i]$, where G is a feature extractor that encodes input samples into latent features, and F is a task-specific classifier.

Adaptation on a target domain Consider a dataset sampled from a target domain, denoted as $\mathcal{D}_T := \{\mathbf{x}_{\mathbf{t}}^i\}_{i=1}^M$, where $\mathbf{x}_{\mathbf{t}}^i$ refers to the i-th data sample from the target dataset. During adaptation, it is important to note that class labels for all target samples are not accessible. In this stage, the goal is to have a target model f_t that minimizes the generalization error on the target data $\epsilon_{\mathcal{D}_T}(f_t) := \sum_{i=1}^M \mathbb{P}[f_s(\mathbf{x}_t^i) \neq \mathbf{y}_t^i]$, possibly guided by the source pre-trained model f_s without having access to the source data. One example of leveraging the source pre-trained model f_s is to initialize the parameters of the target model f_t with those of f_s.

3.2 Contrastive SFDA

Contrastive learning is a widely recognized algorithm for SSL. It operates on the principle that if data samples can be effectively clustered within a specific embedding space, the resulting model has the potential to exhibit robust performance across various downstream tasks, provided that fine-tuning is conducted appropriately.

In the context of SFDA, we choose to formulate the contrastive objective within the output logit space instead of the feature or embedding space used in SSL. This decision is motivated by the use of equal number of classes for classification in both the source and target domains. Note that in our empirical findings, there is no noticeable difference between performing distribution alignment on the output logit space and the output probability space. To simplify the mathematical notations, we conduct all theoretical analyses focusing on the alignment of output logits. For clarity, the output probability vector is the softmax output of logit vector. For any input $\mathbf{x}$, the sum of all elements in the output probability vector equals one, i.e., $\sum_{z=1}^{Z}[Softmax(f_t(\mathbf{x}))]_z = 1$, where Z denotes the number of classes.

In comparison to SSL, formulating in either the logit or probability space simplifies the direct clustering of data samples according to the number of ground truth classes.

3.3 Definition of Neighborhood

To establish a neighborhood, we first define a feature bank $\mathbb{B}_T := \{G(\mathbf{x_t}^i) \,|\, \mathbf{x_t}^i \in \mathcal{D}_T\}_{i=1}^M$ where G is a feature extractor initialized with the parameters of G_s and updated throughout the adaptation. Similar to the neighborhood discovery used in unsupervised representation learning Huang et al. (2019); Van Gansbeke et al. (2020), given a query sample, we define a neighborhood of the sample as its K-Nearest Neighbors (K-NNs), with proximity determined by the cosine similarity between the features of the query sample and those of another sample drawn from $\mathbb{B}_T$:

$$d(\mathbf{x}_t^i, \mathbf{x}_t^j) := \frac{G(\mathbf{x}_t^i) \cdot \mathbb{B}_{T,j}}{||G(\mathbf{x}_t^i)|| \cdot ||\mathbb{B}_{T,j}||}. \tag{1}$$

where $\mathbb{B}_{T,j}$ denotes the j-th element of $\mathbb{B}_T$ corresponding to the features of a data sample $\mathbf{x}_t^j$. Thus, the neighborhood $\mathbb{N}_K(\mathbf{x}_t^i)$ of $\mathbf{x}_t^i$ comprises the top K similar samples with respect to feature similarity, defined as:

$$\mathbb{N}_K(\mathbf{x}_t^i) := \arg max_{\mathcal{S} \subset \mathbb{B}_T, |\mathcal{S}|=K} \sum_{\mathbf{x} \in \mathcal{S}} d(\mathbf{x}_t^i, \mathbf{x}). \tag{2}$$

The centroid of the neighborhood, denoted as $\mu_K(\mathbf{x}^i)$, is the mean of the feature vectors of each sample within $\mathbb{N}_K(\mathbf{x}_t^i)$.

4 Theoretical Analysis of Contrastive SFDA

In this section, we engage in theoretical analysis concerning alignment errors when performing contrastive learning in the output logit space. In the meantime, we forge links between these error terms and the ground truth labels of target samples in the context of SFDA. This theoretical analysis not only sheds light on the crucial aspects of SFDA that necessitate attention from the research community, but it also clarifies the existing research gaps that our work endeavors to fill. All the proofs can be found in the appendix.

4.1 The Behavior of Contrastive Loss in SFDA

We start by closely examining how InfoNCE-based contrastive loss can be applied to address SFDA problems. For brevity, we use the term *transformation* to encompass the process of generating positive samples $\mathbf{x}^+$ from the query $\mathbf{x}$, whether through neighborhood searching or data augmentation. The transformations of other samples within the same mini-batch are used as negative samples $\mathbf{x}^-$.

Cosine similarity is commonly used in SSL to formulate contrastive loss within a high-dimensional embedding space. However, when applying contrastive loss in the output logit space for SFDA, further clarification is necessary. To provide a clearer understanding of this modification, we begin our discussion by redefining an

upper bound for the contrastive loss formulated in the output logit space. This refinement allows us to focus on analyzing the alignment of output predictions through contrastive loss, using Euclidean distance as our measure.

Proposition 1. *When formulated in the output logit space, the InfoNCE-based contrastive loss, denoted as $\mathcal{L}_{cont}$, serves as an upper bound for the misalignment associated with two distinct alignment errors in predictions.*

$$\sum_{i=1}^{m}\left(\log(m-1) + \frac{||\,f_t(\mathbf{x}_i) - f_t(\mathbf{x}_i^+)\,||_2^2}{2\tau} - \frac{1}{m-1}\sum_{j\neq i}\frac{||f_t(\mathbf{x}_i) - f_t(\mathbf{x}_j^+)||_2^2}{2\tau}\right) \leq \mathcal{L}_{cont}.$$

Here, τ represents the temperature parameter, m is the mini-batch size, $\mathbf{x}_j^+$ denotes a negative sample $\mathbf{x}^-$ given the query $\mathbf{x}_i$, and $\mathcal{L}_{cont}$ is defined as follows:

$$\mathcal{L}_{cont} = -\sum_{i=1}^{m} log \frac{e^{f_t^\top(\mathbf{x}_i) f_t(\mathbf{x}_i^+)/\tau}}{\sum_{j\neq i} e^{f_t^\top(\mathbf{x}_i) f_t(\mathbf{x}_j^+)/\tau}}.$$

The proof for the proposition is provided in Appendix B.1. According to Proposition 1, minimizing the InfoNCE loss involves reducing the alignment error between the predictions of the query sample and its positive key $\mathbf{x}^+$, while introducing misalignment with the predictions of transformations applied to other samples within the same mini-batch. Therefore, optimizing the InfoNCE loss formulated in the logit space leads to the formation of discriminative clusters, however, it does not guarantee the alignment of these clusters with the ground truth.

4.2 What Has Been Missing in Contrastive SFDA

Now, let us begin establishing a connection between the prediction alignments introduced by contrastive loss and the target classification error in a task involving Z classes. With z denoting an index, which corresponds to a specific ground truth class, for a group of output logits. $\mathcal{C}_z$ represents a set of target samples belonging to class z and having predictions that are close to each other in the output logit space. Within each $\mathcal{C}_z$, there exists a subset $\mathcal{C}_z^\delta$ that exclusively comprises samples predicted to be class z and exhibits no overlapping with any other C_l for $l \neq z$. Therefore, we can reasonably assume that there exists an Euclidean space in which the logits of this subset of samples can be enclosed within a ball $\mathcal{C}_z^\delta$ of diameter δ. The set of positive keys, whose logits can confidently be considered to lie within this ball, can be represented as:

$$\mathcal{S}_z^+ = \{\mathbf{x}^+ \in \mathcal{C}_z : \forall \mathbf{x} \in \mathcal{C}_z^\delta, ||f_t(\mathbf{x}^+) - f_t(\mathbf{x})||_2^2 \leq \delta\},$$

and a set of negative keys, whose logits are confirmed to exist outside the ball, is denoted as:

$$\mathcal{S}_z^- = \{\mathbf{x}^- \in \mathcal{C}_z : \forall \mathbf{x} \in \mathcal{C}_z^\delta, ||f_t(\mathbf{x}^-) - f_t(\mathbf{x})||_2^2 > \delta\}.$$

To establish a coherent connection between the target classification error and the prediction alignment errors, we introduce a definition for the target classification error concerning the logit groups and their associated ground truth:

$$\epsilon_{\mathcal{D}_T} = \sum_{z=1}^{Z}(\mathbb{P}[f_t(\mathbf{x}_t) \neq z, \forall \mathbf{x}_t \in \mathcal{C}_z] + \mathbb{P}[z \neq \mathbf{y}_t, \forall \mathbf{x}_t \in \mathcal{C}_z]), \tag{3}$$

The first term represents the probability of misclassification by the classifier f_t for a given group class z within the logit group $\mathcal{C}_z$. The second term indicates the probability that the ground truth for a sample $\mathbf{x}_t$ within the logit group $\mathcal{C}_z$ does not align with the group class z. This notation for classification error is inspired by the theoretical framework developed within the context of contrastive SSL Huang et al. (2021b).

Assuming that near-perfect prediction alignments, as introduced in Proposition 1, can be achieved by minimizing $\mathcal{L}_{cont}$, we can derive an upper bound for the error defined in Equation 3 as follows:

Lemma 2. *If $\mathcal{C}_z^\delta \cap \mathcal{C}_l^\delta = \emptyset$ holds for any $l \neq z$, then the error $\epsilon_{\mathcal{D}_T}$ defined on the groups of logits is upper bounded by:*

$$\epsilon_{\mathcal{D}_T} \leq R_\delta + \sum_{z=1}^{Z} \left(\mathbb{P}[f_t(\mathbf{x}^+) \neq \mathbf{y}_t, \forall \mathbf{x}^+ \in \mathcal{S}_z^+] + \mathbb{P}[f_t(\mathbf{x}^-) = \mathbf{y}_t, \forall \mathbf{x}^- \in \mathcal{S}_z^-] \right),$$

where $R_\delta = \frac{\cup_{z=1}^{Z}(\mathcal{C}_z - \mathcal{C}_z^\delta)}{\cup_{z=1}^{Z}\mathcal{C}_z}$ and $(\mathcal{C}_z - \mathcal{C}_z^\delta)$ may overlap with $(\mathcal{C}_l - \mathcal{C}_l^\delta)$ for any $l \neq z$.

The proof for the lemma is provided in Appendix B.2. Lemma 2 suggests that the target classification error, as defined in Equation 3, is affected by the overlap between $\mathcal{C}_z$ and $\mathcal{C}_l$ for any $l \neq z$, as well as the misclassification of the transformations $\mathbf{x}^+$ and $\mathbf{x}^-$. Given the connection between the prediction alignments introduced by contrastive loss and the target classification error, we will now explore how the two types of transformations, namely, *neighborhood searching* and *augmentation*, contribute to reducing the upper bound provided in Lemma 2.

Data augmentation. Augmentation-based contrastive SFDA methods augment data in the input space and use the logits of the augmented view as the positive key for contrastive clustering Zhang et al. (2022). However, solely relying on the augmented view transformed in the input space has limitations in mitigating the overlap of clusters Huang et al. (2021b). Employing standard data augmentation techniques without addressing domain divergence may not effectively reduce misclassifying transformations – called the **first oversight**.

Neighborhood searching. It involves using the logits of the query's K nearest neighbors, located in the latent feature space *w.r.t* the model parameters, as the positive key for contrastive clustering. However, mitigating the misclassification of transformations through neighborhood searching, akin to K-NN classifiers, requires an intensive search to find the most suitable K for the given task and data. Increasing the number of nearest neighbors, *i.e.,* larger K, results in smoother predictions but also leads to a greater overlap of logit groups, *i.e.,* higher R_δ Wu et al. (2002) – the **second oversight**. Existing methods Yang et al. (2022) assume that the informativeness of a query's neighborhood can be achieved by initializing the model f with the parameters of the source model f_s. However, as the model is updated for contrastive clustering, the initially informative neighborhood information from f_s diminishes. This underscores the necessity for a more effective utilization of f_s during adaptation to enhance the informativeness of query neighborhoods and to further reduce the risk of misclassifying transformations – the **third oversight**.

In summary, existing contrastive SFDA methods can mitigate either R_δ (with data augmentation) or the misclassification of transformations (with neighborhood searching), but they cannot simultaneously handle both of them.

5 The Proposed Framework

In this section, we present the *source-informed latent augmented neighborhood* (SiLAN) method, which harnesses the advantages of both *neighborhood searching* and *augmentation* to address the previously mentioned oversights.

5.1 Source-informed Latent Augmentation

To clarify the proposed work, we introduce an additional feature bank denoted as $\mathbb{B}_S := \{G_s(\mathbf{x}_\mathbf{t}^i) \,|\, \mathbf{x}_\mathbf{t}^i \in \mathcal{D}_T\}_{i=1}^{M}$. During adaptation, G_s remains unchanged and is used to search the source-informed neighborhood $\mathbb{N}_K^s(\mathbf{x}_\mathbf{t}^i)$ for a given target query $\mathbf{x}_\mathbf{t}^i$. For a given $\mathbf{x}_\mathbf{t}^i$, we independently and identically (i.i.d) sample random noise $\xi \in \mathbb{R}^H$ from $\mathcal{N}(\mathbf{0}, \sigma_K^s{}^2(\mathbf{x}_\mathbf{t}^i))$, where $\sigma_K^s{}^2(\mathbf{x}_\mathbf{t}^i)$ is the variance of $\mathbb{N}_K^s(\mathbf{x}_\mathbf{t}^i)$, and H is the dimension of a feature vector. We then add ξ to the latent features of the query's neighborhood (*w.r.t* the current target model f_t) centroid, denoted as $\mu_K^t(\mathbf{x}_\mathbf{t}^i)$, to generate positive keys:

$$\hat{\mathbf{h}} := G_t(\mu_K^t(\mathbf{x}_\mathbf{t}^i)) + \xi. \tag{4}$$

Note that $\hat{\mathbf{h}}$ follows a Gaussian distribution, *i.e.,* $\hat{\mathbf{h}} \sim \mathcal{N}(G_t(\mu_K^t(\mathbf{x}_\mathbf{t}^i)), \sigma_K^s{}^2(\mathbf{x}_\mathbf{t}^i))$.

5.2 InfoNCE-based Contrastive Framework

To illustrate the integration of SiLAN into existing contrastive SFDA frameworks, we specifically employ the InfoNCE contrastive framework Oord et al. (2018); Chen et al. (2020); He et al. (2020) as an example. We adhere to the settings of existing contrastive SFDA methods, formulating it within the output logit space for each mini-batch of size m:

$$\mathcal{L}_{SiLAN} = -\sum_{i=1}^{m} log \frac{e^{[F_t(G_t(\mathbf{x_t}^i))]^\top F_t(\hat{\mathbf{h}}_i)/\tau}}{\sum_{j \neq i} e^{[F_t(G_t(\mathbf{x_t}^i))]^\top F_t(\hat{\mathbf{h}}_j)/\tau}} \tag{5}$$

where G_t and F_t represent the feature extractor and task-specific classifier of f_t, respectively. $\hat{\mathbf{h}}_j$ denotes the augmentation of other samples in the same mini-batch, and τ is the temperature parameter. Note that the focus of our work is to examine the informativeness of the dispersion of $\mathbb{N}_K^s$ in the latent space. Consequently, we refrain from incorporating additional techniques, such as momentum update He et al. (2020), to enhance contrastive clustering, despite their potential to improve the performance.

From an intuitive perspective, optimizing a contrastive objective with positive keys defined by $F_t(\hat{\mathbf{h}}_i)$ can be likened to applying forces that attract the predictions of $\hat{\mathbf{h}}_i$, which are informed by $\mathbb{N}_K^s(\mathbf{x_t}^i)$, towards the logit group where the query sample $\mathbf{x_t}^i$ belongs to. In the meantime, this optimization exerts a repelling effect on those $\hat{\mathbf{h}}_j$ that are located outside the logit group, pushing them away from it.

5.3 Integrating SiLAN into InfoNCE during Adaptation

To clarify the integration of our SiLAN into the InfoNCE contrastive framework, we provide a detailed description of the integration process in Algorithm 1, which outlines the target adaptation phase when incorporating SiLAN.

Algorithm 1: SiLAN-Enhanced InfoNCE for Target Adaptation

Input: mini-batch target data $\mathbf{x_t} \in \mathcal{D}_T$; source model $F_s(G_s(\cdot))$; neighbor number K; temperature τ and maximum epoch N.

1 **Initialization:** $F_t(G_t(\cdot)) \leftarrow F_s(G_s(\cdot))$ and $n = 0$;
2 **while** $n \leq N - 1$ **do**
3   Find K-NNs for $\mathbf{x_t}$ using G_t to form their target neighborhoods $\mathbb{N}_K^t(\mathbf{x_t})$;
4   Find K-NNs for $\mathbf{x_t}$ using G_s to form their source-informed neighborhoods $\mathbb{N}_K^s(\mathbf{x_t})$;
5   Compute centroids for target neighborhoods: $\mu_K^t(\mathbf{x_t}) = \frac{1}{K}\sum_{i=1}^{K} \mathbb{N}_K^{t,i}(\mathbf{x_t})$;
6   Compute variances for source-informed neighborhoods:
       $\sigma_K^s{}^2(\mathbf{x_t}) = \frac{1}{K}\sum_{j=1}^{K}\left(G_s(\mathbb{N}_K^{s,j}(\mathbf{x_t})) - \frac{1}{K}\sum_{i=1}^{K}G_s(\mathbb{N}_K^{s,i}(\mathbf{x_t}))\right)^2$;
7   Sample noises from a Gaussian with variance $\sigma_K^s{}^2(\mathbf{x_t})$: $\xi \sim \mathcal{N}(0, \sigma_K^s{}^2(\mathbf{x_t}))$;
8   Augment the latent features for the positive keys to guide contrastive clustering:
       $\hat{\mathbf{h}} = G_t(\mu_K^t(\mathbf{x_t})) + \xi$;
9   Optimize the model parameters for $F_t(G_t(\cdot))$ to minimize the InfoNCE loss $\mathcal{L}_{SiLAN}$:
       $-\sum_{i=1}^{m} log \frac{e^{[F_t(G_t(\mathbf{x_t}^i))]^\top F_t(\hat{\mathbf{h}}_i)/\tau}}{\sum_{j \neq i} e^{[F_t(G_t(\mathbf{x_t}^i))]^\top F_t(\hat{\mathbf{h}}_j)/\tau}}$;
10      $n = n + 1$;
11 **end**

5.4 Unveiling Rationale for Latent Augmented Neighborhood

Diversifying data augmentation techniques in the input space enhances the concentration of augmented data Wang & Liu (2021), thereby reducing R_δ. Yet, it introduces notable variations in the latent space due to minor changes in input, posing a risk of altering the semantics of queries. To address this, we propose performing latent augmentation on the query's neighborhood centroid for positive key generation.

Figure 2: The transformation of a query sample traverses a Gaussian profile defined by source-informed neighbors in the latent space, initiating a pull-and-push effect to reduce feature overlaps among logit groups.

To understand the rationale behind our latent augmentation on the query's neighborhood centroid, let us first examine a general case where random noise $\xi_0 \sim \mathcal{N}(\mathbf{0}, \sigma^2)$ is added to the latent features of $\mu_K(\mathbf{x})$. Such augmentation enriches the diversity of the neighborhood by allowing the transformation to traverse around a Gaussian profile whose radius is determined by its standard deviation σ. A larger σ promotes extensive exploration, capturing diverse but potentially irrelevant data variations. Conversely, a smaller σ restricts exploration to local and fine-grained variations within a specific logit group. This flexibility enables the model to adapt to varying degrees of data complexity and distribution shifts, making it well-suited for reducing misclassification of the transformation in contrastive SFDA.

Moreover, traversing augmentations around Gaussian profiles enhances contrastive clustering by pushing non-overlapping logit group regions apart, ensuring well-separated features. This improved separability aligns with the desired behavior as established by the theoretical findings in the subsequent lemma. To be specific, for a query sample within a logit group $\mathcal{C}_i$, traversing its augmentations around the Gaussian profile (while aligning their predictions with that of the query through a contrastive objective) will stretch the non-overlapping region $\mathcal{C}_i^\delta$ and extend its boundary. Conversely, traversing the augmentations of its negative samples, which likely do not belong to the same category (diverging their predictions from that of the query), will push $\mathcal{C}_i^\delta$ farther away from other logit groups to which these negative samples belong, as illustrated in Figure 2. This adaptive process encourages the model f_t, optimized by a contrastive loss, to dynamically reduce R_δ during adaptation.

To clarify the subsequent lemma, consider G_t^{opt} as a target feature extractor that converges on a contrastive objective with augmentation traversing a Gaussian profile with σ. To quantify the gap between clusters post-convergence, we employ the concept of calculating the effective region of a Gaussian beam as introduced in Hogg & Lang (2013). Following their approach, we denote the noise variance per augmentation in the extraneous noise as σ_{ext}^2 [1] from the overlapping regions.

Proposition 3. *If $\mathcal{C}_z^\delta \cap \mathcal{C}_l^\delta = \emptyset$ holds for any $z \neq l$, and the assumption that the representation of a query sample in the feature space remains close to those of its positive augmentations and far away from those of its negative samples holds, then for all $z \neq l$ and $i \neq j$ (where $\mathbf{x}_i \in \mathcal{C}_z^\delta$ and $\mathbf{x}_j \in \mathcal{C}_l^\delta$), their distance in the*

---

[1]Extraneous noise is a term derived from physics that refers to a transient portion of a wave, which does not belong to the ambient waves, nor does it originate from the source being studied. It is important to distinguish this concept from the notion of random noise used for augmentation.

latent feature space has a lower bound as we take the limit $\sigma_{ext}^2 \to 0$, as follows:

$$|G_t^{opt}(\mathbf{x}_i) - G_t^{opt}(\mathbf{x}_j)| \geq 3.1704\sigma.$$

The proof for the proposition is provided in Appendix B.3. Here, the optimal aperture radius for a Gaussian profile approximates 1.5852σ. In the optimal scenario, the Gaussian profile maximizes its transformation-to-noise ratio under the assumption that σ_{ext}^2 is close to 0.

Similarly, let F_t^{opt} denote the target classification head, which is linear in our work. With Proposition 3 in consideration, we can derive a lower bound for the gap between any two logit groups in the output space when a Gaussian profile is used to augment the query's neighborhood features:

Lemma 4. *$\forall z \neq l$ and $i \neq j$, if the linear classifier F^{opt} is L-bi-Lipschitz continuous, $\mathcal{C}_z^\delta \cap \mathcal{C}_l^\delta = \emptyset$ holds for any $z \neq l$ where $\mathbf{x}_i \in \mathcal{C}_z^\delta$ and $\mathbf{x}_j \in \mathcal{C}_l^\delta$, and $\sigma_{ext}^2 \to 0$:*

$$|f_t^{opt}(\mathbf{x}_i) - f_t^{opt}(\mathbf{x}_j)| \geq \frac{3.1704\sigma}{L},$$

where $f_t^{opt} = F_t^{opt}(G_t^{opt}(\cdot))$ and the Lipschitz constant L depends on the number of parameters of $F_t(\cdot)$.

The proof for the lemma is provided in Appendix B.4. Lemma 4 suggests that when the parameters of $f_t(\cdot)$ converge on the contrastive loss with SiLAN augmentation for positive keys, the augmented views of the query's neighborhood centroid within a Gaussian profile can ensure a lower bound, dependent on the standard deviation of the Gaussian and the number of parameters of the linear classifier, for the minimum gap among the non-overlapping regions of the logit groups.

Therefore, we can conclude that a better separation among logit groups (larger non-overlapping regions) can be achieved by using a Gaussian profile with a higher standard deviation for SiLAN, as stated in Lemma 4. However, if the Gaussian profile extends beyond the boundaries of the query's logit group in the latent feature space (when σ is too large), the augmentation might traverse outside the logit group. This introduces ambiguity into contrastive clustering, leading to more errors in mislabeling transformations. To be specific, a large σ for the augmentation might cause the predictions of positive keys to fall outside the query's logit group, leading to an increase in $\sum_{z=1}^Z (\mathbb{P}[f_t(\mathbf{x}^+) \neq \mathbf{y}_t, \forall \mathbf{x}^+ \in \mathcal{S}_z^+])$. Meanwhile, it could result in the predictions of negative keys falling within the query's logit group, leading to an increase in $\mathbb{P}[f_t(\mathbf{x}^-) = \mathbf{y}_t, \forall \mathbf{x}^- \in \mathcal{S}_z^-])$.

5.5 Informativeness of σ

Recalling the phenomenon highlighted in *Observations on Neighborhood Informativeness*, which suggests that the dispersed neighbors derived from $\mathbb{N}_k^s(\mathbf{x}_t)$ carry valuable insights into the ground truth of $\mathbf{x}_t$ (as nearby points share the same labels), the incorporation of this information becomes significant in the process of discriminative clustering. Therefore, it is crucial to perform SILAN in a manner that covers these neighbors to reduce the likelihood of mislabeled augmentations. To achieve this, expanding the scope of the Gaussian profile's influence based on the query's neighborhood as determined by the source model is necessary. Specifically, the radius of the Gaussian profile should be determined by $\mathbb{N}_K^s(\mathbf{x_t})$, thereby setting σ to σ_K^s.

In summary, the optimal value for σ should be large enough to create a substantial gap among logit groups, making them more distinguishable, while avoiding the generation of an excessive number of ambiguous augmentations. Interestingly, the dispersion of $\mathbb{N}_K^s(\mathbf{x}_t)$ that adversely impacts discriminability on $\mathcal{D}_T$ actually proves beneficial in determining the optimal value of σ for the proposed SiLAN.

6 Experiments

6.1 Experiments on Toy Dataset

In this section, we demonstrate the effectiveness of SiLAN on a toy dataset, the *moon* dataset, which simulates domain shift by rotating data sample orientations. The source domain features an interleaving half circle

with 1000 data points, and the target domain replicates this structure with a 30-degree rotation around the mean. Both domains incorporate Gaussian noise with a standard deviation of 0.1 and are generated using distinct random seeds. The experimental setup includes a 5-layer fully connected network. As depicted in Figure 3, the source-only model encounters challenges in accurately classifying numerous points, while our SiLAN method excels in achieving accurate classification.

(a) Source Only   (b) SiLAN

Figure 3: **(Best viewed in color.)** Visualization of the decision boundary derived from the *moon* dataset *w/wo* SiLAN.

Table 1: Comparison of SFDA methods using ResNet-50 on *Office-31*. The best results are highlighted.

Method	A→D	A→W	D→W	D→A	W→D	W→A	Avg.
ResNet-50 He et al. (2016)	68.9	68.4	96.7	62.5	99.3	60.7	76.1
SHOT Liang et al. (2020)	94.0	90.1	98.4	74.7	99.9	74.3	88.6
NRC Yang et al. (2021a)	96.0	90.8	99.0	75.3	100.0	75.0	89.4
3C-GAN Li et al. (2020)	92.7	93.7	98.5	75.3	99.8	**77.8**	89.6
HCL Huang et al. (2021a)	94.7	92.5	98.2	75.9	100.0	77.7	89.8
AaD Yang et al. (2022)	96.4	92.1	**99.1**	75.0	100.0	76.5	89.9
SiLAN (Ours)	**97.1**	**95.8**	98.9	**76.4**	**100.0**	76.9	**90.7**

Table 2: Comparison of the SFDA methods on *Office-Home* (ResNet-50).

Method	Ar→Cl	Ar→Pr	Ar→Rw	Cl→Ar	Cl→Pr	Cl→Rw	Pr→Ar	Pr→Cl	Pr→Rw	Rw→Ar	Rw→Cl	Rw→Pr	Avg.
ResNet-50 He et al. (2016)	34.9	50.0	58.0	37.4	41.9	46.2	38.5	31.2	60.4	53.9	41.2	59.9	46.1
G-SFDA Yang et al. (2021b)	57.9	78.6	81.0	66.7	77.2	77.2	65.6	56.0	82.2	72.0	57.8	83.4	71.3
SHOT Liang et al. (2020)	57.1	78.1	81.5	68.0	78.2	78.1	67.4	54.9	82.2	73.3	58.8	84.3	71.8
NRC Yang et al. (2021a)	57.7	80.3	82.0	68.1	**79.8**	78.6	65.3	56.4	**83.0**	71.0	58.6	85.6	72.2
AaD Yang et al. (2022)	59.3	79.3	82.1	68.9	**79.8**	79.5	67.2	57.4	83.1	72.1	58.5	85.4	72.7
DaC Zhang et al. (2022)	**59.5**	79.5	81.2	69.3	78.9	79.2	67.4	56.4	82.4	74.0	**61.4**	84.4	72.8
SiLAN (Ours)	58.2	**81.2**	**82.5**	**69.8**	78.6	**80.3**	**68.4**	**58.6**	82.5	**75.6**	60.8	**86.1**	**73.6**

6.2 Experiments on Benchmark Datasets

Datasets. We have conducted a thorough evaluation of our SiLAN model on three benchmark datasets for SFDA:

- **Office-31** Saenko et al. (2010), which consists of 4,652 images of 31 object classes captured from three domains: Amazon (**A**), Webcam (**W**), and DSLR (**D**).

Table 3: Comparison of the SFDA methods on *VisDA2017* (ResNet-101).

Method	plane	bcycl	bus	car	horse	knife	mcycl	person	plant	sktbrd	train	truck	Avg.
ResNet-101 He et al. (2016)	55.1	53.3	61.9	59.1	80.6	17.9	79.7	31.2	81.0	26.5	73.5	8.5	52.4
SHOT Liang et al. (2020)	94.3	88.5	80.1	57.3	93.1	94.9	80.7	80.3	91.5	89.1	86.3	58.2	82.9
HCL Huang et al. (2021a)	93.3	85.4	80.7	68.5	91.0	88.1	86.0	78.6	86.6	88.8	80.0	74.7	83.5
G-SFDA Yang et al. (2021b)	96.1	88.3	85.5	74.1	97.1	95.4	89.5	79.4	95.4	92.9	89.1	42.6	85.4
NRC Yang et al. (2021a)	96.8	**91.3**	82.4	62.4	96.2	95.9	86.1	80.6	94.8	94.1	90.4	**59.7**	85.9
AaD Yang et al. (2022)	95.2	90.5	85.5	79.2	96.4	96.2	88.8	80.4	93.9	91.8	91.1	55.9	87.1
DaC Zhang et al. (2022)	96.6	86.8	**86.4**	78.4	96.4	96.2	**93.6**	**83.8**	**96.8**	95.1	89.6	50.0	87.3
SiLAN (Ours)	**97.5**	90.1	85.8	**80.4**	**97.6**	**95.5**	92.0	82.9	96.5	**95.3**	**92.6**	53.4	**88.3**

- **Office-Home** Venkateswara et al. (2017), which has 15,500 images of 65 classes from four domains: Artistic (**Ar**), Clipart (**Cl**), Product (**Pr**), and Real-World (**Rw**).

- **VisDA-C 2017** Peng et al. (2017), a large-scale dataset used for the 2017 ICCV visual DA challenge, with 280K images of 12 object categories. The source domain contains synthetic images generated via 3D model rendering, while the target domain consists of real images.

Experiment Setup. For fair comparisons with other SFDA methods, we maintain consistency in network architecture, training techniques, and hyperparameters across all experiments. Specifically, we utilize ResNet-50 for Office-31 and Office-Home, and ResNet-101 for VisDA-C. The classifier F consists of two linear layers. We adopt the InfoNCE-based loss from *SimCLR* Chen et al. (2020) for contrastive learning. The optimization uses an SGD optimizer with a momentum of 0.9, and the batch size is set to 32 for Office datasets and 64 for VisDA-C. The learning rates for all experiments are fixed at $1e^{-3}$. Results for Office-31 and Office-Home are reported after 100-epoch training, while VisDA results are presented after 15-epoch training. In Office-Home experiments, we apply regularization to the diagonal matrix of predictions in a mini-batch, achieved through singular value decomposition Cui et al. (2020). The SiLAN hyperparameters, including K_t and K_s, represent the number of neighbors determined by the target and source models, respectively. They are set to 3 for most Office experiments and 15 for VisDA-C. The temperature parameter τ for *InfoNCE* loss is set to 0.11 for most experiments.

Results. Results for Office-31, Office-Home, and VisDA-C 2017 are shown in Tables 1, 2, and 3, respectively. The results for *ResNet-X* represent applying the source pre-trained model directly to target domain without adaptation. Our framework achieves state-of-the-art performance across all three benchmarks compared to other SFDA methods.

7 Conclusions

The present paper provided a thorough analysis of SFDA methods based on contrastive learning, revealing that their effectiveness depends on the degree of overlap among logit groups and the informativeness of augmentations for positive key generation. Building on these insights, we introduced a novel latent augmentation method to address the limitations of existing contrastive SFDA methods. This method utilized the dispersion of latent features around query samples, guided by the source pre-trained model, to reduce logit group overlaps and improve positive key generation. The proposed method, relying on a single InfoNCE loss, demonstrated superior performance compared to existing SFDA methods across various benchmark datasets. Our research contributed to the understanding of applying contrastive learning in the context of SFDA and provides a practical solution to enhance model generalization in the absence of source data.

References

Shai Ben-David, John Blitzer, Koby Crammer, Alex Kulesza, Fernando Pereira, and Jennifer Wortman Vaughan. A theory of learning from different domains. *Machine Learning*, 79(1):151–175, 2010.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International Conference on Machine Learning (ICML)*, pp. 1597–1607. PMLR, 2020.

Jiashun Cheng, Man Li, Jia Li, and Fugee Tsung. Latent augmentation for better graph self-supervised learning. *arXiv preprint arXiv:2206.12933*, 2022.

Tsz-Him Cheung and Dit-Yan Yeung. Modals: Modality-agnostic automated data augmentation in the latent space. In *International Conference on Learning Representations (ICLR)*, 2020.

Shuhao Cui, Shuhui Wang, Junbao Zhuo, Liang Li, Qingming Huang, and Qi Tian. Towards discriminability and diversity: Batch nuclear-norm maximization under label insufficient situations. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 3941–3950, 2020.

Terrance DeVries and Graham W Taylor. Dataset augmentation in feature space. *arXiv preprint arXiv:1702.05538*, 2017.

Alhussein Fawzi, Matej Balog, Aja Huang, Thomas Hubert, Bernardino Romera-Paredes, Mohammadamin Barekatain, Alexander Novikov, Francisco J R Ruiz, Julian Schrittwieser, Grzegorz Swirszcz, et al. Discovering faster matrix multiplication algorithms with reinforcement learning. *Nature*, 610(7930):47–53, 2022.

Yaroslav Ganin and Victor Lempitsky. Unsupervised domain adaptation by backpropagation. In *International Conference on Machine Learning (ICML)*, pp. 1180–1189. PMLR, 2015.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, 2016.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 9729–9738, 2020.

David W Hogg and Dustin Lang. Replacing standard galaxy profiles with mixtures of gaussians. *Publications of the Astronomical Society of the Pacific*, 125(928):719, 2013.

Qianjiang Hu, Xiao Wang, Wei Hu, and Guo-Jun Qi. Adco: Adversarial contrast for efficient learning of unsupervised representations from self-trained negative adversaries. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 1074–1083, 2021.

Jiabo Huang, Qi Dong, Shaogang Gong, and Xiatian Zhu. Unsupervised deep learning by neighbourhood discovery. In *International Conference on Machine Learning (ICML)*, pp. 2849–2858. PMLR, 2019.

Jiaxing Huang, Dayan Guan, Aoran Xiao, and Shijian Lu. Model adaptation: Historical contrastive learning for unsupervised domain adaptation without source data. *Advances in Neural Information Processing Systems (NeurIPS)*, 34:3635–3649, 2021a.

Weiran Huang, Mingyang Yi, and Xuyang Zhao. Towards the generalization of contrastive self-supervised learning. *arXiv preprint arXiv:2111.00743*, 2021b.

Prannay Khosla, Piotr Teterwak, Chen Wang, Aaron Sarna, Yonglong Tian, Phillip Isola, Aaron Maschinot, Ce Liu, and Dilip Krishnan. Supervised contrastive learning. *Advances in Neural Information Processing Systems (NeurIPS)*, 33:18661–18673, 2020.

Varun Kumar, Hadrien Glaude, Cyprien de Lichy, and William Campbell. A closer look at feature space data augmentation for few-shot intent classification. *arXiv preprint arXiv:1910.04176*, 2019.

Rui Li, Qianfen Jiao, Wenming Cao, Hau-San Wong, and Si Wu. Model adaptation: Unsupervised domain adaptation without source data. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 9641–9650, 2020.

Jian Liang, Dapeng Hu, and Jiashi Feng. Do we really need to access the source data? source hypothesis transfer for unsupervised domain adaptation. In *International Conference on Machine Learning (ICML)*, pp. 6028–6039. PMLR, 2020.

Jian Liang, Dapeng Hu, Ran He, and Jiashi Feng. Distill and fine-tune: Effective adaptation from a black-box source model. *arXiv preprint arXiv:2104.01539*, 1(3), 2021a.

Jian Liang, Dapeng Hu, Yunbo Wang, Ran He, and Jiashi Feng. Source data-absent unsupervised domain adaptation through hypothesis transfer and labeling transfer. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2021b.

Xiaofeng Liu, Yang Zou, Lingsheng Kong, Zhihui Diao, Junliang Yan, Jun Wang, Site Li, Ping Jia, and Jane You. Data augmentation via latent space interpolation for image classification. In *2018 24th International Conference on Pattern Recognition (ICPR)*, pp. 728–733. IEEE, 2018.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

X. Peng, B. Usman, N. Kaushik, J. Hoffman, D. Wang, and K. Saenko. Visda: The visual domain adaptation challenge. *arXiv preprint*, pp. arXiv:1710.06924, 2017.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *International Journal of Computer Vision*, 115(3):211–252, 2015.

K. Saenko, B. Kulis, M. Fritz, and T. Darrell. Adapting visual category models to new domains. *In European Conference on Computer Vision (ECCV)*, pp. 213–226, 2010.

David Stutz, Matthias Hein, and Bernt Schiele. Disentangling adversarial robustness and generalization. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 6976–6987, 2019.

Paul Upchurch, Jacob Gardner, Geoff Pleiss, Robert Pless, Noah Snavely, Kavita Bala, and Kilian Weinberger. Deep feature interpolation for image content changes. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 7064–7073, 2017.

Wouter Van Gansbeke, Simon Vandenhende, Stamatios Georgoulis, Marc Proesmans, and Luc Van Gool. Scan: Learning to classify images without labels. In *European Conference on Computer Vision (ECCV)*, pp. 268–285. Springer, 2020.

H. Venkateswara, J. Eusebio, S. Chakraborty, and S. Panchanathan. Deep hashing network for unsupervised domain adaptation. *In the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 5385–5394, 2017.

Feng Wang and Huaping Liu. Understanding the behaviour of contrastive loss. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 2495–2504, 2021.

Yingquan Wu, Krassimir Ianakiev, and Venu Govindaraju. Improved k-nearest neighbor classification. *Pattern recognition*, 35(10):2311–2318, 2002.

Shiqi Yang, Joost van de Weijer, Luis Herranz, Shangling Jui, et al. Exploiting the intrinsic neighborhood structure for source-free domain adaptation. *Advances in Neural Information Processing Systems*, 34: 29393–29405, 2021a.

Shiqi Yang, Yaxing Wang, Joost van de Weijer, Luis Herranz, and Shangling Jui. Generalized source-free domain adaptation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 8978–8987, 2021b.

Shiqi Yang, Yaxing Wang, Kai Wang, Shangling Jui, et al. Attracting and dispersing: A simple approach for source-free domain adaptation. In *Conference on Neural Information Processing Systems (NeurIPS)*, 2022.

Ziyi Zhang, Weikai Chen, Hui Cheng, Zhen Li, Siyuan Li, Liang Lin, and Guanbin Li. Divide and contrast: Source-free domain adaptation via adaptive contrastive learning. In *Conference on Neural Information Processing Systems (NeurIPS)*, 2022.

A   Ablation Studies

A.1   Number of Nearest Neighbors for $\mathbb{N}_K^t$ and $\mathbb{N}_K^s$.

During target adaptation, we distinguish the number of nearest neighbors for $\mathbb{N}_K^t$ determined by the target model as K_t and for $\mathbb{N}_K^s$ determined by the source model as K_s. As discussed earlier, selecting a small value for K_t can enhance clustering but may introduce less smooth predictions, susceptible to noise from inconsistent neighbors. Conversely, choosing a large value of K_t yields smoother predictions but increases the overlap among logit groups. The value of K_s should be determined empirically to find a balance. It should ensure a sufficiently large standard deviation for traversal around $\mathbb{N}_K^s$ while avoiding excessive values that introduce augmentations whose predictions lie in other logit groups. We conduct this ablation study on Office-31 to adapt the model pre-trained on *Amazon* to *Webcam*. As shown in Table 4, our framework is robust to the choices of both K_t and K_s within a reasonable range.

A.2   Standard Deviation of $\mathbb{N}_K^s$.

The impact of K_s on the standard deviation of latent features within $\mathbb{N}_K^s$ is evaluated through experiments on the Office-31 dataset. In this ablation study, a model trained on *Amazon* is adapted to *Webcam*. Table 4 presents the average standard deviations of the features extracted from all samples in *Webcam* using the converged model, with varying values of K_s, under the column **Noise Std**.

Table 4: Ablation study for the number of nearest neighbors, K_t and K_s, on the adaptation performance on Office-31 using ResNet-50.

K_t	K_s	Result	Noise Std.	K_t	K_s	Result	Noise Std.
\multicolumn{8}{c}{**Office-31 Amazon→Webcam**}
2	2	92.7	0.049	3	2	93.6	0.078
2	3	93.2	0.068	**3**	**3**	**94.6**	**0.105**
2	4	93.0	0.059	3	4	94.0	0.085
2	5	92.8	0.052	3	5	93.2	0.071
4	2	92.8	0.058	5	2	92.2	0.032
4	3	93.4	0.062	5	3	93.2	0.068
4	4	93.2	0.056	5	4	93.4	0.070
4	5	93.9	0.078	5	5	93.2	0.072

Temperature for Contrastive Loss. The strength of penalties on negative keys in the contrastive loss is governed by the temperature parameter τ. A small temperature increases the penalization of negative samples, pushing their latent features farther away from those of the query, as highlighted in Wang & Liu (2021). Conversely, a large temperature results in more compact latent features within each logit group, but reduces sensitivity to negative samples in clustering. To empirically evaluate the effect of τ, experiments are conducted on Office-31 with K_s and K_t set to 3, respectively. The results, illustrated in Figure 4, demonstrate the impact of τ on the target classification performance.

Figure 4: Ablation experiments on Office-31 using ResNet-50 to evaluate how classification performance varies with temperature parameter τ.

A.3 Ablation on SiLAN's Impact on InfoNCE Loss.

In this ablation study, we evaluate the effectiveness of SiLAN in improving the *InfoNCE* baseline using the Office-Home dataset. We compare the classification accuracies in the target domain for models trained with and without the use of SiLAN for positive key generation to guide *InfoNCE* contrastive clustering. The results, as shown in Table 5, demonstrate that SiLAN significantly improves the performance of the InfoNCE baseline, highlighting its robustness.

Table 5: Comparing the InfoNCE baseline performance with and without SiLAN on Office-Home using ResNet-50.

Method	Ar $\rightarrow$			Cl $\rightarrow$		
	Cl	Pr	Rw	Ar	Pr	Rw
InfoNCE+K-NNs	55.6	76.4	80.6	66.4	75.2	76.4
InfoNCE+SiLAN (Ours)	**58.2**	**81.2**	**82.5**	**69.8**	**78.6**	**80.3**
Method	Pr $\rightarrow$			Rw $\rightarrow$		
	Ar	Cl	Rw	Ar	Cl	Pr
InfoNCE+K-NNs	66.2	53.8	80.5	72.8	56.8	83.5
InfoNCE+SiLAN (Ours)	**68.4**	**58.6**	**82.5**	**75.6**	**60.8**	**86.1**

B Proof

B.1 Proof of Proposition 1

Proposition 1. The InfoNCE-based contrastive loss, denoted as $\mathcal{L}_{cont}$, serves as an upper bound for achieving two distinct alignments in the output logit space. Formally,

$$\sum_{i=1}^{m} \left(log(m-1) + \frac{||f_t(\mathbf{x}_i) - f_t(\mathbf{x}_i^+)||_2^2}{2\tau} + \frac{1}{m-1} \sum_{j \neq i} -\frac{||f_t(\mathbf{x}_i) - f_t(\mathbf{x}_j^+)||_2^2}{2\tau} \right) \leq \mathcal{L}_{cont},$$

where with τ being a temperature and m being the size of a mini-batch, $\mathcal{L}_{cont}$ is defined as,

$$\mathcal{L}_{cont} = -\sum_{i=1}^{m} log \frac{e^{f_t^\top(\mathbf{x}_i) f_t(\mathbf{x}_i^+)/\tau}}{\sum_{j \neq i} e^{f_t^\top(\mathbf{x}_i) f_t(\mathbf{x}_j^+)/\tau}}.$$

Proof. the InfoNCE loss defined in the output logit space is formulated as:

$$
\begin{aligned}
\mathcal{L}_{cont} &= -\sum_{i=1}^{m} log \frac{e^{f_t^\top(\mathbf{x}_i) f_t(\mathbf{x}_i^+)/\tau}}{\sum_{j \neq i} e^{f_t^\top(\mathbf{x}_i) f_t(\mathbf{x}_j^+)/\tau}} \\
&= \sum_{i=1}^{m} \left((-f_t^\top(\mathbf{x}_i) f_t(\mathbf{x}_i^+)/\tau + log\Big(\frac{m-1}{m-1} \sum_{j \neq i} e^{f_t^\top(\mathbf{x}_i) f_t(\mathbf{x}_j^+)/\tau}\Big) \right).
\end{aligned}
\tag{6}
$$

Then, we apply Jensen's inequality to Equation 6:

$$
\begin{aligned}
\mathcal{L}_{cont} &\geq \sum_{i=1}^{m} \left(-f_t^\top(\mathbf{x}_i) f_t(\mathbf{x}_i^+)/\tau + \frac{1}{m-1} \sum_{j \neq i} log\Big((m-1)\ e^{f_t^\top(\mathbf{x}_i) f_t(\mathbf{x}_j^+)/\tau} \Big) \right) \\
&= \sum_{i=1}^{m} \left(-f_t^\top(\mathbf{x}_i) f_t(\mathbf{x}_i^+)/\tau + \frac{1}{m-1} \sum_{j \neq i} f_t^\top(\mathbf{x}_i) f_t(\mathbf{x}_j^+)/\tau + \frac{1}{m-1} \sum_{j \neq i} log(m-1) \right) \\
&= \sum_{i=1}^{m} \left(log(m-1) - f_t^\top(\mathbf{x}_i) f_t(\mathbf{x}_i^+)/\tau + \frac{1}{m-1} \sum_{j \neq i} f_t^\top(\mathbf{x}_i) f_t(\mathbf{x}_j^+)/\tau \right)
\end{aligned}
\tag{7}
$$

Then, express cosine similarity between two functions in terms of Euclidean distance:

$$
-u^\top v := \frac{||u - v||_2^2}{2} - 1.
\tag{8}
$$

Plugging Eqn 8 into Inequality 7:

$$
\sum_{i=1}^{m} \left(log(m-1) + \frac{||f_t(\mathbf{x}_i) - f_t(\mathbf{x}_i^+)||_2^2}{2\tau} + \frac{1}{m-1} \sum_{j \neq i} -\frac{||f_t(\mathbf{x}_i) - f_t(\mathbf{x}_j^+)||_2^2}{2\tau} \right) \leq \mathcal{L}_{cont},
\tag{9}
$$

End of the proof. □

B.2 Proof of Lemma 2

Lemma 2. If $\mathcal{C}_z^\delta \cap \mathcal{C}_l^\delta = \emptyset$ holds for any $l \neq z$, then the error $\epsilon_{\mathcal{D}_T}$ defined on the groups of logits is upper bounded by:

$$
\epsilon_{\mathcal{D}_T} \leq R_\delta + \sum_{z=1}^{Z} (\mathbb{P}[f_t(\mathbf{x}^+) \neq \mathbf{y}_t, \forall \mathbf{x}^+ \in \mathcal{S}_z^+] + \mathbb{P}[f_t(\mathbf{x}^-) = \mathbf{y}_t, \forall \mathbf{x}^- \in \mathcal{S}_z^-]),
$$

where $R_\delta = \frac{\cup_{z=1}^{Z}(\mathcal{C}_z - \mathcal{C}_z^\delta)}{\cup_{z=1}^{Z} \mathcal{C}_z}$ and $(\mathcal{C}_z - \mathcal{C}_z^\delta)$ may overlap with $(\mathcal{C}_l - \mathcal{C}_l^\delta)$ for any $l \neq z$.

Proof. Based on Huang et al. (2021b), our study refines the theoretical problem of target classification error within the context of contrastive clustering. It decomposes the classification error, focusing on the groups of output logits $\mathcal{C}_z$ where $z \in [1, Z]$, as illustrated in Equation 3.

The first error term can only occur within the overlapping regions (*i.e.,* intersections) between the groups of logits generated through contrastive learning Huang et al. (2021b). Therefore, we have:

$$
\sum_{z=1}^{Z} \mathbb{P}[f_t(\mathbf{x}_t) \neq z, \forall \mathbf{x}_t \in \mathcal{C}_z] \leq \mathbb{P}[\overline{\cup_{z=1}^{Z} \mathcal{C}_z^\delta}].
\tag{10}
$$

The informativeness of the group assignment depends entirely on the informativeness of the transformations of queries when optimizing the contrastive loss. Thus, the upper bound of the second error term can be established as:

$$
\sum_{z=1}^{Z} \mathbb{P}[z \neq \mathbf{y}_t, \forall \mathbf{x}_t \in \mathcal{C}_z] \leq \sum_{z=1}^{Z} \left(\mathbb{P}[f_t(\mathbf{x}^+) \neq \mathbf{y}_t, \forall \mathbf{x}^+ \in \mathcal{S}_z^+] + \mathbb{P}[f_t(\mathbf{x}^-) = \mathbf{y}_t, \forall \mathbf{x}^- \in \mathcal{S}_z^-] \right),
\tag{11}
$$

where the first term represents the error of assigning the logits of positive samples to a group that does not correspond to the ground truth of the query; and the second term denotes the error that occurs when assigning the logits of negative samples to the group to which the query should belong based on its ground truth.

Incorporating Inequalities 10 and 11 into Equation 3, we have:

$$\epsilon_{\mathcal{D}_T} \leq \mathbb{P}[\overline{\cup_{z=1}^{Z} \mathcal{C}_z^{\delta}}] + \sum_{z=1}^{Z} \Big(\mathbb{P}[f_t(\mathbf{x}^+) \neq \mathbf{y}_t, \forall \mathbf{x}^+ \in \mathcal{S}_z^+] + \mathbb{P}[f_t(\mathbf{x}^-) = \mathbf{y}_t, \forall \mathbf{x}^- \in \mathcal{S}_z^-] \Big)$$

$$= 1 - \frac{\cup_{z=1}^{Z} \mathcal{C}_z^{\delta}}{\cup_{z=1}^{Z} \mathcal{C}_z} + \sum_{z=1}^{Z} \Big(\mathbb{P}[f_t(\mathbf{x}^+) \neq \mathbf{y}_t, \forall \mathbf{x}^+ \in \mathcal{S}_z^+] + \mathbb{P}[f_t(\mathbf{x}^-) = \mathbf{y}_t, \forall \mathbf{x}^- \in \mathcal{S}_z^-] \Big).$$

End of the proof. □

B.3 Proof of Proposition 3

Proposition 3. If $\mathcal{C}_z^{\delta} \cap \mathcal{C}_l^{\delta} = \emptyset$ holds for any $z \neq l$, and the assumption that the representation of query samples in the feature space will stay close to their positive augmentations and be far away from their negative samples holds, then $\forall z \neq l$ and $i \neq j$ (where $\mathbf{x}_i \in \mathcal{C}_z^{\delta}$ and $\mathbf{x}_j \in \mathcal{C}_l^{\delta}$), their distance in the latent space is lower bounded when we take the limit $\sigma_{ext}^2 \to 0$ as follows:

$$|G_t^{opt}(\mathbf{x}_i) - G_t^{opt}(\mathbf{x}_j)| \geq 3.1704\sigma,$$

Proof. Inspired by the methodology introduced in Hogg & Lang (2013) for calculating the effective region of a Gaussian beam, we introduce the concept of the Gaussian beam to estimate the effective region of our SiLAN augmentation, whose effect is within a Gaussian profile. Here, all the possible augmented views, originating from a query sample $\mathbf{x}$, center at the mean $\mu_K(\mathbf{x})$ of the neighborhood of the query.

Hence, a radial profile with radius R and centroid $\mu_K(\mathbf{x})$ can be employed to represent the effective region of the potential augmented views from SiLAN:

$$AR(R) = \int_0^R \hat{\mathbf{h}}(r) 2\pi r dr,$$

where $\hat{\mathbf{h}}(r)$ is a radial profile function well-sampled and determined by SiLAN and the feature extractor parameters.

Assuming perfect alignment is achieved after G_t^{opt} converges on the contrastive objective, meaning positive augmentations (keys) lie in the same cluster as the query while negative keys do not lie in the query's cluster, then, as shown in Figure 5, the gap between any two distinct clusters (i.e., $|G_t^{opt}(\mathbf{x}_i) - G_t^{opt}(\mathbf{x}_j)|$) will be determined by the augmentation that belongs to one cluster and is nearest to the other cluster. In summary, under perfect alignment, there is no overlap between the Gaussian profiles of samples from different clusters. Thus, we have:

$$|G_t^{opt}(\mathbf{x}_i) - G_t^{opt}(\mathbf{x}_j)| \geq 2R.$$

Then, considering the extraneous noise with variance σ_{ext}^2, the total variance in the informative radius, with respect to $\mu_k(\mathbf{x})$, out to R can be written as:

$$\sigma_{total}^2(R) = AR(R) + \pi R^2 \sigma_{ext}^2,$$

where πR^2 is the aperture area given R, containing possible augmented views centered at $\mu_k(\mathbf{x})$.

Figure 5: The minimum gap between the non-overlapping regions of two clusters has a lower bound determined by the radius of the Gaussian profile.

The transformation-to-noise ratio T/N, which is similar to the definition of signal-to-noise ratio to quantify Gaussian beam Hogg & Lang (2013), as a function of radius R can be written as:

$$T/N = \frac{AR(R)}{\sqrt{AR(R) + \pi R^2 \sigma_{ext}^2}}$$
$$= \frac{\int_0^R \hat{\mathbf{h}}(r) 2\pi r dr}{\sqrt{\int_0^R \hat{\mathbf{h}}(r) 2\pi r dr + \pi R^2 \sigma_{ext}^2}}.$$

After adding random noise ξ, we have a 2D Gaussian for the source profile centered at $\mu_K(\mathbf{x})$:

$$\hat{\mathbf{h}}(r) = \frac{1}{2\pi\sigma^2} e^{\frac{-r^2}{2\sigma^2}},$$

where σ is the standard deviation of the profile. Then,

$$T/N = \frac{1 - e^{\frac{-R^2}{2\sigma^2}}}{\sqrt{1 - e^{\frac{-R^2}{2\sigma^2}} + \pi R^2 \sigma_{ext}^2}}.$$

Taking $\frac{\partial(T/N)}{\partial R} = 0$ and the limit as $\sigma_{ext}^2 \to 0$, we have the optimum radius $R \approx 1.5852\sigma$.

By incorporating $R \approx 1.5852\sigma$ into the inequality, we have:

$$|G_t^{opt}(\mathbf{x}_i) - G_t^{opt}(\mathbf{x}_j)| \geq 3.1704\sigma,$$

End of the proof. □

B.4 Proof of Lemma 4

Lemma 4. $\forall z \neq l$ and $i \neq j$, if the linear classifier F^{opt} is L-bi-Lipschitz continuous, $\mathcal{C}_z^\delta \cap \mathcal{C}_l^\delta = \emptyset$ holds for any $z \neq l$ where $\mathbf{x}_i \in \mathcal{C}_z^\delta$ and $\mathbf{x}_j \in \mathcal{C}_l^\delta$, and $\sigma_{ext}^2 \to 0$:

$$|f_t^{opt}(\mathbf{x}_i) - f_t^{opt}(\mathbf{x}_j)| \geq \frac{3.1704\sigma}{L},$$

where $f_t^{opt} = F_t^{opt}(G_t^{opt}(\cdot))$.

Proof. As the classifier F is linear and L-bi-Lipschitz continuous, we have:

$$|f_t^{opt}(\mathbf{x}_i) - f_t^{opt}(\mathbf{x}_j)| = |F_t^{opt}(G_t^{opt}(\mathbf{x}_i)) - F_t^{opt}(G_t^{opt}(\mathbf{x}_j))|$$
$$\geq \frac{1}{L}|G_t^{opt}(\mathbf{x}_i) - G_t^{opt}(\mathbf{x}_j)|.$$

From Proposition 3, we have $|G_t^{opt}(\mathbf{x}_i) - G_t^{opt}(\mathbf{x}_j)| \geq 3.1407\sigma$, thus

$$|f_t^{opt}(\mathbf{x}_i) - f_t^{opt}(\mathbf{x}_j)| \geq \frac{1}{L}3.1407\sigma$$

End of the proof. □