Interventional Few-Shot learning for ML Reproducibility Challenge 2020

Łukasz Bala
Warsaw University of Technology and TCL Research Europe
Plac Politechniki 1, 00-661 Warsaw and Wspólna 56 00-684 Warsaw
lukasz3.bala@gmail.com

Reproducibility Summary

Scope of Reproducibility

Main claim of the paper states that by using intervention ($P(Y|do(X))$ in few-shot learning (FSL) problem, we can lower the bias coming from pre-trained models. Moreover the authors claim that they have an evidence of pre-trained models being a confound variable in FSL tasks, meaning that relying too much on pre-trained features in training stage based on support samples may lead to more errors in query set which is significantly different from support set. They provide three different ways of implementing the intervention, based on backdoor adjustment for their Structural Causal Model proposition. These are as follows:

- Feature-wise adjustment
- Class-wise adjustment
- Combined feature and class-wise adjustment

Report is focused on combined adjustment, as it gave best results in almost all of the cases mentioned in the paper.

Due to computing restraints (and some dataset unknowns) we decided to restrict our reproducibility to MTL (meta-transfer learning) and SIB (Synthetic information bottleneck) settings on miniImagenet datasets.

Methodology

Authors provided the code, which can be found in https://github.com/yue-zhongqi/ifsl mini-ImageNet split was taken from https://github.com/hushell/sib_meta_learn for SIB implementation and https://github.com/yaoyao-liu/meta-transfer-learning, as stated by the authors in their repository. We changed some minor elements of the pipeline to enable additional logging and hyperparameter optimisation. Trainings were generally done on 1 RTX2080 GPU, no multi-gpu training was tested. The time needed to train one model varied from 5h for 1-shot Resnet-based training of MTL to about 70h of training for IFSL 5-shot Resnet-based setting.

Results

0.0.1 SIB

For all the runs we used default hyperparameters that were provided in authors' code. We tried to perform hyperparameter optimisation, however for all runs the results were much worse as compared to the original implementation. One can see that for Resnet architecture we achieve results slightly worse than the mean provided by the authors, however, excluding 1-shot IFSL case, they fit in 3σ requirement. However, according to the paper, the most important thing is the performance improvement. Authors report improvement in the range of 1.5-2 percentage points in accuracy on test set, however we observe improvement in the range of 0.5-1 percentage points for all runs. It's worth to note that in all the cases the performance is actually improved.

As compared to the paper, the results from the SIB algorithm on the test set are following:

Setting used	Test acc 1-shot	Test acc 5-shot
Resnet10 Baseline - ours	67.33 ± 0.59	79.01 ± 0.37
Resnet10 IFSL - ours	68.20 ± 0.56	79.93 ± 0.35
Resnet10 Baseline - paper	67.10 ± 0.56	78.88 ± 0.35
Resnet10 IFSL - paper	68.85 ± 0.56	80.32 ± 0.35

Table 1: Table with results for our run of SIB algorithm as compared to those showed in original paper.

0.0.2 MTL

As compared to the paper, the results from the MTL algorithm on the test set are following:

Setting used	Test acc 1-shot	Test acc 5-shot
Resnet10 Baseline - ours	53.01 ± 0.44	72.27 ± 0.36
Resnet10 IFSL - ours	60.16 ± 0.44	78.03 ± 0.34
Resnet10 Baseline - paper	58.49 ± 0.46	75.65 ± 0.35
Resnet10 IFSL - paper	61.17 ± 0.45	78.03 ± 0.33

Table 2: Table with results for our run of MTL algorithm as compared to those showed in original paper.

One can observe that the performance improvement in case of this setting is much higher (around 5 to 7 percentage points of accuracy), although baseline results are significantly lower than those provided by the authors.

What was easy

Running MTL and SIB algorithms was quite easy - for basic run provided instructions were sufficient. The only missing thing were sufficient confurables of paths - one had to look through all the project to change paths in a given file. Including additional logging and hyperparameter search with Weights and Biases framework didn't cause much trouble either.

What was difficult

There was a problem with consistency of miniImagenet dataset download - the main repository stated that one should download it using `https://github.com/hushell/sib_meta_learn`, whereas the subrepository with MAML code stated that on should use the `https://github.com/wyharveychen/CloserLookFewShot`, which required the download of whole ImageNet. Due to missing "novel.hdf5" file I couldn't reproduce results from MAML part of the paper. I described the issue in github repository `https://github.com/yue-zhongqi/ifsl/issues/4`.

The other thing to note is the length of training - it was possible to train the baselines in about 10-30 hours on single RTX2080 depending on basic architecture (Resnet or Wide-Resnet), however introducing intervention increased this time by a factor of 5, with less efficient GPU utilisation present.

Communication with original authors

I tried to communicate with authors only by the repository with official code implementation, however I got no response.

Code and runs

Code: `https://github.com/freefeynman123/ifsl/tree/develop`

Runs: `https://wandb.ai/freefeynman123/mtl_ifsl_mini_imagenet?workspace=user-freefeynman123`

Hyperparameter tuning for baseline: `https://wandb.ai/freefeynman123/mtl_baseline_sweeps?workspace=user-freefeynman123`