SePer: Measure retrieval utility through the lens of semantic perplexity reduction

Lu Dai[1,2], Yijie Xu[2], Jinhui Ye[3,2], Hao Liu[2,1,*], Hui Xiong[2,1,*]
[1]The Hong Kong University of Science and Technology, Hong Kong, China
[2]The Hong Kong University of Science and Technology (Guangzhou), Guangzhou, China
[3]Carnegie Mellon University, Pittsburgh, USA
`ldaiae@connect.ust.hk, yxu409@connect.hkust-gz.edu.cn`
`jinhuiy@andrew.cmu.edu, liuh@ust.hk, xionghui@ust.hk`

Abstract

Large Language Models (LLMs) have demonstrated improved generation performance by incorporating externally retrieved knowledge, a process known as retrieval-augmented generation (RAG). Despite the potential of this approach, existing studies evaluate RAG effectiveness by 1) assessing retrieval and generation components jointly, which obscures retrieval's distinct contribution, or 2) examining retrievers using traditional metrics such as NDCG, which creates a gap in understanding retrieval's true utility in the overall generation process. To address the above limitations, in this work, we introduce an automatic evaluation method that measures retrieval quality through the lens of information gain within the RAG framework. Specifically, we propose *Semantic Perplexity (SePer)*, a metric that captures the LLM's internal belief about the correctness of the retrieved information. We quantify the utility of retrieval by the extent to which it reduces semantic perplexity post-retrieval. Extensive experiments demonstrate that SePer not only aligns closely with human preferences but also offers a more precise and efficient evaluation of retrieval utility across diverse RAG scenarios.

1 Introduction

Retrieval plays a crucial role in satisfying information needs across various interactive systems. With the rapid advancement of Large Language Models (LLMs), retrieval has become deeply interwoven with generation processes Lewis et al. (2020); Guu et al. (2020). This integration not only enhances the accuracy and faithfulness of generated content Chen et al. (2017) but also enables handling more complex applications such as multi-hop reasoning Trivedi et al. (2022a), information seeking Hu et al. (2024), and task completion Yao et al. (2023).

To evaluate and enhance these retrieval-augmented systems Salemi & Zamani (2024), a key challenge lies in measuring the contribution of retrieved information to the overall performance, i.e., the *utility of retrieval*. For instance, a reasoning process may require different pieces of information at different steps to infer the final answer Yang et al. (2018); Talmor & Berant (2018); Gu et al. (2024) as shown in Figure 1. However, most evaluation methods fail to respond to middle-step information, which may not directly match the ground truth text span. Besides, while a RAG workflow or agent task might trigger retrieval multiple times within a single interaction cycle Asai et al. (2023); Jiang et al. (2023), it's difficult to quantify which retrieval effort brings in the most rewards. The lack of evaluator's sensitivity to partial information also results in discontinuous scoring of retrieved information Schaeffer et al. (2023), hampering the development of more efficient retrieval mechanisms.

Unlike the independent evaluation of retrievers, the utility of information retrieval (IR) hinges not only on the quality of the information but also on the prior knowledge of the recipient (e.g., LLM or human), their capacity to integrate external inputs and the way it interacts with the retriever Yoran et al. (2024); Shi et al. (2024). For example, a widely-known fact would bring no knowledge gain in LLMs while it is both relevant and correct. An irrelevant long document may undermine LLM performance even though it does not contain false facts and is harmless in general. Therefore, traditional IR metrics that evaluate the retriever as an independent module cannot reflect its actual helpfulness from a systemic perspective. Recent works also use well-trained LLMs such as GPT-4

---

*Corresponding authors.

as generalizable judges to evaluate different aspects of RAG systems, such as relevancy, correctness, and faithfulness Es et al. (2024). However, these methods are often expensive and inefficient, especially for large-scale datasets and complex RAG workflows.

In this work, we propose the perspective to measure retrieval utility based on the knowledge gain of LLMs Belkin (1980); Belkin et al. (1982a;b). Ideally, an effective measure of information retrieval utility should reflect the satisfaction of the recipient Cooper (1973).

Historically, this approach has been hypothetical because the knowledge gain in real humans is intangible in computation. However, when LLMs act as information recipients, it is possible to estimate the shift in the LLM's knowledge distribution and use it as an indicator of retrieval effectiveness. Along this line, we define *Semantic Perplexity (SePer)*, a sampling-based method to estimate LLM's belief conditioned on an input query. Specifically, we first sample multiple responses and cluster them based on their semantic meanings and re-aggregate their likelihoods following the concept of semantic entropy Kuhn et al. (2023). In this way, we can compute probabilities in the semantic meaning space to obtain a more accurate estimation of the belief distribution, as opposed to vocabulary space.

Figure 1: An illustration of retrieval utility in the multi-step RAG process. Unlike previous methods that only evaluate the final retrieval outcome, our approach assesses the utility of intermediate retrieval steps, even when the information retrieved is insufficient to fully answer the query.

We then compute the cross-entropy between the estimated semantic distribution and ground truth distribution, the exponential form of which is defined as *Semantic Perplexity (SePer)*. By doing so, we make it tangible to estimate the knowledge distribution shift of LLMs and use it to quantify retrieval utility.

In summary, our contributions are three-fold:

- We introduce *SePer*, an assessment method for evaluating retrieval utility based on shifts in LLMs' knowledge distributions. This approach not only aligns closer with human annotations but also is more consistent with inference-time situations.
- We conduct theoretical analysis and extensive experiments to demonstrate that *SePer* provides a more accurate, fine-grained, and efficient evaluation of retrieval utility. It is also generalizable across a broad range of RAG scenarios. Furthermore, we augment the evaluation of various RAG systems with our *SePer* metric for the reference of future research, which is maintained in an anonymous repo in `https://anonymous.4open.science/r/SePer/` at review.
- By utilizing *SePer*, we quantify the retrieval needs across different scenarios. Our findings offer valuable insights for data selection and budget allocation in practical RAG systems.

2 RELATED WORKS

Evaluation of Information Retrieval. Current evaluation of retrieval can be divided into two major categories: Direct content evaluation, which scrutinizes the relevance of the retrieved content itself, and response-based evaluation, which gauges the quality of the responses to reflect on the effectiveness of in-the-middle modules Salemi & Zamani (2024). However, current methods suffer from several short-comings individually. Direct context evaluation treats retrieval as an independent module, which cannot reflect the utility of the receiver model. Response-based methods can be further divided into two categories: model-based and reference-based methods. model-based methods require a knowledgable model, such as human and GPT-4 Liu et al. (2023), to evaluate whether the LLM output is a desired response to a given query. reference-based methods require a reference answer and evaluate the LLM outputs by their matching score to the reference, such as BLEU Papineni et al. (2002), ROUGE Lin (2004), and BERTScore Zhang et al. (2020). However, these methods mainly reflect lexical information and cannot capture the nuanced relationship in semantic meaning. More recent works also leverage LLM judges, such as ARES Saad-Falcon et al. (2024), Prometheus Kim et al. (2024), and Auto-J Li et al. (2024) to assess the distance between reference and output. These LLM-based methods are often more accurate due to the language understanding ability and comprehensive world knowledge of LLMs. However, they are often slow and expensive.

Knowledge Estimation in LLMs. There is a view regarding LLM as a knowledge base Petroni et al. (2019); Geva et al. (2021), and generation can be viewed as retrieval from internal parametric memory Jiang et al. (2020). From this perspective, injecting external knowledge into latent knowledge of LLM via in-context learning is equivalent to fine-tuning Dai et al. (2023). Xie et al. (2022) also explain in-context learning in a Bayesian inference framework and show that prompt influences LLM output by shifting its latent concept distribution. While the internal knowledge latent distribution is unobservable, many research works have managed to estimate from other signals, such as probing model internal states Ribeiro et al. (2016); Adi et al. (2017); Meng et al. (2022) and prompted responses Zhong et al. (2021). Studies also find that uncertainty in LLM is highly correlated with knowledge correctness, i.e., hallucinationKuhn et al. (2023); Cheng et al. (2024), which provides an informative analysis of how knowledgeable LLM is.

3 QUANTIFY RETRIEVAL UTILITY

In this section, we justify our quantification of *retrieval utility* as a computable belief distribution shift in the information recipient model. This approach is grounded in the Bayesian framework, where new evidence updates prior beliefs. However, unlike traditional Bayesian updating that aims to learn model parameters, our focus is on evaluating the utility of the retrieved information in terms of its impact on the model's existing belief. We begin by envisioning several properties that *retrieval utility* should possess. We then formally define *retrieval utility* as reducing belief in ground-truth answers and proving it satisfies the desirable properties. Finally, we instantiate this formulation in the RAG scenario and introduce the algorithm details to compute *SePer* and retrieval utility.

3.1 NOTATIONS

Throughout this paper, we use the following notations. Let M denote a well-trained language model (the *information receiver*) capable of generating answers to queries q. The correct answer set to the query q is denoted by $\mathcal{A} = \{a^*\}$. The retrieved result is denoted by D, where $\mathcal{D}$ is a set of n atomic information d_i, i.e., $\mathcal{D}=\{d_1, d_2, ..., d_n\}$. We denote by $P_M(a)$ the likelihood model M assigns to answer a without retrieval, and by $P_M(a \mid \mathcal{D})$ the likelihood after incorporating $\mathcal{D}$.

3.2 RETRIEVAL UTILITY AS BELIEF REVISION

To align with cognitive intuitions and provide a robust foundation for our conceptualization of retrieval utility $U(M, d)$, we incorporate insights from cognitive information retrieval theories. These theories emphasize the dynamic interplay between information, the user's knowledge state, and the context of information retrieval. Consequently, we envision that an effective retrieval utility metric $U(M, d)$ should satisfy the following properties:

Property 1. *The retrieval utility $U(M, d)$ depends on both the retrieved information d and the information receiver M.*

According to Cooper (1971; 1973); Dervin (1999); Ingwersen (1996), the effectiveness of a retrieval system is contingent upon the user's existing knowledge and the relevance of the retrieved information. This perspective necessitates the introduction of dependence property, which considers both the information receiver and the retrieved content in evaluation.

Property 2 (Zero Utility). *For a given query q, the retrieval utility $U(M, d)$ is zero if the information d retrieved is either irrelevant to q or if the model M already possesses the requisite knowledge to address q effectively without d.*

Belkin et al. (1982a) posits that information is sought to resolve an anomaly in the user's knowledge state. Thus, if the retrieved information does not address this anomaly or if the user's knowledge is already sufficient, the information holds no utility, thereby justifying the zero utility property.

Property 3 (Monotonicity). *Given an information receiver M and an unsatisfied information need q, the retrieval utility $U(M, d)$ is a monotonically increasing function of the relevance of the retrieved information d to q.*

According to Ingwersen (1996), $U(M, d)$ depends on information relevance and the user's cognitive space. With cognitive space fixed, increasing the relevance of retrieved information enhances utility, supporting the Monotonicity property that $U(M, d)$ increases with the relevance of d to q.

Intuitively, the retrieval utility quantifies how much the retrieved information d shifts the model's belief toward the correct answer a^*. Accordingly, we define the retrieval utility as follows:

Definition 1 (Retrieval Utility). *The retrieval utility is defined as the change in the model's belief about the correct answer a^* due to the retrieved information d:*

$$U(M, d) = P_M(a^* \mid d) - P_M(a^*). \tag{1}$$

We demonstrate that Definition 1 satisfies the properties listed above.

Proof of Property 1. The retrieval utility $U(M, d)$ depends explicitly on both d and M through the probabilities $P_M(a^* \mid d)$ and $P_M(a^*)$.

Proof of Property 2. We discuss the two distinct scenarios in the property separately:

1) Irrelevance of d to q: When d is irrelevant, it fails to contribute any new information relevant to the correct answer a^*. Consequently, the conditional probability of a^* given d equals the prior probability, $P_M(a^* \mid d) = P_M(a^*)$. Thus, the utility $U(M, d) = P_M(a^* \mid d) - P_M(a^*) = 0$.

2) Redundancy of d for M: If M already knows a^*, the probability $P_M(a^*)$ is 1. Since probabilities cannot exceed 1, $P_M(a^* \mid d)$ also cannot exceed 1, implying $U(M, d) = P_M(a^* \mid d) - 1 = 0$. Here, since d adds no value, $P_M(a^* \mid d) = P_M(a^*)$, and thus $U(M, d)$ remains 0.

Proof of Property 3. Following Dai et al. (2024), we define the relevance of the retrieved information d to the query q as:

$$\text{Rel}(d, q) = \begin{cases} 1, & \text{if } d \vdash a^*, \\ 0, & \text{otherwise}, \end{cases} \quad (2)$$

where $d \vdash a^*$ denotes that d entails a^*.

When $\text{Rel}(d, q) = 0$, according to Property 2, the retrieval utility $U(M, d) = 0$.

When $\text{Rel}(d, q) = 1$, since $d \vdash a^*$, assuming the receiver M can effectively utilize d, we have $P_M(a^* \mid d) > P_M(a^*)$. Therefore, the retrieval utility is positive:

$$U(M, d) = P_M(a^* \mid d) - P_M(a^*) > 0. \quad (3)$$

Thus, as $\text{Rel}(d, q)$ increases from 0 to 1, $U(M, d)$ increases from 0 to a positive value, demonstrating the monotonicity property under this binary definition of relevance.

For more general cases where $\text{Rel}(d, q)$ is ordinal or continuous — for example, in multi-step reasoning where d partially contributes to a^* and $0 < \text{Rel}(d, q) < 1$ — we empirically demonstrate that our belief change based utility metric exhibits a significantly higher correlation with human-annotated context utility compared to other methods in Table 2.

Figure 2: *SePer*: Estimating retrieval utility in multi-step retrieval-augmented generation (RAG) processes by measuring changes in model belief. *SePer* consists of four key steps: ① Probing the model's belief through Monte-Carlo Sampling, where the LM generates N responses to the query using a temperature parameter. ② Estimating the belief distribution over possible answers using semantic clustering. ③ Calculating the model's semantic perplexity by comparing the estimated belief distribution with the ground truth distribution. ④ Assessing the unity of partial retrieval by measuring the change in semantic perplexity before and after retrieval.

3.3 BELIEF ESTIMATION THROUGH SAMPLING

Estimating model belief $P_M(a)$ is challenging due to the vast output space of the language model. Moreover, the model's outputs are in the vocabulary space, whereas our belief probabilities are defined over the semantic space. For example, "*Peter*", "*Peter Bergmann*" and "*Ludwig Planck*" are equally correct answers to the question "*Who did Einstein work with in 1933?*" and should be considered the same event in the probabilistic space Kuhn et al. (2023).

Extending semantic entropy Farquhar et al. (2024), we calculate the model's likelihood on a^* based on the distribution of semantic meanings.

Definition 2 (Semantic Equivalence). *Two texts x and y are semantically equivalent, denoted $x \equiv y$, if $x \vdash y$ and $y \vdash x$, where $\vdash$ means entailment.*

Practically, the entailment relationship is computed from a function $E : \mathcal{X} \times \mathcal{X} \to [0, 1]$, where $\mathcal{X}$ is the set of all possible texts. Given two texts x and y, $E(x, y)$ outputs a score representing the degree to which x entails y. The entailment relation holds if $E(x, y)$ exceeds a predefined threshold τ. We also experimentally demonstrate that using the entailment model to define semantic equivalence Yao & Barbosa (2024) aligns much more accurately with human-annotated semantic equivalence, compared to traditional lexical-matching methods and trained LLM-judges, almost on par with GPT-4 evaluation. Results are shown in Figure 2.

Given a set of responses $\{r_i\}$, *semantic clustering* is the process of grouping responses into clusters $\mathcal{C} = \{C_k\}$ such that all responses within a cluster are semantically equivalent:

$$C_k = \{r_i \mid r_i \equiv r_j, \forall r_j \in C_k\}. \tag{4}$$

The original semantic entropy makes the entropy computable in the sampled distribution:

$$\text{SE}(q) = -\sum_c \left(\left(\sum_{r \in c} p(r \mid q) \right) \log \left[\sum_{r \in c} p(r \mid q) \right] \right) \approx \sum_{i=1}^{|\mathcal{C}|} -|C_i|^{-1} \log p(C_i \mid q). \tag{5}$$

Since the first equation is not computable due to infinite sentence space, the expectation is estimated using Monte-Carlo integration over sampled semantic cluster $\mathcal{C}$. By *the Law of Large Numbers*, as the number of samples $N \to \infty$, the frequency of responses converges to the model's belief distribution. We use similar approximation in make *SePer* computable. But unlike semantic entropy Farquhar et al. (2024), we estimate model belief shift on the reference answer instead of estimating the output uncertainty in LLM for the original uses, such as hallucination detection. We will detail the computation of *SePer* in the following part.

3.4 Δ*SePer*: SEMANTIC PERPLEXITY REDUCTION IN RAG

To estimate model belief on reference answers $P(\{a^*\})$, instead of computing the entropy of semantic clusters, we further determine which clusters are semantically equivalent to any of the a in $\{a^*\}$. For clarity, we begin with the special case where there is only one $a*$.

Thus, $P(a^*)$ is calculated by:

$$P(a^* \mid q) = \sum_c k(c, a^*) \sum_{r \in c} p(r \mid q), \tag{6}$$

where $r = \{t_1, t_2, \ldots, t_{i-1}\}$ and $p(r \mid q)$ is the output sequence likelihood from M:

$$p(r \mid q) = \prod_{i=1}^{|r|} p(t_i \mid t_1, t_2, \ldots, t_{i-1}, q). \tag{7}$$

$k(c, a^*)$ is a kernel function to measure the distance between the semantic meaning of c and a^*. We tested two different implementations of $k(c, a^*)$: entailment model score $E(x, y)$ and Indicator function $I(c, a^*)$:

$$I(c, a^*) = \begin{cases} 1, & \text{if } c \equiv a^*, \\ 0, & \text{otherwise.} \end{cases} \tag{8}$$

Finally, the *SePer* score is calculated by:

$$SePer_M(q, a^*) = P_M(a^* \mid q) \approx \sum_{C_i \in \mathcal{C}} k(c, a^*) p(C_i \mid q). \tag{9}$$

Similar to 5, the right approximate equation is an unbiased estimator of the left one. This naturally extends to the general cases where there are multiple ground-truth a^* provided:

$$SePer_M(q, \mathcal{A}) \approx \frac{1}{|\mathcal{A}|} \sum_{a^* \in \mathcal{A}} \left[\sum_{C_i \in \mathcal{C}} k(c, a^*) p(C_i \mid q) \right]. \tag{10}$$

Algorithm 1 *SePer* & Δ*SePer*

Require: Model M, reference answer a^*, entailment model E, threshold τ, number of samples N.

1: Sample responses: $r_i \sim P_M(r)$, for $i = 1, \ldots, N$.
2: Compute likelihoods: $\ell_i = P_M(r_i)$.
3: *SePer*$_H$:   *SePer*$_S$:

    1. Semantic clustering: Group responses r_j into clusters   **1.** Compute entailment scores:
       $\mathcal{C} = \{C_k\}$ such that $E(r_i, r_j) \geq \tau$ within each cluster. $k_i = E(r_i, a^*)$.
    2. Identify C_{a^*}: matching reference answer with semantic   **2.** Compute soft belief:
       cluster, where $\forall r \in C_{a^*}, r \equiv a^*$. $P_M(a^*) = \sum_{i=1}^{N} \ell_i \cdot k_i$.
    3. Compute semantic perplexity: $P_M(a^*) = \sum_{r_i \in C_{a^*}} \ell_i$.
4: Repeat steps with retrieved information C to obtain $P_M(a^* \mid C)$.
5: Compute utility: $U(M, C) = \Delta$*SePer* $= P_M(a^* \mid C) - P_M(a^*)$.

Lastly, retrieval utility $U(M, C)$ is calculated by Δ*SePer*, i.e., semantic perplexity reduction:

$$U(M, C) = \Delta\textit{SePer} = P_M(a^* \mid q, d) - P_M(a^* \mid q). \tag{11}$$

Through Monte-Carlo sampling and semantic clustering, Δ*SePer* quantifies the extent to which receiver M's belief shifts towards ground-truth answer after retrieval, i.e., how much beneficial information gain the information piece d brought to the model. Based on two different kernel function choices, we implemented *SePer*$_S$ and *SePer*$_H$ separately. The incorporation of kernel-based soft matching provides a more nuanced and continuous evaluation Nikitin et al. (2024). The *SePer* and Δ*SePer* algorithms are fully described in Algorithm 1.

4 EVALUATION OF *SePer*

In this section, we conducted experiments to prove the validity and reliability of the proposed *SePer* metric Xiao et al. (2023); Jacobs & Wallach (2021); Wagner et al. (2021). For validity testing, we first show experiments in Section 4.1.1 to prove that *SePer* is a more reliable and fine-grained indicator for reference-based response evaluation and then demonstrate its better correlation and alignments with human judgments about retrieval utility in Section 4.1.2. For reliability testing, we test the robustness of the performance of *SePer* on different aspects, including varying datasets, repeated computation, and the number of samples used. Results in Section 4.2 show that under our default setting, *SePer* achieved high reliability and stability with less cost in time and money. We also add ablation results about more hyperparameters in A to prove the robustness of *SePer*.

4.1 VALIDITY OF *SePer*

4.1.1 VALIDITY OF SEMANTIC-BASED ANSWER SCORING

First, we evaluate the basic component of computing *SePer*, i.e., using the entailment model to calculate the semantic similarity between the generated answer and the ground-truth answer.

Datasets. We use EVOUNA Wang et al. (2024), a Question Answering (QA) benchmark, to evaluate the reliability of QA evaluators. Based on Natural Questions (NQ) Kwiatkowski et al. (2019) and TriviaQA Joshi et al. (2017), EVOUNA augmented the datasets with LLM-generated responses and asked humans to annotate whether a response is semantically equivalent to the golden answer.

Baselines. We include two types of baselines: Matching-based evaluation, such as lexical match and BERTScore, and LLM judge evaluators, such as Auto-J and Prometheus.

Model. We use the `deberta-v2-xlarge-mnli` He et al. (2021) model fine-tuned on the MNLI dataset to assess the entailment relationship between two text pairs following the setting of Kuhn et al. (2023), which is far more efficient than API-based entailment judgment Yao & Barbosa (2024) without a significant performance drop. In our implementation, we further leverage the entailment score to get a probabilistic estimation of the likelihood of semantic equivalence.

Results. As shown in Table 1, the NLI-based module in *SePer* demonstrates significantly higher alignment with human judgment compared to traditional matching-based response evaluation by surpassing the baselines by $2\% \sim 6\%$ F1-score across various generators and datasets. Notably, it is close to or minorly surpasses the response evaluation performance of GPT-4 in this benchmark. BERTScore, while capturing semantic meaning, may fail to capture the relationships in QA tasks. At the same time, trained LLM judges did not demonstrate an edge over traditional methods on this

benchmark, with reference-free judges falling far behind reference-based methods. These results show that computing the semantic-equivalence score based on the entailment model is both an efficient and reliable method. Its high correlation score in matching responses and answers also set a solid step for the next stage of computation of *SePer*.

Evaluator	Natural Questions					TriviaQA				
	DPR-FiD F1/Acc	InstructGPT F1/Acc	ChatGPT F1/Acc	GPT-4 F1/Acc	BingChat F1/Acc	DPR-FiD F1/Acc	InstructGPT F1/Acc	ChatGPT F1/Acc	GPT-4 F1/Acc	BingChat F1/Acc
Matching-based										
Lexical Match	92.0/89.7	86.9/84.8	85.0/80.3	87.6/82.5	87.8/82.3	91.8/94.7	94.8/92.3	95.2/92.3	94.8/91.1	94.1/89.8
BERTScore	83.5/75.1	77.6/69.5	81.2/72.8	84.3/76.0	77.5/67.5	75.1/65.5	84.1/75.7	88.4/80.8	90.5/93.5	88.3/80.4
Entail (*SePer*)	96.6/95.3	92.0/90.1	91.2/87.8	93.1/89.7	91.4/87.0	97.6/96.1	97.5/96.0	97.9/96.4	98.5/97.2	96.2/93.2
LLM-as-a-Judge										
Auto-J	57.8/54.2	71.9/62.1	76.4/66.5	75.4/65.1	72.8/62.2	76.3/66.7	80.8/71.5	81.4/71.3	80.4/68.7	83.0/73.0
Prometheus	83.8/77.8	81.1/70.5	86.4/77.7	89.3/81.5	89.5/82.3	89.4/83.1	90.0/83.2	93.0/87.7	94.7/90.2	95.4/91.8
Human-level										
GPT-4	96.0/94.5	93.2/91.0	93.7/90.6	95.1/92.0	94.7/91.4	98.3/97.3	98.4/97.5	98.5/97.5	98.8/97.8	98.1/96.5
Human	97.4/96.3	97.8/96.8	96.5/95.6	97.9/96.6	97.2/95.5	100/100	99.6/99.4	99.2/98.8	99.2/99.8	99.9/99.8

Table 1: Correlation of entailment-based answer scoring (*SePer*) with human answer scoring. We use the F1-score and Accuracy to measure the degree of correlation. As shown in the table, *SePer* achieves the highest accuracy in answer scoring and is on par with human-level judgments.

4.1.2 VALIDITY OF $\Delta SePer$ ON QUANTIFYING RETRIEVAL UTILITY

Secondly, we prove that using $\Delta SePer$ in measuring retrieval utility is highly correlated with human annotations with a larger margin than baseline methods. We test our method in two different settings: 1) Simple question-answering tasks, which generally require a single document for answer generation, and 2) reasoning-involved question answering, which requires collecting and integrating several steps of partial information to correctly solve a problem.

Datasets. In the simple open QA setting, we use three representative datasets: NQ, MS MARCO Bajaj et al. (2016), and SQuAD Rajpurkar et al. (2016). Each of these datasets has annotations of questions, golden answers, and human-annotated positive/negative passages. Since answering the question requires only one passage, we first attach the positive passages with a utility score of 1 and the negative passages with a utility score of 0. Since positive passages can not bring utility to LLMs based on their known knowledge, we then filter out those cases in which LLM has already succeeded in each dataset to eliminate the baseline effect. Through this preprocessing, we got the utility label on passages from real-human annotations. In the reasoning-involved QA setting, we use four typical Multihop-QA datasets, 2WikiMultihopQA Ho et al. (2020), HotpotQA Yang et al. (2018), IIRC Ferguson et al. (2020), and MuSiQue Trivedi et al. (2022b), which contains annotations of positive passages in the middle steps of a reasoning chain. Since each step only contains in-complete information pieces, we make a natural assumption that the overall information utility is uniformly assigned to each step and thus attach a ground-truth utility score of $1/n_{\text{steps}}$ for each middle-step passage. While not perfect, we find this assumption reasonable since these datasets are mostly collected by means of question composition, as detailed in Appendix I.

Metrics. We use the Pearson correlation score to measure the correlation between our $\Delta SePer$ Score and Ground-Truth utility score. We use t-test to assess the significance of the observed correlation coefficient, with statistic t computed with $t = r \times \sqrt{(n-2)/(1-r^2)}$. We then map the t to p-value using the Student's t-distribution table. As a result, all the Pearson correlation coefficients in Table 2 have corresponding p-values less than 0.01, providing strong evidence against the null hypothesis and indicating a high level of statistical significance.

Baselines. We choose various methods that can be used to estimate the LLM's knowledge of a question. Lexical-matching-based methods include EM, ROUGE, and BLEU, which measure the response correctness score through matching text spans. BERTScore matches predicted answers and ground truth through embedding similarity. Another category of baselines is uncertainty measures, such as perplexity, entropy, and semantic entropy. Unlike the matching-based method, these uncertainty measures do not require golden answers in computation. While they are not directly defined on the correctness dimension, we include them because recent literature also shows that in calibrated LLMs, uncertainty is correlated with knowledge capabilitiesFarquhar et al. (2024); Cheng et al. (2024). We also included LLM-judges similar to Table 1.

Implementation details. We use the same semantic equivalence scoring algorithm as tested in 1. For each query, we sample $k = 10$ times and obtain the response along with sequence likelihood. All baseline methods are sampled at the same time, and the final score comes from mean aggregation. In Table 2, we use `Llama-2-7b-chat` as the generator LLM. We also tested other sizes and showed a tendency results in Figure 4.

Results. We show the result in Table 2. $\Delta SePer$ scores show significant improvement on other metrics. Specifically, $\Delta SePer_S$ has a marginal improvement on $\Delta SePer_H$ across different datasets, which may indicate that soft probability mass assignment can capture more nuanced meanings, especially in free-formgenerations. Comparing Simple and Reasoning QA tasks, the scores of almost different metrics are all lower by $\sim 10\%$, indicating the challenging nature of reasoning-based QA. Even though $\Delta SePer$ can achieve a Pearson correlation score greater than 0.5 across almost all datasets, Showing its great potential to act as an automatic evaluation metric for retrieval utility.

Method	Simple			Reasoning			
	NQ	MS MARCO	SQuAD	2WikiMHQA	HotpotQA	IIRC	MuSiQue
Exact Match	0.454	0.197	0.422	0.307	0.392	0.303	0.298
ROUGE	0.691	0.443	0.808	0.482	0.578	0.399	0.489
BLEU	0.188	0.353	0.298	0.197	0.206	0.126	0.163
BERTScore	0.592	0.322	0.564	0.361	0.451	0.197	0.392
Perplexity	0.008	0.005	0.024	0.005	0.013	0.009	0.011
Entropy	0.431	0.142	0.557	0.226	0.276	0.292	0.203
Semantic Entropy	0.491	0.171	0.621	0.262	0.339	0.342	0.258
Auto-J	0.421	0.022	0.406	0.243	0.183	0.096	0.169
Prometheus	0.639	0.307	0.707	0.502	0.508	0.383	0.464
$\Delta SePer_H$	0.752	0.512	0.904	0.559	0.634	0.446	0.543
$\Delta SePer_S$	**0.769**	**0.533**	**0.905**	**0.584**	**0.660**	**0.461**	**0.559**

Table 2: Pearson correlation between different evaluation metrics and ground-truth retrieval utility with p-value < 0.01 for $\Delta SePer$. As shown in the table, both $\Delta SePer_H$ and $\Delta SePer_S$ significantly outperform other baselines in measuring retrieval utility in simple and reasoning-type tasks, with the soft version leading an edge.

4.2 RELIABILITY OF *SePer*

We further test the reliability of *SePer* from different aspects, i.e., whether *SePer* produces consistent and stable evaluation across different datasets, random repetitions, and number of samples.

We tested *SePer*-H and *SePer*-S with different numbers of samples across four datasets: NQ, HotpotQA, MS MARCO, and SQuAD, and the results are shown in Figure 3. We choose the number of sampled responses n at $\{1, 5, 10, 15, 20\}$ for ablation purposes, extending the default choice of $n = 10$. We find that the conclusion is consistent in different datasets: As n increases, the correlation of *SePer* with ground truth also increases, indicating better accuracy. Besides, the variance generally becomes smaller as n increases, indicating better robustness. Generally, the elbow point appears at $n = 5$ to $n = 10$, with $n = 10$ having less than 1% performance drop compared to $n = 20$. Thus, using $n = 10$ in *SePer* computation would be an effective choice.

Figure 3: Influence of the number of samples and repeated calculation of *SePer* on four datasets.

The shadow area and error bar in Fig.3 shows that the fluctuation of *SePer*'s quality among repeated calculations is less than 1%, indicating high stability according to measurement theory. More experiments and ablation about the robustness of *SePer* can be found in Appendix A.

5 FINDINGS BASED ON *SePer*

In this section, we apply *SePer* to different modules in the RAG pipeline and exhibit our findings through the new lens of *SePer*. In general, RAG pipelines use techniques such as reranker, refiner, and control flow to improve generation quality. Through the unique lens of *SePer*, we can get a more fine-grained and accurate view of how these factors affect the overall performance of RAG. We benchmark current RAG workflows in Appendix C. A brief introduction of these components in RAG and experiment details can be found in Appendix D.

Figure 4: Results about applying *SePer* on different RAG settings. The ■ and ■ areas represent the positive and negative differences between *SePer* for generation w/ and w/o retrieval, respectively. The solid blue line indicates Δ*SePer*, i.e., the utility of retrieval. The red dashed line indicates the zero point of the differences.

5.1 EXPERIMENT GOALS

We aim to address the following main research questions (RQs) through the lens of *SePer*. RQ1-4 aims to observe the utility of RAG components on the final performance, including retrieval, reranker, and prompt compression. Specifically, RQ1 and RQ2 look closer at the retrieval utility and what impact on RAG can be brought by varying numbers of retrieved items and the choice of generator models of different sizes. These RQs are all designed to provide evidence and guidance on designing more efficient and effective RAG pipelines:

- **RQ1:** What is the utility of retrieval on LLMs of different sizes?
- **RQ2:** How does the number of retrieved items influence overall RAG performance?
- **RQ3:** How do different prompt compression methods influence the overall RAG performance?
- **RQ4:** How does the reranking phase influence the overall RAG performance?

5.2 RETRIEVAL UTILITY FOR GENERATOR MODELS OF VARYING SIZES (RQ1)

In figure 4, we evaluate how LLMs of different sizes can benefit from retrieval. Our experiments are conducted on both simple QA and multi-hop QA datasets, and more implementation details can be found in Appendix D. We observed that 1) for both scenarios of QA tasks, models of different sizes generally make positive use of retrieved information to produce better answers for most datasets. An exception is MS MARCO, which we attribute to its corpus inconsistency with the Wikipedia corpus we used. 2) According to our experiments, medium-size models benefit the most from retrieved information. This could be due to 1. its weaker initial knowledge without retrieval and 2. its better ability to absorb retrieved in-context information as compared to smaller models.

5.3 UTILITY OF DIFFERENT NUMBERS OF RETRIEVED ITEMS (RQ2)

The number of in-context retrieved items used in prompts, noted as k, can significantly impact the model's generation results. Figure 5(a) shows the experiments about the impact of k on the overall RAG performance, with k set at $\{1, 5, 10\}$. For most datasets, retrieving more information progressively positively affects answering questions. However, increasing the number of in-context items from 5 to 10 only brings marginal improvement and sometimes even slightly hurts the generation performance, as in the AmbigQA dataset. This might be due to the extra noise brought by an increasing number of retrieved documents.

Figure 5: Differences in *SePer* across various retrieval and generation settings. Panel (a) illustrates the differences in *SePer* between generations w/ and w/o retrieval, analyzed under different retrieved items. Panel (b) highlights the effect of prompt compression methods on *SePer* differences compared to generation w/o retrieval. Panel (c) examines the impact of the reranker on *SePer* differences relative to generation w/o retrieval.

5.4 UTILITY OF PROMPT COMPRESSION METHODS (RQ3)

The prompt compression module is used to reduce the prompt length to lower the inference cost while preserving or facilitating the RAG performance.

Figure 5(b) illustrates the results of our experiments. We test the utility of two major prompt compression works, selective-context Li et al. (2023) and LongLLMLingua Jiang et al. (2024). Although both prompt compression methods slightly reduce *SePer* compared to no compression, both methods can reduce the prompt by about 40%, thus lowering the inference costs to about one-third of the original. Additionally, we note that the LongLLMLingua maintains a relatively higher *SePer* than selective-context, becoming a preferred choice for balancing performance and inference cost. More details about prompt compression methods can be found in Appendix D.1.

5.5 UTILITY OF RERANKER (RQ4)

While retrieval can quickly gather candidate items from large document collections to aid generation, it often lacks precision in small k, which leaves out important information and brings in many noises. To this end, the reranker module is introduced to the RAG pipeline, which not only selects relevant documents into prompt contexts with better accuracy but also re-arranges them in the best order for overall generation quality Liu et al. (2024). More details about the lines of work on reranker can be found in Appendix D.2.

Figure 5(c) shows experimental results comparing Δ*SePer* with and without rerankers from the implementation of `bge-reranker-large` Xiao et al. (2024). We set top-k values of 20 for retrieved items and 5 for reranked items in reranked scenarios while keeping a constant top-k of 5 in non-reranked scenarios. Results from Δ*SePer* are consistent with the conclusions of works in the field that reranker, in general, brings significant improvement to the RAG pipeline by removing noises and reordering contexts. However, in NQ and AmbigQA (which are also derived from NQ), it seems that the reranking process has a negative impact on answer quality. This might indicate that simply putting more relevant contexts at an earlier position may not be the best strategy. How the ordering of contexts influences the final generation results is open for exploration.

6 DISCUSSION

This study introduces Semantic Perplexity (*SePer*) and then Δ*SePer*, a novel metric that evaluates the utility of information retrieval by measuring the knowledge gain in large language models (LLMs). *SePer* provides a more nuanced understanding of retrieval effectiveness beyond mere accuracy, aligning closer with real-world inference needs.

Our findings demonstrate that Δ*SePer* can effectively quantify retrieval needs across various scenarios, aiding in data selection and resource allocation in RAG systems. This metric can enhance the optimization of RAG systems for both efficiency and effectiveness, promising improved performance in complex AI applications. Future work will focus on extending *SePer*'s applicability to more diverse and challenging datasets.

REFERENCES

Yossi Adi, Einat Kermany, Yonatan Belinkov, Ofer Lavi, and Yoav Goldberg. Fine-grained analysis of sentence embeddings using auxiliary prediction tasks. In *International Conference on Learning Representations (ICLR)*, 2017.

Akari Asai, Zeqiu Wu, Yizhong Wang, Avirup Sil, and Hannaneh Hajishirzi. Self-rag: Learning to retrieve, generate, and critique through self-reflection. In *The Twelfth International Conference on Learning Representations (ICLR)*, 2023.

Payal Bajaj, Daniel Campos, Nick Craswell, Li Deng, Jianfeng Gao, Xiaodong Liu, Rangan Majumder, Andrew McNamara, Bhaskar Mitra, Tri Nguyen, et al. Ms marco: A human generated machine reading comprehension dataset. *arXiv preprint arXiv:1611.09268*, 2016.

N. J. Belkin. Anomalous states of knowledge as a basis for information retrieval. *The Canadian Journal of Information Science*, 1980.

N. J. Belkin, R. N. Oddy, and H. M. Brooks. Ask for information retrieval: Part i. background and theory. *Journal of Documentation*, 1982a.

N. J. Belkin, R. N. Oddy, and H. M. Brooks. Ask for information retrieval: Part ii. results of a design study. *Journal of Documentation*, 1982b.

Danqi Chen, Adam Fisch, Jason Weston, and Antoine Bordes. Reading Wikipedia to answer open-domain questions. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (ACL)*, 2017.

Qinyuan Cheng, Tianxiang Sun, Xiangyang Liu, Wenwei Zhang, Zhangyue Yin, Shimin Li, Linyang Li, Zhengfu He, Kai Chen, and Xipeng Qiu. Can ai assistants know what they don't know? In *Forty-first International Conference on Machine Learning (ICML)*, 2024.

Christopher Clark, Kenton Lee, Ming-Wei Chang, Tom Kwiatkowski, Michael Collins, and Kristina Toutanova. BoolQ: Exploring the surprising difficulty of natural yes/no questions. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers) (NAACL)*, 2019.

William S Cooper. A definition of relevance for information retrieval. *Information Storage and Retrieval*, 1971.

William S Cooper. On selecting a measure of retrieval effectiveness. *Journal of the American Society for Information Science*, 1973.

Damai Dai, Yutao Sun, Li Dong, Yaru Hao, Shuming Ma, Zhifang Sui, and Furu Wei. Why can gpt learn in-context? language models secretly perform gradient descent as meta-optimizers. In *Findings of the Association for Computational Linguistics: ACL 2023*, 2023.

Lu Dai, Hao Liu, and Hui Xiong. Improve dense passage retrieval with entailment tuning. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2024.

Brenda Dervin. On studying information seeking methodologically: the implications of connecting metatheory to method. *Information Processing & Management*, 1999.

Matthijs Douze, Alexandr Guzhva, Chengqi Deng, Jeff Johnson, Gergely Szilvasy, Pierre-Emmanuel Mazaré, Maria Lomeli, Lucas Hosseini, and Hervé Jégou. The faiss library. *arXiv preprint arXiv:2401.08281*, 2024.

Shahul Es, Jithin James, Luis Espinosa Anke, and Steven Schockaert. Ragas: Automated evaluation of retrieval augmented generation. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics: System Demonstrations (EACL)*, 2024.

Sebastian Farquhar, Jannik Kossen, Lorenz Kuhn, and Yarin Gal. Detecting hallucinations in large language models using semantic entropy. *Nature*, 2024.

James Ferguson, Matt Gardner, Hannaneh Hajishirzi, Tushar Khot, and Pradeep Dasigi. Iirc: A dataset of incomplete information reading comprehension questions. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2020.

Yunfan Gao, Yun Xiong, Xinyu Gao, Kangxiang Jia, Jinliu Pan, Yuxi Bi, Yi Dai, Jiawei Sun, Meng Wang, and Haofen Wang. Retrieval-augmented generation for large language models: A survey. *arXiv preprint arXiv:2312.10997*, 2023.

Mor Geva, Roei Schuster, Jonathan Berant, and Omer Levy. Transformer feed-forward layers are key-value memories. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2021.

Zhouhong Gu, Lin Zhang, Xiaoxuan Zhu, Jiangjie Chen, Wenhao Huang, Yikai Zhang, Shusen Wang, Zheyu Ye, Yan Gao, Hongwei Feng, and Yanghua Xiao. DetectBench: Can large language model detect and piece together implicit evidence? In *Findings of the Association for Computational Linguistics: EMNLP 2024 (ACL)*, 2024.

Kelvin Guu, Kenton Lee, Zora Tung, Panupong Pasupat, and Mingwei Chang. Retrieval augmented language model pre-training. In *International Conference on Machine Learning (ICML)*, 2020.

Hiroaki Hayashi, Prashant Budania, Peng Wang, Chris Ackerson, Raj Neervannan, and Graham Neubig. Wikiasp: A dataset for multi-domain aspect-based summarization. *Transactions of the Association for Computational Linguistics (TACL)*, 2021.

Pengcheng He, Xiaodong Liu, Jianfeng Gao, and Weizhu Chen. Deberta: Decoding-enhanced bert with disentangled attention. In *International Conference on Learning Representations (ICLR)*, 2021.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. In *International Conference on Learning Representations (ICLR)*, 2021.

Xanh Ho, Anh-Khoa Duong Nguyen, Saku Sugawara, and Akiko Aizawa. Constructing a multi-hop QA dataset for comprehensive evaluation of reasoning steps. In *Proceedings of the 28th International Conference on Computational Linguistics (COLING)*, 2020.

Ziniu Hu, Ahmet Iscen, Chen Sun, Kai-Wei Chang, Yizhou Sun, David Ross, Cordelia Schmid, and Alireza Fathi. Avis: Autonomous visual information seeking with large language model agent. *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

Peter Ingwersen. Cognitive perspectives of information retrieval interaction: elements of a cognitive ir theory. *Journal of Documentation*, 1996.

Gautier Izacard, Mathilde Caron, Lucas Hosseini, Sebastian Riedel, Piotr Bojanowski, Armand Joulin, and Edouard Grave. Unsupervised dense information retrieval with contrastive learning. *Transactions on Machine Learning Research (TMLR)*, 2022.

Abigail Z Jacobs and Hanna Wallach. Measurement and fairness. In *Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency*, 2021.

Huiqiang Jiang, Qianhui Wu, Xufang Luo, Dongsheng Li, Chin-Yew Lin, Yuqing Yang, and Lili Qiu. LongLLMLingua: Accelerating and enhancing LLMs in long context scenarios via prompt compression. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers) (ACL)*, 2024.

Zhengbao Jiang, Frank F Xu, Jun Araki, and Graham Neubig. How can we know what language models know? *Transactions of the Association for Computational Linguistics (TACL)*, 2020.

Zhengbao Jiang, Frank F Xu, Luyu Gao, Zhiqing Sun, Qian Liu, Jane Dwivedi-Yu, Yiming Yang, Jamie Callan, and Graham Neubig. Active retrieval augmented generation. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2023.

Jiajie Jin, Yutao Zhu, Xinyu Yang, Chenghao Zhang, and Zhicheng Dou. Flashrag: A modular toolkit for efficient retrieval-augmented generation research. *CoRR*, abs/2405.13576, 2024.

Jeff Johnson, Matthijs Douze, and Hervé Jégou. Billion-scale similarity search with GPUs. *IEEE Transactions on Big Data (TBD)*, 2019.

Mandar Joshi, Eunsol Choi, Daniel S Weld, and Luke Zettlemoyer. Triviaqa: A large scale distantly supervised challenge dataset for reading comprehension. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers) (ACL)*, 2017.

Ashwin Kalyan, Abhinav Kumar, Arjun Chandrasekaran, Ashish Sabharwal, and Peter Clark. How much coffee was consumed during EMNLP 2019? fermi problems: A new reasoning challenge for AI. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2021.

Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. Dense passage retrieval for open-domain question answering. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2020.

Seungone Kim, Jamin Shin, Yejin Cho, Joel Jang, Shayne Longpre, Hwaran Lee, Sangdoo Yun, Seongjin Shin, Sungdong Kim, James Thorne, et al. Prometheus: Inducing fine-grained evaluation capability in language models. In *The Twelfth International Conference on Learning Representations (ICLR)*, 2024.

Lorenz Kuhn, Yarin Gal, and Sebastian Farquhar. Semantic uncertainty: Linguistic invariances for uncertainty estimation in natural language generation. In *The Eleventh International Conference on Learning Representations (ICLR)*, 2023.

Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Jacob Devlin, Kenton Lee, et al. Natural questions: a benchmark for question answering research. *Transactions of the Association for Computational Linguistics (TACL)*, 2019.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. Retrieval-augmented generation for knowledge-intensive nlp tasks. *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

Junlong Li, Shichao Sun, Weizhe Yuan, Run-Ze Fan, Pengfei Liu, et al. Generative judge for evaluating alignment. In *The Twelfth International Conference on Learning Representations (ICLR)*, 2024.

Yucheng Li, Bo Dong, Frank Guerin, and Chenghua Lin. Compressing context to enhance inference efficiency of large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2023.

Chin-Yew Lin. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, 2004.

Nelson F Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics (TACL)*, 2024.

Yang Liu, Dan Iter, Yichong Xu, Shuohang Wang, Ruochen Xu, and Chenguang Zhu. G-eval: Nlg evaluation using gpt-4 with better human alignment. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2023.

Yu A Malkov and Dmitry A Yashunin. Efficient and robust approximate nearest neighbor search using hierarchical navigable small world graphs. *IEEE Transactions on Pattern Analysis and Machine Intelligence (TPAMI)*, 2018.

Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. Locating and editing factual associations in gpt. *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

Alexander V Nikitin, Jannik Kossen, Yarin Gal, and Pekka Marttinen. Kernel language entropy: Fine-grained uncertainty quantification for LLMs from semantic similarities. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems (NeurIPS)*, 2024.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th annual meeting of the Association for Computational Linguistics (ACL)*, 2002.

Fabio Petroni, Tim Rocktäschel, Sebastian Riedel, Patrick Lewis, Anton Bakhtin, Yuxiang Wu, and Alexander Miller. Language models as knowledge bases? In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, 2019.

Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. Squad: 100,000+ questions for machine comprehension of text. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2016.

Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. " why should i trust you?" explaining the predictions of any classifier. In *Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining (KDD)*, 2016.

Stephen E Robertson, Steve Walker, Susan Jones, Micheline M Hancock-Beaulieu, Mike Gatford, et al. Okapi at trec-3. *Nist Special Publication Sp*, 1995.

Jon Saad-Falcon, Omar Khattab, Christopher Potts, and Matei Zaharia. Ares: An automated evaluation framework for retrieval-augmented generation systems. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers) (NAACL)*, 2024.

Alireza Salemi and Hamed Zamani. Evaluating retrieval quality in retrieval-augmented generation. In *Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR)*, 2024.

Rylan Schaeffer, Brando Miranda, and Sanmi Koyejo. Are emergent abilities of large language models a mirage? *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

Zhihong Shao, Yeyun Gong, Minlie Huang, Nan Duan, Weizhu Chen, et al. Enhancing retrieval-augmented large language models with iterative retrieval-generation synergy. In *The 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2023.

Weijia Shi, Sewon Min, Michihiro Yasunaga, Minjoon Seo, Richard James, Mike Lewis, Luke Zettlemoyer, and Wen-tau Yih. Replug: Retrieval-augmented black-box language models. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers) (NAACL)*, 2024.

Alon Talmor and Jonathan Berant. The web as a knowledge-base for answering complex questions. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers) (NAACL)*, 2018.

James Thorne, Andreas Vlachos, Christos Christodoulopoulos, and Arpit Mittal. FEVER: a large-scale dataset for fact extraction and VERification. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers) (NAACL)*, 2018.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023.

Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. Interleaving retrieval with chain-of-thought reasoning for knowledge-intensive multi-step questions. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers) (ACL)*, 2022a.

Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. ♪ musique: Multi-hop questions via single-hop question composition. *Transactions of the Association for Computational Linguistics (TACL)*, 2022b.

Claudia Wagner, Markus Strohmaier, Alexandra Olteanu, Emre Kıcıman, Noshir Contractor, and Tina Eliassi-Rad. Measuring algorithmically infused societies. *Nature*, 2021.

Cunxiang Wang, Sirui Cheng, Qipeng Guo, Yuanhao Yue, Bowen Ding, Zhikun Xu, Yidong Wang, Xiangkun Hu, Zheng Zhang, and Yue Zhang. Evaluating open-qa evaluation. *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

Liang Wang, Nan Yang, Xiaolong Huang, Binxing Jiao, Linjun Yang, Daxin Jiang, Rangan Majumder, and Furu Wei. Text embeddings by weakly-supervised contrastive pre-training. *arXiv preprint arXiv:2212.03533*, 2022.

Shitao Xiao, Zheng Liu, Peitian Zhang, Niklas Muennighoff, Defu Lian, and Jian-Yun Nie. C-pack: Packed resources for general chinese embeddings. In *Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR)*, 2024.

Ziang Xiao, Susu Zhang, Vivian Lai, and Q Vera Liao. Evaluating evaluation metrics: A framework for analyzing nlg evaluation metrics using measurement theory. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2023.

Sang Michael Xie, Aditi Raghunathan, Percy Liang, and Tengyu Ma. An explanation of in-context learning as implicit bayesian inference. In *The Tenth International Conference on Learning Representations (ICLR)*, 2022.

Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William Cohen, Ruslan Salakhutdinov, and Christopher D Manning. Hotpotqa: A dataset for diverse, explainable multi-hop question answering. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2018.

Peiran Yao and Denilson Barbosa. Accurate and nuanced open-QA evaluation through textual entailment. In *Findings of the Association for Computational Linguistics: ACL 2024*, 2024.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik R Narasimhan, and Yuan Cao. React: Synergizing reasoning and acting in language models. In *The Eleventh International Conference on Learning Representations (ICLR)*, 2023.

Ori Yoran, Tomer Wolfson, Ori Ram, and Jonathan Berant. Making retrieval-augmented language models robust to irrelevant context. In *The Twelfth International Conference on Learning Representations (ICLR)*, 2024.

Zichun Yu, Chenyan Xiong, Shi Yu, and Zhiyuan Liu. Augmentation-adapted retriever improves generalization of language models as generic plug-in. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers) (ACL)*, 2023.

Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q Weinberger, and Yoav Artzi. Bertscore: Evaluating text generation with bert. In *International Conference on Learning Representations (ICLR)*, 2020.

Zexuan Zhong, Dan Friedman, and Danqi Chen. Factual probing is [mask]: Learning vs. learning to recall. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL)*, 2021.

Part I

Appendix

Table of Contents

A DETAILS OF EXPERIMENTS

A.1 DATASET STATISTICS

This section presents the datasets used in our experiments, detailing their names, sizes, sources, and key characteristics.

Dataset	Size	Source	Key Characteristics
Single QA			
MS MARCO Bajaj et al. (2016)	101,093	Bing	Search engine queries, web passages
SQuAD Rajpurkar et al. (2016)	10,570	Wikipedia	Standard reading comprehension
BoolQ Clark et al. (2019)	3,270	Wikipedia	Yes/No questions, requires inference
Fermi Kalyan et al. (2021)	1,000	Wikipedia	Estimation-based reasoning
Multi-hop QA			
HotpotQA Yang et al. (2018)	7,405	**Wikipedia**	Requires multi-hop reasoning
2WikiMultihopQA Ho et al. (2020)	12,576	Wikipedia	Cross-document multi-hop reasoning
MuSiQue Trivedi et al. (2022b)	2,417	Wikipedia	Multi-hop reasoning, complex questions
Fact Verification			
FEVER Thorne et al. (2018)	10,444	Wikipedia	Fact verification
Multiple-choice QA			
MMLU Hendrycks et al. (2021)	14,042	N/A	Multiple-choice, general knowledge
Summarization			
WikiASP Hayashi et al. (2021)	37,368	Wikipedia	Open-domain summarization

Table 3: Dataset Details

A.2 ROBUSTNESS OF *SePer* IN REPEATED TESTS

Dataset	# Repetition	# Samples	σ		Coefficient Variance	
			SePer	**Correlation**	*SePer*	**Correlation**
NQ Kwiatkowski et al. (2019)	5	10	0.053	0.002	0.028	0.002
MS MARCO Bajaj et al. (2016)	5	10	0.055	0.003	0.003	0.005
HotpotQA Yang et al. (2018)	5	10	0.045	0.001	0.037	0.001
SQuAD Rajpurkar et al. (2016)	5	10	0.056	0.004	0.063	0.004

Table 4: Extended experimental details on the robustness test of *SePer*. As shown in the table, *SePer* demonstrates stability upon repeated testing in our default choice of ten samples.

Table 4 shows that the standard deviation(σ) and coefficient variation in calculating *SePer* is less than 10%, which means that *SePer* produces the result of low variance in repeated tests. We also calculated the variation in the degree of correlation with human judgments in repeated tests. Results show that the fluctuation of the correlation score is less than 1%. All these experimental signs prove that the proposed *SePer* is a reliable and stable measurement according to the theory of statistics.

A.2.1 *P*-VALUES WITH THE PEARSON CORRELATION OF Δ*SePer*

Dataset	NQ	MS MARCO	SQuAD	HotPotQA	2WikiMHQA	Musique	IIRC
p-value	0	0	2.86×10^{-207}	0	0	0	2.88×10^{-218}

Table 5: *p*-values across different datasets. The *p*-value 0 does not necessarily mean zero, but below the numerical precision, which indicates a number very close to 0.

B EXTENDED RESULTS

B.1 QUALITATIVE ANALYSIS

In this section, we analyze two RAG cases qualitatively to demonstrate the effectiveness of the proposed $\Delta SePer$ in measuring retrieval utility.

We use two cases from two typical scenarios: one for simple RAG, in which the answer is contained in a single document, and another for reasoning-intensive RAG, in which the answer should be reasoned over multiple documents.

Question:	Who sings does he love me with reba?
Reference Docs:	**Doc1**: "Does He Love You" is a song written by Sandy Knox and Billy Stritch, and recorded as a duet by American country music artists Reba McEntire and Linda Davis. It was released in August 1993 as the first single from Rebaś album "Greatest Hits Volume Two". It is one of country musicś several songs about a love triangle. "Does He Love You" was written in 1982 by Billy Stritch. He recorded it with a trio in which he performed at the time, because he wanted a song that could be sung by the other two members.
Ground Truth Answer	Linda Davis.

Retrieved Docs Doc1	Model Answer (x10)	GT Answer	$\Delta SePer$	Amount of information
×	Reba McEntire: 10	Linda Davis	0	0
✓	Linda Davis: 10		1.0	1

Table 6: Case #1 of simple RAG task: $\Delta SePer$ on single retrieved doc. $\Delta SePer$ accurately reflects the utility of retrieved documents.

Results Analysis of Case #1: Results in Table 6 shows that when no useful document is provided (the ✓ means the retrieved document is irrelevant), the model consistently fails to answer the question correctly, even with ten times' sampling. At this time, the calculated $\Delta SePer$ is 0, accurately indicating the zero utility of irrelevant information. When a positive document is retrieved, the model successfully generates the correct answer. At this time, the calculated $\Delta SePer$ is 1, accurately indicating the utility of useful information.

Question:	Are the Laleli Mosque and Esma Sultan Mansion located in the same neighborhood?
Reference Docs:	**Doc1**: The Laleli Mosque (Turkish: 'Laleli Camii', or Tulip Mosque) is an 18th-century Ottoman imperial mosque located in Laleli, Fatih, Istanbul, Turkey.
Doc2: The Esma Sultan Mansion (Turkish: 'Esma Sultan Yalısı'), a historical yalı (English: waterside mansion) located on the Bosphorus in the Ortaköy neighborhood of Istanbul, Turkey, named after its original owner, Esma Sultan, is now used as a cultural center after redevelopment.
Ground Truth Answer	No.

Retrieved Docs Doc1	Doc2	Model Answer (x10)	GT Answer	$\Delta SePer$	Amount of information
×	×	Yes: 10, No: 0		0	0
×	✓	Yes: 7, No: 3	No	0.15	1/2
✓	×	Yes: 8, No: 2		0.1	1/2
✓	✓	Yes: 3, No: 7		0.7	1

Table 7: Case #2 of reasoning-based RAG task: $\Delta SePer$ on multiple retrieved docs. $\Delta SePer$ reflects the utility of retrieved information in a fine-grained way, successfully responding to partial information.

Results Analysis of Case #2: Results in Table 7 demonstrate that when no relevant retrieval is provided, the model consistently gives the incorrect answer, "Yes," which indicates it is unable to infer the relationship between the two locations. When only one piece of contextual information is made available, the model's answers begin to vary. This outcome suggests that partial information, although not sufficient for producing the correct answer consistently, causes the model to reconsider its initially confident but incorrect response. Traditional evaluation methods often assess retrieval utility based solely on whether the retrieved information directly enables the model to provide a correct answer and overlook the intermediate benefits that partial information can offer. In contrast, our $\Delta SePer$ successfully responds to even partial information, providing a fine-grained evaluation of information utility.

B.2 EFFICIENCY ANALYSIS

We conduct a latency and cost analysis using widely available commercial LLM APIs. Specifically, we evaluate multiple APIs with varying pricing structures from providers, including OpenAI, Anthropic, Google, and Deepseek.

In the *Direct Evaluation* setting, we prompt the LLM with a given question, context, and answer and request the model to assess the contribution of the context to the overall response by assigning an integer score between 1 and 10. While in the *Reduction Evaluation* setting, we first query the LLM with the combination of query, context, and answer to evaluate the correctness of the answer. Subsequently, we query the LLM with only the query and answer to assess the correctness without the context. The difference between these two scores is computed to determine the $\Delta SePer$.

For our experiments, we utilize the Natural Questions Kwiatkowski et al. (2019) dataset, selecting 10 questions with corresponding references collected from passages in the Wikipedia corpus using the E5 Wang et al. (2022) model. We report the average prompt length and the average time consumed across the ten questions. We list the user prompts used in the experiment as follows:

Prompt for *Direct Evaluation* in LLM APIs

Evaluate the contribution of the given context to the provided answer for the specified question.
Your evaluation should be based on how effectively the context supports or justifies the answer.
Provide your assessment using an integer rating between 1 (minimal or no contribution) and 10 (critical or complete contribution).
Do not output any other information or context.
- Question: {question}
- Context: {context}
- Answer: {answer}
Your evaluation:

Prompt for *Reduction Evaluation* in LLM APIs with context

Evaluate the correctness of the given answer based on the question and the provided context.
Rate correctness using an integer between 1 (completely incorrect) and 10 (completely correct).
Only provide the rating as your output.
- Question: {question}
- Context: {context}
- Answer: {answer}
Your rating:

> **Prompt for *Reduction Evaluation* in LLM APIs without context**
>
> Evaluate the correctness of the given answer based solely on the question.
> Ignore any external information and rate correctness using an integer between 1 (completely incorrect) and 10 (completely correct).
> Only provide the rating as your output.
> - Question: {question}
> - Answer: {answer}
> Your rating:

Table 8 summarizes the average time latencies and costs across different API providers. We checked the latest pricing on the official websites of each API and did not enable any potential batching mechanisms. Additionally, it demonstrates the advantages of our proposed *SePer* and Δ*SePer* in terms of time and economic costs.

Models	Company	Direct Evaluation		Reduction Evaluation	
		Time (s)	Cost ($)	Time (s)	Cost ($)
chatgpt-4o-latest	OpenAI[*]	4.22	0.0077	6.13	0.0080
gpt-4-turbo	OpenAI[*]	2.01	0.0155	3.80	0.0163
gpt-3.5-turbo	OpenAI[*]	3.34	0.0008	3.89	0.0008
claude-3-5-sonnet-nx	Anthropic[†]	7.45	0.0046	30.30	0.0052
claude-3-haiku-nx	Anthropic[†]	5.63	0.0003	19.21	0.0004
gemini-1.5-pro	Google[‡]	3.29	0.0192	6.97	0.0203
gemini-1.5-flash	Google[‡]	3.56	0.0001	6.26	0.0001
deepseek-chat	Deepseek[§]	0.88	0.0000	1.68	0.0000
SePer & ΔSePer	N/A	**0.12**	**Free**	**0.24**	**Free**

Table 8: **Latency ($\downarrow$) and Cost ($\downarrow$) Comparison of Various LLM Models in Direct and Reduction Evaluation Settings.** The table shows the average response time (in seconds) and cost (in USD) for each model in Direct and Reduction evaluation tasks.

B.3 CIRCUMSTANCES OF NEGATIVE UTILITY

Additionally, our experiments, conducted according to the settings outlined in Figure 6, revealed that some retrieved items negatively impact question-answering performance. We extended our tests to additional datasets to further investigate this phenomenon, and the datasets involved are listed in Table 3.

We first observed that in certain datasets, the retrieved items hindered the model's question-answering ability. For instance, in the MMLU dataset, which is a multiple-choice dataset with relatively straightforward questions, the model can often rely on its own knowledge to answer correctly. In such cases, the retrieved items proved detrimental. For the MS MARCO dataset, we attributed this issue to distribution shifts, as the corpus differs from the one used during training. For more complex datasets like MuSiQue, 2WikiMultihopQA, and Fermi, which require multi-step reasoning and logical chains, a small number of retrieved items could not provide all the necessary information. However, when enough items were retrieved, they offered a more comprehensive information set, thereby assisting the model in making correct inferences. In the FEVER dataset, focused on Fact Verification, an excessive number of retrieved items disrupted the model's ability to verify facts effectively.

Regarding prompt compression methods, excluding the datasets that already exhibited negative effects without compression (as discussed in the previous paragraph), the Fermi dataset, which in-

---

[*]https://openai.com/api/pricing/

[†]https://www.anthropic.com/pricing#anthropic-api

[‡]https://ai.google.dev/pricing

[§]https://api-docs.deepseek.com/quick_start/pricing

volves numerous mathematical logits, was particularly impacted by incorrect token compression, leading to errors. Similarly, in the 2WikiMultihopQA dataset, incorrect compression of logical chains was identified as a key issue.

Despite these challenges, we still found that the use of the reranker consistently improved performance across these datasets, further validating its robustness.

Figure 6: Differences in *SePer* under various retrieval and generation settings. Same as Figure 5, Panel (a) shows the differences in *SePer* for generation with and without retrieval under different numbers of retrieved information. Panel (b) illustrates the impact of using prompt compression and which compression method on the differences in *SePer* compared to generation without retrieval. Panel (c) demonstrates the reranker's effect compared to generation without retrieval.

B.4 ABLATION OF THE CONSISTENCY OF *SePer* WITH DIFFERENT ENTAILMENT MODELS

In this paper, we choose `deberta-v2-xlarge-mnli`[§] He et al. (2021) following Farquhar et al. (2024) for deciding the entailment relationship, which strikes a balance between accuracy and efficiency. For the sake of the ablation study, we tested the influence of the choice of entailment models on the result of *SePer* in Figure 7. We choose seven mainstream models used for NLI classification tasks with varying sizes and architectures and compute the Pearson correlation of *SePer* produced from these models. Specifically, the entailment models we used are listed as follows:

Model	Developer	Size (Parameters)	# of Layers	Hidden Size	Architecture
DeBERTa-Base-MNLI[*]	Microsoft	86M	12	768	Encoder-only
DeBERTa-Large-MNLI[†]	Microsoft	350M	24	1024	Encoder-only
DeBERTa-XLarge-MNLI[‡]	Microsoft	700M	48	1024	Encoder-only
DeBERTa-V2-XLarge-MNLI[§]	Microsoft	710M	24	1536	Encoder-only
DeBERTa-V2-XXLarge-MNLI[¶]	Microsoft	1.3B	48	1536	Encoder-only
RoBERTa-Large-MNLI[‖]	Facebook	355M	24	1024	Encoder-only
BART-Large-MNLI[**]	Facebook	406M	12+12	1024	Encoder-Decoder

Table 9: Details of different entailment models for ablation study on the robustness of *SePer*. We choose main-stream models used in the field of NLI, covering different sizes and architectures.

We tested 7 NLI models on 9 datasets and 3 different choices for k (number of items retrieved and used in in-context prompting) in computing *SePer*.

According to the results in Figure 7, all of the Pearson correlation scores between the results of model pairs are above 0.7. Specifically, for simple-type QA tasks (NQ, AmbigQA, MSMARCO, SQuAD, TriviaQA, PopQA), the entailment judgments are even more consistent, with all scores above 0.85 and most scores above 0.9. For reasoning-type QA tasks (HotpotQA, 2WikiMultihopQA, MuSiQue), the entailment scores are all above 0.7, with most scores above 0.9.

---

[*] https://huggingface.co/microsoft/deberta-base-mnli
[†] https://huggingface.co/microsoft/deberta-large-mnli
[‡] https://huggingface.co/microsoft/deberta-xlarge-mnli
[§] https://huggingface.co/microsoft/deberta-v2-xlarge-mnli
[¶] https://huggingface.co/microsoft/deberta-v2-xxlarge-mnli
[‖] https://huggingface.co/FacebookAI/roberta-large-mnli
[**] https://huggingface.co/facebook/bart-large-mnli

Based on these high correlation scores among different entailment models, we can safely draw the conclusion that *SePer* is robust in computation in terms of entailment model choice, and it is still effective and reliable on small models (86M) when high efficiency is required.

Figure 7: Consistency of *SePer* computation among different entailment models.

C   BENCHMARKING RETRIEVER AND WORKFLOW

For more detailed information on benchmarking the retriever and the entire workflow, please visit the following link: *SePer* Benchmarks.

C.1   BENCHMARKING RETRIEVER QUALITY AND UTILITY

The majority of dense retrievers in dense retrieval paradigms are based on transformer architectures such as BERT. This opens the possibility for further fine-tuning with more extensive and higher-quality datasets, as well as more advanced algorithms. Consequently, a wide variety of retrievers have emerged in the community. To evaluate their performance, we present benchmarks based on multiple datasets (described in Table 3) and multiple retrievers, utilizing *SePer* as the evaluation framework. These benchmarks aim to assess both the quality and utility of different retrievers.

For quality evaluation, we provide a benchmark comparing the performance of retrievers on standard retrieval tasks with various numbers of retrieved items. For utility evaluation, we propose a Δ*SePer*-based benchmark. In this setup, the Δ*SePer* is computed by taking the difference between the *SePer* scores achieved using *question-answer* pairs and those obtained using *question-retrieval context-answer* pairs.

We evaluate six dense retrievers: AAR_{ANCE} Yu et al. (2023), $AAR_{Contriever}$ Yu et al. (2023), *BGE* Xiao et al. (2024), *Contriever* Izacard et al. (2022), *DPR* Karpukhin et al. (2020), and *E5* Wang et al. (2022), alongside the classical sparse retriever *BM25* Robertson et al. (1995). The results of the quality and utility benchmarks are presented in Tables 10 and 11, respectively.

C.2   BENCHMARKING WORKFLOW UTILITY

Naive RAG strictly follows the *retrieval-generation* paradigm, which limits its ability to utilize retrieved information for further retrieval. This limitation is critical for complex reasoning tasks, such as multi-hop question answering. Therefore, recent research has proposed several workflows that enable the entire RAG pipeline to perform multiple retrievals and integrate information, which may enhance the reasoning ability of large language models.

We benchmarked four RAG workflows—*RetRobust* Yoran et al. (2024), *FLARE* Jiang et al. (2023), *IRCoT* Trivedi et al. (2022a), and *Iter-RetGen* Shao et al. (2023)—on multiple datasets using varying numbers of retrieved items. Since these methods may involve multiple rounds of retrieval, existing retrieval metrics, such as retrieval recall, are no longer suitable. Thus, we only report the Δ*SePer* metric. Additionally, *RetRobust* only provides LoRA checkpoints for Llama 2 Touvron et al. (2023) 13B, so results for the 7B model are marked as "N/A." The results of the benchmark are shown in Table 12.

Metric		SePer										Retrieval Recall		
Top-k		1			5			10				1	5	10
Dataset name	Retriever	7B	13B	70B	7B	13B	70B	7B	13B	70B			N/A	
NQ	AAR-ANCE	0.323	0.321	0.383	0.413	0.424	0.493	0.446	0.461	0.533		0.331	0.574	0.647
	AAR-contriever	0.385	0.376	0.445	0.481	0.496	0.563	0.497	0.516	0.593		0.391	0.670	0.754
	bge	0.464	0.449	0.517	0.530	0.537	0.598	0.535	0.551	0.609		0.507	0.740	0.800
	bm25	0.282	0.270	0.347	0.367	0.377	0.457	0.409	0.431	0.505		0.248	0.463	0.562
	contriever	0.301	0.309	0.368	0.409	0.421	0.501	0.448	0.472	0.544		0.272	0.539	0.632
	dpr	0.403	0.389	0.448	0.469	0.482	0.560	0.490	0.510	0.586		0.424	0.662	0.722
	e5	0.504	0.489	0.555	0.557	0.563	0.620	0.560	0.565	0.621		0.570	0.774	0.833
TriviaQA	AAR-ANCE	0.550	0.577	0.640	0.605	0.635	0.708	0.626	0.671	0.708		0.444	0.632	0.698
	AAR-contriever	0.627	0.629	0.689	0.684	0.699	0.761	0.702	0.723	0.761		0.548	0.725	0.776
	bge	0.629	0.624	0.684	0.675	0.690	0.750	0.697	0.711	0.750		0.580	0.738	0.795
	bm25	0.606	0.607	0.684	0.632	0.662	0.729	0.659	0.688	0.729		0.508	0.688	0.739
	contriever	0.554	0.579	0.656	0.634	0.656	0.720	0.659	0.688	0.720		0.427	0.659	0.734
	dpr	0.587	0.607	0.667	0.667	0.688	0.745	0.682	0.709	0.745		0.555	0.740	0.786
	e5	0.677	0.667	0.736	0.714	0.727	0.783	0.730	0.739	0.783		0.635	0.779	0.818
2WikiMultihopQA	AAR-ANCE	0.348	0.341	0.344	0.371	0.358	0.404	0.380	0.403	0.429		0.175	0.300	0.348
	AAR-contriever	0.357	0.349	0.348	0.383	0.375	0.412	0.398	0.414	0.452		0.189	0.336	0.419
	bge	0.368	0.350	0.371	0.403	0.391	0.431	0.408	0.420	0.453		0.216	0.405	0.467
	bm25	0.374	0.367	0.378	0.392	0.398	0.428	0.403	0.434	0.460		0.244	0.390	0.457
	contriever	0.353	0.349	0.353	0.373	0.380	0.403	0.385	0.407	0.435		0.154	0.273	0.335
	dpr	0.326	0.322	0.309	0.352	0.341	0.370	0.362	0.368	0.399		0.150	0.244	0.299
	e5	0.366	0.354	0.361	0.389	0.393	0.427	0.402	0.424	0.465		0.223	0.384	0.467
HotpotQA	AAR-ANCE	0.297	0.295	0.365	0.339	0.345	0.444	0.347	0.364	0.474		0.205	0.367	0.428
	AAR-contriever	0.376	0.351	0.445	0.402	0.394	0.507	0.409	0.409	0.519		0.287	0.465	0.538
	bge	0.392	0.378	0.464	0.423	0.423	0.537	0.436	0.448	0.543		0.326	0.573	0.639
	bm25	0.383	0.361	0.468	0.422	0.427	0.535	0.430	0.440	0.535		0.311	0.496	0.564
	contriever	0.309	0.305	0.380	0.352	0.341	0.457	0.369	0.376	0.479		0.198	0.359	0.440
	dpr	0.314	0.301	0.360	0.335	0.340	0.440	0.350	0.361	0.454		0.229	0.376	0.438
	e5	0.378	0.373	0.460	0.421	0.414	0.527	0.428	0.442	0.545		0.307	0.534	0.610
PopQA	AAR-ANCE	0.395	0.394	0.415	0.467	0.480	0.513	0.478	0.490	0.551		0.431	0.662	0.726
	AAR-contriever	0.375	0.372	0.394	0.418	0.435	0.477	0.431	0.452	0.504		0.403	0.579	0.645
	bge	0.456	0.454	0.474	0.489	0.513	0.550	0.477	0.515	0.566		0.510	0.704	0.766
	bm25	0.287	0.282	0.301	0.334	0.339	0.379	0.358	0.366	0.427		0.286	0.437	0.488
	contriever	0.297	0.291	0.325	0.356	0.367	0.408	0.382	0.386	0.442		0.281	0.446	0.508
	dpr	0.330	0.321	0.344	0.396	0.409	0.445	0.397	0.425	0.465		0.355	0.532	0.593
	e5	0.474	0.466	0.486	0.512	0.528	0.571	0.512	0.535	0.590		0.528	0.729	0.790

Table 10: *SePer* Benchmark Across Retrievers and Parameter Sizes. The colors highlight the best-performing retrievers under each dataset.

Metric		ΔSePer										Retrieval Recall		
Top-k		1			5			10				1	5	10
Dataset name	Retriever	7B	13B	70B	7B	13B	70B	7B	13B	70B			N/A	
NQ	AAR-ANCE	-0.033	-0.068	-0.101	0.057	0.036	0.009	0.090	0.072	0.049		0.331	0.574	0.647
	AAR-contriever	0.029	-0.012	-0.039	0.125	0.108	0.079	0.141	0.127	0.109		0.391	0.670	0.754
	bge	0.108	0.060	0.033	0.174	0.149	0.114	0.178	0.162	0.125		0.507	0.740	0.800
	bm25	-0.074	-0.118	-0.137	0.010	-0.012	-0.027	0.053	0.042	0.021		0.248	0.463	0.562
	contriever	-0.055	-0.079	-0.116	0.053	0.033	0.017	0.091	0.083	0.060		0.272	0.539	0.632
	dpr	0.047	0.000	-0.036	0.113	0.093	0.076	0.134	0.121	0.102		0.424	0.662	0.722
	e5	0.148	0.100	0.071	0.201	0.174	0.136	0.204	0.176	0.137		0.570	0.774	0.833
TriviaQA	AAR-ANCE	-0.031	-0.059	-0.116	0.025	-0.001	-0.048	0.017	0.035	-0.025		0.444	0.632	0.698
	AAR-contriever	0.046	-0.007	-0.067	0.104	0.063	0.006	0.035	0.087	0.019		0.548	0.725	0.776
	bge	0.049	-0.012	-0.071	0.095	0.054	-0.005	0.045	0.075	0.015		0.580	0.738	0.795
	bm25	0.025	-0.029	-0.072	0.052	0.025	-0.027	0.040	0.051	-0.005		0.508	0.688	0.739
	contriever	-0.026	-0.057	-0.099	0.053	0.020	-0.036	0.022	0.051	-0.008		0.427	0.659	0.734
	dpr	0.007	-0.029	-0.088	0.086	0.052	-0.011	-0.001	0.073	0.010		0.555	0.740	0.786
	e5	0.097	0.031	-0.020	0.133	0.091	0.028	0.039	0.103	0.034		0.635	0.779	0.818
2WikiMultihopQA	AAR-ANCE	-0.015	0.008	-0.021	0.008	0.025	0.039	0.017	0.070	0.063		0.175	0.300	0.348
	AAR-contriever	-0.006	0.015	-0.017	0.020	0.042	0.047	0.035	0.081	0.087		0.189	0.336	0.419
	bge	0.005	0.016	0.006	0.040	0.058	0.065	0.045	0.087	0.088		0.216	0.405	0.467
	bm25	0.011	0.034	0.013	0.030	0.065	0.062	0.040	0.101	0.095		0.244	0.390	0.457
	contriever	-0.009	0.016	-0.013	0.010	0.047	0.038	0.022	0.074	0.070		0.154	0.273	0.335
	dpr	-0.037	-0.011	-0.056	-0.011	0.008	0.005	-0.001	0.035	0.033		0.150	0.244	0.299
	e5	0.003	0.021	-0.004	0.027	0.060	0.062	0.039	0.091	0.100		0.223	0.384	0.467
HotpotQA	AAR-ANCE	0.003	-0.002	-0.039	0.045	0.048	0.040	0.053	0.067	0.070		0.205	0.367	0.428
	AAR-contriever	0.083	0.054	0.041	0.108	0.097	0.103	0.115	0.112	0.115		0.287	0.465	0.538
	bge	0.098	0.081	0.060	0.129	0.126	0.132	0.142	0.151	0.138		0.326	0.573	0.639
	bm25	0.089	0.064	0.064	0.129	0.130	0.130	0.136	0.143	0.131		0.311	0.496	0.564
	contriever	0.015	0.009	-0.024	0.058	0.044	0.053	0.075	0.079	0.075		0.198	0.359	0.440
	dpr	0.020	0.004	-0.044	0.041	0.043	0.035	0.056	0.064	0.050		0.229	0.376	0.438
	e5	0.084	0.076	0.056	0.127	0.117	0.122	0.134	0.145	0.140		0.307	0.534	0.610
PopQA	AAR-ANCE	0.124	0.110	0.058	0.196	0.196	0.156	0.207	0.206	0.194		0.431	0.662	0.726
	AAR-contriever	0.104	0.088	0.037	0.147	0.151	0.119	0.160	0.168	0.147		0.403	0.579	0.645
	bge	0.185	0.170	0.117	0.218	0.229	0.193	0.206	0.231	0.209		0.510	0.704	0.766
	bm25	0.016	-0.002	-0.057	0.063	0.055	0.022	0.087	0.082	0.069		0.286	0.437	0.488
	contriever	0.026	0.007	-0.032	0.086	0.083	0.051	0.111	0.102	0.085		0.281	0.446	0.508
	dpr	0.059	0.037	-0.013	0.125	0.125	0.087	0.127	0.141	0.108		0.355	0.532	0.593
	e5	0.203	0.182	0.128	0.241	0.244	0.214	0.241	0.251	0.233		0.528	0.729	0.790

Table 11: ΔSePer Benchmark Across Retrievers and Parameter Sizes. The colors highlight the best-performing retrievers under each dataset.

Metric		Δ*SePer*					
Top-k		1		5		10	
Dataset name	Workflow	7B	13B	7B	13B	7B	13B
2WikiMultihopQA	*Naive*	0.366	0.354	0.389	0.393	0.402	0.424
	RetRobust	N/A	0.623	N/A	0.644	N/A	0.700
	FLARE	0.360	0.358	0.369	0.336	0.374	0.344
	IRCoT	0.339	0.365	0.364	0.388	0.386	0.405
	Iter-RetGen	0.371	0.346	0.420	0.413	0.435	0.446
HotpotQA	*Naive*	0.378	0.373	0.421	0.414	0.428	0.442
	RetRobust	N/A	0.537	N/A	0.575	N/A	0.589
	FLARE	0.283	0.286	0.290	0.271	0.299	0.277
	IRCoT	0.362	0.418	0.409	0.452	0.442	0.466
	Iter-RetGen	0.396	0.380	0.447	0.447	0.465	0.486
MuSiQue	*Naive*	0.087	0.089	0.116	0.125	0.128	0.137
	RetRobust	N/A	0.456	N/A	0.464	N/A	0.485
	FLARE	0.110	0.140	0.113	0.133	0.115	0.135
	IRCoT	0.143	0.131	0.161	0.157	0.176	0.164
	Iter-RetGen	0.109	0.106	0.143	0.159	0.156	0.178
NQ	*Naive*	0.504	0.489	0.557	0.563	0.560	0.565
	RetRobust	N/A	0.580	N/A	0.605	N/A	0.594
	FLARE	0.333	0.234	0.343	0.222	0.340	0.235
	IRCoT	0.457	0.500	0.493	0.534	0.510	0.515
	Iter-RetGen	0.497	0.476	0.540	0.547	0.561	0.559
PopQA	*Naive*	0.474	0.466	0.512	0.528	0.512	0.535
	RetRobust	N/A	0.493	N/A	0.553	N/A	0.521
	FLARE	0.328	0.248	0.347	0.244	0.343	0.247
	IRCoT	0.426	0.451	0.478	0.496	0.483	0.493
	Iter-RetGen	0.462	0.447	0.499	0.512	0.486	0.523
TriviaQA	*Naive*	0.677	0.667	0.714	0.727	0.730	0.739
	RetRobust	N/A	0.778	N/A	0.815	N/A	0.811
	FLARE	0.555	0.504	0.558	0.486	0.568	0.490
	IRCoT	0.597	0.688	0.671	0.722	0.704	0.730
	Iter-RetGen	0.688	0.677	0.730	0.734	0.740	0.751

Table 12: Δ*SePer* Benchmark Across Workflow and Parameter Sizes. The colors highlight the best-performing retrievers under each dataset.

D   EXPERIMENT DETAILS IN SECTION 5

To demonstrate that our proposed *SePer* and Δ*SePer* effectively integrate with various RAG pipelines, we conduct extensive experiments in Section 5. We also aim to show that *SePer* and Δ*SePer* are module-agnostic within RAG pipelines.

Following the taxonomy proposed by Jin et al. (2024); Gao et al. (2023), modern modular RAG systems consist of various interchangeable and combinable modules, including refiner and reranker. These modules can be adapted or replaced to better target specific downstream tasks, providing greater flexibility and task-specific optimization. We additionally selected the **prompt compression** (a kind of refiner) and **reranker** modules for benchmarking and aim to provide a detailed explanation of their mechanisms and roles here.

D.1   PROMPT COMPRESSION

Prompt compression shortens the prompt by filtering redundant and low-value content while ensuring the context fits within the model's context length.

Given a large language model (LLM) and an input prompt x, let the response generated by the model be denoted as $\text{LLM}(x)$. The goal of prompt compression is to find a compressed prompt x' such that:

$$\mathcal{D}\big(\mathcal{P}_{\text{LLM}(x)}, \mathcal{P}_{\text{LLM}(x')}\big) < \epsilon, \tag{12}$$

where $\mathcal{P}_{\text{LLM}(x)}$ and $\mathcal{P}_{\text{LLM}(x')}$ represent the distributions over the model's responses when prompted with x and x', respectively. These distributions reflect the stochasticity introduced by sampling methods (e.g., temperature scaling, top-k, or nucleus sampling) during text generation.

Here, $\mathcal{D}(\cdot, \cdot)$ denotes a divergence metric, such as KL divergence, computed in a semantically meaningful space. Since the responses are text, we embed them in a suitable representation space (e.g., sentence embeddings) where these metrics can effectively measure differences in meaning and style.

The compression requirement is formalized as:

$$\text{len}(x') < \text{len}(x). \tag{13}$$

This ensures that x' retains the semantic and functional equivalence of x, while reducing token length.

We will also present the technical details of the two prompt compression methods we employed.

Selective-context Li et al. (2023) ranks and filters lexical units (e.g., tokens, phrases, or sentences) based on their informativeness. Informativeness is measured using *self-information*, defined for a token x_t as:

$$I(x_t) = -\log_2 P(x_t | x_0, \ldots, x_{t-1}). \tag{14}$$

In practice, self-information is calculated with smaller models for efficiency. Tokens with higher self-information are considered more informative, while redundant tokens have lower scores. To avoid disjoint filtering, tokens are grouped into larger lexical units (e.g., noun phrases or sentences). The self-information of each unit is computed by summing the scores of its tokens. Units are ranked by their scores, and a percentile-based threshold of p is applied to retain the most informative content.

LongLLMLingua Jiang et al. (2024) aligns closely with RAG use cases, decomposing prompt compression into modular steps:

- **Coarse-Grained Compression:** Documents are ranked by relevance using perplexity conditioned on the question: $r_k = -\frac{1}{N_c} \sum_{i=1}^{N_c} \log p(x_i^{\text{que, restrict}} | \mathbf{x}_k^{\text{doc}})$, where higher r_k values prioritize relevant documents.

- **Fine-Grained Compression:** Token-level relevance is evaluated with *contrastive perplexity*: $s_i = \text{perplexity}(x_i | x_{<i}) - \text{perplexity}(x_i | x^{\text{que}}, x_{<i})$, highlighting critical tokens based on their importance to the query.

- **Adaptive Compression Ratio:** Compression budgets are dynamically allocated using: $\tau_k^{\mathrm{doc}} = \max\left(\min\left((1 - \frac{2I(r_k)}{K'})\delta\tau + \tau^{\mathrm{doc}}, 1\right), 0\right)$, where higher-ranked documents $(I(r_k))$ receive lower compression ratios.

- **Subsequence Recovery:** Ensures content integrity by 1) identifying the longest matching substring $\widetilde{\boldsymbol{y}}_{\mathrm{key},l}$ in the LLM's response, 2) matching it with the maximum common subsequence $\boldsymbol{x}_{i,j}$ in the original prompt, and 3) replacing response tokens with the original prompt's subsequence.

- **Optimization Objective:** The overall objective balances output accuracy and compression: $\min_{\widetilde{\mathbf{x}}} D_\phi\left(\mathbf{y}, \widetilde{\mathbf{y}}\right) + \lambda\|\widetilde{\mathbf{x}}\|_0$, where D_ϕ measures the divergence between the original and compressed prompts' outputs, and λ controls the compression tradeoff.

This approach ensures compressed prompts remain concise and informative, optimizing both efficiency and effectiveness for long-context scenarios.

D.2   RERANKERS

To improve the precision and relevance of retrieved results, our pipeline employs rerankers to reorder coarse retrieval outputs. Below, we describe the underlying mechanisms of rerankers and their role in our system. To ensure clarity, we also briefly outline the retriever's principle and contrast it with the reranker.

Retriever. We only consider dense retrieval here. The retriever uses a **dual-tower architecture**, wherein:

- **Query Encoder**: Encodes the query into a dense embedding $\mathbf{q} \in \mathbb{R}^d$.

- **Document Encoder**: Encodes each document into a corresponding dense embedding $\mathbf{d} \in \mathbb{R}^d$.

The similarity between a query $\mathbf{q}$ and a document $\mathbf{d}_i$ is computed using a dot product:

$$\mathrm{score}(\mathbf{q}, \mathbf{d}_i) = \mathbf{q}^\top \mathbf{d}_i, \quad i = 1, \ldots, N. \tag{15}$$

The retriever selects the top-k documents with the highest scores as candidates. This coarse retrieval process is efficient and scalable because document embeddings can be pre-computed independently and stored, allowing for rapid approximate nearest neighbor (ANN) searches in vector space Douze et al. (2024); Johnson et al. (2019); Malkov & Yashunin (2018), which is ideal for large-scale retrieval. However, this independence of query and document encoding also makes the retriever less sensitive to context, as it cannot fully capture the nuanced interactions between queries and documents.

Reranker. Rerankers are employed to refine the results of coarse retrieval by reordering and filtering the candidate documents based on relevance. To overcome the drawbacks stated above, rerankers use a **cross-encoder architecture** to jointly encode the query and document, capturing their semantic interactions.

The reranker operates as follows:

- **Input Preparation**: Each query-document pair (q, d_i) is concatenated into a single sequence, i.e.: *{[CLS], q, [SEP], d_i, [SEP]}*, where *[CLS]* and *[SEP]* are special tokens for encoding in Transformer-based models. This is a typical setup for cross-encoder architectures.

- **Contextual Encoding**: The concatenated sequence is input into a transformer (e.g., BERT), which computes a joint representation of the query and document. This step enables the model to capture rich contextual interactions, which are absent in retrievers due to their independent encoding process.

- **Relevance Scoring**: A relevance score is computed to quantify the alignment between the query and the document. In a standard cross-encoder setup, the output corresponding to the *[CLS]* token is passed through a scoring head (e.g., a linear layer):

$$\mathrm{score}(q, d_i) = f\left(\mathbf{h}_{[\mathrm{CLS}]}\right), \tag{16}$$

where $\mathbf{h}_{[CLS]}$ represents the contextual representation of the *[CLS]* token. Alternatively, some architectures may use pooling methods (e.g., mean or max pooling) overall token representations or token-level interactions to derive the relevance score.

- **Reordering and Selection**: Based on the computed relevance scores, the candidate documents are reordered, and the top-k items are selected for downstream processing.

The key differences between retrievers and rerankers are summarized in Table 13. While retrievers are efficient and suitable for coarse retrieval over large document collections, rerankers excel in precision by capturing query-document interactions.

Module	Retriever	Reranker
Architecture	Dual-tower (independent encoding)	Cross-encoder (joint encoding)
Input	Separate query and document inputs	Concatenated query-document pair
Output	Dot-product score for similarity	Relevance score for each pair
Efficiency	High efficiency, scalable to corpus	Costly, only for candidate sets
Interaction	No interaction between pairs	Captures rich semantic interactions
Use Case	Coarse-grained candidate selection	Fine-grained reordering and filtering

Table 13: Comparison between retriever and reranker mechanisms.

D.3 DATASET SELECTION

We select commonly used Single QA and Multi-hop QA datasets for inference to evaluate the performance of *SePer* in different scenarios. The dataset selection is guided by the need to cover a variety of QA tasks, ensuring a more comprehensive evaluation. Wherever possible, we perform inference on the `test` set; if the `test` set is unavailable, we use the `dev` set instead. We re-sample the datasets, and for datasets with more than 1000 instances, we randomly select 1000 examples for inference. Figure 3 in the appendix presents the basic information of our utilized datasets.

D.4 HYPERPARAMETER SETTING

We conduct experiments using the Llama 2 model series Touvron et al. (2023) from the Meta Llama family, specifically `Llama-2-7b-chat-hf`[*], `Llama-2-13b-chat-hf`[†], and `Llama-2-70b-chat-hf`[‡]. Considering that the task involves instruction-following generation, we choose the chat versions of these models. To generate various and complete answers of various kinds for *SePer* computation, we set the temperature parameter of each model to 1.0, enabled `do_sample`, and set the maximum tokens for generation to 512. For the retrieval corpus, we use the DPR version of the Wikipedia December 2018 dataset[¶] as our retrieval corpus, following the configuration we utilize in the RAG framework FlashRAG Jin et al. (2024). We experiment with the set of top-k values for retrieval being $\{1, 5, 10\}$, and follow each method's official implementation for the hyper-parameters of different prompt compression methods. For reranker usage, we set the reranker model as `BAAI/bge-reranker-large`[§]. We set the initial top-k value for retrieval to 20 and then apply the set as $\{1, 5, 10\}$ for the reranker to choose items, leveraging the reranker's ability to both rank and filter out irrelevant content. We enable mix precision when calculating *SePer*.

---

[*]https://huggingface.co/meta-llama/Llama-2-7b-chat-hf
[†]https://huggingface.co/meta-llama/Llama-2-13b-chat-hf
[‡]https://huggingface.co/meta-llama/Llama-2-70b-chat-hf
[§]https://huggingface.co/BAAI/bge-reranker-large
[¶]https://archive.org/download/enwiki-20181220

D.5 PROMPT DESIGN AND IMPLEMENTATION

The selection of prompts is crucial for enabling large language models (LLMs) to understand tasks and produce responses that align with the desired style and requirements. In this work, we present two types of prompts: those that generate responses directly without retrieval and those that include references for retrieval-augmented generation. Specifically, we leverage the prompts introduced in Jin et al. (2024), which are listed as follows:

Prompt for naive generation

Answer the question based on your own knowledge. Only give me the answer and do not output any other words.
Question: {question}

Prompt for RAG

Answer the question based on the given document. Only give me the answer and do not output any other words.
The following are given documents.{reference}
Question: {question}

D.6 SYSTEM SPECIFICATIONS FOR REPRODUCTIVITY

Our experiments were conducted on high-performance servers, each equipped with either an Intel(R) Xeon(R) Platinum 8378A CPU @ 3.00GHz or an Intel(R) Xeon(R) Platinum 8358P CPU @ 2.60GHz, 1TB of RAM, and 4/6 NVIDIA A800 GPUs with 80GB memory. Machines with 4 GPUs are configured with the SXM4 version, while those with 6 GPUs use the PCIe version. The software environment included *Python* 3.11, *PyTorch* 2.4, and *NCCL* 2.21.5 for reproductivity.