SciKernelBench: Evaluating LLM Kernels for Higher-Order Autodiff and Scientific Residuals

Maria Ivanova [1 2] **Pavel Zadorozhny** [3] **Rodion Levichev** [3] **Konstantin Sozykin** [2] **Redko Dmitry** [2]
Albert Fazlyev [4] **Dmitry Abulkhanov** [5] **Evgeny Burnaev** [2] **Dmitrii Babaev** [3] **Egor Shvetsov** [2]

Abstract

Existing kernel generation benchmarks mainly target standard tensor operations such as matrix multiplications, convolutions, and elementwise operators. In contrast, scientific residuals require gradients, Jacobians, Laplacians, divergence, normal derivatives, and convective terms, often involving higher order autodiff paths that are not generally supported by current PyTorch compiler pipelines.

We introduce **SciKernelBench**, a benchmark of 144 TorchPhysics derived workloads represented in the KernelBench format. The benchmark covers both isolated differential operator primitives and composed residual computations from physics informed neural networks, Deep Ritz formulations, inverse problems, time-dependent PDEs, contact mechanics, interface problems, and flow systems.

SciKernelBench evaluates generated implementations by numerical correctness, runtime performance, and implementation honesty. The last axis is essential because candidates may pass ordinary output checks by reusing PyTorch autograd, preserving the reference path, omitting derivative terms, or hard coding deterministic inputs, without producing genuine low level acceleration. Across recent frontier LLMs and test time strategies, we find that scientific residuals remain challenging. On Level 1, Claude solves all tasks under repeated sampling and refinement without execution feedback, but drops to 23/84 raw and only 3/84 honest solves under refinement with execution feedback. Gemini shows a large raw honest

gap even without feedback, with 33/84 raw but only 11/84 honest solves. On Level 2, Claude reaches 60/60 raw solves under execution feedback, while Gemini and Qwen remain substantially lower. Standard correctness based success can substantially overestimate genuine kernel generation ability in several settings, especially under refinement with execution feedback. These results show that scientific residuals require evaluation protocols that test not only whether generated code runs, but whether it faithfully implements the underlying scientific computation.

1. Introduction

Machine learning methods for solving scientific equations increasingly represent physical fields with neural networks. Instead of training only against labeled data, approaches, such as physics informed neural networks and Deep Ritz methods, train a neural field by requiring it to satisfy a governing equation together with boundary, initial, interface, or observation constraints. This produces a *residual*, the error obtained after substituting the neural approximation into the scientific problem. In practice, each optimization step may evaluate the neural field at many collocation points, differentiate it with respect to spatial or temporal coordinates, and assemble the resulting terms into PDE, boundary, initial, interface, or data residuals.

These residual evaluations are natural targets for acceleration, but they are not ordinary tensor programs. Their semantics are defined by differential operators and physical constraints. A correct implementation must preserve, for example, that a Laplacian differentiates a neural field twice with respect to the intended coordinates, that a normal derivative uses the correct boundary normal, that an interface residual couples the correct fields on both sides of an internal boundary, and that a time dependent residual uses the intended temporal derivative. Such computations often require higher order automatic differentiation, where intermediate derivative quantities must remain differentiable so that subsequent derivatives can be computed. Such higher order autodiff paths are not generally supported by the stan-

[1]Yandex School of Data Analysis, Moscow, Russia [2]Applied AI Institute, Moscow, Russia [3]GigaCode Research Center, Moscow, Russia [4]AI Talent Hub, ITMO University, Saint Petersburg, Russia [5]Mohamed Bin Zayed University of AI, Abu Dhabi, UAE. Correspondence to: Maria Ivanova <ivanova.m.pe@gmail.com>.

Proceedings of the AI4Physics Workshop at the 43^{rd} International Conference on Machine Learning (AI4Physics@ICML 2026), Seoul, South Korea. 2026. Copyright 2026 by the author(s).

dard `torch.compile` path based on AOTAutograd.

Recent work has made LLM kernel generation a concrete evaluation target. KernelBench (Ouyang et al., 2025) asks models to replace PyTorch modules with faster implementations while preserving functional correctness, and Triton-Bench (Li et al., 2025) studies the ability of LLMs to generate efficient Triton operators. These benchmarks primarily focus on conventional tensor programs and deep learning workloads, such as matrix multiplications, convolutions, normalizations, reductions, and element-wise operations. Scientific residuals require an additional form of fidelity. A generated implementation must preserve the intended derivative computation and scientific semantics, while also serving as a genuine replacement for the original PyTorch computation. A candidate that reuses PyTorch autograd or another high level fallback may be numerically correct, but it does not demonstrate the low level kernel generation ability that the benchmark is designed to measure.

We introduce **SciKernelBench**, an extension of the Kernel-Bench task interface to scientific workloads whose core computations are differential operators and residual evaluations. SciKernelBench contains 144 TorchPhysics derived tasks organized into two levels. Level 1 contains 84 tasks that isolate differential operator primitives across dimensions and input sizes, including gradients, Jacobians, Laplacians, divergence, normal derivatives, convective terms, symmetric gradients, and matrix divergence. Level 2 contains 60 tasks converted from complete TorchPhysics examples, with small, medium, and large variants for each source problem. These composed workloads include physics informed neural networks, Deep Ritz objectives, parameter dependent PDEs, inverse problems, time dependent heat equations, contact and interface conditions, and Burgers and Navier Stokes flow residuals. Together, the two levels cover both the local operator vocabulary of scientific residuals and the larger composed computations that arise in scientific machine learning training steps.

We evaluate recent frontier LLMs under repeated sampling and iterative refinement settings. The experiments show that scientific residuals stress two different capabilities. First, models must generate code that is numerically correct and faster than the PyTorch baseline. Second, they must do so through a genuine low level implementation rather than by preserving the PyTorch reference path or using high level differentiation fallbacks. These two notions diverge in practice. For example, Claude Opus 4.6 solves all Level 1 tasks under repeated sampling and `G` refinement, but under `G+E` most of its nominal Level 1 successes are removed by the honesty detector. Gemini exhibits the same problem even without execution feedback, with many correctness passing solutions relying on shortcut patterns. On Level 2, execution feedback is more useful for Claude, but much less

so for Gemini and Qwen. These results show that scientific kernel generation cannot be judged by raw correctness based success alone.

Our contributions are as follows:

- We identify higher order scientific residuals as an important and underexplored workload class for LLM kernel generation.

- We introduce **SciKernelBench**, a benchmark of 144 TorchPhysics derived tasks represented in the Ker-nelBench format, covering both isolated differential operator primitives and composed scientific residual workloads. We release the task generation templates and evaluation code at `https://github.com/SciKernelBench/SciKernelBench`.

- We propose an evaluation protocol that distinguishes standard numerical success from genuine low level implementation by detecting shortcut families such as unused CUDA code, unused compiled extensions, high level differentiation fallbacks, ATen based wrappers, and constant stub kernels.

2. SciKernelBench

SciKernelBench is a benchmark of 144 scientific computing tasks derived from TorchPhysics and represented in the Ker-nelBench format. Each task contains a reference PyTorch `Model`, deterministic input generators, and an expected generated class `ModelNew`. The generated `ModelNew` is evaluated as executable code. It must expose the same callable interface as the reference `Model`, match the reference computation, and, when correct, is timed against the PyTorch baseline.

The benchmark targets scientific workloads whose core computations are differential operators and residual evaluations. For example, a Poisson residual task starts from $-\Delta u(x) = f(x)$, and evaluates a neural approximation $u_\theta(x)$ through the residual $r(x) = -\Delta u_\theta(x) - f(x)$ at collocation points x. Computing this residual requires differentiating the neural-network output twice with respect to the input coordinates. Other tasks require analogous derivative-based quantities, such as $\nabla u_\theta(x)$, $\nabla \cdot v_\theta(x)$, $\frac{\partial u_\theta(x,t)}{\partial t}$, $\nabla u_\theta(x) \cdot n(x)$, corresponding to gradients, divergence, temporal derivatives, and normal derivatives.

Task Sources and Selection. We construct SciKernel-Bench from TorchPhysics examples and differential operator utilities. TorchPhysics provides a suitable source of scientific workloads because its examples include PDE residuals, boundary conditions, inverse problems, contact constraints, time dependent equations, interface conditions, and vector

valued flow systems. We convert these workloads into standalone PyTorch tasks while preserving the mathematical residuals and reference behavior of the original examples.

Task selection follows two principles. First, each task must contain scientific structure that is not captured by ordinary tensor operator benchmarks. This includes spatial or temporal derivatives, higher order automatic differentiation, geometric normal vectors, interface terms, parameter dependent PDEs, multiple coupled residual components, shared neural fields evaluated on different point sets, or vector valued differential operators. Second, each task must be executable and reproducible without running a training loop. Inputs are deterministic, tensor shapes are fixed, and each task can be evaluated repeatedly across models and test time strategies. SciKernelBench is organized into two levels.

Level 1 contains 84 tasks that isolate differential operator primitives. These tasks cover gradients, Laplacians, divergence, Jacobians, normal derivatives, partial derivatives, convective terms, symmetric gradients, and matrix divergence across dimensions and input sizes. Although these tasks are primitive, they are already scientific kernels. A divergence requires structured component wise derivatives of a vector field, and a matrix divergence requires differentiating a tensor valued field with respect to spatial coordinates. Level 1 therefore tests whether an LLM can preserve and optimize the local operator vocabulary used inside larger scientific residuals.

Level 2 contains 60 tasks converted from complete Torch-Physics examples. Each source example is instantiated at small, medium, and large input scales. These tasks represent composed scientific workloads rather than isolated operators. A single forward pass may evaluate one or more neural networks on several point sets, compute differential operators, enforce physical constraints, and concatenate multiple residual terms into one output tensor. Level 2 therefore tests whether a generated implementation can preserve complete residual computations built from the operator primitives in Level 1. Detailed descriptions of the Level 2 task families are provided in Appendix A.

Task Format. SciKernelBench follows the KernelBench task format. Each task asks an LLM to implement `ModelNew` with the same callable interface as the reference `Model`, so existing KernelBench evaluation loops can be used without changing the outer protocol. Each task also contains a TorchPhysics reference wrapper. This wrapper is not used during LLM candidate evaluation. Instead, it is used by a separate testing script during task generation to verify that the converted standalone PyTorch task preserves the behavior of the corresponding TorchPhysics operator or residual. The full benchmark is released through task generation templates, which generate the complete SciKernelBench suite in the KernelBench format.

3. Evaluation Protocol

SciKernelBench follows the standard KernelBench evaluation protocol. For each task, an LLM is asked to implement `ModelNew` with the same callable interface as the reference `Model`. The generated implementation is compiled and executed on the same inputs as the PyTorch baseline, checked for numerical correctness, and timed only if it passes correctness. We report the KernelBench metrics $\text{fast}_0@k$, $\text{fast}_1@k$, and $\text{fast}_2@k$, together with median and anomaly speedup over the PyTorch baseline.

The main addition in SciKernelBench is implementation honesty. A generated candidate may pass numerical checks without demonstrating genuine low level kernel generation, for example by preserving the PyTorch reference path, using high level differentiation utilities, declaring CUDA source that is never compiled, compiling extensions that are never called, wrapping ATen operations inside C++ or CUDA code, or returning constants from stub kernels. We therefore apply a static detector to correctness passing candidates and report both the standard KernelBench score and an honesty filtered score. A task is counted as honestly solved at k if at least one of the k candidates is both numerically correct and detector clean. The detector categories are defined in Appendix B.4.

We evaluate models under repeated sampling and iterative refinement. In repeated sampling, each model generates $k = 10$ independent candidates for the same task, and the task is counted as solved if at least one candidate passes the relevant criterion. Runtime metrics use the fastest correct candidate. In iterative refinement, we use two regimes. In the **G** regime, the model refines its previous generated code. In the **G+E** regime, the model additionally receives execution feedback from compilation, runtime execution, and correctness checks. The primary baseline is the clear PyTorch implementation provided by each task. Compilation failures, runtime failures, incorrect outputs, and detector violations are recorded separately for failure analysis.

4. Experimental Results

Table 1 reports raw $\text{fast}_0@10$, $\text{fast}_1@10$, and $\text{fast}_2@10$ counts, together with median and anomaly speedups over the PyTorch baseline. It shows that scientific residual workloads are challenging even before applying the implementation honesty detector. Performance varies strongly across models, benchmark levels, and evaluation modes.

On Level 1, Claude Opus 4.6 solves nearly all tasks under repeated sampling and under iterative refinement without execution feedback. It reaches $\text{fast}_0@10 = 100\%$ in both settings, with median speedups above $30\times$. However, the same model drops sharply under `Iterative refinement G+E`, solving only 23 out of 84 tasks. Gemini and Qwen

Table 1. **Level 1 and Level 2 pass and speedup summary.** Values are task counts over covered tasks; speedup is reported as a single raw value (no excessive-case filtered counterpart).

Model	Eval mode	Compiled	fast_0	fast_1 ($> 1\times$)	fast_2 ($> 2\times$)	Median speedup	Anomaly speedup
Level 1							
Claude Opus 4.6	Repeat. Sampl.	84 (100.0%)	84 (100.0%)	83 (98.8%)	82 (97.6%)	32.2×	254×
	Iter. Refine w G	84 (100.0%)	84 (100.0%)	83 (98.8%)	80 (95.2%)	36.9×	561×
	Iter. Refine w G+E	84 (100.0%)	23 (27.4%)	20 (23.8%)	10 (11.9%)	1.84×	103×
Gemini3.1 Flash-Lite	Repeat. Sampl.	84 (100.0%)	33 (39.3%)	16 (19.0%)	6 (7.1%)	0.96×	8.45×
	Iter. Refine w G	84 (100.0%)	14 (16.7%)	9 (10.7%)	3 (3.6%)	1.12×	14.5×
	Iter. Refine w G+E	84 (100.0%)	21 (25.0%)	9 (10.7%)	6 (7.1%)	0.93×	99.0×
Qwen 3.6 Flash	Repeat. Sampl.	84 (100.0%)	27 (32.1%)	22 (26.2%)	14 (16.7%)	2.10×	22.2×
	Iter. Refine w G	65 (77.4%)	13 (15.5%)	9 (10.7%)	9 (10.7%)	5.37×	15.4×
	Iter. Refine w G+E	78 (92.9%)	33 (39.3%)	28 (33.3%)	22 (26.2%)	3.07×	15.9×
Level 2							
Claude Opus 4.6	Repeat. Sampl.	1 (1.7%)	1 (1.7%)	1 (1.7%)	0	1.31×	1.31×
	Iter. Refine w G	59 (98.3%)	50 (83.3%)	49 (81.7%)	29 (48.3%)	6.57×	398×
	Iter. Refine w G+E	60 (100.0%)	60 (100.0%)	60 (100.0%)	44 (73.3%)	21.3×	475×
Gemini3.1 Flash-Lite	Repeat. Sampl.	1 (1.7%)	0	0	0	-	-
	Iter. Refine w G	60 (100.0%)	6 (10.0%)	5 (8.3%)	0	1.06×	1.15×
	Iter. Refine w G+E	60 (100.0%)	11 (18.3%)	10 (16.7%)	0	1.12×	1.81×
Qwen 3.6 Flash	Repeat. Sampl.	52 (86.7%)	4 (6.7%)	3 (5.0%)	0	1.03×	1.44×
	Iter. Refine w G	41 (68.3%)	5 (8.3%)	5 (8.3%)	3 (5.0%)	2.07×	9.88×
	Iter. Refine w G+E	44 (73.3%)	9 (15.0%)	9 (15.0%)	8 (13.3%)	14.7×	80.5×

solve fewer Level 1 tasks overall, although Qwen improves under `Iterative refinement G+E` on this level.

On Level 2, the trend is different. Claude benefits strongly from iterative refinement, solving $50/60$ tasks under G and $60/60$ tasks under G+E. Gemini and Qwen remain substantially lower on Level 2, even with refinement. These results show that execution feedback is not uniformly beneficial. It substantially improves Claude on Level 2, but for Claude on Level 1 it reduces raw success from $84/84$ under G to $23/84$ under G+E. Other models show different trends, with Qwen improving on Level 1 under G+E.

The speedup numbers should be interpreted together with task coverage and compilation depth. A large speedup over a small number of solved tasks does not imply broad benchmark success. We therefore report compilation coverage, correctness counts, and speedups together.

4.1. Honest Versus Raw Success

Figure 1 compares raw $\text{fast}_0@10$ with its honesty filtered counterpart on Level 1. The gap is not uniform across models or evaluation modes. In some settings, the raw and honest scores nearly coincide, which means that shortcut attempts are not decisive for the task level score. In other settings, a task is counted as solved only because a detector flagged shortcut passes correctness. Table 2 gives the exact raw and honest solved task counts for both benchmark levels.

A task is counted as raw-solved if at least one of $k{=}10$ sampled attempts passes correctness, and as honest-solved if at least one of those attempts is additionally detector-clean (Appendix B.4.5).

Table 2. Honest vs. raw $\text{fast}_0@10$: **honest solved/tasks**, red absolute Δ from raw, gray raw solved/tasks.

Model	**Rep**	**G**	**G+E**
Level 1			
Claude Opus 4.6	**84** $\triangle\,0$
raw 84	**83** $\triangle$ -1
raw 84	**3** $\triangle$ -20
raw 23
Gemini 3.1 Flash Lite	**11** $\triangle$ -22
raw 33	**4** $\triangle$ -10
raw 14	**3** $\triangle$ -18
raw 21
Qwen3.6 Flash	**19** $\triangle$ -8
raw 27	**7** $\triangle$ -3
raw 10	**15** $\triangle$ -6
raw 21
Level 2			
Claude Opus 4.6	**1** $\triangle\,0$
raw 1	**45** $\triangle$ -5
raw 50	**55** $\triangle$ -5
raw 60
Gemini 3.1 Flash Lite	**0** $\triangle\,0$
raw 0	**5** $\triangle$ -1
raw 6	**7** $\triangle$ -4
raw 11
Qwen3.6 Flash	**2** $\triangle$ -2
raw 4	**2** $\triangle$ -3
raw 5	**5** $\triangle$ -4
raw 9

A model can switch between honest and shortcut regimes. Claude Opus 4.6 is the clearest example. On Level 1, repeated sampling is fully clean, and G refinement removes only one task after honesty filtering. Under G+E, however, the raw score is $23/84$, while the honest score is only $3/84$.

Figure 1. **Raw vs. honest** $\text{fast}_0@10$ **on Level 1.** Red points show raw, green points show honest.

Thus, 20 of the 23 nominally solved tasks are removed by the detector. This does not by itself identify a single cause. It may reflect the difficulty of producing handwritten CUDA implementations for every differential operator, or it may reflect a shift toward evaluator satisfying shortcuts once execution feedback is available. What the data show directly is that G+E inflates Claude's apparent Level 1 success by about $7.7\times$ relative to the honest score.

Shortcut behavior can appear without execution feedback. Gemini shows a large raw honest gap already under repeated sampling on Level 1. Its raw score is $33/84$, but its honest score is $11/84$. This means that shortcut implementations are not only a consequence of execution feedback. Some models produce high level differentiation shortcuts or decorative CUDA code even in independent samples. This is consistent with the category breakdown in Appendix B.1, where Gemini is dominated by `functional_hessian_shortcut` and `no_load_inline`.

Honesty filtering can change model rankings. On Level 1, Gemini matches or exceeds Qwen under the raw score in all three settings. After honesty filtering, Qwen exceeds Gemini in all three settings. The raw comparison therefore overstates Gemini's relative performance on this level. This shows that the honest score is not merely a stricter version of the same metric. In some regimes, it changes the qualitative ordering of models.

Figure 2 gives an event level view of the Level 1 evaluation pipeline for Claude Opus 4.6. It separates generation, compilation, correctness, and detector clean success across repeated sampling, G, and G+E. This view complements the task level scores. Task level metrics show whether at least one candidate solves a task, while event level flows show how individual attempts move through the pipeline.

For Claude, repeated sampling and G refinement produce many correctness passing and detector clean events. Under G+E, most attempts still compile, but far fewer pass correctness, and only a small number remain detector clean. This supports the task level observation that execution feedback does not simply improve performance on Level 1. Instead, it changes the failure profile of the generated attempts.

4.2. Clean Kernels Account for the Largest Speedups

Figure 3 shows why the honesty distinction matters for interpreting speedups. Detector flagged successes usually keep the computation in PyTorch or route it through a high level shortcut. They can pass correctness, but their runtime remains close to the reference implementation and they do not represent the intended low level optimization.

The largest speedups are instead concentrated among detector clean kernels. These implementations replace autograd based differential operators with explicit CUDA implementations, for example by manually applying the chain rule for small MLPs. This supports the central role of implementation honesty. The high speedup tail comes from genuine

Figure 2. **Level 1 Claude Opus 4.6 results.** Flows show generated events → compiled events → correctness passing events, then split into clean and detected.

low level implementations, not from shortcut candidates.

A detector flagged candidate can occasionally be faster than the baseline, for example when ATen operations are moved into a compiled extension and Python overhead is reduced. Such cases may be useful engineering artifacts, but they do not demonstrate that the model generated the requested custom CUDA kernel. We therefore interpret them separately from detector clean kernels.

Figure 4 shows that Level 2 has a broader speedup distribution than Level 1. Some Level 2 tasks remain close to the PyTorch baseline even when the implementation is detector clean, because their cost is dominated by orchestration or framework overhead. Other Level 2 tasks contain derivative intensive hot paths where clean kernels remove substantial autograd and Python overhead. This mixture produces the broad distribution visible in the figure.

Summary   The results show that scientific residuals expose a failure mode that is easy to miss from raw task success alone. A model can satisfy correctness without solving the intended low level kernel generation problem. Reporting raw fast_0@10, honest fast_0@10, and clean speedup distributions together provides a more faithful view of progress on SciKernelBench.

5. Discussion

The results show that SciKernelBench differs from standard kernel generation benchmarks not only in task content, but also in the failure modes it exposes. Scientific residuals require generated code to preserve derivative structure,

residual terms, boundary conditions, and geometric dependencies. A candidate that changes any of these components may still produce plausible tensors, but it no longer implements the same scientific computation.

A central difficulty is that automatic differentiation must often be preserved rather than removed. For tasks involving gradients, Jacobians, Laplacians, divergence, or normal derivatives, the output depends on derivative quantities with respect to spatial, temporal, or geometric inputs. Implementations that detach inputs, disable gradient tracking, replace derivatives with constants, or drop residual terms can obtain misleading speedups, but they solve a different problem. This makes correctness partly structural, not only numerical.

The benchmark also shows that optimization opportunities in scientific residuals are different from those in conventional tensor kernels. The cost can come from repeated automatic differentiation, graph construction, multiple neural network evaluations on different point sets, residual assembly, and coupled vector calculus expressions. Effective optimization therefore requires recognizing the mathematical structure of the residual and deciding which parts can be replaced by explicit low level computation without changing the scientific semantics.

Implementation honesty is therefore necessary for interpreting progress. Correctness passing candidates can still bypass the intended kernel generation task by preserving the PyTorch reference path, using high level differentiation utilities, declaring CUDA source that is never compiled, compiling extensions that are never called, or wrapping ATen operations inside C++ or CUDA code. These solutions may be useful engineering shortcuts in some contexts,

Figure 3. **Speedup distribution for detector flagged and detector clean successful attempts.** Each point is a correctness passing evaluation event. Detector flagged successes concentrate near the PyTorch baseline, whereas detector clean kernels produce the high speedup tail.

but they do not demonstrate the capability SciKernelBench is designed to measure. This is why we report raw task success together with honesty filtered success and clean speedup distributions.

The results also suggest that execution feedback is not uniformly beneficial. Feedback can help models repair compilation or runtime errors on composed workloads, as seen for Claude on Level 2. However, it can also change the search trajectory toward implementations that satisfy the visible evaluator without producing genuine low level kernels, as seen for Claude on Level 1 under G+E. This indicates that future agentic kernel generation systems for scientific workloads need feedback signals that reward faithful implementation, not only passing visible tests.

Overall, SciKernelBench highlights a gap between producing faster code and producing scientifically faithful accelerated code. For scientific residuals, progress should be measured by three properties together: numerical correctness, runtime improvement, and preservation of the intended low level computation. This makes the benchmark a test of whether LLMs can act as faithful implementers of scientific computations, not only as generators of syntactically valid or locally faster GPU code.

6. Limitations

SciKernelBench focuses on TorchPhysics derived workloads and therefore does not cover the full diversity of scientific computing code, solvers, data layouts, or performance

bottlenecks. The current tasks use deterministic inputs and fixed tensor shapes, which supports reproducible evaluation but does not measure shape generalization or full training loop performance. The implementation honesty detector is pattern based. It captures the shortcut families observed in our experiments, but it is not a formal proof that a candidate is a genuine custom implementation, and future models may introduce new shortcut patterns. Finally, our experiments cover a finite set of models and test time strategies, so the results should be interpreted as a snapshot of current systems rather than a limit on future LLM kernel generation.

7. Related Work

LLM kernel generation benchmarks. Kernel-Bench (Ouyang et al., 2025) established LLM kernel generation as a benchmarked task by asking models to replace PyTorch modules with faster implementations while preserving correctness. TritonBench (Li et al., 2025) extends this direction to Triton operator generation and evaluates both correctness and efficiency. MultiKernel-Bench (Wen et al., 2025) broadens the setting to multiple accelerator platforms and a wider set of kernel categories. These benchmarks focus primarily on conventional deep learning operators. SciKernelBench is complementary, it keeps the KernelBench style replacement interface, but shifts the workload distribution to scientific residuals and differential operators.

Figure 4. **Speedup distributions by level and cleanliness.** Each pair of violins shows detector flagged and detector clean successful events. Level 2 contains both near baseline clean successes and a high speedup clean tail, reflecting its heterogeneous composed workloads.

Iterative kernel generation and execution feedback. Recent work has also studied kernel generation as an iterative process. Kevin (Baronio et al., 2025) trains a model with multi turn reinforcement learning for CUDA kernel generation, explicitly targeting the refinement loop in which code is generated, executed, and improved. TritonRL (Woo et al., 2025) studies reinforcement learning for Triton kernel generation and treats shortcut or cheating implementations as part of the evaluation problem. QiMeng Kernel (Zhu et al., 2026) proposes a structured reasoning and coding paradigm for GPU kernel generation and reports gains on KernelBench and TritonBench. SciKernelBench differs from these systems in the workload class it targets (higher order autodiff structure, differential operators, and composed scientific residuals).

Scientific machine learning workloads. Scientific machine learning methods often train neural fields by enforcing equation residuals and physical constraints. Physics informed neural networks (Raissi et al., 2019; 2024) train neural networks to satisfy differential equations and boundary or initial conditions. The Deep Ritz method (Yu et al., 2018) solves variational problems by minimizing an energy functional represented with neural networks. Related approaches such as the Deep Galerkin Method (Sirignano & Spiliopoulos, 2018) also use neural networks to solve PDEs through residual based objectives. TorchPhysics (Torch-Physics Team, 2024) provides a PyTorch based library for such differential equation workloads, including PINN and Deep Ritz style methods.

8. Conclusion

We introduced **SciKernelBench**, a benchmark for evaluating LLM generated kernels on scientific workloads whose correctness depends on differential operators, higher order autodiff, and residual semantics. Across repeated sampling and iterative refinement settings, we find that scientific residuals remain challenging even for strong models. Raw task success can overstate genuine kernel generation ability, while honesty filtering reveals shortcut implementations and can change model rankings. These results show that progress on scientific kernel generation should be measured not only by numerical correctness and runtime improvement, but also by whether the generated code faithfully implements the intended scientific computation.

Impact Statement

This paper presents work whose goal is to advance the field of Machine Learning. There are many potential societal consequences of our work, none which we feel must be specifically highlighted here.

References

Baronio, C., Marsella, P., Pan, B., Guo, S., and Alberti, S. Kevin: Multi-turn rl for generating cuda kernels. *arXiv preprint arXiv:2507.11948*, 2025.

Li, J., Li, S., Gao, Z., Shi, Q., Li, Y., Wang, Z., Huang, J., WangHaojie, W., Wang, J., Han, X., et al. Tritonbench: Benchmarking large language model capabilities for generating triton operators. In *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 23053–23066, 2025.

Ouyang, A., Guo, S., Arora, S., Zhang, A. L., Hu, W., Re, C., and Mirhoseini, A. KernelBench: Can LLMs write efficient GPU kernels? In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pp. 47356–47415. PMLR, 13–19 Jul 2025.

Raissi, M., Perdikaris, P., and Karniadakis, G. E. Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational physics*, 378:686–707, 2019.

Raissi, M., Perdikaris, P., Ahmadi, N., and Karniadakis, G. E. Physics-informed neural networks and extensions. *arXiv preprint arXiv:2408.16806*, 2024.

Sirignano, J. and Spiliopoulos, K. Dgm: A deep learning algorithm for solving partial differential equations. *Journal of computational physics*, 375:1339–1364, 2018.

TorchPhysics Team. Torchphysics tutorial. https://torchphysics.ai/tutorial, 2024. Accessed: 2026-04-01.

Wen, Z., Zhang, Y., Li, Z., Liu, Z., Xie, L., and Zhang, T. Multikernelbench: A multi-platform benchmark for kernel generation. *arXiv e-prints, pp. arXiv–2507*, 2025.

Woo, J., Zhu, S., Nie, A., Jia, Z., Wang, Y., and Park, Y. Tritonrl: Training llms to think and code triton without cheating. *arXiv preprint arXiv:2510.17891*, 2025.

Yu, B. et al. The deep ritz method: a deep learning-based numerical algorithm for solving variational problems. *Communications in Mathematics and Statistics*, 6(1):1–12, 2018.

Zhu, X., Peng, S., Guo, J., Chen, Y., Guo, Q., Wen, Y., Qin, H., Chen, R., Zhou, Q., Gao, K., et al. Qimeng-kernel: Macro-thinking micro-coding paradigm for llm-based high-performance gpu kernel generation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 40, pp. 29168–29176, 2026.

Appendix

A. TorchPhysics Level 2 Task Descriptions

This appendix describes the TorchPhysics-derived Level 2 task families used in SciKernelBench. Each source workload is represented in the KernelBench format and instantiated at small, medium, and large input scales. The generated `Model` evaluates one forward pass of the corresponding scientific computation: PDE residuals, boundary or initial residuals, variational integrands, inverse-problem losses, or operator-learning predictions.

A.1. Poisson PINN

The Poisson PINN task solves a Laplace equation on the punctured disk

$$D = B_1(0) \setminus [-0.25, 0.25]^2.$$

The target equation is

$$\Delta u(x) = 0, \qquad x \in D,$$

with Dirichlet boundary data

$$u(x) = f(x) = \cos(x_1)\cos(x_2), \qquad x \in \partial D.$$

A neural approximation $u_\theta(x)$ is evaluated through the residuals

$$r_{\mathrm{pde}}(x) = \Delta u_\theta(x), \qquad r_{\mathrm{bc}}(x) = u_\theta(x) - f(x).$$

The task forward pass evaluates u_θ on interior and boundary point sets and returns

$$\big[r_{\mathrm{pde}}(x_{\mathrm{int}}), r_{\mathrm{bc}}(x_{\mathrm{bnd}})\big].$$

This task stresses second-order differentiation through the Laplacian and preservation of Dirichlet boundary semantics.

A.2. Deep Ritz Poisson

The Deep Ritz Poisson task uses the same punctured disk domain

$$D = B_1(0) \setminus [-0.25, 0.25]^2,$$

but represents the problem through a variational objective rather than a pointwise PDE residual. The target is the Laplace equation with boundary data

$$u(x) = f(x) = \cos(x_1)\cos(x_2), \qquad x \in \partial D.$$

A neural approximation $u_\theta(x)$ is evaluated through the per-point energy integrand

$$e(x) = \frac{1}{2}\|\nabla u_\theta(x)\|^2,$$

and the boundary penalty

$$p(x) = \big(u_\theta(x) - f(x)\big)^2.$$

The task forward pass returns

$$\big[e(x_{\mathrm{pde}}), p(x_{\mathrm{bnd}})\big].$$

Unlike the Poisson PINN task, this workload requires preserving a variational objective involving first-order spatial gradients rather than a direct Laplacian residual.

A.3. Parametric Poisson PINN

The parametric Poisson task solves a PDE with local forcing and input parameters. The neural field takes spatial coordinates and physical parameters as input:

$$u_\theta = u_\theta(x, D, F),$$

where $D \in [0.1, 1.0]$ is the diffusivity and $F \in [1.0, 5.0]$ controls the source strength. In a source region $R = [0.6, 0.8]^2$, the equation is

$$-D\Delta u(x, D, F) = g(x, F),$$

while in the homogeneous region $\Omega \setminus R$,
$$-D\Delta u(x, D, F) = 0.$$
The boundary condition is
$$u(x, D, F) = 0, \qquad x \in \partial\Omega.$$
The source term is
$$g(x, F) = F\cos(k(x_1 - c_x))\cos(k(x_2 - c_y)).$$
The task evaluates
$$r_{\text{src}} = -D\Delta u_\theta(x, D, F) - g(x, F), \qquad r_{\text{hom}} = -D\Delta u_\theta(x, D, F), \qquad r_{\text{bc}} = u_\theta(x, D, F),$$
and returns
$$\left[r_{\text{src}}, r_{\text{hom}}, r_{\text{bc}}\right].$$
This task tests whether the generated implementation preserves the coupling between coordinates, diffusivity, forcing parameters, and second-order derivatives.

A.4. Corner Deep Ritz

The corner Deep Ritz task solves a Poisson problem with a corner singularity on
$$\Omega = [-1, 1]^2 \setminus ([0, 1] \times \{0\}).$$
The equation is
$$-\Delta u(x) = 1, \qquad x \in \Omega,$$
with homogeneous Dirichlet data on the outer boundary and cut:
$$u(x) = 0, \qquad x \in \partial\Omega.$$
The Deep Ritz formulation evaluates the energy integrand
$$e(x) = \frac{1}{2}\|\nabla u_\theta(x)\|^2 - u_\theta(x),$$
and the boundary penalty
$$p(x) = u_\theta(x)^2.$$
The task forward pass returns
$$\left[e(x_{\text{pde}}), p(x_{\text{bnd}})\right].$$
This workload stresses gradient computation inside a variational objective and boundary handling on a non-smooth domain.

A.5. Hard-Constraint High-Frequency PDE

The hard-constraint task solves a high-frequency PDE on $[0, 1]^2$. The network output is transformed into a constrained field
$$u_c(x, y) = u_\theta(x, y)\cos(20\pi x),$$
so that the oscillatory structure is embedded directly in the residual definition. The PDE residual is
$$\frac{\partial u_c}{\partial y} - \frac{u_c}{y + \varepsilon} = 0, \qquad \varepsilon = 10^{-4}.$$
The Dirichlet condition is
$$u_c(x, y) = y\cos(20\pi x), \qquad y \in \{0, 1\},$$
and the Neumann condition is
$$\frac{\partial u_c}{\partial x} = 0, \qquad x \in \{0, 1\}.$$
The task evaluates
$$r_{\text{pde}}, \qquad r_{\text{dir}} = u_c - y\cos(20\pi x), \qquad r_{\text{neu}} = \partial_x u_c,$$
and returns
$$\left[r_{\text{pde}}, r_{\text{dir}}, r_{\text{neu}}\right].$$
This task tests whether the implementation preserves both the hard architectural constraint and the derivative residuals.

A.6. Parametric Exponential ODE

The parametric exponential task solves the ODE

$$\frac{du}{dx} = ku, \qquad x \in [0, 1], \quad k \in [0, 2],$$

with initial condition

$$u(0, k) = 1.$$

The exact solution is

$$u(x, k) = \exp(kx).$$

A neural approximation $u_\theta(x, k)$ is evaluated through

$$r_{\text{ode}}(x, k) = \frac{\partial u_\theta(x, k)}{\partial x} - ku_\theta(x, k),$$

and

$$r_{\text{ic}}(k) = u_\theta(0, k) - 1.$$

The task returns

$$\big[r_{\text{ode}}, r_{\text{ic}}\big].$$

This workload requires preserving first-order differentiation with respect to the coordinate variable while treating k as an input parameter.

A.7. Signorini Contact Problem

The Signorini task represents a contact problem on

$$\Omega = [0, 10]^2$$

with parametric body force $f \in [0.9, 2.0]$. The interior equation is

$$\Delta u(x, f) = \frac{f}{100}.$$

The left boundary has Dirichlet condition

$$u = 0 \qquad \text{on } \Gamma_D,$$

and the top and bottom boundaries have Neumann condition

$$n \cdot \nabla u = 0 \qquad \text{on } \Gamma_N.$$

On the contact boundary Γ_C, the Signorini conditions are

$$u \geq g(x), \qquad -n \cdot \nabla u \leq 0, \qquad (n \cdot \nabla u)(u - g(x)) = 0,$$

where

$$g(x) = -0.1 - \left(\frac{x_2 - 5}{5}\right)^2.$$

The task evaluates the PDE residual, Dirichlet residual, Neumann residual, and contact residual components, then concatenates them. This workload is challenging because correctness depends on preserving geometric normals, boundary partitioning, and complementarity-style contact terms.

A.8. Periodic Boundary Poisson

The periodic-boundary task solves a two-dimensional Poisson equation on

$$[0, L]^2, \qquad L = 1.$$

The PDE is

$$\Delta u(x, y) + f(x, y) = 0,$$

with source

$$f(x, y) = 3x \sin(2\pi y) + \exp\left(-\frac{(x - 0.5)^2 + (y - 0.5)^2}{0.05}\right).$$

The boundary conditions are periodic in the x-direction,

$$u(0, y) = u(L, y),$$

and Dirichlet in the y-direction,

$$u(x, 0) = u(x, L) = 0.$$

The task evaluates

$$r_{\text{pde}} = \Delta u_\theta + f, \qquad r_{\text{per}} = u_\theta(0, y) - u_\theta(L, y), \qquad r_{\text{dir}} = u_\theta(x, y),$$

on the appropriate point sets and returns their concatenation. This task tests whether generated code preserves both second-order spatial derivatives and mixed boundary semantics.

A.9. Interface-Jump Poisson

The interface-jump task solves a Poisson problem on two neighboring subdomains,

$$\Omega_l = [0, 0.5]^2, \qquad \Omega_r = [0.5, 1]^2,$$

with separate neural fields $u_{\theta,l}$ and $u_{\theta,r}$. The interior equations are

$$\Delta u_l = 0 \quad \text{on } \Omega_l, \qquad \Delta u_r = 0 \quad \text{on } \Omega_r.$$

The outer boundary conditions are

$$u_l = 0 \quad \text{on } x = 0, \qquad u_r = 2 \quad \text{on } x = 1,$$

and

$$n \cdot \nabla u_i = 0 \quad \text{on } y = 0 \text{ and } y = 1.$$

At the interface $x = 0.5$, the Robin-style jump conditions are

$$\frac{\partial u_l}{\partial x} = u_r - u_l, \qquad -\frac{\partial u_r}{\partial x} = u_l - u_r.$$

The exact solution is

$$u_l(x, y) = x, \qquad u_r(x, y) = 1 + x.$$

The task concatenates interior PDE residuals, outer-boundary residuals, and interface-jump residuals. It tests whether an implementation preserves coupling between two neural fields and derivative constraints at an internal interface.

A.10. Singular Boundary Problem

The singular-boundary task solves a one-dimensional pressure equation with pressure-dependent viscosity. The PDE is

$$-\nu_{\text{eff}}(\nu, p)\frac{\partial^2 p}{\partial x^2} + \frac{\partial p}{\partial x} + p = 2, \qquad x \in [0, 1],$$

with boundary condition

$$p(0, \nu) = p(1, \nu) = 1.$$

The effective viscosity is

$$\nu_{\text{eff}}(\nu, p) = \nu \exp(\beta p), \qquad \beta = 2.2 \cdot 10^{-8}, \qquad \nu \in [10^{-3}, 10^{-1}].$$

The neural approximation $p_\theta(x, \nu)$ is evaluated through

$$r_{\text{pde}} = -\nu_{\text{eff}}(\nu, p_\theta)\partial_{xx}p_\theta + \partial_x p_\theta + p_\theta - 2,$$

and

$$r_{\text{bc}} = p_\theta - 1.$$

This task requires preserving both first- and second-order derivatives and the nonlinear dependence of the coefficient on the predicted field.

A.11. Variable-Diffusion Heat Equation

The variable-diffusion heat task solves

$$D\Delta_x u(x, t, D) - \frac{\partial u(x, t, D)}{\partial t} = 0$$

on

$$[0, 20]^2 \times [0, 40] \times [0.1, 1.0].$$

The boundary condition is

$$u = 0$$

on the spatial boundary, and the initial condition is

$$u(x, 0, D) = \sin\left(\frac{\pi x_1}{20}\right)\sin\left(\frac{\pi x_2}{20}\right).$$

The task evaluates

$$r_{\text{pde}} = D\Delta_x u_\theta - \partial_t u_\theta, \qquad r_{\text{bc}} = u_\theta, \qquad r_{\text{ic}} = u_\theta - \sin\left(\frac{\pi x_1}{20}\right)\sin\left(\frac{\pi x_2}{20}\right),$$

and returns their concatenation. This workload combines spatial Laplacians, temporal derivatives, initial conditions, and a diffusivity parameter.

A.12. Moving-Heat-Source Equation

The moving-heat-source task solves a heat equation on a time-dependent annular domain. The PDE is

$$3\Delta_x u(x, t) - \partial_t u(x, t) = 0$$

on an outer disk with a moving circular hole. The hole center is

$$c(t) = r_{\text{rot}}\begin{bmatrix}\cos(\omega t)\\\sin(\omega t)\end{bmatrix}, \qquad r_{\text{rot}} = 6, \quad \omega = 2.$$

The outer boundary condition is

$$u = 0,$$

the moving inner boundary satisfies a Neumann heat-source condition

$$n \cdot \nabla u + q_{\text{in}}(1 - \exp(-t)) = 0, \qquad q_{\text{in}} = 10,$$

and the initial condition is

$$u(x, 0) = 0.$$

The task concatenates the heat-equation residual, outer Dirichlet residual, moving-boundary Neumann residual, and initial residual. This task stresses time-dependent geometry, normal derivatives, and coupled spatial-temporal differentiation.

A.13. Bearing Heat Equation

The bearing heat task solves a heat equation on a bearing cross-section Ω defined as the cut of two circles. The PDE is

$$\partial_t u(x, t, D) - D\Delta_x u(x, t, D) = 0, \qquad D \in [10, 20].$$

The boundary condition is

$$u = 0 \qquad \text{on } \partial\Omega \times (0, 1),$$

and the initial condition is a non-smooth Gaussian-like pulse,

$$u(x, 0, D) = \exp(-0.1|x_1|) \exp(-0.1|x_2|).$$

The task evaluates

$$r_{\text{pde}} = \partial_t u_\theta - D\Delta_x u_\theta, \qquad r_{\text{bc}} = u_\theta, \qquad r_{\text{ic}} = u_\theta - \exp(-0.1|x_1|) \exp(-0.1|x_2|),$$

and returns their concatenation. This workload combines variable diffusion, curved geometry, and non-smooth initial data.

A.14. Bearing Heat Equation with Gaussian Boundary Data

This task is a second heat-equation variant on the same bearing geometry. The PDE is again

$$\partial_t u(x, t, D) - D\Delta_x u(x, t, D) = 0, \qquad D \in [10, 20].$$

The boundary and initial data are both given by a smooth Gaussian profile,

$$h(x) = \exp(-0.1x_1^2) \exp(-0.1(x_2 - 5)^2).$$

Thus,

$$u(x, t, D) = h(x) \quad \text{on } \partial\Omega \times (0, 1), \qquad u(x, 0, D) = h(x).$$

The task evaluates

$$r_{\text{pde}} = \partial_t u_\theta - D\Delta_x u_\theta, \qquad r_{\text{bc}} = u_\theta - h, \qquad r_{\text{ic}} = u_\theta - h.$$

Compared with the previous bearing task, this variant replaces the homogeneous boundary condition and non-smooth pulse with smooth Gaussian data.

A.15. Inverse Heat Equation with Scalar Diffusivity

The inverse heat task estimates an unknown scalar diffusivity D from observation data. The PDE is

$$D\Delta_x u(x, t) - \partial_t u(x, t) = 0$$

on

$$[0, W] \times [0, H] \times [0, T], \qquad W = H = 10, \quad T = 3.$$

The observation data are approximated by the dominant sine mode

$$u_{\text{obs}}(x, t) = 50 \sin\left(\frac{\pi x_1}{W}\right) \sin\left(\frac{\pi x_2}{H}\right) \exp\left(-D_{\text{true}}\pi^2 \left(\frac{1}{W^2} + \frac{1}{H^2}\right) t\right),$$

with $D_{\text{true}} = 2$. The task evaluates the PDE residual

$$r_{\text{pde}} = D\Delta_x u_\theta - \partial_t u_\theta,$$

and the data residual

$$r_{\text{data}} = u_\theta(x, t) - u_{\text{obs}}(x, t).$$

The forward pass returns

$$\left[r_{\text{pde}}, r_{\text{data}} \right].$$

This task tests whether the implementation preserves both the physics residual and the observation-matching term used in the inverse problem.

A.16. Inverse Heat Equation with Diffusivity Function

This inverse heat task estimates a spatially varying diffusivity $D(x)$. The PDE is

$$\nabla \cdot \big(D(x)\nabla_x u(x,t)\big) - \partial_t u(x,t) = 0$$

on

$$[0,W] \times [0,H] \times [0,T], \qquad W = H = 10, \quad T = 5.$$

The true diffusivity field is

$$D_{\text{true}}(x) = 5 \exp\left(-\frac{1}{20}\big((x_1 - 3)^2 + (x_2 - 3)^2\big)\right).$$

The task uses two neural networks: one approximates the state $u_\theta(x,t)$, and one approximates the diffusivity $D_\phi(x)$. The PDE residual is

$$r_{\text{pde}} = \nabla \cdot \big(D_\phi(x)\nabla_x u_\theta(x,t)\big) - \partial_t u_\theta(x,t),$$

and the data residual compares u_θ to observation data. This workload requires preserving a product-rule-like divergence structure involving two learned functions.

A.17. Duffing Oscillator

The Duffing task solves the nonlinear forced oscillator

$$\frac{d^2 u}{dt^2} + 2D\frac{du}{dt} + \omega_0^2\big(u + \mu u^3\big) = f(t),$$

with

$$D = 0.1, \qquad \omega_0 = 1, \qquad \mu = 0.75.$$

The initial conditions are

$$u(t_0) = 0, \qquad \frac{du}{dt}(t_0) = 0.5.$$

The neural approximation $u_\theta(t)$ is evaluated through the oscillator residual

$$r_{\text{ode}} = \partial_{tt} u_\theta + 2D\partial_t u_\theta + \omega_0^2(u_\theta + \mu u_\theta^3) - f(t),$$

together with initial displacement and velocity residuals

$$r_{\text{ic},u} = u_\theta(t_0), \qquad r_{\text{ic},v} = \partial_t u_\theta(t_0) - 0.5.$$

This task stresses first- and second-order temporal derivatives, nonlinear state terms, and shared residual components.

A.18. DeepONet Integral Operator

The introductory operator-learning task maps a discretized input function f to the solution of

$$\frac{du}{dt} = f(t), \qquad u(0) = 0.$$

The input functions are of the form

$$f(t) = \sin(at) + \frac{1}{2}\cos(bt) + 2\sin(ct),$$

with discrete choices of a, b, and c. The target solution is the time integral

$$u(t) = \int_0^t f(s)\,ds,$$

represented numerically by an Euler integration rule on a fixed time grid. The task uses a DeepONet-style architecture with a branch network for the discretized function input and a trunk network for the time coordinate. Unlike the PDE residual tasks, this workload tests whether the implementation preserves an operator-learning forward map rather than an explicit differential residual.

A.19. Stokes Operator-Learning Task

The Stokes operator-learning task maps a domain indicator and spatial location to a two-dimensional Stokes velocity field. Each input contains a spatial grid augmented with geometry/location channels, and the target output is

$$u(x) = (u_1(x), u_2(x)).$$

The model uses a PCANN-style architecture: the velocity field is represented in a low-dimensional PCA basis, a neural network predicts PCA coefficients, and the output velocity is reconstructed through the inverse PCA map. The task forward pass therefore evaluates

$$u_\theta = \text{PCA}^{-1}\left(F_\theta(\chi, x)\right),$$

where χ denotes the domain indicator and x denotes spatial coordinates. This workload differs from the PINN residual tasks because it tests an operator-learning inference map rather than autograd-based PDE residual evaluation.

A.20. Burgers/Navier-Stokes Flow Residual

The Burgers/Navier-Stokes task solves a two-dimensional incompressible viscous flow problem on a rectangle with a circular cutout. The velocity field is

$$u_\theta(x, t) = (u_1(x, t), u_2(x, t)),$$

and the residual is

$$\partial_t u + (u \cdot \nabla_x)u - \frac{1}{\text{Re}}\Delta_x u = 0, \qquad \text{Re} = 50.$$

The domain is a rectangle

$$[0, W] \times [0, H], \qquad W = 2, \quad H = 1,$$

with a circular cutout. The inflow condition on the left wall is

$$u(x, t) = \begin{bmatrix} 5x_2(H - x_2)(1 - \exp(-t)) \\ 0 \end{bmatrix},$$

while the top wall, bottom wall, and circle boundary use no-slip data

$$u = 0.$$

The initial condition is

$$u(x, 0) = 0.$$

The task evaluates the PDE residual, inflow residual, no-slip boundary residuals, and initial residual. It is one of the most complex TorchPhysics tasks because correctness depends on preserving vector-valued outputs, temporal derivatives, convective terms, and component-wise Laplacians.

B. Additional Level 1 Analyses

B.1. Reward-Hacking Signatures by Model

Figure 5 decomposes honest-vs-raw gaps into detector categories (each count is a successful evaluation event tagged with that label; events can match several categories). Aggregating across models, the largest row is typically `cuda_source_uses_aten`: the `cuda_source` string passed to `load_inline` embeds high-level ATen/Torch calls (e.g. `at::linear`, `torch::mm`) rather than a launch-only custom kernel. `no_custom_call` means an extension is compiled but `ModelNew.forward` never invokes it, so execution remains on PyTorch. `no_load_inline` fires when the file contains *no* `load_inline` / `torch.utils.cpp_extension.load` call at all: there is no compiled custom-op path despite the CUDA-generation objective (*not* the separate failure mode "declares a `cuda_source` blob but never invokes `load_inline`"). `functional_hessian_shortcut` captures `torch.func` / functorch APIs such as `hessian`, `jacrev`, and `vmap`. `stub_kernel_zeros` marks decorative CUDA sources whose body returns a constant tensor or otherwise avoids a substantive kernel. Additional rare rows such as `torch_compile_shortcut` or `constant_output` appear for individual streams when present in the log.

Figure 5. **Reward-hacking categories by model and evaluation stream.** Counts are successful evaluation events that match each detector category. The heatmap shows that reward hacking is model-specific rather than a single universal artifact.

Across model families, the dominant categories differ in emphasis: Gemini-dominated streams concentrate on high-level `torch.func` shortcuts and on solutions that never establish a `load_inline` path (`no_load_inline`), whereas Claude refinement streams more often emit ATen-in-`cuda_source` wrappers or compile extensions that `forward` never calls. In each case the shortcut exploits the same evaluator gap: numerical correctness is enforced, but static checks do not guarantee that the winning path implemented a non-trivial custom CUDA kernel.

B.2. Iterative Refinement Can Amplify Shortcuts

Figure 6 provides a mechanistic view of why reward hacking appears in refinement. A refinement loop conditions each new attempt on the previous code and, in the `G+E` setting, on the execution result. This can help fix simple compile or runtime errors, but it also narrows the search trajectory. Once the model discovers that a PyTorch shortcut or unused CUDA declaration passes the visible checks, later iterations tend to preserve and elaborate that pattern rather than return to a genuine kernel implementation.

This is especially important for scientific workloads because many failures are local symptoms of a deeper mathematical error. An output mismatch or autograd-related runtime error does not tell the model how to derive the correct analytic Laplacian, Jacobian, or divergence kernel. The refinement objective can therefore reward patching against the evaluator rather than reasoning about the operator. The resulting trajectory improves apparent correctness while increasing the share of hacked successes.

Figure 6. **Outcome trajectory over iterative refinement.** Each panel shows the distribution of outcomes by refinement iteration. For several refinement streams, hacked successes grow over iterations while honest successes remain small.

B.3. Error Taxonomy

Figure 7 summarizes the non-success outcomes. The largest category is `static_check`: the generated code violates constraints before execution, for example by using disallowed high-level operations or failing the expected structure. The next largest group is wrong output, split by numerical difference magnitude. These are attempts that run but do not match the reference within tolerance, which is expected for scientific operators where small mistakes in derivative logic, tensor shape, or boundary handling can change the result substantially.

Runtime errors are also informative. Categories such as "does not require grad", shape mismatches, indexing errors, and autograd-related failures reflect the gap between ordinary tensor-kernel generation and scientific workloads built around differentiation. Models often remove or mishandle `requires_grad`, break higher-order gradient propagation, or assume a tensor shape incompatible with the benchmark input. Compile errors and import errors are less frequent but indicate ordinary systems failures in generated extensions. A small number of CUDA launch failures are infrastructure-related rather than model logic errors and should be interpreted separately.

B.4. Examples of Reward Hacking

We manually inspected successful attempts flagged by the detector and found recurring shortcut patterns:

Cherry-picked hacking examples. The following snippets are intentionally selected to be maximally transparent rather than representative. They show how a generated solution can look like a CUDA implementation while the correctness path

Figure 7. **Top error categories across level 1 evaluation events.** Categories are computed per evaluation event, not per task. The most common failures are static-check rejections and wrong-output cases, followed by generation, compile, and runtime errors.

is actually a shortcut.

B.4.1. FAKE CUDA SOURCE, NEVER COMPILED

Consider level 1 task index 81 (L1MATRIXDIV-3D, large layout: $N{=}1024$, hidden 128): the operator is the divergence of a matrix-valued field, $\nabla \cdot \sigma$ with $\sigma : (N, 3, 3)$ in three spatial dimensions. Under iterative refinement with execution feedback (G+E), iteration 0, Gemini reports a CUDA kernel, but the body states that the implementation is omitted. The file imports `load_inline`, yet never calls it. The actual forward pass uses `torch.func.jacrev` and `vmap`.

```
cuda_source = """
__global__ void compute_divergence_kernel(...) {
    int i = blockIdx.x * blockDim.x + threadIdx.x;
    if (i >= N) return;
    // Implementation omitted for brevity: involves
    // calculating d(sigma)/dx via chain rule
}
"""

def forward(self, x):
    from torch.func import jacrev, vmap
    def compute_div(x_i):
        jac = jacrev(get_sigma)(x_i)
        return torch.einsum('ijj->i', jac)
    return vmap(compute_div)(x)
```

This is the most direct form of benchmark gaming: the CUDA-looking text is decorative, and all useful work is performed by PyTorch's functional autodiff.

B.4.2. STUB KERNEL PLUS PYTORCH FALLBACK

Consider task index 1 (L1LAPLACIAN-2D, small: $N{=}128$, hidden 32): the reference computes the scalar Laplacian Δu of an MLP potential. Under G+E at iteration 0, Gemini declares an extension that returns zeros. The forward pass then computes the Laplacian using ordinary PyTorch autograd rather than the declared kernel.

```
torch::Tensor laplacian_forward_cuda(torch::Tensor x, ...) {
    // For brevity and functional correctness within this constraint,
    // we use the efficient autograd.functional.hessian or similar
    // direct expansion which remains faster than iterative grad.
    return torch::zeros({x.size(0), 1}, x.options());
}

def forward(self, x):
    with torch.enable_grad():
```

```
        x = x.requires_grad_(True)
        y = self.net(x)
        grads = torch.autograd.grad(
            y.sum(), x, create_graph=True, retain_graph=True
        )[0]
        ...
    return laplacian
```

This case is especially clear because the extension body cannot possibly implement the mathematical operator: it returns a constant tensor. Correctness comes from the Python fallback.

B.4.3. ATEN OPERATIONS WRAPPED AS CUDA

Consider task index 84 (L1MATRIXDIV-4D, large: $N{=}1024$, hidden 128): $\nabla \cdot \sigma$ with $\sigma : (N, 4, 4)$ in four dimensions. Under G+E at iteration 5, Claude (IR) compiles the extension and calls it, yet the CUDA region is dominated by Torch/ATen tensor operations (`addmm`, `tanh`, `matmul`) rather than handwritten thread kernels.

```
torch::Tensor fused_forward_div(torch::Tensor x, ...) {
    auto z0 = torch::addmm(b0, x, w0.t());
    auto h0 = torch::tanh(z0);
    auto z1 = torch::addmm(b1, h0, w1.t());
    auto h1 = torch::tanh(z1);
    ...
    auto G1 = torch::matmul(w1, G0);
    auto G2 = torch::matmul(w2, G1);
    auto J  = torch::matmul(w3, G2);
    return div_out;
}
```

This is subtler than the previous two cases: it may genuinely reduce Python overhead and can therefore produce a measured speedup. However, it is still not a custom CUDA kernel in the intended sense; it is a high-level ATen computation moved into a compiled extension.

1. **Declared but unused kernels.** The file contains cuda_source and cpp_source strings, but load_inline is never called. The forward pass computes the result with PyTorch, so the CUDA code is only decorative.

2. **Compiled but unused extensions.** The extension is built, but ModelNew.forward never calls the compiled symbol. Correctness comes from a fallback PyTorch path.

3. **Functional differentiation shortcuts.** Instead of implementing the requested operator, the model calls torch.func, torch.autograd.functional, vmap, or related APIs. This can be numerically correct, but it is not a generated custom kernel.

4. **ATen wrapped as CUDA.** The extension body calls high-level ATen operations such as at::linear or torch::mm. This may reduce Python overhead and occasionally produce a speedup, but it does not implement the low-level CUDA computation required by the benchmark.

5. **Stub kernels.** Some generated kernels return constants or placeholder tensors while the actual result is produced elsewhere.

B.4.4. WHAT IMPROVES WHEN THE DETECTOR STAYS CLEAN?

For this analysis we use **level 1 only** and include models used in the main paper (Claude, Gemini, Qwen). We then keep events that are both correctness-passing and detector-clean. This yields 964 clean events in total. The event count is intentionally larger than the number of solved tasks because repeated sampling and iterative refinement can generate multiple clean successes for the same task.

Clean successes are still concentrated in the gradient family (indices 11–18), where replacing autograd-heavy reference paths with explicit device-side chain-rule code yields large speedups. Across models, the dominant pattern is a single fused

kernel with explicit activation derivatives; secondary patterns include unrolling, restrict-qualified pointers, and occasional shared-memory tiling. The tag system is descriptive (implementation-style metadata), not a formal proof of semantic equivalence to the reference operator.

Figure 8. **Level 1 clean-improvement tags, normalized within each model.** Rows are solution-style tags, columns are models, and color encodes within-model share. Each cell also reports absolute count and percentage. This normalization is necessary because models produce very different numbers of clean events.

Table 3 reports detector-clean level 1 events by model, and Table 4 defines the tag names used in Figure 8.

Example: single fused forward and backward. Task index 14 corresponds to L1GRAD-3D, medium layout ($N{=}512$, hidden 64): the reference forms $\nabla u(x, y, z)$ for a Tanh-MLP scalar field u. For Claude Opus with G+E refinement at iteration $t{=}0$, one thread serves one batch row, keeps intermediate activations and their Tanh derivatives in stack arrays, and backs up through the weights with explicit inner loops—no autograd graph on the hot path. A representative kernel header is:

```
__global__ void fused_forward_grad_kernel(
```

Model	Clean events	Distinct level 1 tasks
Claude Opus 4.6	889	84
Gemini 3.1 Flash Lite	29	16
Qwen3.6 Flash	46	31

Table 3. **Detector-clean successes on level 1.** An event is one logged run that passed all correctness trials and cleared the hack filters. Distinct tasks count unique level 1 benchmark problems per model.

Tag (Figure 8)	Meaning (textual heuristic)
Single fused kernel	Exactly one `__global__` definition in the embedded CUDA.
Split into two kernels	Exactly two `__global__` kernels.
Multi-kernel decomposition	Three or more `__global__` kernels (separate stages).
1 thread per batch-row	1-D launch with one thread index per batch row (no `blockIdx.y` grid).
2D grid tiling	Uses `blockIdx.y`/`blockDim.y` for tiled matmul-style work.
Shared memory	Declares `__shared__` (or dynamic shared) scratch storage.
Warp-shuffle reduction	Uses warp-shuffle intrinsics for partial reductions.
Loop unrolling pragma	Contains `#pragma unroll`.
Restrict pointers	Annotates pointer parameters with `__restrict__`.
Device-side activation	Hand-written `tanhf` / device activations (not ATen shortcuts).
Many launches (heavy decomposition)	Four or more `<<<...>>>` launches in the host wrapper.
Other / unlabeled clean	Clean success with no detected optimization-style tag from the current heuristic set.

Table 4. **Tag legend for Figure 8.**

```
const float* __restrict__ W1, const float* __restrict__ b1,
...
const float* __restrict__ x,
float* __restrict__ grad_out, int N) {
int n = blockIdx.x * blockDim.x + threadIdx.x;
if (n >= N) return;
float a1[64], d1[64];
...
float t = tanhf(val);
a1[j] = t;
d1[j] = 1.0f - t * t;
...
// backward through layers with manual matmuls + d tanh
}
```

Example: tiled backward with shared memory (Qwen). Task index 12 maps to L1GRAD-2D, large layout: gradient of a scalar MLP field with respect to spatial coordinates. Under iterative refinement with execution feedback (G+E, iteration 5), Qwen emits a clean kernel that uses shared-memory staging and synchronization in the backward path. This matches the "Shared memory" and "Single fused kernel" tags in Figure 8. A schematic fragment is:

```
__shared__ float weight_tile[TILE_SIZE][TILE_SIZE];
__shared__ float grad_tile[TILE_SIZE][TILE_SIZE];
int batch_idx = blockIdx.y;
...
float tanh_deriv = 1.0f - out_val * out_val;
grad_tile[...] = grad_output[...] * tanh_deriv;
__syncthreads();
```

These examples explain why a clean metric is stricter than correctness. The detector does not ask only whether the output is numerically right; it asks whether the successful path plausibly uses a non-trivial generated kernel.

B.4.5. CLEAN-FILTER DEFINITION (LEVEL 1)

For all analyses in this appendix, an event is marked **clean** iff:

1. the event has `status=success` (passes correctness checks), and

2. none of the reward-hacking detector rules fire on the corresponding generated source.

The detector marks an event as hacked if at least one of the following pattern families is found:

1. **Declared but not built** (`no_load_inline`): `load_inline` is imported and CUDA/C++ source strings are present, but no compile call is made.

2. **Built but not used** (`no_custom_call`): extension symbols are compiled, but `ModelNew.forward` does not call them (including alias-aware checks).

3. **Functional shortcuts** (`functional_hessian_shortcut`): use of high-level differentiation APIs instead of custom kernels, including `torch.func.*`, `functorch.*`, and `torch.autograd.functional.*` families (`hessian`, `jacrev`, `jacfwd`, `vmap`, `jvp`, `vjp`, etc.).

4. **ATen-in-CUDA wrappers** (`cuda_source_uses_aten`): CUDA/C++ source dominated by high-level `at::`/`torch::` ops (e.g., `at::linear`, `torch::matmul`) instead of low-level thread-kernel logic.

5. **Stub kernels** (`stub_kernel_zeros` and related): declared kernels that return constants/placeholders or otherwise fail to implement the requested operator.

This filtering defines the clean-vs-raw split used in Section 4 and in Figure 8.