ACTING IN DELAYED ENVIRONMENTS WITH NON-STATIONARY MARKOV POLICIES

ABSTRACT

The standard Markov Decision Process (MDP) formulation hinges on the assumption that an action is executed immediately after it was chosen. However, assuming it is often unrealistic and can lead to catastrophic failures in applications such as robotic manipulation, cloud computing, and finance. We introduce a framework for learning and planning in MDPs where the decision-maker commits actions that are executed with a delay of m steps. The brute-force state augmentation baseline where the state is concatenated to the last m committed actions suffers from an exponential complexity in m, as we show for policy iteration. We then prove that with execution delay, Markov policies in the original state-space are sufficient for attaining maximal reward, but need to be non-stationary. As for stationary Markov policies, we show they are sub-optimal in general. Consequently, we devise a non-stationary Q-learning style model-based algorithm that solves delayed execution tasks without resorting to state-augmentation. Experiments on tabular, physical, and Atari domains reveal that it converges quickly to high performance even for substantial delays, while standard approaches that either ignore the delay or rely on state-augmentation struggle or fail due to divergence. The code will be shared upon publication.

1 INTRODUCTION

The body of work on reinforcement learning (RL) and planning problem setups has grown vast in recent decades. Examples for such distinctions are different objectives and constraints, assumptions on access to the model or logged trajectories, on-policy or off-policy paradigms, etc. (Puterman, 2014). However, the study of delay in RL remains scarce. It is almost always assumed the action is executed as soon as the agent chooses it. This assumption seldom holds in real-world applications (Dulac-Arnold et al., 2019). Latency in action execution can either stem from the increasing computational complexity of modern systems and related tasks, or the infrastructure itself. The wide range of such applications includes robotic manipulation, cloud computing, financial trading, sensor feedback in autonomous systems, and more. To elaborate, consider an autonomous vehicle required for immediate response to a sudden hazard on the highway. Driving at high speed, it suffers from perception module latency when inferring the surrounding scene, as well as delay in actuation once a decision has been made. While the latter phenomenon is an instance of *execution delay*, the former corresponds to *observation delay*. These two types of delay are in fact equivalent and can thus be treated with the same tools (Katsikopoulos & Engelbrecht, 2003).

Related works. The notion of delay is prominent in control theory with linear time-invariant systems (Bar-Ilan & Sulem, 1995; Dugard & Verriest, 1998; Richard, 2003; Fridman, 2014; Bruder & Pham, 2009). While the delayed control literature is vast, our work intersects with it mostly in motivation. In the above control theory formulations, the system evolves according to some known diffusion or stochastic differential equation. Differently, the discrete-time MDP framework does not require any structural assumption on the transition function or reward.

A few works consider a delay in the reward signal rather than in observation or execution. Delayed reward has been studied on multi-armed bandits for deterministic and stochastic latencies (Joulani et al., 2013) and for the resulting arm credit assignment problem (Pike-Burke et al., 2017). In the MDP setting, Campbell et al. (2016) proposed a Q-learning variant for reward-delay that follows a Poisson

distribution. Katsikopoulos & Engelbrecht (2003) considered three types of delay: observation, execution, and reward. Chen et al. (2020b) studied execution delay on multi-agent systems. The above works on MDPs employed state-augmentation with a primary focus on empirical evaluation of the degradation introduced by the delay. In this augmentation method, all missing information is concatenated with the original state to overcome the partial observability induced by the delay. The main drawback of this embedding method is the exponential growth of the state-space with the delay value (Walsh et al., 2009; Chen et al., 2020a) and, in the case of (Chen et al., 2020b), an additional growth that is polynomial with the number of agents.

Walsh et al. (2009) avoided state-augmentation in MDPs with delayed feedback and used a planning approach. By assuming the transition kernel to be close to deterministic, their *model-based simulation* (MBS) algorithm explicitly determines the most-likely present state based on the history of states and actions. The Delayed-Q algorithm we devise here resembles MBS in spirit, though MBS requires the state-space to be finite or discretized. As we shall demonstrate in Sec. 7 [Fig. 3(c)], MBS is thus highly sensitive to the state-space size.

Recent studies considered a concurrent control setting where action sampling occurs simultaneously with state transition (Ramstedt & Pal, 2019; Xiao et al., 2020). Both assumed a single action selection between two consecutive observations, thus reducing the problem to an MDP with execution delay of $m = 1$. Chen et al. (2020a) have generalized it to an arbitrary number of actions between two observations. Hester & Stone (2013) addressed execution delay in the braking control of autonomous vehicles with a relatively low delay of $m \leqslant 3$. All these works employ state-augmentation to preserve the Markov property of the process, whereas we are interested whether this restriction can be lifted. Additionally, they studied policy-gradient (policy-based) methods, while we introduce a Q-learning style (value-based) algorithm. Likewise, Firoiu et al. (2018) proposed a modified version of the policy-based IMPALA (Espeholt et al., 2018) which is evaluated on a single video game with delay values of $m \leqslant 7$. To the best of our knowledge, our work is the first to tackle a delayed variant of the popular Atari suite (Bellemare et al., 2013).

Contributions. Revisiting RL with execution delay both in theory and practice, we introduce:

1. An analytical study of delay on an example MDP quantifying the trade-off between stochasticity and delay.

2. The first tight upper and lower complexity bounds on an algorithm (policy iteration) for action-augmented MDPs.

3. A new formalism of execution-delay MDPs that avoids action-embedding. This leads to (i) the formal understanding that restricting to non-stationary Markov policies is sufficient for optimality in delayed MDPs, and (ii) a Bellman-type recursion for a *delayed value function*.

4. A model-based DQN-style algorithm that yields non-stationary Markov policies. Our algorithm outperforms the alternative standard and state-augmented DDQN in 47 of 48 experiments spanning over 3 environment categories and delay of up to $m = 25$.

2 PRELIMINARIES: NON-DELAYED STANDARD MDP

Here, we describe the standard non-delayed MDP setup. Later, in Sec. 5, we introduce its generalization to the delayed case. We follow and extend notations from (Puterman, 2014)[Sec. 2.1.]. An infinite horizon discounted MDP is a tuple $(\mathcal{S}, \mathcal{A}, P, r, \gamma)$ where $\mathcal{S}$ and $\mathcal{A}$ are finite state and action spaces, $P : \mathcal{S} \times \mathcal{A} \to \Delta_{\mathcal{S}}$ is a transition kernel, the reward $r : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ is a bounded function, and $\gamma \in [0, 1)$ is a discount factor. At time t, the agent is in s_t and draws an action a_t according to a decision rule d_t that maps past information to a probability distribution q_{d_t} over the action set. Once a_t is taken, the agent receives a reward $r(s_t, a_t)$.

A decision rule can be history-dependent (H) or Markovian (M) , and randomized (R) or deterministic (D). Denote by $\mathcal{H}_t$ the set of possible histories up to time t. Then, a history-dependent decision-rule is given by $d_t : \mathcal{H}_t \to \Delta_{\mathcal{A}}$ with $h_t \mapsto q_{d_t(h_t)}(\cdot)$. A Markovian decision-rule, on the other hand, maps states to actions, i.e., $d_t : \mathcal{S} \to \Delta_{\mathcal{A}}$ with $s \mapsto q_{d_t(s)}(\cdot)$. A *policy* $\pi := (d_t)_{t \geqslant 0}$ is a sequence of decision rules whose type dictates that of the policy. It can be either Markovian deterministic (Π^{MD}) or randomized (Π^{MR}), history-dependent deterministic (Π^{HD}) or randomized (Π^{HR}). It is stationary if its decision rules do not depend on time, i. e., $d_t = d$ for all $t \geqslant 0$. This defines the smaller class

of stationary policies: deterministic (Π^{SD}) and randomized (Π^{SR}). Note that stationary policies are inherently Markovian. Indeed, at time $t = 0$, $d : \mathcal{H}_0 \to \Delta_{\mathcal{A}}$ is state-dependent because $\mathcal{H}_0 = \mathcal{S}$. Since the policy is stationary, i. e., $d_t = d \ \forall t$, subsequent decision rules are also state-dependent, thus Markovian. This makes Π^{HR} the most general set and Π^{SD} the most specific.

We denote probability model by $\mathbb{P}_0^\pi$, where the subscript 0 stands for the delay value $m = 0$. The related random variables are denoted by $\tilde{s}_t \in \mathcal{S}, \tilde{a}_t \in \mathcal{A}$ and $\tilde{h}_t \in (\mathcal{S} \times \mathcal{A})^t \times \mathcal{S}$. The value function given policy $\pi \in \Pi^{\text{HR}}$ is defined as $v^\pi(s) = \mathbb{E}_0^\pi \left[\sum_{t=0}^{\infty} \gamma^t r(\tilde{s}_t, \tilde{a}_t) \ \middle| \ \tilde{s}_0 = s \right]$, where the expectation is taken with respect to (w.r.t.) $\mathbb{P}_0^\pi(\cdot|\tilde{s}_0 = s)$. Let the optimal value function

$$v^*(s) := \max_{\pi \in \Pi^{\text{HR}}} v^\pi(s), \quad \forall s \in \mathcal{S}. \tag{1}$$

Our goal is to find a policy π^* that yields v^*, and it is known that focusing on stationary deterministic policies $\pi \in \Pi^{\text{SD}}$ is sufficient for reaching the optimum in (1) (Puterman, 2014)[Thm. 6.2.10.].

3 MDPs with Delay: A Degradation Example

In an MDP with execution delay[1] m, any action chosen at time t is executed at $t + m$. Therefore, at each step, the agent witnesses the current state and action being executed, but selects a new action that will be applied in a future state. We assume that m decided actions are already awaiting execution at $t = 0$, so at any given time, the queue of pending actions is of constant length m. As we illustrate in the next example, having a delay generally comes at a price. We stress that the effect of execution delay is identical to that of observation delay, as we shall explain in Sec. 6.

Figure 1: Degradation due to delay in a two-state MDP.

Example 3.1 (Two-state MDP). *Consider the MDP in Fig. 1. It has two states and two actions from each state: $\mathcal{S} = \{s_0, s_1\}, \mathcal{A} = \{a_0, a_1\}$. The transition kernel is independent of the action: for all $s, s' \in \mathcal{S}$ s.t. $s \neq s'$, $P(s'|s, a) = P(s'|s) = p$ where $p \in [0.5, 1]$. The reward is positive for one of the two actions only: $r(s_0, a_0) = r(s_1, a_1) = 1, r(s_0, a_1) = r(s_1, a_0) = 0$.*

We inspect the return obtained from the commonly used set of stationary deterministic policies Π^{SD}. As expected, the highest possible return is attained when $m = 0$, but monotonically decreases with the delay, m, and increases with the level of certainty, p. We analytically quantify this effect in the following and give a proof in Appx. A.1.

Proposition 3.1. *For delay $m \in \mathbb{N}$ and $p \in [0.5, 1]$, the optimal return of $\pi^* \in \Pi^{\text{SD}}$ is $\frac{1+(2p-1)^m}{2(1-\gamma)}$.*

Remark 3.1. *This result demonstrates a clear tradeoff between stochasticity and delay. For $p \to 0.5$ or $m \to \infty$, the return goes to its minimal value of $0.5/(1 - \gamma)$. Contrarily, for $p \to 1$ or $m \to 0$, it goes to its maximal value of $1/(1 - \gamma)$.*

4 The Augmentation Approach

In this section, we consider state-augmentation for solving MDPs with execution delay. We begin with defining an equivalent MDP with a larger state space that memorizes all missing information for an informed decision. Due to the full observability, the resulting optimal augmented policy attains the optimal return in the original delayed MDP.

---

[1]The exact terminology used by Katsikopoulos & Engelbrecht (2003) is *action delay*, while in (Bertsekas et al., 1995)[Section 1.4] it is *time lag*. We prefer the term *execution delay* since the action is itself decided instantaneously.

Definition 4.1 (*m*-AMDP). *Given MDP* $(\mathcal{S}, \mathcal{A}, P, r, \gamma)$ *and* $m \in \mathbb{N}$, *an* m-*Augmented MDP* (m-*AMDP*) *is a tuple* $(\mathcal{X}_m, \mathcal{A}, F, g, \gamma)$ *such that* $\mathcal{X}_m := \mathcal{S} \times \mathcal{A}^m$ *is the augmented state-space*, $\mathcal{A}$ *the original action-space*, F *is the transition matrix given in Appx. B.1 (14), and* g *is the reward function given in Appx. B.1, (15).*

The pending action queue is concatenated to the original state to form an augmented state $x_t := (s_t, a_t^{-1}, \cdots, a_t^{-m}) \in \mathcal{X}_m$, where a_t^{-i} is the i-th pending action at time t. It means that in the following step, $t + 1$, action a_t^{-m} will be executed independently of the present action selection, the queue will shift to the right, and the newly selected action will be at the second coordinate. By construction, the m-AMDP is non-delayed; it directly accounts for execution delay through its state-representation, as opposed to our coming formulation in Sec. 5. We further define a stationary deterministic policy $\bar{\pi} \in \bar{\Pi}_m^{\text{SD}}$ with corresponding decision rule $\bar{d} : \mathcal{X}_m \to \Delta_\mathcal{A}$ and *augmented value function* $v^{\bar{\pi}}(x) := \mathbb{E}^{\bar{\pi}} \left[\sum_{t=0}^{\infty} \gamma^t g(\tilde{x}_t, \tilde{a}_t) | \tilde{x}_0 = x \right]$. As in (1), our goal is to solve $\bar{v}^*(x) = \max_{\bar{\pi} \in \bar{\Pi}_m^{\text{SD}}} v^{\bar{\pi}}(x) \quad \forall x \in \mathcal{X}_m$.

We now analyze the classical Policy Iteration (PI) algorithm (Howard, 1960) for m-augmented MDPs and provide a finite-time analysis of its convergence. We refer to it as mA-PI and provide its pseudo-code in Appx. B.2. We consider PI since it is a canonical representative upon which many other algorithms are built. Admittedly, we did not find any other formal result quantifying the effect of augmentation on a planning or learning algorithm, other than a PAC upper bound for R-max with ϵ-optimal policies (Walsh et al., 2009). A proof for the next result is given in Appx. B.4.

Proposition 4.1 (Lower Bound for mA-PI). *The number of iterations required for* mA-PI *to converge in* m-*AMDP* $\mathcal{M}_m$ *is* $\Omega(|\mathcal{X}_m|) = \Omega(|\mathcal{S}||\mathcal{A}|^m)$.

In fact, the above lower bound is tight (up to a factor of $|\mathcal{A}|$ and logarithmic terms) and mA-PI is guaranteed to converge after $\tilde{O}(|\mathcal{S}||\mathcal{A}|^{m+1})$. A proof is given in Appx. B.5.

Theorem 4.1 (mA-PI Convergence). *The* mA-PI *algorithm converges to the optimal value-policy pair* $(\bar{v}^*, \bar{\pi}^*)$ *in at most* $|\mathcal{S}||\mathcal{A}|^m(|\mathcal{A}| - 1) \left\lceil \log\left(1/\gamma \right)^{-1} \log\left(1/1-\gamma \right) \right\rceil$ *iterations.*

5 EXECUTION-DELAY MDP: A NEW FORMULATION

In this section, we introduce and study the stochastic process generated by an MDP with execution delay, without resorting to state-augmentation. In the ED-MDP we consider, the probability measure changes according to the delay value m. Since the first decided action at $t = 0$ is actuated at $t = m$ only, we assume that during the m initial steps, actions are sequentially executed according to a *fixed* queue $\bar{a} := (\bar{a}_0, \cdots, \bar{a}_{m-1}) \in \mathcal{A}^m$. Unlike m-AMDPs, the initial queue of pending actions here plays the role of an exogenous variable that is not embedded into the state-space. A policy $\pi \in \Pi^{\text{HR}}$ induces a probability measure $\mathbb{P}_m^\pi$ that is defined through a set of equations which, for brevity, we defer to Appx. C [(16)-(19)]. Note that for $t < m$, decision rules do not depend on the history, while for $t \geq m$, they depend on the history up to $t - m$ only. Let μ be an initial state distribution and δ a Dirac distribution. Using this and the notations from Sec. 2, we can explicitly write the probability of a sample path. See proof in Appx. C.1.

Proposition 5.1. *For policy* $\pi := (d_0, d_1, \cdots) \in \Pi^{\text{HR}}$, *the probability of observing history* $h_t := (s_0, a_0, s_1, a_1 \cdots, a_{t-1}, s_t)$ *is given by:*

$$
\mathbb{P}_m^\pi(\tilde{s}_0 = s_0, \tilde{a}_0 = a_0, \tilde{s}_1 = s_1, \tilde{a}_1 = a_1, \cdots, \tilde{a}_{t-1} = a_{t-1}, \tilde{s}_t = s_t)
$$
$$
= \mu(s_0) \left(\prod_{k=0}^{m-1} \delta_{\bar{a}_k}(a_k) p(s_{k+1}|s_k, a_k) \right) \left(\prod_{k=m}^{t-1} q_{d_{k-m}(h_{k-m})}(a_k) p(s_{k+1}|s_k, a_k) \right).
$$

From Prop. 5.1 we deduce that, differently than the standard MDP setting where any Markov policy induces a Markov process, the delayed process is not Markovian even for stationary policies (see Appx. C.2 for a formal proof). Next, we show that for any history-dependent policy and starting state, there exists a Markov policy (not necessarily stationary) that generates the same process distribution. Consequently, despite execution delay, one can restrict attention to Markov policies without impairing performance. See proof in Appx. C.3.

Theorem 5.1. *Let $\pi := (d_0, d_1, \cdots) \in \Pi^{\mathrm{HR}}$ be a history dependent policy. For all $s_0 \in \mathcal{S}$, there exists a Markov policy $\pi' := (d'_0, d'_1, \cdots) \in \Pi^{\mathrm{MR}}$ that yields the same process distribution as π, i.e.,*

$$\mathbb{P}_m^{\pi'}(\tilde{s}_{t-m} = s', \tilde{a}_t = a | \tilde{s}_0 = s_0) = \mathbb{P}_m^{\pi}(\tilde{s}_{t-m} = s', \tilde{a}_t = a | \tilde{s}_0 = s_0), \qquad \forall a \in \mathcal{A}, s' \in \mathcal{S}, t \geqslant m.$$

The formal proof is given in Appx. C.3. It builds on the concept that for each history-dependent policy π^{HR}, one can choose a sequence of Markov decision rules that reconstruct the same time-dependent action distribution in the process induced by π^{HR}.

This result proves attainability of the optimum over Π^{MR}, but not how one can efficiently find an optimal policy. In Appx. C.5, we formally define a *delayed value function* and show that it satisfies a non-stationary Bellman-type recursion. The question of how to efficiently find an optimal non-stationary Markov policy and which role the delayed value function plays in that process remains open.

Degradation due to stationarity. As to complement the finding that a Markov policy can be optimal for any ED-MDP, we show that restricting to stationary policies impairs performance in general. Therefore, while in non-delayed MDPs it is enough to focus on stationary policies, in ED-MDPs the restriction should be to the more general class of Markov policies.

Proposition 5.2. *There exists an m-ED-MDP for which all stationary policies are sub-optimal.*

This result follows from computing the optimal return for stationary and non-stationary policies in the ED-MDP from Example 3.1 using simulation. We elaborate on this further in Appx. C.4. There, we also confirm that our theoretical return from Prop. 3.1 matches closely with simulation.

6 A New Algorithm: Delayed-Q

In this section, we introduce a new algorithm capable of successfully handling tasks with execution delay. To solve such delayed MDP, the agent needs to infer the future m-step state whenever it chooses an action.

Figure 2: Delayed-Q algorithm diagram.

The algorithm is depicted in Fig. 2. As a first stage, to select an action a_t to be executed in a future state s_{t+m}, we infer that future state $\hat{s}_{t+m}$ using the current state s_t and the queue of pending actions $(a_{t-m}, \ldots, a_{t-1})$. This is done by successively applying an approximate forward model m times: $\hat{s}_{t+1} = f(s_t, a_{t-m}), \ldots, \hat{s}_{t+m} = f(\hat{s}_{t+m-1}, a_{t-1})$. More details on the forward models used in the three environment types are given next, in Sec. 7. Compared to other model-based algorithms such as tree-search methods, the approximate model here is simpler since it does not require access to the reward function. Also, only a single trajectory is sampled rather than exponentially many w.r.t. the horizon length. We do note this method relies on the environment not being entirely stochastic (Walsh et al., 2009). Still, as we shall show next, it performs well even in moderately noisy environments.

As a second stage, we select an action according to a policy $a_t = \pi(\hat{s}_{t+m})$. The two stages of this procedure can be represented as a non-stationary Markov policy $\pi_t(s_t)$, where the non-stationarity stems from the time-dependency via the action queue, and the Markov property from the policy being applied on s_t and no other prior history. Notably, the Q-function here does not take as input the action history, as opposed to the augmentation approach in Sec. 4. To better stress the non-stationarity, we note that applying the policy on the same state at different times can yield different action probability outcomes. Lastly, for training, we maintain a sample-buffer of length m which we use to shift action a_t into the tuple $(s_{t+m}, r_{t+m}, a_t, s_{t+m+1})$ prior to each insertion to the replay buffer.

7 EXPERIMENTS

We perform experiments in a wide range of domains: tabular, physical, and image-based Atari. All of them include stochasticity: In the maze we inject noise to actions; in the physical domains we perturb the masses at each step; and Atari is stochastic by nature. We compare our algorithm with two baselines: *Oblivious-Q* and *Augmented-Q*. Oblivious-Q is the standard Q-learning that ignores delay and assumes each decided action to be immediately executed. Augmented-Q acts on the $m-$AMDP introduced in Def. 4.1. We test all domains on delays $m \in \{0, 5, 15, 25\}$ with 5 seeds per each run. All results are summarized with standard deviations in Appx. D, Table 2.

Tabular Maze Domain. We begin with testing Delayed-Q on a Maze domain (Brockman et al., 2016)[`tinyurl.com/y34tmfm9`]. It is based on textbook tabular Q-learning and enables us to study the merits of our method decoupled from the DDQN added complexities. Moreover, it conveys the exponential complexity of Augmented-Q. The forward-model we construct is naturally tabular as well: it predicts a state s' according to the highest visitation frequency given (s, a). The objective in Maze is to find the shortest path from a start position to a goal state in a randomly-generated $N \times N$ maze. Reaching the goal yields a reward of 1, and $-1/(10N^2)$ per step otherwise. The maximal episode length is $10N^2$ steps, so the cumulative reward is in $[-1, 1]$. We also create a Noisy Maze environment that perturbs each action w.p. $p \in [0, 0.5]$.

Convergence plots are given in Fig. 4(a). Delayed-Q outperforms the rest for all delay values m. Since the augmented state-space grows exponentially with m, Augmented-Q converges more slowly as m increases. In fact, for $m > 15$ the simulation fails to run due to memory incapacity for the Q-table; this explains its absence in Figs. 4(a)-6. Oblivious-Q fails in all runs for $m > 0$. To further analyze the sensitivity of tabular Delayed-Q to the state-space size, we run Delayed-Q with increasing maze sizes, for a fixed $m = 5$. As Fig. 3(c) shows, the performance drops exponentially fast, which suggests high sensitivity of Delayed-Q to the state-space size and highlights one shortcoming of the MBS method (Walsh et al., 2009) to which our algorithm resembles in its tabular form.

(a) (b) (c)

Figure 3: Performance of (a) Noisy Maze and (b) Cartpole as function of delay value and stochasticity. (c) Reward on varying Maze sizes.

Physical Domains. Next, we test our approach on two continuous domains: CartPole[2] and Acrobot. The CartPole task requires balancing a pole connected to a cart that actuates left or right. In Acrobot, one needs to swing up the lower of two links connected by a joint above a certain height. The agent receives a reward of 1 if the pole stays above a certain angle in Cartpole, and in Acrobot it receives -1 until it reaches the goal. The episode length is 500 steps in both tasks. We also create noisy versions of both tasks: At each step, normal additive noises are independently added to each physical component's mass, with standard deviation of 0.1 of the nominal mass.

To solve these tasks, we extend the DDQN algorithm (Van Hasselt et al., 2015), which is a known and common baseline. Nonetheless, our method is general and can be seamlessly integrated into any Q-learning based algorithm. Our one-step forward-model is implemented

---

[2]Since Cartpole fails in ~ 10 steps if the initial actions are random, we initialize the m-lengthed action-queue with optimal actions using a pretrained non-delayed model. We wait for $2m$ steps before starting to append samples to the replay buffer to avoid unfair advantage due to these actions.

Figure 4: Convergence plots for (a) Maze, (b) Noisy Cartpole and (c) Atari Boxing. Note that the scale of the y-axes (performance) may change from figure to figure.

with a neural network of the same architecture as the one used to estimate the Q-function. Namely, it consists of two hidden layers, each of width 24, with ReLu activations. The input of the forward-model NN is the concatenation of (s, a) and its output is s'. Training the forward-model NN is conducted together with the Q-network training with the same hyperparameters and sample batches; this makes the implementation easy and simple. For Augmented-Q, a concatenation of the pending action queue to the state is fed to the Q-network.

We depict the performance of the three algorithms for different values of m for Noisy Cartpole in Fig. 4(b). As expected from a physical domain, ignoring the delay gives catastrophic results even for $m = 5$. Augmented-Q performs moderately up to $m = 15$, but fails with larger delays. Delayed-Q performs the best for all m values and performs well, even for the challenging task of balancing a noisy pole with $m = 25$. We observed similar behavior in all Cartpole and Acrobot experiments, as shown in Fig. 6. Moreover, in Fig. 5, we demonstrate the relative robustness of Delayed-Q to different delay values on Noisy Cartpole. Interestingly, Delayed-Q with relatively high delay ($m = 25$) performs more or less the same as low-delay oblivious Q-learning ($m = 5$). The same applies for Cartpole, Acrobot, and Maze domains, as we see in Fig. 6. Lastly, in Figs. 3(a)-3(b), we see a clear trade-off between noise and delay: noise and delay adversely affect performance, as we also discuss in Rmk. 3.1. Observe that when the delay is significant, the agent is much more sensitive to an increase in stochasticity.

Figure 5: Noisy Cartpole: Performance as a function of the delay.

Atari Domains. We further investigate the Atari Learning Environment (Bellemare et al., 2013). We inspect 10 arbitrary games that were successfully tackled with the original Q-network architecture and hyperparameters of DDQN (Van Hasselt et al., 2015). Since a learned forward-model for images

Figure 6: Experiment summary: mean of episodic return for all domains, with a positive translation of 1 for Maze and 500 for Acrobot. Delayed-Q outperforms the alternatives in 47 of 48 experiments.

conditioned on actions is a hanging question in the research frontier, we leave it for future research and use the simulator itself for prediction. It is stochastic in nature and thus encompasses approximation error. For Augmented-Q, we concatenate the action queue to the output of the CNN part of the Q-network; the extended vector is then fed into the subsequent fully-connected part of it. We train all games for 1M steps. Fig. 4(c) shows convergence plots for Boxing. Delayed-Q is consistently better than Augmented-Q for all m values, which is, in turn, better than Oblivious-Q. Although the gap between all three algorithms is relatively small for $m = 5$, it increases with m. For $m = 25$, the delay is too large for the augmentation to have a positive effect compared to Oblivious-Q, and they perform the same. This behavior is representative of all Atari games, as can be seen in Fig. 6.

8 DISCUSSION

The main message of this work is that dealing with execution delay requires non-stationary Markov policies. The standard state augmentation approach, though optimal in terms of expressiveness, is intractable in all but the shortest delays. The oblivious approach that ignores the delay suffers from inferior performance and breaks down at some point, if the system is stochastic enough. We derived a Q-learning based algorithm that generates a Markov policy. Our approach is based on combining a forward model with a policy learning model. A thorough simulation study demonstrates the efficacy of the proposed method. While we focused on execution delay, we note that execution delay and observation delay where at time t the agent observes that state at time $t - m$ and the action is performed without delay are equivalent (Katsikopoulos & Engelbrecht, 2003). As such, our results apply for the observation delay model.

The forward model we used is a simple point estimate. Incorporating probabilistic estimates and other improvements for the forward model, such as integration of image-based action-dependent learned forward-models, are left for future research. Another interesting extension of our work is to consider varying execution delay that may depend on the state or even future actions. For example, consider systems where the distance from a computing center is crucial for the length of the delay; or "difficult" states that require a delicate computation, as opposed to "easy" states where fast computation is sufficient. Differently than the augmentation approach, our algorithm can handle such arbitrary delay, and quantization of the delay is not essential as long as the forward model can operate with variable delay values. Finally, our framework can be extended to policy-gradient based methods that are particularly useful for continuous control, where observation delay is inherent.

REFERENCES

Avner Bar-Ilan and Agnès Sulem. Explicit solution of inventory problems with delivery lags. *Mathematics of Operations Research*, 20(3):709–720, 1995.

Marc G Bellemare, Yavar Naddaf, Joel Veness, and Michael Bowling. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47: 253–279, 2013.

Dimitri P Bertsekas, Dimitri P Bertsekas, Dimitri P Bertsekas, and Dimitri P Bertsekas. *Dynamic programming and optimal control*, volume 1. Athena scientific Belmont, MA, 1995.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. OpenAI Gym. arXiv:1606.01540v1, 2016.

Benjamin Bruder and Huyên Pham. Impulse control problem on finite horizon with execution delay. *Stochastic Processes and their Applications*, 119(5):1436–1469, 2009.

Jeffrey S Campbell, Sidney N Givigi, and Howard M Schwartz. Multiple model q-learning for stochastic asynchronous rewards. *Journal of Intelligent & Robotic Systems*, 81(3-4):407–422, 2016.

Baiming Chen, Mengdi Xu, Liang Li, and Ding Zhao. Delay-aware model-based reinforcement learning for continuous control. *arXiv preprint arXiv:2005.05440*, 2020a.

Baiming Chen, Mengdi Xu, Zuxin Liu, Liang Li, and Ding Zhao. Delay-aware multi-agent reinforcement learning. *arXiv preprint arXiv:2005.05441*, 2020b.

Luc Dugard and Erik I Verriest. *Stability and control of time-delay systems*, volume 228. Springer, 1998.

Gabriel Dulac-Arnold, Daniel Mankowitz, and Todd Hester. Challenges of real-world reinforcement learning. *arXiv preprint arXiv:1904.12901*, 2019.

Lasse Espeholt, Hubert Soyer, Remi Munos, Karen Simonyan, Volodymir Mnih, Tom Ward, Yotam Doron, Vlad Firoiu, Tim Harley, Iain Dunning, et al. Impala: Scalable distributed deep-rl with importance weighted actor-learner architectures. *arXiv preprint arXiv:1802.01561*, 2018.

Vlad Firoiu, Tina Ju, and Josh Tenenbaum. At human speed: Deep reinforcement learning with action delay. *arXiv preprint arXiv:1810.07286*, 2018.

Emilia Fridman. *Introduction to time-delay systems: Analysis and control*. Springer, 2014.

Todd Hester and Peter Stone. Texplore: real-time sample-efficient reinforcement learning for robots. *Machine learning*, 90(3):385–429, 2013.

Ronald A Howard. Dynamic programming and Markov processes. *John Wiley*, 1960.

Pooria Joulani, Andras Gyorgy, and Csaba Szepesvári. Online learning under delayed feedback. In *International Conference on Machine Learning*, pp. 1453–1461, 2013.

Konstantinos V Katsikopoulos and Sascha E Engelbrecht. Markov decision processes with delays and asynchronous cost collection. *IEEE transactions on automatic control*, 48(4):568–574, 2003.

Ciara Pike-Burke, Shipra Agrawal, Csaba Szepesvari, and Steffen Grünewälder. Bandits with delayed anonymous feedback. *stat*, 1050:20, 2017.

Martin L Puterman. *Markov Decision Processes.: Discrete Stochastic Dynamic Programming*. John Wiley & Sons, 2014.

Simon Ramstedt and Chris Pal. Real-time reinforcement learning. In *Advances in Neural Information Processing Systems*, pp. 3073–3082, 2019.

Jean-Pierre Richard. Time-delay systems: an overview of some recent advances and open problems. *automatica*, 39(10):1667–1694, 2003.

Bruno Scherrer et al. Improved and generalized upper bounds on the complexity of policy iteration. *Mathematics of Operations Research*, 41(3):758–774, 2016.

Hado Van Hasselt, Arthur Guez, and David Silver. Deep reinforcement learning with double q-learning. *arXiv preprint arXiv:1509.06461*, 2015.

Thomas J Walsh, Ali Nouri, Lihong Li, and Michael L Littman. Learning and planning in environments with delayed feedback. *Autonomous Agents and Multi-Agent Systems*, 18(1):83, 2009.

Ted Xiao, Eric Jang, Dmitry Kalashnikov, Sergey Levine, Julian Ibarz, Karol Hausman, and Alexander Herzog. Thinking while moving: Deep reinforcement learning with concurrent control. *arXiv preprint arXiv:2004.06089*, 2020.