# Transferring Pre-trained Multimodal Representations with Cross-modal Similarity Matching

## Abstract

Despite surprising performance on zero-shot transfer, pre-training a large-scale multimodal model is often prohibitive as it requires a huge amount of data and computing resources. In this paper, we propose a method (**BeamCLIP**) that can effectively transfer the representations of a large pre-trained multimodal model (CLIP ViT-B/16) into a small target model (ResNet-50). For unsupervised transfer, we introduce *cross-modal similarity matching* (CSM) that enables a student model to learn the representations of a teacher model by matching the relative similarity distribution across text prompt embeddings. To better encode the text prompts, we design *context-based prompt augmentation* (CPA) that can alleviate the lexical ambiguity of input text prompts. Our experiments show that unsupervised representation transfer of a large pre-trained multimodal model can provide good ImageNet linear probe accuracy (74.8%), while outperforming the existing self-supervised learning methods (SimCLR: 65.6%) and closing the gap with supervised learning (76.2%).

## 1   Introduction

Learning transferable representations is crucial for successful downstream applications. Contrastive learning such as SimCLR and MoCo-v2 have shown notable success by forcing features of individual classes to be clustered and sufficiently scattered [41]. But their downstream performances are still far behind the supervised training as shown in Figure 1. Recently, large-scale vision and language pre-trained (VLP) models provide highly transferable visual representations via language supervision. However, learning VLP models from the scratch is prohibitive as it requires large amounts of training data and computing resource. For example, training CLIP [32] requires 400M paired image-text data and several hundreds of GPUs. ALIGN [22] further scales up to leverage alternative texts specified for descriptions of web images. While these models are often based on

Figure 1: ImageNet top-1 accuracy of linear probe on ResNet-50. By transferring the representations of CLIP ViT-B/16 [32], the BeamCLIP achieves 74.8%. It outperforms SimCLR [4] (65.6%) and reduces the gap to the supervised learning (76.2%). The numbers in parentheses denote the batch sizes.

large Transformers [40], small ConvNets such as ResNet-50 [17] and MobileNet [20] are still widely used in practice [1] and even more crucial for low-resource environments. We reformulate represen-

tation learning in terms of knowledge transfer from a large pre-trained model to a small practical model.

Large pre-trained models exhibit strong alignments between different modalities. CLIP learns visual concepts from natural language supervision, mapping image and text into the same vector space. As their training data is not only huge but inaccessible, however, conventional knowledge distillation based on instance similarity is no longer a viable option. Instead, we propose *cross-modal similarity matching* (CSM). Imagine your goal is to learn a high quality representation for an input dog image in CIFAR-10 as in Figure 2. Since CLIP was trained on numerous image-caption pairs, angular distances from the dog image embedding to the caption embeddings of other anchor prompt texts such as "a photo of cat" or "a photo of horse" must comprehensively preserve their visual differences. By training the student to preserve angular relations witnessed from the teacher, our model achieves near benchmark performance without accessing the original data for training CLIP.

To measure the effects of different amounts of supervisions, we design *context-based prompt augmentation* (CPA) that can alleviate the lexical ambiguity of the input text prompts. We find that lexical ambiguity in prompt texts can lead to semantically incorrect text embeddings. This may result in unexpected discrepancies of image-text alignment in the teacher's embedding space. Also, it is known that the zero-shot performance of CLIP can be improved by designing task-specific prompt texts. Inspired by this, we design CPA that extends the basic prompt of CLIP to better encode prototypical anchor representations.

Our experimental result shows that our BeamCLIP achieves the strongest and near benchmark performance on ImageNet-1K Top-1 linear probe accuracy when using most popular ResNet-50 as the student network. We also compare the effectiveness of BeamCLIP against zero-shot transfer learning. Further, we provide ablation study results to show how much each component contribute to the performance.

Contributions of this paper can be summarized as follows:

- We propose a method (**BeamCLIP**) that can effectively transfer the representations of a large pre-trained multimodal model (CLIP ViT-B/16) into a small target model (ResNet-50). To achieve this, we introduce *cross-modal similarity matching* (CSM) and *context-based prompt augmentation* (CPA). (Figure 2).

- We empirically show that BeamCLIP can provide favorably good ImageNet linear probe accuracy (74.8%), while outperforming the state-of-the-art self-supervised methods (SimCLR: 65.6%) and closing the gap with supervised learning (76.2%). (Figure 1 and Table 2).

- We also show that BeamCLIP (from CLIP-ViT to ResNet50) can significantly improve zero-shot transfer learning accuracy, especially when the zero-shot accuracy (CLIP-RN50) is relatively week. (Table 4 and Table 5).

## 2 Related Work

**Vision and language pre-trainig.**  Vision and language pre-training (VLP) aims to jointly learn vision and language representations that can be transferred to the downstream tasks such as visual question answering (VQA), image captioning, and vision and language navigation (VLN). There are BERT-based vision and language models such as VLBERT [35], ViLBERT [26], and UNITER [7]. Also, there are contrastive learning-based models such as CLIP [32] and ALIGN [22]. These models use contrastive loss [29] to learn aligned vision and language representations by performing a task of matching a large-scale image and text pairs. The BeamCLIP aims to transfer the rich representations of large-scale vision and language pre-trained models such as CLIP and ALIGN to a small target model.

**Self-supervised learning.**  Self-supervised learning (SSL) aims to learn highly transferable representations by using unlabeled data. In computer vision, at the early stage, task-specific self-supervised methods were introduced. These include Context Prediction [11], Rotation Prediction [14], and Colorization [43]. More recently, contrastive learning-based methods were introduced as a task-agnostic approach. These include SimCLR [4] and MoCo-v2 [18]. However, since contrastive self-supervised methods require a large batch size, non-contrastive methods have been introduced. These include SwAV [3], BYOL [16], and SimSiam [5]. In this paper, we empirically show that the BeamCLIP can

provide better visual representations than the state-of-the-art SSL methods by leveraging a large-scale pre-trained multimodal model.

**Knowledge distillation.**  Knowledge distillation (KD) [19] aims to transfer rich knowledge from a strong teacher model to a target student model. In a conventional setting, it encourages the student model to mimic the task-specific prediction of the teacher model. As the student model is trained to predict the same probability distribution over pre-defined classes as the teacher model's, using Kullback-Leibler (KL) divergence is a natural metric to measure the error between the two models. For a classification task, the loss function can be formulated as follows:

$$\mathcal{L}_{\text{KD}} = \sum_i H(p_i, q_i^S) + \sum_i KL(p_i^T \| p_i^S). \tag{1}$$

The first term indicates the supervised loss, where $p_i$ denotes the one-hot labels and $H(p, q)$ denotes cross-entropy. The second term is the distillation loss, where $p_i^T$ and $p_i^S$ are the softmax predictions of the teacher and student models, respectively.

**Similarity-based knowledge distillation.**  Recently, similarity-based knowledge distillation such as SEED [13], OSS [8], and ISD [37] was introduced in the context of self-supervised learning (SSL). SEED [13] showed that the linear probe accuracy of a small student (ResNet-18) can be improved by transferring the representations of a larger teacher (ResNet-50) pre-trained by SSL methods such as MoCo-v2 [6]. Unlike this, OSS [8] aims to transfer representations of an evolving teacher (ResNet-50) into a smaller student (ResNet-18) on the fly. Unlike SEED and OSS, ISD [37] considered the same size student and teacher network (ResNet-18), and showed a student can learn visual representations by iterativly distilling the similarity of teacher's representations. These works are closely related to our work. Unlike these works, the BeamCLIP aims to transfer rich vision and language representations of large-scale pre-trained models such as CLIP-ViT/16 [32] into a smaller network such as ResNet-50.

**Prompt engineering.**  Recently, researchers showed that prompt engineering [2] is surprisingly effective at improving the performance of large-scale language models (LLMs) on downstream tasks without fine-tuning. Prompts are input texts of language models that usually consists of a task description or several examples. To further simplify prompt engineering, prompt tuning [24] proposed to add $k$ learnable tokens to the input texts, while having language models frozen. Similar to GPT-3, it is known that the zero-shot performance of CLIP [32] can be improved by designing the prompt texts to each task. For example, on satellite image classification datasets, `"A satellite photo of a {label}"` provides better performance than the default `"A photo of a {label}"`. Inspired by this, we propose context-based prompt augmentation that extends the basic prompt of CLIP to better encode prototypical text anchor representations by alleviating the lexical ambiguity of class label texts.

## 3  Method

**Problem formulation.**  Formally, our problem is to transfer aligned cross-modal representations of a strong teacher model $f_\phi^T(\cdot)$ into a target student model $f_\theta^S(\cdot)$ with unlabeled data $\mathcal{D}_u = \{x_i\}_{i=1}^N$. Given each unlabeled image $x_i$, we formulate representation transfer as a regression task that matches teacher representations $f_\phi^T(x_i)$ to a student's $f_\theta^S(x_i)$. As the student network is parameterized by $\theta$, the learning objective is

$$\arg\min_\theta \sum_i^N \|f_\theta^S(x_i) - f_\phi^T(x_i)\|_2^2. \tag{2}$$

Normalizing the representations via $l_2$-normalization (*i.e.,* $q_i = f_\theta^S(x_i)/\|f_\theta^S(x_i)\|_2$ and $k_i = f_\phi^T(x_i)/\|f_\phi^T(x_i)\|_2$) leads to the following simplification:

$$\arg\min_\theta \sum_i^N \|q_i - k_i\|_2^2 = \arg\min_\theta \sum_i^N (2 - 2q_i \cdot k_i). \tag{3}$$

The problem now involves maximizing the cosine similarity between $l_2$-normalized representations from teacher and student models.

Figure 2: **Overview of the BeamCLIP.** Representation transfer can be viewed as a task in which, given a query input, a student model learns to regress a vector representation of a teacher model. The BeamCLIP first measures the normalized cross-modal similarity of the query image compared to anchor text representations in the teacher's embedding space. Then, it encourages the student to mimic the same cross-modal similarity in the student's embedding space. To better align image representations, our method uses self-supervised pre-training of the student model. Finally, to avoid text ambiguity, we uses context-based prompt augmentation.

**Method overview.** The overview of **BeamCLIP** is shown in Figure 2. The teacher model of the BeamCLIP consists of an image encoder $f_\phi^T(\cdot)$ and a text encoder $g_\psi^T(\cdot)$. These encoders are pre-trained under a simple task of matching images to texts with large-scale corpora. Image representations $f_\phi^T(x_i)$ and text representations $g_\psi^T(t_i)$ are thus well-aligned within a cross-modal embedding space. We provide the details of the BeamCLIP in the following sections. More specifically, we describe how to extend the basic problem setting by leveraging the unique features of CLIP where vision and language representations are precisely aligned. Throughout the paper, we use the notation CLIP-ViT/16 to denote the CLIP [32] model that uses Vision Transformer (ViT) [12] with the patch size of 16x16 as the image encoder. Similar to this, CLIP-RN50 denotes the CLIP model with ResNet-50 [17] as the image encoder.

### 3.1 Similarity-based cross-modal representation transfer

To effectively distill cross-modal representations, we use similarity-based matching as described above. Our similarity-based representation transfer utilizes two carefully designed loss functions: (1) instance similarity matching (ISM) loss and (2) cross-modal similarity matching (CSM) loss.

**Instance similarity matching.** This objective is directly derived from Eq. 3. Given a query image $x_i$, it encourages the student image encoder $f_\theta^S(\cdot)$ to regress the representation of the teacher image encoder $f_\phi^T(\cdot)$. We apply conventional image augmentations (see Appendix B) on a query image $x_i$, and the same augmented image $\hat{x}_i$ is fed to both the teacher and student image encoders. Given unlabeled query images $\mathcal{D}_u = \{x_i\}_{i=1}^N$, it is formulated as follows:

$$\mathcal{L}_{\text{ISM}} = -\sum_{i=1}^N \left( \frac{f_\theta^S(\hat{x}_i)}{\|f_\theta^S(\hat{x}_i)\|_2} \cdot \frac{f_\phi^T(\hat{x}_i)}{\|f_\phi^T(\hat{x}_i)\|_2} \right) = -\sum_{i=1}^N (q_i \cdot k_i). \tag{4}$$

However, the similarity signal from a single instance is not enough to constrain the student representations. For example, the topological ambiguity may occur in image encoding, since two symmetric representations have the same cosine similarity compared to a single teacher representation. We conjecture that this can be mitigated by incorporating multiple anchor points to the query points. Based on this idea, we introduce cross-modal similarity matching loss.

**Cross-modal similarity matching.** To better align a student representation $q_i$ with the teacher representation $k_i$, we introduce cross-modal similarity matching (CSM) loss. We use multiple anchor points to cope with the ambiguity problem mentioned above. Further, we use text representations as anchor points, since we can easily generate prototypical anchor points by using text prompts and class

Table 1: Examples of context-based prompt augmentation for ambiguous class labels on Flowers102.

| Label Index | Label Name | Text Prompt |
|:---:|:---|:---|
| 7 | bird of paradise | "A photo of {bird of paradise}. {Strelitzia is a genus of five species of perennial plants, native to South Africa. It belongs to the plant family Strelitziaceae}." |
| 10 | snapdragon | "A photo of {snapdragon}. {Antirrhinum is a genus of plants commonly known as dragon flowers or snapdragons because of the flowers' fancied resemblance to the face of a dragon that opens and closes its mouth when laterally squeezed}." |

labels. Since image and text representations are precisely aligned in CLIP, we can effectively apply this approach. More specifically, the BeamCLIP first measures the normalized image-text similarity of the query image compared to prototypical text points in the teacher's embedding space. Then, it encourages the student to mimic the same image-text similarity in the student's embedding space.

More formally, we generate multiple anchor representations $A = \{a_j\}_{j=1}^M$ by encoding class texts $C = \{c_j\}_{j=1}^M$ with the teacher text encoder $g_\psi^T(\cdot)$ (in other words, $a_j = g_\psi^T(c_j)$). To measure the similarity regarding to multiple anchor representations $A$, we define the normalized cross-modal similarity as follows:

$$s_j(k_i, A) = \frac{\exp\left((k_i \cdot a_j)/\tau\right)}{\sum_{m=1}^M \exp\left((k_i \cdot a_m)/\tau\right)} \tag{5}$$

where $\tau$ is a temperature hyperparameter that is set to 0.01 in our experiments.

Then, we evaluate the cross-modal similarity distribution by using a set of normalized cross-modal similarities:

$$P(k_i|A) = [s_1(k_i, A), ..., s_M(k_i, A)]. \tag{6}$$

Then, the student model is optimized to mimic the normalized cross-modal similarity of the teacher's embedding space by minimizing the cross entropy, *i.e.,* $H(P(k_i|A), P(q_i|A))$.

We further minimize the entropy of normalized cross-modal similarities in the student embedding space *i.e.,* $H(P(q_i|A))$. This minimization helps the student provide query representations $q_i$ that are more attracted to anchor representations $A = \{a_j\}_{j=1}^M$. This entropy minimization is also known to be effective in other domains such as semi-supervised learning [15].

Altogether, the CSM loss is formulated as follows:

$$\mathcal{L}_{\text{CSM}} = \sum_{i=1}^N H(P(k_i|A), P(q_i|A)) + \sum_{i=1}^N H(P(q_i|A)). \tag{7}$$

**Final Loss.** The final loss of the BeamCLIP is formulated as follows:

$$\mathcal{L}_{\text{BeamCLIP}} = \mathcal{L}_{\text{CSM}} + \lambda_{\text{ISM}}\mathcal{L}_{\text{ISM}} \tag{8}$$

where $\lambda_{\text{ISM}}$ is the scale hyperparameter that is set to 10 in our experiments.

### 3.2 Context-based prompt augmentation

We found that lexical ambiguity in prompt texts can lead to semantically incorrect text embeddings. This may result in an unexpected discrepancy of image-text alignment in the teacher's embedding space. For example, Flowers102 [28] dataset has some classes with unusual and ambiguous flower names, such as "snapdragon", "bird of paradise", and "colt's foot".[1] Therefore, incorrect prototypical anchor points might be compared with a query image. To address this issue of semantic ambiguities in the text, we introduce context-based prompt augmentation (CPA), a data-driven approach that augments basic prompts with contextual text such as Wikipedia descriptions or hierarchical labels.

---

[1]Examples can be found at: 102 Category Flower Dataset.

For prompt tuning with Wikipedia descriptions, we use the template "A photo of a {label}. {Wikipedia description}". We use this template for Flowers102 and Pets37 in our experiments. We provide some examples from the Flowers102 dataset in Table 1. For prompt tuning with hierarchical labels, we use the template "A photo of a {fine label}, categorized as {coarse label}". We use this template for CIFAR100 and ImageNet in our experiments. Analogous examples from CIFAR100 can be found in Table 8 of Appendix C.

## 3.3 Other details

**Self-supervised pre-training of student.** To help the student mimic the teacher's cross-modal embedding space better, we pre-train the student image encoder with a self-supervised method. Since self-supervised pre-training such as SimCLR [4] and MoCo-V2 [18] provides a weakly clustered embedding space based on similarities, it can be used as a better initial state for the student to mimic the teacher's embedding space.

For self-supervised pre-training, we adopt SimCLR, since it is simple and effective. SimCLR learns transferable visual representations by using InfoNCE loss [30, 39] which encourages agreement between multiple views of the same image. More specifically, InfoNCE maximizes the similarity between multiple views of the same image (*i.e.,* positive samples) and minimizes the similarity to multiple views of all other images in a training batch (*i.e.,* negative samples). InfoNCE loss of SimCLR can be formulated as follows:

$$\mathcal{L}_{\text{InfoNCE}} = -\log \frac{\exp\left((h_i^S \cdot h_{i'}^S)/\tau\right)}{\sum_{k=1}^{2B} \mathbb{1}_{[k \neq i]} \exp\left((h_i^S \cdot h_k^S)/\tau\right)} \tag{9}$$

where $h_i^S \in \mathbb{R}^{128}$ is a projection of a student representation $q_i \in \mathbb{R}^{512}$, $\tau$ is a temperature hyperparameter that is set to 0.1, $\mathbb{1}_{[k \neq i]}$ is an indicator function whose value is 1 if $k \neq i$, and $B$ is a batch size. Here, $h_i$ and $h_{i'}$ are projections of multiple views of the same input images $x_i$.

**Optimization.** For optimization we use SGD with cosine annealing schedule (SGDR) [25]. To stabilize training, we use a momentum encoder that updates its weights via exponential moving average (EMA) [18, 16]. The momentum encoder of a student $\theta_{\hat{S}}$ is updated using the following rule:

$$\theta_{\hat{S}} \leftarrow m\theta_{\hat{S}} + (1-m)\theta_S \tag{10}$$

where $\theta_S$ is the image encoder of a student model and $m$ is a momentum hyperparameter that is set 0.99 in our experiments.

## 4 Experiments

**Downstream datasets.** We evaluate the BeamCLIP on six standard benchmark datasets: CIFAR10 [23], CIFAR100 [23], STL10 [9], Flowers102 [28], Pets37 [31], and ImageNet-1K [10]. Following convention, we split the datasets into train, validation, and test sets. Then, we use train set for transfer, and test set for evaluation. For ImageNet, we use the validation set as a test set, since its test set does not provide labels. More details on the datasets can be found in Appendix A.

### 4.1 Linear probe accuracy on ImageNet-1K

**BeamCLIP-RN50.** We compare the BeamCLIP with various self-supervised methods in terms of linear probe accuracy on ImageNet-1K. Following the conventional protocol, we use ResNet-50 [17] as the base encoder and evaluate the learned representations by using logistic regression. We use LBFGS algorithm [44] for logistic regression. Its hyperparameter $C$ is determined through coarse-grained hyperparameter search on the validation split. And, the accuracy is evaluated in the test split. We found that it provides the best linear probe accuracy when $C$ is set to 100. We perform our experiments on 8 NVIDA A100 GPUs and it takes about 30 hours for 200 epoch training.

Table 2 shows the comparison of the BeamCLIP with vision-only self-supervised methods such as SimCLR [4], MoCo-v2 [6], SwAV [3], BYOL [16], and SimSiam [5]. The BeamCLIP provides better visual representation by achieving 74.8% top-1 linear probe accuracy on ImageNet-1K [10]. While self-supervised methods take long training epochs to achieve comparable accuracy, BeamCLIP-RN50

Table 2: **Comparison of linear probe accuracy on ImageNet-1K.** We compare the BeamCLIP with vision-only self-supervised methods in terms of linear probe accuracy on ImageNet-1K. The BeamCLIP representations provide higher linear probe accuracy than self-supervised methods. This means better transferability. We denote each row with gray color in case the number of epochs is greater than 200.

| Type | Method | Img. Enc. | Teacher | Text | Batch | Epochs | Top-1 |
|---|---|---|---|---|---|---|---|
| | Supervised | RN50 | ✗ | ✗ | 256 | 100 | 76.2 |
| Self-Supervised Learning | SimCLR [4] | RN50 | ✗ | ✗ | 512 | 200 | 65.6 |
| | SimCLR | RN50 | ✗ | ✗ | 512 | 400 | 66.7 |
| | SimCLR | RN50 | ✗ | ✗ | 512 | 800 | 67.4 |
| | SimCLR | RN50 | ✗ | ✗ | 4096 | 200 | 66.8 |
| | SimCLR | RN50 | ✗ | ✗ | 4096 | 800 | 69.1 |
| | MoCo-v2 [6] | RN50 | ✗ | ✗ | 256 | 200 | 67.5 |
| | MoCo-v2 | RN50 | ✗ | ✗ | 256 | 400 | 70.1 |
| | MoCo-v2 | RN50 | ✗ | ✗ | 256 | 800 | 71.1 |
| | SwAV [3] | RN50 | ✗ | ✗ | 256 | 200 | 72.0 |
| | SwAV | RN50 | ✗ | ✗ | 256 | 400 | 74.3 |
| | BYOL-GA [16] | RN50 | ✗ | ✗ | 4,096 | 200 | 70.6 |
| | BYOL-GA | RN50 | ✗ | ✗ | 4,096 | 1,000 | 74.3 |
| Vision-Language Pre-training | CLIP [32] | RN50 | ✗ | ✓ | 32,768 | 32 | 73.3 |
| | CLIP | ViT-B/16 | ✗ | ✓ | 32,768 | 32 | 80.2 |
| Unsupervised Representation Transfer | **BeamCLIP** (ours) | RN50 | CLIP | ✗ | 512 | 200 | **74.8** |
| | Δ SimCLR | - | - | - | - | - | +9.2 |
| | Δ CLIP-RN50 | - | - | - | - | - | +1.5 |

achieves better accuracy with less training epochs. Also, note that BeamCLIP-RN50's representations provide better accuracy than CLIP-RN50's representations.

**BeamCLIP-RN18.** We also provide the ImageNet-1K linear probe accuracy on BeamCLIP-RN18 representations in Table 10 of Appendix C. The BeamCLIP-RN18 achieves 62.7% linear probe accuracy, while outperforming the SSL methods such as SimCLR (47.1%) and MoCo-v2 (48.6%).

### 4.2 Zero-shot accuracy on ImageNet-1K

To check if the BeamCLIP also inherits the powerful zero-shot capability of CLIP, we compare zero-shot accuracy of CLIP variants on ImageNet-1K. For zero-shot measure, we use CC-3M [34] and ImageNet-21K (12M samples) [33] that do not have overlap with Imagenet-1K. Table 3 shows the comparison of zero-shot accuracy. The BeamCLIP-RN50 achieves about 53.6% zero-shot accuracy that is highly comparable with CLIP RN-50 (59.6%).

### 4.3 Transfer learning accuracy on various datasets

**Setting.** We evaluate how effectively the BeamCLIP transfers CLIP-ViT representations into a student model by evaluating classification accuracy on various datasets (see Table 4). We choose ResNet-50 [17] as the student model to compare the distilled target model with CLIP-RN50. Also, ResNet-50 is conventionally used in evaluating linear probe accuracy on ImageNet-1K. However, the BeamCLIP can adopt any architecture, not just ResNet-50.

As baselines, we choose two representative distillation methods among many methods: (1) conventional knowledge distillation (KD) [19] and (2) contrastive representation distillation (CRD) [38]. Since conventional KD aims to mimic the task-specific predictions of the teacher model unlike the BeamCLIP, we apply the KL divergence on minimizing the cross-modal similarity distribution (*i.e.,* $P(q_i|A)$ and $P(k_i|A)$), instead of the Cross-entropy (CE). CRD proposes a variant of InfoNCE loss for representation distillation, which we apply on normalized representations (*i.e.,* $q_i$ and $k_i$). The details of each method can be found in the related work section 2.

Table 3: **Comparison of zero-shot accuracy on ImageNet-1K.** On ImageNet-1K, the BeamCLIP RN50 achieves about 53.6% zero-shot accuracy that is higly comparable with CLIP RN-50 (59.6%). To achieve such a high zero-shot accuracy, CLIP uses very large image-text pair data (WIT-400M). Instead, the BeamCLIP can achieve the comparable zero-shot accuracy by effectively transferring the teacher's representations, while using only 3% data (ImageNet-21K (12M)). Note that OpenCLIP provides only about 36.5% zero-shot accuracy with the similar amount of data (CC-12M).

| Method | Image Encoder | Training Data | Teacher | Text Anchor | Batch | Epochs | ImageNet Zero-shot |
|---|---|---|---|---|---|---|---|
| CLIP [32] | ViT-B/16 | WIT-400M | ✗ | ✗ | 32,768 | 32 | 68.6 |
| CLIP [32] | RN50 | WIT-400M | ✗ | ✗ | 32,768 | 32 | **59.6** |
| OpenCLIP [21] | RN50 | CC-12M | ✗ | ✗ | $256 * 8$ | 32 | 36.5 |
| OpenCLIP [21] | RN50 | YFCC-15M | ✗ | ✗ | $256 * 8$ | 32 | 32.7 |
| **BeamCLIP** | RN50 | CC-3M | CLIP | IN-1K | $64 * 8$ | $100^*$ | $49.5^*$ |
| **BeamCLIP** | RN50 | IN-21K (12M) | CLIP | IN-1K | $64 * 8$ | $50^*$ | $53.6^*$ |
| **BeamCLIP** (not ZS) | RN50 | IN-1K (1.2M) | CLIP | IN-1K | $64 * 8$ | 200 | 66.2 |

Table 4: **Comparison of teacher and student accuracy on various datasets.** Conventional knowledge distillation with the KL divergence is not effective in transferring CLIP-ViT representations. In contrast, the BeamCLIP effectively transfers CLIP-ViT/16 representations into ResNet-50 by using unlabeled query data. Compared to zero-shot CLIP-RN50, the BeamCLIP improves about 6.57% accuracy on ImageNet-1K. We denoted with $*$ in cases our student model outperforms the teacher model.

| Method | Model Type | Img. Enc. | Param. Size | CIFAR10 | CIFAR100 | STL10 | Flowers102 | Pets37 | ImageNet-1K |
|---|---|---|---|---|---|---|---|---|---|
| CLIP [32] (zero-shot) | T | ViT-B/16 | 76M | 91.6 | **68.7** | **98.2** | 70.4 | **88.9** | **68.6** |
| CLIP [32] (zero-shot) | - | RN50 | 24M | 75.6 | 41.6 | 94.3 | 65.9 | 85.4 | 59.6 |
| CRD [38] | S | RN50 | 24M | 76.78 | 38.83 | 81.41 | 26.15 | 62.22 | 30.90 |
| KD [19] | S | RN50 | 24M | 90.89 | 58.02 | 93.28 | 49.01 | 77.51 | 56.38 |
| **BeamCLIP** (ours) | S | RN50 | 24M | **92.10**$^*$ | **67.35** | **97.45** | **75.86**$^*$ | **86.94** | **66.17** |
| Δ CLIP-RN50 | - | - | - | +16.4 | +25.78 | +3.15 | +9.96 | +1.54 | +6.57 |
| Δ Teacher (%) | - | - | - | 100.5 | 98.0 | 99.2 | 107.7 | 97.8 | 96.5 |

**Results.** Table 4 shows a comparison of teacher and student accuracy on various datasets. We empirically demonstrate that the BeamCLIP can effectively transfer vision and language representations of a large teacher model (CLIP-ViT/16) into a small student model (ResNet-50), while achieving comparable or better classification accuracy. We find that the KL divergence used in conventional knowledge distillation (KD) is not effective in transferring CLIP-ViT representations. Also, the contrastive learning-based approach is not effective. Unlike this, the BeamCLIP can effectively transfer CLIP-ViT/16 representations into ResNet-50, achieving very high accuracy that is comparable or better than the teacher accuracy. For example, for ImageNet-1K, when compared to zero-shot CLIP-RN50, BeamCLIP-RN50 provides about 10.5% better accuracy on the same size model. When compared to CLIP-ViT/16, BeamCLIP-RN50 provides about 1.8% better accuracy on the much smaller model. KD simply minimizes the error between single instances. We conjecture that the cross-modal similarity to multiple anchor points introduced in the BeamCLIP helps the student preserve the topology of the teacher's embedding space.

Also, note that context-based prompt augmentation helps achieve better accuracy after distillation. Since Flowers102 has many ambiguous labels, our experiment shows that text prompt augmentation significantly increases the student's accuracy compared to the teacher's accuracy.

Table 5: **Ablation study results.** The acronym denotes the sub-methods introduces in the BeamCLIP : (1-1) ISM means instance similarity matching loss, (1-2) CSM means cross-modal similarity matching loss, (2) CPA means context-based prompt augmentation, and (3) SSL PT means self-supervised pre-training of student, . All the technical components contribute to the improvements of transfer learning accuracy at the student. Note that we only perform CPA on datasets with more than 100 of class labels.

| Method | Type | Img. Enc. | (1-1) ISM | (1-2) CSM | (2) CPA | (3) SSL PT | CIFAR10 | CIFAR100 | Flowers102 | ImageNet-1K |
|---|---|---|---|---|---|---|---|---|---|---|
| CLIP [32] (zero-shot) | T | ViT-B/16 | - | - | - | - | 91.6 | **68.7** | 70.4 | **68.6** |
| | S | RN50 | Cosine | ✗ | ✗ | ✗ | 39.07 | 6.04 | - | - |
| | S | RN50 | Cosine | ✗ | ✗ | SimCLR | 87.00 | 48.26 | 3.59 | 51.83 |
| Unsupervised | S | RN50 | ✗ | CE | ✗ | ✗ | 91.28 | 58.90 | 12.94 | 63.30 |
| Representation | S | RN50 | ✗ | CE | ✗ | SimCLR | 91.53 | 65.64 | 62.18 | 65.45 |
| Transfer | S | RN50 | ✗ | CE+EntMin | ✗ | SimCLR | 91.71 | 66.14 | 63.96 | **66.23** |
| (**BeamCLIP**) | S | RN50 | Cosine | CE+EntMin | ✗ | SimCLR | 92.10* | 66.18 | 64.14 | 65.76 |
| | S | RN50 | Cosine | CE+EntMin | ✓ | SimCLR | - | **67.35** | **75.86*** | 66.17 |

## 4.4 Ablation study

Table 5 shows the ablation study results of the BeamCLIP . Our empirical findings are as follows: (1) instance similarity distillation is not enough by itself to preserve the topology of the teacher's embedding space. (2) cross-modal similarity distillation compared to multiple anchor points helps the student mimic the teacher's embedding space. (3) self-supervised pre-training of the student significantly helps the student mimic the teacher's embedding space. (4) Entropy minimization (EntMin) helps to improve the accuracy. (5) Context-based prompt augmentation helps measure the similarity more precisely. As shown in the table, Flowers102 dataset is sensitive to self-supervised pre-training of student. We conjecture that since Flowers102 dataset has only 1020 training samples for the 102 classes, it is not enough to probe the teacher's representation space.

## 5 Conclusion and Limitations

**Conclusion.** Our BeamCLIP provides an effective and accessible framework that distills large-scale multimodal representations of CLIP. Combining our similarity-based distillation and context-based prompt augmentation with self-supervised training, we empirically demonstrate that the BeamCLIP can effectively transfer the vision and language representations of a large teacher model (CLIP-ViT/16) into a smaller student model (ResNet-50) while achieving comparable or better classification accuracy. We also show that the BeamCLIP provides better visual representations by achieving 74.8% top-1 linear probe accuracy on ImageNet-1K when compared to vision-only self-supervised methods (SimCLR: 65.6%, supervised: 76.2%).

**Limitations.** With the help of rich representations of pre-trained CLIP, the BeamCLIP can learn better representations than SSL methods. However, since SSL methods can increase the performance at longer training epochs, the performance margin may be decreased in such a setting. Another shortcoming is that context-based prompt augmentations may require additional engineering efforts.

## Broader impact

This research aims to provide an simple and effective way to leverage CLIP for representation learning. With the help of CLIP, the BeamCLIP can learn better representations than self-supervised learning (SSL) methods. Since training CLIP requires very large data and hundreds of GPUs, it is important to provide a way to effectively reuse the pre-trained CLIP rather than training from scratch on a target model. We believe that BeamCLIP can help to save cost and time.

## References

[1] L. Beyer, X. Zhai, A. Royer, L. Markeeva, R. Anil, and A. Kolesnikov. Knowledge distillation: A good teacher is patient and consistent. *arXiv preprint arXiv:2106.05237*, 2021.

[2] T. Brown, B. Mann, N. Ryder, M. Subbiah, J. D. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell, et al. Language models are few-shot learners. *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[3] M. Caron, I. Misra, J. Mairal, P. Goyal, P. Bojanowski, and A. Joulin. Unsupervised learning of visual features by contrasting cluster assignments. In *Neural Information Processing Systems (NeurIPS)*, 2020.

[4] T. Chen, S. Kornblith, M. Norouzi, and G. Hinton. A simple framework for contrastive learning of visual representations. In *International Conference on Machine Learning (ICML)*, 2020.

[5] X. Chen and K. He. Exploring simple siamese representation learning. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 15750–15758, 2021.

[6] X. Chen, H. Fan, R. Girshick, and K. He. Improved baselines with momentum contrastive learning. *arXiv preprint arXiv:2003.04297*, 2020.

[7] Y.-C. Chen, L. Li, L. Yu, A. El Kholy, F. Ahmed, Z. Gan, Y. Cheng, and J. Liu. Uniter: Universal image-text representation learning. In *European Conference on Computer Vision (ECCV)*, 2020.

[8] H. M. Choi, H. Kang, and D. Oh. Unsupervised representation transfer for small networks: I believe i can distill on-the-fly. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2021.

[9] A. Coates, A. Ng, and H. Lee. An analysis of single-layer networks in unsupervised feature learning. In *International Conference on Artificial Intelligence and Statistics*, 2011.

[10] J. Deng, W. Dong, R. Socher, L.-J. Li, K. Li, and L. Fei-Fei. Imagenet: A large-scale hierarchical image database. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2009.

[11] C. Doersch, A. Gupta, and A. A. Efros. Unsupervised visual representation learning by context prediction. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2015.

[12] A. Dosovitskiy, L. Beyer, A. Kolesnikov, D. Weissenborn, X. Zhai, T. Unterthiner, M. Dehghani, M. Minderer, G. Heigold, S. Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations (ICLR)*, 2021.

[13] Z. Fang, J. Wang, L. Wang, L. Zhang, Y. Yang, and Z. Liu. Seed: Self-supervised distillation for visual representation. In *International Conference on Learning Representations (ICLR)*, 2021.

[14] S. Gidaris, P. Singh, and N. Komodakis. Unsupervised representation learning by predicting image rotations. In *International Conference on Learning Representations (ICLR)*, 2018.

[15] Y. Grandvalet and Y. Bengio. Semi-supervised learning by entropy minimization. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2005.

[16] J.-B. Grill, F. Strub, F. Altché, C. Tallec, P. H. Richemond, E. Buchatskaya, C. Doersch, B. A. Pires, Z. D. Guo, M. G. Azar, et al. Bootstrap your own latent: A new approach to self-supervised learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[17] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *IEEE/CVF conference on Computer Vision and Pattern Recognition (CVPR)*, 2016.

[18] K. He, H. Fan, Y. Wu, S. Xie, and R. Girshick. Momentum contrast for unsupervised visual representation learning. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.

[19] G. Hinton, O. Vinyals, and J. Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

[20] A. G. Howard, M. Zhu, B. Chen, D. Kalenichenko, W. Wang, T. Weyand, M. Andreetto, and H. Adam. Mobilenets: Efficient convolutional neural networks for mobile vision applications. *arXiv preprint arXiv:1704.04861*, 2017.

[21] G. Ilharco, M. Wortsman, R. Wightman, C. Gordon, N. Carlini, R. Taori, A. Dave, V. Shankar, H. Namkoong, J. Miller, H. Hajishirzi, A. Farhadi, and L. Schmidt. Openclip, jul 2021. URL https://doi.org/10.5281/zenodo.5143773.

[22] C. Jia, Y. Yang, Y. Xia, Y.-T. Chen, Z. Parekh, H. Pham, Q. V. Le, Y. Sung, Z. Li, and T. Duerig. Scaling up visual and vision-language representation learning with noisy text supervision. In *International Conference on Machine Learning (ICML)*, 2021.

[23] A. Krizhevsky, G. Hinton, et al. Learning multiple layers of features from tiny images. 2009.

[24] B. Lester, R. Al-Rfou, and N. Constant. The power of scale for parameter-efficient prompt tuning. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2021.

[25] I. Loshchilov and F. Hutter. Sgdr: Stochastic gradient descent with warm restarts. In *International Conference on Learning Representations (ICLR)*, 2017.

[26] J. Lu, D. Batra, D. Parikh, and S. Lee. Vilbert: Pretraining task-agnostic visiolinguistic representations for vision-and-language tasks. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

[27] R. Müller, S. Kornblith, and G. Hinton. When does label smoothing help? In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

[28] M.-E. Nilsback and A. Zisserman. Automated flower classification over a large number of classes. In *Indian Conference on Computer Vision, Graphics & Image Processing*, 2008.

[29] A. Oliver, A. Odena, C. A. Raffel, E. D. Cubuk, and I. Goodfellow. Realistic evaluation of deep semi-supervised learning algorithms. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2018.

[30] A. v. d. Oord, Y. Li, and O. Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

[31] O. M. Parkhi, A. Vedaldi, A. Zisserman, and C. Jawahar. Cats and dogs. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2012.

[32] A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark, et al. Learning transferable visual models from natural language supervision. *arXiv preprint arXiv:2103.00020*, 2021.

[33] T. Ridnik, E. Ben-Baruch, A. Noy, and L. Zelnik-Manor. Imagenet-21k pretraining for the masses. 2021.

[34] P. Sharma, N. Ding, S. Goodman, and R. Soricut. Conceptual captions: A cleaned, hypernymed, image alt-text dataset for automatic image captioning. In *the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2018.

[35] W. Su, X. Zhu, Y. Cao, B. Li, L. Lu, F. Wei, and J. Dai. Vl-bert: Pre-training of generic visual-linguistic representations. In *International Conference on Learning Representations (ICLR)*, 2019.

[36] C. Szegedy, V. Vanhoucke, S. Ioffe, J. Shlens, and Z. Wojna. Rethinking the inception architecture for computer vision. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016.

[37] A. Tejankar, S. A. Koohpayegani, V. Pillai, P. Favaro, and H. Pirsiavash. Isd: Self-supervised learning by iterative similarity distillation. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2021.

[38] Y. Tian, D. Krishnan, and P. Isola. Contrastive representation distillation. In *International Conference on Learning Representations (ICLR)*, 2020.

[39] M. Tschannen, J. Djolonga, P. K. Rubenstein, S. Gelly, and M. Lucic. On mutual information maximization for representation learning. In *International Conference on Learning Representations (ICLR)*, 2020.

[40] W. Van Gansbeke, S. Vandenhende, S. Georgoulis, M. Proesmans, and L. Van Gool. Scan: Learning to classify images without labels. In *European Conference on Computer Vision (ECCV)*, 2020.

[41] T. Wang and P. Isola. Understanding contrastive representation learning through alignment and uniformity on the hypersphere. In *International Conference on Machine Learning*, pages 9929–9939. PMLR, 2020.

[42] L. Yuan, F. E. Tay, G. Li, T. Wang, and J. Feng. Revisiting knowledge distillation via label smoothing regularization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.

[43] R. Zhang, P. Isola, and A. A. Efros. Colorful image colorization. In *European Conference on Computer Vision (ECCV)*, 2016.

[44] C. Zhu, R. H. Byrd, P. Lu, and J. Nocedal. Algorithm 778: L-bfgs-b: Fortran subroutines for large-scale bound-constrained optimization. *ACM Transactions on mathematical software (TOMS)*, 23(4):550–560, 1997.


# A  Datasets Details

We demonstrate the effectiveness of the BeamCLIP by using six downstream datasets. Table 5 shows the details of the downstream datasets.

Table 5: Details of datasets used for the BeamCLIP evaluation.

| Dataset | Image Size | Classes | Train Size | Val Size | Test Size |
|---------|-----------|---------|-----------|----------|-----------|
| CIFAR10 [23] | 32x32 | 10 | 40,000 | 10,000 | 10,000 |
| CIFAR100 [23] | 32x32 | 100 | 40,000 | 10,000 | 10,000 |
| STL10 [9] | 128x128 | 10 | 4,000 | 1,000 | 8,000 |
| Flowers102 [28] | 224x224 | 102 | 1,020 | 1,020 | 6,149 |
| Pets37 [31] | 224x224 | 37 | 2,944 | 736 | 3,669 |
| ImageNet [10] | 224x224 | 1,000 | 1,231,167 | 50,000 | 50,000 |

# B  Method Details

In this section, we provide some details of the BeamCLIP . More specifically, we provide the details of two main contributions that are (1) cross-modal similarity matching (CSM) and (2) context-based prompt augmentation (CPA). Also, we provide the other implementation details such as image augmentation, similarity smoothing, model hyperparameters, etc.

## B.1  Image augmentation details

We use conventional image augmentation when performing representation transfer by using unlabeled images in downstream datasets. Table 6 provides a list of image augmentation used for unsupervised representation transfer on downstream datasets.

Table 6: A list of image augmentations used in the BeamCLIP .

| Mode | Augmentation | Parameters |
|------|-------------|-----------|
| Train | RandomResizedCrop | - |
| | RandomHorizontalFlip | p=0.5 |
| | RandomColorJitter | p=0.8 |
| | GaussianBlur | p=0.5, min=0.1, miax=2.0 |
| | Normalize | - |
| Val | Resize | input_size + 0.1 * input_size |
| | CenterCrop | input_size |
| | Normalize | - |

## B.2  Cross-modal similarity matching details

Cross-modal similarity matching (CSM) is the main method of the BeamCLIP . To make the concept of CSM clearer, we provide an illustration of CSM in Figure 3.

## B.3  Context-based prompt augmentation details

To prepare for better text anchor embeddings for unsupervised representation transfer, we introduce context-based prompt augmentation (CPA). To make the concept of CPA clearer, we provide an illustration of CPA in Figure 4.

## B.4  Other implementation details

**Similarity Smoothing.** To improve the effectiveness of distillation, we apply Label Smoothing (LS) [36] to the cross-modal similarity distillation loss. Recent works [27, 42] show that Label Smoothing

query image $x_i$

topological ambiguity
in image encoding

query image $x_i$

"a photo {dog}"

"a photo {cat}"

"a photo {horse}"

at the student $\approx$ at the teacher

**Cross-modal Similarity Distillation**

Figure 3: **Illustration of cross-modal similarity matching.** Topological ambiguity may occur in image encoding, since query image embedding $q_{i1}$ and $q_{i2}$ can have the same cosine similarity compared to a single teacher image embedding $k$, while heading towards different directions. To mitigate this problem, we introduce cross-modal similarity matching that encourage the student to mimic the same cross-modal similarity distribution (measured against multiple anchor text points) in teacher's embedding space.

$a_i$ "a photo {snapdragon}"

$a_j$ "a photo {dragon}"

Lexical ambiguity
in text encoding

$a_k$ "a photo {flower}"

"a photo {snapdragon}.
{Antirrhinum is a genus of plants commonly known as dragon flowers ⋯ because of the flowers' fancied resemblance to the face of a dragon ⋯}"

$a_j$ "a photo {dragon}"

$a_k$ "a photo {flower}"

**Context-based Prompt Augmentation**

Figure 4: **Illustration of context-based prompt augmentation.** The lexical ambiguity may occur in text encoding, since the same text may have multiple different meanings. To mitigate this problem, we introduce context-based prompt augmentation that helps resolve the ambiguity with contextual texts such as Wikipedia descriptions.

helps knowledge distillation. To apply Label Smoothing, we determine the most similar anchor representation as follows:

$$j^* = \arg\max_j s_j(k_i, A). \tag{11}$$

Table 7: Coarse and fine labels for CIFAR100.

| Coarse Label | Fine Label |
|---|---|
| aquatic mammals | beaver, dolphin, otter, seal, whale |
| fish | aquarium fish, flatfish, ray, shark, trout |
| flowers | orchid, poppy, rose, sunflower, tulip |
| food containers | bottle, bowl, can, cup, plate |
| household electrical devices | clock, keyboard, lamp, telephone, television |
| household furniture | bed, chair, couch, table, wardrobe |
| insects | bee, beetle, butterfly, caterpillar, cockroach |
| large carnivores | bear, leopard, lion, tiger, wolf |
| large man-made outdoor things | bridge, castle, house, road, skyscraper |
| large natural outdoor scenes | cloud, forest, mountain, plain, sea |
| large omnivores and herbivores | camel, cattle, chimpanzee, elephant, kangaroo |
| medium mammals | fox, porcupine, possum, raccoon, skunk |
| non-insect invertebrates | crab, lobster, snail, spider, worm |
| people | baby, boy, girl, man, woman |
| reptiles | crocodile, dinosaur, lizard, snake, turtle |
| small mammals | hamster, mouse, rabbit, shrew, squirrel |
| trees | maple tree, oak tree, palm tree, pine tree, willow tree |
| vehicles 1 | bicycle, bus, motocycle, pickup truck, train |
| vehicles 2 | lawn mower, rocket, streetcar, tank, tractor |

Table 8: Examples of prompt augmentation with hierarchical labels for CIFAR100.

| Label Name | Text Prompt |
|---|---|
| baby | `"A photo of a {baby}, categorized as {people}."` |
| beaver | `"A photo of a {beaver}, categorized as {aquatic mammals}."` |
| bee | `"A photo of a {bee}, categorized as {insect}."` |

Then, we generate a modified cross-modal similarity distribution:

$$s_j(k_i, A)^{LS} = \mathbb{1}_{[j=j^*]}(1-\alpha) + \alpha/M \tag{12}$$

where $\mathbb{1}_{[j=j^*]}$ is the indicator function whose value is 1 if $j = j^*$, $M$ is the number of anchors, and $\alpha$ is the smoothing hyperparameter that is set to 0.2 in our experiments.

## B.5 Model hyperparameters

Table 9 provides the summary of model hyperparamters. We use the same hyperparameters on all downstream datasets if not explicitly declared.

Table 9: BeamCLIP hyperparameters.

| Hyperparameter | Value |
|---|---|
| CSM loss temperature | 0.01 |
| ISM loss scale | {0.1, 1.0, 10.0} |
| similarity smoothing (LS) sacle | 0.2 |
| optimizer | SGDR [25] |
| initial learning rate | 0.5 |
| weight decay | 1e-6 |
| EMA momentum | 0.99 |
| batch size | {256, 512} |
| epochs | 200 |

## C   Additional Experiment Results

In this section, we provide additional experiment results. Especially, we provide some experiment results to discuss the characteristics of unsupervised representation transfer with cross-modal similarity matching.

### C.1   ImageNet-1K linear probe accuracy on ResNet-50

In the experiment section, we provide ImageNet-1K top-1 linear probe accuracy on ResNet-50 to measure the effectiveness of the representations of the BeamCLIP . We show that the visual representations transferred from a large pre-trained multimodal model (i.e., CLIP) outperform the state-of-the-art self-supervised learning methods such as SimCLR (65.6%) and MoCo-v2 (67.5%), while closing the gap with supervised learning (76.2%). In this subsection, we additionally provide the linear probe accuracy by increasing the training epochs. As shown in Figure 5, it slightly increases (from 74.8% to 75.0%), as the training epochs increases from 200 to 400.

Figure 5: ImageNet-1K top-1 linear probe accuracy on ResNet-50.

Also, we provide the learning curve of transfer learning on ImageNet in Figure 6.

Figure 6: Validation accuracy on representation transfer with ImageNet

## C.2  ImageNet-1K linear probe on ResNet-18

To check if the BeamCLIP can transfer CLIP representations into smaller models than ResNet-50 (24M), we also measure ImageNet-1K Top-1 linear probe accuracy on ResNet-18 (11M). ResNet-18 is trained from scratch (not self-supervised pre-trained with SimCLR), while transferring CLIP ViT-B/16 representations. Table 10 shows ImageNet-1K Top-1 linear probe accuracy on ResNet-18 representations. As similar to ResNet-50, BeamCLIP learns better representations than SSL methods such as SimCLR [4], MoCo-v2 [6], BYOL [16], and SwAV [3]. More important, the BeamCLIP provides better performance than OSS [8] that simultaneously learns and transfers representations from ResNet-50.

Table 10: **ImageNet-1K Top-1 linear probe accuracy on ResNet-18**. By transferring the representations of CLIP ViT-B/16 to ResNet-18, the BeamCLIP-RN18 achieves 62.7% linear probe accuracy, while outperforming the SSL methods such as SimCLR (47.1%) and MoCo-V2 (48.6%).

| | | Epochs | | |
|---|---|---|---|---|
| Method | Teacher | 100 | 200 | 400 |
| Supervised | ✗ | | 69.8 | |
| SimCLR [4] | ✗ | 47.1 | 49.9 | 51.8 |
| MoCo-V2 [6] | ✗ | 48.6 | 49.9 | 51.9 |
| BYOL [16] | ✗ | 44.2 | 47.5 | 46.8 |
| BYOL-GA [16] | ✗ | 54.2 | 56.9 | 61.4 |
| SwAV [3] | ✗ | 57.7 | 61.2 | 63.7 |
| OSS [8] | SSL RN50 | 60.0 | 64.1 | 65.8 |
| **BeamCLIP** (ours) | CLIP ViT-B/16 | **62.7** | **64.8** | - |

Figure 7: ImageNet-1K top-1 linear probe accuracy on ResNet-18.

## C.3  Effects of random text prompts

In this section, we further analyze the effect of text prompts from the perspective of unsupervised learning. Before that, we briefly review the proposed method. In this paper, we propose the BeamCLIP , an unsupervised representation transfer method of a large pre-trained multimodal model such as CLIP. The BeamCLIP can transfer the visual representations of CLIP by using unlabeled images on a downstream dataset. To achieve this, we propose cross-modal similarity matching (CSM). In CSM, at first, given an unlabeled image, cross-modal similarity distribution is measured from multiple text prompt embeddings in the teacher's embedding space. Then, a student model is encouraged to mimic the cross-modal similarity distribution of the teacher model by matching these similarity distributions. To achieve effective transfer, we use anchor text embeddings by encoding text prompts. For example, on CIFAR10, we use ten text prompts in the form of `"a photo of {class name}"`. Note that the text prompts are not paired with each image.

**CIFAR10.** To further decouple the dependency to the class names of a dataset, we measure the transfer learning accuracy by using random prompts. Figure 8 shows the transfer learning accuracy on CIFAR10 with regard to the number of random text prompt of CLIP. As shown in Figure 8 (a), the BeamCLIP is effective, while using only subset text prompts. Note that the BeamCLIP (CE+EntMin) is more effective than BeamCLIP (KL), as we use more text prompts. As shown in Figure 9, the BeamCLIP is still effective compared to CLIP-RN50, even though random prompts from ImageNet are used. The values in Figure 8 are also presented in Table 11 and Table 13.

**CIFAR100.** We perform the similar experiment on CIFAR100. Table 9 shows unsupervised transfer learning accuracy of CIFAR100 [23] with regard to the number of random text prompts. The values in Figure 9 are also presented in Table 13 and Table 14.

(a) Subset prompts from CIFAR10

(b) Random prompts from ImageNet

Figure 8: **Transfer learning accuracy on CIFAR10 w.r.t the number of random text prompt. (a)** The text prompts are randomly selected from the 10 class names of CIFAR10. As shown in the blue line, the BeamCLIP is effective, while using only subset text prompts. The BeamCLIP (KL) means to use the KL-divergence for matching cross-modal similarity distribution. Note that it is more effective, when using very few text prompts (noted in a purple line). However, the BeamCLIP (CE+EntMin) is more effective as we use more text prompts. **(b)** The text prompts are randomly selected from the 1000 class names of ImageNet. The BeamCLIP is still effective compared to CLIP-RN50, even though random prompts from ImageNet.

Table 11: Transfer learning accuracy on CIFAR10 w.r.t the number of subset text prompts.

| Method | Type | Img. Enc. | 3 | 5 | 7 | 9 | 10 | - |
|---|---|---|---|---|---|---|---|---|
| CLIP [32] (zero-shot) | T | ViT-B/16 | - | - | - | - | - | **91.6** |
| CLIP [32] (zero-shot) | - | RN50 | - | - | - | - | - | 75.6 |
| BeamCLIP (CE+EntMin) | S | RN50 | 83.47 | 83.25 | 88.26 | 91.84 | **92.10**$^*$ | - |
| BeamCLIP (KL) | S | RN50 | 89.36 | 90.43 | 90.15 | 90.54 | 90.85 | - |

Table 12: Transfer learning accuracy on CIFAR10 w.r.t the number of random text prompts.

| Method | Type | Img. Enc. | 10 | 20 | 30 | 40 | - |
|---|---|---|---|---|---|---|---|
| CLIP [32] (zero-shot) | T | ViT-B/16 | - | - | - | - | **91.6** |
| CLIP [32] (zero-shot) | - | RN50 | - | - | - | - | 75.6 |
| BeamCLIP (CE+EntMin) | S | RN50 | 81.49 | 82.05 | 84.09 | **84.51** | - |
| BeamCLIP (KL) | S | RN50 | 87.76 | 87.67 | 87.83 | 87.88 | - |

(a) Subset prompts from CIFAR100

(b) Random prompts from ImageNet

Figure 9: **Unsupervised transfer learning accuracy on CIFAR100 w.r.t the number of text prompts. (a)** The text prompts are randomly selected from the 100 class names of CIFAR100. As shown in the blue line, the BeamCLIP is effective, while using only subset text prompts. Note that the BeamCLIP (KL) is more effective, when using very few text prompts (noted in a purple line). However, the BeamCLIP (CE+EntMin) is more effective as we use more text prompts. **(b)** The text prompts are randomly selected from the 1000 class names of ImageNet.

Table 13: Transfer learning accuracy on CIFAR100 w.r.t the number of subset text prompts.

| Method | Type | Img. Enc. | Prompts | | | | | - |
| | | | 20 | 40 | 60 | 80 | 100 | |
| CLIP [32] (zero-shot) | T | ViT-B/16 | - | - | - | - | - | 68.7 |
| CLIP [32] (zero-shot) | - | RN50 | - | - | - | - | - | 41.6 |
| BeamCLIP (CE+EntMin) | S | RN50 | 21.72 | 32.19 | 45.38 | 56.93 | **67.35** | - |
| BeamCLIP (KL) | S | RN50 | 52.10 | 52.93 | 53.88 | 55.15 | 56.12 | - |

Table 14: Transfer learning accuracy on CIFAR100 w.r.t the number of random text prompts.

| Method | Type | Img. Enc. | Prompts | | | - |
| | | | 100 | 500 | 1000 | |
| CLIP [32] (zero-shot) | T | ViT-B/16 | - | - | - | 68.7 |
| CLIP [32] (zero-shot) | - | RN50 | - | - | - | 41.6 |
| BeamCLIP (CE+EntMin) | S | RN50 | 45.36 | 52.44 | **58.93** | - |
| BeamCLIP (KL) | S | RN50 | 48.68 | 46.82 | 46.15 | - |

## C.4 Qualitative results

Figure 10 shows qualitative results via top-5 text-image retrieval. A red rectangle denotes an incorrect result. CLIP-RN50 provides many incorrect results since it shows relatively low zero-shot accuracy. In contrast, BeamCLIP-RN50 provides much improved results, since it is distilled from CLIP-ViT/16 which shows very high zero-shot accuracy. More interestingly, BeamCLIP-RN50 provides surprisingly good text-image retrieval results, even though unseen text prompts such as `"a photo of {pink rose}"` or `"a photo of {yellow rose}"` are given.

Figure 10: **Comparison of CLIP-RN50 and BeamCLIP-RN50.** This figure shows the top-5 text-image retrieval results. A red rectangle denotes an incorrect result. CLIP-RN50 provides many incorrect results, since it shows relatively low zero-shot accuracy. In contrast, BeamCLIP-RN50 provides much improved results, since it is distilled from CLIP-ViT/16 that shows very high zero-shot accuracy.

Figure 11: Zero-shot accuracy on ImageNet-1K trained by using ImageNet-21K