Exploring the Limits of Out-of-Distribution Detection

Abstract

Near out-of-distribution detection (OOD) is a major challenge for deep neural networks. We demonstrate that large-scale pre-trained transformers can significantly improve the state-of-the-art (SOTA) on a range of near OOD tasks across different data modalities. For instance, on CIFAR-100 vs CIFAR-10 OOD detection, we improve the AUROC from 85% (current SOTA) to more than 96% using Vision Transformers pre-trained on ImageNet21k. On a challenging genomics OOD detection benchmark, we improve the AUROC from 66% to 77% using transformer and unsupervised pre-training. To further improve performance, we explore the few-shot outlier exposure setting where a few examples from outlier classes may be available; we show that pre-trained transformers are particularly well-suited for outlier exposure, and that the AUROC of OOD detection on CIFAR-100 vs CIFAR-10 can be improved to 98.7% with just 1 image per OOD class, and 99.46% with 10 images per OOD class. For multi-modal image-text pre-trained transformers such as CLIP, we explore a new way of using just the names of outlier classes as a sole source of information without any accompanying images, and show that this outperforms previous SOTA on standard OOD benchmark tasks.

1 Introduction

Deep neural networks are increasingly used in high-stakes applications such as healthcare [Roy et al., 2021, Ren et al., 2019]. Safe deployment of models requires that models not only be accurate but also be robust to distribution shift [Amodei et al., 2016]. Neural networks can assign high-confidence predictions to mis-classified inputs [Guo et al., 2017, Lakshminarayanan et al., 2017] as well as test inputs that do not belong to one of the training classes [Nguyen et al., 2015]. This motivates the need for methods that can reliably detect out-of-distribution (OOD) inputs. There has been a lot of progress in detecting OOD inputs including methods based on discriminative models [Hendrycks and Gimpel, 2016, Lee et al., 2018, Liang et al., 2017, Liu et al., 2020] as well as methods based on deep generative models [Nalisnick et al., 2019, Zhang et al., 2020].

The difficulty of the OOD detection task depends on how semantically close the outliers are to the inlier classes. Winkens et al. [2020] distinguish between *near-OOD* tasks which are harder and *far-OOD* tasks which are easier, as evidenced by the difference in state-of-the-art (SOTA) for area under the receiver operating characteristic curve (AUROC). For instance, for a model trained on CIFAR-100 (which consists of classes such as mammals, fish, flowers, fruits, household devices, trees, vehicles, insects, etc), a far-OOD task would be detecting digits from street-view house numbers (SVHN) dataset as outliers. For the same model, detecting images from CIFAR-10 datasets (which consists of the following ten classes: airplane, automobile, bird, cat, deer, dog, frog, horse, ship, truck) would be considered a near-OOD task which is more difficult as the classes are semantically similar. There has been impressive progress on far-OOD detection, for instance there are several approaches which can achieve AUROC close to 99% on CIFAR-100 (in) vs SVHN (out) task, cf. [Sastry and Oore, 2020]. However, the state-of-the-art for near-OOD detection is much lower, for instance the SOTA AUROC

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

Figure 1: A two-dimensional PCA projection of the space of embedding vectors for 3 models, with examples of 2 in-distribution (from CIFAR-100) and 1 out-of-distribution class (from CIFAR-10). The color coding shows the Mahalanobis outlier score, while the points are projections of embeddings of members of the in-distribution CIFAR-100 classes "sunflowers" (black plus signs) and "turtle" (yellow crosses), and the OOD CIFAR-10 class "automobile" (red circles). The left panel shows a ResNet-20 trained on CIFAR-100, which assigns low Mahalanobis distance to OOD inputs and leads to overlapping clusters of class embeddings. The ViT pre-trained on ImageNet-21k (middle panel) is able to distinguish classes from each other well, but does not lead to well-separated outlier scores. ViT fine-tuned on CIFAR-100 (right panel) is great at clustering embeddings based on class, as well as assigning high Mahalanobis distance to OOD inputs (red).

for CIFAR-100 (in) vs CIFAR-10 (out) task is around 85% [Zhang et al., 2020] which is much lower than the SOTA for far-OOD tasks. Similar trends are observed in other modalities such as genomics where the SOTA AUROC of near-OOD detection is only 66% [Ren et al., 2019]. Improving the SOTA for these near-OOD detection tasks and closing the performance gap between near-OOD detection and far-OOD detection is one of the key challenges in ensuring the safe deployment of models.

Large-scale pre-trained transformers have led to significant accuracy improvements in multiple domains, cf. Bidirectional Encoder Representations from Transformers (BERT) for text [Devlin et al., 2018], Vision Transformers (ViT) for images [Dosovitskiy et al., 2021], Contrastive Language–Image Pre-training (CLIP) trained on image-text pairs [Radford et al., 2021]. We show that classifiers obtained by fine-tuning large-scale pre-trained transformers are significantly better at near-OOD detection. Intuitively, large-scale pre-training makes classifiers less vulnerable to *shortcut learning* [Geirhos et al., 2020] and making these representations better suited for near-OOD detection. Figure 1 visualizes two-dimensional PCA projections of representations from residual networks (ResNet) [He et al., 2016] trained on CIFAR-100 and ViT model pre-trained on ImageNet-21k and fine-tuned on CIFAR-100; we can observe that representations obtained by fine-tuning pre-trained transformers are better suited at near-OOD detection than representations from ResNet just trained on CIFAR-100.

Motivated by real-world applications which demand very high level of OOD detection for safe deployment, we explore variants of outlier exposure to further improve OOD detection. We show that pre-trained transformers are particularly well-suited at leveraging known outliers due to their high-quality representations (see Figure 1). We systematically vary the number of outlier examples per class, and show that even a handful of known outliers can significantly improve OOD detection, we refer to this setting as *few shot outlier exposure*. For multi-modal pre-trained transformers, we explore a new form of outlier exposure that leverages names of outlier classes without any accompanying images, and show that this can significantly improve OOD detection for zero-shot classification.

In summary, our contributions are the following:

- We show that pre-trained transformers lead to significant improvements on near-OOD benchmarks. Concretely, we improve the AUROC of OOD detection on CIFAR-100 → CIFAR-10 from 85% (current SOTA) to more than 96% using ViT pre-trained on ImageNet-21k, and improve the AUROC on a genomics OOD detection benchmark from 66% (current SOTA) to 77% using BERT.
- We show that pre-trained transformers are well-suited for few-shot outlier exposure. With just 10 labeled examples per class, we can improve the AUROC of OOD detection on CIFAR-100 vs CIFAR-10 to 99%, and improve the AUROC of OOD detection on genomics to 86%.
- We explore OOD detection for pre-trained multi-modal image-text transformers in the zero-shot classification setting, and show that just using the names of outlier classes as candidate text labels for CLIP can achieve AUROC of 94.8% on CIFAR-100 vs CIFAR-10 task. On easier far-OOD tasks such as CIFAR-$\{100, 10\}$ → SVHN, we achieve AUROC of 99.6% and 99.9% respectively.

2 Background and Related work

Notation We assume that we have an in-distribution dataset $\mathcal{D}^{\text{in}}$ of $(\boldsymbol{x}^{\text{in}}, y^{\text{in}})$ pairs where $\boldsymbol{x}$ denotes the input feature vector, and $y^{\text{in}} \in \mathcal{Y}^{\text{in}} := \{1, \ldots, K\}$ denotes the class label. Let $\mathcal{D}^{\text{out}}$ denote an out-of-distribution dataset of $(\boldsymbol{x}^{\text{out}}, y^{\text{out}})$ pairs where $y^{\text{out}} \in \mathcal{Y}^{\text{out}} := \{K{+}1, \ldots, K{+}O\}, \mathcal{Y}^{\text{out}} \cap \mathcal{Y}^{\text{in}} = \emptyset$. Depending on how different $\mathcal{D}^{\text{out}}$ is from $\mathcal{D}^{\text{in}}$, we categorize the OOD detection tasks into near-OOD and far-OOD. We first study the scenario where the model is fine-tuned only on the training set $\mathcal{D}^{\text{in}}_{\text{train}}$ without any access to OOD data. The test set contains $\mathcal{D}^{\text{in}}_{\text{test}}$ and $\mathcal{D}^{\text{out}}_{\text{test}}$ for evaluating OOD performance using AUROC. Next, we explore the scenario where a small number of OOD examples are available for training, i.e. the few-shot outlier exposure setting. In this setting, the training set contains $\mathcal{D}^{\text{in}}_{\text{train}} \bigcup \mathcal{D}^{\text{out}}_{\text{few-shot}}$, where $|\mathcal{D}^{\text{out}}_{\text{few-shot}}|$ is smaller than 100 per OOD class.

2.1 Methods for detecting OOD inputs

We describe a few popular techniques for detecting OOD inputs using neural networks.

Maximum over softmax probabilities (MSP) A baseline method for OOD detection is to use the maximum softmax probability as the confidence score, i.e. $\text{score}_{\text{msp}}(\boldsymbol{x}) = \max_{c=1,\ldots,K} p(y = c | \boldsymbol{x})$ [Hendrycks and Gimpel, 2016]. While being slightly worse than other techniques, its simplicity and performance make it an ideal baseline.

Mahalanobis distance Lee et al. [2018] proposed to fit a Gaussian distribution to the class-conditional embeddings and use the Mahalanobis distance for OOD detection. Let $f(\boldsymbol{x})$ denote the embedding (e.g. the penultimate layer before computing the logits) of an input $\boldsymbol{x}$. We fit a Gaussian distribution to the embeddings, computing per-class mean $\boldsymbol{\mu}_c = \frac{1}{N_c} \sum_{i:y_i=c} f(\boldsymbol{x}_i)$ and a shared covariance matrix $\boldsymbol{\Sigma} = \frac{1}{N} \sum_{c=1}^{K} \sum_{i:y_i=c} \big(f(\boldsymbol{x}_i) - \boldsymbol{\mu}_c\big)\big(f(\boldsymbol{x}_i) - \boldsymbol{\mu}_c\big)^{\top}$. The Mahalanobis score (negative of the distance) is then computed as: $\text{score}_{\text{Maha}}(\boldsymbol{x}) = -\min_c \left(\frac{1}{2}\big(f(\boldsymbol{x}) - \boldsymbol{\mu}_c\big)\boldsymbol{\Sigma}^{-1}\big(f(\boldsymbol{x}) - \boldsymbol{\mu}_c\big)^{\top} \right)$.

Outlier exposure Hendrycks et al. [2018] proposed *outlier exposure* which leverages a large dataset of known outliers. For classification problems, the model is trained to predict uniform distribution over labels for these inputs. Thulasidasan et al. [2021] proposed to use a single outlier class as the $(K + 1)^{\text{th}}$ class for a K-way classification problem. Roy et al. [2021] showed that leveraging the labels of known outliers (rather than assigning all known outliers to a single class) can further improve OOD detection performance.

2.2 Pre-training neural networks

Architectures using self-attention, typically based on the Transformer [Vaswani et al., 2017], often combined with large-scale pre-training directly on raw text, are very popular for natural language processing (NLP) tasks in recent years [Devlin et al., 2018, Dai and Le, 2015, Peters et al., 2018, Howard and Ruder, 2018, Radford et al., 2018, Raffel et al., 2019]. Often followed by fine-tuning on a smaller, downstream dataset, large-scale pre-training techniques lead to highly informative embeddings that are broadly useful in natural language tasks. The advantage of the transformer architecture is its ability to scale to very large model sizes, reaching up to 1 trillion parameter mark [Fedus et al., 2021]. Large pre-trained models, such as GPT-3 [Brown et al., 2020], have shown the potential of large-scale task-agnostic pre-training in language.

The Vision Transformer (ViT) [Dosovitskiy et al., 2021] has shown that self-attention combined with large-scale pre-training is a viable strategy for vision tasks as well. The performance of ViT is comparable to other state-of-the-art models, while being more efficient to train. Its ability to quickly fine-tune to a smaller, downstream dataset, generalizing even in a few-shot regime, makes it an attractive backbone for tasks such as out-of-distribution (OOD) detection. In this paper, we use ViT pre-trained on ImageNet-21k [Ridnik et al., 2021].

Multi-modal text-image transformers such as CLIP (Contrastive Language-Image Pre-Training) [Radford et al., 2021] pre-train on 400 million (image,text) pairs from the internet to learn to predict a raw text caption from an image, and by doing so develop state-of-the-art visual representations and their natural language counterparts. In this paper, we use the shared image-text embedding to introduce a new zero-shot OOD detection method. Self-supervised learning techniques have also been shown to improve OOD robustness; Hendrycks et al. [2019] use rotation prediction, Winkens et al. [2020] use contrastive training.

3 Near-OOD detection on image classification benchmarks

3.1 Fine-tuning the Vision Transformer

We use the Vision Transformer (ViT) architecture [Doso-vitskiy et al., 2021] and its pre-trained model checkpoints.[1] The checkpoints are pre-trained on ImageNet-21k [Deng et al., 2009]. We fine-tune the full ViT architecture on a downstream task that is either the CIFAR-10 or CIFAR-100 classification problem (using a TPU in Google Colab). We found that we get better generalization and higher quality embeddings when we do not use data augmentation for fine-tuning. Once the model is fine-tuned, we get its pre-logit embeddings (the layer immediately preceding the final layer) for the train and test sets of CIFAR-10 and CIFAR-100 to use for out-of-distribution tasks. For OOD detection, we use the maximum over softmax probabilities (labeled as MSP) and the Mahalanobis distance (labeled as Maha).

Figure 2: Left: CIFAR-100 vs CIFAR-10 OOD AUROC for previous state-of-the-art Zhang et al. [2020], and our fine-tuned ViT with two different backbones, ViT-B_16 and R50+ViT-B_16. Right: CIFAR-10 vs CIFAR-100 OOD task.

Table 1: ImageNet-21k pre-trained ViT/ BiT fine-tuned on the in-distribution training set.

Model	In-distribution	fine-tuned test accuracy	Out-distribution	Mahalanobis AUROC	MSP AUROC
BiT-M R50x1	CIFAR-100	86.89%	CIFAR-10	81.38%	81.04%
ViT-B_16	CIFAR-100	90.95%	CIFAR-10	95.53%	91.89%
R50+ViT-B_16	CIFAR-100	91.71%	CIFAR-10	**96.23%**	92.08%
BiT-M R50x1	CIFAR-10	97.66%	CIFAR-100	94.57%	85.65%
ViT-B_16	CIFAR-10	98.10%	CIFAR-100	98.42%	97.68%
R50+ViT-B_16	CIFAR-10	98.70%	CIFAR-100	**98.52%**	97.75%

The results are summarized in Table 1 and Figure 2. We observe that the MSP baseline yields surprisingly good results when used on top of a large pre-trained transformer that has been fine-tuned on the in-distribution training set. The Mahalanobis distance technique improves OOD detection even further. Applying Mahalanobis distance to a pre-trained ViT fine-tuned on CIFAR-100, we achieve AUROC of 96% on CIFAR-100 vs CIFAR-10, significantly improving over the previous SOTA of 85% using a hybrid model [Zhang et al., 2020]. To study the effect of model architecture, we also evaluate OOD performance on another large-scaled pre-trained model, Big Transfer (BiT) [Kolesnikov et al., 2019][2], as a comparison to ViT. We use model BiT-M R50x1 pre-trained on ImageNet-21k, and fine-tuned the full model architecture on CIFAR-10 and CIFAR-100 respectively. The results are shown in Table 1. For both directions, the AUROCs for BiT are lower than that for ViT. Note that the fine-tuned test accuracy for BiT is slightly lower than that for ViT, which may affect the performance. More importantly, BiT uses a different model architecture ResNet instead of transformer, which may explains the large difference on the OOD performance.

Due to semantic similarity between classes in CIFAR, this task is hard for humans as well.[3] We also evaluated the performance of our approach on popular far-OOD benchmarks such as CIFAR-* vs SVHN and CIFAR-* Textures, and achieve very high AUROC values of around 98% or higher, see Table 6 in Appendix C. We mainly focus on the difficult near-OOD problem as this is a more challenging and realistic problem; many methods can achieve high AUROC on the easier far-OOD

---

[1]https://github.com/google-research/vision_transformer

[2]https://github.com/google-research/big_transfer

[3]To approximately estimate the human performance, we performed the CIFAR-100 vs CIFAR-10 near-OOD detection ourselves. We set-up a simple GUI to randomly sample images from both CIFAR-100 and CIFAR-10 datasets, where the task was to identify images that belong to the CIFAR-10 classes. Note that this setup is easier for humans as they only have to remember 10 classes in CIFAR-10 (as opposed to the 100 classes in CIFAR-100). The estimated human performance was 96% which demonstrates the difficulty of the task. We do not claim that this is the best possible human performance, we will open source the code so that readers can estimate their OOD detection performance themselves. Further details are available in Appendix A.

benchmarks, but do not perform as well as near-OOD tasks, cf. [Winkens et al., 2020, Table 1] which compares many methods on near-OOD and far-OOD tasks.

3.2 Few-shot outlier exposure using ViT

In Section 3.1, we demonstrated that fine-tuning a pre-trained ViT model can improve near-OOD detection (with relatively simple OOD detection techniques such as MSP and Mahalanobis distance). Figure 1 shows that the representations from fine-tuned ViT models are well-clustered. This motivates *few-shot outlier exposure*, where we assume to just a handful of known outliers (and optionally their labels). This setting is motivated by real-world applications which require high-quality OOD detection and teams are willing to collect a handful of known outlier examples (rather than just rely on modeling approaches) to improve safety. Another setting is the case where models are being continuously re-trained; once an outlier is detected, it is desirable to include that in the training corpus to encourage the model to correctly detect similar examples as outliers in the future.

Figure 3: Few-shot outlier exposure with pre-trained transformers. The OOD samples are used to fine-tune a simple classifier (linear classifier for ViT which uses supervised pre-training, and shallow MLP with one hidden layer for genomics which uses unsupervised pre-training). We use the in-distribution classes in addition to multiple OOD classes (when labels available), or a single OOD class. The confidence score is the sum of probabilities corresponding to the in-distribution classes.

The general approach is shown in Figure 3. By using the in-distribution training set $D_{\text{train}}^{\text{in}}$ with K classes and a small number of known OOD examples from $D_{\text{few-shot}}^{\text{out}}$ with O classes. We train a simple classifier $h(\cdot)$ that maps an embedding vector $\boldsymbol{z}$ to a probability vector $\boldsymbol{p} \in \mathbb{R}^{K+O}$, which concatenates the in- and out-of-distribution classes. We considered two types of outlier exposure, one which assumes access to outlier labels (similar to [Roy et al., 2021]) and one where all the outlier examples are collapsed to a single $K+1$th class (similar to [Thulasidasan et al., 2021]). For models pre-trained with labels (such as ViT), we use a linear classifier. For models that use unsupervised pre-training (e.g. genomics in Section 4), we use a shallow multi-layer perceptron (MLP) with a single hidden layer so that fine-tuning can learn discriminative features. We use the sum of the probabilities of all K in-distribution classes as the confidence score for the OOD detection task, $\text{score}_{\text{oe}}(\boldsymbol{x}) = p(\text{in}|\boldsymbol{x}) = \sum_{c=1,\ldots,K} p(y=c|\boldsymbol{x})$. When training the MLP $h(\cdot)$ with few-shot OOD examples, there could be many more examples of the in-distribution data than the small number of OOD data. We therefore oversample the OOD inputs by a factor that we calculate as $(|\mathcal{D}_{\text{train}}^{\text{in}}|/|\mathcal{D}_{\text{oe}}^{\text{out}}|)(O/K)$. This makes the training classes approximately balanced during training. We used a single layer MLP from `scikit-learn` [Pedregosa et al., 2011], batch size 200, L_2 penalty of 1, learning rate 0.001 with *Adam*, maximum of 1,000 iterations. Algorithm 1 and Algorithm 2 describe the details of training and scoring.

Algorithm 1 Few-shot outlier exposure training

1: **Input:** In-distribution train set $\mathcal{D}_{\text{train}}^{\text{in}} = \{(\boldsymbol{x}, y)\}$ with K classes, out-of-distribution train subset $\mathcal{D}_{\text{few-shot}}^{\text{out}} = \{(\boldsymbol{x}, y)\}$ with O classes, oversampling factor Γ, a pre-trained feature extractor $f(\cdot) : \boldsymbol{x} \to \boldsymbol{z}$, a simple classification head $h(\cdot) : \boldsymbol{z} \to \boldsymbol{p} \in \mathbb{R}^{K+O}$.
2: **Initialize:** Initialize $h(\cdot)$ at random, generate random batches from $\mathcal{D}_{\text{train}}^{\text{in}} \bigcup \mathcal{D}_{\text{train}}^{\text{out}}$, oversampling $\mathcal{D}_{\text{train}}^{\text{out}}$ by Γ.
3: **for** train_step = 1 **to** max_step **do**
4:     loss = CrossEntropy($h(f(\boldsymbol{x})), y$)
5:     SGD update of $h(\cdot)$ w.r.t loss
6: **end for**

Algorithm 2 Few-shot outlier inference

1: **Input:**
In-distribution test set $\mathcal{D}_{\text{test}}^{\text{in}} = \{(\boldsymbol{x}, y)\}$ with K classes, out-of-distribution test subset $\mathcal{D}_{\text{test}}^{\text{out}} = \{(X, y)\}$ with O classes, a pre-trained $f(\cdot) : \boldsymbol{x} \to \boldsymbol{z}$ from inputs to embedding vectors, a trained classification head $h(\cdot) : \boldsymbol{z} \to \boldsymbol{p} \in \mathbb{R}^{K+O}$.
2: Compute $\text{score}_{\text{oe}}^{\text{in}}(\boldsymbol{x}), \boldsymbol{x} \in \mathcal{D}_{\text{test}}^{\text{in}}$
3: Compute $\text{score}_{\text{oe}}^{\text{out}}(\boldsymbol{x}), \boldsymbol{x} \in \mathcal{D}_{\text{test}}^{\text{out}}$
4: Compute AUROC based on the scores.

We systemically vary the number of known outliers from 1-10 examples per OOD class and evaluate the OOD detection performance. We also show results for more number of examples per class for completeness as it illustrates how quickly the performance saturates. Figure 4 and Table 2 show the few-shot outlier exposure results for CIFAR-100 vs CIFAR-10 and CIFAR-10 vs CIFAR-100. We evaluate performance of the pre-trained transformer (without any fine-tuning on CIFAR-*) as well as a fine-tuned transformer. We observe that even with 1-10 known outliers per class, we can achieve 99% AUROC for near-OOD detection on CIFAR-100 vs CIFAR-10. Interestingly, we observe that having labels for outliers is less important when the transformer is fine-tuned on in-distribution (dashed vs solid red lines) than the scenario where the transformer is not fine-tuned (dashed vs solid blue lines). Intuitively, the embeddings obtained by fine-tuning a pre-trained transformer are well-clustered, so just a handful of known outliers can significantly improve OOD detection, as illustrated in Figure 9 in Appendix B.

Figure 4: The effect of few-shot outlier exposure and fine-tuning on CIFAR-100 vs CIFAR-10 (left) and CIFAR-10 vs CIFAR-100 (right) using a R50+ViT-B_16 pre-trained on ImageNet-21k. Fine-tuning on in-distribution (red) prior to outlier exposure outperforms no fine-tuning (blue).

Table 2: ImageNet-21k pre-trained ViT (some of them fine-tuned on in-distribution), with an additional final layer that was trained using the in-distribution train set and a small number of examples of the OOD train set (including the O OOD class labels, corresponding to the red curves in Figure 4).

(a) CIFAR-100 → CIFAR-10 AUROC results.

Number of OOD (CIFAR-10) examples per class	R+ViT (without fine-tuning)	R+ViT fine-tuned on CIFAR-100
1	88.73 ± 1.08%	98.70 ± 0.08%
2	92.94 ± 0.55%	99.02 ± 0.15%
3	93.25 ± 0.59%	99.16 ± 0.11%
10	95.73 ± 0.31%	99.46 ± 0.01%
100	97.70 ± 0.01%	99.67 ± 0.01%

(b) CIFAR-10 → CIFAR-100 AUROC results.

Number of OOD (CIFAR-100) examples per class	R+ViT (without fine-tuning)	R+ViT fine-tuned on CIFAR-10
1	94.35 ± 0.05%	98.96 ± 0.05%
2	95.10 ± 0.30%	99.11 ± 0.04%
3	95.60 ± 0.01%	99.17 ± 0.03%
10	96.42 ± 0.02%	99.29 ± 0.02%
100	97.38 ± 0.01%	99.50 ± 0.01%

4 Near OOD detection of genomic sequences

We investigate OOD detection in genomics as another input modality for near-OOD detection. Ren et al. [2019] proposed a benchmark dataset[4] for OOD detection in genomics, motivated by the real-world problem of bacteria identification based on genomic sequences. Real bacteria sequencing data can contain approximately 60-80% of sequences from unknown classes that have not been studied before. Hence, a classifier trained on all known classes so far will be inevitably asked to predict on genomes that do not belong to one of the known classes. Since different bacteria classes are discovered gradually over the years, Ren et al. [2019] use a set of 10 bacteria classes that were discovered before the year 2011 as in-distribution classes, use a set of 60 bacteria classes discovered between 2011-2016 as the validation OOD, and use a set of 60 different bacteria classes discovered after 2016 as the test OOD. The training set only contains genomic sequences of in-distribution classes. The validation and test sets contain sequences from both in-distribution and OOD classes. The genomic sequence is of fixed length of 250 base pairs, composed by characters of A, C, G, T. In the previous work, 1-dimensional convolutional Neural networks (1D CNN) was used to build the

---

[4]https://www.tensorflow.org/datasets/catalog/genomics_ood

classifier for the 10 in-distributional classes, and the Maximum of softmax probability (MSP) and Mahalanobis distance were used for OOD detection. The best AUROC for MSP was only 0.6614, and 0.6241 for Mahalanobis distance [Ren et al., 2019].

Similar to the previous section, we explore the usefulness of pre-trained transformers and fine-tuning for near-OOD detection. Unsupervised pre-training and fine-tuning approach has been applied to several bio-informatic problems, such as protein function prediction [Elnaggar et al., 2020, Littmann et al., 2021], protein structure prediction [Rives et al., 2021], and predicting promoters, splice sites and transcription factor binding sites [Ji et al., 2020], but it has not been studied yet how pre-training could help near-OOD detection.

(a) BERT pre-training and fine-tuning for genomics.   (b) AUROC of near-OOD detection

Figure 5: (a) Model architecture for BERT pre-training and fine-tuning. The unsupervised pre-training model uses a transformer encoder to predict the masked token (shown in red). The fine-tuned model adds a simple classification head (MLP with one hidden layer) to predict in-distribution classes. (b) The relationship between the minimum genetic distance and the AUROC scores for the 60 OOD test classes. The pre-train+fine-tune based MSP and Mahalanobis distance methods have significantly higher AUROC overall, and the positive correlation between the minimum distance and the AUROC are more prominent than the baseline model.

Unsupervised BERT pre-training and supervised fine-tuning   We first pre-train the transformer model in an unsupervised fashion as in BERT to capture biologically relevant properties. For unlabeled in-distribution sequences in the training set, we randomly mask the characters in the sequence at the rate of 0.15, feed the masked sequence into transformer-based model of 8 heads and 6 layers and embedding dimension 512, and predict the masked characters. To boost the performance, we add the unlabeled validation data to the training set for pre-training. In the fine-tuning stage, we load the pre-trained transformer model, mean pool the embeddings over the positions, and add a single linear projection classification head for 10 in-distribution classes on top of the embeddings. The setup is shown in Figure 5a. All the parameters in the model including those in the pre-trained transformer and those in the classification head are fine-tuned using the labeled training data. The model is pre-trained for 300,000 steps using learning rate of 0.001 and Adam optimizer [Kingma and Ba, 2014] on TPU, and the accuracy for predicting the masked token is 48.35%. The model is fine-tuned for 100,000 steps at the learning rate of 0.0001, and the classification accuracy is 89.84%. We use the validation in-distribution and validation OOD data to select the best model checkpoint for each of the two methods and evaluate on test set.

Table 3: Genomics OOD BERT pre-trained and fine-tuned on the in-distribution training set. Error bars represent standard deviation over 3 runs. See Table 7 in Appendix D for AUPRC and FPR95.

Model	Test Accuracy	Mahalanobis AUROC	MSP AUROC
1D CNN [Ren et al., 2019]	85.93±0.11%	64.75±0.73%	65.84±0.46%
BERT pre-train and fine-tune	89.84±0.00%	**77.49±0.04%**	73.53±0.03%

The results are reported in Table 3. It can be seen that using the approach of pre-training transformer and fine-tuning, the OOD detection performance is significantly improved, from 64.75% to 77.49% for Mahalanobis distance, and from 65.84% to 73.53% for MSP. The in-distribution accuracy also improves a bit, from 85.93% to 89.84%. We also study the relationship between the genetic distance

and the AUROC of OOD detection for the 60 test OOD classes. We compute the genetic distance using the popular alignment-free method d_2^S which is based on the similarity between the word frequencies of the two genomes [Ren et al., 2018, Reinert et al., 2009]. Studies have shown that this genetic distance reflects true evolutionary distances [Chan et al., 2014, Bernard et al., 2016]. For each of the 60 OOD test classes, we use the minimum genetic distance between this OOD class to any of the 10 in-distribution classes as the final distance measure. Figure 5 shows the AUROC and the minimum distance for each of the 60 OOD classes. We expect the AUROC is higher as the distance is greater. Using the baseline model 1D CNN, we did not see obvious correlation between the AUROC and the minimum distance, with $r^2 = 0.0000$, based on Mahalanobis distance. The AUROC based on MSP method has positive correlation to the minimum distance, with $r^2 = 0.1190$. After we use the pre-trained+fine-tuned transformer, both MSP and Mahalanobis distance methods have significantly higher AUROC overall, and the positive correlation between the minimum distance and the AUROC are more prominent than the baseline model.

Few-shot outlier exposure Given that pre-trained and fine-tuned model improves the OOD performance, we next explore the idea of few shot outlier exposure to further boost the performance. We randomly select 1, 2, 5, 10, 100 examples per test OOD class and add them to the training set respectively. For each input x in the training set, we extract its corresponding embedding vector z from the above pre-trained and fine-tuned model (or alternatively the model without fine-tuned). We construct a single layer perceptron network of 1024 units for classifying each individual in-distribution classes and OOD classes, as shown in Figure 3. At inference time, we use the sum of the probability of in-distribution classes as the final confidence score for OOD detection. Additionally, we also tried the idea of collapsing all OOD classes into one single class (as in [Thulasidasan et al., 2021]) for comparison. The model is trained for 10,000 steps with the learning rate of 0.001. The best model checkpoint is selected based on the highest AUROC on a small set of validation dataset disjoint from the test set.

Figure 6: Few-shot outlier exposure for genomics OOD. The x-axis shows the number of outliers per class that the model was exposed to. The y-axis is OOD AUROC in %. The shading shows the standard deviation over 3 runs. See Table 8 for exact numbers.

Results are shown in Figure 6. We observe that exposing to just a small number of OOD examples significantly improves the OOD performance, increasing AUROC from 76.73% to 88.48%. As expected, using the embeddings from the fine-tuned model (blue lines) is better than that from the model without fine-tuning (purple lines). Also, using the outlier labels (purple solid line) has a slightly better performance than collapsing the OOD classes into a single class (purple dashed line) using the pre-trained embeddings without fine-tuning.

5 Using candidate labels with multi-modal text-image models such as CLIP

Multi-modal transformers such as CLIP [Radford et al., 2021], which are pre-trained on image-text pairs, have been shown to perform well on zero-shot classification tasks. *We show that such multi-modal transformers open the door to new forms of outlier exposure which can significantly improve out-of-distribution (OOD) detection in the zero-shot classification setting.* Our goal is to show that multi-modal transformers can leverage a weaker form of outlier exposure than the few-shot outlier exposure assumption in previous sections, and improve their safety for zero-shot classification.

We use the pre-trained CLIP model[5] (specifically ViT-B/32) that was trained on 400 million (text,image) pairs from the internet. Its image encoder can map an image I into an embedding vector $z_{\text{image}}(I)$, while its text encoder can do the same for a string T as $z_{\text{text}}(T)$. By choosing a set of D *candidate labels* for an image, the similarity between the embedding of the candidate label T_i and an image I can be used as the i^{th} component of the image's embedding vector z as $z_i = z_{\text{text}}(T_i) \cdot z_{\text{image}}(I)$.

---

[5]https://github.com/openai/CLIP

Figure 7: Using candidate text labels and an image-text multi-modal model (CLIP) to produce an embedding vector for OOD detection. We use two sets of candidate labels, evaluate the semantic alignment of the image with each label, apply softmax, and use the difference between the sum of probabilities in the first (in) and second (out) set as an OOD score. Note that this is zero-shot classification and the model is not fine-tuned and does not leverage any in-distribution or OOD images/labels. It only uses the names of the classes (or other informative words) as candidate labels and works well due to the strong pre-training of CLIP.

Zero-shot outlier exposure In the zero-shot classification setting, the candidate labels are chosen to describe the semantic content of the in-distribution classes (e.g. names of the classes). We propose to include the candidate labels related to the out-of-distribution classes, and utilize this knowledge as a very weak form of outlier exposure in multi-modal models. This could be relevant in applications, where we might not actually have any outlier images for fine-tuning but we might know the *names* or *descriptions* of outlier classes.

The procedure is shown in Figure 7. We choose two groups of candidate labels, in-distribution and out-of-distribution labels (e.g. CIFAR-100 and CIFAR-10 class names). We produce an embedding vector z for each image I, apply softmax to get probabilities as $\mathbf{p} = \text{softmax}(z)$. Those get split to $p(\text{in}|\boldsymbol{x}) = \sum_{i \in \text{in}} \mathbf{p}_i$, and $p(\text{out}|\boldsymbol{x}) = \sum_{i \in \text{out}} \mathbf{p}_i$, where $p(\text{in}|\boldsymbol{x}) + p(\text{out}|\boldsymbol{x}) = 1$. Similar to Figure 3, we use $\text{score}_{\text{oe}}(\boldsymbol{x}) = p(\text{in}|\boldsymbol{x})$ as the confidence score. By choosing the candidate labels to represent the in-distribution and OOD dataset we would like to distinguish (e.g. CIFAR-100 and 10), we can get a very informative score that leads to AUROC above previous SOTA, despite no exposure to the training set of the in-distribution (zero-shot) Our results are shown in Table 4.

Table 4: Zero-shot OOD detection using image-text multi-modal models. We compare CLIP that uses only the names in-distribution classes (baseline) and compare it to our proposed variant that uses just the names of out-of-distribution classes as candidate labels. Even in the zero-shot setting (without any fine-tuning on either in-distribution or OOD dataset), we outperform previous SOTA.

Distribution 1	Distribution 2	Labels 1	Labels 2	AUROC
CIFAR-100	CIFAR-10	CIFAR-100 names	—	69.49%
CIFAR-100	CIFAR-10	CIFAR-100 names	CIFAR-10 names	94.68%
CIFAR-10	CIFAR-100	CIFAR-10 names	—	89.17%
CIFAR-10	CIFAR-100	CIFAR-10 names	CIFAR-100 names	94.68%
CIFAR-100	SVHN	CIFAR-100 names	—	93.05%
CIFAR-100	SVHN	CIFAR-100 names	["number"]	99.67%
CIFAR-10	SVHN	CIFAR-10 names	—	96.90%
CIFAR-10	SVHN	CIFAR-10 names	["number"]	99.95%

6 Conclusion

We focus on the challenging problem of near-OOD detection. We show that fine-tuning large-scale pre-trained transformers and using few-shot outlier exposure can significantly improve the SOTA. On the CIFAR-100 vs CIFAR-10 visual OOD detection benchmark, we improve the SOTA from 85% to 96% (without outlier exposure) and 99% (with outlier exposure), essentially closing the gap between SOTA and the ideal performance. On a challenging genomics benchmark, we improve the SOTA from 66% to 77% using BERT (without outlier exposure) and 88% (with outlier exposure). We also show that multi-modal pre-trained transformers open the door to new, weaker forms of outlier exposure which only use names of OOD inputs; we apply this to CLIP and achieve AUROC of 94.7% in the zero-shot classification setting. We believe that our findings will be of interest to the research community as well as practitioners working on safety-critical applications.

References

Dario Amodei, Chris Olah, Jacob Steinhardt, Paul Christiano, John Schulman, and Dan Mané. Concrete problems in AI safety. *arXiv preprint arXiv:1606.06565*, 2016.

Guillaume Bernard, Cheong Xin Chan, and Mark A Ragan. Alignment-free microbial phylogenomics under scenarios of sequence divergence, genome rearrangement and lateral genetic transfer. *Scientific reports*, 6(1):1–12, 2016.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners, 2020.

Cheong Xin Chan, Guillaume Bernard, Olivier Poirion, James M Hogan, and Mark A Ragan. Inferring phylogenies of evolving sequences without multiple sequence alignment. *Scientific reports*, 4: 6504, 2014.

M. Cimpoi, S. Maji, I. Kokkinos, S. Mohamed, and A. Vedaldi. Describing textures in the wild. In *Proceedings of the IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2014.

Andrew M Dai and Quoc V Le. Semi-supervised sequence learning. In *NeurIPS*, 2015.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2009.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. *ICLR*, 2021.

Ahmed Elnaggar, Michael Heinzinger, Christian Dallago, Ghalia Rihawi, Yu Wang, Llion Jones, Tom Gibbs, Tamas Feher, Christoph Angerer, Martin Steinegger, et al. Prottrans: Towards cracking the language of life's code through self-supervised deep learning and high performance computing. *arXiv preprint arXiv:2007.06225*, 2020.

William Fedus, Barret Zoph, and Noam Shazeer. Switch transformers: Scaling to trillion parameter models with simple and efficient sparsity, 2021.

Robert Geirhos, Jörn-Henrik Jacobsen, Claudio Michaelis, Richard Zemel, Wieland Brendel, Matthias Bethge, and Felix A Wichmann. Shortcut learning in deep neural networks. *Nature Machine Intelligence*, 2(11):665–673, 2020.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q Weinberger. On calibration of modern neural networks. *arXiv preprint arXiv:1706.04599*, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

Dan Hendrycks and Kevin Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. *arXiv preprint arXiv:1610.02136*, 2016.

Dan Hendrycks, Mantas Mazeika, and Thomas G Dietterich. Deep anomaly detection with outlier exposure. *arXiv preprint arXiv:1812.04606*, 2018.

Dan Hendrycks, Mantas Mazeika, Saurav Kadavath, and Dawn Song. Using self-supervised learning can improve model robustness and uncertainty. *arXiv preprint arXiv:1906.12340*, 2019.

Jeremy Howard and Sebastian Ruder. Universal language model fine-tuning for text classification. *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2018. URL http://dx.doi.org/10.18653/v1/p18-1031.

Yanrong Ji, Zhihan Zhou, Han Liu, and Ramana V Davuluri. Dnabert: pre-trained bidirectional encoder representations from transformers model for dna-language in genome. *bioRxiv*, 2020.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Alexander Kolesnikov, Lucas Beyer, Xiaohua Zhai, Joan Puigcerver, Jessica Yung, Sylvain Gelly, and Neil Houlsby. Big transfer (bit): General visual representation learning. *arXiv preprint arXiv:1912.11370*, 6(2):8, 2019.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *NeurIPS*, 2017.

Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. In *NeurIPS*, 2018.

Shiyu Liang, Yixuan Li, and R Srikant. Enhancing the reliability of out-of-distribution image detection in neural networks. *arXiv preprint arXiv:1706.02690*, 2017.

Maria Littmann, Michael Heinzinger, Christian Dallago, Tobias Olenyi, and Burkhard Rost. Embeddings from deep learning transfer go annotations beyond homology. *Scientific reports*, 11(1):1–14, 2021.

Jeremiah Zhe Liu, Zi Lin, Shreyas Padhy, Dustin Tran, Tania Bedrax-Weiss, and Balaji Lakshminarayanan. Simple and principled uncertainty estimation with deterministic deep learning via distance awareness. *NeurIPS*, 2020.

Eric Nalisnick, Akihiro Matsukawa, Yee Whye Teh, Dilan Gorur, and Balaji Lakshminarayanan. Hybrid models with deep and invertible features. In *ICML*, 2019.

Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Bo Wu, and Andrew Y Ng. Reading digits in natural images with unsupervised feature learning. 2011.

Anh Nguyen, Jason Yosinski, and Jeff Clune. Deep neural networks are easily fooled: High confidence predictions for unrecognizable images. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 427–436, 2015.

F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.

Matthew E. Peters, Mark Neumann, Mohit Iyyer, Matt Gardner, Christopher Clark, Kenton Lee, and Luke Zettlemoyer. Deep contextualized word representations, 2018.

Alec Radford, Karthik Narasimhan, Tim Salimans, and Ilya Sutskever. Improving language understanding by generative pre-training. 2018.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. *arXiv preprint arXiv:2103.00020*, 2021.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. Exploring the limits of transfer learning with a unified text-to-text transformer, 2019.

Gesine Reinert, David Chew, Fengzhu Sun, and Michael S Waterman. Alignment-free sequence comparison (I): statistics and power. *Journal of Computational Biology*, 16(12):1615–1634, 2009.

Jie Ren, Xin Bai, Yang Young Lu, Kujin Tang, Ying Wang, Gesine Reinert, and Fengzhu Sun. Alignment-free sequence analysis and applications. *Annual Review of Biomedical Data Science*, 1: 93–114, 2018.

Jie Ren, Peter J Liu, Emily Fertig, Jasper Snoek, Ryan Poplin, Mark A DePristo, Joshua V Dillon, and Balaji Lakshminarayanan. Likelihood ratios for out-of-distribution detection. *NeurIPS*, 2019.

Tal Ridnik, Emanuel Ben-Baruch, Asaf Noy, and Lihi Zelnik-Manor. Imagenet-21k pretraining for the masses, 2021.

Alexander Rives, Joshua Meier, Tom Sercu, Siddharth Goyal, Zeming Lin, Jason Liu, Demi Guo, Myle Ott, C Lawrence Zitnick, Jerry Ma, et al. Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. *Proceedings of the National Academy of Sciences*, 118(15), 2021.

Abhijit Guha Roy, Jie Ren, Shekoofeh Azizi, Aaron Loh, Vivek Natarajan, Basil Mustafa, Nick Pawlowski, Jan Freyberg, Yuan Liu, Zach Beaver, Nam Vo, Peggy Bui, Samantha Winter, Patricia MacWilliams, Greg S. Corrado, Umesh Telang, Yun Liu, Taylan Cemgil, Alan Karthikesalingam, Balaji Lakshminarayanan, and Jim Winkens. Does your dermatology classifier know what it doesn't know? Detecting the long-tail of unseen conditions. *arXiv preprint arXiv:2104.03829*, 2021.

Chandramouli Shama Sastry and Sageev Oore. Detecting out-of-distribution examples with Gram matrices. In *ICML*, 2020.

Sunil Thulasidasan, Sushil Thapa, Sayera Dhaubhadel, Gopinath Chennupati, Tanmoy Bhattacharya, and Jeff Bilmes. A simple and effective baseline for out-of-distribution detection using abstention. 2021. URL https://openreview.net/forum?id=q_Q9MMGwSQu.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need, 2017.

Jim Winkens, Rudy Bunel, Abhijit Guha Roy, Robert Stanforth, Vivek Natarajan, Joseph R. Ledsam, Patricia MacWilliams, Pushmeet Kohli, Alan Karthikesalingam, Simon Kohl, Taylan Cemgil, S. M. Ali Eslami, and Olaf Ronneberger. Contrastive training for improved out-of-distribution detection. *arXiv preprint arXiv:2007.05566*, 2020.

Hongjie Zhang, Ang Li, Jie Guo, and Yanwen Guo. Hybrid models for open set recognition. *European Conference on Computer Vision*, 2020.

Bolei Zhou, Agata Lapedriza, Aditya Khosla, Aude Oliva, and Antonio Torralba. Places: A 10 million image database for scene recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2017.