Zero-Shot Coordination via Semantic Relationships Between Actions and Observations

Abstract

An unaddressed challenge in zero-shot coordination is to take advantage of the semantic relationship between the features of an action and the features of observations. Humans take advantage of these relationships in highly intuitive ways. For instance in the absence of a shared-language, we might point to the object we desire or hold up fingers to indicate how many objects we want. To address this challenge, we investigate the effect of network architecture on the propensity of learning algorithms to make use of these relationships in human-compatible ways. We find that attention-based architectures that jointly process a featurized representation of the observation *and* the action, have a better inductive bias for exploiting semantic relationships for zero-shot coordination. Excitingly, in a set of diagnostic tasks, these agents produce highly human-compatible policies, without requiring the symmetry relationships of the problems to be hard-coded.

1 Introduction

Successful collaboration between agents requires coordination (Tomasello et al., 2005; Misyak et al., 2014; Kleiman-Weiner et al., 2016). Yet coordination is challenging because coordinated strategies can be arbitrary (Lewis, 1969; Young, 1993; Lerer & Peysakhovich, 2018). One cannot deduce from first principles whether to drive on the right or left side of the road nor what utterance should be used to refer to a particular object (Pal et al., 2020). In these cases coordination can arise from best responding to what others are already doing i.e., following a convention. In the United States one drives on the right and says "heart" to refer to ♡ while in Japan one drives on the left and says "shinzo" to refer to ♡. Yet in many situations prior conventions may not be available, agents may be faced with entirely novel situations or partners for which there is no shared notions of how they should coordinate. In this work we study ways that agents may learn to leverage abstract relations between the observations and actions to coordinate with agents they have had no experience interacting with before.

To illustrate, consider the following situations where people can figure out how to coordinate without prior experienced or shared conventions. Imagine a store that sells strawberries and blueberries. You want to buy strawberries but you don't share any common language with the clerk and can't point at either object. You are however wearing a red hat and you wave the hat at the clerk to hint that the strawberries are what you want. The clerk has two baskets of strawberries remaining, and so you raise a single finger to indicate that you only want one of the baskets. The clerk produces a paper and plastic bag and you point to the paper bag to indicate that you want the paper one. These examples are so simple that they seem obvious: the red hat matches the colors of the strawberries, the number of fingers matches the number of baskets you want, and you extend a finger in the direction of the desired packaging (Grice, 1975). While obvious to people, who rely on a theory-of-mind in understanding others, we will show that these inferences remain a challenge for multi-agent reinforcement learning agents.

Less obvious examples are common in the cognitive science literature. Consider the shapes in Fig. 1. When asked to assign the names "Boubo" and "Kiki" to the two shapes people name the jagged object "Kiki" and the curvy object "Boubo" (Köhler, 1929). This finding is robust across different linguistic communities and cultures and is even found in young children (Maurer et al., 2006). The causal explanation is that people match a "jaggedness"-feature and "curvey"-feature in both the visual and auditory data. Across the above these cases, there seem to be a generalized

mechanism for mapping the features of the persons action with the features of the desired action. All are examples of where in the absence of norms or conventions, people minimize the distance between features when making a choice. This basic form of zero-shot coordination predates verbal behavior (Tomasello et al., 2007) and this capability has been hypothesized as a key predecessor to more sophisticated language development and acquisition (Tomasello et al., 2005). Modeling these capacities is key for building machines that can robustly coordinate with other agents and with people (Kleiman-Weiner et al., 2016; Dafoe et al., 2020).

Figure 1: When asked to assign the names "Boubo" and "Kiki" to these two shapes, people systematically assign the name "Boubo" to the jagged object on the left and "Kiki" to the curvy object on the right.

However as we will show, the naive training of reinforcement learning (RL) agents with self-play fail to learn to coordinate even in these obvious ways. Instead they develop arbitrary private languages that are uninterpretable to both the same models trained with a different random seed as well as to human partners (Foerster et al., 2019). For instance in the examples above, they would be equally likely to wave a red-hat to hint they want strawberries as they would to hint that they want blueberries, raising a single finger would correspond to an arbitrary desired quantity, and even pointing itself, instead of referring to the object that is in straight line correspondence with the extended finger would be mapped to an arbitrary reference such as the object to the left of the extended finger or something equally nonsensical.

These problems also emerge at scale in the decentralized partially observable Markov decision process (Dec-POMDP) benchmark Hanabi (Bard et al., 2019). When agents are trained with self-play using standard architectures in Hanabi they do not develop strategies that take into account the correspondence between the features of the actions (colored and numbered cards) and the observation of the game state (other colored and numbered cards). In contrast, both novice and expert human players will hint a red card in order to signal to other players that this red card should be played next but agents trained with self-play do not learn these kind of simple correspondences. Yet building in these kinds of abstract knowledge is challenging. It is hard to express the general principle in a way that applies across a broad number of contexts. Instead we take a learning based approach. Our aim is to build an agent with the capacity to develop these kinds of abstract correspondences during self-play such that they can robustly succeed during cross-play or during play with people.

Our contributions are as follows: (1) We extend Dec-POMDPs to allow actions and observations to be represented using shared features and develop a novel human-interpretable environment for studying coordination in this setting. (2) We evaluate the role of neural network (NN) architectures including feedforward, recurrent, and attention mechanisms on both cross-play generalization and ability to create human-interpretable conventions. (3) We show that an attention architecture which takes *both* the action and observations as input allows the agent to exploit the semantic relationships for coordination, resulting in strong cross-play and human compatible policies. The model also demonstrates sophisticated coordination patterns that exploit mutual exclusivity and implicature, two well-known phenomena studied in cognitive science.

2 RELATED WORK

Our work is inspired by and builds on advances in cooperative multi-agent reinforcement learning (MARL) for Dec-POMDPs (Oliehoek & Amato, 2016). First, the failures of self-play in cooperative games has been recently explored. Carroll et al. (2019) use grid-world MDPs to show that that both self-play and population-based training fail when paired with human collaborators. In Hanabi, agents trained via self-play develop conventions that fail to generalize to the same agents but trained with different random seeds (Bard et al., 2019; Hu et al., 2020). Hu et al. (2020) also formally introduced the zero-shot coordination (ZSC) setting, where the goal is to maximize the cross-play (XP) of independently trained agents. ZSC is an alternative to ad-hoc teamwork, a framework for measuring coordinated team success when faced with players with unknown behavior (Stone et al., 2010; Barrett et al., 2011).

Further work focused around the game Hanabi has attempted to address ZSC. "Other Play" (OP) exploits the symmetries in a Dec-POMDPs to prevent agents from learning equivalent but mutually incompatible policies (Hu et al., 2020). OP prevents tie-breaking using experimenter-coded symmetries, preventing equivalent conventions from forming. Unlike OP our approach requires no experimenter-coding. Other recent work from the same authors introduced "Off Belief Learning" (OBL) which regularizes agents' ability to make inferences based on the behavior of others (Hu et al., 2021). Compared to prior work on Hanabi where self-play scores in Dec-POMDPs were high but cross-play scores were near chance both of these techniques drastically improve cross-play scores and show promising preliminary results in play with people. However neither of these algorithms can exploit the correspondences between features of an action and the observation of the state as we show in this work, unless this falls out of the environment dynamics.

Finally, we are inspired by how humans coordinate their behavior in cooperative settings. Theory-of-mind, the mechanism people use to infer intentions from the actions of others plays a key role in structuring coordination (Wu et al., 2021; Shum et al., 2019). In particular Rational Speech Acts (RSA) is a particularly influential model of pragmatic implicature (Frank & Goodman, 2012; Goodman & Stuhlmüller, 2013). These models make intuitive predictions about how different words will change their meaning depending on the context. For instance, in some contexts "some" refers to at least one, but in other cases it refers to "at least one but not all". At the heart of these approaches are probabilistic representations of belief which allow for the modeling of uncertainty and recursive reasoning about each others beliefs which enables higher-order mental state inferences. This recursive reasoning step is sometimes called cognitive hierarchy or level-K reasoning and is a useful tool for explaining certain focal points (Camerer, 2011; Stahl & Wilson, 1995; Camerer et al., 2004). However constructing recursive models of players beliefs and behavior is computationally expensive.

3 BACKGROUND

Dec-POMDPs We use decentralized partially observable Markov decision processes (Dec-POMDPs) to formalize our setting (Nair et al., 2003). In a Dec-POMDP, each player i observes the underlying state s partially through an observation function $\Omega^i(s) \in \mathcal{O}^i$, and takes action $a^i \in \mathcal{A}^i$. Players receive a common reward $R(s, a)$ and the state follows the transition function $\mathcal{T}(s, a)$. The historical trajectory is denoted as $\tau = (s_1, a_1, \ldots, a_{t-1}, s_t)$. Player i's *action-observation history* (AOH) is denoted as $(\Omega^i(s_1), a_1^i, \ldots, a_{t-1}^i, \Omega^i(s_t))$. The policy for player i takes as input an AOH and outputs a distribution over actions, denoted by $\pi^i(a^i \mid \tau_t^i)$. The joint policy is denoted by π.

Zero-Shot Coordination Zero-shot coordination is a problem setting in Dec-POMDPs in which learning algorithms are evaluated based on their cross play scores, subject to the constraint that these algorithms may not exploit arbitrary design choices, such as tie breaking mechanisms (Hu et al., 2020).

Attention Mechanisms in Deep Learning Attention mechanisms (Vaswani et al., 2017; Bahdanau et al., 2015; Xu et al., 2016) are an important tool for large sequence models. Given a sequence of input vectors $(x_1, ..., x_m)$, quadratic attention uses three weight matrices (Q, K, V) to obtain triples (Qx_i, Kx_i, Vx_i) for each $i \in \{1, \ldots, m\}$, called query vectors, key vectors, and value vectors. We abbreviate these as (q_i, k_i, v_i). Next, for each i, j, quadratic attention computes logits using dot products $q_i \cdot k_j$. These logits are in turn used to compute an output matrix

$$[\text{softmax}(q_i \cdot k_1/\sqrt{m}, \ldots, q_i \cdot k_m/\sqrt{m}) \cdot v_j]_{i,j}.$$

We denote this output matrix as $Attention(x_1, \ldots, x_m)$.

4 DEC-POMDPS WITH SHARED ACTION AND OBSERVATION FEATURES

It is common to describe the states and observations in Dec-POMDPs using features, e.g. in games each card has a rank and a suit. These featurized observations can be readily exploited by function approximators. In contrast, in typical implementations the actions are outputs of the neural network and do not take advantage of features. Another option is to represent the Dec-POMDP as an abstract graph, where all states, observations and actions are nodes and the transition function specifies the

weight of the edges between them. In this abstract representation each state and observation is unque and all feature similarity between them is lost.

In the standard representation of Dec-POMDPs actions are defined solely through their effect on the environment. In contrast, in real world environments they are commonly grounded and can be described with semantic features referring to the object they are action on, e.g. "I pull the *red lever*".

Next we formalize the concept of observation and action features in Dec-POMDPs. We say a Dec-POMDP has *observation features* if for at least one player i, we can factor the observation $\Omega^i(s)$ into objects $\Omega^i(s) = (O_1, \ldots, O_n)$ where each object is described by features, $O_j = (f_1, \ldots, f_n)$, where for each feature $f_j \in F_j$, the feature space.

Similarly a Dec-POMDP has *action features* if we can factor the representation of the actions. In this case, at time t, player i takes an action $a_t^i = (\hat{f}_1, \ldots, \hat{f}_m)$ where $\hat{f}_i \in \hat{F}$ is the feature representation of the action. We note that this representation typically is a function of the current state, e.g. an agent might always have 5 actions available (pulling a given lever), but the color of the color of the levers available is contextual. In some Dec-POMDPs the actions can further be described using some of the same features that describe the observations, for example when an agent can both observe the "red" light and pull the "red" lever. In these cases there is a non-empty intersection between F_i and $\hat{F}$ which can be used to coordinate.

We note that in generality the action space may also include actions that act on sets of objects. While our formalism can be naturally extended to cover this, we will omit it here for brevity since it's not needed for our examples.

5 THE HINT-AND-GUESS GAME

Figure 2: Example scenarios in the hint-and-guess game. The *Hinter* and *Guesser* are dealt a hand of cards where each card has a randomly sampled letter [A-C] and number [1-3]. All cards are visible to both players. Only the *Hinter* knows which of the *Guesser's* cards is the target card, outlined with a dotted red line above. The goal of the game is for the *Guesser* to select the target card but the only actions the *Hinter* can take is to point to one of their own cards. Shown above are four hand crafted scenarios that test distinct dimensions important for zero-shot coordination. The highlighted yellow card corresponds to a human interpretable choice. The two right scenarios require agents to reason about implicatures, i.e., the interpretable choice has zero feature overlap with the target card. Model performance is shown in Table 2.

We develop a novel Dec-POMDP with shared actions and observation features to study coordination in this setting. Our environment is two player game called the "hint-and-guess" game where players must coordinate in order to successfully guess a target card. The game consists of a *Hinter* and a *Guesser*. Both players are given a hand of N cards, $H_1 = \{C_1^1, \ldots C_N^1\}$ for the *Hinter* and $H_2 = \{C_1^2, \ldots C_N^2\}$ for the *Guesser*. Each card is marked by two features (f_1, f_2) where $f_1 \in F_1$ and $f_2 \in F_2$. Cards in each hand are drawn independently and randomly with replacement, with equal probability for any feature combination. Both hands, H_1 and H_2, are public information and are exposed to both players. Before the game starts, one card of the *Guesser*, C_i^2, is randomly chosen to be the target card and its features are revealed to the *Hinter*, but not the *Guesser*.

In the first round, the *Hinter* (who observes H_1, H_2, C_i^2) chooses a card of its own, call it C_j^1, to show to the *Guesser*. And in the second round, the *Guesser* (who observes H_1, H_2 and the features of C_j^1) guesses which of its cards is the target. Both players receive a common reward $r = 1$ if the features of the card played match those of the target, and otherwise $r = 0$.

Figure 2 shows some simple scenarios that probe key dimensions of coordination with $N = 2$, $F_1 = \{1, 2, 3\}$ and $F_2 = \{A, B, C\}$. Each of these scenarios have a human-interpretable solution. The first scenario (Exact Match) is the most simple, the *Hinter* has a copy of the target card, 2B, so they can just hint 2B. Note that while this strategy is human interpretable, the opposite convention would work in this particular case. The next scenario (Feature Similarity) requires reasoning about the features under some ambiguity since none of the cards in the two hands are a direct match. In this case, both cards in the *Hinter's* hand share one feature with the Guesser. The human-interpretable strategy would be to match the cards that share features to each other. Although like before the exactly opposite strategy would also work well.

We also develop stimuli that require more sophisticated inferences (labeled implicatures in Figure 2). Implicatures require understanding the action embedded within its context. The third scenario (mutual exclusivity) invokes a simple kind of implicature: mutual exclusivity. In this scenario, human-interpretable reasoning follows the logic of: "if the target card *was* 1B, the *Hinter* would choose 1B so that means 1B is taken and 3C should correspond to 2A even though they share zero feature overlap. The final scenario combines feature similarity and mutual exclusivity. These scenarios are particularly interesting because deep learning models often struggle to effectively grapple with mutual exclusivity (Gandhi & Lake, 2020).

6   The Effect of Architecture Choice on Zero-Shot Coordination

We consider the following architectures to investigate the effect of policy parameterization on the agents' ability to exploit shared action-and observation features for ZSC.

Deep Q-Learning (DQN). We first use standard DQN with feedforward neural networks (NN). All observations are concatenated and fed into an NN, which outputs the estimated Q-value for each action. There is no explicit representation of action-observation relationships in this model, since observations are inputs and actions are outputs. E.g. for multi-layer perceptrons (MLP) the inputs and outputs can be permuted arbitrarily whiteout changing the learning problem.

Recurrent Deep Q-Learning (RDQN). In the RDQN model, we feed in objects in the observation (namely, vectors representing cards) sequentially to a long short-term memory (LSTM) network (Hochreiter & Schmidhuber, 1997). To improve trainability we concatenate all hidden states from each step and use that as input to a feedforward NN, noting that this is somewhat unconventional. Like the MLP, the LSTM does not explicitly model the relationship between action and observation features.

Attention Mechanisms. The core of attention is the dot product, which is fundamentally a comparative operator. As such, it is natural to explore attention for ZSC in our setting and in the following we present three different options for attention based architectures. While the attention mechanism is the same for all three architectures, they differ in terms of their overall design and we will see that these differences are highly relevant for the learning outcomes. Let $Attention(\cdot)$ denote the attention layer as introduced in Section 3.

Attention for Observation (Obs). The first model feeds observations into the attention layer, then the flattened output is passed through a simple ReLU feedforward layer and produces the estimated Q-values for all actions as an output.

$$S = Attention(O_1, \ldots, O_n)$$
$$P = ReLU(S),$$

where P are the estimated Q-values for all of the actions.

Attention with Action as Output (Action-Out). In order to more explicitly represent the relational structure, we take the dot product of a linear transform of the attention layer and an embedding vector for each of the actions.

$$S = Attention(O_1, \ldots, O_n)$$
$$P = Linear(S) \cdot Linear(A),$$

where $Linear(X) = XW + b$, where W is the weight matrix and b is the bias term.

Attention with Action as Input (Action-In). Next we extend this architecture to take advantage of the shared features between observations and actions. To do so, we feed a feature based representation for a given action (one at a time) into the attention mechanism along with the observation. This outputs a single scalar value at a time, the estimated Q-value for the specific action being fed into the network.

$$S_i = Attention(O_1, \ldots, O_n, A_k) \quad \text{for } k = 1, \ldots, m$$
$$P = [Linear(S_1), \ldots, Linear(S_m)].$$

To be clear, this architecture will take N forward passes (one per action) to calculate the Q-values for all actions.

7 EXPERIMENTS

We evaluate the architectures in the Hint-and-Guess game mentioned in Section 5. We fix the hand size $N = 5$ and the features to be $F_1 = \{1, 2, 3\}$ and $F_2 = \{A, B, C\}$. We use a two-hot vector to represent the features of each card. The observation input is a concatenation of these representations for both hands, H_1 and H_2, with the vector representing the target card, C_i^2 and hinted card C_j^1. We evaluate the agents' performance and behavior in both self-play, zero-shot coordination setting, and ability to match the human interpretable response in four scenarios.

7.1 MARL TRAINING SETUP

We train agents in the standard self-play setting using independent Q-learning (IQL, Section 3), where the *Hinter* and *Guesser* are jointly trained to maximize their score in 4M randomly initialized games. We use standard experience-replay with a replay memory of size 300K. For optimization, we use the mean squared error loss, stochastic gradient descent with learning rate set to 10^{-4} and minibatches of size 500 each. To allow more data to be collected between training steps, we update the network only after we receive 500 new observations rather than after every observation. We use the standard exponential decay scheme with exploration rate $\epsilon = \epsilon_m + (\epsilon_0 - \epsilon_m) \exp(-n/K)$, where n is the number of episodes, $\epsilon_m = 0.01$, $\epsilon_0 = 0.95$, and $K = 50,000$. All experiments were run on two computing nodes with 256GB of memory and a 28-Core Intel 2.4GHz CPU. A single training run takes roughly 8 hours for the Action-In model and 2 hours for all other models. All *Hinters* and *Guessers* have the same model structure. To avoid giving the set-based attention architectures an unfair advantage, we independently permute the cards observed by the agents so they are not able to coordinate using the position of the cards. More details about the model architectures can be found in Appendix A.1.

Figure 3: Training performance of different architectures for the Hint-and-Guess game. The x-aixs is the number of episodes and Y-axis is the mean training reward. Solid line is the mean, shading is the standard error of the mean (s.e.m) across 20 different seeds.

8 RESULTS

We focus our investigation on cross-play performance and study the kinds of policies agents form with different NN architectures.

8.1 CROSS-PLAY PERFORMANCE.

First, we evaluate model performance for each architecture in the cross-play (XP) setting. In this setting, agents from independent training runs with different random seeds are paired together. Clearly,

Figure 4: Cross-play performance. Visualization of paired evaluation of different agents trained under the same method. The top row is the result for the full Hint-and-Guess game and the bottom row is the result for a simplified game where the *Hinter* and *Guesser* agents are always dealt the exact same hand. The y-axis represents the agent index of the *Hinter* and the x-axis represents the agent index of the *Guesser*. Each block in the grid is obtained by evaluating the pair of agents on 10K games with different random seeds. Numerical performance is shown in Table 1

high XP performance is a prerequisite or necessary (but not sufficient) condition for coordinating with other AI agents or humans. If agents trained from independent runs using the same model and training algorithm cannot coordinate with each other, it is highly unlikely they will be able to coordinate with agents built with different architectures or trained using different procedures and even less likely they will be able to coordinate with people (Hu et al., 2020).

Figure 4 records the scores obtained by each pair of agents, where the diagonal entries are the within-pair SP scores and the off-diagonal entries are XP scores. The bottom row shows the same results for a simplified version of the game, where both *Hinter* and *Guesser* have the same hand. In the simplified game, an optimal and intuitive strategy exists, which is to always hint the target card and then guess the card that is hinted. Table 1 summarizes average SP and XP scores across agents.

From the top row of Figure 4 (i.e., the full game setting), one immediately notices that while the XP performance all architectures except Action-In lack an interpretable pattern. Most of the architectures are at chance. However, the XP matrix for the Action-In model splits into two clusters. Within the clusters, agents show XP performance almost identical to SP, implying that they coordinate nearly perfectly with other agents trained with a different seed, whereas outside the clusters they achieve a return close to 0. As we will show in the next section, the upper cluster that has higher average XP score corresponds to the strategy where agents maximize the "closeness" between the target card and the hint card, as well as between the hint card and the guess card. In the lower, second cluster, agents try to do the opposite. They try to hint/guess cards that ideally share no common feature with the target/hint cards. In the rest of the paper, we will refer to the cluster where agents try to maximize the closeness between cards as Cluster 1, and the cluster where agents try to maximize the dissimilarity as Cluster 2.

In the bottom row of Figure 4 (i.e., the same hand condition), DQN and RDQN also has better performance than in the full game. This is likely because in the simplified setting, an optimal solution that always guarantees reward exists, and therefore the agents do not need to take advantage of features to converge to that solution. Action-In still splits into two clusters; cluster 1 (hint "closest") has perfect performance for SP and XP since it is the optimal solution, and cluster 2 (hint "furthest") is sub-optimal as agents may not tie-break when there are multiple cards the can hint/guess.

Table 1 summarizes XP and SP scores across models. We see that DQN and RDQN do not take explicit advantage of shared action and observation features which results in agents that perform well in SP but have XP scores close to chance. As we shall show shortly, they exploit features arbitrarily, resulting in miscoordination in XP. The Obs agent behaves similarly to the DQN/RDQN agents. The Action-Out and Action-In agents, on the other hand, have lower SP scores that are

close to their XP scores. This is because they learn simpler conventions using common features in the observations and actions. In other words, they achieve a SP-XP trade-off using the inherent inductive bias in the attention architecture.

Method	Full Game		Same Hand Condition	
	Cross-Play	Self-Play	Cross-Play	Self-Play
DQN	0.27 ± 0.13	0.85 ± 0.02	0.79 ± 0.09	0.98 ± 0.08
RDQN	0.30 ± 0.15	0.86 ± 0.02	0.68 ± 0.10	0.98 ± 0.03
Obs	0.27 ± 0.12	0.87 ± 0.03	0.29 ± 0.14	0.92 ± 0.03
Action-Out	0.26 ± 0.10	0.76 ± 0.05	0.27 ± 0.16	0.82 ± 0.08
Action-In	0.37 ± 0.35	0.76 ± 0.05	0.45 ± 0.47	0.90 ± 0.13
Action-In (Cluster 1)	0.77 ± 0.02	0.82 ± 0.02	1.00 ± 0.00	1.00 ± 0.00
Action-In (Cluster 2)	0.71 ± 0.03	0.72 ± 0.02	0.73 ± 0.03	0.73 ± 0.01

Table 1: Cross-play performance. We show results for both the full hint-and-guess game and the simplified version where both agents have the same hand. Each entry is the average performance is of 20 pairs of agents that are trained with different random seeds. Please refer to Fig. 4 for visualization of performance for each individual pair. Cross-Play score is the nondiagonal mean of each grid. Self-Play score is the diagonal mean, i.e. the score attained when agents play with the peer they are trained with.

8.2 Policy Evaluation.

Figure 5: Policy Evaluation. The top row shows the conditional probability for the *Hinter* to hint a particular card (x-axis) when the target card is the card on the y-axis. The bottom row is the conditional probability matrix for the *Guesser* to guess a particular card (x-axis) when the hinted card is the card on the y-axis. Each subplot is the sample average of 20 agent-pairs with different seeds for 1K games within pair.

Next, we evaluate the policies of agents in more detail. In Figure 5, we provide the conditional probability for the *Hinter* to hint a card given the target card it sees (top row) and the conditional probability for the *Guesser* to guess a card given the hint card it sees (bottom row).

We analyze whether agents assign different probabilities to actions based on the features they share with the observation. We see that for DQN, RDQN and Obs, the probability matrices for both target-hint and hint-guess are nearly uniform. The probability for the *Hinter* to hint $1A$ is the same no matter the target card is exactly $1A$, or $3C$ that shares no feature in common with $1A$ across seed. This implies that the SP policies across seeds each form their own private language for arbitrary and undecipherable coordination.

In contrast, for Action-Out, the probability matrix is visually less uniform (although still quite noisy). Indeed, in the target-hint matrix we can see that the *Hinter* will tend to hint $1A$ if it has $1A$, $2B$ if it has $1B$, $1C$ if it has $1C$, etc. In sum, Action-Out agents relatively prefer actions that are "closer" to the observation.

For the two clusters of the Action-In model this tendency is much stronger. For cluster 1 we see that both the *Hinter* and the *Guesser* prioritize acting with the card that is the same as the target/hint. If

Scenario	Self-Play (cluster 1)		Cross-Play (cluster 1)		Self-Play (cluster 2)		Cross-Play (cluster 2)	
	% Human	% Win	% Human	% Win	% Human	% Win	% Human	% Win
Exact match	100.0%	100.0%	100.0%	100.0%	0.0%	100.0%	0.0%	100.0%
Feature similarity	100.0%	100.0%	100.0%	100.0%	0.0%	100.0%	0.0%	100.0%
Mutual exclusivity	100.0%	100.0%	100.0%	100.0%	9.3%	91.2%	9.3%	92.2%
Similarity + Exclusivity	92.0%	91.7%	97.9%	99.5%	3.2%	98.4%	0.0%	99.9%

Table 2: Behavioral analysis for the Action-In model in the Figure 2 scenarios. We randomly chose 10 agent-pairs from each cluster and simulated the same scenario 1K times. % Human denotes the fraction of games where the *Hinter* hints the card that corresponds to human interpretable choice (highlighted in yellow in Fig. 2), and % Win denotes the fraction of games where the *Guesser* correctly guesses.

the exact match is not available, they turn to cards that share one feature in common. Hence, cluster 1 agents are solving $\max \sum_{i \in \{1,2\}} \mathbb{I}(f_i = \hat{f}_i)$, where $\mathbb{I}$ is the indicator function, f_i / $\hat{f}_i$ are the two observation and action features. For cluster 2 we see that agents do exactly the opposite — they solve $\min \sum_{i \in \{1,2\}} \mathbb{I}(f_i = \hat{f}_i)$, and therefore put equal probability on cards that share nothing in common with the target/hint cards. In summary, the two clusters represent two equilibria Action-In agents converge to in this game — maximizing or minimizing the feature-closeness between the observation and the action.

8.3 Scenario Analysis

Finally, we examine in a fine-grained way whether the agents in the two clusters of the Action-In models exhibit more sophisticated behavior beyond simply minimizing/maximizing the distance between features. Here we run simulations on the four scenarios shown in Figure 2 and described in Section 5. We find that the agents in cluster 1 of Action-In demonstrate coordination patterns that are nearly identical to the human-interpretable response. These results are surprising given that our models have never been trained with any human data. Furthermore, mutual exclusivity was thought to be hard for deep learning models to learn (Gandhi & Lake, 2020). In contrast, agents in cluster 2 always perform actions that are the opposite to the human-interpretable policy.

9 Discussion, Conclusion and Further Research

We have investigated the effect of network architectures on the ability of learning algorithms to make use of the semantic relationships between shared features across actions and observations in the context of Zero-Shot coordination. We compared the behavior of agents with feedforward, recurrent, and attention-based architectures and find that attention-based architectures that jointly process a featurized representation of the observation and the action have a better inductive bias for exploiting this relationship. This results in high cross-play performance as well as human-compatible policies in our novel hint-guess game, which we introduced as a new test bed for coordination.

Further research directions includes testing the different policy parameterization in sequential settings and testing in settings where features are not losslessly permutable (i.e. there is no true symmetry between the different features). Currently our method relies on a majority vote to obtain the more human-like cluster from a number of independent runs, it would be great to find a more robust, general purpose prior that biases towards this cluster in a single run. Furthermore, humans are able to use similarity across different modalities (vision and phonetic sound in the "Bouba" and "Kiki" example) using abstract representations of learned features, which is another exciting direction for future work. The method should also be tested with humans in more complex settings, e.g. in the benchmark games Hanabi or Overcooked.

REFERENCES

Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. Neural machine translation by jointly learning to align and translate. *International Conference on Learning Representations*, 2015.

Nolan Bard, Jakob N Foerster, Sarath Chandar, Neil Burch, Marc Lanctot, H Francis Song, Emilio Parisotto, Vincent Dumoulin, Subhodeep Moitra, Edward Hughes, Iain Dunning, Shibl Mourad, Hugo Larochelle, Marc G Bellemare, and Michael Bowling. The Hanabi Challenge: A New Frontier for AI Research. *arXiv*, 2019. doi: 10.1016/j.artint.2019.103216.

Samuel Barrett, Peter Stone, and Sarit Kraus. Empirical evaluation of ad hoc teamwork in the pursuit domain. In *AAMAS*, pp. 567–574, 2011.

Colin F Camerer. *Behavioral game theory: Experiments in strategic interaction*. Princeton university press, 2011.

Colin F Camerer, Teck-Hua Ho, and Juin-Kuan Chong. A cognitive hierarchy model of games. *The Quarterly Journal of Economics*, 119(3):861–898, 2004.

Micah Carroll, Rohin Shah, Mark K Ho, Tom Griffiths, Sanjit Seshia, Pieter Abbeel, and Anca Dragan. On the utility of learning about humans for human-ai coordination. *Advances in Neural Information Processing Systems*, 32:5174–5185, 2019.

Allan Dafoe, Edward Hughes, Yoram Bachrach, Tantum Collins, Kevin R McKee, Joel Z Leibo, Kate Larson, and Thore Graepel. Open problems in cooperative ai. *arXiv preprint arXiv:2012.08630*, 2020.

Jakob Foerster, Francis Song, Edward Hughes, Neil Burch, Iain Dunning, Shimon Whiteson, Matthew Botvinick, and Michael Bowling. Bayesian action decoder for deep multi-agent reinforcement learning. In *International Conference on Machine Learning*, pp. 1942–1951. PMLR, 2019.

Michael C Frank and Noah D Goodman. Predicting pragmatic reasoning in language games. *Science*, 336(6084):998–998, 2012.

Kanishk Gandhi and Brenden M Lake. Mutual exclusivity as a challenge for deep neural networks. *Advances in Neural Information Processing Systems*, 33, 2020.

Noah D Goodman and Andreas Stuhlmüller. Knowledge and implicature: Modeling language understanding as social cognition. *Topics in cognitive science*, 5(1):173–184, 2013.

Herbert P Grice. Logic and conversation. In *Speech acts*, pp. 41–58. Brill, 1975.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural Comput.*, 9(8): 1735–1780, November 1997. ISSN 0899-7667. doi: 10.1162/neco.1997.9.8.1735. URL https://doi.org/10.1162/neco.1997.9.8.1735.

Hengyuan Hu, Adam Lerer, Alex Peysakhovich, and Jakob Foerster. "Other-Play" for Zero-Shot Coordination. *arXiv*, 2020.

Hengyuan Hu, Adam Lerer, Brandon Cui, Luis Pineda, David Wu, Noam Brown, and Jakob Foerster. Off-belief learning. *arXiv preprint arXiv:2103.04000*, 2021.

Max Kleiman-Weiner, Mark K Ho, Joseph L Austerweil, Michael L Littman, and Joshua B Tenenbaum. Coordinate to cooperate or compete: abstract goals and joint intentions in social interaction. In *CogSci*, 2016.

W Köhler. *Gestalt psychology*. Liveright, 1929.

Adam Lerer and Alexander Peysakhovich. Learning social conventions in markov games. *arXiv preprint arXiv:1806.10071*, 2018.

David K Lewis. *Convention: A Philosophical Study*. Blackwell, 1969.

Daphne Maurer, Thanujeni Pathman, and Catherine J Mondloch. The shape of boubas: Sound–shape correspondences in toddlers and adults. *Developmental science*, 9(3):316–322, 2006.

Jennifer B Misyak, Tigran Melkonyan, Hossam Zeitoun, and Nick Chater. Unwritten rules: virtual bargaining underpins social interaction, culture, and society. *Trends in cognitive sciences*, 18(10): 512–519, 2014.

R Nair, M Tambe, M Yokoo, D Pynadath, and S Marsella. Taming decentralized pomdps: Towards efficient policy computation for multiagent settings. *International Joint Conferences on Artificial Intelligence*, pp. 705–711, 2003.

Frans A Oliehoek and Christopher Amato. *A concise introduction to decentralized POMDPs*. Springer, 2016.

Avik Pal, Jonah Philion, Yuan-Hong Liao, and Sanja Fidler. Emergent road rules in multi-agent driving environments. In *International Conference on Learning Representations*, 2020.

Michael Shum, Max Kleiman-Weiner, Michael L Littman, and Joshua B Tenenbaum. Theory of minds: Understanding behavior in groups through inverse planning. In *Proceedings of the AAAI conference on artificial intelligence*, volume 33, pp. 6163–6170, 2019.

Dale O Stahl and Paul W Wilson. On players´models of other players: Theory and experimental evidence. *Games and Economic Behavior*, 10(1):218–254, 1995.

Peter Stone, Gal A Kaminka, Sarit Kraus, and Jeffrey S Rosenschein. Ad hoc autonomous agent teams: Collaboration without pre-coordination. In *Twenty-Fourth AAAI Conference on Artificial Intelligence*, 2010.

Michael Tomasello, Malinda Carpenter, Josep Call, Tanya Behne, and Henrike Moll. Understanding and sharing intentions: The origins of cultural cognition. *Behavioral and brain sciences*, 28(5): 675–691, 2005.

Michael Tomasello, Malinda Carpenter, and Ulf Liszkowski. A new look at infant pointing. *Child development*, 78(3):705–722, 2007.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention Is All You Need. *arXiv*, 2017.

Sarah A Wu, Rose E Wang, James A Evans, Joshua B Tenenbaum, David C Parkes, and Max Kleiman-Weiner. Too many cooks: Bayesian inference for coordinating multi-agent collaboration. *Topics in Cognitive Science*, 13(2):414–432, 2021.

Kelvin Xu, Jimmy Ba, Ryan Kiros, Kyunghyun Cho, Aaron Courville, Ruslan Salakhutdinov, Richard Zemel, and Yoshua Bengio. Show, attend and tell: Neural image caption generation with visual attention. *International Conference on Machine Learning*, 2016.

H Peyton Young. The evolution of conventions. *Econometrica: Journal of the Econometric Society*, pp. 57–84, 1993.

A APPENDIX

A.1 MODEL AND ARCHITECTURE DETAILS

Deep Q-Learning (DQN). The DQN agent is a feedforward ReLU NN with 3 hidden layers (width 128).

Recurrent Deep Q-Learning (RDQN). The RDQN agent has an LSTM layer with 128 LSTM units followed by two fully-connected layers with 128 ReLU units. The input of the RDQN agent is the same as that of the DQN agent but vectors representing the cards are fed in sequentially to the LSTM before we concatenate all hidden states from each step and use that as input to a feedforward NN.

Attention Models. All three attention-based models share the same single-head attention layer with size determined by the shapes of the input and output. We do not add position encoding. In Obs, we add a feedforward ReLU NN with 3 hidden layers (width 128) after the attention layer. In Action-Out and Action-In, we do not add extra ReLU layers.