Evaluating the Reversal Curse in Model Editing

Abstract

Large language models (LLMs) are prone to hallucinate unintended text due to false or outdated knowledge. Since retraining LLMs is resource intensive, there has been a growing interest in *model editing*. Despite the emergence of benchmarks and approaches, these *unidirectional* editing and evaluation have failed to explore the *reversal curse*. In this paper, we study bidirectional language model editing, aiming to provide a rigorous evaluation to assess if edited LLMs can recall the editing knowledge bidirectionally. A metric of *reversibility* is introduced and a benchmark dubbed as **B**idirectional **A**ssessment for **K**nowledge **E**diting (BAKE) is constructed to evaluate if post-edited models can recall the editing knowledge in the reverse direction of editing. We conduct extensive experiments using a variety of editing methods and LLMs. The results show that while most editing methods are able to accurately recall editing facts along the modification direction, they exhibit substantial systematic deficiencies when evaluating in the reverse direction. To further investigate the underlying causes of reversal curse and to explore potential strategies for mitigation, a detailed analysis are conducted from three perspectives. Our findings reveal that although the in-context learning (ICL) can mitigate the reversal curse to a certain extent, it lacks continuity, is limited by the the input length, and may introduce hallucinations. Therefore, it is promising to combine the advantages of ICL and other editing methods to develop new editing paradigms.

1 Introduction

Large language models (LLMs) have shown impressive capabilities in understanding and generating text, improving performance on a variety of tasks (Chen et al., 2021; Ouyang et al., 2022; Zhang et al., 2023a). However, existing LLMs inevitably exhibit hallucinations due to incorrect or outdated knowledge stored in their parameters (Zhang et al., 2023b; Peng et al., 2023; Ji et al., 2023). Considering the huge computing resource consumption of retraining LLMs and echoing green deep learning (Schwartz et al., 2020; Xu et al., 2021), there has been considerable and growing attention on the research regarding *knowledge editing* (a.k.a., *model editing*) (Sinitsin et al., 2020; Cao et al., 2021; Meng et al., 2022; 2023; Dai et al., 2022; Mitchell et al., 2022b; Yao et al., 2023; Gu et al., 2024; Xu et al., 2025), which aims at efficiently modifying and updating specific knowledge without full retraining.

Existing model editing methods fall into two categories (Yao et al., 2023): *Parameter-preserving methods* (Wang et al., 2024a), and *Parameter-modifying* (Mitchell et al., 2022b; Meng et al., 2023) paradigms. The effectiveness of an editing method is usually evaluated along three dimensions of *efficacy*, *generalization* and *locality*. The ZsRE (Levy et al., 2017) and CounterFact (Meng et al., 2022) datasets are primarily utilized to assess whether edited models can recall the newly injected facts, as depicted in Figure 1(a). Besides, Yao et al. (2023) and Zhong et al. (2023) have introduced *portability* and MQuAKE respectively to extend the assessment of generalization by measuring whether edited models can correctly answer the questions entailed by the editing facts, as shown in Figure 1(b). Despite the emergence of benchmarks and techniques for editing, they all operate under the *unidirectional* paradigm following only the direction being edited. The *reversal curse* (Berglund et al.) has not yet been explored in model editing, and it remains unclear whether edited models can reason and recall the editing facts in the reverse direction of editing, as shown in Figure 1(c).

Figure 1: Comparison of *unidirectional* evaluation paradigms that assess whether edited models can recall the editing facts (a) via single-hop questions, or (b) via entailed questions in the direction of editing; and (c) the proposed *bidirectional* paradigm that assesses model editing in the reverse direction of editing. f_θ / f_{θ_e} denotes the models before / after editing.

In this paper, we study bidirectional language model editing, determining if edited LLMs can accurately recall the editing knowledge bidirectionally. Among various kinds of learned beliefs such as logical, spatial, or numerical knowledge, this paper investigates factual knowledge within LLMs, where each piece of knowledge is represented in the form of a *(subject, relation, object)* triple. A metric of *reversibility* is introduced to evaluate the effectiveness of edited models in recalling knowledge in the reverse direction of editing. A benchmark dubbed as **B**idirectional **A**ssessment for **K**nowledge **E**diting (BAKE) is constructed. When inverting the relation between subject and object, the taxonomy which categorizes relations between entities into four classes: *one-to-one*, *one-to-many*, *many-to-one*, *many-to-many* (Bordes et al., 2013), is considered. To characterize these symmetrical and asymmetrical relations, two evaluation forms of *question answering* (QA) and *judgment* are adopted for evaluation.

To establish the comparison of existing model editing methods on bidirectional model editing, this paper conducts meticulous experiments on nine editing methods in two categories, including parameter-modifying methods: FT (Zhu et al., 2020), MEND (Mitchell et al., 2022a), MEMIT (Meng et al., 2023) ROME (Meng et al., 2022), RECT (Gu et al., 2024), AlphaEdit (Fang et al., 2025), and parameter-preserving methods: GRACE (Hartvigsen et al., 2023), WISE (Wang et al., 2024a) and IKE (Zheng et al., 2023). Five representative LLMs of varying sizes are selected as the base models including GPT-2 XL (1.5B) (Radford et al., 2019), GPT-J (6B) (Wang & Komatsuzaki, 2021), LLaMA-2 (7B) (Touvron et al., 2023), LLaMA-2 (13B) (Touvron et al., 2023) and LLaMA-3 (8B) (Dubey et al., 2024). We surprisingly observe that the vast majority of current editing methods and LLMs, while effective in recalling editing facts in the direction of editing, suffer serious deficiencies when evaluated in the reverse direction. Strikingly, the LLaMA-3 (8B) model edited by the state-of-the-art AlphaEdit (Fang et al., 2025) can recall 98.45% of the editing facts in the editing direction, but only 0.88% of the editing facts in the reverse direction. Another interesting finding is that when an in-context learning (ICL)-based method IKE is used for model editing, the reverse knowledge recall accuracy on LLaMA-3 (8B) reaches 51.78%, indicating that the reversal curse could be mitigated to some extent.

To further investigate the underlying causes of the reversal curse, a detailed analysis are conducted from three perspectives. Our findings and conclusions are mainly in three aspects: (1) We compared the probability of the model generating the original answer and the desired answer after editing. Unexpectedly, the models edited by most methods did not increase the probability of the desired answer, which indicates that they lacks a true understanding of editing knowledge, leading to the "reversal curse". (2) The ICL mechanism can help other editing methods mitigate the reversal curse to some extent, but it lacks continuity and is limited by the length of the context window. (3) When using ICL-based methods for editing, the model may output answers that are irrelevant to the question. Although these findings reveal that ICL mechanism can mitigate the reversal curse to a certain extent, it lacks continuity, scalability, and may introduce hallucinations. Therefore, it is particularly important to better combine it with existing editing methods to develop new editing paradigms.

In summary, our contributions are three-fold: (1) This study makes the first attempt to explore bidirectional language model editing. A metric of reversibility is introduced and a benchmark of BAKE is constructed to assess the reversibility of edited models. (2) This paper conducts meticulous experiments and presents surprising finding that existing methods and LLMs suffer from the severe reversal curse on model editing. (3) This paper presents a detailed analysis and provides initial insight into the underlying causes of the reversal curse, while also exploring a potential direction to mitigate the problem. All data and code are available to facilitate reproducing our results. We hope that both our benchmark and analysis can shed light on bidirectional language model editing.

2 Related Work

Model Editing   Existing model editing methods are generally categorized into two types: those that modify model parameters and those that preserve them using auxiliary mechanisms to avoid direct weight changes. *Parameter-modifying methods* inject new knowledge by directly updating model weights within the original architecture. It can be further divided into two categories. Meta-learning approaches such as KE (Cao et al., 2021), MEND (Mitchell et al., 2022a), and InstructEdit (Zhang et al., 2024) rely on hypernetworks to generate updates. Locate-then-edit approaches like ROME (Meng et al., 2022), MEMIT (Meng et al., 2023), and EAC (Xu et al., 2025) utilize causal tracing and compressed updates to reduce side effects such as knowledge forgetting. PRUNE (Ma et al., 2025) restricts the conditional number to localize parameter changes more effectively. *Parameter-preserving methods* aim to retain the original model weights by leveraging external modules or non-invasive editing strategies. IKE (Zheng et al., 2023) and DeCK (Bi et al., 2024) use in-context learning to condition the model on new information, while SERAC (Mitchell et al., 2022b) employs an external memory to store and retrieve edits. T-Patcher (Huang et al., 2023) and CaliNet (Dong et al., 2022) inject additional neurons into the model architecture, GRACE (Hartvigsen et al., 2023) replaces internal hidden states with codebook representations, and WISE (Wang et al., 2024a) integrates updates using parameterized memory. Meanwhile, several benchmarks have emerged to evaluate the performance and reliability of model editing methods (Meng et al., 2022; 2023; Yao et al., 2023; Mitchell et al., 2022b; Zhong et al., 2023). For instance, Zhong et al. (2023) propose the use of multi-hop questions to assess whether editing one fact also necessitates coherent adjustments to related knowledge across the model.

The Reversal Curse of LLMs   Recent works have studied the reversal curse (Berglund et al.; Lv et al., 2023; Guo et al., 2024; Lu et al., 2024; Apaolaza et al., 2025) in auto-regressive LLMs. Berglund et al. have verified that a model fine-tuned on a sentence of the form "*A is B*", it will not automatically generalize to the reverse direction "*B is A*". Moreover, the likelihood of the correct answer will not be higher than for a random answer. This is termed as the *reversal curse*. Contemporary to this work, Grosse et al. (2023) determined how much adding a given training example influences an LLM's outputs. For instance, given the input A, what most influences the likelihood of B? In their experiments, training examples that match the order ("*A precedes B*") are far more influential than examples with reverse order ("*B precedes A*"). Results show that if a pretrained model was not trained on facts in both directions, it would not generalize to both directions.

Compared with previous studies (Dai et al., 2022; Meng et al., 2022; 2023; Mitchell et al., 2022a; Yao et al., 2023; Zhong et al., 2023; Berglund et al.) that are the most relevant to our work, a main difference should be highlighted. These studies target only on unidirectional model editing, while this study explores bidirectional editing and evaluation. To the best of our knowledge, this paper makes the first attempt to introduce a metric of *reversibility*, build a benchmark for evaluating the reversibility of editing methods, analyze the underlying causes of the reversal curse in model editing and point out future exploration directions to mitigate it.

3 Preliminary

The goal of model editing is to insert new facts into model parameters without retraining. In this paper, we study facts of the form (s, r, o), consisting of a subject s, a relation r, and an object o (e.g., $s =$ Eiffel Tower, $r =$ locate in, $o =$ Paris). Besides, we follow previous works (Zhong et al., 2023; Yao et al., 2023) to employ discrete prompts (question or cloze-style statement) to test whether a fact is in a model. Editing a fact is

to insert a new triple (s, r, o^*) in place of the current triple (s, r, o), where these two triples share the same subject and relation. An editing operation is represented as $e = (s, r, o, o^*)$ for brevity.

Given an edit e and a model f, model editing involves learning a function K that yields an edited language model $f^* : K(f, e) = f^*$. To evaluate the effectiveness of model editing methods, previous works focus on evaluation along three dimensions: efficacy, generalization and locality (Mitchell et al., 2022a; Meng et al., 2022).

Efficacy validates whether the edited models could recall the exact editing fact when presented with the sole editing prompt p. The assessment is based on Efficacy Score **(ES)** representing as: $\mathbb{1}[\operatorname{argmax}_o P_{f^*}(o \mid p) = o^*]$, where $\mathbb{1}$ is the indicator function.

Generalization verifies whether the edited models could recall the editing fact under paraphrase prompts via Generalization Score **(GS)**: $\mathbb{E}_{p \in \mathcal{P}^G}[\mathbb{1}[\operatorname{argmax}_o P_{f^*}(o \mid p) = o^*]]$.

Locality[1] is to verify whether the output of the edited models for inputs out of editing scope remains unchanged after editing under locality prompts via Locality Score **(LS)**: $\mathbb{E}_{p_l \in \mathcal{P}^L}[\mathbb{1}[\operatorname{argmax}_o P_{f^*}(o \mid p_l) = o_l]]$, where o_l was the original answer of p_l.

For example, given an editing fact $(s = \text{Eiffel Tower}, r = \text{located in}, o = \text{Paris}, o^*=\text{London})$, the editing prompt p could be "Eiffel Tower is located in", A paraphrase prompt could be "What is the location of the Eiffel Tower?". A locality prompt and its original answer could be "Where is the Louvre?" and "Paris" respectively.

4 BAKE: Bidirectional Assessment for Knowledge Editing

The BAKE benchmark comprises two datasets of BAKE-Q&J and BAKE-J. Since it is difficult to directly measure the existing outdated and false knowledge in LLMs. Therefore, following previous works (Meng et al., 2022; Zhong et al., 2023; Yao et al., 2023), both datasets are designed for evaluating counterfactual edits in LLMs. When inverting the relation between subject and object, two evaluation forms of *question answering (Q)* and *judgment (J)* are adopted to characterize these symmetrical and asymmetrical relations.

4.1 Relation Category

There are various relations between entities in factual knowledge, which could be classified into four classes: *one-to-one*, *one-to-many*, *many-to-one*, and *many-to-many* (Bordes et al., 2013), as shown in Figure 2.

For *one-to-one* and *one-to-many* relations, both *question answering* and *judgment* forms are employed since there is only one definite output after inverting the relation. Take "*developed*" relation from *one-to-many* category in Figure 2(b) as an example, one can construct the factual statement "*Apple developed iPhone*". When it is validated reversely, it could be presented to models in QA form like "*iPhone is developed by ___*" or *judgment* form like "*Whether iPhone is developed by Apple?*" Similarly, *one-to-one* category shares the same property as *one-to-many*.

(a) one-to-one (b) one-to-many (c) many-to-one (d) many-to-many

Figure 2: Examples of four relation categories. A given relation is considered (a) *one-to-one* if a subject can be associated with at most one object; (b) *one-to-many* if a subject can be associated with multiple objects; (c) *many-to-one* if multiple subjects can be linked to the same object; or (d) *many-to-many* if multiple subjects can be linked to multiple objects.

On the other hand, only the *judgment* form is employed for *many-to-one* and *many-to-many* relations, since there are alternative outputs to a given reversal relation. Suppose a "*written by*" relation from *many-to-one* category shown in Figure 2(c) is chosen to form a statement "*The Trial is written by Kafka*". If presented to models for reverse validation in QA form like "*Kafka has written ___*", there may be many correct answers such as *The Metamorphosis* and *The Castle*. It is notable that

---

[1]Also referred to as *specificity* in Meng et al. (2022; 2023).

edited models are expected to output *The Trial* intended for reversal evaluation instead of *The Metamorphosis* and *The Castle.* Therefore, evaluating the reversal relation for *many-to-one* and *many-to-many* categories via *judgment* is better. Similarly, the *many-to-many* category shares the same property as the *many-to-one* category.

4.2 Data Construction of BAKE-Q&J

This dataset is constructed based on Wikidata (Vrandecic & Krötzsch, 2014), a knowledge base containing millions of fact triples. First, we manually chose a total of 25 *one-to-one* and *one-to-many* relations, and all fact triples under each relation, denoted as $F(r) = \{(s, r, o) \mid s$ and o are linked by r in Wikidata$\}$. For each relation r, ChatGPT (gpt-4o) was used to generate some templates $T(r)$ and those $T(r^{-1})$ corresponding to its inverse relation[2] r^{-1}. Appendix A provides some examples of these templates. Entities can be replaced to form full prompts[3]: $\mathcal{P}(s, r) = \{t.\texttt{format}(s) \mid t \in T(r)\}$, where `.format()` is string substitution. For example, a template for (r = written by) might be "*{} is written by*", where "*Hamlet*" substitutes "*{}*".

Constructing counterfactual edits To construct an editing example, two triples sharing the relation r are sampled from Wikidata, denoted as (s, r, o) and (s^*, r, o^*) respectively. An edit is represented as $\mathcal{E} = \{s, r, o, o^*, p\}$ to test *efficacy*, where the editing prompt $p \sim \mathcal{P}(s, r)$. Besides, to test *generalization*, a set of two semantically-equivalent paraphrase prompts $\mathcal{P}^G$ are sampled from $\mathcal{P}(s, r) \setminus \{p\}$. Moreover, to test *locality*, a set of triples that share the same object o are collected: $\mathcal{S} = \{(s', r', o)\}$. For example, select (*s*= *Eiffel Tower, r= located in, o= Paris*), $\mathcal{S}$ might contain triple like (*s= France, r= has capital, o= Paris*). Then a set of prompts $\{\mathcal{P}(s', r') \mid (s', r', o) \in \mathcal{S}\}$ are constructed to sample the locality prompts $\mathcal{P}^L$.

Constructing reverse prompts As for the *reversibility* proposed in this paper, after modifying the knowledge from (s, r, o) to (s, r, o^*), the edited model should be capable of deducing (o^*, r^{-1}, s) if it is reversible. To ensure that the evaluation is valid after editing, we should make the triple (o^*, r^{-1}, s) is not included (editing knowledge should not pre-exist) and (o^*, r^{-1}, s^*) is included (original knowledge should pre-exist) in the original LLM. If not, this editing example will be filtered out accordingly. Specifically, given o^* and r^{-1}, we tested if a model can output s^* rather than s, to deduce if the triple (o^*, r^{-1}, s^*) is included in the model. Furthermore, there are QA and *judgment* forms prompts in this dataset and the reverse-qa prompt is represented as $\mathcal{P}^{Rq} = \{o^*, r^{-1}, s^*, s, p^{-1}\}$, where $p^{-1} \sim \mathcal{P}(o^*, r^{-1})$ and s is the desired answer after editing (e.g., if s=Apple, s^*=Microsoft, r=developed, o^*=Windows, then r^{-1}=developed by, and p^{-1} might be "*Windows is developed by which company?*"). Besides, the reverse-judge prompt $\mathcal{P}^{Rj}$ is a *judgment* question based on p^{-1}, for instance, "*Whether Windows is developed by Apple?*", which should be answered with "*yes*" after editing or "*no*" before editing.

Table 1: An example in the BAKE-Q&J dataset. a and a^* in different columns represent the original answer and desired answer after editing respectively.

$\mathcal{E}$	(s, r, o): (Paris, capital of, France)
(s^*, r, o^*): (London, capital of, England)
(Paris, capital of, France → England)
p: Paris is the capital of (a: France, a^*: England)
$\mathcal{P}^G$	Paris, which is the capital of
Paris is the political center of which country?
(a: France, a^*: England)
$\mathcal{P}^L$	Palace of Versailles is located in
Marseille is the city of which country?
(a: France, a^*: France)
$\mathcal{P}^{Rq}$	What is the capital of England?
(a: London, a^*: Paris)
$\mathcal{P}^{Rj}$	Whether the capital of England is Paris?
(a: no, a^*: yes)

4.3 Data Construction of BAKE-J

The construction of this dataset is similar to BAKE-Q&J, and the difference lies in that 20 *many-to-one* and *many-to-many* relations in total were manually selected. Moreover, only the *judgment* form is adopted for validating the reversibility, which has been explained in Section 4.1.

---

[2]Inverse relation r^{-1} and its templates are only for evaluation.
[3]They could be in the form of question or cloze-style statement.

Table 2: The categories of editing methods.

| Type | Parameter-modifying | | | | | | Parameter-preserving | | |
	Gradient-based		Locate-then-edit				External parameter		ICL-based
Method	FT	MEND	ROME	MEMIT	RECT	AlphaEdit	GRACE	WISE	IKE

4.4 Dataset Summary

Dataset Format   As shown in Table 1, each example in the BAKE benchmark is represented as a tuple ($\mathcal{E}$, $\mathcal{P}^G$, $\mathcal{P}^L$, $\mathcal{P}^{Rq}$, $\mathcal{P}^{Rj}$), where $\mathcal{E}$ is the editing knowledge which will be injected into the language model. $\mathcal{P}^G$ and $\mathcal{P}^L$ are the prompts utilized to validate generalization and locality respectively. $\mathcal{P}^{Rq}$ and $\mathcal{P}^{Rj}$ correspondingly represent the reverse-qa and reverse-judge prompts for reversibility. a and a^* denote the original answer and desired answer after editing respectively.

Dataset Statistics   Readers can refer to Appendix B for the details of the statistics of the BAKE-Q&J and BAKE-J datasets. To verify generalization and locality, there is at least one prompt for each editing example. Meanwhile, there is one reverse-qa prompt (only for BAKE-Q&J) and one reverse-judge prompt to verify reversibility. Both datasets consist of counterfactual edits utilized to investigate if edited models can recall the editing facts in both the editing and reverse directions.

5 Experiments

5.1 Experimental Setup

Base LLMs   Given limited computing resources, experiments were conducted on five LLMs of different sizes including **GPT-2 XL** (1.5B) (Radford et al., 2019), **GPT-J** (6B) (Wang & Komatsuzaki, 2021), **LLaMA-2** (7B) (Touvron et al., 2023), **LLaMA-3** (8B) (Dubey et al., 2024) and **LLaMA-2** (13B) (Touvron et al., 2023).

Editing Methods   Nine model editing methods were selected as the baselines, as show in Table 2. Readers can refer to Appendix C.1 for more details.

Evaluation Metrics   In addition to the proposed *Reversibility*, three basic metrics of *Efficacy*, *Generalization* and *Locality* (Meng et al., 2022; 2023) introduced in Section 3 were adopted. Given two facts of (s, r, o) and (s^*, r, o^*), one editing operation updated (s, r, o) to (s, r, o^*) and the edited model f^* was obtained. And the reverse-qa prompts $\mathcal{P}^{Rq}$ were formulated by o^* and r^{-1}, with answer s. *Reversibility* was to evaluate the effectiveness of edited models in recalling the editing knowledge under reverse prompts. For QA form prompts, Reverse-QA Score **(RQS)** was defined as: $\mathbb{E}_{p \in \mathcal{P}^{Rq}}[\,\mathbb{1}[\mathrm{argmax}_o P_{f^*}(o\,|\,p) = s]\,]$. As for judgment form prompts, Reverse-Judgment Score **(RJS)** was defined as: $\mathbb{E}_{p \in \mathcal{P}^{Rj}}[\,\mathbb{1}[\mathrm{argmax}_o P_{f^*}(o\,|\,p) = yes]\,]$. For all the above metrics, the average results across all edits in each dataset were reported. Define RS was as the average of RQS and RJS[4], the harmonic mean of ES, GS, LS, and RS was reported as Score **(S)** to comprehensively evaluate the performance of edited models in a more balanced manner.

5.2 Evaluation Results

Table 3 reported the results of different editing methods on BAKE-Q&J and BAKE-J. The RQS and RJS results for each base LLM were 0, since the counterfactual editing triples that pre-existed in each LLM have been filtered out as mentioned in Section 4.2.

Existing methods perform well in the direction of editing   Most methods have high efficacy and generalization performance, showing that existing editing methods are capable of effectively recalling the editing facts in editing direction. However, the performance in terms of locality was still limited and deserves

---

[4]Since there is no RQS in BAKE-J, only RJS is used to compute the harmonic mean.

Table 3: Evaluation results (%) of the BAKE-Q&J and BAKE-J datasets. The settings for these methods were the same with the published literature. The row named after the model name represents the results evaluated on the base model.

| Editor | BAKE-Q&J | | | | | | BAKE-J | | | | |
| | Score | Previous | | | Reversibility | | Score | Previous | | | Reversibility |
	S↑	ES↑	GS↑	LS↑	RQS↑	RJS↑	S↑	ES↑	GS↑	LS↑	RJS↑
GPT-2 XL (1.5B)											
FT	19.40	78.11	49.64	64.12	2.79	9.89	25.54	85.88	52.97	65.01	9.03
MEND	3.88	94.01	78.12	28.14	1.75	0.31	0.28	90.89	74.25	29.17	0.09
MEMIT	16.41	72.59	63.97	64.13	0.31	9.75	18.93	83.12	69.53	66.29	5.89
ROME	41.35	97.99	91.74	51.97	3.56	31.88	49.89	98.16	86.31	62.79	23.54
RECT	38.94	95.69	93.27	58.17	2.98	28.10	48.25	96.63	84.56	69.85	21.55
AlphaEdit	43.62	93.99	94.74	79.16	3.01	31.55	47.90	97.84	82.39	75.44	20.88
GRACE	38.51	88.05	30.84	99.99	4.58	35.35	43.78	91.60	35.52	95.98	23.88
WISE	50.63	92.87	90.04	99.68	5.12	37.34	55.07	90.69	85.61	98.78	25.12
IKE	78.26	92.45	95.19	89.97	38.14	68.94	84.70	98.34	88.43	85.37	71.26
GPT-J (6B)											
FT	12.90	72.69	41.35	73.17	0.62	7.12	23.94	83.55	44.26	70.59	8.45
MEND	1.22	95.37	70.98	37.22	0.79	0.43	0.99	91.79	70.34	35.11	0.25
MEMIT	21.05	96.58	87.32	66.37	0.17	12.89	35.46	96.38	83.50	70.52	13.11
ROME	42.92	98.32	94.17	55.11	2.76	34.12	55.78	97.55	90.87	64.79	28.56
RECT	40.62	97.74	94.27	52.08	2.12	32.10	55.36	98.36	88.71	77.29	26.40
AlphaEdit	42.29	98.12	95.88	62.37	2.55	31.98	57.95	97.88	90.12	80.56	28.33
GRACE	31.95	86.65	20.48	99.87	3.15	33.34	41.17	92.63	23.12	99.91	30.21
WISE	48.19	93.85	85.32	99.32	4.72	34.83	64.76	99.91	81.34	99.87	33.96
IKE	76.06	97.56	92.17	82.34	35.83	67.54	85.81	95.37	92.26	85.11	73.84
LLaMA-2 (7B)											
FT	13.79	97.85	90.46	33.14	0.27	8.11	31.19	94.97	88.12	24.85	15.12
MEND	16.95	90.76	71.55	40.57	0.52	10.22	12.48	89.01	66.18	42.99	3.69
MEMIT	38.71	99.71	97.22	60.94	0.17	29.85	64.97	97.34	90.11	72.17	37.95
ROME	47.58	99.39	95.26	65.84	0.32	41.06	68.89	97.55	90.86	73.47	43.12
RECT	46.23	98.43	91.68	74.60	0.98	37.44	64.73	99.61	90.69	64.17	39.77
AlphaEdit	46.06	99.11	92.94	72.16	0.81	37.55	68.27	98.98	91.55	75.15	41.23
GRACE	40.04	98.05	28.85	99.79	2.54	41.88	48.27	97.92	25.63	99.96	42.31
WISE	54.13	99.71	88.42	99.99	3.12	43.87	74.87	99.82	88.89	99.98	45.14
IKE	83.62	96.34	90.89	86.56	45.79	76.45	86.74	96.99	93.21	84.67	69.98
LLaMA-3 (8B)											
FT	15.71	96.41	89.98	39.24	0.26	9.37	27.41	91.91	91.04	20.35	13.35
MEND	13.25	84.36	75.31	45.31	0.52	7.33	12.09	88.34	72.37	46.11	3.52
MEMIT	37.59	97.72	92.81	60.19	0.19	28.88	62.21	98.70	86.29	71.74	34.92
ROME	41.43	98.69	92.71	53.60	0.24	34.86	67.98	98.40	93.57	64.09	44.66
RECT	44.66	98.88	93.04	56.83	0.27	38.86	66.58	98.42	92.37	67.13	41.33
AlphaEdit	40.69	98.45	91.41	77.31	0.88	30.24	66.96	99.20	88.43	73.11	40.54
GRACE	42.52	98.18	34.88	99.91	3.89	40.34	59.65	95.03	38.69	99.97	48.34
WISE	63.33	98.58	89.82	99.98	4.08	41.22	78.10	97.98	90.81	99.98	50.01
IKE	83.68	97.99	93.45	88.73	51.78	76.83	88.55	98.52	92.79	86.34	73.98
LLaMA-2 (13B)											
FT	16.99	96.04	92.21	40.04	0.33	10.24	29.08	90.41	88.43	26.63	12.88
MEND	14.57	87.21	72.15	43.88	0.47	8.36	23.02	90.16	71.88	43.84	7.94
MEMIT	36.95	96.76	90.68	70.96	0.35	27.12	61.98	96.81	90.84	76.87	33.12
ROME	39.76	99.84	87.08	63.35	0.31	31.28	66.33	99.75	87.12	64.41	42.97
RECT	47.55	99.50	94.92	78.14	0.88	38.54	68.16	99.12	85.98	69.81	44.17
AlphaEdit	45.21	97.99	92.37	79.18	1.01	35.48	70.38	99.65	90.88	76.89	43.88
GRACE	42.03	99.12	32.11	99.88	2.63	42.91	49.48	99.11	27.12	99.97	41.88
WISE	53.03	99.89	93.20	99.94	2.99	44.63	76.83	99.57	93.41	99.09	47.12
IKE	85.65	96.75	94.19	86.88	53.96	75.17	89.75	99.12	90.18	89.11	77.19

further investigation. Moreover, with the increase in model size, the performance of a specific editing method continued to improve on these three metrics. For instance, the performance of MEMIT applied to LLaMA-2 (13B) was notably higher than that applied to GPT-2 XL in terms of ES, GS, and LS by 23.33%, 27.91%, and 6.65% respectively on the BAKE-Q&J dataset.

Most methods fail in the reverse direction of editing Surprisingly, we observed that most editing methods and LLMs failed catastrophically when evaluated in the reverse direction of editing, especially in the QA form. Taking LLaMA-3 (8B) edited by AlphaEdit on BAKE-Q&J as an example, it achieved 98.45%

(ES) which exhibited an impressive ability of recalling the editing facts in the direction of editing. However, it could only recall 0.88% (**RQS**) of the editing facts when evaluated in the reverse direction of editing using the QA format. Even when evaluated via the judgment form, it answered only 30.24% (**RJS**) of the questions correctly. These results show a surprising conclusion that, although current editing methods and LLMs can effectively recall the editing facts in the direction of editing, they suffer serious deficiencies when evaluated in the reverse direction. Our results suggest that current editing methods are far from fully understanding the injected knowledge, but just simply memorize via hard encoding. These also echo the *reversal curse* in Berglund et al. and Grosse et al. (2023), and we hope to attract more attention to this challenging issue.

Different categories of editing methods have significant performance differences for the same metric   For RJS, the performance of gradient-based methods (FT, MEND) was markedly lower compared to methods that rely on locating knowledge neurons (MEMIT, ROME, AlphaEdit). This suggests that gradient updates demonstrate a myopic nature, showing a weak capacity to update information in the reverse direction. In addition, we found that the parameter-preserving methods (GRACE, WISE, IKE) outperformed the parameter-modifying approaches (RECT, AlphaEdit) on both LS and RJS metrics. This suggests that directly modifying model parameters introduces changes that hinder the model's ability to retain original knowledge and update information in reverse direction.

IKE mitigates the reversal curse to some extent   As shown in Table 3, IKE was also applied to five LLMs. Specifically, under the same base model, IKE's ability to recall editing facts in the forward direction was comparable to that of other methods, with a slight improvement. More importantly, when evaluating reverse knowledge, IKE consistently achieved higher RQS and RJS scores than the other methods. From these experiments, we conclude that IKE leverages ICL to help the model deeply understand the incorporated knowledge, enabling the edited model to directly and reliably generate the reverse form of the editing knowledge. However, several limitations remain for IKE. First, there is still a considerable gap between forward editing performance and reverse editing performance. In addition, it relies on prompts, does not have the ability of long-term memory, and the context window length of the model's limits its scalability. These issues further highlight the inherent complexity and challenges of the "reversal curse" in model editing, which deserves further study.

6   Analysis

6.1   Probability of Desired Outputs

Although the results in Section 5.2 indicate that the vast majority of current editing methods are almost completely invalid when evaluated in the QA form, we aim to further explore *what is the reason that causes this edited model to be ineffective in reverse*? To this end, the average log probability of the desired outputs before and after editing on LLaMA-3 (8B) on the reverse-qa prompts of BAKE-Q&J was illustrated in Figure 3. Readers can refer to Appendix D for the results of other LLMs.

Desired answer after editing   An effective editing method should increase the probability of the desired answer. The *orange* columns in Figure 3 show that the probabilities of most methods kept unchanged or even became smaller compared with the base LLaMA-3, demonstrating these methods fail to increase the probability of the desired answer. Besides, IKE was able to increase this probability, which is why it worked in the reverse direction.

Original answer after editing   An effective editing method should also reduce the probability of the original answer. As shown in the *green* columns in Figure 3, the probabilities of all methods became almost unchanged, which demonstrated the inadequacy of existing methods in reducing the probability of the original answer.

Comparison between original and desired answer after editing   For most methods, the probability of the original answer was significantly higher than that of the desired answer after editing, and the margin

Figure 3: Average log probability of the original and desired answers after editing on the reverse-qa prompts. The closer the value is to 0, the higher the probability.

between them was almost unchanged or became larger compared to the unedited LLaMA-3. This explains why most editing methods were almost ineffective in the QA form.

6.2 Collaborative Editing with In-context Learning

As demonstrated in Section 5.2, IKE exhibited a superior ability to comprehend reverse knowledge than other methods. This raised an important question: *could incorporating in-context learning into existing editing methods enhance their understanding of knowledge and further mitigate the reversal curse?* To investigate this question, several methods were applied to edit LLaMA-3 (8B), both with and without the incorporation of ICL. The detailed experimental results were presented in Figure 4. The analysis and findings are provided as follows.

The incorporating of ICL helps editing methods mitigate the reversal curse As shown in Figure 4, the introduction of in-context learning led to a significant improvement in reverse editing performance for both ROME and MEMIT. This suggests that ICL enables models to fully understand the knowledge to be edited, rather than merely memorizing it through localized parameter updates. By leveraging surrounding context, models were able to form a more comprehensive understanding of the knowledge, which in turn facilitated a deeper comprehension of the reverse information associated with it. This improvement underscores the potential of integrating context-based mechanisms into existing editing frameworks to enhance the generality of model editing.

The parameter-modifying methods compromise the ICL ability of the edited model It is worth noting that even with the incorporation of ICL, the reverse editing performance of ROME and MEMIT still lagged behind that of the IKE method. This gap is attributed to the fact that ROME and MEMIT directly modify parameters to edit knowledge, which may interfere with the model's language modeling ability and inadvertently undermine the model's ability to fully exploit contextual clues. As a result, the model struggled to accurately process and generalize the reverse information. This observation highlights the limitations of parameter-modifying methods and points to the importance of developing more flexible and context-aware methods for editing. These findings provide a valuable foundation for future research to achieve more reliable model updates.

Figure 4: Comparison of editing performance using ROME, MEMIT and WISE with and without In-context learning (ICL) on LLaMA-3 (8B), Evaluated on the BAKE-Q&J dataset.

6.3 The Analysis of IKE Output

Since the reverse editing performance of IKE was much lower than that of the forward one, to better understand its mechanism, the first 1000 samples of the BAKE-Q&J dataset was used to analyze the output of LLaMA-3 (8B) to reverse-qa questions after editing. We found that the model's output to reverse questions could be categorized into three types: (1) desired answers that reflect the editing knowledge, (2) original answers that revert to the original knowledge, and (3) answers with irrelevant information. As shown in Figure 5, nearly 50% of reverse questions were successfully answered using the editing knowledge. In the remaining cases, most failures were due to the model outputting original knowledge. However, some responses were unrelated to the questions, suggesting that ICL may interfere with the model's behavior and induce hallucinations. This underscores the challenge of conducting further research to fully address this issue.

6.4 Concept-Level Analysis of Reversal Curse

Beyond entity-level factual relations, model editing in practice often involves higher-level conceptual knowledge, such as abstract definitions or category semantics. To examine whether the reversal curse still persists under such

Figure 5: Distribution of LLaMA-3 (8B) responses to the reverse questions, after editing with IKE, based on the first 1,000 samples from the BAKE-Q&J dataset.

settings, we extend our analysis to concept-level edits. Specifically, we construct a concept-based evaluation set by transforming concept-editing instances from the ConceptEdit (Wang et al., 2024c) into the judgment-based evaluation format of BAKE-J. In the concrete construction process, we start from 902 concept-editing samples from ConceptEdit-Inter and ConceptEdit-Intra, and convert each sample into a reverse-judgment task, resulting in a total of 902 judgment-based evaluation examples. For each concept, the editing operation is formulated as a counterfactual modification of a natural-language concept definition, in which the original definition is replaced by an alternative description. All converted samples are represented using exactly the same data structure as BAKE-J, including the editing request, the reverse-judgment prompt, paraphrase prompts derived from the original concept description, and locality checks inherited from ConceptEdit. All concept-level edits are evaluated under the same judgment-only evaluation protocol as BAKE-J, enabling the analysis of conceptual reversibility within a unified evaluation framework in our study.

Table 4 reports the analysis results under the concept-level editing setting. Across all evaluated models, we observe a consistent degradation in performance on reverse-judgment prompts compared

to forward-direction metrics, to a substantial extent, indicating that the reversal curse remains prominent under conceptual edits. While most editing methods are able to successfully inject the edited conceptual definitions, their ability to correctly judge the reversed statements is substantially limited.

This trend is observed consistently across different model scales and architectures, including GPT-based and LLaMA-based models. In particular, methods that achieve strong performance on editing success and generalization still exhibit relatively low reverse-judgment scores, suggesting a persistent asymmetry between forward incorporation and reverse verification of edited conceptual knowledge.

The observed difficulty in reversing conceptual edits can be attributed to the abstract and distributed nature of conceptual knowledge. Unlike entity-level factual relations, conceptual definitions are typically encoded across broader semantic representations rather than localized associations. As a result, editing operations that successfully enforce a new definition in the forward direction may not correspondingly restructure the underlying conceptual space required for reliable reverse judgment. Furthermore, the persistent gap between forward incorporation and reverse verification suggests that current editing methods tend to prioritize surface-level consistency over bidirectional semantic coherence. While edited models may learn to reproduce the new conceptual description, they often fail to internalize the mutual exclusivity between the original and modified definitions. This indicates that achieving true reversibility at the conceptual level likely requires editing mechanisms that explicitly model semantic contrasts and relational structure, in a more principled manner, rather than relying solely on direct parameter updates.

Table 4: Analysis results under concept-level editing settings.

Model	Method	S	ES	GS	LS	RJS
GPT2-XL	FT	17.06	28.11	25.50	69.67	6.88
	MEMIT	14.49	40.82	31.37	96.11	4.78
	ROME	41.08	83.84	49.93	84.34	18.67
	RECT	46.20	87.14	58.97	85.11	21.55
GPT-J	FT	28.65	53.35	54.08	24.78	16.11
	MEMIT	28.72	99.74	57.53	94.59	9.87
	ROME	58.03	99.21	82.48	70.61	30.69
	RECT	60.70	99.39	83.11	74.55	32.88
LLaMA2-7B	FT	24.84	45.12	39.28	82.82	9.87
	MEMIT	61.59	97.02	79.80	91.74	32.04
	ROME	63.92	99.81	75.14	92.17	35.21
	RECT	65.73	99.19	77.21	93.06	36.93
LLaMA2-13B	FT	26.73	47.13	41.67	74.99	10.98
	MEMIT	60.28	94.98	77.19	92.21	31.22
	ROME	66.10	99.80	74.44	94.63	37.74
	RECT	68.62	98.94	76.87	95.12	40.55
LLaMA3-8B	FT	27.30	50.41	47.55	60.27	11.23
	MEMIT	62.99	97.54	78.42	89.01	34.17
	ROME	63.90	98.08	75.04	85.18	36.58
	RECT	67.77	98.54	76.66	85.67	41.39

7 Conclusion & Limitation

We study bidirectional language model editing to assess if edited LLMs can recall the editing knowledge bidirectionally. A metric of *reversibility* is introduced and a benchmark dubbed as BAKE is constructed. Our experiments reveal that most existing methods suffer serious deficiencies when evaluated in the reverse direction, often relying on hard-coded memorization rather than true understanding. We further analyze the causes of this phenomenon through three perspectives. Our findings indicate that while ICL can mitigate the reversal curse to some extent, it lacks continuity, is constrained by the context window length, and may lead to hallucinations. Therefore, combining the strengths of ICL with other editing methods holds promise for developing new editing paradigms. We hope our work will contribute to advancing future research in bidirectional language model editing.

There are several limitations to our work. First, although the in-context learning mechanism has shown potential in alleviating the 'reversal curse,' it still falls short of achieving robust and long-term bidirectional editing. Developing a more efficient bidirectional editing method with continuous learning capabilities and reduced hallucinations is a crucial direction for future research. Secondly, this work focuses on factual knowledge, but we have not investigated other types of learned beliefs, such as logical, spatial, or numerical knowledge. Finally, our research focuses on autoregressive models, and further exploration is needed for non-autoregressive models.

References

Jon F Apaolaza, Begoña Altuna, Aitor Soroa, and Inigo Lopez-Gazpio. Exploring the dilemma of causal incoherence: A study on the approaches and limitations of large language models in natural language inference. *Procesamiento del Lenguaje Natural*, 74:207–219, 2025.

Lukas Berglund, Meg Tong, Maximilian Kaufmann, Mikita Balesni, Asa Cooper Stickland, Tomasz Korbak, and Owain Evans. The reversal curse: Llms trained on "a is b" fail to learn "b is a". In *The Twelfth International Conference on Learning Representations*.

Baolong Bi, Shenghua Liu, Lingrui Mei, Yiwei Wang, Pengliang Ji, and Xueqi Cheng. Decoding by contrasting knowledge: Enhancing llms' confidence on edited facts. *CoRR*, abs/2405.11613, 2024. doi: 10.48550/ARXIV.2405.11613. URL https://doi.org/10.48550/arXiv.2405.11613.

Antoine Bordes, Nicolas Usunier, Alberto García-Durán, Jason Weston, and Oksana Yakhnenko. Translating embeddings for modeling multi-relational data. In Christopher J. C. Burges, Léon Bottou, Zoubin Ghahramani, and Kilian Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 26: 27th Annual Conference on Neural Information Processing Systems 2013. Proceedings of a meeting held December 5-8, 2013, Lake Tahoe, Nevada, United States*, pp. 2787–2795, 2013. URL https://dl.acm.org/doi/10.5555/2999792.2999923.

Nicola De Cao, Wilker Aziz, and Ivan Titov. Editing factual knowledge in language models. In Marie-Francine Moens, Xuanjing Huang, Lucia Specia, and Scott Wen-tau Yih (eds.), *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing, EMNLP 2021, Virtual Event / Punta Cana, Dominican Republic, 7-11 November, 2021*, pp. 6491–6506. Association for Computational Linguistics, 2021. doi: 10.18653/v1/2021.emnlp-main.522. URL https://doi.org/10.18653/v1/2021.emnlp-main.522.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Pondé de Oliveira Pinto, Jared Kaplan, Harrison Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, Alex Ray, Raul Puri, Gretchen Krueger, Michael Petrov, Heidy Khlaaf, Girish Sastry, Pamela Mishkin, Brooke Chan, Scott Gray, Nick Ryder, Mikhail Pavlov, Alethea Power, Lukasz Kaiser, Mohammad Bavarian, Clemens Winter, Philippe Tillet, Felipe Petroski Such, Dave Cummings, Matthias Plappert, Fotios Chantzis, Elizabeth Barnes, Ariel Herbert-Voss, William Hebgen Guss, Alex Nichol, Alex Paino, Nikolas Tezak, Jie Tang, Igor Babuschkin, Suchir Balaji, Shantanu Jain, William Saunders, Christopher Hesse, Andrew N. Carr, Jan Leike, Joshua Achiam, Vedant Misra, Evan Morikawa, Alec Radford, Matthew Knight, Miles Brundage, Mira Murati, Katie Mayer, Peter Welinder, Bob McGrew, Dario Amodei, Sam McCandlish, Ilya Sutskever, and Wojciech Zaremba. Evaluating large language models trained on code. *CoRR*, abs/2107.03374, 2021. URL https://arxiv.org/abs/2107.03374.

Damai Dai, Li Dong, Yaru Hao, Zhifang Sui, Baobao Chang, and Furu Wei. Knowledge neurons in pretrained transformers. In Smaranda Muresan, Preslav Nakov, and Aline Villavicencio (eds.), *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2022, Dublin, Ireland, May 22-27, 2022*, pp. 8493–8502. Association for Computational Linguistics, 2022. doi: 10.18653/v1/2022.acl-long.581. URL https://doi.org/10.18653/v1/2022.acl-long.581.

Qingxiu Dong, Damai Dai, Yifan Song, Jingjing Xu, Zhifang Sui, and Lei Li. Calibrating factual knowledge in pretrained language models. In Yoav Goldberg, Zornitsa Kozareva, and Yue Zhang (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2022, Abu Dhabi, United Arab Emirates, December 7-11, 2022*, pp. 5937–5947. Association for Computational Linguistics, 2022. doi: 10.18653/V1/2022.FINDINGS-EMNLP.438. URL https://doi.org/10.18653/v1/2022.findings-emnlp.438.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, Arun Rao, Aston Zhang, Aurélien Rodriguez, Austen Gregerson, Ava Spataru, Baptiste Rozière, Bethany Biron, Binh Tang, Bobbie Chern, Charlotte Caucheteux, Chaya Nayak, Chloe Bi, Chris Marra, Chris McConnell, Christian Keller, Christophe Touret, Chunyang Wu, Corinne Wong, Cristian Canton Ferrer, Cyrus Nikolaidis, Damien Allonsius, Daniel

Song, Danielle Pintz, Danny Livshits, David Esiobu, Dhruv Choudhary, Dhruv Mahajan, Diego Garcia-Olano, Diego Perino, Dieuwke Hupkes, Egor Lakomkin, Ehab AlBadawy, Elina Lobanova, Emily Dinan, Eric Michael Smith, Filip Radenovic, Frank Zhang, Gabriel Synnaeve, Gabrielle Lee, Georgia Lewis Anderson, Graeme Nail, Grégoire Mialon, Guan Pang, Guillem Cucurell, Hailey Nguyen, Hannah Korevaar, Hu Xu, Hugo Touvron, Iliyan Zarov, Imanol Arrieta Ibarra, Isabel M. Kloumann, Ishan Misra, Ivan Evtimov, Jade Copet, Jaewon Lee, Jan Geffert, Jana Vranes, Jason Park, Jay Mahadeokar, Jeet Shah, Jelmer van der Linde, Jennifer Billock, Jenny Hong, Jenya Lee, Jeremy Fu, Jianfeng Chi, Jianyu Huang, Jiawen Liu, Jie Wang, Jiecao Yu, Joanna Bitton, Joe Spisak, Jongsoo Park, Joseph Rocca, Joshua Johnstun, Joshua Saxe, Junteng Jia, Kalyan Vasuden Alwala, Kartikeya Upasani, Kate Plawiak, Ke Li, Kenneth Heafield, Kevin Stone, and et al. The llama 3 herd of models. *CoRR*, abs/2407.21783, 2024. doi: 10.48550/ARXIV.2407.21783. URL https://doi.org/10.48550/arXiv.2407.21783.

Junfeng Fang, Houcheng Jiang, Kun Wang, Yunshan Ma, Shi Jie, Xiang Wang, Xiangnan He, and Tat-Seng Chua. Alphaedit: Null-space constrained knowledge editing for language models. *The Thirteenth International Conference on Learning Representations, ICLR*, 2025. URL https://openreview.net/pdf?id=HvSytvg3Jh.

Roger B. Grosse, Juhan Bae, Cem Anil, Nelson Elhage, Alex Tamkin, Amirhossein Tajdini, Benoit Steiner, Dustin Li, Esin Durmus, Ethan Perez, Evan Hubinger, Kamile Lukosiute, Karina Nguyen, Nicholas Joseph, Sam McCandlish, Jared Kaplan, and Samuel R. Bowman. Studying large language model generalization with influence functions. *CoRR*, abs/2308.03296, 2023. doi: 10.48550/arXiv.2308.03296. URL https://doi.org/10.48550/arXiv.2308.03296.

Jia-Chen Gu, Hao-Xiang Xu, Jun-Yu Ma, Pan Lu, Zhen-Hua Ling, Kai-Wei Chang, and Nanyun Peng. Model editing harms general abilities of large language models: Regularization to the rescue. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing, EMNLP 2024, Miami, FL, USA, November 12-16, 2024*, pp. 16801–16819. Association for Computational Linguistics, 2024. URL https://aclanthology.org/2024.emnlp-main.934.

Qingyan Guo, Rui Wang, Junliang Guo, Xu Tan, Jiang Bian, and Yujiu Yang. Mitigating reversal curse in large language models via semantic-aware permutation training. In *Findings of the Association for Computational Linguistics ACL 2024*, pp. 11453–11464, 2024.

Tom Hartvigsen, Swami Sankaranarayanan, Hamid Palangi, Yoon Kim, and Marzyeh Ghassemi. Aging with GRACE: lifelong model editing with discrete key-value adaptors. In Alice Oh, Tristan Naumann, Amir Globerson, Kate Saenko, Moritz Hardt, and Sergey Levine (eds.), *Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023*, 2023. URL http://papers.nips.cc/paper_files/paper/2023/hash/95b6e2ff961580e03c0a662a63a71812-Abstract-Conference.html.

Zeyu Huang, Yikang Shen, Xiaofeng Zhang, Jie Zhou, Wenge Rong, and Zhang Xiong. Transformer-patcher: One mistake worth one neuron. In *The Eleventh International Conference on Learning Representations, ICLR 2023, Kigali, Rwanda, May 1-5, 2023*. OpenReview.net, 2023. URL https://openreview.net/forum?id=4oYUGeGBPm.

Ziwei Ji, Nayeon Lee, Rita Frieske, Tiezheng Yu, Dan Su, Yan Xu, Etsuko Ishii, Yejin Bang, Andrea Madotto, and Pascale Fung. Survey of hallucination in natural language generation. *ACM Comput. Surv.*, 55(12): 248:1–248:38, 2023. doi: 10.1145/3571730. URL https://doi.org/10.1145/3571730.

Omer Levy, Minjoon Seo, Eunsol Choi, and Luke Zettlemoyer. Zero-shot relation extraction via reading comprehension. In Roger Levy and Lucia Specia (eds.), *Proceedings of the 21st Conference on Computational Natural Language Learning (CoNLL 2017), Vancouver, Canada, August 3-4, 2017*, pp. 333–342. Association for Computational Linguistics, 2017. doi: 10.18653/v1/K17-1034. URL https://doi.org/10.18653/v1/K17-1034.

Zhicong Lu, Li Jin, Peiguang Li, Yu Tian, Linhao Zhang, Sirui Wang, Guangluan Xu, Changyuan Tian, and Xunliang Cai. Rethinking the reversal curse of llms: a prescription from human knowledge reversal. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 7518–7530, 2024.

Ang Lv, Kaiyi Zhang, Shufang Xie, Quan Tu, Yuhan Chen, Ji-Rong Wen, and Rui Yan. Are we falling in a middle-intelligence trap? an analysis and mitigation of the reversal curse. *arXiv preprint arXiv:2311.07468*, 2023.

Jun-Yu Ma, Hong Wang, Hao-Xiang Xu, Zhen-Hua Ling, and Jia-Chen Gu. Perturbation-restrained sequential model editing. *The Thirteenth International Conference on Learning Representations, ICLR*, 2025. URL https://openreview.net/pdf?id=bfI8cp8qmk.

Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. Locating and editing factual associations in GPT. In *NeurIPS*, 2022. URL https://arxiv.org/abs/2202.05262.

Kevin Meng, Arnab Sen Sharma, Alex J. Andonian, Yonatan Belinkov, and David Bau. Mass-editing memory in a transformer. In *The Eleventh International Conference on Learning Representations, ICLR 2023, Kigali, Rwanda, May 1-5, 2023*. OpenReview.net, 2023. URL https://openreview.net/pdf?id=MkbcAHIYgyS.

Eric Mitchell, Charles Lin, Antoine Bosselut, Chelsea Finn, and Christopher D. Manning. Fast model editing at scale. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*. OpenReview.net, 2022a. URL https://openreview.net/forum?id=0DcZxeWfOPt.

Eric Mitchell, Charles Lin, Antoine Bosselut, Christopher D. Manning, and Chelsea Finn. Memory-based model editing at scale. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvári, Gang Niu, and Sivan Sabato (eds.), *International Conference on Machine Learning, ICML 2022, 17-23 July 2022, Baltimore, Maryland, USA*, volume 162 of *Proceedings of Machine Learning Research*, pp. 15817–15831. PMLR, 2022b. URL https://proceedings.mlr.press/v162/mitchell22a.html.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul F. Christiano, Jan Leike, and Ryan Lowe. Training language models to follow instructions with human feedback. In *NeurIPS*, 2022. URL https://arxiv.org/abs/2203.02155.

Baolin Peng, Michel Galley, Pengcheng He, Hao Cheng, Yujia Xie, Yu Hu, Qiuyuan Huang, Lars Liden, Zhou Yu, Weizhu Chen, and Jianfeng Gao. Check your facts and try again: Improving large language models with external knowledge and automated feedback. *CoRR*, abs/2302.12813, 2023. doi: 10.48550/arXiv.2302.12813. URL https://doi.org/10.48550/arXiv.2302.12813.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

Roy Schwartz, Jesse Dodge, Noah A. Smith, and Oren Etzioni. Green AI. *Commun. ACM*, 63(12):54–63, 2020. doi: 10.1145/3381831. URL https://doi.org/10.1145/3381831.

Anton Sinitsin, Vsevolod Plokhotnyuk, Dmitry V. Pyrkin, Sergei Popov, and Artem Babenko. Editable neural networks. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=HJedXaEtvS.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton-Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy

Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, et al. Llama 2: Open foundation and fine-tuned chat models. *CoRR*, abs/2307.09288, 2023. doi: 10.48550/arXiv.2307.09288. URL https://doi.org/10.48550/arXiv.2307.09288.

Denny Vrandecic and Markus Krötzsch. Wikidata: a free collaborative knowledgebase. *Commun. ACM*, 57 (10):78–85, 2014. doi: 10.1145/2629489. URL https://doi.org/10.1145/2629489.

Ben Wang and Aran Komatsuzaki. Gpt-j-6b: A 6 billion parameter autoregressive language model, 2021.

Peng Wang, Zexi Li, Ningyu Zhang, Ziwen Xu, Yunzhi Yao, Yong Jiang, Pengjun Xie, Fei Huang, and Huajun Chen. WISE: rethinking the knowledge memory for lifelong model editing of large language models. In Amir Globersons, Lester Mackey, Danielle Belgrave, Angela Fan, Ulrich Paquet, Jakub M. Tomczak, and Cheng Zhang (eds.), *Advances in Neural Information Processing Systems 38: Annual Conference on Neural Information Processing Systems 2024, NeurIPS 2024, Vancouver, BC, Canada, December 10 - 15, 2024*, 2024a. URL http://papers.nips.cc/paper_files/paper/2024/hash/60960ad78868fce5c165295fbd895060-Abstract-Conference.html.

Peng Wang, Ningyu Zhang, Bozhong Tian, Zekun Xi, Yunzhi Yao, Ziwen Xu, Mengru Wang, Shengyu Mao, Xiaohan Wang, Siyuan Cheng, et al. Easyedit: An easy-to-use knowledge editing framework for large language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 3: System Demonstrations)*, pp. 82–93, 2024b.

Xiaohan Wang, Shengyu Mao, Shumin Deng, Yunzhi Yao, Yue Shen, Lei Liang, Jinjie Gu, Huajun Chen, and Ningyu Zhang. Editing conceptual knowledge for large language models. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2024, Miami, Florida, USA, November 12-16, 2024*, pp. 706–724. Association for Computational Linguistics, 2024c. doi: 10.18653/V1/2024.FINDINGS-EMNLP.40. URL https://doi.org/10.18653/v1/2024.findings-emnlp.40.

Hao-Xiang Xu, Jun-Yu Ma, Zhen-Hua Ling, Ningyu Zhang, and Jia-Chen Gu. Constraining sequential model editing with editing anchor compression. In *Findings of the Association for Computational Linguistics: NAACL 2025*, pp. 5499–5515, 2025.

Jingjing Xu, Wangchunshu Zhou, Zhiyi Fu, Hao Zhou, and Lei Li. A survey on green deep learning. *CoRR*, abs/2111.05193, 2021. URL https://arxiv.org/abs/2111.05193.

Yunzhi Yao, Peng Wang, Bozhong Tian, Siyuan Cheng, Zhoubo Li, Shumin Deng, Huajun Chen, and Ningyu Zhang. Editing large language models: Problems, methods, and opportunities. In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, EMNLP 2023, Singapore, December 6-10, 2023*, pp. 10222–10240. Association for Computational Linguistics, 2023. URL https://aclanthology.org/2023.emnlp-main.632.

Biao Zhang, Barry Haddow, and Alexandra Birch. Prompting large language model for machine translation: A case study. In Andreas Krause, Emma Brunskill, Kyunghyun Cho, Barbara Engelhardt, Sivan Sabato, and Jonathan Scarlett (eds.), *International Conference on Machine Learning, ICML 2023, 23-29 July 2023, Honolulu, Hawaii, USA*, volume 202 of *Proceedings of Machine Learning Research*, pp. 41092–41110. PMLR, 2023a. URL https://proceedings.mlr.press/v202/zhang23m.html.

Ningyu Zhang, Bozhong Tian, Siyuan Cheng, Xiaozhuan Liang, Yi Hu, Kouying Xue, Yanjie Gou, Xi Chen, and Huajun Chen. Instructedit: Instruction-based knowledge editing for large language models. In *Proceedings of the Thirty-Third International Joint Conference on Artificial Intelligence, IJCAI 2024, Jeju, South Korea, August 3-9, 2024*, pp. 6633–6641. ijcai.org, 2024. URL https://www.ijcai.org/proceedings/2024/733.

Yue Zhang, Yafu Li, Leyang Cui, Deng Cai, Lemao Liu, Tingchen Fu, Xinting Huang, Enbo Zhao, Yu Zhang, Yulong Chen, Longyue Wang, Anh Tuan Luu, Wei Bi, Freda Shi, and Shuming Shi. Siren's song in the AI ocean: A survey on hallucination in large language models. *CoRR*, abs/2309.01219, 2023b. doi: 10.48550/arXiv.2309.01219. URL https://doi.org/10.48550/arXiv.2309.01219.

Ce Zheng, Lei Li, Qingxiu Dong, Yuxuan Fan, Zhiyong Wu, Jingjing Xu, and Baobao Chang. Can we edit factual knowledge by in-context learning? In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, EMNLP 2023, Singapore, December 6-10, 2023*, pp. 4862–4876. Association for Computational Linguistics, 2023. doi: 10.18653/V1/2023.EMNLP-MAIN.296. URL `https://doi.org/10.18653/v1/2023.emnlp-main.296`.

Zexuan Zhong, Zhengxuan Wu, Christopher D. Manning, Christopher Potts, and Danqi Chen. Mquake: Assessing knowledge editing in language models via multi-hop questions. In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, EMNLP 2023, Singapore, December 6-10, 2023*, pp. 15686–15702. Association for Computational Linguistics, 2023. URL `https://aclanthology.org/2023.emnlp-main.971`.

Chen Zhu, Ankit Singh Rawat, Manzil Zaheer, Srinadh Bhojanapalli, Daliang Li, Felix X. Yu, and Sanjiv Kumar. Modifying memories in transformer models. *CoRR*, abs/2012.00363, 2020. URL `https://arxiv.org/abs/2012.00363`.

A Bidirectional Templates

Table 5 shows some examples of templates.

Table 5: The templates $T(r)$ for relation r and the $T(r^{-1})$ for its inverse relation r^{-1}. Actually, there are several templates for each relation in both directions. Here we only display one template for each relation.

Relation (r)	$T(r)$	$T(r^{-1})$
capital	"The capital of {} is"	"{} is the capital of"
chief executive officer	"The chief executive officer of {} is"	"{} is the chief executive officer of"
founded	"{}, who has founded"	"The {} has been founded by"
currency	"{}, which has the currency"	"The {} is the currency utilized in"

B Dataset Statistics

Table 6 summarizes the statistics of the BAKE-Q&J and BAKE-J datasets.

Table 6: The statistics of both BAKE-Q&J and BAKE-J.

Type	$Num_{BAKE-Q\&J}$	Num_{BAKE-J}
Editing examples	4,694	3,184
Relations	25	20
Paraphrase prompts	8,811	5,917
Locality prompts	16,378	23,770
Reverse-qa prompts	4,694	-
Reverse-judge prompts	4,694	3,184

C Experimental Setup

C.1 Baseline Models

Nine popular model editing methods were selected as baselines including:

- **FT** (Zhu et al., 2020): this method simply performed gradient descent on the edits to update model parameters. It fine-tuned one layer in the model with a norm constraint on weight changes to prevent forgetfulness. Since the original authors did not publish their code, we followed Meng et al. (2022) re-implementation in their study.

- **MEND** (Mitchell et al., 2022a)[5]: it learned a hypernetwork to produce weight updates by decomposing the fine-tuning gradients into rank-1 form.

- **MEMIT** (Meng et al., 2023)[6]: it extended ROME to edit a large set of facts and updated a sequence of MLP layers to update knowledge.

- **ROME** (Meng et al., 2022)[7]: it first localized the factual knowledge at a specific layer in the transformer MLP modules, and then updated the knowledge by directly writing new key-value pairs in the MLP module.

- **RECT** (Gu et al., 2024)[8]: it is designed to reduce the unintended side effects of model editing on the general capabilities of large language models (LLMs). While editing can enhance factual accuracy,

---

[5]https://github.com/eric-mitchell/mend
[6]https://github.com/kmeng01/memit
[7]https://github.com/kmeng01/rome
[8]https://github.com/JasonForJoy/Model-Editing-Hurt

it often harms performance on tasks such as reasoning and question answering. RECT tackles this problem by regularizing weight updates during the editing process, thereby limiting excessive changes that may cause overfitting. As a result, RECT achieves strong editing performance while preserving the model's overall abilities.

- **AlphaEdit** (Fang et al., 2025)[9]: It mitigates catastrophic forgetting during model editing by preserving previously learned knowledge, and extends this capability to a lifelong editing setting through a null-space projection strategy. This approach ensures that new edits do not interfere with prior information by projecting updates into directions that minimally affect existing representations, thereby maintaining model stability across a long sequence of edits.

- **GRACE** (Hartvigsen et al., 2023)[10]: it introduces a lifelong model editing framework that leverages a local codebook in the latent space to support thousands of sequential edits without compromising overall model performance. It enables precise modifications while maintaining generalization, and achieves strong results on T5, BERT, and GPT in terms of edit retention and generalization.

- **WISE** (Wang et al., 2024a)[11]: it integrates a parameterized memory module to enable efficient merging of new and existing knowledge within the model. This mechanism allows the model to retain prior information while seamlessly incorporating updated facts, reducing the risk of interference and improving the stability of edits over time.

- **IKE** (Zheng et al., 2023)[12]: it achieves parameter-free model editing through in-context learning, allowing the model to incorporate knowledge updates during inference without making any changes to its underlying parameters.

The ability of these methods were assessed based on EasyEdit (Wang et al., 2024b), an easy-to-use knowledge editing framework which integrates the released codes and hyperparameters from previous methods.

Figure 6: Average log probability of the original and desired answers after editing on the reverse-qa prompts on GPT-2 XL (1.5B). The closer the value is to 0, the higher the probability.

---

[9]https://github.com/ jianghoucheng/AlphaEdit
[10]https://github.com/thartvigsen/grace
[11]https://github.com/zjunlp/EasyEdit
[12]https:// github.com/PKUnlp-icler/IKE

Figure 7: Average log probability of the original and desired answers after editing on GPT-J (6B).

Figure 8: Average log probability of the original and desired answers after editing on LLaMA-2 (7B).

C.2 Experiments Compute Resources

We used NVIDIA A800 80GB GPU for experiments. For LLaMA-2 (7B), it occupies about 40+GB memory to edit MEND, ROME, MEMIT, and BIRD. It occupies 60GB for FT. For the time costs of 1000 edits, MEND and FT are about 1 hour, ROME and MEMIT are about 6 hours, BIRD is about 8 hours. The costs of LLaMA-1 (7B) is similar with LLaMA-2 (7B). The time cost of GPT-J (6B) is 40% higher than LLaMA-2 (7B). The memory and time cost of GPT-2 XL (1.5B) is approximately 30% that of LLaMA-2 (7B).

D   Log Probability for LLMs

Figure 3 depicts the log probability of the original and desired answers after editing on LLaMA-3 (8B). Figure 6, 7, and 8 show the log probability of other LLMs: GPT-2 XL (1.5B), GPT-J (6B), LLaMA-2 (7B) respectively.

E   Broader Impact

The research centers on a pivotal facet of LLMs: mitigating hallucinations through model editing, which aim to facilitate better human-AI interactions and contribute to the development of safer and more responsible AI technologies. This not only enhances the scientific community's comprehension of the strengths and limitations inherent in existing editing methods but also brings to light the challenges associated with the reversal curse in language model editing. The acquired insights from our research contribute to the current understanding and serve as a catalyst for future investigations into bidirectional relationships within language models. Furthermore, our work highlights the importance of responsible and transparent approaches, encouraging researchers to actively contribute to the ongoing discourse on responsible AI. This emphasis is pivotal in enhancing the overall reliability and trustworthiness of language models in real-world applications.

Despite these advancements, there are potential negative societal impacts to consider. The ability to edit LLMs bidirectionally could be misused to propagate disinformation more effectively. For example, malicious actors could exploit this technology to create AI systems that recall and reinforce false narratives or biased information in a way that appears more coherent and credible. This capability might amplify the spread of fake news or disinformation campaigns, posing significant risks to public opinion and democratic processes.

To mitigate these risks, several strategies can be implemented. First, strict access controls and auditing mechanisms should be established to monitor the use of bidirectional editing tools. Second, developers could integrate robust mechanisms to detect and prevent the propagation of disinformation, such as incorporating fact-checking algorithms and promoting transparency in AI outputs. Lastly, continuous monitoring and regular updates of the models should be enforced to ensure they do not harbor outdated or harmful information. These measures can help balance the innovative potential of bidirectional model editing with the need to safeguard societal well-being and ethical standards.