The Disagreement Problem in Explainable Machine Learning: A Practitioner's Perspective

Abstract

As various post hoc explanation methods are increasingly being leveraged to explain complex models in high-stakes settings, it becomes critical to develop a deeper understanding of if and when the explanations output by these methods disagree with each other, and how such disagreements are resolved in practice. However, there is little to no research that provides answers to these critical questions. In this work, we introduce and study the disagreement problem in explainable machine learning. More specifically, we formalize the notion of disagreement between explanations, analyze how often such disagreements occur in practice, and how practitioners resolve these disagreements. We first conduct interviews with data scientists to understand what constitutes disagreement between explanations generated by different methods for the same model prediction and introduce a novel quantitative framework to formalize this understanding. We then leverage this framework to carry out a rigorous empirical analysis with four real-world datasets, six state-of-the-art post hoc explanation methods, and eight different predictive models, to measure the extent of disagreement between the explanations generated by various popular explanation methods. In addition, we carry out an online user study with data scientists to understand how they resolve the aforementioned disagreements. Our results indicate that (1) state-of-the-art explanation methods often disagree in terms of the explanations they output, and (2) machine learning practitioners often employ ad hoc heuristics when resolving such disagreements. These findings suggest that practitioners may be relying on misleading explanations when making consequential decisions. They also underscore the importance of developing principled frameworks for effectively evaluating and comparing explanations output by various state-of-the-art methods.

1 Introduction

As machine learning (ML) models become integral in high-stakes domains like healthcare and finance, the interpretability of these models is crucial for ML practitioners and domain experts (e.g., doctors, policymakers). Understanding model behavior is essential to identify errors and biases and gauge the reliability of model predictions, especially in complex models Doshi-Velez & Kim (2017). Several post hoc explanation methods have been proposed such as perturbation-based methods (e.g., LIME Ribeiro et al. (2016b), SHAP Lundberg & Lee (2017)) and gradient-based methods (e.g., Gradient times Input Simonyan et al. (2014), SmoothGrad Smilkov et al. (2017), Integrated Gradients Sundararajan et al. (2017), GradCAM Selvaraju et al. (2017)).

Prior research has investigated various aspects of explanation methods. For example, metrics have been developed to assess the faithfulness of explanations to the model's behavior, such as comparing them to a model's ground truth feature importances or using the "Remove and Retrain" (ROAR) approach Liu et al. (2021); Hooker et al. (2018). However, challenges arise due to the unavailability of ground truth in real-world applications and the impracticality of retraining models in certain settings Zhou et al. (2021). Studies have shown that popular explanation methods can produce inconsistent or misleading explanations, leading to risks like deploying biased models or making erroneous clinical decisions Aivodji et al. (2019); Slack et al. (2020).

However, while prior research has studied explanation methods, the (dis)agreement among different methods has not been extensively investigated. Practitioners often use multiple methods, but these can yield conflicting explanations. Therefore, resolving these disagreements is crucial to avoid reliance on misleading explanations with potentially severe consequences Slack et al. (2020). Yet, there is a lack of research on the extent to which explanations disagree and how practitioners resolve these disagreements.

In this work, we introduce and investigate the *disagreement problem* in explainable ML, a novel area of research that examines conflicts among post hoc explanation methods. We present the following key contributions:

1. We conduct semi-structured interviews with 25 data scientists, gaining insights on the nature and frequency of explanation disagreements in their workflows. This input helps us define what constitutes an explanation disagreement in practical scenarios[1].

2. Building on these insights, we formalize the concept of explanation disagreement and create a new evaluation framework to quantitatively assess disagreements between pairs of explanations for the same model prediction.

3. We apply this framework in an extensive empirical analysis, measuring disagreement levels across four real-world datasets, three data modalities, six advanced explanation methods, and various predictive models, including logistic regression, tree-based models, and various neural networks.

4. Finally, we conduct an online user study with another set of 25 data scientists. We present them with pairs of conflicting explanations, assessing which they would rely on and their rationale. We also gather insights on their strategies for resolving such disagreements in their daily work.

Our findings reveal that explanation disagreements are common and problematic: 84% of interviewees reported encountering disagreements in their practice. The empirical analysis confirms widespread discrepancies across different methods and data modalities (tabular, text, and image). Moreover, 86% of user study participants admitted to using arbitrary heuristics or being uncertain about resolving these disagreements. This highlights the need for better evaluation metrics and enhanced practitioner understanding of the underlying principles of explanation methods.

2 Related Work

Our work is grounded in the extensive literature on explainable ML which we discuss in this section.

Inherently Interpretable Models and Post Hoc Explanations. A variety of approaches have been developed to learn inherently interpretable models for tasks such as classification and clustering Letham et al. (2015); Lakkaraju et al. (2016); Bien & Tibshirani (2009); Kim et al. (2014); Lou et al. (2012); Caruana et al. (2015). However, complex models like deep neural networks often outperform these simpler models in terms of accuracy Ribeiro et al. (2016b). This has led to significant interest in post hoc explanations, which aim to understand the behavior of these complex models. Techniques like LIME, SHAP, Anchors, BayesLIME and BayesSHAP Ribeiro et al. (2016a); Lundberg & Lee (2017); Slack et al. (2021); Ribeiro et al. (2018) are perturbation-based local explanation methods, while methods such as Gradient times Input, SmoothGrad, Integrated Gradients and GradCAM Simonyan et al. (2014); Sundararajan et al. (2017); Selvaraju et al. (2017); Smilkov et al. (2017) are gradient-based local explanations. Global explanations, on the other hand, aim to summarize the behavior of black box models as a whole Bastani et al. (2017); Lakkaraju et al. (2019). Our work is focused on analyzing the disagreements among explanations generated by these local post hoc explanation methods.

Analyzing and Evaluating Post hoc Explanations. Prior research has proposed several notions of explanation quality, such as faithfulness, stability, consistency, and sparsity Liu et al. (2021); Petsiuk et al. (2018); Slack et al. (2021); Zhou et al. (2021). Metrics have also been proposed to quantify these aspects of

---

[1]All the user interviews and studies in this work were approved by our institution's IRB.

explanation quality Zhou et al. (2021); Carvalho et al. (2019); Gilpin et al. (2018); Liu et al. (2021). These properties and metrics have been leveraged to theoretically and empirically analyze the behavior of popular post hoc explanations Ghorbani et al. (2019); Slack et al. (2020); Dombrowski et al. (2019); Adebayo et al. (2018); Alvarez-Melis & Jaakkola (2018); Levine et al. (2019); Chalasani et al. (2020); Agarwal et al. (2021). However, our work is the first to highlight and study the critical issue of disagreement in explainable machine learning. This research has also inspired subsequent works that delve deeper into this topic Han et al. (2022); Banegas-Luna et al. (2023). For instance, Han et al. (2022) built on this work and theoretically analyzed multiple state-of-the-art explanation methods to understand the reasons behind their disagreements.

Human Factors in Explainability. Many user studies have been conducted to evaluate how well humans can understand and use explanations Doshi-Velez & Kim (2017). Some of these studies have shown that data scientists often struggle to understand and effectively leverage state-of-the-art explanation techniques Kaur et al. (2020). Others have identified a variety of stakeholders across the model life cycle and highlighted the core goals of model explanations Hong et al. (2020); Chen et al. (2022). Prior works have also examined whether explanations help users in performing specific tasks Buçinca et al. (2021); Bansal et al. (2021); Fan et al. (2022); Sperrle et al. (2021); Chen et al. (2022); Vasconcelos et al. (2023); Fok & Weld (2023). However, none of these works focus on understanding the disagreement problem, the extent to which practitioners face it and/or how they resolve it.

3 Understanding and Measuring Disagreement Between Model Explanations

In this section, we discuss practitioner perspectives on what constitutes disagreement between two explanations and then formalize the notion of explanation disagreement. To this end, we first describe the study that we carry out with data scientists to understand what constitutes explanation disagreement, and the extent to which they encounter this problem in practice. We then discuss the insights from this study and leverage these insights to propose a novel framework that can quantitatively measure the disagreement between any two explanations.

3.1 Characterizing Explanation Disagreement Using Practitioner Inputs

Here, we describe the interviews we conducted with data scientists to characterize explanation disagreement and outline findings and insights from these interviews.

3.1.1 Interviews with Data Scientists

We conducted 30-minute semi-structured interviews with 25 data scientists who employ explainability techniques to understand model behavior and explain it to their customers and managers. We recruited these participants by emailing the explainable machine learning groups (and relevant mailing lists) in three different for-profit companies in the technology and financial services sectors across the United States. We conducted basic checks (e.g., pre-screening interviews and profile checks) to ensure that each recruited participant has at least one year of experience as a data scientist, and has working knowledge of data science and machine learning.

Furthermore, all of these data scientists used state-of-the-art local post hoc explanation methods (e.g., LIME, SHAP, and gradient-based methods) in their day-to-day workflow. 19 participants (76%) were male, and 6 (24%) were female. 16 participants (64%) had more than 2 years of experience working with explainability techniques, and the remaining 9 (36%) had about 8 to 12 months of experience. Our interviews included, but were not limited to the following questions: Q1) *How often do you use multiple explanation methods to understand the same model prediction?* Q2) *What constitutes disagreement between two explanations that explain the same model prediction?* Q3) *How often do you encounter disagreements between explanations output by different methods for the same model prediction?*

3.1.2   Findings and Insights

The interviews revealed how data scientists use explanation methods and their perspectives on what constitutes disagreement among explanations. 22 out of the 25 participants (88%) said that they almost always use multiple explanation methods to understand the same model prediction. Furthermore, 21 out of the 25 participants (84%) mentioned that they have often run into some form of disagreement between explanations generated by different methods for the same prediction. We found that data scientists consider explanations to disagree when:

Top features are different: Most popular post hoc explanation methods return feature importance values for each feature. These values indicate which features contribute most (either positively or negatively) to the prediction, i.e., top features. 21 out of the 25 participants (84%) mentioned that such a set of top features is *"the most critical piece of information"* that they rely on in their day-to-day workflow. They also noted that they typically look at the top 5 to 10 features provided by an explanation for each prediction. When two explanations have different sets of top features, they consider it to be a disagreement.

Ordering among top features is different: 18 out of 25 participants (72%) indicated that they also consider the ordering among the top features very carefully in their workflow. Therefore, they consider a mismatch in the ordering of the top features provided by two different explanations to be a disagreement.

Direction of top feature contributions is different: 19 out of 25 participants (76%) mentioned that the *sign* or *direction* of the feature contribution (i.e., whether the feature contributes positively or negatively to the prediction) is another critical piece of information. Any mismatch in the signs of the top features between two explanations is a sign of disagreement. As one participant remarked: *"I saw an explanation indicating that a top feature bankruptcy contributes positively to a particular loan denial, and another explanation saying that it contributes negatively. That is a clear disagreement. The model prediction can be trusted with the former explanation, but not with the latter."*.

Relative ordering of features of interest is different: 16 of our study participants (64%) indicated that they also look at relative ordering between certain features of interest, and that, they consider explanations to disagree if explanations provide contradicting information about this aspect. As one participant remarked: *"I often check if salary is more important than credit score in loan approvals. If one explanation says salary is more important than credit score, and another says credit score is more important than salary; then it is a disagreement."*

A striking finding from our study is that participants characterize explanation disagreement based on factors such as mismatch in top features, feature ordering, directions of feature contributions, and relative feature ordering, but not on the feature importance values output by different explanation methods. 24 out of 25 participants (96%) opine that feature importance values output by different explanation methods are not directly comparable. For example, they note that while LIME outputs coefficients of a linear model as feature importance values, SHAP outputs Shapley values as feature attributions which sum to the probability of the predicted class. Thus, data scientists do not try to base explanation disagreement on these numbers not being equal or similar. One of our participants succinctly summarized practitioners' perspective on this explanation disagreement problem: *"The values generated by different explanation methods are clearly different. So, I would not characterize disagreement based on that. But, I would at least want the explanations they output to give me consistent insights. The explanations should agree on what are the most important features, the ordering among them and so on for me to derive consistent insights. But, they don't!"*

3.2   Formalizing the Notion of Explanation Disagreement

Our study indicates that ML practitioners consider the following key aspects when they think about explanation disagreement: a) the extent to which explanations differ in the top-k features, the signs of these top-k features, and the ordering of these top-k features, and b) the extent to which explanations differ in the relative ordering of certain features of interest. To capture these intuitions about explanation disagreement,

we propose six different metrics: *feature agreement*, *rank agreement*, *sign agreement*, *signed rank agreement*, *rank correlation*, and *pairwise rank agreement*. The first four metrics capture disagreement with respect to the top-k features of the explanations and the last two metrics capture disagreement with respect to a selected set of features that could be provided as input by an end user. For all six metrics, lower values indicate stronger disagreement. See Section A for formal definitions.

3.2.1 Measuring Disagreement With Respect to Top-k Features

We now define four metrics, which capture specific aspects of explanation disagreement with respect to the top-k features.[2]

Feature Agreement: ML practitioners in interviews (Section 3.1) clearly indicated that a key notion of disagreement between a pair of explanations is that they output different top-k features. To capture this notion, feature agreement computes the fraction of common features between the sets of top-k features of two explanations.

Rank Agreement: Practitioners also indicated that if the ordering of the top-k features is different for two explanations (even if the feature sets are the same), then they consider it to be a disagreement. To capture this notion, rank agreement computes the fraction of features that are not only common between the sets of top-k features of two explanations, but also have the same position in the respective rank orders. Rank agreement is a stricter metric than feature agreement since it also considers the ordering of the top-k features.

Sign Agreement: In our study, practitioners also mentioned that they consider two explanations to disagree if the feature attribution signs (i.e. directions of feature contribution) do not align for the top-k features. To capture this notion, sign agreement computes the fraction of features that are not only common between the sets of top-k features of two explanations, but also share the same sign in both explanations. Sign agreement is a stricter metric than feature agreement since it also considers signs of the top-k features.

Signed Rank Agreement: This metric fuses the above three notions of explanation disagreement, and computes the fraction of features that are not only common between the sets of top-k features of two explanations, but also share the same feature attribution sign and rank in both explanations. Signed rank agreement is the strictest compared to all the aforementioned metrics since it considers both the ordering and the signs of the top-k features.

3.2.2 Measuring Disagreement With Respect to Features of Interest

Practitioners also indicated that they consider two explanations to be different if the relative ordering of features of interest (e.g., salary and credit score discussed in Section 3.1) differ between the explanations. To formalize this notion, we introduce the two metrics below.

Rank Correlation: In practice, this selected set of features corresponds to features that are of interest to end users and can be provided as input by end users. Rank correlation computes the Spearman's rank correlation coefficient between feature rankings provided by two explanations for these selected set of features.

Pairwise Rank Agreement: Pairwise rank agreement takes as input a set of features that are of interest to the user and computes the fraction of feature pairs for which the relative ordering is the same between two explanation.

4 Empirical Analysis of Explanation Disagreement

We leverage the metrics outlined in Section 3 and carry out a comprehensive empirical analysis with six state-of-the-art explanation methods and four real-world datasets spanning three data modalities to study

---

[2]The top-k features of an explanation are typically computed only based on the magnitude of the feature importance values and not the signs.

the explanation disagreement problem. In this section, we describe the datasets, experimental setup, and key findings.

4.1 Datasets

To carry out our empirical analysis, we use four datasets spanning three data modalities (tabular, text, and image). For **tabular** data, we use the Correctional Offender Management Profiling for Alternative Sanctions (COMPAS) ProPublica and German Credit datasets Repository. The COMPAS dataset comprises seven features on the demographics, criminal history, and prison time of 4,937 defendants. Each defendant is classified as either low or high risk for recidivism based on the COMPAS algorithm's risk score. The German Credit dataset contains twenty features on the demographics, credit history, bank account balance, loan information, and employment information of 1,000 loan applicants. Each applicant is classified as either low or high risk for defaulting on a loan. For **text** data, we use Antonio Gulli (AG)'s corpus of news articles (AG_News) ag (2005). It contains 127,600 sentences (collected from 1,000,000+ articles from 2,000+ sources with a vocabulary size of 95,000+ words). The class label is the topic of the article from which a sentence was obtained (World, Sports, Business, or Science/Technology). For **image** data, we use the ImageNet$-1k$ Russakovsky et al. (2015); ima (2015) object recognition dataset. It contains 1,381,167 images belonging to 1000 categories. We obtain segmentation maps from PASCAL VOC 2012 voc (2012) that are directly used as super-pixels for the explanation methods.

4.2 Experimental Setup

We train a variety of black box models. For tabular data, we train four models: logistic regression, densely-connected feed-forward neural network, random forest, and gradient-boosted tree. For text data, we train a widely-used vanilla LSTM-based text classifier on AG_News Zhang et al. (2015) corpus. For image data, we use the pre-trained ResNet-18 He et al. (2016) for ImageNet.

Next, we apply six state-of-the-art post hoc explanation methods to explain the black box models' predictions for a set of test data points. We apply two perturbation-based explanation methods (LIME Ribeiro et al. (2016b) and KernelShap Lundberg & Lee (2017)), and four gradient-based explanation methods (Vanilla Gradient Simonyan et al. (2014), Gradient times Input Shrikumar et al. (2017), Integrated Gradients Sundararajan et al. (2017), and SmoothGrad Smilkov et al. (2017)). For explanation methods with a sample size hyper-parameter, we either run the explanation method to convergence (i.e., select a sample size such that an increase in the number of samples does not significantly change the explanations) or use a sample size that is much higher than the sample size recommended by previous work.

We then evaluate the (dis)agreement between the explanation methods using the metrics described in Section 3.2. For tabular and text data, we apply rank correlation and pairwise rank agreement across all features; and feature agreement, rank agreement, sign agreement, signed rank agreement across top-k features for varying values of k. For image data, metrics that operate on the top-k features are more applicable to super-pixels. Thus, we apply the six disagreement metrics on explanations output by LIME and KernelSHAP (which leverage super pixels), and calculate rank correlation (across all pixels as features) between the explanations output by gradient-based methods. Additional details are described in Appendix B.

4.3 Results and Insights

We discuss the results of our empirical analysis for each of the three data modalities.

4.3.1 Tabular Data

Figure 1 shows the disagreement between various pairs of explanation methods for the neural network model trained on the COMPAS dataset. We computed the six metrics outlined in Section 3.2 using $k = 5$ (out of 7 features) for metrics that focus on top-k features. Each cell in the heatmap shows the metric value averaged over the test data points for each pair of explanation methods with lighter colors indicating stronger disagreement. We see that explanation methods tend to exhibit slightly higher values on pairwise rank

Figure 1: Disagreement between explanation methods for neural network model trained on COMPAS dataset measured by six metrics: rank correlation and pairwise rank agreement across all features, and feature, rank, sign, and signed rank agreement across top $k = 5$ features. Heatmaps show the average metric value over test set data points for each pair of explanation methods, with lower values (lighter colors) indicating stronger disagreement. The disagreement between a pair of explanations is considered non-trivial if less than 75% of features agree (i.e., if feature agreement, rank agreement, sign agreement, signed rank agreement, or pairwise rank agreement is less than 0.75), or if the correlation among features is only moderately positive, nonexistent, or negative (i.e., if rank correlation is less than 0.50). Across all six heatmaps, the standard error ranges between 0 and 0.01.

agreement and feature agreement metrics, and relatively lower values on other metrics (indicating stronger disagreement).

We next study the effect of the number of top features on the degree of disagreement. Figure 2 shows the disagreement of explanation methods for the neural network model trained on the COMPAS dataset. We computed rank agreement (top row) and signed rank agreement (bottom row) at top-k features for increasing values of k. We see that as the number of top-k features increases, rank agreement and signed rank agreement decrease. This indicates that, as k increases, top-k features of a pair of explanation methods are less likely to contain shared features with the same rank (as measured by rank agreement) or shared features with the same rank and sign (as measured by signed rank agreement). These patterns are consistent across other models trained on the COMPAS dataset. See Appendix C.1.

In addition, across metrics, values of k, and models, the specific explanation method pairs of Vanilla Gradient-SmoothGrad and Gradient times Input-Integrated Gradients exhibit strong agreement while the pairs of Vanilla Gradient-Integrated Gradients, Vanilla Gradient-Gradient times Input, SmoothGrad-Gradient times Input and SmoothGrad-Integrated Gradients consistently exhibit stronger disagreement. These results are consistent with the theoretical findings indicating that certain pairs of explanation methods are more consistent with one another than other pairs Han et al. (2022).

Figure 2: Disagreement between explanation methods for neural network model trained on COMPAS dataset measured by rank agreement (top row) and signed rank agreement (bottom row) at top-k features for increasing values of k. Each cell in the heatmap shows the metric value averaged over test set data points for each pair of explanation methods, with lower values (lighter colors) indicating stronger disagreement. We follow the same disagreement interpretation described in Figure 1. Across all six heatmaps, the standard error ranges between 0 and 0.01.

Furthermore, there are varying degrees of disagreement among pairs of explanation methods. For example, for the neural network model trained on the COMPAS dataset, rank correlation displays a wide range of values across explanation method pairs, with 14 out of 15 explanation method pairs even exhibiting negative rank correlation when explaining multiple data points. This is shown in the left panel of Figure 3, which displays the rank correlation over all the features among all pairs of explanation methods for neural network model trained on COMPAS dataset.

All the patterns discussed above are also generally reflected in the German Credit dataset (Appendix C.1). However, explanation methods sometimes display stronger disagreement for the German Credit dataset than for the COMPAS dataset. For example, rank agreement and signed rank agreement are lower for the German Credit dataset than for the COMPAS dataset at top 25%, 50%, 75%, and 100% of features for both logistic regression and neural network models. One possible reason is that the German Credit dataset has a larger set of features than the COMPAS dataset, resulting in a larger number of possible ranking and sign combinations assigned by a given explanation method and making it less likely for two explanation methods to produce consistent explanations.

Lastly, explanation methods display trends associated with model complexity. For example, the disagreement between explanation methods is similar or stronger for the neural network model than for the logistic regression model across metrics and values of k, for both COMPAS and German Credit datasets (Appendix C.1). In addition, explanation methods show similar levels of disagreement for the random forest and gradient-boosted tree models. These trends suggest that disagreement among explanation methods may increase with model complexity. As the complexity of the black box model increases, it may be more difficult to accurately approximate the black box model with a simpler model (LIME's strategy, for example) and more difficult to

disentangle the contribution of each feature to the model's prediction. Thus, the higher the model complexity, the more difficult it may be for different explanation methods to generate the true explanation and the more likely it may be for different explanation methods to generate differently false explanations, leading to stronger disagreement among explanation methods.

Figure 3: Distribution of rank correlation over all features for neural network model trained on COMPAS (left), and rank correlation across all features (middle) and signed rank agreement across top-11 features (right) for neural network model trained on AG_News.

4.3.2 Text Data

Figure 4: Disagreement between explanation methods for LSTM trained on the AG_News dataset using $k = 11$ features for metrics operating on top-k features, and all features for other metrics. Each heatmap shows the metric value averaged over test data for each pair of explanation methods. Lighter colors indicate more disagreement. Standard error ranges from 0.0 to 0.0025 for all six metrics.

In the case of text data, we deal with a high-dimensional feature space where words are features. We plot the six metrics for $k = 11$ which is around 25% of the average text length of a sentence (data point) in the dataset (Figure 4). As seen in the figure, we observe severe disagreements across all the six disagreement metrics. Rank agreement and signed rank agreement are the lowest between explanations with values under 0.1 for most cases indicating disagreement in over 90% of the top-k features. Trends are quite similar for rank correlation and feature agreement with better agreement between gradient-based explanation methods, such as a feature agreement of 0.61 for the Gradient times Input and Vanilla Gradient method pair.

Other than the overall disagreements, we also notice specific patterns of agreement between a group of explanation methods. Based on middle and right panels of Figure 3, we notice that there is a high rank correlation between pairs of gradient-based explanations. Although Integrated Gradients has the lowest correlation with the rest of the gradient-based methods, this correlation is still significantly higher than its correlation with KernelSHAP and LIME. We also notice that disagreement is lower between LIME and other explanation methods than between KernelSHAP and other methods (e.g., rank correlation of 0.4-0.6 for LIME as opposed to 0.2-0.4 for KernelSHAP. See Appendix C for other metrics). Lastly, we see a higher disagreement among explanation methods for text data than for tabular data which suggests that disagreement may worsen as the number of features increases. We also observe a similar disagreement pattern between LIME and other methods which was also observed in experiments with tabular datasets, suggesting that LIME explanations are more aligned with other post hoc explanation methods.

4.3.3 Image Data

While LIME and KernelSHAP consider super pixels of images as features, gradient-based methods consider pixels as features. In addition, the notion of top-k features and the metrics we define on top-k features are not semantically meaningful when we consider pixels as features. We compute all the six metrics to capture disagreement between explanations output by LIME and KernelSHAP with super pixels as features. We also compute rank correlation on all the pixels (features) to capture disagreement between explanations output by gradient-based methods.

Unlike earlier trends with tabular and text data, we see higher agreement between KernelSHAP and LIME on all the six metrics: rank correlation of 0.8977, pairwise rank agreement of 0.9302, feature agreement of 0.9535, rank agreement of 0.8478, sign agreement of 0.9218 and signed rank agreement of 0.8193.

However, the trends are quite opposite when we compute rank correlation at pixel-level for gradient-based methods (See Appendix C). For instance, rank correlation between Integrated Gradients and SmoothGrad is 0.001, indicating strong disagreement. The disagreement is similarly quite strong in the case of other pairs of gradient-based methods. This suggests that disagreement could potentially vary significantly based on the granularity of image representation.

5 Resolving the Disagreement Problem in Practice: A Qualitative Study

After establishing the fact that the majority of practitioners observe disagreement between explanations using both qualitative analysis (Section 3) as well as quantitative analysis (Section 4), we try to understand the different ways practitioners tackle this disagreement. To this end, we conduct a qualitative user study targeted towards explainability practitioners. We next describe our user study design and discuss our findings.

5.1 User Study Design

In total, 25 participants participated in our study, 13 from academia and 12 from industry. Participants from academia were graduate students and postdoctoral researchers. In contrast, participants from industry were data scientists and ML engineers from three different for-profit companies in the technology and financial services sectors across the United States. We recruited these participants by emailing the explainable ML groups (and relevant mailing lists) within these organizations. 19 participants in this study (76%) also participated in the interviews in Section 3.1.[3] We conducted basic checks (e.g., pre-screening interviews and

---

[3]The remaining 6 participants from the interviews were unavailable during the time of the second study.

profile checks) to ensure that each recruited participant has at least one year of experience as a data scientist, and has working knowledge of data science and ML. 20 of these participants indicated that they had used explanation methods in their work in various ways, including doing research, helping clients explain their models, and debugging their own models. Following the setup in Section 4, we asked participants to compare the output of five pairs of explanation methods on the predictions made by the neural network we trained on the COMPAS dataset. We chose the COMPAS dataset because it only has 7 features, making it easy for participants to understand the explanations.

First, the participants are shown an information page explaining the COMPAS risk score binary prediction setting and various explanation methods. We indicate that we trained a neural network to predict the COMPAS risk score (low or high) from the seven COMPAS features. We also give a brief description of each of these seven features to participants and tell them to assume that the criminal defendant's risk of recidivism is correctly predicted to be high risk. In this information page, we also briefly introduce and summarize the six explanation methods we use in the study (LIME, KernelSHAP, Vanilla Gradient, Gradient times Input, SmoothGrad, and Integrated Gradients). Finally, we provide links to the papers describing each method. We include a screenshot of this information page in Appendix D.1.

Next, participants were shown a series of 5 prompts, a sample of which is shown in Figure 5. Each prompt presented two explanations of the neural network model's prediction corresponding to a particular data point generated using two different explanation methods (e.g., LIME and KernelSHAP in Figure 5). We chose a different data point from COMPAS to run the two methods, giving us a set of 15 prompts for each of the 15 pairs of explanation methods. These prompts were picked to showcase various levels of agreement. We displayed the full set of $k = 7$ COMPAS features, showing the feature importance of each feature. The red and blue bars indicate that the feature contributes negatively and positively, respectively, to the model prediction. Participants were first asked the question *"To what extent do you think the two explanations shown above agree or disagree with each other?"* and given four choices: *completely agree, mostly agree, mostly disagree*, and *completely disagree*. If the participants indicated any level of disagreement (i.e., any of the latter 3 choices), we then asked them *"Since you believe that the above explanations disagree (to some extent), which explanation would you rely on?"* and presented them with three choices: the two explanation methods shown and *"it depends"*. Then, they were asked to explain their response. Participants were allowed to take as much time as they needed.

5.2 Results and Insights

We now discuss the results and findings from our user study.

5.2.1 Do practitioners observe disagreements?

We aggregated the responses to the first question in each prompt, *"To what extent do you think the explanations shown above agree or disagree with each other?"*. Overall, 4%, 28%, 50%, and 18% of responses indicate *completely agree, mostly agree, mostly disagree*, and *completely disagree*, respectively, highlighting that there is significant disagreement among our prompts. See Appendix D.4 for more details.

5.2.2 Are certain explanations favored over others?

Next, since different explanation methods have different levels of popularity, we analyze if certain methods are chosen more often in disagreements. Figure 6a shows the distribution of how participants resolved disagreements for each prompt (dropping prompts with 4 or fewer responses). We first emphasize that there is high variability in how participants chose to resolve disagreements, showing a lack of consensus for the majority of prompts. However, when participants do decide to choose a method rather than abstaining, they often choose the same method. For example, for the Vanilla Gradient vs. SmoothGrad pair (top row in Figure 6a), participants either chose SmoothGrad over Vanilla Gradient or chose neither. We also aggregate these choices over all prompts, and in Figure 6b, we plot how often each of the six explanation methods is chosen, finding that indeed, certain methods were favored over others. While KernelSHAP was chosen 66.7% of the time when there are disagreements, Gradient times Input was only chosen 7.0% of the time. We

Figure 5: The user interface for a prompt. The user is shown two explanations for a COMPAS data point, showing the feature importance value of each of the 7 features. Red and blue indicate negative and positive feature values, respectively. See the text for more details.

include a further explanation of why participants chose each of the explanations in Appendix D.5, including quotes from participants that supported each method.

(a) The frequency with which each of the explanations in a pair is selected upon disagreement. The blue, gold, and grey bars show the percentage of participants (X axis) that picked the left, right, and neither method when presented with the pair of methods shown on the Y axis.

(b) The frequency with which each of the explanations was chosen when there is a disagreement. X axis indicates the explanation method and Y axis indicates the frequency.

Figure 6: Figures highlight which methods participants chose when the explanations they were shown disagreed. In (a), we show how participants resolved each particular prompt. In (b), we show the overall frequencies with which an explanation method was selected.

5.2.3 How do practitioners resolve disagreements?

Across all six explanation methods, we find three unifying themes that dictated why participants chose one explanation over the other. We give a high-level description of these themes below, highlighting direct quotes from participants in Table 1.

1. One method is inherently better than the other because of its associated theory or publication time (33%): Participants often indicated preference towards a particular method without referencing the shown explanation citing features such as the paper's publication time (more recent is better), the theory behind the method, and the method's stability.

2. One of the generated explanations matches intuition better (32%): Participants frequently said that one method's explanation aligned with their intuition better, citing the absolute and relative values of specific features as evidence.

3. LIME and SHAP are better because COMPAS dataset comprises of tabular data (23%): Participants said that they mainly used LIME and SHAP for tabular data and commonly cited this as their sole reason.

Theme Highlighted	Sample Quotes
1. One method's paper/theory suggests that it's inherently better (33%).	• *"I have no reason to believe the gradient holds anywhere other than very locally."*
• *"[Integrated Gradients is] more rigorous [than SmoothGrad] based on the paper and axioms"*
• *"gradient explanations are more unstable"*
2. One explanation matches intuition better (32%).	• *"seems unlikely that all features contributed to a positive classification"*
• *"features such as priors_count and length of stay [are] important for determining"*
• *"Gradient*Input only consider[s] sensitive features (age, race) as impactful which could be a sign of a biased underlying data distribution"*
3. LIME/SHAP are better for tabular data (23%).	• *"I use LIME for structured data"*
• *"SHAP is more commonly used [than Vanilla Gradient] for tabular data"*

Table 1: Themes summarizing how participants decided between explanations when faced with disagreement along with quotes.

5.2.4 Experiencing and resolving disagreements in day-to-day workflow

After answering all 5 prompts, participants were asked a set of questions on their experience with the disagreement problem in their day to day work. First, to filter out participants who didn't use explanation methods, we asked: *"Have you used explanation methods in your work before?".* Of the 25 participants, 5 of them indicated that they had not. We asked the other 20 participants further questions to better understand their experience with the disagreement problem. The full set of questions can also be found in Appendix D.3. Having understood what participants look for to determine disagreement in Section 3.1, we next sought to better understand two crucial questions related to the disagreement problem: *(Q1): Do you observe disagreements between explanations output by state-of-the-art methods in your day-to-day workflow?* and *(Q2): How do you resolve such disagreements in your day to day workflow?.*

One of the 20 participants declined to respond to (Q1) and (Q2) because they were not a practitioner. Out of the other 19, 14 participants (74%) responded *"yes"* to (Q1), indicating that they did in fact encounter explanation disagreement in practice. Of the remaining 5 who said they did not, 3 said they had not really paid attention to the issue. We also aimed to uncover how participants dealt with the disagreement problem when it arose in practice (Q2). 14 participants responded affirmatively to (Q1), and their responses to (Q2) can be grouped into 3 categories. 50% favored using adhoc heuristics based on personal preferences for choosing which methods to use (*"picking their favorite method"*, *"rules of thumb based on results in papers"*). These heuristics varied among participants and included ease of implementation, accompanying theoretical results, recency of publication, ease of understanding, and documentation of packages. 36% did not indicate

any explicit way for resolving these disagreements, but instead demonstrated confusion and uncertainty (*"no clear answer to me"*). Several of these responses also indicated the desire for the research community to make progress and help (*"I hope research community can provide some guidance"*). The remaining 14% proposed to use other metrics such as fidelity (*"try and use some metric to measure fidelity"*). See Appendix D.7 for more details.

6 Discussion and Conclusion

In our research, we explored the *disagreement problem* in explainable ML, focusing on how different explanation methods often yield conflicting results. We formalized the concept of disagreement between explanations, and through interviews with data scientists and a novel quantitative framework, we assessed the frequency and nature of these disagreements. Our empirical analysis involved four real-world datasets, six advanced post hoc explanation methods, and eight predictive models, revealing significant discrepancies in the explanations provided by various methods. Additionally, an online user study with ML practitioners highlighted that 84% of them face the disagreement problem regularly. While there exist metrics and frameworks to both evaluate and compare explanations output by state-of-the-art methods Agarwal et al. (2021; 2022); Han et al. (2022), we found that most practitioners lack a principled strategy to resolve these conflicts, often resorting to arbitrary choices or admitting uncertainty, as indicated by 86% of respondents in our study. This underlines a critical gap in current ML practices regarding the interpretation of model explanations.

Naturally, the results of this study raise the question of how to systematically characterize when state-of-the-art explanation methods disagree, and analyze the reasons behind these disagreements. Moreover, our results raises the question of how to resolve these disagreements. While this remains an open question and an active area of research, one approach to select among explanation methods is to first define the desired goal of an explanation and then select the explanation method that best meets this goal. For example, Han et al. (2022) defines local function approximation as the desired goal of an explanation, develops a framework to analyze how faithfully each method performs local function approximation, and advises selecting the method that performs it most faithfully over a given input space. Given the high-stakes applications of model explanations, using a principled, systematic approach to select among explanations methods is preferable to the ad hoc strategies currently employed by practitioners.

References

Antonio Gulli corpus of news articles. `http://groups.di.unipi.it/~gulli/AG_corpus_of_news_articles.html`, 2005. Accessed: 2021-01-20.

Pascal Visual Object Classes 2012. `http://host.robots.ox.ac.uk/pascal/VOC/index.html/`, 2012. Accessed: 2021-01-20.

ImageNet. `https://www.image-net.org/challenges/LSVRC/index.php`, 2015. Accessed: 2021-01-20.

Julius Adebayo, Justin Gilmer, Michael Muelly, Ian Goodfellow, Moritz Hardt, and Been Kim. Sanity checks for saliency maps. In *Advances in Neural Information Processing Systems*, 2018.

Chirag Agarwal, Eshika Saxena, Satyapriya Krishna, Martin Pawelczyk, Nari Johnson, Isha Puri, Marinka Zitnik, and Himabindu Lakkaraju. OpenXAI: Towards a transparent evaluation of model explanations. *36th Conference on Neural Information Processing Systems (NeurIPS 2022) Track on Datasets and Benchmarks*, 2022.

Sushant Agarwal, Shahin Jabbari, Chirag Agarwal, Sohini Upadhyay, Zhiwei Steven Wu, and Himabindu Lakkaraju. Towards the unification and robustness of perturbation and gradient based explanations. In *International Conference on Machine Learning*, 2021.

Ulrich Aivodji, Hiromi Arai, Olivier Fortineau, Sébastien Gambs, Satoshi Hara, and Alain Tapp. Fairwashing: the risk of rationalization. In *International Conference on Machine Learning*, 2019.

David Alvarez-Melis and Tommi S Jaakkola. On the robustness of interpretability methods. *arXiv preprint arXiv:1806.08049*, 2018.

Antonio Jesus Banegas-Luna, Carlos Martınez-Cortes, and Horacio Perez-Sanchez. Fighting the disagreement in explainable machine learning with consensus. *arXiv preprint arXiv:2307.01288*, 2023.

Gagan Bansal, Tongshuang Wu, Joyce Zhou, Raymond Fok, Besmira Nushi, Ece Kamar, Marco Tulio Ribeiro, and Daniel Weld. Does the whole exceed its parts? the effect of ai explanations on complementary team performance. In *Proceedings of the 2021 CHI Conference on Human Factors in Computing Systems*, 2021.

Osbert Bastani, Carolyn Kim, and Hamsa Bastani. Interpretability via model extraction. *arXiv preprint arXiv:1706.09773*, 2017.

Jacob Bien and Robert Tibshirani. Classification by set cover: The prototype vector machine. *arXiv preprint arXiv:0908.2284*, 2009.

Zana Buçinca, Maja Barbara Malaya, and Krzysztof Z Gajos. To trust or to think: Cognitive forcing functions can reduce overreliance on ai in ai-assisted decision-making. *Proceedings of the ACM on Human-Computer Interaction*, 2021.

Rich Caruana, Yin Lou, Johannes Gehrke, Paul Koch, Marc Sturm, and Noemie Elhadad. Intelligible models for healthcare: Predicting pneumonia risk and hospital 30-day readmission. In *ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pp. 1721–1730, 2015.

Diogo V Carvalho, Eduardo M Pereira, and Jaime S Cardoso. Machine learning interpretability: A survey on methods and metrics. *Electronics*, 2019.

Prasad Chalasani, Jiefeng Chen, Amrita Roy Chowdhury, Xi Wu, and Somesh Jha. Concise explanations of neural networks using adversarial training. In *International Conference on Machine Learning*, 2020.

Chacha Chen, Shi Feng, Amit Sharma, and Chenhao Tan. Machine explanations and human understanding. *arXiv preprint arXiv:2202.04092*, 2022.

Ann-Kathrin Dombrowski, Maximillian Alber, Christopher Anders, Marcel Ackermann, Klaus-Robert Müller, and Pan Kessel. Explanations can be manipulated and geometry is to blame. *Advances in Neural Information Processing Systems*, 2019.

Finale Doshi-Velez and Been Kim. Towards a rigorous science of interpretable machine learning. *arXiv preprint arXiv:1702.08608*, 2017.

Mingming Fan, Xianyou Yang, TszTung Yu, Q Vera Liao, and Jian Zhao. Human-ai collaboration for ux evaluation: Effects of explanation and synchronization. *Proceedings of the ACM on Human-Computer Interaction*, 2022.

Raymond Fok and Daniel S Weld. In search of verifiability: Explanations rarely enable complementary performance in ai-advised decision making. *arXiv preprint arXiv:2305.07722*, 2023.

Amirata Ghorbani, Abubakar Abid, and James Zou. Interpretation of neural networks is fragile. In *AAAI Conference on Artificial Intelligence*, 2019.

Leilani H Gilpin, David Bau, Ben Z Yuan, Ayesha Bajwa, Michael Specter, and Lalana Kagal. Explaining explanations: An overview of interpretability of machine learning. In *2018 IEEE 5th International Conference on data science and advanced analytics (DSAA)*, 2018.

Tessa Han, Suraj Srinivas, and Himabindu Lakkaraju. Which explanation should i choose? a function approximation perspective to characterizing post hoc explanations. In *Advances in Neural Information Processing Systems*, 2022.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2016.

Sungsoo Ray Hong, Jessica Hullman, and Enrico Bertini. Human factors in model interpretability: Industry practices, challenges, and needs. *Proceedings of the ACM on Human-Computer Interaction*, 2020.

Sara Hooker, Dumitru Erhan, Pieter-Jan Kindermans, and Been Kim. Evaluating feature importance estimates. 2018.

Harmanpreet Kaur, Harsha Nori, Samuel Jenkins, Rich Caruana, Hanna Wallach, and Jennifer Wortman Vaughan. Interpreting interpretability: Understanding data scientists' use of interpretability tools for machine learning. In *Proceedings of the 2020 CHI Conference on Human Factors in Computing Systems*, 2020.

Been Kim, Cynthia Rudin, and Julie A Shah. The bayesian case model: A generative approach for case-based reasoning and prototype classification. In *Advances in Neural Information Processing Systems*, 2014.

Himabindu Lakkaraju, Stephen H. Bach, and Jure Leskovec. Interpretable decision sets: A joint framework for description and prediction. In *ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 2016.

Himabindu Lakkaraju, Ece Kamar, Rich Caruana, and Jure Leskovec. Faithful and customizable explanations of black box models. In *AAAI Conference on Artificial Intelligence, Ethics, and Society*, pp. 131–138, 2019.

Benjamin Letham, Cynthia Rudin, Tyler McCormick, and David Madigan. Interpretable classifiers using rules and bayesian analysis: Building a better stroke prediction model. *Annals of Applied Statistics*, 2015.

Alexander Levine, Sahil Singla, and Soheil Feizi. Certifiably robust interpretation in deep learning. *arXiv preprint arXiv:1905.12105*, 2019.

Yang Liu, Sujay Khandagale, Sujay Khandagale, Colin White, and Willie Neiswanger. Synthetic benchmarks for scientific research in explainable machine learning. In *Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks*, 2021.

Yin Lou, Rich Caruana, and Johannes Gehrke. Intelligible models for classification and regression. In *ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 2012.

Scott M Lundberg and Su-In Lee. A unified approach to interpreting model predictions. In *Advances in Neural Information Processing Systems*, 2017.

Vitali Petsiuk, Abir Das, and Kate Saenko. Rise: Randomized input sampling for explanation of black-box models. *arXiv preprint arXiv:1806.07421*, 2018.

ProPublica. How we analyzed the compas recidivism algorithm. `https://www.propublica.org/article/how-we-analyzed-the-compas-recidivism-algorithm`. Accessed: 2021-01-20.

UCI Machine Learning Repository. German credit dataset. `https://archive.ics.uci.edu/ml/datasets/statlog+(german+credit+data)`. Accessed: 2021-01-20.

Marco Ribeiro, Sameer Singh, and Carlos Guestrin. Anchors: High-precision model-agnostic explanations. In *AAAI Conference on Artificial Intelligence*, 2018.

Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. Model-agnostic interpretability of machine learning. In *ICML Workshop on Human Interpretability in Machine Learning (WHI)*, 2016a.

Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. "Why should I trust you?" Explaining the predictions of any classifier. In *ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 2016b.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision (IJCV)*, 2015. doi: 10.1007/s11263-015-0816-y.

Ramprasaath Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *IEEE International Conference on Computer Vision*, 2017.

Avanti Shrikumar, Peyton Greenside, and Anshul Kundaje. Learning important features through propagating activation differences. In *Proceedings of the 34th International Conference on Machine Learning*, 2017.

Karen Simonyan, Andrea Vedaldi, and Andrew Zisserman. Deep inside convolutional networks: Visualising image classification models and saliency maps. In *International Conference on Learning Representations*, 2014.

Dylan Slack, Sophie Hilgard, Emily Jia, Sameer Singh, and Himabindu Lakkaraju. How can we fool LIME and SHAP? Adversarial attacks on post hoc explanation methods. In *AAAI/ACM Conference on AI, Ethics, and Society*, 2020.

Dylan Slack, Anna Hilgard, Sameer Singh, and Himabindu Lakkaraju. Reliable post hoc explanations: Modeling uncertainty in explainability. *Advances in Neural Information Processing Systems*, 2021.

Daniel Smilkov, Nikhil Thorat, Been Kim, Fernanda Viégas, and Martin Wattenberg. Smoothgrad: Removing noise by adding noise. *arXiv preprint arXiv:1706.03825*, 2017.

Fabian Sperrle, Mennatallah El-Assady, Grace Guo, Rita Borgo, D Horng Chau, Alex Endert, and Daniel Keim. A survey of human-centered evaluations in human-centered machine learning. In *Computer Graphics Forum*, 2021.

Mukund Sundararajan, Ankur Taly, and Qiqi Yan. Axiomatic attribution for deep networks. In *International Conference on Machine Learning*, 2017.

Helena Vasconcelos, Matthew Jörke, Madeleine Grunde-McLaughlin, Tobias Gerstenberg, Michael S Bernstein, and Ranjay Krishna. Explanations can reduce overreliance on ai systems during decision-making. *Proceedings of the ACM on Human-Computer Interaction*, 7(CSCW1):1–38, 2023.

Xiang Zhang, Junbo Zhao, and Yann LeCun. Character-level convolutional networks for text classification. In *Advances in Neural Information Processing Systems*, 2015.

Jianlong Zhou, Amir H Gandomi, Fang Chen, and Andreas Holzinger. Evaluating the quality of machine learning explanations: A survey on methods and metrics. *Electronics*, 2021.

A   Measuring Disagreement

In this section we formally define our 6 different metrics: *feature agreement*, *rank agreement*, *sign agreement*, *signed rank agreement*, *rank correlation*, and *pairwise rank agreement*. The first four metrics capture disagreement with respect to the top-k features of the explanations and the last two metrics capture disagreement with respect to a selected set of features that could be provided as input by an end user. For all six metrics, lower values indicate stronger disagreement.

A.1   Measuring Disagreement With Respect to Top-k Features

We now define four metrics, which capture specific aspects of explanation disagreement with respect to the top-k features.[4]

---

[4]The top-k features of an explanation are typically computed only based on the magnitude of the feature importance values and not the signs.

Feature Agreement: ML practitioners in interviews (Section 3.1) clearly indicated that a key notion of disagreement between a pair of explanations is that they output different top-k features. To capture this notion, we introduce the feature agreement metric which computes the fraction of common features between the sets of top-k features of two explanations. Given two explanations E_a and E_b, feature agreement is formulated as:

$$FeatureAgreement(E_a, E_b, k) = \frac{|TF(E_a, k) \cap TF(E_b, k)|}{k}$$

where $TF(E, k)$ returns the set of top-k features of explanation E based on the magnitude of the feature importance values. If the sets of top-k features of explanations E_a and E_b contain the same features, then $FeatureAgreement(E_a, E_b, k) = 1$.

Rank Agreement: Practitioners also indicated that if the ordering of the top-k features is different for two explanations (even if the feature sets are the same), then they consider it to be a disagreement. To capture this notion, we introduce the rank agreement metric which computes the fraction of features that are not only common between the sets of top-k features of two explanations, but also have the same position in the respective rank orders. Rank agreement is a stricter metric than feature agreement since it also considers the ordering of the top-k features. Given two explanations E_a and E_b, rank agreement is formulated as:

$$RankAgreement(E_a, E_b, k) = \frac{| \bigcup_{f \in F} \{f \mid f \in TF(E_a, k) \wedge f \in TF(E_b, k) \wedge R(E_a, f) = R(E_b, f)\}|}{k}$$

where F is the complete set of features in the data, $TF(E, k)$ is as defined above, and $R(E, f)$ returns the rank of feature f according to explanation E. If the rank-ordered lists of top-k features of explanations E_a and E_b match, then $RankAgreement(E_a, E_b, k) = 1$.

Sign Agreement: In our study, practitioners also mentioned that they consider two explanations to disagree if the feature attribution signs (i.e. directions of feature contribution) do not align for the top-k features. To capture this notion, we introduce the sign agreement metric which computes the fraction of features that are not only common between the sets of top-k features of two explanations, but also share the same sign in both explanations. Sign agreement is a stricter metric than feature agreement since it also considers signs of the top-k features. Given two explanations E_a and E_b, sign agreement is formulated as:

$$SignAgreement(E_a, E_b, k) = \frac{| \bigcup_{f \in F} \{f \mid f \in TF(E_a, k) \wedge f \in TF(E_b, k) \wedge S(E_a, f) = S(E_b, f)\}|}{k}$$

where F and $TF(E, k)$ are as defined above and $S(E, f)$ returns the sign of feature f according to explanation E.

Signed Rank Agreement: This metric fuses the above three notions of explanation disagreement, and computes the fraction of features that are not only common between the sets of top-k features of two explanations, but also share the same feature attribution sign and rank in both explanations. Signed rank agreement is the strictest compared to all the aforementioned metrics since it considers both the ordering and the signs of the top-k features. Given two explanations E_a and E_b, signed rank agreement is formulated as:

$$SignedRankAgreement(E_a, E_b, k) = \frac{| \bigcup_{f \in F} \{f \mid f \in TF(E_a, k) \wedge f \in TF(E_b, k) \wedge S(E_a, f) = S(E_b, f) \wedge R(E_a, f) = R(E_b, f)\}|}{k}$$

where F, $TF(E, k)$, $S(E, f)$, and $R(E, f)$ are as defined above. $SignedRankAgreement(E_a, E_b, k) = 1$ if the top-k features of two explanations match on all aspects (i.e., features, feature attribution signs, rank ordering) barring the exact feature importance values.

A.2 Measuring Disagreement With Respect to Features of Interest

Practitioners also indicated that they consider two explanations to be different if the relative ordering of features of interest (e.g., salary and credit score discussed in Section 3.1) differ between the two explanations. To formalize this notion, we introduce the two metrics below.

Rank Correlation: We adopt a standard rank correlation metric (i.e., Spearman's rank correlation coefficient) to measure the agreement between feature rankings provided by two explanations for a selected set of features. In practice, this selected set of features corresponds to features that are of interest to end users and can be provided as input by end users. Given two explanations E_a and E_b, rank correlation is formulated as:

$$RankCorrelation(E_a, E_b, F) = r_s(R(E_a, F), R(E_b, F))$$

where $F = \{f_1, f_2 \cdots\}$ is a set of features selected by an end user, r_s computes Spearman's rank correlation coefficient, and $R(E, F)$ assigns ranks to features in F based on explanation E.

Pairwise Rank Agreement: Pairwise rank agreement takes as input a set of features that are of interest to the user and captures if the relative ordering of every pair of features in that set is the same for both the explanations, i.e., if feature A is more important than B according to one explanation, then the same should be true for the other explanation. This metric computes the fraction of feature pairs for which the relative ordering is the same between two explanations. Given two explanations E_a and E_b, pairwise rank agreement is formulated as:

$$PairwiseRankAgreement(E_a, E_b, F) = \frac{\sum\limits_{i,j \text{ for } i<j} \mathbb{1}[\text{RO}(E_a, f_i, f_j) = \text{RO}(E_b, f_i, f_j)]}{\binom{|F|}{2}}$$

where $F = \{f_1, f_2 \cdots\}$ is a set of features selected by an end user, the relative ordering function $\text{RO}(E, f_i, f_j)$ is an indicator function that returns 1 if feature f_i is more important than feature f_j according to explanation E and returns 0 otherwise.

B Experimental Setup

B.1 Black Box Models: Training and Performance

For tabular data, we train four models: a logistic regression model, a gradient-boosted tree model (50 estimators), a random forest model (50 estimators), and a densely-connected feed-forward neural network (with 3 hidden layers with relu activation consisting of 50, 100, and 50 neurons, respectively). For the COMPAS dataset, we train the four models based on a 80%-20% train-test split of the dataset, using features to predict COMPAS risk score group. The test accuracies of the four models are 0.75, 0.79, 0.79, and 0.73, respectively. For the German credit dataset, we train the same four models based on a 80%-20% train-test split of the dataset, using features to predict credit risk group. The test accuracies of the four models are 0.65, 0.70, 0.73, and 0.64, respectively.

For text data, we trained a widely-used LSTM-based text classifier, based on 120,000 training samples and 7,600 test samples, to predict the news category of the article from which a sentence was obtained. The model performs with 90.67% accuracy. The architecture comprises of an embedding layer of dimension 300, followed by an LSTM layer of hidden size 256 connected to a four-dimensional output layer.

For image data, we use the pre-trained ResNet-18 model He et al. (2016) and analyze explanations generated for predictions made to classify images to one of the 1000 classes. This model performs 69.758 % and 89.078 % on Accuracy@1 and Accuracy@5 metrics[5], respectively.

---

[5]https://pytorch.org/vision/stable/models.html

B.2 Explanation Methods

For tabular data, the perturbation-based explanation methods (LIME and KernelSHAP) were applied to explain all four models while the gradient-based explanation methods (Vanilla Gradients, Integrated Gradients, Gradient*Input, and SmoothGRAD) were applied to explain the logistic regression and neural network models to explain samples from the test set (1,198 samples for the COMPAS dataset and 200 samples for the German Credit dataset). Because gradients are not computed for tree-based models, the gradient-based explanation methods were not applied to the random forest and gradient-boosted tree models. When applying explanation methods with a sample size hyperparameter (LIME, KernelSHAP, Integrated Gradients, SmoothGRAD), we performed a convergence check and selected the sample size at which an increase in the number of samples does not significantly change the explanations. Change in explanations at the current versus previous sample size is measured by L2 distance of feature attributions, L2 distance of the ranks of all features, and the six metrics. For both COMPAS and German Credit datasets, we used 2,000 samples for relevant methods (i.e. LIME, KernelSHAP, SmoothGRAD, and Integrated Gradients).

For text data, we applied all six explanation methods on the LSTM-based classifier to explain predictions for 7,600 samples in the test set. For LIME and KernelSHAP, we follow the convergence analysis described above and find that attributions do not change significantly beyond 500 perturbations; hence, we use 500 perturbations for LIME and KernelSHAP. Integrated Gradients explanations were generated using 500 steps which is higher than the recommended number of steps mentioned in Sundararajan et al. (2017). SmoothGRAD explanations were generated using 500 samples to get the most confident attribution which is significantly higher the recommended number of 50 samples Smilkov et al. (2017).

For image data, we applied all six explanation methods on the ResNet-18 model He et al. (2016) to explain predictions for the PASCAL VOC 2012 test set of 1,449 samples. Integrated Gradients explanations were generated using 400 steps, significantly higher than the recommendation of 300 Sundararajan et al. (2017), to obtain a stable and confident attribution map. Similarly, SmoothGRAD explanations were generated using a sample size of 200 which is also higher than the recommended sample size of 50 Smilkov et al. (2017). For LIME and KernelSHAP, we chose 100 perturbations to train the surrogate model as we did not notice any significant changes in attributions beyond 50 perturbations. KernelSHAP and LIME were used to compute attributions of super-pixels annotated in PASCAL VOC 2012 segmentation maps. Due to a larger feature space in images compared to the previous tabular and text datasets, disagreement metrics based on top-k features may not provide a clear picture. Hence, we use Rank Correlation and cosine distance between attribution maps generated by a pair of explanation methods as the disagreement metric. Higher cosine distance between attribution maps indicate larger disagreement between explanation methods.

C Results from Empirical Analysis of Disagreement Problem

C.1 Tabular Data: COMPAS and German Credit Datasets

The tabular datasets consist of the COMPAS and German Credit datasets. The full set of figures showing explanation disagreement for the two datasets, over four models, measured by six metrics, displayed in two formats (metric mean in heatmap and metric distribution in boxplot) for varying values of top-k features can be found in the code repository accompanying this paper. Here, we elaborate on trends of explanation disagreement at the level of metrics, models, and datasets.

At the level of metrics, explanations show stronger disagreement when measured by stricter metrics (such as signed rank agreement) than by less strict metrics (such as feature agreement and sign agreement). Generally, as the number of top-k features increases, metrics show stronger disagreement between explanations. The exception is the feature agreement metric which, by definition equals one (indicating perfect agreement) when the k is the total number of features. For both datasets, the majority of models and explanation pairs have several points for which the rank correlation metric is near zero or even negative, indicating disagreeing, and even opposing, explanations.

At the level of models, explanations for more complex models (such as the neural network) tend to show similar or stronger disagreement than explanations for less complex models (such as the logistic regression

model). As discussed in the main section of the paper, as the complexity of the black box model increases, it may be more difficult to explain the model's decision-making process and more difficult to disentangle the contribution of each feature to the model's prediction. Thus, the higher the model complexity, the more difficult it may be for different explanation methods to generate the true explanation and the more likely it may be for different explanation methods to generate differently false explanations, leading to stronger disagreement among explanation methods.

At the level of datasets, explanations for the German Credit dataset showed similar or stronger levels of disagreement than those for the COMPAS dataset. As discussed in the main paper, one possible reason is that the German Credit dataset has more features than the COMPAS dataset, resulting in a larger number of possible ranking and sign combinations assigned by a given explanation method and making it less likely for two explanation methods to produce consistent explanations.

Figure 7: Box plot for feature agreement on AG_News dataset for k = [3,7,11]

C.2   Text Data: AG_News Dataset

In this section, we analyse the trends in pair-wise disagreement w.r.t the feature agreement metric with increasing number of features considered for measuring disagreement($k = [3, 7, 11]$). We observe that agreement between gradient based methods is significantly more compared to that with perturbation-based explanation method, which is more prominent for larger values of k.

C.3   Image Data: ImageNet Dataset

In Table 2, we analyse disagreement between perturbation-based explanation methods when feature attributions are computed at super-pixel level, and observe a significantly high agreement in terms of all the proposed disagreement metrics. However, there is little to no agreement when its computed at pixel level in terms of the rank correlation between explanations, shown in Figure 8.

Metrics	ResNet-18
Rank correlation	0.8977
Pairwise rank agreement	0.9302
Feature agreement	0.9535
Rank agreement	0.8478
Sign agreement	0.9218
Signed rank agreement	0.8193

Table 2: Disagreement on ImageNet between LIME and KernelSHAP

Figure 8: Rank correlation for explanations computed at pixel level by gradient-based explanation methods

D   Omitted Details from Section 5

D.1   Screenshots of UI

In Figures 9 and 10, we present screenshots of the UI that participants are presented with before beginning the study. The purpose of this introduction page is to familiarize the participants with the COMPAS prediction setting, the six explainability methods we use, and the explainability plots we show in each of the prompts.

Introduction

COMPAS is a popular commercial algorithm used by judges for determining a criminal defendant's likelihood of reoffending (recidivism).

The COMPAS dataset consists of 7 features:

- **age**
- **two_year_recid**: whether the defendant recidivated within 2 years of the original crime
- **priors_count**: number of prior crimes committed
- **length_of_stay**: length the defendant stayed in jail
- **c_charge_degree**: one of Misdemeanor, Felony
- **sex**: one of Male, Female
- **race**: one of African-American, Asian, Caucasian, Hispanic, Native American, or Other

For this study, we trained a neural network on the COMPAS dataset to **predict a criminal defendant's COMPAS risk score (low or high), corresponding to whether he/she would commit a crime after two years past the date of the original crime**. Since it is important to understand our model's predictions (explainability), we also ran six popular explainability algorithms on various input points.

The explainability algorithms we use are listed here. **You do not need to understand them past what we have described here.**

- **LIME**: an explanation based on a locally linear approximation of the model at that input
- **KernelSHAP**: a combination of LIME and Shapley Values, which identify the contribution of each feature based on interactions with other features
- **Gradient**: the gradient of the model at the input
- **Gradient*Input**: the dot product of the input features and the gradient explanation
- **SmoothGrad**: weighted average of the gradient at points around the input
- **Integrated Gradients**: a modification of the gradient method to satisfy two axioms, *sensitivity* and *implementation invariance*

Figure 9: This is a screenshot of the first half of the introductory page, describing our COMPAS risk score prediction setting and briefly summarizing the six explainability algorithms used (with links to their corresponding papers for the interested participant).

Your Task

On each of the next 5 pages, you will see the result of two explainability methods on the same input sample from COMPAS, as shown below. **Assume that the criminal defendant's risk of recidivism was correctly predicted to be high.** The explanation of the prediction will then be shown to you, as in the figure below.

The y-axis lists each of the 7 COMPAS features, and the x-axis shows the importance of that feature. Positive importance values are shown in blue, while negative importance values are shown in red. A **high positive importance** for a feature means that the feature contributed greatly to the correct prediction, while a **high negative importance** means that the feature negatively contributed (was misleading) to the prediction. Note the different x-axis scales resulting from different methods. You will be asked to compare the two explanations.

Figure 10: This is a screenshot of the second half of the introductory page, describing the concrete task and an explanation of what is shown in the explainability plots.

D.2   Prompts Used

In this section, we share the 15 prompts that we showed users. Each prompt highlights a pair of different explainability algorithms on a COMPAS data point. For each pair, we chose the data point from the entire COMPAS set that maximized the rank correlation between the explanations.

D.3   User Study Questions

In each of the five prompts, we asked participants the following questions, which we refer to as *Set 1*. Questions 3-4 were only shown if the user selected *Mostly agree*, *Mostly disagree*, or *Completely disagree* to Question (1).

1. To what extent do you think the two explanations shown above agree or disagree with each other? (choice between *Completely agree, Mostly agree, Mostly disagree, Completely disagree*)

2. Please explain why you chose the above answer.

3. Since you believe that the above explanations disagree (to some extent), which explanation would you rely on? (choice between *Algorithm 1 explanation, Algorithm 2 explanation, It depends*)

4. Please explain why you chose the above answer.

After answering all five prompts, the user was then asked the following set of questions, which we refer to as *Set 2*. Questions 4-9 were only shown if the user selected *Yes* to Question 3.

1. (Optional) What is your name?

2. What is your occupation? (eg: PhD student, software engineer, etc.)

3. Have you used explainability methods in your work before? (*Yes/No*)

4. What do you use explainability methods for?

5. Which data modalities do you run explainability algorithms on in your day to day workflow? (eg: tabular data, images, language, audio, etc.)

6. Which explainability methods do you use in your day to day workflow? (eg: LIME, KernelSHAP, SmoothGrad, etc.)

7. Which methods do you prefer, and why?

Figure 11: Images showing the 15 prompts we used. Each prompt shows the explanation of the same input point with two different interpretability algorithms.

8. Do you observe disagreements between explanations output by state of the art methods in your day to day workflow?

9. How do you resolve such disagreements in your day to day workflow?

D.4 Further analysis of overall agreement levels

In this section, we present further plots analyzing responses to questions (1) in Set 1. As shown in Figure 12a, only 32% of responses were *Mostly Agree/Completely Agree* and 68% were *Mostly Disagree/Completely Disagree*, indicating that participants experienced the disagreement problem. We also grouped the responses by prompt, shown in Figure 12b, highlighting that different pairs of algorithms can have different levels of disagreement. We removed prompts with less than 4 total responses. We see that there are varying levels of disagreements among prompts. For example, all participants who were shown the Gradient vs. SmoothGrad prompt believed they agreed to some extent, while all participants who were shown the Gradient vs. Integrated Gradients prompt believed they disagreed to some extent.

(a) This figure shows the distribution of responses in aggregation over all prompts. The x-axis shows the four possible responses, and the y-axis shows the number of times that response was chosen. Observe that in 68% of cases, participants indicated that the prompts mostly or completely disagreed.

(b) This figure shows the distribution of responses, sorted by prompt. The y-axis shows the pair of explainability algorithms shown in the prompt, and the x-axis shows the frequency that each response was chosen.

Figure 12: These figures show the distribution of answers to Question (1) in Set (1) from Section D.4 in aggregation over all participants.

D.5 Further analysis of reasons participants chose specific algorithms

In this section, we analyze the responses to Set 1, Question (3) in Section D.3. We saw, in 5.2.2, that algorithms such as KernelSHAP were favored over other algorithms. In Table 3, we list the top reasons the four most frequently chosen algorithms were preferred, showcasing direct quotes from participants.

D.6 Analysis of reasons participants chose neither algorithm

In this section, we analyze the responses to Set 1, Question (4) in Section D.3, focusing on when participants selected *"It depends"* in Question (3), which was chosen in 38% of cases. Again, we present an overarching summary of the reasons participants made this decision in Table 4.

Algorithm	Reasons that algorithm was chosen in disagreement
KernelSHAP	• [36%] SHAP is better for tabular data (*"SHAP is more commonly used [than Gradient] for tabular data"*)
• [25%] SHAP is more familiar (*"More information present + more familiarity"*)
• [14%] SHAP is a better algorithm overall (*"SHAP seems more methodical than LIME", "SHAP is a more rigorous approach [than LIME] in theory"*)
SmoothGrad	• [33%] SmoothGrad paper is newer or better (*"SmoothGrad is apparently more robust", "SmoothGrad is often considered improved version of grad"*)
• [58%] Reasons based on the explainability map shown (*"directionality of the attributions ... [agree] with intuition", "gradient has instability problems [, so] smoothgrad"*)
LIME	• [54%] LIME is better for tabular data (*"I use LIME for structured data."*)
• [15%] LIME is more familiar/easier to interpret (*"I am more familiar with LIME", "LIME is easy to interpret"*)
Integrated Gradients	• [86%] Integrated Gradients paper is better (*"IG came after gradients and paper shows improvements", "integrated gradients paper showed improvements [over Gradient × Input]"*)

Table 3: Reasons participants chose the top four most favored explainability algorithms (KernelSHAP, SmoothGrad, LIME, and Integrated Gradients) over others when explanations disagreed.

Rationale	Representative Quote
1. Need more information	• *"need to see the final prediction of the model and the feature values"*
2. Pick neither explanation	• *"No compelling reason to choose one over the other. Both don't align with intuition."*
3. Unsure/Don't know	• *"I'm not sure which of the two methods is more trustworthy"*
4. Would consult an expert	• *"I would ask a domain expert for his/her opinion"*
5. Combine explanations	• *"I would combine both – note that age might be doing weird things, but that length of stay and race both contribute to a negative prediction"*
6. Depends on use case	• *"The two methods have different interpretations - it depends on if I'm more interested in comparing my explanation to some baseline individual state versus just interested in understanding the immediate local behavior"*

Table 4: Reasons people answered *"It depends"* after being asked to choose between disagreements

D.7 Further analysis of concluding questionnaire

In this section, we extend the analysis presented in 5.2.3, analyzing the responses to questions in Set 2 of Section D.3. As stated in 5.2.3, we received a total of 20 positive responses to Question (3), but one declined to answer Questions (4) through (9). Therefore, we analyze the remaining 19 responses.

In Question (4), we found that study participants use explainability methods for a variety of reasons such as understanding models, debugging models, help explain models to clients, research. In Question (5), we found that 16 of 19 participants employed explanations for tabular data, 6 of 19 participants for text and language data, 11 of 19 participants for image data, and 1 of 19 for audio data. In Question (6), we found that 14 of 19 participants used LIME, 14 of 19 participants used SHAP, and 13 of 19 participants used some sort of gradient-based methods. Participants also indicated using methods like GradCAM, dimensionality reduction, MAPLE, and rule-based methods. In Question (7), 9 of 19 participants stated that they preferred both LIME and SHAP, with another 3 of 19 participants stating LIME only. We showcase some intriguing answers from Question (7) below:

- "LIME and SHAP seem to be the most universally applicable and I can understand."

- "Methods with underlying theoretical justifications such as KernelSHAP and Integrated Gradients"

- "LIME and SHAP ... [easy to implement] and can work with black box"

- "SHAP and LIME because ... [they are] easy to understand and have standard implementations"

- "LIME, because everything else isn't necessarily capturing what I actually want to know about the local behavior"

Finally, we provide additional quotes highlighting the responses to Questions (8) and (9), which were briefly analyzed in Section 5.2.3. These are shown in Table 5.

Category of Response	Samples Quotes
1. Make arbitrary decisions (50%).	• *"Such disagreements are resolved by data scientists picking their favorite algorithm"*
• *"I try to use rules of thumb based on results in research papers and/or easy to understand outputs."*
• *"I favor LIME and SHAP because there is well documented packages on GitHub"*
2. Unsure/Don't know/Don't resolve (36%)	• *"there is no clear answer to me. I hope research community can provide some guidance"*
• *"unfortunately there is no good answer at my end ... I hope you can help me with finding an answer"*
3. Use other metrics (fidelity) (14%).	• *"By quantitative assessment of feature importance methods that assess specific properties like faithfulness"*
• *"I might try and use some metric to measure fidelity."*

Table 5: Representative quotes highlighting themes of how participants address the disagreement problem in their day to day work