SYMMETRY-AWARE ACTOR-CRITIC FOR 3D MOLECULAR DESIGN

ABSTRACT

Automating molecular design using deep reinforcement learning (RL) has the potential to greatly accelerate the search for novel materials. Despite recent progress on leveraging graph representations to design molecules, such methods are fundamentally limited by the lack of three-dimensional (3D) information. In light of this, we propose a novel actor-critic architecture for 3D molecular design that can generate geometrically complex molecular structures unattainable with previous approaches. This is achieved by exploiting the symmetries of the design process through a rotationally covariant state-action representation based on a spherical harmonics series expansion. We demonstrate the benefits of our approach on several 3D molecular design tasks, where we find that building in such symmetries significantly improves generalization and the quality of generated molecules.

1 INTRODUCTION

The search for molecular structures with desirable properties is a challenging task with important applications in *de novo* drug design and materials discovery (Schneider et al., 2019). There exist a plethora of machine learning approaches to accelerate this search, including generative models based on variational autoencoders (VAEs) (Gómez-Bombarelli et al., 2018), recurrent neural networks (RNNs) (Segler et al., 2018) and generative adversarial networks (GANs) (De Cao & Kipf, 2018). However, the reliance on a sufficiently large dataset for exploring unknown regions of chemical space is a severe limitation of such supervised models. Recent RL-based methods (e.g., Olivecrona et al. (2017), Jørgensen et al. (2019), Simm et al. (2020)) mitigate the need for an existing dataset of molecules as they only require access to a reward function.

Most approaches rely on graph representations of molecules, where atoms and bonds are represented by nodes and edges, respectively. This is a strongly simplified model designed for the description of single organic molecules. It is unsuitable for encoding metals and molecular clusters as it lacks information about the relative position of atoms in 3D space. Further, geometric constraints on the design process cannot be included, e.g. those given by the active site of an enzyme. A more general representation closer to the physical system is one in which a molecule is described by its atoms' positions in Cartesian coordinates. However, it would be very inefficient to naively learn a model based on this representation. That is because molecular properties such as the energy are *invariant* (i.e. unchanged) under symmetry operations like translation or rotation of all atomic positions. A model without the right inductive bias would thus have to learn those symmetries from scratch.

In this work, we develop a novel RL approach for designing molecules in Cartesian coordinates that explicitly encodes these symmetry operations. The agent builds molecules by consecutively placing atoms such that if the generated structure is rotated or translated, the agent's action is rotated and translated accordingly; this way, the reward remains the same (see Fig. 1 (a)). We achieve this through a rotationally *covariant* state representation based on spherical harmonics, which we integrate into a novel actor-critic network architecture with an auto-regressive policy that maintains the desired covariance. Building in this inductive bias enables us to generate geometrically complex molecular structures that were unattainable with previous approaches. Finally, we perform experiments using standard policy gradient methods across several 3D molecular design tasks, including a newly proposed task that showcases the generalization capabilities of our agent.

Figure 1: **(a)** Illustration of a rotation-covariant state-action representation. If the structure is rotated by $\mathcal{R}$, the position x of the action transforms accordingly. **(b)** Rollout with bag $\mathcal{B}_0 = \mathrm{SOF}_4$. The agent builds a molecule by repeatedly taking atoms from the bag and placing them onto the 3D canvas. Bonds connecting atoms are only for illustration and not part of the MDP.

2 BACKGROUND

2.1 REINFORCEMENT LEARNING FOR MOLECULAR DESIGN

In the standard RL setting (Sutton & Barto, 2018), an agent interacts with the environment so as to maximize its reward. Formally, such an environment is described by a Markov decision process (MDP) $\mathcal{M} = (\mathcal{S}, \mathcal{A}, \mathcal{T}, \mu_0, \gamma, r)$ with states $s_t \in \mathcal{S}$, actions $a_t \in \mathcal{A}$, transition dynamics $\mathcal{T} : \mathcal{S} \times \mathcal{A} \mapsto S$, initial state distribution μ_0, discount factor $\gamma \in (0, 1]$, and reward function $r : \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R}$. The goal is to learn a stochastic policy $\pi(a_t|s_t)$ that maximizes the expected discounted return $J(\theta) = \mathbb{E}_{s_0 \sim \mu_0}[V^\pi(s_0)]$, where the value function $V^\pi(s_t) = \mathbb{E}_\pi[\sum_{t'=t}^T \gamma^{t'} r(s_{t'}, a_{t'})|s_t]$ is defined as the expected discounted return when starting from state s_t and following policy π.

Following Simm et al. (2020), we design molecules by iteratively picking atoms from a **bag** and positioning them on a 3D **canvas**. Such a sequential decision-making problem is described by an MDP where the state $s_t = (\mathcal{C}_t, \mathcal{B}_t)$ comprises both the canvas $\mathcal{C}_t$ and the bag $\mathcal{B}_t$. The canvas $\mathcal{C}_t = \mathcal{C}_0 \cup \{(e_i, x_i)\}_{i=0}^{t-1}$ is a set of atoms with chemical element $e_i \in \{\mathrm{H}, \mathrm{C}, \mathrm{N}, \mathrm{O}, \dots\}$ and position $x_i \in \mathbb{R}^3$ placed up to time $t - 1$, where $\mathcal{C}_0$ can either be empty or contain a set of initially placed atoms. The number of atoms on the canvas is denoted by $|\mathcal{C}_t|$. The bag $\mathcal{B}_t = \{(e, m(e))\}$ is a multi-set of atoms yet to be placed, where $m(e)$ is the multiplicity of the element e. Each action $a_t = (e_t, x_t)$ consists of the element $e_t \in \mathcal{B}_t$ and position $x_t \in \mathbb{R}^3$ of the next atom to be added to the canvas. Placing an atom through action a_t in state s_t is modeled by a deterministic transition function $\mathcal{T}(s_t, a_t)$ that yields the next state $s_{t+1} = (\mathcal{C}_{t+1}, \mathcal{B}_{t+1})$ with $\mathcal{B}_{t+1} = \mathcal{B}_t \backslash e_t$.

The reward function $r(s_t, a_t) = -\Delta E(s_t, a_t)$ is given by the negative energy difference between the resulting structure described by $\mathcal{C}_{t+1}$, and the sum of energies of the current structure $\mathcal{C}_t$ and a new atom of element e_t placed at the origin, i.e. $\Delta E(s_t, a_t) = E(\mathcal{C}_{t+1}) - [E(\mathcal{C}_t) + E(\{(e, \mathbf{0})\})]$. Intuitively, the reward encourages the agent to build stable, low-energy structures. We choose to evaluate the energy using the fast semi-empirical Parametrized Method 6 (PM6) (Stewart, 2007) as implemented in the software package SPARROW (Husch et al., 2018; Bosia et al., 2020); see Appendix A for details.

An example rollout is shown in Fig. 1 (b). At the beginning of the episode, the agent observes the initial state $(\mathcal{C}_0, \mathcal{B}_0) \sim \mu_0(s_0)$, e.g. $\mathcal{C}_0 = \emptyset$ and $\mathcal{B}_0 = \mathrm{SOF}_4$[1]. The agent then iteratively constructs a molecule by placing atoms from the bag onto the canvas until the bag is empty.[2]

2.2 ROTATIONALLY COVARIANT NEURAL NETWORKS

A function $f : \mathcal{X} \mapsto \mathcal{Y}$ is **invariant** under a transformation operator $T_g : \mathcal{X} \mapsto \mathcal{X}$ if $f(T_g[x]) = f(x)$ for all $x \in \mathcal{X}, g \in G$, where G is a mathematical group. In contrast, f is **covariant** with respect to T_g if there exists an operator $T'_g : \mathcal{Y} \mapsto \mathcal{Y}$ such that $f(T_g[x]) = T'_g[f(x)]$. To achieve

---

[1] Short hand for $\{(\mathrm{S}, 1), (\mathrm{O}, 1), (\mathrm{F}, 4)\}$.

[2] Hereafter, we drop the time index when it is clear from context.

rotational covariance, it is natural to work with spherical harmonics. They are a set of complex-valued functions $Y_\ell^m : \mathbb{S}^2 \mapsto \mathbb{C}$ with $\ell = 0, 1, 2, \dots$ and $m = -\ell, -\ell+1, \dots, \ell-1, \ell$ on the unit sphere $\mathbb{S}^2$ in $\mathbb{R}^3$. The first few spherical harmonics are in Appendix B. They are defined by

$$Y_\ell^m(\vartheta, \varphi) = (-1)^m \sqrt{\frac{2\ell+1}{4\pi} \frac{(\ell-m)!}{(\ell+m)!}} P_l^m(\cos(\vartheta)) e^{im\varphi}, \quad \varphi \in [0, 2\pi], \quad \vartheta \in [0, \pi], \quad (1)$$

where P_ℓ^m denotes the associated normalized Legendre polynomials of the first kind (Bateman, 1953), and each Y_ℓ^m is normalized such that $\iint |Y_\ell^m(\vartheta, \varphi)|^2 \sin\vartheta d\vartheta d\varphi = 1$. Any square-integrable function $f : \mathbb{S}^2 \mapsto \mathbb{C}$ can be written as a series expansion in terms of the spherical harmonics,

$$f(\tilde{x}) = \sum_{\ell=0}^{\infty} \sum_{m=-\ell}^{\ell} \hat{f}_\ell^m Y_\ell^m(\tilde{x}), \quad (2)$$

where $\tilde{x} = (\vartheta, \varphi) \in \mathbb{S}^2$. The complex-valued coefficients $\{\hat{f}_\ell^m\}$ are the analogs of Fourier coefficients and are given by $\hat{f}_\ell^m = \int f(\tilde{x}) Y_\ell^{m*}(\tilde{x}) \Omega(d\tilde{x})$. Such a function f can be modeled by learning the coefficients $\{\hat{f}_\ell^m\}$ using CORMORANT (Anderson et al., 2019), a neural network architecture for predicting properties of chemical systems that works entirely in Fourier space. A key feature is that each neuron is covariant to rotation but invariant to translation; further, each neuron explicitly corresponds to a subset of atoms in the molecule. The input of CORMORANT is a spherical function $f^0 : \mathbb{S}^2 \mapsto \mathbb{C}^d$ and the output is a collection of vectors $\hat{f} = \{\hat{f}_0, \hat{f}_1, \dots, \hat{f}_L\}$, where each $\hat{f}_\ell \in \tau \times (2\ell+1)$ is a rotationally covariant vector with τ channels. That is, if the input is rotated by $\mathcal{R} \in \mathrm{SO}(3)$, then each $\hat{f}_\ell$ transforms as $\hat{f}_\ell \mapsto D^\ell(\mathcal{R})\hat{f}_\ell$, where $D^\ell(\mathcal{R}) : \mathrm{SO}(3) \mapsto \mathbb{C}^{(2\ell+1)\times(2\ell+1)}$ are the irreducible representations of $\mathrm{SO}(3)$, also called the Wigner D-matrices.

3 COVARIANT POLICY FOR MOLECULAR DESIGN

An efficient RL agent needs to exploit the symmetries of the molecular design process. Therefore, we require a policy $\pi(a|s)$ with actions $a = (e, x)$ that is covariant under translation and rotation with respect to the position x, i.e., x should rotate (or translate) accordingly if the atoms on the canvas $\mathcal{C}$ are rotated (or translated). In contrast, the policy needs to be invariant with respect to element e, i.e. the chosen element remains unchanged under such transformations (see Fig. 1 (a)). Since learning such a policy is difficult when working directly in global Cartesian coordinates, we instead follow Simm et al. (2020) and use an action representation that is local with respect to an already placed **focal atom**. If the next atom is placed relative to the focal atom, covariance under translation of x is automatically achieved and only the rotational covariance remains to be dealt with.

As shown in Fig. 2, we model the action a through a sequence of sub-actions: (1) the index[3] $f \in \{1, \dots, |\mathcal{C}|\}$ of the focal atom around which the next atom is placed, (2) the element $e \in \{1, \dots, N_e\}$ of the next atom from the set of available elements, (3) a distance $d \in \mathbb{R}_+$ between the focal atom and the next atom, and (4) the orientation $\tilde{x} = (\vartheta, \varphi) \in \mathbb{S}^2$ of the atom on a unit sphere around the focal atom. Denoting x_f as the position of the focal atom, we obtain action $a = (e, x)$ by mapping the local coordinates $(\tilde{x}, d, f)$ to global coordinates $x = x_f + d \cdot \tilde{x}$, where x is now covariant under translation *and* rotation. We choose these sub-actions using the following auto-regressive policy:

$$\pi(a|s) = \pi(\tilde{x}, d, e, f|s) = p(\tilde{x}|d, e, f, s)\, p(d|e, f, s)\, p(e|f, s)\, p(f|s). \quad (3)$$

A novel actor-critic neural network architecture that implements this policy is illustrated in Fig. 3. In the following, we discuss its state embedding, actor and critic networks in more detail.

3.1 STATE EMBEDDING

The state embedding network transforms canvas $\mathcal{C}$ and bag $\mathcal{B}$ to obtain a rotationally covariant and translationally invariant representation. For that, we concatenate a vectorized representation of the bag with each atom on the canvas and feed it into CORMORANT, i.e. $s^{\mathrm{cov}} \leftarrow \mathrm{CORMORANT}(\mathcal{C}, \mathcal{B})$, where $s^{\mathrm{cov}} = \{s_\ell^{\mathrm{cov}}\}_{\ell=0}^{L_{\max}}$, $s_\ell^{\mathrm{cov}} \in \mathbb{C}^{|\mathcal{C}| \times \tau \times (2\ell+1)}$, and τ is the number of channels. For the sake of

---

[3]If the canvas $\mathcal{C}_0$ is empty, the agent selects an element $e_0 \in \mathcal{B}_0$ and places it at the origin, i.e. $a_0 = (e_0, \mathbf{0})$.

Figure 2: Action representation of the auto-regressive policy. The agent chooses focal atom f, element e, distance d and orientation $\tilde{x}$. We then map back to global coordinates x to obtain action $a = (e, x)$. Bonds between atoms are only for illustration.

Figure 3: Illustration of the state embedding, actor and critic networks. Both canvas $\mathcal{C}$ and bag $\mathcal{B}$ are fed to the **state embedding** network CORMORANT to obtain rotation-covariant (s^{cov}) and -invariant (s^{inv}) state representations. The **actor** network then samples the different sub-actions highlighted in bold. The **critic** takes the invariant representation s^{inv} to compute a value V.

exposition, we assume a single channel for each element in the bag, i.e. $\tau = N_e$ (cf. Fig 3); in practice, we use up to four channels per element.

However, not every sub-action in Eq. (3) should transform equally under rotation and translation. While the orientation $\tilde{x}$ needs to be *covariant* under rotation, the choice of focal atom f, element e, and distance d have to be *invariant* to rotation and translation. For these sub-actions, we additionally require an invariant state representation. To obtain such a representation $s^{\text{inv}} \in \mathbb{R}^{|\mathcal{C}| \times k}$, we employ a combination of transformations from Anderson et al. (2019) as listed in Appendix C (e.g. for $\ell = 0$, one can simply select the $s^{\text{cov}}_{\ell=0}$ component), which we collectively denote as $\mathcal{T}_{\text{inv}}$.

3.2 ACTOR

Focal Atom and Element The distribution $p(f|s)$ over the focal atom f is modeled as categorical, $f \sim \text{Cat}(f; h_f)$, where h_f are the logits for each atom in $\mathcal{C}$ predicted by a multi-layer perceptron (MLP). Likewise, the distribution over the element e is given by $p(e|f, s) = \text{Cat}(e; h_e)$

with $h_e = \text{MLP}_e(s_f^{\text{inv}})$, where s_f^{inv} is the invariant representation for the focal atom. Since the number of possible focal atoms f increases and the set of available elements e decreases during a rollout, we mask out invalid focal atoms $f \notin \{1, \dots, |\mathcal{C}_t|\}$ and elements $e \notin \mathcal{B}_t$ by setting their probabilities to zero and re-normalizing the categorical distributions. The agent does *not* make use of chemical concepts like bond connectivity to aid the choice of the focal atom.

Distance We select the channel τ_e corresponding to element e from s_f^{cov} to obtain $s_{f,e}^{\text{cov}} := \{s_{\ell_{f,e}}^{\text{cov}}\}_{\ell=0,\dots,L_{\max}}$ and $s_{f,e}^{\text{inv}} \leftarrow \mathcal{T}_{\text{inv}}(s_{f,e}^{\text{cov}})$. Then we model the distribution over the distance d between the focal atom and the next atom to be placed as a mixture of M Gaussians, $p(d|e, f, s) = \sum_{m=1}^{M} \pi_m \mathcal{N}(\mu_m, \sigma_m^2)$, where π_m is the mixing coefficient of the m-th Gaussian $\mathcal{N}(\mu_m, \sigma_m^2)$. The mixing coefficients and the means are predicted by a mixture density network (MDN) (Bishop, 1994), i.e. $\{\pi_m, \mu_m\}_{m=1}^{M} = \text{MDN}(s_{f,e}^{\text{inv}})$. The standard deviations $\{\sigma_m\}_{m=1}^{M}$ are global parameters. We guarantee that the sampled distances are positive by clipping values below zero.

Combining Invariant and Covariant Features The choice of distance d can significantly affect the orientation $\tilde{x}$ of the atom. For example, if d has the length of a triple bond, then $\tilde{x}$ will be very different from if it was a single bond. Thus, we condition $s_{f,e}^{\text{cov}}$ on distance d through a non-linear and learnable transformation that preserves rotational covariance. We then use this representation to model a spherical distribution over $\tilde{x}$. Kondor & Trivedi (2018) showed that a linear transformation with learnable parameters is only covariant if the operation combines fragments with the same ℓ. Further, the Clebsch-Gordan (CG) non-linearity allows to combine two covariant features such that the result is still covariant. Thus, we obtain a rotationally covariant representation $\hat{r} := \{\hat{r}_\ell\}_{\ell=0,\dots,L_{\max}} \leftarrow \mathcal{T}_{\text{cov}}(d, s_{f,e}^{\text{cov}})$ conditioned on all previous sub-actions as follows:

$$\hat{r}_\ell = \left[s_{\ell_{f,e}}^{\text{cov}} \oplus d \cdot s_{\ell_{f,e}}^{\text{cov}} \oplus (d \cdot s_{f,e}^{\text{cov}} \otimes_{\text{cg}} d \cdot s_{f,e}^{\text{cov}})_\ell \right] \cdot W_\ell \quad \forall \ell, \tag{4}$$

where $\oplus$ denotes the appropriate concatenation of matrices, and W_ℓ is a learnable complex-valued matrix. As in Anderson et al. (2019), we perform the CG product $\otimes_{\text{cg}}$ only channel-wise to reduce computational complexity.

Orientation Next, we utilize $\hat{r}$ to obtain a rotationally covariant spherical distribution for the orientation $\tilde{x}$ based on the series expansion in Eq. (2). Taking inspiration from commonly used distributions (Jammalamadaka & Terdik, 2019), we propose to use the following expression:

$$p(\tilde{x}|d, e, f, s) = \frac{1}{Z} \exp\left(-\beta \left| \frac{1}{\sqrt{k}} \sum_{\ell=0}^{L_{\max}} \sum_{m=-\ell}^{\ell} \hat{r}_\ell^m Y_\ell^m(\tilde{x}) \right|^2 \right), \tag{5}$$

where $\beta \in \mathbb{R}$ is a scaling parameter, and the term $1/\sqrt{k}$ with $k = \sum_{\ell=0}^{L_{\max}} \sum_{m=-\ell}^{\ell} |\hat{r}_\ell^m|^2$ regularizes the distribution so that it does not approach a delta function. The normalization constant Z is estimated via Lebedev quadrature (Lebedev, 1975; 1977). We sample from the distribution in Eq. (5) using rejection sampling (Bishop, 2009) with a uniform proposal distribution $q(\tilde{x}) = (4\pi)^{-1}$. Note that in contrast to more commonly used parametric distributions (e.g. von Mises-Fisher), this formulation allows to model multi-modalities. We discuss alternatives to Eq. (5) in Appendix D.

3.3 CRITIC

The critic needs to compute a value V for the state s that is invariant under translation and rotation. Given s^{inv}, we apply a permutation-invariant set encoding (Zaheer et al., 2017) of the atoms, i.e.

$$V(s) = \text{MLP}_\rho \left(\sum_{i=1}^{|\mathcal{C}|} \text{MLP}_\phi(s_i^{\text{inv}}) \right). \tag{6}$$

Finally, we use PPO (Schulman et al., 2017) to learn the parameters of the actor-critic architecture. To encourage sufficient exploration, we add an entropy regularization term over the categorical sub-action distributions of the auto-regressive policy. For offline evaluation, we evaluate the policy without any exploration by choosing the most probable action. While the mode of the distributions for f and e is available in closed form, we approximate the global mode of the distributions over d and $\tilde{x}$ by evaluating the density at S samples and picking the one with the highest density.

4 RELATED WORK

Reinforcement Learning for Molecular Design   There exist a large variety of RL-based approaches for molecular design using either string- or graph-based representations of molecules (Olivecrona et al., 2017; Guimaraes et al., 2018; Putin et al., 2018; Neil et al., 2018; Popova et al., 2018; You et al., 2018; Zhou et al., 2019). However, the choice of representation limits the molecules that can be generated to a (small) region of chemical space for which the representation is applicable, i.e., single organic molecules. Such representations also prohibit the use of reward functions based on quantum-mechanical properties; instead, heuristics are often used. Lastly, geometric constraints on the design process cannot be imposed as the representation does not include any 3D information.

Molecular Design in Cartesian Coordinates   Another downside of string- and graph-based approaches is their neglect of information encoded in the interatomic distances. In light of this, Gebauer et al. (2018; 2019) proposed a supervised generative neural network for sequentially placing atoms in Cartesian coordinates. While the model respects local symmetries by construction, atoms are placed on a 3D grid. Similar to other supervised approaches, one further requires a dataset that covers the particular class of molecules to be generated. Hammer and coworkers (Jørgensen et al., 2019; Meldgaard et al., 2020) employed a Deep Q-Network (Mnih et al., 2015) to build 2D structures and planar compounds by placing atoms on a grid.

Simm et al. (2020) presented an RL formulation for molecular design in continuous 3D space. The agent models the position of the next atom to be placed in internal coordinates—i.e. the distance, angle and dihedral angle with respect to already existing atoms—which are invariant under translation and rotation. By mapping from internal to Cartesian coordinates, they then obtain a policy that is covariant under these symmetry operations. However, choosing the atoms acting as reference points for the internal coordinates can be problematic in highly symmetric states (as commonly encountered in materials, for example). Further, the distributions over internal coordinates were modeled as factorized Gaussians, which cannot naturally handle periodicity.

Covariant Neural Networks in Chemical Science   Prior work employed rotationally covariant neural networks to predict translation- and rotation-invariant physical properties (Thomas et al., 2018; Kondor et al., 2018; Weiler et al., 2018; Anderson et al., 2019; Miller et al., 2020; Finzi et al., 2020; Fuchs et al., 2020), e.g. scalars such as the electronic energy. In contrast, we propose a translation-invariant and rotation-covariant neural network architecture for generating molecules. For a more general treatment of covariance (or equivariance) in RL, see van der Pol et al. (2020).

5 EXPERIMENTS

We perform experiments to answer the following questions: (1) is the agent able to learn to build geometrically complex molecules in Cartesian coordinates from scratch, (2) can we increase the validity and diversity of generated molecules, and (3) does our approach lead to improved generalization? We address (1) and (2) by evaluating the agent on a diverse range of tasks from the MOLGYM benchmark suite (Simm et al., 2020), and (3) on a newly proposed *stochastic-bag* task (see Section 5.1) where bags are sampled from a distribution over bags.[4]

We compare our approach (COVARIANT) against the RL agent proposed by Simm et al. (2020), which iteratively builds molecules on a 3D canvas by working in internal coordinates (INTERNAL). As an additional baseline we consider a classical, optimization-based agent (OPT) with access to a black-box function that yields the energy $E(\mathcal{C})$ and the atomic forces $F(\mathcal{C})$ for a given canvas.[5] The agent constructs molecules by alternating between randomly placing an atom and optimizing the structure. Moreover, the agent applies several heuristics inspired by fundamental chemical concepts to guide the random placement of atoms. To make the comparisons fair, we grant OPT a comparable computational budget in terms of the total number of energy computations. Finally, for some experiments the best possible performance based on quantum-chemical calculations can be reported. See Appendices E and F for more details on the baselines and experimental settings.

---

[4]Source code will be made available upon publication.

[5]For the calculation of $E(\mathcal{C})$ and $F(\mathcal{C})$ we employ PM6; the same method as in the reward function.

Figure 4: **(a)** Average offline performance on the *single-bag* task with bags SOF_4 (left) and IF_5 (right) across 10 seeds. In the lower right, molecular structures generated by the agents are shown. Dashed lines denote the optimal return for each experiment. Error bars show two standard deviations. **(b)** Further molecular structures generated by COVARIANT, namely SOF_6 and SF_6.

5.1 STOCHASTIC-BAG TASK

In Simm et al. (2020), a set of molecular design tasks was introduced: the *single-bag* task assesses an agent's ability to build single stable molecules, whereas the *multi-bag* task focuses on building several molecules of different composition and size at the same time. A limitation of these tasks is that the initial bags were selected such that they correspond to known formulas, which in practice might not be known a priori. In the *stochastic-bag* task, we relax this assumption by sampling from a more general distribution over bags. Before each episode, we construct a bag $\mathcal{B} = \{(e, m(e))\}$ by sampling counts $(m(e_1), ..., m(e_{max})) \sim \text{Mult}(\zeta, p_e)$, where the bag size ζ is sampled uniformly from the interval $[\zeta_{min}, \zeta_{max}]$. Here, we obtain an empirical distribution p_e from the multiplicities $m(e)$ of a given bag $\mathcal{B}^*$. For example, with $\mathcal{B}^* = \{(H, 2), (O, 1)\}$ we obtain $p_H = \frac{2}{3}$ and $p_O = \frac{1}{3}$. Since sampled bags might no longer correspond to valid molecules when placed completely, we discard bags where the sum of valence electrons over all atoms contained in the bag is odd. This ensures that the agent is able to build a *closed-shell* system.

5.2 RESULTS

Building Geometrically Complex Molecules First, we evaluate the ability to build stable molecules featuring complex geometries on the *single-bag* task with bags SOF_4, IF_5, SOF_6 and SF_6. As shown in Fig. 4 (a), COVARIANT is able to solve the task for SOF_4 and IF_5 within 30 000 to 40 000 steps, whereas INTERNAL fails to build low-energy configurations as it cannot distinguish highly symmetric intermediates. Further results in Fig. 4 (b) for SOF_6 and SF_6 show that COVARIANT is capable of building such structures. OPT found the optimal structures for all four bags.

Validity and Diversity of Generated Molecules Similar to the *GuacaMol* benchmark (Brown et al., 2019), we compare the chemical *validity* and *diversity* of the molecules generated by the agents for different experiments. A molecule is considered valid if it can be successfully parsed by RDKIT (Landrum, 2019). The *validity* reported in Table 1 is the ratio of valid molecules generated during offline evaluation at the end of training over 10 seeds. Two molecules are considered identical if the SMILES strings generated by RDKIT are the same. The *diversity* shown in Table 1 is the total number of unique and valid structures generated during offline evaluation throught the course of training over 10 seeds.[6] In the two *stochastic-bag* experiments, the agents are trained on bags of sizes from the interval $[16, 22]$ sampled with $\mathcal{B}^* = C_7H_8N_2O_2$ and $C_7H_{10}O_2$, respectively.

Results are listed in Table 1. We observe that COVARIANT significantly outperforms the other agents on most experiments both in terms of validity and diversity. The difference is particularly large for

---

[6]For a fairer comparison in the *stochastic-bag* task, we use the structures generated during offline evaluation, instead of those generated during training as in Simm et al. (2020).

Table 1: Validity and diversity of generated structures in different experiments.

Task	Experiment	Validity			Diversity		
		OPT	INTERNAL	COVARIANT	OPT	INTERNAL	COVARIANT
Single-bag	$C_3H_5NO_3$	0.06	0.70	0.90	19	35	65
	C_4H_7N	0.10	0.80	0.70	35	18	25
	C_3H_8O	0.06	0.90	0.80	2	4	8
	$C_7H_{10}O_2$	0.05	0.50	0.80	10	21	85
	$C_7H_8N_2O_2$	0.03	0.60	0.70	5	58	118
Multi-bag		0.54	0.78	0.89	22	19	42
Stochastic-bag	$C_7H_{10}O_2$	0.05	0.40	0.60	10	26	59
	$C_7H_8N_2O_2$	0.03	0.10	0.80	5	28	84
Stochastic-bag (generalization)	$C_7H_0O_2$	0.00	0.00	0.13	0	38	68
	$C_7H_8N_2O_2$	0.00	0.05	0.30	0	40	227

the more challenging *stochastic-bag* tasks, where COVARIANT does similarly well as on the *single-bag* experiments. This finding is confirmed in Fig. 5 (a), showing that the exact stoichiometry does not need to be known a priori for the agent to build valid molecules. In contrast, OPT often fails to build valid structures. Inspection of the generated structures reveals that for larger bags the agent tends to build multi-molecular clusters, which are considered invalid in this experiment.

Generalization We train on a distribution over bags with $\mathcal{B}^* = C_7H_{10}O_2$ and $C_7H_8N_2O_2$, and test on sets of larger, out-of-distribution bags $\{C_6H_{14}O_3, C_7H_{16}O, C_7H_{16}O_2, C_8H_{18}O\}$, and $\{C_8H_{12}N_2O, C_6H_{12}N_2O_3, C_7H_{14}N_2O, C_7H_{14}N_2O_2\}$ respectively. As shown in Fig. 5 (b), CO-VARIANT obtains higher average returns with lower variance compared to INTERNAL on $C_7H_{10}O_2$, while performing only slightly worse than the agent trained directly on the test bags (purple). Results for $C_7H_8N_2O_2$ are in Appendix G. Table 1 highlights the higher quality of the generated structures, indicating better generalization to unseen bags of larger size. OPT fails completely at this task.

Figure 5: Average offline performance on the *stochastic-bag* task with $\mathcal{B}^* = C_7H_{10}O_2$ evaluated on (a) $C_7H_{10}O_2$ and (b) larger, unseen bags $\{C_6H_{14}O_3, C_7H_{16}O, C_7H_{16}O_2, C_8H_{18}O\}$ over 10 seeds. For comparison, we show an agent trained only on the test bags (purple). Error bars are two standard deviations. Molecular structures generated by COVARIANT (Stochastic) are shown.

6 CONCLUSION

We proposed a novel covariant actor-critic architecture based on spherical harmonics for designing geometrically complex molecules in 3D. We showed empirically that exploiting symmetries of the molecular design process improves the quality of the generated molecules and leads to better generalization. In future work, we aim to employ more accurate quantum-chemical methods (e.g., density function theory) required for building transition metal complexes or structures in which weak intermolecular interactions are important. For that, however, the sample-efficiency of our agent needs to be improved. Finally, we aim to explore reward functions specifically tailored towards drug design.

REFERENCES

Brandon Anderson, Truong Son Hy, and Risi Kondor. Cormorant: Covariant Molecular Neural Networks. In *Advances in Neural Information Processing Systems 32*, pp. 14537–14546. Curran Associates, Inc., 2019.

Harry Bateman. *Higher Transcendental Functions*, volume I-III. McGraw-Hill Book Company, New York, 1953.

Christopher M Bishop. Mixture density networks. Technical report, Aston University, 1994.

Christopher M. Bishop. Rejection sampling. In *Pattern Recognition and Machine Learning*, Information Science and Statistics, pp. 528–530. Springer, New York, 2009. ISBN 978-0-387-31073-2.

Francesco Bosia, Tamara Husch, Alain C. Vaucher, and Markus Reiher. QCScine Sparrow: Release 2.0.1. https://doi.org/10.5281/zenodo.3907313, 2020.

Nathan Brown, Marco Fiscato, Marwin H.S. Segler, and Alain C. Vaucher. GuacaMol: Benchmarking Models for de Novo Molecular Design. *J. Chem. Inf. Model.*, 59(3):1096–1108, 2019.

Nicola De Cao and Thomas Kipf. MolGAN: An implicit generative model for small molecular graphs. *arXiv preprint arXiv:1805.11973*, 2018.

Marc Finzi, Samuel Stanton, Pavel Izmailov, and Andrew Gordon Wilson. Generalizing Convolutional Neural Networks for Equivariance to Lie Groups on Arbitrary Continuous Data. *arXiv preprint arXiv:2002.12880*, 2020.

Fabian B Fuchs, Daniel E Worrall, Volker Fischer, and Max Welling. SE (3)-transformers: 3D roto-translation equivariant attention networks. *arXiv preprint arXiv:2006.10503*, 2020.

Niklas W. A. Gebauer, Michael Gastegger, and Kristof T. Schütt. Generating equilibrium molecules with deep neural networks. *arXiv preprint arXiv:1810.11347*, 2018.

Niklas W. A. Gebauer, Michael Gastegger, and Kristof T. Schütt. Symmetry-adapted generation of 3D point sets for the targeted discovery of molecules. In *Advances in Neural Information Processing Systems*, pp. 7564–7576, 2019.

Rafael Gómez-Bombarelli, Jennifer N. Wei, David Duvenaud, José Miguel Hernández-Lobato, Benjamín Sánchez-Lengeling, Dennis Sheberla, Jorge Aguilera-Iparraguirre, Timothy D. Hirzel, Ryan P. Adams, and Alán Aspuru-Guzik. Automatic Chemical Design Using a Data-Driven Continuous Representation of Molecules. *ACS Cent. Sci.*, 4(2):268–276, 2018.

Gabriel Lima Guimaraes, Benjamin Sanchez-Lengeling, Carlos Outeiral, Pedro Luis Cunha Farias, and Alán Aspuru-Guzik. Objective-Reinforced Generative Adversarial Networks (ORGAN) for Sequence Generation Models. *arXiv preprint arXiv:1705.10843*, 2018.

J. D. Hunter. Matplotlib: A 2D graphics environment. *Comput. Sci. Eng.*, 9(3):90–95, 2007.

Tamara Husch and Markus Reiher. Comprehensive Analysis of the Neglect of Diatomic Differential Overlap Approximation. *J. Chem. Theory Comput.*, 14(10):5169–5179, 2018.

Tamara Husch, Alain C. Vaucher, and Markus Reiher. Semiempirical molecular orbital models based on the neglect of diatomic differential overlap approximation. *Int. J. Quantum Chem.*, 118 (24):e25799, 2018.

S. Rao Jammalamadaka and György H. Terdik. Harmonic analysis and distribution-free inference for spherical distributions. *J. Multivar. Anal*, 171:436–451, 2019.

Mathias S. Jørgensen, Henrik L. Mortensen, Søren A. Meldgaard, Esben L. Kolsbjerg, Thomas L. Jacobsen, Knud H. Sørensen, and Bjørk Hammer. Atomistic structure learning. *J. Chem. Phys.*, 151(5):054111, 2019.

Risi Kondor and Shubhendu Trivedi. On the Generalization of Equivariance and Convolution in Neural Networks to the Action of Compact Groups. In *International Conference on Machine Learning*, pp. 2747–2755. PMLR, 2018.

Risi Kondor, Zhen Lin, and Shubhendu Trivedi. Clebsch– Gordan Nets: A Fully Fourier Space Spherical Convolutional Neural Network. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 10117–10126. Curran Associates, Inc., 2018.

Gregory Landrum. RDKit 2019.09.3. http://www.rdkit.org/, 2019. (Accessed: 22. January 2019).

V. I. Lebedev. Values of the nodes and weights of ninth to seventeenth order gauss-markov quadrature formulae invariant under the octahedron group with inversion. *Zh. Vychisl. Mat. Mat. Fiz.*, 15(1):44–51, 1975.

V. I. Lebedev. Spherical quadrature formulas exact to orders 25–29. *Sibirsk. Mat. Zh.*, 18(1):99–107, 1977.

Wes McKinney. Data Structures for Statistical Computing in Python. In Stéfan van der Walt and Jarrod Millman (eds.), *Proceedings of the 9th Python in Science Conference*, pp. 51–56, 2010.

Søren A. Meldgaard, Henrik L. Mortensen, Mathias S. Jørgensen, and Bjørk Hammer. Structure prediction of surface reconstructions by deep reinforcement learning. *J. Phys.: Condens. Matter*, 32(40):404005, 2020.

Benjamin Kurt Miller, Mario Geiger, Tess E. Smidt, and Frank Noé. Relevance of Rotationally Equivariant Convolutions for Predicting Molecular Properties. *arXiv preprint arXiv:2008.08461*, 2020.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A. Rusu, Joel Veness, Marc G. Bellemare, Alex Graves, Martin Riedmiller, Andreas K. Fidjeland, Georg Ostrovski, Stig Petersen, Charles Beattie, Amir Sadik, Ioannis Antonoglou, Helen King, Dharshan Kumaran, Daan Wierstra, Shane Legg, and Demis Hassabis. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.

Daniel Neil, Marwin Segler, Laura Guasch, Mohamed Ahmed, Dean Plumbley, Matthew Sellwood, and Nathan Brown. Exploring Deep Recurrent Models with Reinforcement Learning for Molecule Design. *OpenReview*, 2018. URL https://openreview.net/forum?id=HkcTe-bR-.

Marcus Olivecrona, Thomas Blaschke, Ola Engkvist, and Hongming Chen. Molecular de-novo design through deep reinforcement learning. *J. Cheminf.*, 9(1):48, 2017.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. PyTorch: An Imperative Style, High-Performance Deep Learning Library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8026–8037. Curran Associates, Inc., 2019.

Mariya Popova, Olexandr Isayev, and Alexander Tropsha. Deep reinforcement learning for de novo drug design. *Sci. Adv.*, 4(7):eaap7885, 2018.

Evgeny Putin, Arip Asadulaev, Yan Ivanenkov, Vladimir Aladinskiy, Benjamin Sanchez-Lengeling, Alán Aspuru-Guzik, and Alex Zhavoronkov. Reinforced Adversarial Neural Computer for de Novo Molecular Design. *J. Chem. Inf. Model.*, 58(6):1194–1204, 2018.

Petra Schneider, W. Patrick Walters, Alleyn T. Plowright, Norman Sieroka, Jennifer Listgarten, Robert A. Goodnow, Jasmin Fisher, Johanna M. Jansen, José S. Duca, Thomas S. Rush, Matthias Zentgraf, John Edward Hill, Elizabeth Krutoholow, Matthias Kohler, Jeff Blaney, Kimito Funatsu, Chris Luebkemann, and Gisbert Schneider. Rethinking drug design in the artificial intelligence era. *Nat. Rev. Drug Discovery*, pp. 1–12, 2019.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Marwin H. S. Segler, Thierry Kogej, Christian Tyrchan, and Mark P. Waller. Generating Focused Molecule Libraries for Drug Discovery with Recurrent Neural Networks. *ACS Cent. Sci.*, 4(1): 120–131, 2018.

Gregor NC Simm, Robert Pinsler, and José Miguel Hernández-Lobato. Reinforcement learning for molecular design guided by quantum mechanics. In *International Conference on Machine Learning*, 2020. URL `http://arxiv.org/abs/2002.07717`.

James J. P. Stewart. Optimization of parameters for semiempirical methods V: Modification of NDDO approximations and application to 70 elements. *J. Mol. Model.*, 13(12):1173–1213, 2007.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

Nathaniel Thomas, Tess Smidt, Steven Kearnes, Lusann Yang, Li Li, Kai Kohlhoff, and Patrick Riley. Tensor field networks: Rotation- and translation-equivariant neural networks for 3D point clouds. *arXiv preprint arXiv:1802.08219*, 2018.

Elise van der Pol, Daniel E Worrall, Herke van Hoof, Frans A Oliehoek, and Max Welling. MDP homomorphic networks: Group symmetries in reinforcement learning. *arXiv preprint arXiv:2006.16908*, 2020.

Maurice Weiler, Mario Geiger, Max Welling, Wouter Boomsma, and Taco S Cohen. 3D Steerable CNNs: Learning Rotationally Equivariant Features in Volumetric Data. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 10381–10392. Curran Associates, Inc., 2018.

Jiaxuan You, Bowen Liu, Zhitao Ying, Vijay Pande, and Jure Leskovec. Graph Convolutional Policy Network for Goal-Directed Molecular Graph Generation. In *Advances in Neural Information Processing Systems*, pp. 6410–6421, 2018.

Manzil Zaheer, Satwik Kottur, Siamak Ravanbakhsh, Barnabas Poczos, Russ R Salakhutdinov, and Alexander J Smola. Deep sets. In *Advances in Neural Information Processing Systems*, pp. 3391–3401, 2017.

Zhenpeng Zhou, Steven Kearnes, Li Li, Richard N. Zare, and Patrick Riley. Optimization of Molecules via Deep Reinforcement Learning. *Sci. Rep.*, 9(1):1–10, 2019.

A   REWARD CALCULATION

In the reward function, the energy E has to be computed using quantum-chemical methods. For that we use the fast semi-empirical Parametrized Method 6 (PM6) (Stewart, 2007). In particular, we use the implementation from the software package SPARROW (Husch et al., 2018; Bosia et al., 2020). For each calculation, a molecular charge of zero and the lowest possible spin multiplicity are chosen. All calculations are spin-unrestricted.

Limitations of semi-empirical methods are highlighted in, for example, recent work by Husch & Reiher (2018). More accurate methods such as approximate density functionals need to be employed especially for systems containing transition metals.

Further, we enforce that atoms are not placed too close (< 0.6 Å) nor too far away from each other (> 2.0 Å). If the agent places an atom outside these boundaries, the minimum reward of -0.6 is awarded and the episode terminates. Further, the environment encourages the agents to build single molecular structures by terminating the episode and return a reward of -0.6 if elements forming stable bimolecular compounds (e.g, H_2) are placed too far away from other atoms on the canvas.

B   SPHERICAL HARMONICS

The spherical harmonics form an orthonormal basis of the Hilbert space of square-integrable functions $L^2_{\mathbb{C}}(\mathcal{S}^2)$. The first few spherical harmonics are given by:

$$Y_0^0(\vartheta, \varphi) = \frac{1}{2\sqrt{\pi}}, \tag{7}$$

$$Y_1^{-1}(\vartheta, \varphi) = \sqrt{\frac{3}{8\pi}} \sin\vartheta e^{-i\varphi}, \quad Y_1^0(\vartheta, \varphi) = \sqrt{\frac{3}{4\pi}} \cos\vartheta, \quad Y_1^1(\vartheta, \varphi) = -\sqrt{\frac{3}{8\pi}} \sin\vartheta e^{i\varphi}, \tag{8}$$

$$Y_2^{-2}(\vartheta, \varphi) = \sqrt{\frac{15}{32\pi}} \sin^2\vartheta e^{-i2\varphi}, \quad Y_2^{-1}(\vartheta, \varphi) = \sqrt{\frac{15}{8\pi}} \cos\vartheta \sin\vartheta e^{-i\varphi},$$

$$Y_2^0(\vartheta, \varphi) = \sqrt{\frac{5}{16\pi}} \left(3\cos^2\vartheta - 1\right), \tag{9}$$

$$Y_2^1(\vartheta, \varphi) = -\sqrt{\frac{15}{8\pi}} \cos\vartheta \sin\vartheta e^{i\varphi}, \quad Y_2^2(\vartheta, \varphi) = \sqrt{\frac{15}{32\pi}} \sin^2\vartheta e^{i2\varphi}.$$

The spherical harmonics are normalized such that:

$$\int_0^{2\pi} \int_0^\pi |Y_\ell^m(\vartheta, \varphi)|^2 \sin\vartheta d\vartheta d\varphi = 1 \qquad \forall \ell, m. \tag{10}$$

C   CALCULATION OF INVARIANT FEATURES

One can obtain scalar invariats from the covariant features $\hat{f}$ (Anderson et al., 2019):

- Take the component $\ell = 0$: $\xi_1(\hat{f}) = \hat{f}_{\ell=0}$.
- Calculate the scalar product with itself: $\xi_2(\hat{f}_\ell) = \text{Re}[\tilde{\xi}_2(\hat{f})] + \text{Im}[\tilde{\xi}_2(\hat{f})]$, where $\tilde{\xi}_2(\hat{f}) = \sum_{m=-\ell}^\ell (-1)^m \hat{f}_\ell^m \hat{f}_\ell^{-m}$.
- Calculate the SO(3)-invariant norm: $\xi_3(\hat{f}_\ell) = \sum_{m=-\ell}^\ell \hat{f}_\ell^m \left(\hat{f}_\ell^m\right)^*$, where $*$ denotes the complex conjugate.

The invariant components are then concatenated $f^{\text{inv}} \leftarrow \mathcal{T}_{\text{inv}} = \xi_1(\hat{f}) \oplus \left(\bigoplus_{\ell=0}^L \xi_2(\hat{f}_\ell) \oplus \xi_3(\hat{f}_\ell)\right)$.

D   PROBABILITY DISTRIBUTION FOR ORIENTATION

In the main paper, we propose the expression in Eq. (5) for the distribution $p(\tilde{x}|d, e, f, s)$. An alternative, equally valid expression is

$$p(\tilde{x}|d, e, f, s) = \left| \sum_{\ell=0}^{L_{\max}} \sum_{m=-\ell}^{\ell} \frac{1}{\sqrt{k}} \hat{r}_\ell^m Y_\ell^m(\tilde{x}) \right|^2, \tag{11}$$

where the term $1/\sqrt{k}$ with $k = \sum_{\ell=0}^{L_{\max}} \sum_{m=-\ell}^{\ell} |\hat{r}_\ell^m|^2$ normalizes the distribution. We found experimentally that an agent using this expression performs worse when generating molecular structures feature complex geometries. We hypothesize that this is because the distribution cannot not get peaked enough for $L_{\max} \leq 5$. As larger $L_{\max}$ would result in a significant increase in computational complexity, we chose the expression in Eq. (5) over that in Eq. (11).

The normalization constant Z in Eq. (5) is estimated via Lebedev quadrature with 1730 angular grid points (Lebedev, 1975; 1977). We sample from the distribution in Eq. (5) using rejection sampling (Bishop, 2009) with a uniform proposal distribution $q(\tilde{x}) = \frac{1}{4\pi}$. In rejection sampling, one first draws a sample from $\tilde{x}_0$ from $q(\tilde{x})$. Then, one generates a random number u_0 from the uniform distribution over $[0, Mq(\tilde{x}_0)]$, where M is such that $Mq(\tilde{x}) \geq p(\tilde{x}|d, e, f, s)$. We determine M by evaluating $p(\tilde{x}|d, e, f, s)$ on a uniform grid on $\mathcal{S}^2$ employing a Fibonacci 'sunflower' grid. Finally, if $u_0 > p(\tilde{x}|d, e, f, s)$ then the sample is accepted.

E   BASELINES

E.1   OPT AGENT

Below, we detail the algorithm of the OPT agent. At the beginning of each experiment, the agent is given a canvas $\mathcal{C}_0$, a bag $\mathcal{B}_0$, and a black-box function that can compute the energy $E(\mathcal{C})$ and the atomic forces $F(\mathcal{C})$ for a given canvas. We assume a total charge of zero and a low-spin configuration. At the end of each experiment, we compute the total reward obtained for the final structure on canvas $\mathcal{C}_T$ and report the total number of energy and gradient computations.

1. If the canvas $\mathcal{C}_t$ is not empty, randomly choose a focal atom f from the list of available atoms on the canvas. An atom is considered available if its number of neighbors is less than a predefined number that depends on its element (e.g., one for hydrogen and four for carbon). Two atoms on the canvas are neighbors if their Euclidean distance is below 1.5 Å. If there are no available atoms on the canvas, a focal atom is randomly chosen from the list of atoms on the canvas.

2. Randomly choose an element e_t from the bag $\mathcal{B}_t$.

3. Randomly place the atom $a_t = (e_t, x_t)$ on a sphere with radial distance $d = 1.1$ Å around x_f to obtain $\mathcal{C}_{t+1,\text{raw}}$. If the canvas is empty, place the atom at the origin.

4. Optimize only the position of a_t using F to obtain $\mathcal{C}_{t+1,\text{opt}}$.

5. Compute the energy difference $\Delta E(t) = E(\mathcal{C}_{t+1,\text{opt}}) - [E(\mathcal{C}_t) + E(\{e_t, \mathbf{0}\})]$.

6. If $\Delta E(t) > 0$, return e_t to the bag and go back to step 1.

7. Optimize canvas $\mathcal{C}_{t+1,\text{opt}}$ using F to obtain $\mathcal{C}_{t+1}$.

8. Increment t by 1.

9. If the bag is not empty, go back to step 1.

E.2   OPTIMAL RETURN

The optimal return for the *single-bag* tasks was derived in the following way. First, we obtained molecular structures for the complexes SOF_4, IF_5, SF_6, and SOF_6. Subsequently, we performed a structure optimization using the PM6 method. Since the undiscounted return is path-independent,

we determined the return $R(s)$ by computing the total interaction energy in the canvas $\mathcal{C}$, i.e.

$$R(s) = \left\{ \sum_{i=1}^{|\mathcal{C}|} E(\{e_i, \mathbf{0}\}) \right\} - E(\mathcal{C}). \tag{12}$$

F EXPERIMENTAL DETAILS

F.1 COMPUTING INFRASTRUCTURE

Experiments were run on an Intel Xeon E5-2650 v4 2.2GHz 12-core processor (96GiB RAM) and a Nvidia P100 GPU (16GiB). Our agent is implemented in the deep learning framework `PyTorch` (Paszke et al., 2019). Data analysis was performed with the Python libraries `matplotlib` (Hunter, 2007) and `pandas` (McKinney, 2010).

F.2 IMPLEMENTATION DETAILS

The model architecture is summarized in Table 2, where the dimensions of s^{inv} and $s_{f,e}^{\mathrm{inv}}$ are $d^{\mathrm{inv}} = (L_{\mathrm{max}} + 2) \cdot \tau \cdot 2$ and $d_{f,e}^{\mathrm{inv}} = (L_{\mathrm{max}} + 2) \cdot \tau_e \cdot 2$, respectively. We initialize the biases of each network with 0 and each weight matrix as a (semi-)orthogonal matrix. After each hidden layer, a ReLU non-linearity is employed. As explained in the main text, both MLP_f and MLP_e use a masked softmax activation function to guarantee that only valid actions are chosen. To model the distance d, we employ a Gaussian mixture model consisting of $M = 3$ Gaussians. As we treat the standard deviations $\{\sigma_m\}_{m=1}^3$ as global parameters, the MDN has 6 outputs. Further, we rescale the means $\mu_m \in [-1, 1]$ to $\mu_m \in [d_{\mathrm{min}}, d_{\mathrm{max}}]$. If the sampled distance is negative, we clip the value at 0.001.

Hyperparameters for CORMORANT are listed in Table 3. In our experiments, we found it important to use multiple filters τ_e per element. For more details on CORMORANT, see the original work (Anderson et al., 2019). Further hyperparameters used in our experiments are in Table 4.

Table 2: Model architecture for actor and critic networks.

Network	Dimensions per layer	Output activation
MLP_f	$d^{\mathrm{inv}}, 128, 1$	masked softmax
MLP_e	$d^{\mathrm{inv}}, 128, e_{\mathrm{max}}$	masked softmax
MDN	$d_{f,e}^{\mathrm{inv}}, 128, 6$	linear (π_m), tanh (μ_m)
MLP_ϕ	$d^{\mathrm{inv}}, 128, 128$	linear
MLP_ρ	$128, 128, 1$	linear

Table 3: Hyperparameters for CORMORANT (Anderson et al., 2019) used in all experiments.

Hyperparameter	Value
Number of Clebsch-Gordan layers	3
L_{max} in spherical harmonics series expansion	4
Number of filters τ_e per element	4
Number of filters τ	$\tau_e \cdot N_e$

Table 4: Hyperparameters for the *single-bag*, *multi-bag* and *stochastic-bag* tasks. Values in parentheses were only used for the *single-bag* task. For further details on how the PPO hyperparameters are defined, please refer to Schulman et al. (2017).

Hyperparameter	Search Set	Value
Range $[d_{\min}, d_{\max}]$ (Å)	—	$[0.95, 1.80]$
Workers	—	10
PPO clipping ϵ	—	0.2
PPO gradient clipping	—	0.5
PPO GAE parameter λ	—	0.95
PPO value function coefficient c_1	—	1
PPO entropy coefficient c_2	$\{0.01, 0.05\}$	0.01
Number of optimization epochs	—	7
Adam stepsize	—	3×10^{-4}
Discount factor γ	—	0.99
Time horizon T	—	256 (128)
Scaling factor β	$\{-100, -10, -1, 1, 10, 100\}$	100 (−10)
Number of samples S for mode estimation	—	1024

G   ADDITIONAL RESULTS

Figure 6: Average offline performance on the *stochastic-bag* task with $\mathcal{B}^* = C_7H_8N_2O_2$ evaluated on (a) $C_7H_8N_2O_2$ and (b) larger, unseen bags $\{C_6H_{14}O_3, C_7H_{16}O, C_7H_{16}O_2, C_8H_{18}O\}$ across 10 seeds. For comparison, we show an agent that is trained only on the test bags (purple). Error bars indicate two standard deviations.