Class-Disentanglement and Applications in Adversarial Detection and Defense

Abstract

What is the minimum necessary information required by a neural net $D(\cdot)$ from an image x to accurately predict its class? Extracting such information in the input space from x can allocate the areas $D(\cdot)$ mainly attending to and shed novel insights to the detection and defense of adversarial attacks. In this paper, we propose "class-disentanglement" that trains a variational autoencoder $G(\cdot)$ to extract this class-dependent information as $x - G(x)$ via a trade-off between reconstructing x by $G(x)$ and classifying x by $D(x - G(x))$, where the former competes with the latter in decomposing x so the latter retains only necessary information for classification in $x - G(x)$. We apply it to both clean images and their adversarial images and discover that the perturbations generated by adversarial attacks mainly lie in the class-dependent part $x - G(x)$. The decomposition results also provide novel interpretations to classification and attack models. Inspired by these observations, we propose to conduct adversarial detection and adversarial defense respectively on $x - G(x)$ and $G(x)$, which consistently outperform the results on the original x. In experiments, this simple approach substantially improves the detection and defense against different types of adversarial attacks.

1   Introduction

Deep learning provides an end-to-end solution to challenging tasks with data of complicated structures and have achieved breakthrough across different domains in recent years. However, what essential information the neural nets extract from the input and mainly rely on in producing predictions for the targeted tasks still remains mysterious. Moreover, the trained models are known to be fragile and sensitive to adversarial perturbations on the input, but how to explain this failure is still an open problem. Given entangled raw features as input, the inference of neural nets tend to remove task-redundant information and compress task-essential information to abstract concepts. On the one hand, identifying the task-essential information in the input can allocate the areas that the neural nets mainly attend to and explain the model prediction. On the other hand, this information can also be the main target of adversarial attacks, while the removed task-redundant information may suffer less distortion under attacks and still preserve clues to correct the prediction. Hence, disentanglement of these two types of information in the input (termed "task-disentanglement") may shed critical insights to address aforementioned problems.

Disentangled representations [3] have been extensively studied in unsupervised learning when training a generative model, where each dimension of the representation controls a single generative factor of data variations and changing it does not affect other factors. Probably the most studied disentanglement model is β-variational autoencoder (VAE) [18], whose objective aims to reconstruct the input x from the latent representation z via $p(x|z)$ while keeping $p(z|x)$ close to the standard Gaussian $p(z) = \mathcal{N}(\mathbf{0}, \mathbf{I})$, which encourages the disentanglement of latent factors in z. However, VAE usually produces unrealistic and blurry images comparing to other generative models such as GAN [14]. And encouraging the disentanglement can further weaken the reconstruction performance. In addition, the learned latent factors in z are often exceedingly abstract and their correspondence to specific tasks can be obscure. Hence, it is challenging to derive task-disentanglement of input from the disentangled latent representation.

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

Information bottleneck (IB) [35, 36, 1] can potentially provide an information-theoretic perspective of the task-disentanglement problem. IB models the information flow from input x to task output y through some latent representation z. In IB, the ideal z only preserves the minimum necessary information to predict y but discards all redundant information in x that cannot further contribute to predicting y. This leads to an optimization principle that maximizes the mutual information $I(z; y)$ and meanwhile keeps $I(x; z)$ small. From IB's perspective, for supervised learning such as classification, maximizing $I(z; y)$ corresponds to minimizing the classification error of using z to predict the class y. In unsupervised learning models like VAE, maximizing $I(z; y)$ corresponds to minimizing the reconstruction error (or maximizing the data likelihood). In both cases, an additional constraint is adopted to limit the amount of information transmitted from x to z, forming an "information bottleneck" that filters out information redundant to the task. In β-VAE, the constraint keeps the posterior $p(z|x)$ sufficiently close to the standard Gaussian. For classification, previous researches [38, 42] argue that the hierarchical structure of neural nets encourages more information compression as going to deeper layers and the deep learning scheme (SGD + cross entropy loss) inherently solves an IB problem. However, IB has been mainly studied for latent bottleneck representations z [31, 2] but underexplored to disentangle the task-relevant information in the input space. Specifically, it is non-trivial to design an IB constraint in the input space.

Figure 1: Architecture and Training/Inference of class-disentangled variational auto-encoder (CD-VAE).

In this paper, we focus on image classification tasks and study "class-disentanglement" as a special case of "task-disentanglement", i.e., how to decompose an input image x into $x = G(x) + (x - G(x))$, where $G(x)$ contains all the information redundant or irrelevant to the class y, while $x - G(x)$ captures the essential information to predict the class y. To this end, we develop a simple architecture composed of a variational autoencoder (VAE) $G(\cdot)$ generating $G(x)$ from x and a classification network $D(\cdot)$ that can be applied to both $x - G(x)$ and x. A class-disentanglement model is achieved by jointly training $G(\cdot)$ to reconstruct x and $D(\cdot)$ to classify $x - G(x)$, where each task forms an IB constraint for the other in the objective. Therefore, $x - G(x)$ only competes the essential information for classification with $G(x)$ and $G(x)$ preserves all the class-redundant information for better reconstruction.

Unlike disentanglement of latent factors and IB defined in a latent space [5, 9, 20], class-disentanglement performs disentanglement of class-essential and class-redundant information in the more intricate but interpretable input space. Hence, it can be applied to analysing the behaviors of neural nets and intrinsic properties of complicated data, shedding novel insights that cannot be revealed by latent factors. For example, $x - G(x)$ can highlight the areas in an image x that neural nets mainly attend to and help explain why correct or incorrect predictions are made. In this paper, we mainly explore its applications on analyzing adversarial examples. In particular, we find that the adversarial perturbations generated by mainstream attack algorithms primarily lie in $x - G(x)$, while $G(x)$ still preserves uncontaminated information useful for classification. Therefore, we propose to detect adversarial attacks on $x - G(x)$ and defense the attacks by make predictions based on $G(x)$. In extensive experiments on both CIFAR and ImageNet dataset, these simple strategies significantly improves previous approaches directly applied on x and additionally provide novel interpretations to the results. We also present an empirical study of the trade-off between reconstruction and classification when changing their weights in the objective.

2 Related Work

Disentangled Representation Different variants of VAE [5, 9, 18, 20] have been developed in recent years for learning disentangled latent representations. They all rely on unsupervised learning to automatically discover explanatory factors of variation. However, as suggested by the theoretical analysis in [27], unsupervised disentanglement is fundamentally impossible without proper inductive biases on models and data. Hence, (implicit) supervision is necessary and might provide crucial guidance to disentanglement, as shown in class-disentanglement of this paper as well. Inspired by image translation, disentangling the content and style of an image is studied in [26, 4, 13, 19]. These methods leverage the supervised information, i.e., the domains or groups that every sample belongs to. Unlike previous works, class-disentanglement in this paper combines unsupervised learning and supervised learning in one objective to train a disentanglement model. These two tasks compete with each other and form IB constraints to each other, which leads to efficient disentanglement of class-essential and class-redundant information. Another highlighted difference is that class-disentanglement is defined in the input space instead of a low-dimensional latent space.

Adversarial Detection aims to distinguish adversarial examples from natural examples. Given a neural net trained on a clean dataset for the original task, many existing methods [30, 16, 8] train a binary classification network on top of some intermediate-layer of the given network as the adversarial detector. However, as pointed out by [6], these methods may fail when the detector model is leaked. Another strategy is motivated by the observation that adversarial examples have very different distribution from natural examples on intermediate-layer features. So a detector can be built upon some statistics of the distribution, e.g., [12] estimates the kernel density of an example as its proximity to the natural examples' manifold; [24] models the natural examples' distribution by a multivariate Gaussian and the Mahalanobis distance of an example to this Gaussian is used for adversarial detection; [28] introduces local intrinsic dimensionality to describe the distribution of adversarial examples. Most of these methods directly apply a detection on the input example x. Instead, we propose to conduct the detection on the $x - G(x)$ capturing the essential information of the class. This simple method consistently improves the detection accuracy and is complementary to existing approaches.

Adversarial Defense is usually achieved by adversarial training [29] and its variants [41] that augment the training set with adversarial examples. Another type of adversarial defense trains a GAN [34] or an auto-encoder [25]to remove adversarial perturbations (if any) from a sample before sending it to the classifier. For instance, [34] proposes an adversarial perturbation erasing GAN (APE-GAN) that can modify an adversarial example close to a natural example; [25] proposed a high-level representation guided denoiser (HGD) to remove adversarial noise. In this paper, we show that classification on the class-redundant part $G(x)$ is robust to adversarial attacks. So our method falls into this category. However, it differs from APE-GAN and HGD as we do not utilize adversarial examples during training.

3 Class-Disentanglement

In this section, we first introduce a simple VAE-classifier architecture and an associated optimization objective to train it for class-disentanglement. We then conduct an empirical study that applies the class-disentanglement model to both clean images and their adversarial examples. The results show that the adversarial perturbations mainly reside in the class-essential part $x - G(x)$. These observations motivate us to conduct adversarial detection and defense on $x - G(x)$ and $G(x)$, respectively, which are elaborated at the end of this section.

3.1 Class-Disentangled Variational Auto-Encoder

We propose a model architecture shown in Fig. 1 to decompose an input image x into a part retaining only essential information for classification (i.e., class-essential) and a part covering all the rest redundant information (i.e., class-redundant). Adding the two parts together exactly recovers x. In the proposed "class-disentangled variational auto-encoder (CD-VAE)", we employ a variataional auto-encoder (VAE) $G(\cdot)$ to capture the class-redundant information $G(x)$ and then send the complementary part $R(x) \triangleq x - G(x)$ to a classification network $D(\cdot)$. They are trained jointly: VAE $G(\cdot)$ aims for reconstructing x while classifier $D(\cdot)$ aims for predicting the class of x from $x - G(x)$. Therefore, the reconstruction and classification compete with each other on the input

135 pixels of x and thus discourage sending redundant information to each other. From the information
136 bottleneck perspective, each of them places an IB constraint for the information flowing to the other.

137 In CD-VAE, VAE $G(\cdot)$ is composed of (1) an encoder parameterized by ϕ and producing the posterior
138 $q_\phi(z|x)$ of latent factors z; and (2) an decoder parameterized by θ and producing the data likelihood
139 $p_\theta(x|z)$. Classification network $D(\cdot)$ predicts the class probabilities for x based on $x - G(x)$ and
140 it has parameters ω. We jointly train $G(\cdot)$ and $D(\cdot)$ by optimizing the following objective, which
141 combines the objective $L_G(\phi, \theta)$ of β-VAE and the cross-entropy loss $L_D(\omega)$ for classification, i.e.,

$$\min_{\phi, \theta, \omega} \ \mathbb{E}_{(x,y) \sim p_{data}(x,y)} \left[L_G(\phi, \theta) + \gamma L_D(\omega) \right] \tag{1}$$

$$L_G(\phi, \theta) = -\mathbb{E}_{q_\phi(z|x)} \log p_\theta(x|z) + \beta D_{KL}(q_\phi(z|x) \| p(z)), \tag{2}$$

$$L_D(\omega) = -\log D(x - G(x); \omega)[y], \tag{3}$$

142 where $p(z) = \mathcal{N}(\mathbf{0}, \mathbf{I})$ is the prior of z that encourages its disentanglement, and $D_{KL}(\cdot \| \cdot)$ measures
143 the Kullback–Leibler divergence of posterior $q_\phi(z|x)$ from prior $p(z)$. The first term in $L_G(\phi, \theta)$
144 is the marginal likelihood of data in the VAE-generation process. It aims for reconstructing x under
145 the IB constraint of the KL-divergence. In $L_D(\omega)$, $D(x - G(x); \omega)[y]$ is the predicted probability
146 for the ground-truth class y. There are two hyperparameters in the CD-VAE objective: β controls the
147 strength of representation-disentanglement inside the β-VAE, while γ controls the trade-off between
148 reconstruction task (by $G(x)$) and classification task (by $D(x - G(x))$).

149 Not every pixel in an image x is related to the class label y and many previous works [43, 33] imply
150 that a neural net classifier makes predictions by merely attending to sparse regions of the image.
151 However, the rest information outside the scope of classifiers, e.g., illumination, background colors,
152 patterns shared with other classes, objects of other classes, etc., are all critical to the reconstruction
153 of x. Hence, the trade-off between VAE $G(\cdot)$ and classifier $D(\cdot)$ in CD-VAE is efficient for
154 class-disentanglement: while the classifier $D(\cdot)$ quickly picks the class-specific regions in x, the
155 class-redundant information more general across classes can be easily captured by $G(\cdot)$'s bottleneck
156 factors z with higher priority.

3.2 Class-Disentanglement on Natural Images vs. Adversarial Images: An Empirical Study

158 CD-VAE provides novel perspectives to understand (1) how a neural net classifier predicts the class of
159 an image and (2) how an adversarial example attacks the classifier. In particular, $x - G(x)$ reveals the
160 regions in an image that a classifier mainly attend to, and our empirical study shows that they are also
161 the regions that adversarial examples mainly attack. Since adversarial perturbations are optimized
162 and generated in the input space, class-disentanglement in the input space is more adapted for their
163 analysis than representation-disentanglement.

164 Given a classifier $D(\cdot)$ and a clean image x with label y, an adversarial image $\hat{x} = x + \delta$ is usually
165 generated by optimizing δ to maximize the classification loss within an ϵ-ball around x, i.e.,

$$\max_{\|\delta\|_p \le \epsilon} -\log D(x + \delta)[y], \tag{4}$$

166 where the popular choices for p include $p = \infty, 1, 2$. This is called "non-targeted" attack since it
167 does not specific a target class that the prediction should change to after applying the perturbation δ.
168 A widely used algorithm to tackle the above optimization is projected gradient descent (PGD), which
169 iterates between gradient sign ascent of step size α and projection $\mathcal{P}_{\|x'-x\|_p \le \epsilon}(\cdot)$ to the ϵ-ball around
170 x for multiple steps, i.e.,

$$x' \leftarrow \mathcal{P}_{\|x'-x\|_p \le \epsilon} \left(x' + \alpha \operatorname{sign} \left(\nabla_{x'} - \log D(x')[y] \right) \right). \tag{5}$$

171 Although there exist other types of adversarial attacks that can also be analyzed by class-
172 disentanglement, we mainly use PGD attack here and will include more attacks in later experiments.

173 In our empirical study, we compare the class-disentanglement results of a clean images x and an
174 adversarial image x' generated from it, i.e., $G(x)$, $R(x) = x - G(x)$, $G(x')$, $R(x') = x' - G(x')$.
175 We are particularly interested in (1) which parts of an image suggested by $R(x)$ and $R(x')$ that a
176 neural net classifier mainly attends to; and (2) the difference between x and x' on their original pixels,
177 class-essential parts, class-redundant parts and hidden space. Specifically, we investigate

$$\delta \triangleq x - x', \ \ \delta_G \triangleq G(x) - G(x'), \ \ \delta_R \triangleq R(x) - R(x'), \ \ \delta_z \triangleq z - z'. \tag{6}$$

Original label: Vizsla, Macaw, Airedale, King crab, English springer, Gibbon, Weimaraner, Saluki

Predicted label after attack: Afghan hound, Lorikeet, Otterhound, Rock crab, Cocker spaniel, Patas, Chesapeake bay retriever, Basenji

Figure 2: Class-Disentanglement results by CD-VAE on restricted ImageNet.

For each dataset from CIFAR-10 and ImageNet, we train a CD-VAE model on the (clean) training set. We then apply the CD-VAE model to both the (clean) test/validation set images and the corresponding adversarial images generated by PGD attack (ℓ_∞-ball constraint) [29] towards a pre-trained classifier (WideResNet-28-10 [40] for CIFAR-10 and ResNet-50 [17] for ImageNet). Fig. 2 presents some examples from the ImageNet experiment, while the result for CIFAR-10 can be found in Appendix.

	Consine Similarity	FID
$G(x)$ vs. $G(x')$	1.0 ± 0.00	0.90
$R(x)$ vs. $R(x')$	0.95 ± 0.02	22.31

Table 1: Cosine similarity and FID.

It shows that the class-essential part $R(x) = x - G(x)$ only highlight sparse regions of each image but can capture critical features of the class that are sufficient for the classification task, e.g., ears and nose of dog, eyes of parrot, etc. Hence, $R(x)$ can provide a natural interpretation to the prediction made by the neural net classifier, which has complicated structure and is usually treated as a black box. Comparison among δ, δ_R and δ_G shows that the adversarial perturbation δ mainly

	$\ell_1 \times 10^{-3}$	ℓ_2	ℓ_∞
x	142.83 ± 37.02	427.99 ± 92.59	2.49 ± 0.20
$G(x)$	133.68 ± 37.07	397.77 ± 92.14	2.08 ± 0.11
$R(x)$	36.76 ± 11.75	127.95 ± 37.27	2.45 ± 0.46
x'	142.74 ± 36.57	427.91 ± 91.19	2.53 ± 0.18
$G(x')$	133.52 ± 36.96	397.26 ± 91.85	2.08 ± 0.11
$R(x')$	38.13 ± 11.06	131.20 ± 35.37	2.46 ± 0.45
δ	13.65 ± 0.88	39.09 ± 1.40	0.14 ± 0.00
δ_G	4.15 ± 0.65	16.56 ± 2.47	0.39 ± 0.17
δ_R	13.78 ± 0.92	40.97 ± 1.87	0.48 ± 0.16

Table 2: ℓ_p norm/distance of different parts in CD-VAE.

lies in δ_R and cause slight change δ_G on $G(x)$. This indicates that the attacks to x mainly reside in $R(x')$ but do not heavily distort $G(x)$. This observation directly leads to two applications. First, we may better detect adversarial examples in the space of $R(x)$. In Fig. 2, the sparse regions captured by $R(x')$ largely narrow the search range for the attacked regions and thus might make the detection easier. Secondly, $G(x)$ in Fig. 2 still contains useful information for class prediction—it is redundant

and less discriminative than $R(x)$ but is almost undistorted in $G(x')$, so classification on $G(x')$ might be more robust to adversarial attacks and provide a simple defense strategy.

Our quantitative analysis to δ, δ_R and δ_G also support the observations above. In Table 2, we report several statistics of them, e.g., the mean and standard deviation for their ℓ_p norms with $p = \{1, 2, \infty\}$. To further study the similarity of $R(x)$ and $R(x')$ as images, we also report the statistics for their cosine similarity and Fréchet Inception Distance (FID) in Table 1. $R(x')$ and $R(x)$ are distant from each other while $G(x')$ is close to $G(x)$ in terms of all those distance metrics. This again supports the adversarial detection on $R(x)$ and adversarial defense on $G(x)$. In addition, we calculate the (Pearson) correlation between z and z' on each dimension and report its histogram and p-value in Fig. 3. It shows a strong correlation between z and z', which implies that $G(x)$ is robust to the adversarial perturbations.

Figure 3: Pearson correlation of z and z'.

dataset	Test / Training	x	$R(x)$	$G(x)$
CIFAR-10	x	96.01(99.84)	92.68(99.65)	18.86(67.93)
	$R(x)$	95.81(99.81)	96.20(99.82)	18.12(66.30)
	$G(x)$	51.84(86.52)	25.67(68.98)	75.25(97.39)
Restricted ImageNet	x	82.53(96.88)	11.17(25.61)	65.26(88.94)
	$R(x)$	63.33(82.14)	82.14(96.47)	5.36(12.01)
	$G(x)$	44.46(69.13)	1.71(5.02)	74.08(93.37)

Table 3: Training on one part of CD-VAE (using large $\gamma = 10$) and test on another part: Top-1(Top-5)

In Table 3, In order to further understand how the class-information is distributed into $R(x)$ and $G(x)$ and why the adversarial attacks towards x mainly affect $R(x)$ instead of $G(x)$, we train three classifiers respectively on x, $G(x)$ and $R(x)$ of training images and evaluate their accuracy when applied to x, $G(x)$ and $R(x)$ of test images. The results are reported in Table 3, from which we observe: (1) the classifier trained on $R(x)$ is highly effective on x and vice versa (with only one exception) so they share class-information important to both classifiers; (2) the classifier trained on $G(x)$ has some classification accuracy, indicating that $G(x)$ still preserves useful information about class even with large γ. But the classifier trained on x performs poorly on $G(x)$ so it ignores and does not rely on the class-information in $G(x)$; (3) the classifier trained on $R(x)$ achieves poor accuracy on $G(x)$ and vice versa, indicating that they use different information for classification. Therefore, adversarial attacks to the classifier trained on x will mainly distort the class-information shared by and important to both x and $R(x)$ but slightly affect the class-information in $G(x)$.

3.3 Applying Class-Disentanglement to Adversarial Detection

Inspired by the empirical study, we propose to apply existing adversarial detection methods to $R(x) = x - G(x)$ instead of x. For example, given an image x, [24] builds a kernel density estimator $K(\cdot, D_\ell(X))$ for the intermediate-layer embedding (e.g., the ℓ^{th} layer output $D_\ell(\cdot)$ of a classifier $D(\cdot)$) of the (clean) training set X and use it to compute the kernel density of a given sample x, i.e., $K(x, D_\ell(X))$. Intuitively, adversarial examples will have smaller density than the natural samples. Hence, previous works detect them via thresholding to the density value. Instead, we propose to apply the same method to $R(x)$ computed by CD-VAE, i.e., we detect sample x as an adversarial example if its kernel density $K(R(x), D_\ell(R(X)))$ is below a threshold. Note this simple strategy is complementary to existing techniques for adversarial detection methods and thus can be generally applied to improving them.

3.4 Applying Class-Disentanglement to Adversarial Defense

The empirical study shows that $G(x')$ contains useful information for classification that is less distorted by the adversarial perturbation. This leads to a simple defense strategy that sends $G(x')$ to the pre-trained model that the adversarial example x' attacks. Since the adversarial perturbation δ is

mainly retained in $R(x')$ and removed from $G(x')$ by class-disentanglement, we can achieve a more robust classification performance on $G(x')$.

4 Experiments

In this section, we evaluate the classification and reconstruction in CD-VAE under different γ and apply CD-VAE to adversarial detection and defense of a variety of attacks, as suggested by the empirical study above. We further compare CD-VAE with popular approaches developed for the two tasks and show consistent improvement over them brought by our strategies proposed in Sec. 3.3-3.4. In particular, all the experiments are conducted on two datasets, CIFAR-10 [22] and restricted ImageNet [37]. CIFAR-10 consists of 60,000 color images belonging to 10 classes, with 50,000 training images and 10000 test images. Restricted ImageNet [37] is an ImageNet [10] subset with 203 classes including 257,748 training images and 10,150 test images.

CD-VAE Setting For CIFAR-10, we use a VAE $G(\cdot)$ with a few convolutional layers [21] and WideResNet-28-10 [40] as the image classifier $D(\cdot)$. For restricted ImageNet, due to the high resolution (299×299), we use VQ-VAE [32] as $G(\cdot)$ and ResNet-50 [17] as $D(\cdot)$. We set $\beta = 0.2$. During training, we use AdamW [11] with a weight decay of 1e-6 as the optimizer to minimize Eq. (2) in an end-to-end manner for 300(60) epochs on CIFAR-10(restricted ImageNet).

4.1 Trade-off between Reconstruction and Classification in CD-VAE (via γ)

(a) CIFAR-10   (b) Restricted ImageNet

Figure 4: Trade-off between reconstruction accuracy and classification accuracy by changing γ.

In the CD-VAE objective Eq. (2), γ controls the trade-off between classification on $R(x) = x - G(x)$ and reconstruction by $G(x)$. When applied to adversarial detection and defense, it may lead to more complicated trade-off behaviors. In Fig. 4, we evaluate classification accuracy of $D(R(x))$, reconstruction accuracy on $G(x)$ (i.e., $1 - \|x - G(x)\|_2/\|x\|_2$), adversarial detection accuracy, and the defense accuracy on adversarial examples, when using different γ to train CD-VAE. In both plots, classification (reconstruction) accuracy quickly grows when increasing (decreasing) γ from small (large) values and then saturates after sufficiently large (small) γ, indicating that moving more information to $R(x)$ ($G(x)$) cannot improve the classification (reconstruction). Therefore, for both datasets, a sweet spot is achieved at $\gamma = 10$ for the classification-reconstruction trade-off. Changing γ also leads to visual changes of $R(x)$ and $G(x)$ shown in Fig. 5, which provides interesting perspectives for interpretation of neural nets. As γ increasing, $R(x)$ starts by first capturing the most discriminative (but sparse) features, e.g., the tongue/nose of dogs and the hair of monkeys, and gradually adds more class-relevant features. On the contrary, $G(x)$ becomes more blurry and lose more details but still tends to preserve the colors and shapes that are more critical to reconstruction. Fig. 4 also reports how the adversarial detection and defense accuracy changes with γ (against PGD-attack to a pre-trained classifier on the training set). They does not change monotonically with γ since increasing (decreasing) γ may move both perturbation-specific and true class-specific information into $R(x)$ ($G(x)$): while the former can improve the detection, the latter introduces noises.

4.2 Adversarial Detection

We apply our strategy in Sec. 3.3 to several state-of-the-art adversarial detection approaches, i.e., kernel density (KD) [12], local intrinsic dimensionality (LID) [28] and mahalanbobis distance

Labels: Siamese cat, kelpie, Chesapeake bay retriever, Siberian husky, Curly coated retriever, Titi, Guenon, Bull mastiff

Figure 5: Class-Disentanglement results on restricted ImageNet by CD-VAE with different γ.

Method	FGSM		BIM		C&W		PGD-l_∞		PGD-l_2	
	TNR	AUC	TNR	AUC	TNR	AUC	TNR	AUC	TNR	AUC
KD	42.38	85.74	74.54	94.82	73.33	94.75	73.12	94.59	70.62	93.62
KD ($R(x)$)	57.10	89.69	96.79	99.27	94.67	98.73	96.56	99.30	97.04	99.32
LID	69.05	93.60	77.73	95.20	74.98	94.32	71.52	93.19	72.57	93.46
LID ($R(x)$)	92.60	98.59	86.42	97.29	76.42	95.10	87.54	97.57	87.63	97.38
MD	94.91	98.69	88.33	97.66	86.30	97.36	77.23	95.38	76.70	95.33
MD ($R(x)$)	99.68	99.36	98.92	99.74	98.94	99.68	99.13	99.79	99.13	99.77

Table 4: TNR and AUC (%) of adversarial detection on x vs. $R(x)$ (ours) against 5 attacks (CIFAR-10)

Method	FGSM		BIM		C&W		PGD-l_∞		PGD-l_2	
	TNR	AUC	TNR	AUC	TNR	AUC	TNR	AUC	TNR	AUC
KD	8.76	70.25	99.26	99.82	99.22	99.77	99.25	99.80	44.02	82.81
KD ($R(x)$)	99.40	99.63	100.0	100.0	100.0	100.0	100.0	100.0	92.85	98.40
LID	44.28	85.91	97.92	99.57	97.58	99.49	97.80	99.51	53.78	87.37
LID ($R(x)$)	99.91	99.93	99.46	99.81	98.24	99.40	99.43	99.73	61.32	89.18
MD	34.69	84.96	99.33	99.78	98.72	99.61	99.18	99.70	44.16	82.61
MD ($R(x)$)	100.0	99.99	100.0	99.99	100.0	99.98	99.99	99.95	95.42	98.86

Table 5: TNR and AUC (%) of adversarial detection on x vs. $R(x)$ (ours) against 5 attacks (restricted ImageNet)

Dataset	Defense	Attack					
		Clean	PGD-ℓ_∞	PGD-ℓ_2	C&W-ℓ_∞	C&W-ℓ_2	StAdv
CIFAR10	Normal	96.01	0.0	0.0	0.0	0.0	0.0
	AT PGD-ℓ_∞	86.8	49.0	19.2	26.0	52.0	4.8
	TRADES ℓ_∞	84.9	52.5	23.3	-	-	9.2
	AT PGD-ℓ_2	85.0	39.5	47.8	43.4	50.6	7.8
	AT StAdv	86.2	0.1	0.2	0.2	0.5	53.9
	HGD	80.75	75.93	75.44	75.84	77.15	23.04
	APE-GAN	90.93	59.28	65.17	59.23	65.30	7.28
	Ours	86.81	77.05	78.02	77.04	78.29	19.41
ImageNet	Normal	82.53	0.0	0.0	0.0	0.0	0.0
	AT PGD-ℓ_2	69.89	10.93	60.95	9.49	60.07	0.31
	Ours	65.26	52.48	63.12	52.95	64.98	4.75

Table 6: Defense accuracy (%) of our strategy and baselines against various attacks. AT-adversarial training.

(MD) [24], and compare it with their original versions on the tasks of detecting adversarial examples generated by several state-of-the-art adversarial attacks, i.e., fast gradient sign method (FGSM)[15], basic iterative method (BIM)[23], Carlini& Wagner's method (C&W)[7] and projected gradient descent method (PGD)[29], where ℓ_2-ball and ℓ_∞-ball ϵ-constraints (with $\epsilon = 1$ and $8/255$) are both considered, and iterative attacks run for 5 steps using step size $\frac{\epsilon}{\sqrt{2}}$. We use WideResNet-28-10 (ResNet-50) as the DNN feature extractor for CIFAR-10 (restricted sImageNet), which is $D(\cdot)$ from CD-VAE for our strategy but is trained on the training set for all other baselines. We use true negative rate (TNR) at 95% true positive rate and area under the receiver operating characteristic curve (AUC) to evaluate the detection performance. The results on CIFAR-10 and restricted ImageNet are reported in Table 4-5. By applying the existing detection methods on $R(x)$ instead of x, our strategy consistently and significantly improves all these methods' detection accuracy. For example, FGSM is the most challenging attacks to detect but our method can still improve TNR of KD from 8.76% to 99.40% on restricted ImageNet.

4.3 Adversarial Defense

We evaluate our adversarial defense strategy in Sec. 3.4 against several state-of-the-art attacks, i.e., gradient-based attack (BIM[23], PGD[29] and C&W[7]) and spatial transform-based attacks (StAdv[39]), with $\epsilon = 1$, $8/255$, 0.05 for ℓ_2, ℓ_∞, and StAdv, respectively. We set the iterations of attacks to 100 and the attacks are applied against pre-trained WideResNet-28-10 (Resnet50) on CIFAR-10 (restricted ImageNet). According to the trade-off in Fig. 4, we choose $\gamma = 1e - 2$ for CIFAR-10 and $\gamma = 1$ for restricted ImageNet. We compare our method with adversarial training based methods and preprocessing based methods (HGD[25], APE-GAN[34]). The defense accuracy over adversarial examples are reported in Table 6. Our strategy outperforms most baselines by a large margin when defending all types of attacks, while other methods only excel in defending certain attacks, e.g., adversarial training (AT) methods excel on the attacks used in AT but generalize poorly to other attacks. HGD is the most competitive one among preprocessing based methods but our method consistently outperforms it. Comparing to other baselines relying on adversarial examples for training, CD-VAE trained only on natural examples already achieves higher defense accuracy.

5 Conclusion

In this paper, we propose an VAE+classifier structure, i.e., "class-disentangled variational autoencoder (CD-VAE)" to decompose an input image x into $x = G(x) + R(x)$, where $R(x) = x - G(x)$ captures the essential information for classification while $G(x)$ covers all class-redundant information. We further propose an objective to jointly train the VAE and classifier to gain such class-disentanglement capability. CD-VAE provides novel perspectives to understand (1) how a neural net classifier predicts the class of an image and (2) how an adversarial example attacks the class. Inspired by these observations, we propose to conduct adversarial detection and adversarial defense respectively on $R(x)$ and $G(x)$. These two simple strategies substantially improve the detection and defense against various adversarial attacks.

References

[1] Alexander A Alemi, Ian Fischer, Joshua V Dillon, and Kevin Murphy. Deep variational information bottleneck. *arXiv preprint arXiv:1612.00410*, 2016.

[2] Rana Ali Amjad and Bernhard C Geiger. Learning representations for neural network-based classification using the information bottleneck principle. *IEEE transactions on pattern analysis and machine intelligence*, 42(9):2225–2239, 2019.

[3] Yoshua Bengio, Aaron Courville, and Pascal Vincent. Representation learning: A review and new perspectives. *IEEE transactions on pattern analysis and machine intelligence*, 35(8):1798–1828, 2013.

[4] Diane Bouchacourt, Ryota Tomioka, and Sebastian Nowozin. Multi-level variational autoencoder: Learning disentangled representations from grouped observations. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

[5] Christopher P Burgess, Irina Higgins, Arka Pal, Loic Matthey, Nick Watters, Guillaume Desjardins, and Alexander Lerchner. Understanding disentangling in β-vae. *arXiv preprint arXiv:1804.03599*, 2018.

[6] Nicholas Carlini and David Wagner. Adversarial examples are not easily detected: Bypassing ten detection methods. In *Proceedings of the 10th ACM Workshop on Artificial Intelligence and Security*, pages 3–14, 2017.

[7] Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks. In *2017 ieee symposium on security and privacy (sp)*, pages 39–57. IEEE, 2017.

[8] Fabio Carrara, Rudy Becarelli, Roberto Caldelli, Fabrizio Falchi, and Giuseppe Amato. Adversarial examples detection in features distance spaces. In *Proceedings of the European Conference on Computer Vision (ECCV) Workshops*, pages 0–0, 2018.

[9] Ricky TQ Chen, Xuechen Li, Roger Grosse, and David Duvenaud. Isolating sources of disentanglement in variational autoencoders. *arXiv preprint arXiv:1802.04942*, 2018.

[10] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pages 248–255. Ieee, 2009.

[11] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

[12] Reuben Feinman, Ryan R Curtin, Saurabh Shintre, and Andrew B Gardner. Detecting adversarial samples from artifacts. *arXiv preprint arXiv:1703.00410*, 2017.

[13] Abel Gonzalez-Garcia, Joost Van De Weijer, and Yoshua Bengio. Image-to-image translation for cross-domain disentanglement. *arXiv preprint arXiv:1805.09730*, 2018.

[14] Ian J Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial networks. *arXiv preprint arXiv:1406.2661*, 2014.

[15] Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

[16] Shuangchi Gu, Ping Yi, Ting Zhu, Yao Yao, and Wei Wang. Detecting adversarial examples in deep neural networks using normalizing filters. *UMBC Student Collection*, 2019.

[17] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[18] Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. β-vae: Learning basic visual concepts with a constrained variational framework. 2016.

[19] Maximilian Ilse, Jakub M Tomczak, Christos Louizos, and Max Welling. Diva: Domain invariant variational autoencoders. In *Medical Imaging with Deep Learning*, pages 322–348. PMLR, 2020.

[20] Hyunjik Kim and Andriy Mnih. Disentangling by factorising. In *International Conference on Machine Learning*, pages 2649–2658. PMLR, 2018.

[21] Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

[22] Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

[23] Alexey Kurakin, Ian Goodfellow, Samy Bengio, et al. Adversarial examples in the physical world, 2016.

[24] Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. *arXiv preprint arXiv:1807.03888*, 2018.

[25] Fangzhou Liao, Ming Liang, Yinpeng Dong, Tianyu Pang, Xiaolin Hu, and Jun Zhu. Defense against adversarial attacks using high-level representation guided denoiser. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1778–1787, 2018.

[26] Yen-Cheng Liu, Yu-Ying Yeh, Tzu-Chien Fu, Sheng-De Wang, Wei-Chen Chiu, and Yu-Chiang Frank Wang. Detach and adapt: Learning cross-domain disentangled deep representation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 8867–8876, 2018.

[27] Francesco Locatello, Stefan Bauer, Mario Lucic, Gunnar Raetsch, Sylvain Gelly, Bernhard Schölkopf, and Olivier Bachem. Challenging common assumptions in the unsupervised learning of disentangled representations. In *international conference on machine learning*, pages 4114–4124. PMLR, 2019.

[28] Xingjun Ma, Bo Li, Yisen Wang, Sarah M Erfani, Sudanthi Wijewickrema, Grant Schoenebeck, Dawn Song, Michael E Houle, and James Bailey. Characterizing adversarial subspaces using local intrinsic dimensionality. *arXiv preprint arXiv:1801.02613*, 2018.

[29] Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

[30] Jan Hendrik Metzen, Tim Genewein, Volker Fischer, and Bastian Bischoff. On detecting adversarial perturbations. *arXiv preprint arXiv:1702.04267*, 2017.

[31] Saeid Motiian, Marco Piccirilli, Donald A Adjeroh, and Gianfranco Doretto. Information bottleneck learning using privileged information for visual recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1496–1505, 2016.

[32] Aaron van den Oord, Oriol Vinyals, and Koray Kavukcuoglu. Neural discrete representation learning. *arXiv preprint arXiv:1711.00937*, 2017.

[33] Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE international conference on computer vision*, pages 618–626, 2017.

[34] Shiwei Shen, Guoqing Jin, Ke Gao, and Yongdong Zhang. Ape-gan: Adversarial perturbation elimination with gan. *arXiv preprint arXiv:1707.05474*, 2017.

[35] Naftali Tishby, Fernando C Pereira, and William Bialek. The information bottleneck method. *arXiv preprint physics/0004057*, 2000.

[36] Naftali Tishby and Noga Zaslavsky. Deep learning and the information bottleneck principle. In *2015 IEEE Information Theory Workshop (ITW)*, pages 1–5. IEEE, 2015.

[37] Dimitris Tsipras, Shibani Santurkar, Logan Engstrom, Alexander Turner, and Aleksander Madry. Robustness may be at odds with accuracy. *arXiv preprint arXiv:1805.12152*, 2018.

[38] Zifeng Wu, Chunhua Shen, and Anton Van Den Hengel. Wider or deeper: Revisiting the resnet model for visual recognition. *Pattern Recognition*, 90:119–133, 2019.

[39] Chaowei Xiao, Jun-Yan Zhu, Bo Li, Warren He, Mingyan Liu, and Dawn Song. Spatially transformed adversarial examples. *arXiv preprint arXiv:1801.02612*, 2018.

[40] Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. *arXiv preprint arXiv:1605.07146*, 2016.

[41] Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric Xing, Laurent El Ghaoui, and Michael Jordan. Theoretically principled trade-off between robustness and accuracy. In *International Conference on Machine Learning*, pages 7472–7482. PMLR, 2019.

[42] Jingwei Zhang, Tongliang Liu, and Dacheng Tao. An information-theoretic view for deep learning. *arXiv preprint arXiv:1804.09060*, 2018.

[43] Bolei Zhou, Aditya Khosla, Agata Lapedriza, Aude Oliva, and Antonio Torralba. Learning deep features for discriminative localization. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2921–2929, 2016.