Medix: Robust Gradient Statistics for Out-of-Distribution Detection from Unlabeled Wild Data

Momin Abbas *momin.abbas1@ibm.com*
IBM

Ali Falahati *afalahat@uwaterloo.ca*
University of Waterloo

Hossein Goli *hossein.goli@cuhk.edu.hk*
CUHK

Mohammad Mohammadi Amiri *mamiri@rpi.edu*
Rensselaer Polytechnic Institute

Reviewed on OpenReview: *https://openreview.net/forum?id=jFjA24PBJx*

Abstract

Out-of-distribution (OOD) detection plays a crucial role in ensuring the robustness of machine learning systems deployed in real-world applications. Recent approaches have explored the use of unlabeled data, showing potential for enhancing OOD detection capabilities. However, effectively utilizing unlabeled in-the-wild data remains challenging due to the mixed nature of both in-distribution (InD) and OOD samples. The lack of a distinct set of OOD samples complicates the task of training an optimal OOD classifier. In this work, we introduce Medix, a novel framework designed to identify potential outliers from unlabeled data using the median operation. We use the median because it provides a stable estimate of the central tendency, as an OOD detection mechanism, due to its robustness against noise and outliers. Using these identified outliers, along with labeled InD data, we train a robust OOD classifier. From a theoretical perspective, we derive error bounds that demonstrate Medix achieves a low error rate. Empirical results further substantiate our claims, as Medix outperforms existing methods across the board in open-world settings, confirming the validity of our theoretical insights.

Code

1 Introduction

Deploying machine learning models in real-world applications often exposes them to challenges related to safety and reliability, particularly due to the presence of out-of-distribution (OOD) data. These OOD samples, which come from unknown categories, should not be predicted by the model. However, neural networks are inherently vulnerable and lack the necessary mechanisms to detect and handle OOD inputs in practice (Nguyen et al., 2015).

Identifying OOD samples during inference is critical yet not easy, as models are not exposed to unknown distributions during training and, therefore, cannot reliably distinguish OOD from in-distribution (InD) data. To address this challenge, recent approaches (Katz-Samuels et al., 2022; Du et al., 2024a) have explored using additional "in-the-wild" data to improve OOD detection. Specifically, Katz-Samuels et al. (2022) introduced a method that uses unlabeled wild data for regularizing model training, while still focusing on classifying labeled InD data. The advantage of using such unlabeled wild data lies in its availability, being easily collectible once

Figure 1: Overview of Medix. The method first trains an InD classifier to compute a reference gradient from labeled InD data. It then extracts candidate OOD samples from unlabeled wild data by iteratively identifying gradients that maximally reduce the deviation between the element-wise median (EWM) and the InD reference gradient. Finally, the extracted candidate outliers together with the labeled InD data are used to train an OOD detector.

a model is deployed in its operating environment. This approach allows the model to better capture the true distribution of OOD data encountered during test time and leads to a more robust OOD detection.

However, leveraging unlabeled wild data presents challenges due to the complex mixture of InD and OOD data. The absence of a distinct and clean set of OOD samples complicates the development of robust OOD detection methods, especially since the OOD detector model only encounters data drawn from this mixed distribution, without knowledge of whether each sample is from the InD or OOD category. Currently, the problem remains underexplored, with substantial opportunities for further progress. Moreover, few studies establish a formal theoretical foundation, and to the best of our knowledge, Du et al. (2024a) is the only work that provides such a foundation for the "in-the-wild" setting.

Meanwhile, recent studies have demonstrated the effectiveness of median-based approaches in data pruning (Acharya et al., 2024). Motivated by these developments, this paper aims to answer the following question:

> 💡 **Question.** Can robust gradient statistics leverage unlabeled wild data to facilitate OOD detection, despite the data containing an unknown mixture of InD and OOD samples?

To answer this question, we propose Medix (Figure 1), a framework that converts unlabeled wild data into useful supervision for OOD detection by extracting candidate OOD samples from the unlabeled mixture. We show that this filtering procedure admits provable error guarantees and leads to robust OOD detectors in practice. We provide theoretical guarantees for minimal error, which is further validated through experiments. We benchmark our approach against two categories of methods: (1) those trained solely on InD data, and (2) those trained with both InD data and an auxiliary unlabeled dataset. On CIFAR-100 (Krizhevsky et al., 2009), Medix demonstrates a significant improvement over the strong baseline KNN+ (Sun et al., 2022), outperforming it by an average of 40.98% in terms of FPR95. Unlike approaches such as Outlier Exposure (Hendrycks et al., 2019), which rely on a clean, auxiliary unlabeled dataset (i.e. they make a strong distributional assumption that the auxiliary data is completely separable from the InD data), Medix achieves superior results without such assumptions, offering greater flexibility. Compared to WOODS (Katz-Samuels et al., 2022), Medix reduces the average FPR95 by 1.32% on CIFAR-100 and 2.60% on CIFAR-10.

Our contributions are as follows:

C1) We propose Medix, a median-centric approach that filters outliers from the unlabeled wild data and then trains an OOD detector on the identified outliers and the InD samples. Our main contribution is the filtering stage.

C2) We establish theoretical guarantees for the robustness of median-based filtering in identifying both inliers and outliers within unlabeled mixtures.

C3) We conduct an extensive evaluation of Medix across eleven InD-OOD pairs, comparing its performance against 20 competitive baselines. Our results demonstrate that Medix outperforms all the baselines, achieving superior performance across the board.

2 Preliminaries and Problem Setup

In this section, we provide an overview of the OOD detection problem, and then formally define the data setup, model architecture, loss functions, and the learning goal.

Labeled In-Distribution Data. Consider the input space $\mathcal{X}$ and the label space $\mathcal{Y} = \{1, \ldots, K\}$, which together define the structure of InD data. A labeled dataset $\mathcal{S}_{\text{in}} = \{(\boldsymbol{x}_1, y_1), \ldots, (\boldsymbol{x}_n, y_n)\}$ is generated by sampling n pairs independently and identically distributed (i.i.d.) from $\mathbb{P}_{XY}$, an unknown joint probability distribution over $\mathcal{X} \times \mathcal{Y}$. The marginal distribution of $\mathbb{P}_{XY}$ on $\mathcal{X}$ is denoted as $\mathbb{P}_{\text{in}}$, representing the underlying distribution of InD inputs. We use $\mathcal{S}_{\text{in}}$ to train an InD model.

Out-of-distribution detection. We address a practical scenario where the model is trained using labeled InD data but is later deployed in environments that may contain OOD inputs from classes not represented in the training data, i.e., for some label $y \notin \mathcal{Y}$. The model is expected to abstain from making predictions for such OOD inputs. At inference time, the primary objective is to determine whether a given input belongs to the InD distribution or arises from an OOD source.

Unlabeled wild data. One of the primary obstacles in OOD detection is the scarcity of labeled OOD samples. The potential sample space of OOD data can be very large, making the collection of labeled examples both costly and impractical. To address this, we introduce unlabeled wild data, $\mathcal{S}_{\text{wild}} = \{\tilde{\boldsymbol{x}}_1, \ldots, \tilde{\boldsymbol{x}}_m\}$, into our learning framework to better mimic real-world scenarios as proposed by Katz-Samuels et al. (2022). Wild data is a blend of InD and OOD samples and can be readily collected during the deployment phase of a pre-trained model on $\mathcal{S}_{\text{in}}$. Similar to Du et al. (2024a); Katz-Samuels et al. (2022), we adopt the Huber contamination model (Huber, 1964) to characterize the marginal distribution of the wild data

$$\mathbb{P}_{\text{wild}} := (1 - \pi)\mathbb{P}_{\text{in}} + \pi\mathbb{P}_{\text{out}}, \quad \pi \in (0, 1], \tag{1}$$

where π denotes the proportion of contamination and $\mathbb{P}_{\text{out}}$ captures the OOD distribution on $\mathcal{X}$. We note that the scenario where $\pi = 0$ corresponds to the absence of OOD samples, rendering the problem trivial.

Models and Loss Functions. Let $f_\phi : \mathcal{X} \to \mathbb{R}^K$ represent the InD classifier parameterized by $\phi \in \Phi$, where Φ denotes the parameter space for this classifier. The output of f_ϕ corresponds to a soft probability distribution over the $K = |\mathcal{Y}|$ InD classes. The loss function for the labeled InD data is defined as $\ell : \mathbb{R}^K \times \mathcal{Y} \to \mathbb{R}$. For OOD detection, we introduce a separate classifier $g_\theta : \mathcal{X} \to \mathbb{R}$, parameterized by $\theta \in \Theta$, with Θ as the parameter space. The binary loss function associated with g_θ is denoted as $\ell_b(g_\theta(x), y_b)$, where $y_b \in \mathcal{Y}_b := \{y_+, y_-\}$. Here, $y_+ > 0$ represents the InD class, while $y_- < 0$ corresponds to the OOD class.

Learning objective. Our learning framework is designed to simultaneously train the OOD detector g_θ and the multi-class classifier f_ϕ, leveraging both the InD data $\mathbb{P}_{\text{in}}$ and the wild data $\mathbb{P}_{\text{wild}}$. During testing, we evaluate the performance using the following metrics:

$$\downarrow \text{FPR}(g_\theta) = \mathbb{E}_{\boldsymbol{x} \sim \mathbb{P}_{\text{out}}^{\text{test}}} \left[\mathcal{I}\{g_\theta(\boldsymbol{x}) = \text{in}\} \right],$$

$$\uparrow \text{TPR}(g_\theta) = \mathbb{E}_{\boldsymbol{x} \sim \mathbb{P}_{\text{in}}} \left[\mathcal{I}\{g_\theta(\boldsymbol{x}) = \text{in}\} \right],$$

$$\uparrow \text{Acc}(f_\phi) = \mathbb{E}_{(\boldsymbol{x},y) \sim \mathbb{P}_{XY}} \left[\mathcal{I}\{f_\phi(\boldsymbol{x}) = y\} \right],$$

where $\mathcal{I}\{\cdot\}$ denotes the indicator function, and $\mathbb{P}_{\text{out}}^{\text{test}}$ represents the OOD test data distribution.

3 Medix: Median-Centric Framework for OOD Detection

In this section, we present a novel learning paradigm, termed **Medix**, designed for OOD detection by harnessing the power of unlabeled wild data. Our framework overcomes the limitations of conventional approaches that rely exclusively on InD data and is particularly well-suited for applications in open-world environments, where models are often confronted with previously unseen inputs. The Medix framework is composed of two stages: **1) Outlier Extraction**: A filtering process that isolates candidate OOD samples from the unlabeled wild data (explained in Section 3.1), and **2) Detector Training**: train a binary OOD detector using both InD data and the outlier candidates identified in the previous step (explained in Section 3.2). For stage 2, we follow the protocol introduced by Du et al. (2024a). As we will demonstrate in the subsequent sections, this two-step methodology not only facilitates the effective extraction of OOD data from the unlabelled wild data but also establishes a robust foundation for deploying machine learning models in dynamic, open-world scenarios.

3.1 Extracting Candidate Outliers from the Wild Data

To isolate potential outliers from the wild mixture $\mathcal{S}_{\text{wild}}$, our framework leverages an optimization-based approach that exploits the gradients of the model parameters. These gradients are derived from a classification model, f_ϕ, which is trained solely on the InD dataset $\mathcal{S}_{\text{in}}$. T

Reference gradient estimation from InD data. The first step in our proposed framework is to estimate a reference gradient using the InD dataset $\mathcal{S}_{\text{in}}$. This is achieved by training a classifier f_ϕ on $\mathcal{S}_{\text{in}}$ through empirical risk minimization (ERM) as follows

$$\phi_{\mathcal{S}_{\text{in}}} \in \arg\min_{\phi \in \Phi} \mathcal{L}_{\mathcal{S}_{\text{in}}}(f_\phi), \quad \text{where} \quad \mathcal{L}_{\mathcal{S}_{\text{in}}}(f_\phi) = \frac{1}{n} \sum_{(\boldsymbol{x}_i, y_i) \in \mathcal{S}_{\text{in}}} \ell(f_\phi(\boldsymbol{x}_i), y_i), \tag{2}$$

where $\phi_{S_{\text{in}}}$ denotes the learned parameters. Once the classifier has been trained, we compute the mean gradient $\bar{\nabla}_{\text{in}}$ as the average of the gradients of the loss function with respect to the model parameters over the InD data:

$$\bar{\nabla}_{\text{in}} = \frac{1}{n} \sum_{(\boldsymbol{x}_i, y_i) \in \mathcal{S}_{\text{in}}} \nabla \ell(f_{\phi_{\mathcal{S}_{\text{in}}}}(\boldsymbol{x}_i), y_i). \tag{3}$$

In our approach, $\bar{\nabla}_{\text{in}}$ serves as the reference gradient, allowing the quantification of deviations for other data points relative to this reference.

Motivation. We hypothesize that increasing the number of OOD samples in the wild dataset, $\mathcal{S}_{\text{wild}}$, will lead to a greater deviation from the average InD gradient, $\bar{\nabla}_{\text{in}}$. To test this hypothesis, we design an initial experiment using CIFAR-10 (Krizhevsky et al., 2009) as the InD dataset and SVHN (Netzer et al., 2011) as the OOD dataset. Specifically, $\mathcal{S}_{\text{wild}}$ consists of 10,000 samples drawn from CIFAR-10, ensuring that these samples are disjoint from the training set used to train the model $\phi_{\mathcal{S}_{\text{in}}}$, which we leverage to compute $\bar{\nabla}_{\text{in}}$. We incrementally add SVHN OOD samples to $\mathcal{S}_{\text{wild}}$ and track the behavior of the L_2-norm deviation between $\bar{\nabla}_{\text{in}}$ and the element-wise median (EWM) of the gradients of the wild dataset as follows:

$$\left\| \bar{\nabla}_{\text{in}} - \text{EWM}\left(\left\{ \nabla \ell \left(f_{\phi_{\mathcal{S}_{\text{in}}}}(\tilde{\boldsymbol{x}}_i), \hat{y}_{\tilde{\boldsymbol{x}}_i} \right) \right\}_{i \in \mathcal{S}_{\text{wild}}} \right) \right\|. \tag{4}$$

Here EWM($\cdot$) denotes the element-wise median function, and $\hat{y}_{\tilde{\boldsymbol{x}}_i}$ represents the predicted label for a wild sample $\tilde{\boldsymbol{x}}_i$. Our results, depicted in Figure 2, reveal a clear and monotonic increase in the L_2-norm deviation, supporting our hypothesis. This observation serves as a key motivation for the method we introduce in the subsequent section. Notably, the stopping criterion for our algorithm is derived from this monotonically increasing behavior, where we terminate the algorithm when the L_2-norm deviation between consecutive iterations drops below a threshold ϵ; we will explain this method in detail in the following section.

Filtering potential outliers from unlabeled wild data. Motivated by the results in Figure 2, we formulate the following optimization problem to identify the outlier subset $\mathcal{S}_{\text{out}}^*$ in $\mathcal{S}_{\text{wild}}$:

$$\mathcal{S}_{\text{in}}^* = \arg\min_{\mathcal{S} \subseteq \mathcal{S}_{\text{wild}}} \left\| \bar{\nabla}_{\text{in}} - \text{EWM}(G_{\mathcal{S}}) \right\|, \quad \text{where} \quad G_{\mathcal{S}} = \left\{ \nabla \ell \left(f_{\phi_{\mathcal{S}_{\text{in}}}}(\tilde{\boldsymbol{x}}_i), \hat{y}_{\tilde{\boldsymbol{x}}_i} \right) \right\}_{i \in \mathcal{S}}. \tag{5}$$

The mean gradient is the element-wise average over InD samples, and the EWM is the per-coordinate median over wild samples, computed along the sample axis (for details see Appendix A.11).

The above optimization problem aims to find a subset $\mathcal{S}$ in $\mathcal{S}_{\text{wild}}$ that minimizes the distance between the EWM of the gradients and the average gradient $\bar{\nabla}_{\text{in}}$. According to Figure 2, such a subset, denoted by $\mathcal{S}_{\text{in}}^*$, may well represent the InD data in $\mathcal{S}_{\text{wild}}$, in which case $\mathcal{S}_{\text{out}}^* = \mathcal{S}_{\text{wild}} \backslash \mathcal{S}_{\text{in}}^*$ capture the OOD in $\mathcal{S}_{\text{wild}}$.

Solving the optimization problem in 5 is computationally intractable. To address this, we propose a greedy approximation based on a leave-one-out approach, as outlined in Algorithm 1. The algorithm implements an iterative procedure for outlier detection from a wild dataset, leveraging deviations in gradient information relative to the InD dataset.

The algorithm begins by computing the EWM of the wild data gradients at each iteration, which serves as a reference for comparing against the average

Figure 2: Distance deviation as we increase OOD samples in $\mathcal{S}_{\text{wild}}$.

gradient of the InD data $\bar{\nabla}_{\text{in}}$. We denote by d_t, the L_2 distance between the average InD gradient $\bar{\nabla}_{\text{in}}$ and the EWM gradients of the data left in the wild set, represented by $\mathcal{S}$, i.e., $d_t = \|\text{EWM}(G_{\mathcal{S}}) - \bar{\nabla}_{\text{in}}\|$. The algorithm then iteratively identifies samples in $\mathcal{S}$ that incur the most significant drop in the L_2 distance with d_t when removed from $\mathcal{S}$ as OOD. Specifically, having data samples $\mathcal{S}$ left, we remove each sample $i \in \mathcal{S}$ and compute the EWM as $\text{EWM}(G_{\mathcal{S} \backslash \{i\}})$ and the distance to $\bar{\nabla}_{\text{in}}$ as $\|\text{EWM}(G_{\mathcal{S} \backslash \{i\}}) - \bar{\nabla}_{\text{in}}\|$. We then find the drop in distance $\delta_i = d_t - \|\text{EWM}(G_{\mathcal{S} \backslash \{i\}}) - \bar{\nabla}_{\text{in}}\|$ and find the k samples with the largest drop and identify them as OOD. The algorithm repeats until there is no significant drop in δ_i or a maximum number of iterations is reached. The convergence criterion is based on the change in the L_2 distance between two iterations, which must fall below a predefined ϵ threshold; this criterion is inspired by the monotonically increasing trend that we observed in our preliminary experiment in Figure 2, i.e., as a large number of OOD samples are removed, the L_2 distance gradually decreases to a small value, signaling the point at which the algorithm should halt to avoid identifying InD samples as outliers, thus preventing any degradation in performance.

Algorithm 1 Iterative Outlier Detection via **Medix**

Require: $\bar{\nabla}_{\text{in}}$, $G_i = \nabla \ell(f_{\phi_{\mathcal{S}_{\text{in}}}}(\tilde{\boldsymbol{x}}_i), \hat{y}_{\tilde{\boldsymbol{x}}_i})$, maximum iterations T, hyperparameters ϵ, k
1: Initialize $\mathcal{S} \leftarrow \mathcal{S}_{\text{wild}}$ (wild set), $\mathcal{O} \leftarrow \emptyset$ (outliers), $t \leftarrow 0$ (iteration), $d_t \leftarrow 0$, $\delta_{\max} \leftarrow \infty$ (deviations), $\mathcal{I}_k \leftarrow \emptyset$
2: **while** $t \leq T$ or $|\delta_{\max}| > \epsilon$ **do**
3:      $\mathcal{O} \leftarrow \mathcal{O} \cup \{\tilde{\boldsymbol{x}}_i : i \in \mathcal{I}_k\}$ ▷ Add outliers to set $\mathcal{O}$
4:      $d_t \leftarrow \|\text{EWM}(G_{\mathcal{S}}) - \bar{\nabla}_{\text{in}}\|$ ▷ Compute L2 deviation
5:      **for** each $i \in \mathcal{S}$ **do**
6:          $\delta_i \leftarrow d_t - \|\text{EWM}(G_{\mathcal{S} \backslash \{i\}}) - \bar{\nabla}_{\text{in}}\|$
7:      **end for**
8:      $\mathcal{I}_k \leftarrow \text{indices}(\text{top-}k(\{\delta_i\}_{i \in \mathcal{S}}))$ ▷ Select top-k indices
9:      $\mathcal{S} \leftarrow \mathcal{S} \backslash \mathcal{I}_k$ ▷ Remove outliers from $\mathcal{S}$
10:     $\delta_{\max} \leftarrow \max_{i \in \mathcal{S}}\{\delta_i\}$, $t \leftarrow t + 1$
11: **end while**
12: **return** $\hat{\mathcal{S}}_{\text{out}} = \mathcal{O}$ ▷ Return detected outliers

---

3.2 Training the OOD Detector with Candidate Outliers

After identifying the candidate outlier set $\hat{\mathcal{S}}_{\text{out}}$ from the wild data, we proceed to train the OOD detector g_θ designed to maximize the distinction between InD and candidate outlier data following the protocol in Du et al. (2024a). The objective function enforces separability at the decision boundary (thresholded at

0), assigning positive outputs for labeled InD samples $\boldsymbol{x} \in \mathcal{S}_{\text{in}}$ and negative outputs for candidate outliers $\tilde{\boldsymbol{x}} \in \hat{\mathcal{S}}_{\text{out}}$. Specifically, the loss function is defined as:

$$
\begin{aligned}
\mathcal{L}_{\mathcal{S}_{\text{in}}, \hat{\mathcal{S}}_{\text{out}}}(g_\theta) &= \mathcal{L}_{\mathcal{S}_{\text{in}}}^{+}(g_\theta) + \mathcal{L}_{\hat{\mathcal{S}}_{\text{out}}}^{-}(g_\theta), \\
\mathcal{L}_{\mathcal{S}_{\text{in}}}^{+}(g_\theta) &= \mathbb{E}_{\boldsymbol{x} \in \mathcal{S}_{\text{in}}} \mathcal{I}\{g_\theta(\boldsymbol{x}) \leq 0\}, \\
\mathcal{L}_{\hat{\mathcal{S}}_{\text{out}}}^{-}(g_\theta) &= \mathbb{E}_{\tilde{\boldsymbol{x}} \in \hat{\mathcal{S}}_{\text{out}}} \mathcal{I}\{g_\theta(\tilde{\boldsymbol{x}}) > 0\}.
\end{aligned}
\tag{6}
$$

4 Theoretical Analysis

We now present the theoretical guarantees of Medix's filtering stage. The following theorems provide provable upper bounds on the misclassification rates for both InD and OOD points. Together, they demonstrate the two-sided robustness of our EWM filtering. For detailed proofs, see Appendix C.

Setup. Under the Huber contamination model in Eq. 1, each wild point $\tilde{x}_i \in \mathcal{S}_{\text{wild}}$ is independently InD with probability $1 - \pi$ and OOD with probability π. This partitions $\mathcal{S}_{\text{wild}}$ into a true InD subset $\mathcal{I}$ and a true OOD subset $\mathcal{O}$, whose (random) sizes we write $M_{\text{in}} = |\mathcal{I}|$ and $M_{\text{out}} = |\mathcal{O}|$, with $M_{\text{in}} + M_{\text{out}} = m$ and $\mathbb{E}[M_{\text{in}}] = (1 - \pi)m$. We denote by $G_i = \nabla \ell\big(f_{\phi_{\mathcal{S}_{\text{in}}}}(\tilde{x}_i), \hat{y}_{\tilde{x}_i}\big) \in \mathbb{R}^d$ the gradient of wild sample i, with j-th coordinate $G_{i,j}$ and d the gradient dimension. Our analysis targets the *ideal size-constrained* EWM filter, i.e. the exact minimizer of the objective in Eq. 5 restricted to subsets of size M_{in},

$$
\mathcal{S}^\star \in \arg \min_{\substack{\mathcal{S} \subseteq \mathcal{S}_{\text{wild}} \\ |\mathcal{S}| = M_{\text{in}}}} \big\| \text{EWM}(G_{\mathcal{S}}) - \bar{\nabla}_{\text{in}} \big\|_2,
\tag{7}
$$

which Algorithm 1 approximates greedily. We quantify its quality by the inlier misclassification rate, the fraction of true InD points it discards: $\text{ERR}_{\text{in}} = |\mathcal{I} \setminus \mathcal{S}^\star| / M_{\text{in}}$.

Assumption 4.1 (Sub-Gaussian InD gradients). The InD gradients $\{G_i\}_{i \in \mathcal{I}}$ are i.i.d., and each centered coordinate $G_{i,j} - \bar{\nabla}_{\text{in},j}$ is sub-Gaussian with variance proxy σ^2.

Theorem 4.2 (Inlier Misclassification Bound). *Let Assumption 4.1 hold, fix a confidence level $\delta \in (0, 1)$, and set $\epsilon = \sigma \sqrt{2 \log(4dm/\delta)}$. If*

$$
m \geq \frac{2 \log(2/\delta)}{(1 - \pi)^2},
$$

then, with probability at least $1 - \delta$, the ideal filter $\mathcal{S}^\star$ of Eq. 7 satisfies

$$
\text{ERR}_{\text{in}} \leq \underbrace{\frac{2}{(1 - \pi)^2} \sqrt{\frac{\log(2/\delta)}{2m}}}_{concentration} + \underbrace{\frac{\pi}{1 - \pi}}_{contamination}.
$$

Moreover, the selected subset stays close to the reference gradient, $\big\| \text{EWM}(G_{\mathcal{S}^\star}) - \bar{\nabla}_{\text{in}} \big\|_2 \leq \epsilon \sqrt{d}$.

Theorem 4.2 gives two guarantees for the ideal size-constrained EWM filtering rule. First, the selected subset has controlled EWM deviation from the InD reference gradient: since the true InD subset $\mathcal{I}$ is feasible, optimality ensures that $\mathcal{S}^\star$ cannot have larger median deviation than $\mathcal{I}$. Second, because the filter retains M_{in} samples, each retained OOD point disPLACES one true InD point. Thus the inlier error is controlled by the realized OOD-to-InD ratio. The concentration term comes from fluctuations in the Huber contamination count, while the contamination term captures the nominal ratio $\pi/(1 - \pi)$.

Theorem 4.2 controls the InD-side error; we now bound the complementary OOD-side error, the fraction of true OOD points that the ideal filter $\mathcal{S}^\star$ retains as InD. Recalling $\mathcal{O}$ and $M_{\text{out}} = |\mathcal{O}|$ from above, we measure this by the outlier misclassification rate $\text{ERR}_{\text{out}} = |\mathcal{S}^\star \cap \mathcal{O}| / M_{\text{out}}$. The guarantee depends on the mean OOD gradient μ_{out} and its coordinate-wise sub-Gaussian variance proxy σ_{out}^2.

Assumption 4.3 (Sub-Gaussian OOD gradients with separation). The OOD gradients $\{G_i\}_{i \in \mathcal{O}}$ are i.i.d., and each coordinate is sub-Gaussian with variance proxy σ_{out}^2, centered at the corresponding coordinate of μ_{out}. Moreover, the OOD mean is separated from the reference gradient, $\left\|\mu_{\text{out}} - \bar{\nabla}_{\text{in}}\right\|_2 \geq \Delta\sqrt{d}$ for some $\Delta > 0$.

Theorem 4.4 (Outlier Misclassification Bound). *Let Assumption 4.3 hold, together with the reference EWM accuracy condition stated in Appendix C.2. For any tolerance $\varepsilon \in (0, \Delta)$ and confidence level $\delta \in (0, 1)$, with probability at least $1 - \delta$, the ideal filter $\mathcal{S}^\star$ of Eq. 7 satisfies*

$$\text{ERR}_{\text{out}} \leq \underbrace{2d\exp\left(-\frac{(\Delta - \varepsilon)^2}{2\sigma_{\text{out}}^2}\right)}_{separation} + \underbrace{\sqrt{\frac{\log(1/\delta)}{2M_{\text{out}}}}}_{concentration} + \underbrace{\frac{1 - \pi}{2\pi}}_{contamination}.$$

Theorem 4.4 assumes that the EWM of the true InD gradients in the wild set is close to the InD reference gradient, i.e.,

$$\left\|\text{EWM}(G_I) - \bar{\nabla}_{\text{in}}\right\|_2 \leq \epsilon\sqrt{d}.$$

The following corollary shows that this condition holds with high probability under bounded fourth moments, so the argument does not require sub-Gaussian InD gradients.

Corollary 4.5 (Reference accuracy under bounded fourth moments). *Suppose the true InD gradients in the wild set have bounded fourth moments around the reference gradient $\bar{\nabla}_{\text{in}}$. Then the EWM of these InD gradients concentrates around $\bar{\nabla}_{\text{in}}$ for any tolerance $\varepsilon > 0$ satisfying $p_\varepsilon := \mu_4/\varepsilon^4 < 1/2$,*

$$\left\|\text{EWM}(G_I) - \bar{\nabla}_{\text{in}}\right\|_2 \leq \varepsilon\sqrt{d}$$

with probability at least

$$1 - 2d\exp\left(-2M_{\text{in}}\left(\frac{1}{2} - p_\varepsilon\right)^2\right).$$

Theorem 4.4 complements the previous result by bounding the fraction of OOD points mistakenly retained as InD. Together, Theorems 4.2 and 4.4 provide a two-sided guarantee for the robustness of the Medix filtering method. The inlier and outlier misclassification rates are governed by a balance between the following three effects:

Contamination Effect. For Theorem 4.2, even when the wild dataset contains a significant fraction π of OOD points, the median-based criterion remains stable as long as $\pi < 0.5$. This is reflected in the $\pi/(1 - \pi)$ term of the bound, which increases with π and encodes the risk that OOD gradients may skew the EWM. Conversely, Theorem 4.4 includes a symmetric penalty $\frac{1-\pi}{2\pi}$, quantifying the difficulty of isolating OOD points when they are underrepresented.

Concentration Effect. Both bounds exploit the sub-Gaussian nature of the gradient coordinates. For InD data, this ensures that most gradients concentrate near $\bar{\nabla}_{\text{in}}$, keeping the median stable even in finite samples. For OOD points, concentration around μ_{out} allows us to quantify the risk that a misaligned OOD sample slips past the filter. These concentration terms decay with the relevant sample count, as $1/\sqrt{m}$ for the inlier bound and $1/\sqrt{M_{\text{out}}}$ for the outlier bound.

Separation Effect. Unique to Theorem 4.4, this effect quantifies how far the OOD mean gradient must lie from the InD mean gradient in order to reliably reject OOD samples. The exponential term $\exp(-(\Delta - \varepsilon)^2/2\sigma_{\text{out}}^2)$ captures this trade-off: the more separated the distributions, the less likely it is for OOD gradients to fool the filter.

Remark 4.6. Eq. 5 defines the ideal filtering problem, and Theorems 4.2 and 4.4 analyze its exact solution $\mathcal{S}^\star$. Algorithm 1 is our tractable approximation to this objective. Accordingly, the theorems establish the robustness of the target criterion, while Algorithm 1 is supported by empirical results.

Theorems 4.2 and 4.4 jointly establish that, with high probability, median filtering achieves robust separation of InD and OOD samples in unlabeled data mixtures. The fraction of InD samples misclassified as outliers is bounded by contamination and concentration effects, while the fraction of OOD points incorrectly retained is governed by an exponential separation term, a concentration bound, and a reverse contamination effect.

5 Experiments

This section will demonstrate the efficacy of Medix across various InD-OOD dataset pairs, benchmarking it against 20 widely-used baselines. All experiments are performed on hardware equipped with NVIDIA A100-SXM4-80GB GPUs. We provide the necessary code to reproduce our results.

5.1 Models, Datasets, and Baselines

Datasets. We use the same experimental protocol as Katz-Samuels et al. (2022), which introduced the problem of learning OOD detectors with wild data. Specifically, we use CIFAR-10 and CIFAR-100 as InD datasets ($\mathbb{P}_{\text{in}}$). For OOD testing, we select a suite of image datasets, including PLACES365 (Zhou et al., 2017), SVHN, TEXTURES (Cimpoi et al., 2014), and LSUN-RESIZE & LSUN-C (Yu et al., 2015) as OOD datasets ($\mathbb{P}_{\text{out}}$). To simulate wild data ($\mathbb{P}_{\text{wild}}$), we combine a subset of InD data ($\mathbb{P}_{\text{in}}$) with the OOD data ($\mathbb{P}_{\text{out}}$) under a default mixing parameter $\pi = 0.5$. For example, when using PLACES365 as an OOD test set, we construct a wild mixture by combining CIFAR with PLACES365 as wild data and test on PLACES365 as the OOD set. This procedure is repeated across all OOD datasets and baselines. The InD CIFAR dataset is split into two halves: the first 25,000 images to train $\phi_{\mathcal{S}_{\text{in}}}$, while the remaining images to generate the wild mixture $\mathcal{S}_{\text{wild}}$. For gradient computation, we use the penultimate layer weights, as these have been shown to be particularly informative for OOD detection (Huang et al., 2021).

Evaluation metrics. We evaluate using three standard metrics: (1) False Positive Rate (FPR95↓) of OOD samples when the True Positive Rate of InD samples is 95%, (2) Area Under the Receiver Operating Characteristic Curve (AUROC↑), and (3) InD Classification Accuracy (InD Acc↑).

Baselines. Our comparison is categorized based on whether they are trained using only InD data or both InD and wild data. For the methods trained exclusively on InD data ($\mathbb{P}_{\text{in}}$), we compare Medix against a variety of established OOD detection methods, including Maximum Softmax Probability (MSP) (Hendrycks & Gimpel, 2017), ODIN (Liang et al., 2018), Mahalanobis Distance (Lee et al., 2018b), Energy Score (Liu et al., 2020c), ReAct (Sun et al., 2021), DICE (Sun & Li, 2022), KNN Distance (Sun et al., 2022), and ASH (Djurisic et al., 2023); these methods use a model trained with softmax cross-entropy loss. Additionally, we also compare against methods based on contrastive loss, such as CSI (Tack et al., 2020b) and KNN+ (Sun et al., 2022), for a more comprehensive comparison. For methods that leverage both InD and wild data, we compare against Outlier Exposure (OE) (Hendrycks et al., 2019) and energy-regularization learning (Liu et al., 2020c), which regularize the training by promoting lower confidence or higher energy on outlier data. We also include a comparison with WOODS (Katz-Samuels et al., 2022), which introduced the concept of wild unlabeled data and utilizes it for OOD detection through a constrained optimization approach. Finally, we included more recent baselines, including CONJ (Peng et al., 2024) and DRL (Zhang et al., 2024), to provide a more thorough evaluation.

5.2 Experimental Setup

In line with WOODS (Katz-Samuels et al., 2022), we employ a Wide ResNet architecture (Zagoruyko, 2016) with 40 layers and a width factor of 2 for the InD classifier $\phi_{\mathcal{S}_{\text{in}}}$. It is trained using stochastic gradient descent

with a momentum of 0.9, weight decay of 0.0005, and an initial learning rate of 0.1. Training is performed for 100 epochs with cosine learning rate decay, a batch size of 128, and a dropout rate of 0.3. Hyperparameters ϵ and k used in the proposed method Medix are selected from the sets {5e-5, 5e-4, 5e-3, 5e-2} and {4k, 7k, 10k, 20k}, respectively, taking into account dataset sizes and with the objective of maximizing OOD performance. For the OOD classifier g_θ, we initialize it with the pre-trained InD classifier $\phi_{\mathcal{S}_{in}}$ and add a linear layer that performs binary classification using the penultimate-layer features. The learning rate for this classifier is set to 0.001, and fine-tuning is done for 100 epochs as outlined in Equation 6. We combine the binary classification loss with the InD classification loss, assigning a weight of 10 to the binary classification component. All other training parameters remain the same as those used for training $\phi_{\mathcal{S}_{in}}$.

Table 1: OOD detection performance comparison of Medix and baselines on CIFAR-10 as InD data. Performance averaged over five runs; best results are highlighted in **bold**.

Methods	OOD Datasets												InD ACC↑
	Svhn		Places365		Lsun-C		Lsun-Resize		Textures		Average		
	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	
	Using $\mathbb{P}_{in}$ only												
MSP	48.49	91.89	59.48	88.20	30.80	95.65	52.15	91.37	59.28	88.50	50.04	91.12	94.84
ODIN	33.35	91.96	57.40	84.49	15.52	97.04	26.62	94.57	49.12	84.97	36.40	90.61	94.84
Mahalanobis	12.89	97.62	68.57	84.61	39.22	94.15	42.62	93.23	15.00	97.33	35.66	93.34	94.84
Energy	35.59	90.96	40.14	89.89	8.26	98.35	27.58	94.24	52.79	85.22	32.87	91.73	94.84
KNN	24.53	95.96	25.29	95.69	25.55	95.26	27.57	94.71	50.90	89.14	30.77	94.15	94.84
ReAct	40.76	89.57	41.44	90.44	14.38	97.21	33.63	93.58	53.63	86.59	36.77	91.48	94.84
DICE	35.44	89.65	46.83	86.69	6.32	98.68	28.93	93.56	53.62	82.20	34.23	90.16	94.84
ASH	6.51	98.65	48.45	88.34	0.90	99.73	4.96	98.92	24.34	95.09	17.03	96.15	94.84
CSI	17.30	97.40	34.95	93.64	1.95	99.55	12.15	98.01	20.45	95.93	17.36	96.91	94.17
KNN+	2.99	99.41	24.69	94.84	2.95	99.39	11.22	97.98	9.65	98.37	10.30	97.99	93.19
	Using $\mathbb{P}_{in}$ and $\mathbb{P}_{wild}$												
OE	1.13	99.53	19.48	94.88	1.91	98.16	0.54	98.84	7.75	98.56	6.16	97.99	94.12
Energy (w/ OE)	5.24	98.72	14.66	96.18	2.35	99.30	4.85	98.62	10.51	97.10	7.52	97.98	94.24
WOODS	0.17	99.91	10.19	98.05	0.31	99.14	0.11	99.38	6.21	98.13	3.40	98.92	94.74
Medix	**0.06**	**99.98**	**2.98**	**99.10**	**0.01**	**99.98**	**0.01**	**99.98**	**0.96**	**99.66**	**0.80**	**99.74**	93.58
(Ours)	±0.01	±0.01	±0.29	±0.09	±0.01	±0.00	±0.01	±0.01	±0.13	±0.06	±0.09	±0.03	±0.64

Table 2: OOD detection performance comparison of Medix and baselines on CIFAR-100 as InD data. Performance averaged over five runs; best results are highlighted in **bold**.

Methods	OOD Datasets												InD ACC↑
	Svhn		Places365		Lsun-C		Lsun-Resize		Textures		Average		
	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	
	Using $\mathbb{P}_{in}$ only												
MSP	84.59	71.44	82.84	73.78	66.54	83.79	82.42	75.38	83.29	73.34	79.94	75.55	75.96
ODIN	84.66	67.26	87.88	71.63	55.55	87.73	71.96	81.82	79.27	73.45	75.86	76.38	75.96
Mahalanobis	57.52	86.01	88.83	67.87	91.18	69.69	21.23	96.00	39.39	90.57	59.63	82.03	75.96
Energy	85.82	73.99	80.56	75.44	35.32	93.53	79.47	79.23	79.41	76.28	72.12	79.69	75.96
KNN	66.38	83.76	79.17	71.91	70.96	83.71	77.83	78.85	88.00	67.19	76.47	77.08	75.96
ReAct	74.33	88.04	81.33	74.32	39.30	91.19	79.86	73.69	67.38	82.80	68.44	82.01	75.96
DICE	88.35	72.58	81.61	75.07	26.77	94.74	80.21	78.50	76.29	76.07	70.65	79.39	75.96
ASH	21.36	94.28	68.37	71.22	15.27	95.65	68.18	85.42	40.87	92.29	42.81	87.77	75.96
CSI	64.70	84.97	82.25	73.63	38.10	92.52	91.55	63.42	74.70	92.66	70.26	81.44	69.90
KNN+	32.21	93.74	68.30	75.31	40.37	86.13	44.86	88.88	46.26	87.40	46.40	86.29	73.78
	Using $\mathbb{P}_{in}$ and $\mathbb{P}_{wild}$												
OE	2.86	99.05	40.21	88.75	4.13	99.05	1.25	99.38	22.86	94.63	14.26	96.17	73.38
Energy (w/ OE)	2.71	99.34	34.82	90.05	3.27	99.18	2.54	99.23	30.16	94.76	14.70	96.51	72.76
WOODS	0.17	99.80	21.87	93.73	0.48	99.61	1.24	99.54	9.95	95.97	6.74	97.73	73.91
Medix	**0.16**	**99.96**	**15.99**	**95.23**	**0.13**	**99.98**	**0.83**	**99.83**	**8.02**	**97.79**	**5.42**	**98.96**	73.33
(Ours)	±0.02	±0.00	±0.66	±0.14	±0.06	±0.02	±0.36	±0.06	±0.75	±0.30	±0.37	±0.10	±0.83

5.3 Results

We present our main results in Table 2 on CIFAR-100, where Medix remarkably outperforms all OOD detection baselines. The results highlight the following key observations: (1) Methods trained on both InD and wild data significantly outperform those trained exclusively on InD data. Medix reduces the FPR95 by 52.31% on PLACES365 and 38.24% on TEXTURES compared to KNN+, demonstrating the effectiveness of incorporating in-the-wild data for model regularization. (2) Medix further outperforms competitive methods utilizing wild data ($\mathbb{P}_{wild}$): On CIFAR-100, Medix achieves an average FPR95 of 5.42%, which represents a 1.32% improvement over WOODS. Additionally, Medix maintains a competitive InD accuracy of 73.33%. This slight difference can be attributed to the fact that our method is trained on 25,000 labeled InD samples, while baseline methods, which do not leverage wild data, use the full CIFAR-100 training set of 50,000 samples. We present the results for CIFAR-10 in Table 1, where Medix surpasses all baseline methods. Medix outperforms WOODS by 7.21% on PLACES365 and 5.25% on TEXTURES in terms of FPR95, demonstrating its effectiveness in detecting OOD samples.

Figure 3: Example of Medix applied to unlabeled wild data. (a) Setup of the InD data $\mathcal{S}_{\mathrm{wild}}^{\mathrm{in}}$ and OOD data $\mathcal{S}_{\mathrm{wild}}^{\mathrm{out}}$ in the wild, with inliers sampled from three multivariate Gaussian distributions. (b) Outliers $\hat{\mathcal{S}}_{\mathrm{out}}$ filtered by Medix (in black), with an error rate of $\hat{\mathcal{S}}_{\mathrm{out}}$ containing InD data $\mathcal{S}_{\mathrm{wild}}^{\mathrm{in}}$ is only 12.5%.

A representative visual example of Medix. We further investigate the performance of Algorithm 1 (Outlier Extraction) in extracting OOD samples from wild data $\mathcal{S}_{\mathrm{wild}}$. To visualize this, we design an experiment using 2-dimensional synthetic data. This simulation is designed to be simple to facilitate better understanding. We generate the InD data by sampling from three multivariate Gaussian distributions, corresponding to three classes. The mean vectors are set to $[-2, 0]$, $[2, 0]$, and $[0, 2\sqrt{3}]$, respectively. The covariance matrix for all three classes is fixed at $0.25 \cdot \mathcal{I}$. For the OOD data, we use a multivariate Gaussian distribution $\mathcal{N}([20, 2\sqrt{3}], 0.25 \cdot \mathcal{I})$. In Figure 3, we observe that our method successfully identifies outliers, the majority of which align with the ground truth. Medix successfully flags 87.5% of actual OOD samples as outliers, underscoring its robustness in outlier extraction.

Additional Experiments. We defer additional experiments to Appendix A, which include (1) ablation studies on hyperparameter selection and sensitivity analysis (Appendix A.2), showing Medix's strong robustness to hyperparameters, (2) a comparison between EWM and geometric median (Appendix A.1), showing that EWM is more sensitive to distributional shifts, making it more effective and reliable choice for filtering in our method, (3) a comprehensive comparison with methods employing competitive contrasting learning objectives (Appendix A.3), demonstrating that Medix outperforms even these competitive baselines by a significant margin, (4) evaluation on large-scale data under the complex unseen OOD setting, where $\mathbb{P}_{\mathrm{out}}^{\mathrm{test}} \neq \mathbb{P}_{\mathrm{out}}$ (Appendix A.4), demonstrating that Medix outperforms baselines by a significant margin, (5) evaluating computation and memory efficiency of Medix (Appendix A.6) (6) evaluating the impact of pseudo-label quality (Appendix A.5), showing that our method is resilient to noisy or low-confidence labels, and (7) a comparison with semi-supervised open-set recognition methods (Appendix A.7), (8) a scalability analysis of Medix across larger architectures, showing that the L2-based filtering signal remains robust even in high-dimensional gradient spaces (Appendix A.8), (9) evaluation on ImageNet-1k, demonstrating Medix's strong generalization to high-resolution, large-scale datasets (Appendix A.9), and (10) a comparison against a naive two-stage baseline that replaces our median filter with MSP-filtering (Appendix A.10), confirming that Medix's gains stem from the precision of its median filtering rather than the two-stage pipeline alone.

6 Related Work

In recent years, there has been a growing interest in OOD detection (Fort et al., 2021; Yang et al., 2024; Fang et al., 2022; Zhu et al., 2022; Yang et al., 2022; Wang et al., 2022c; Galil et al., 2023; Djurisic et al., 2023; Tao et al., 2023; Zheng et al., 2023; Wang et al., 2022b; 2023b; Uppaal et al., 2023; Zhu et al., 2023; Bai et al., 2023; Ming & Li, 2024; Zhang et al., 2023; Ghosal et al., 2024; Abbas et al., 2025). One approach to detect OOD data uses scoring functions to assess data distribution, including distance-based methods (Lee et al., 2018a; Tack et al., 2020a; Ren et al., 2021; Sehwag et al., 2021; Sun et al., 2022; Du et al., 2022a; Ming et al., 2023; Ren et al., 2022), gradient-based score (Huang et al., 2021), energy-based score (Liu et al.,

2020b; Wang et al., 2021; Wu et al., 2023), confidence-based approaches (Bendale & Boult, 2016; Hendrycks & Gimpel, 2017; Liang et al., 2018), and Bayesian methods (Gal & Ghahramani, 2016; Lakshminarayanan et al., 2017; Maddox et al., 2019; Malinin & Gales, 2019; Wen et al., 2020; Kristiadi et al., 2020).

Another approach to OOD detection involves using regularization techniques during the training phase (Malinin & Gales, 2018; Geifman & El-Yaniv, 2019; Hein et al., 2019; Meinke & Hein, 2020; Jeong & Kim, 2020; Liu et al., 2020a; Van Amersfoort et al., 2020; Yang et al., 2021; Wei et al., 2022; Du et al., 2022b; 2023; Wang et al., 2023a). For example, regularization techniques can be applied to the model to either reduce its confidence (Lee et al., 2017; Hendrycks et al., 2019) or increase its energy (Liu et al., 2020b; Du et al., 2022c; Ming et al., 2022) on the OOD data. Most of these regularization methods assume the availability of an auxiliary OOD dataset.

Several studies (Zhou et al., 2021; Katz-Samuels et al., 2022; He et al., 2023) have relaxed the assumption of using only labeled data by incorporating unlabeled wild data (Katz-Samuels et al., 2022; Geng et al., 2025), though they did not propose a clear mechanism for outlier detection. In contrast, Du et al. (2024a;b) introduced an explicit outlier filtering method, but their thresholding technique differs fundamentally from ours, as we utilize a new median-centric approach to detect the outliers. Additionally, Katz-Samuels et al. (2022); Du et al. (2024a) operate under the assumption of batch-level mixing, where each batch has a set ratio of InD and OOD samples. However, with large outsourced datasets, such structured mixing is not available-data is mixed randomly across the dataset. Our method addresses this by enabling dataset-level mixing without relying on batch-level structure. Many studies also leverage positive-unlabeled learning, which trains classifiers using positive and/or unlabeled data (Letouzey et al., 2000; Hsieh et al., 2015; Plessis et al., 2015; Niu et al., 2016; Gong et al., 2018; Chapel et al., 2020; Garg et al., 2021; Xu & Denil, 2021; Garg et al., 2022; Zhao et al., 2022; Acharya et al., 2022). However, a key distinction from our approach is that these methods focus solely on differentiating $\mathbb{P}_{out}$ from $\mathbb{P}_{in}$, without simultaneously training an OOD classifier. Additionally, we propose a median-centric method to identify outliers in unlabeled data, with provably low error rates.

Generation-based OOD methods (Marek et al., 2021; Yoon et al., 2023; Gao et al., 2025; Abbas et al., 2025; Yoon et al., 2025; 2023; Lee et al., 2025) represent an important complementary line of research. These approaches synthesise OOD samples using diffusion models, GANs, normalising flows, or LLMs, and then train OOD detectors on the synthetic data. Unlike Medix, which extracts outliers from real unlabeled wild data, generation-based methods do not require a wild mixture but instead rely on a generative model to produce plausible OOD proxies. While Medix offers theoretical guarantees on extraction error and computational simplicity, generation-based methods can be advantageous when no wild data is available or when large-scale synthetic augmentation is desired. A comprehensive comparison of these two paradigms is an interesting direction for future work.

7 Conclusions

In this work, we introduced Medix, a novel median-centric framework for OOD detection that leverages unlabeled in-the-wild data. Using the inherent robustness of median operation, Medix effectively filters outliers from mixed unlabeled data, enabling the training of a reliable OOD detector. Our theoretical analysis established provable bounds on the inlier misclassification rate, demonstrating that Medix maintains robustness even under significant OOD contamination (up to 50%), with errors controlled by sub-Gaussian concentration and contamination effects. We also provided complementary theoretical limits on the rate of OOD misclassification to accurately isolate OOD samples under clear separation conditions. Empirical validation across diverse benchmarks showcased Medix's performance superiority over 20 baselines: it reduced the average FPR95 by 40.98% compared to strong baselines like KNN+ and outperformed state-of-the-art methods such as WOODS and DRL, while achieving an outlier extraction error rate as low as 12.5%.

References

Momin Abbas, Muneeza Azmat, Raya Horesh, and Mikhail Yurochkin. Out-of-distribution detection using synthetic data generation. In *Second Conference on Language Modeling*, 2025.

Anish Acharya, Sujay Sanghavi, Li Jing, Bhargav Bhushanam, Dhruv Choudhary, Michael Rabbat, and Inderjit Dhillon. Positive unlabeled contrastive learning. *arXiv preprint arXiv:2206.01206*, 2022.

Anish Acharya, Inderjit S Dhillon, and Sujay Sanghavi. Geometric median (gm) matching for robust data pruning. *arXiv preprint arXiv:2406.17188*, 2024.

Haoyue Bai, Gregory Canal, Xuefeng Du, Jeongyeol Kwon, Robert D Nowak, and Yixuan Li. Feed two birds with one scone: Exploiting wild data for both out-of-distribution generalization and detection. In *International Conference on Machine Learning*, pp. 1454–1471. PMLR, 2023.

Abhijit Bendale and Terrance E Boult. Towards open set deep networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1563–1572, 2016.

Laetitia Chapel, Mokhtar Z. Alaya, and Gilles Gasso. Partial optimal tranport with applications on positive-unlabeled learning. In *Advances in Neural Information Processing Systems*, volume 33, pp. 2903–2913. Curran Associates, Inc., 2020.

Mircea Cimpoi, Subhransu Maji, Iasonas Kokkinos, Sammy Mohamed, and Andrea Vedaldi. Describing textures in the wild. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 3606–3613, 2014.

Andrija Djurisic, Nebojsa Bozanic, Arjun Ashok, and Rosanne Liu. Extremely simple activation shaping for out-of-distribution detection. In *The Eleventh International Conference on Learning Representations*, 2023.

Xuefeng Du, Gabriel Gozum, Yifei Ming, and Yixuan Li. Siren: Shaping representations for detecting out-of-distribution objects. In *Advances in Neural Information Processing Systems*, volume 35, pp. 20434–20449. Curran Associates, Inc., 2022a.

Xuefeng Du, Xin Wang, Gabriel Gozum, and Yixuan Li. Unknown-aware object detection: Learning what you don't know from videos in the wild. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 13678–13688, 2022b.

Xuefeng Du, Zhaoning Wang, Mu Cai, and Sharon Li. Towards unknown-aware learning with virtual outlier synthesis. In *International Conference on Learning Representations*, 2022c.

Xuefeng Du, Yiyou Sun, Jerry Zhu, and Yixuan Li. Dream the impossible: Outlier imagination with diffusion models. In *Advances in Neural Information Processing Systems*, volume 36, pp. 60878–60901. Curran Associates, Inc., 2023.

Xuefeng Du, Zhen Fang, Ilias Diakonikolas, and Yixuan Li. How does unlabeled data provably help out-of-distribution detection? In *The Twelfth International Conference on Learning Representations*, 2024a.

Xuefeng Du, Reshmi Ghosh, Robert Sim, Ahmed Salem, Vitor Carvalho, Emily Lawton, Yixuan Li, and Jack W Stokes. Vlmguard: Defending vlms against malicious prompts via unlabeled data. *arXiv preprint arXiv:2410.00296*, 2024b.

Yue Fan, Anna Kukleva, Dengxin Dai, and Bernt Schiele. Ssb: Simple but strong baseline for boosting performance of open-set semi-supervised learning. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 16068–16078, October 2023.

Zhen Fang, Yixuan Li, Jie Lu, Jiahua Dong, Bo Han, and Feng Liu. Is out-of-distribution detection learnable? In *Advances in Neural Information Processing Systems*, volume 35, pp. 37199–37213. Curran Associates, Inc., 2022.

Stanislav Fort, Jie Ren, and Balaji Lakshminarayanan. Exploring the limits of out-of-distribution detection. *Advances in Neural Information Processing Systems*, 34:7068–7081, 2021.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *Proceedings of The 33rd International Conference on Machine Learning*, volume 48 of *Proceedings of Machine Learning Research*, pp. 1050–1059, New York, New York, USA, 20–22 Jun 2016. PMLR.

Ido Galil, Mohammed Dabbah, and Ran El-Yaniv. A framework for benchmarking class-out-of-distribution detection and its application to imagenet. In *The Eleventh International Conference on Learning Representations*, 2023.

Xin Gao, Jiyao Liu, Guanghao Li, Yueming Lyu, Jianxiong Gao, Weichen Yu, Ningsheng Xu, Liang Wang, Caifeng Shan, Ziwei Liu, and Chenyang Si. GOOD: Training-free guided diffusion sampling for out-of-distribution detection. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025.

Saurabh Garg, Yifan Wu, Alexander J Smola, Sivaraman Balakrishnan, and Zachary Lipton. Mixture proportion estimation and pu learning:a modern approach. In *Advances in Neural Information Processing Systems*, volume 34, pp. 8532–8544. Curran Associates, Inc., 2021.

Saurabh Garg, Sivaraman Balakrishnan, and Zachary Lipton. Domain adaptation under open set label shift. In *Advances in Neural Information Processing Systems*, volume 35, pp. 22531–22546. Curran Associates, Inc., 2022.

Yonatan Geifman and Ran El-Yaniv. SelectiveNet: A deep neural network with an integrated reject option. In *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 2151–2159. PMLR, 09–15 Jun 2019.

Chuanxing Geng, Qifei Li, Xinrui Wang, Dong Liang, Songcan Chen, and Pong C Yuen. Lod: Loss-difference ood detection by intentionally label-noisifying unlabeled wild data. *arXiv preprint arXiv:2505.12952*, 2025.

Soumya Suvra Ghosal, Yiyou Sun, and Yixuan Li. How to overcome curse-of-dimensionality for out-of-distribution detection? In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pp. 19849–19857, 2024.

Tieliang Gong, Guangtao Wang, Jieping Ye, Zongben Xu, and Ming Lin. Margin based pu learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

Jun-Yi Hang and Min-Ling Zhang. Binary decomposition: A problem transformation perspective for open-set semi-supervised learning. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pp. 17505–17518. PMLR, 21–27 Jul 2024.

Rundong He, Rongxue Li, Zhongyi Han, Xihong Yang, and Yilong Yin. Topological structure learning for weakly-supervised out-of-distribution detection. In *Proceedings of the 31st ACM International Conference on Multimedia*, pp. 4858–4866, 2023.

Matthias Hein, Maksym Andriushchenko, and Julian Bitterwolf. Why relu networks yield high-confidence predictions far away from the training data and how to mitigate the problem. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 41–50, 2019.

Dan Hendrycks and Kevin Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. In *International Conference on Learning Representations*, 2017.

Dan Hendrycks, Mantas Mazeika, and Thomas Dietterich. Deep anomaly detection with outlier exposure. In *International Conference on Learning Representations*, 2019.

Cho-Jui Hsieh, Nagarajan Natarajan, and Inderjit Dhillon. Pu learning for matrix completion. In *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pp. 2445–2453, Lille, France, 07–09 Jul 2015. PMLR.

Rui Huang, Andrew Geng, and Yixuan Li. On the importance of gradients for detecting distributional shifts in the wild. *Advances in Neural Information Processing Systems*, 34:677–689, 2021.

Peter J Huber. Robust estimation of a location parameter. *The Annals of Mathematical Statistics*, 35(1): 73–101, 1964.

Taewon Jeong and Heeyoung Kim. Ood-maml: Meta-learning for few-shot out-of-distribution detection and classification. In *Advances in Neural Information Processing Systems*, volume 33, pp. 3907–3916. Curran Associates, Inc., 2020.

Julian Katz-Samuels, Julia B Nakhleh, Robert Nowak, and Yixuan Li. Training OOD detectors in their natural habitats. In *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 10848–10865. PMLR, 17–23 Jul 2022.

Sungyeon Kim, Dongwon Kim, Minsu Cho, and Suha Kwak. Proxy anchor loss for deep metric learning. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 3235–3244, 2020.

Agustinus Kristiadi, Matthias Hein, and Philipp Hennig. Being bayesian, even just a bit, fixes overconfidence in relu networks. In *International conference on machine learning*, pp. 5436–5446. PMLR, 2020.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

Giwoong Lee, Jiseung Ahn, and Jeongyeol Choe. Hybood: a hybrid generative model for out-of-distribution detection with corruption estimation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pp. 18101–18109, 2025.

Kimin Lee, Honglak Lee, Kibok Lee, and Jinwoo Shin. Training confidence-calibrated classifiers for detecting out-of-distribution samples. *arXiv preprint arXiv:1711.09325*, 2017.

Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. In *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018a.

Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. *Advances in neural information processing systems*, 31, 2018b.

Fabien Letouzey, François Denis, and Rémi Gilleron. Learning from positive and unlabeled examples. In *International Conference on Algorithmic Learning Theory*, pp. 71–85. Springer, 2000.

Shiyu Liang, Yixuan Li, and R. Srikant. Enhancing the reliability of out-of-distribution image detection in neural networks. In *International Conference on Learning Representations*, 2018.

Jeremiah Liu, Zi Lin, Shreyas Padhy, Dustin Tran, Tania Bedrax Weiss, and Balaji Lakshminarayanan. Simple and principled uncertainty estimation with deterministic deep learning via distance awareness. In *Advances in Neural Information Processing Systems*, volume 33, pp. 7498–7512. Curran Associates, Inc., 2020a.

Weitang Liu, Xiaoyun Wang, John Owens, and Yixuan Li. Energy-based out-of-distribution detection. In *Advances in Neural Information Processing Systems*, volume 33, pp. 21464–21475. Curran Associates, Inc., 2020b.

Weitang Liu, Xiaoyun Wang, John Owens, and Yixuan Li. Energy-based out-of-distribution detection. *Advances in neural information processing systems*, 33:21464–21475, 2020c.

Wesley J Maddox, Pavel Izmailov, Timur Garipov, Dmitry P Vetrov, and Andrew Gordon Wilson. A simple baseline for bayesian uncertainty in deep learning. In *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

Andrey Malinin and Mark Gales. Predictive uncertainty estimation via prior networks. In *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018.

Andrey Malinin and Mark Gales. Reverse kl-divergence training of prior networks: Improved uncertainty and adversarial robustness. In *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

Petr Marek, Vishal Ishwar Naik, Anuj Goyal, and Vincent Auvray. Oodgan: Generative adversarial network for out-of-domain data generation. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies: Industry Papers*, pp. 238–245, 2021.

Alexander Meinke and Matthias Hein. Towards neural networks that provably know when they don't know. In *International Conference on Learning Representations*, 2020.

Yifei Ming and Yixuan Li. How does fine-tuning impact out-of-distribution detection for vision-language models? *International Journal of Computer Vision*, 132(2):596–609, 2024.

Yifei Ming, Ying Fan, and Yixuan Li. POEM: Out-of-distribution detection with posterior sampling. In *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 15650–15665. PMLR, 17–23 Jul 2022.

Yifei Ming, Yiyou Sun, Ousmane Dia, and Yixuan Li. How to exploit hyperspherical embeddings for out-of-distribution detection? In *The Eleventh International Conference on Learning Representations*, 2023.

Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Baolin Wu, Andrew Y Ng, et al. Reading digits in natural images with unsupervised feature learning. In *NIPS workshop on deep learning and unsupervised feature learning*, volume 2011, pp. 4. Granada, 2011.

Anh Nguyen, Jason Yosinski, and Jeff Clune. Deep neural networks are easily fooled: High confidence predictions for unrecognizable images. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 427–436, 2015.

Gang Niu, Marthinus Christoffel Du Plessis, Tomoya Sakai, Yao Ma, and Masashi Sugiyama. Theoretical comparisons of positive-unlabeled learning against positive-negative learning. *Advances in neural information processing systems*, 29, 2016.

Bo Peng, Yadan Luo, Yonggang Zhang, Yixuan Li, and Zhen Fang. Conjnorm: Tractable density estimation for out-of-distribution detection. In *The Twelfth International Conference on Learning Representations*, 2024.

Marthinus Du Plessis, Gang Niu, and Masashi Sugiyama. Convex formulation for learning from positive and unlabeled data. In *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pp. 1386–1394, Lille, France, 07–09 Jul 2015. PMLR.

Jie Ren, Stanislav Fort, Jeremiah Liu, Abhijit Guha Roy, Shreyas Padhy, and Balaji Lakshminarayanan. A simple fix to mahalanobis distance for improving near-ood detection. *arXiv preprint arXiv:2106.09022*, 2021.

Jie Ren, Jiaming Luo, Yao Zhao, Kundan Krishna, Mohammad Saleh, Balaji Lakshminarayanan, and Peter J Liu. Out-of-distribution detection and selective generation for conditional language models. In *The Eleventh International Conference on Learning Representations*, 2022.

Kuniaki Saito, Donghyun Kim, and Kate Saenko. Openmatch: Open-set semi-supervised learning with open-set consistency regularization. In *Advances in Neural Information Processing Systems*, volume 34, pp. 25956–25967. Curran Associates, Inc., 2021.

Vikash Sehwag, Mung Chiang, and Prateek Mittal. {SSD}: A unified framework for self-supervised outlier detection. In *International Conference on Learning Representations*, 2021.

Yiyou Sun and Yixuan Li. Dice: Leveraging sparsification for out-of-distribution detection. In *European Conference on Computer Vision*, pp. 691–708. Springer, 2022.

Yiyou Sun, Chuan Guo, and Yixuan Li. React: Out-of-distribution detection with rectified activations. *Advances in Neural Information Processing Systems*, 34:144–157, 2021.

Yiyou Sun, Yifei Ming, Xiaojin Zhu, and Yixuan Li. Out-of-distribution detection with deep nearest neighbors. In *International Conference on Machine Learning*, pp. 20827–20840. PMLR, 2022.

Jihoon Tack, Sangwoo Mo, Jongheon Jeong, and Jinwoo Shin. Csi: Novelty detection via contrastive learning on distributionally shifted instances. In *Advances in Neural Information Processing Systems*, volume 33, pp. 11839–11852. Curran Associates, Inc., 2020a.

Jihoon Tack, Sangwoo Mo, Jongheon Jeong, and Jinwoo Shin. Csi: Novelty detection via contrastive learning on distributionally shifted instances. *Advances in neural information processing systems*, 33:11839–11852, 2020b.

Leitian Tao, Xuefeng Du, Jerry Zhu, and Yixuan Li. Non-parametric outlier synthesis. In *The Eleventh International Conference on Learning Representations*, 2023.

Rheeya Uppal, Junjie Hu, and Yixuan Li. Is fine-tuning needed? pre-trained language models are near perfect for out-of-domain detection. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 12813–12832, Toronto, Canada, July 2023. Association for Computational Linguistics.

Joost Van Amersfoort, Lewis Smith, Yee Whye Teh, and Yarin Gal. Uncertainty estimation using a single deep deterministic neural network. In *International conference on machine learning*, pp. 9690–9700. PMLR, 2020.

Haoqi Wang, Zhizhong Li, Litong Feng, and Wayne Zhang. Vim: Out-of-distribution with virtual-logit matching. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 4921–4930, 2022a.

Haoran Wang, Weitang Liu, Alex Bocchieri, and Yixuan Li. Can multi-label classification networks know what they don't know? *Advances in Neural Information Processing Systems*, 34:29074–29087, 2021.

Qizhou Wang, Feng Liu, Yonggang Zhang, Jing Zhang, Chen Gong, Tongliang Liu, and Bo Han. Watermarking for out-of-distribution detection. *Advances in Neural Information Processing Systems*, 35:15545–15557, 2022b.

Qizhou Wang, Zhen Fang, Yonggang Zhang, Feng Liu, Yixuan Li, and Bo Han. Learning to augment distributions for out-of-distribution detection. In *Advances in Neural Information Processing Systems*, volume 36, pp. 73274–73286. Curran Associates, Inc., 2023a.

Qizhou Wang, Junjie Ye, Feng Liu, Quanyu Dai, Marcus Kalander, Tongliang Liu, Jianye HAO, and Bo Han. Out-of-distribution detection with implicit outlier transformation. In *The Eleventh International Conference on Learning Representations*, 2023b.

Yu Wang, Jingjing Zou, Jingyang Lin, Qing Ling, Yingwei Pan, Ting Yao, and Tao Mei. Out-of-distribution detection via conditional kernel independence model. In *Advances in Neural Information Processing Systems*, volume 35, pp. 36411–36425. Curran Associates, Inc., 2022c.

Zerun Wang, Liuyu Xiang, Lang Huang, Jiafeng Mao, Ling Xiao, and Toshihiko Yamasaki. Scomatch: Alleviating overtrusting in open-set semi-supervised learning. In *European Conference on Computer Vision*, pp. 217–233. Springer, 2024.

Hongxin Wei, Renchunzi Xie, Hao Cheng, Lei Feng, Bo An, and Yixuan Li. Mitigating neural network overconfidence with logit normalization. In *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 23631–23644. PMLR, 17–23 Jul 2022.

Yeming Wen, Dustin Tran, and Jimmy Ba. Batchensemble: an alternative approach to efficient ensemble and lifelong learning. In *International Conference on Learning Representations*, 2020.

Qitian Wu, Yiting Chen, Chenxiao Yang, and Junchi Yan. Energy-based out-of-distribution detection for graph neural networks. In *The Eleventh International Conference on Learning Representations*, 2023.

Danfei Xu and Misha Denil. Positive-unlabeled reward learning. In *Conference on Robot Learning*, pp. 205–219. PMLR, 2021.

Jingkang Yang, Haoqi Wang, Litong Feng, Xiaopeng Yan, Huabin Zheng, Wayne Zhang, and Ziwei Liu. Semantically coherent out-of-distrution detection. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 8301–8309, 2021.

Jingkang Yang, Pengyun Wang, Dejian Zou, Zitang Zhou, Kunyuan Ding, Wenxuan Peng, Haoqi Wang, Guangyao Chen, Bo Li, Yiyou Sun, et al. Openood: Benchmarking generalized out-of-distribution detection. *Advances in Neural Information Processing Systems*, 35:32598–32611, 2022.

Jingkang Yang, Kaiyang Zhou, Yixuan Li, and Ziwei Liu. Generalized out-of-distribution detection: A survey. *International Journal of Computer Vision*, 132(12):5635–5662, 2024.

Suhee Yoon, Sanghyu Yoon, Hankook Lee, Sangjun Han, Ye Seul Sim, Kyungeun Lee, Hyeseung Cho, and Woohyung Lim. Diffusion-based semantic-discrepant outlier generation for out-of-distribution detection. In *NeurIPS 2023 Workshop on Synthetic Data Generation with Generative AI*, 2023.

Suhee Yoon, Sanghyu Yoon, Ye Seul Sim, Sungik Choi, Kyungeun Lee, Hye-Seung Cho, Hankook Lee, and Woohyung Lim. Diffusion-based semantic outlier generation via nuisance awareness for out-of-distribution detection. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pp. 13078–13086, 2025.

Fisher Yu, Ari Seff, Yinda Zhang, Shuran Song, Thomas Funkhouser, and Jianxiong Xiao. Lsun: Construction of a large-scale image dataset using deep learning with humans in the loop. *arXiv preprint arXiv:1506.03365*, 2015.

Sergey Zagoruyko. Wide residual networks. *arXiv preprint arXiv:1605.07146*, 2016.

Jingyang Zhang, Jingkang Yang, Pengyun Wang, Haoqi Wang, Yueqian Lin, Haoran Zhang, Yiyou Sun, Xuefeng Du, Kaiyang Zhou, Wayne Zhang, et al. Openood v1. 5: Enhanced benchmark for out-of-distribution detection. *arXiv preprint arXiv:2306.09301*, 2023.

Yonggang Zhang, Jie Lu, Bo Peng, Zhen Fang, and Yiu ming Cheung. Learning to shape in-distribution feature space for out-of-distribution detection. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024.

Yunrui Zhao, Qianqian Xu, Yangbangyan Jiang, Peisong Wen, and Qingming Huang. Dist-pu: Positive-unlabeled learning from a label distribution perspective. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14461–14470, 2022.

Haotian Zheng, Qizhou Wang, Zhen Fang, Xiaobo Xia, Feng Liu, Tongliang Liu, and Bo Han. Out-of-distribution detection learning with unreliable out-of-distribution sources. *Advances in Neural Information Processing Systems*, 36:72110–72123, 2023.

Bolei Zhou, Agata Lapedriza, Aditya Khosla, Aude Oliva, and Antonio Torralba. Places: A 10 million image database for scene recognition. *IEEE transactions on pattern analysis and machine intelligence*, 40(6):1452–1464, 2017.

Zhi Zhou, Lan-Zhe Guo, Zhanzhan Cheng, Yu-Feng Li, and Shiliang Pu. Step: Out-of-distribution detection in the presence of limited in-distribution labeled data. In *Advances in Neural Information Processing Systems*, volume 34, pp. 29168–29180. Curran Associates, Inc., 2021.

Jianing Zhu, Yu Geng, Jiangchao Yao, Tongliang Liu, Gang Niu, Masashi Sugiyama, and Bo Han. Diversified outlier exposure for out-of-distribution detection via informative extrapolation. *Advances in Neural Information Processing Systems*, 36:22702–22734, 2023.

Yao Zhu, YueFeng Chen, Chuanlong Xie, Xiaodan Li, Rong Zhang, Hui Xue', Xiang Tian, bolun zheng, and Yaowu Chen. Boosting out-of-distribution detection with typical features. In *Advances in Neural Information Processing Systems*, volume 35, pp. 20758–20769. Curran Associates, Inc., 2022.

A   Additional Experiments

A.1   Element-wise Median vs Geometric Median

Another pertinent question to ask is why we chose the element-wise median over the geometric median (Acharya et al., 2024) for outlier detection in Medix. To answer this question, we conducted a preliminary experiment using CIFAR-10 as the InD dataset and SVHN as the OOD dataset. Specifically, $\mathcal{S}_{\text{wild}}$ consists of 5k samples drawn from CIFAR-10, ensuring that these samples are disjoint from the training set used to train the model $\phi_{\mathcal{S}_{\text{in}}}$, which we leverage to compute $\bar{\nabla}_{\text{in}}$. We incrementally add SVHN OOD samples to $\mathcal{S}_{\text{wild}}$ and track the behavior of the L_2-norm deviation between $\bar{\nabla}_{\text{in}}$ and the element-wise median of the gradients of the wild dataset as well as the proportion of OOD samples removed. The results, shown in the Figure 4, demonstrate that for the same number of OOD samples in the wild dataset, the element-wise median identified a significantly higher proportion of OOD samples as outliers compared to the geometric median. This indicates that the element-wise median is more sensitive to distributional shifts, making it a more effective and reliable choice for filtering in our method.

Table 3: Effect of hyperparameters ϵ and k on OOD detection.

Method	FPR95↓	ϵ	k
DICE	88.35	–	–
ASH	21.36	–	–
CSI	64.70	–	–
KNN+	32.21	–	–
OE	2.86	–	–
Energy	2.71	–	–
Medix	0.16	0.005	20000
Medix	0.20	0.0005	20000
Medix	0.68	0.005	10000

A.2   Hyperparameter Selection and Sensitivity Analysis

We conducted an ablation study to assess the sensitivity of Medix to the hyperparameters ϵ and k. For this experiment, we employed CIFAR-100 as the InD dataset and SVHN as the OOD dataset. As shown in Table 3, Medix exhibits strong robustness to variations in the values of ϵ and k. In particular, Medix achieves a remarkably low FPR95 of 0.16 when using $\epsilon = 0.005$ and $k = 20000$. Even when the values of ϵ and k are varied—e.g., reducing ϵ to 0.0005 or halving k to 10000—the performance remains competitive (FPR95 of 0.20 and 0.68, respectively), demonstrating a graceful degradation rather than a sharp drop. The results indicate that while optimal hyperparameter selection is important, Medix maintains its effectiveness across a variety of hyperparameter choices, surpassing the baselines. This insensitivity to exact hyperparameter tuning makes Medix a reliable choice in real-world deployments, where exhaustive tuning may not be feasible.

A.3   Comprehensive comparison with recent competitive methods

We have extended our comparisons to include competitive baselines that employ diverse contrasting learning objectives, such as SSD+ (Sehwag et al., 2021), ProxyAnchor (Kim et al., 2020), and CIDER Ming et al. (2023). Although these methods use contrasting learning objectives, which we do not, we included them for a comprehensive comparison. Additionally, we included more recent methods, such as CONJ (Peng et al.,

Figure 4: Comparison of element-wise median (EWM) and geometric median (GM).

Table 4: OOD detection performance comparison of Medix and recent competitive baselines on CIFAR-100 as InD data. Performance averaged over five runs; best results are highlighted in **bold**.

Methods	OOD Datasets									
	SVHN		PLACES365		LSUN-C		TEXTURES		AVERAGE	
	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑
MSP	78.89	79.80	84.38	74.21	83.47	75.28	86.51	72.53	83.31	75.46
Mahalanobis	87.09	80.62	84.63	73.89	84.15	79.43	61.72	84.87	79.40	79.70
ODIN	70.16	84.88	82.16	75.19	76.36	80.10	85.28	75.23	78.49	78.85
Energy	66.91	85.25	81.41	76.37	59.77	86.69	79.01	79.96	71.78	82.07
ReAct	50.93	88.75	83.55	73.10	64.02	80.31	64.40	81.95	65.72	81.03
KNN	46.25	90.39	82.08	75.44	60.85	85.61	62.39	83.95	62.89	83.85
Vim	73.42	84.62	85.34	69.34	86.96	69.74	74.56	76.23	80.07	74.98
VOS	43.24	82.80	76.85	78.63	73.61	84.69	57.57	87.31	62.82	83.36
CSI	44.53	92.65	79.08	76.27	75.58	83.78	61.61	86.47	65.20	84.79
ProxyAnchor	87.21	82.43	70.10	79.84	37.19	91.68	65.64	84.99	65.04	84.74
SSD+	31.19	94.19	77.74	79.90	79.39	85.18	66.63	86.18	63.74	86.36
KNN+	39.23	92.78	80.74	77.58	48.99	89.30	57.15	88.35	56.53	87.00
ASH	52.96	90.19	72.62	76.38	75.18	76.52	56.17	86.75	64.23	82.46
CIDER	23.09	95.16	79.63	73.43	16.16	96.33	43.87	90.42	40.69	88.84
CONJ	46.19	90.44	80.81	75.83	60.45	85.90	62.13	83.77	62.40	83.99
DRL	20.15	94.07	76.64	77.55	16.97	94.63	31.97	92.09	36.43	89.59
Medix	**0.48**	**99.87**	**24.52**	**93.42**	**0.73**	**99.84**	**8.99**	**97.92**	**8.68**	**97.76**
(Ours)	$\pm$**0.05**	$\pm$**0.02**	$\pm$**1.76**	$\pm$**0.36**	$\pm$**0.08**	$\pm$**0.03**	$\pm$**0.72**	$\pm$**0.24**	$\pm$**0.65**	$\pm$**0.16**

2024), DRL (Zhang et al., 2024), Vim (Wang et al., 2022a), and VOS (Du et al., 2022c), to provide a more thorough evaluation. For this experiment, we use CIFAR-100 as InD dataset and train the ResNet-34 model[1] following the setup in Ming et al. (2023); Zhang et al. (2024). The model is trained using stochastic gradient descent with momentum 0.9, and weight decay 10^{-4} for 500 epochs. The initial learning rate is 0.5 with cosine scheduling and the batch size is 512. We use the checkpoints provided by Ming et al. (2023)[2]. The results, as shown in Table 4, demonstrate that Medix outperforms even these competitive baselines by a significant margin, including those trained with contrastive learning objectives, achieving an average FPR95 of 8.68% and an average AUROC of 97.76%. Furthermore, Medix provides a provably low error rate, offering theoretical guarantees that most alternative approaches do not.

A.4 Evaluation on Large-Scale, Complex Unseen OOD Settings

We next investigate whether Medix can handle large-scale wild OOD data under the unseen OOD setting. This setting is more challenging for two main reasons: (1) it leverages a large-scale wild OOD dataset ($\mathbb{P}_{\text{out}}$), increasing both data complexity and computational demand, and (2) the test-time OOD distribution ($\mathbb{P}_{\text{out}}^{\text{test}}$) is intentionally chosen to be distributionally different from the wild OOD data used during training, i.e., $\mathbb{P}_{\text{out}}^{\text{test}} \neq \mathbb{P}_{\text{out}}$, which better reflects realistic and challenging deployment scenarios.

We used CIFAR-100 as the labeled InD data, 300K Random Images dataset Hendrycks et al. (2019) as the unlabeled wild OOD data and tested on the SVHN dataset as the test OOD data. This setup introduces a greater level of complexity because the large-scale wild OOD data (300K Random Images) is significantly different from the OOD test data (SVHN). To evaluate the performance of our approach, we compare it against baselines that also leverage wild data in training. The results in the

Table 5: Comparison of OOD detection performance on large-scale unseen OOD data.

Method	FPR95↓	AUROC↑
OE	68.80 ± 2.8	82.89 ± 1.1
Energy (w/ OE)	69.81 ± 2.4	85.59 ± 1.0
WOODS	69.41 ± 2.7	86.76 ± 0.8
Medix (ours)	$\mathbf{41.29 \pm 1.2}$	$\mathbf{87.25 \pm 0.9}$

Table 5 highlight the superior performance of our method, Medix, compared to the baselines, with a significantly lower FPR95 (41.29 ± 1.2) and higher AUROC (87.25 ± 0.6), showing its effectiveness in distinguishing between InD and OOD data.

---

[1]Since ResNet-34 is the standard model across these works, we adopt the same model to ensure consistency and facilitate a fair comparison.

[2]https://github.com/deeplearning-wisc/cider

A.5 Evaluating the Impact of Pseudo-Label Quality on OOD Filtering and Robustness

Another important question to ask is whether the quality of pseudo-labels $\hat{y}_{\tilde{x}_i}$, particularly in terms of softmax confidence, affects the performance of OOD filtering, and whether a simple pre-filtering step that removes low-confidence pseudo-labels could improve the robustness of the model. To answer this question, we conducted an experiment to evaluate how filtering low-confidence pseudo-labels affects OOD filtering. For this experiment, we used CIFAR-10 as the InD dataset and LSUN-Resize as the OOD dataset. Specifically, we computed the softmax probabilities for each pseudo-labeled sample and discarded those with low-confidence predictions, setting a threshold of 0.6. After filtering, we found that 15.98% of the samples were removed from the training set.

The results showed that there was virtually no difference in performance between the method with filtering and the method without filtering. Both methods yielded a FPR95 of 0.01%, but with filtering, AUROC increased slightly from 99.98% to 99.99%. Thus, removing low-confidence pseudo-labels doesn't significantly impact the robustness of the model or its ability to detect OOD samples, showing that our method is resilient to noisy or low-confidence labels, and further filtering steps are unlikely to yield meaningful improvements.

A.6 Evaluating Computation and Memory Efficiency in Medix Filtering

We now turn to the question of whether Medix's filtering phase is computationally feasible and memory-efficient on large datasets. In response to this question, we conducted profiling experiments on an NVIDIA A100-SXM4-80GB GPU using approximately 15,000 unlabeled samples for each InD–OOD pair. For this experiment, we used CIFAR-10 and CIFAR-100 as the InD datasets and LSUN-Resize as the OOD dataset. As seen from the results in Table 6, the GPU memory usage remains modest, and the filtering phase completes within a tractable timeframe, even when handling thousands of unlabeled samples. This demonstrates that the Medix filtering process is computationally feasible and does not impose excessive memory overhead, even on large datasets.

Table 6: Profiling results for Medix filtering on NVIDIA A100 80GB GPU.

InD–OOD	Wall Clock Time (s)	Peak GPU Memory (MB)	Current GPU Memory (MB)
CIFAR10 – LSUN-Resize	4497.17	99.46	31.74
CIFAR100 – LSUN-Resize	5478.36	99.56	31.79

A.7 Comparison with Semi-Supervised Open-Set Recognition Methods

Our work differs from recent semi-supervised open-set recognition methods (Saito et al., 2021; Fan et al., 2023; Hang & Zhang, 2024; Wang et al., 2024) in several key ways. For example, in OpenML Saito et al. (2021), the main problem is to handle outliers in semi-supervised learning (SSL) when training a standard classifier, whereas in our setting, the main challenge is to detect OOD samples from unlabeled wild data and train a dedicated OOD detector classifier. In other words, while SSL methods (Saito et al., 2021; Fan et al., 2023; Hang & Zhang, 2024; Wang et al., 2024) aim to improve classification despite outliers, our approach enhances OOD detection in an open-world setting where labeled OOD data is unavailable.

Secondly, these SSL methods aim to train a classifier that is robust to OOD samples in SSL, treating outliers as noise, while in our setting, the goal is to explicitly detect OOD samples and train an OOD detector. In other words, SSL methods focus on suppressing OOD samples during training to improve SSL performance, whereas Medix actively detects and leverages these OOD samples to build a more effective and reliable OOD detection system.

Lastly, the two approaches differ in their techniques: OpenMatch is based on consistency regularization, where the main idea is to enforce consistency across different stochastic transformations of the same input. This is mathematically modeled through soft constraints on the classifier's outputs, encouraging smooth decision boundaries. On the other hand, Medix relies on median-based filtering for outlier detection. The method uses statistical robustness properties of the median, leveraging its insensitivity to extreme values to

identify potential OOD samples. The theoretical analysis derives error bounds based on the contamination effect (proportion of OOD samples) and the concentration effect (sub-Gaussian behavior of InD gradients), ensuring that OOD detection error remains low.

A.8 Scalability Analysis of Medix Across Larger Architectures

We further evaluate Medix on a larger backbone to understand its behavior in high-dimensional gradient spaces. Specifically, we use ResNet-50, where the penultimate layer gradient dimensionality is $d = 2048$, significantly higher than in the architectures used in the main experiments (e.g. WideResNet). We follow the same experimental setup as in Table 2. CIFAR-100 is used as the InD dataset, and we evaluate on two challenging OOD datasets: TEXTURES and PLACES. We also implement WOODS (Katz-Samuels et al., 2022) on ResNet-50 for a direct comparison.

As shown in Table 7, Medix consistently outperforms WOODS by a large margin across both OOD datasets. Notably, Medix achieves an FPR95 of 1.36 on TEXTURES and 4.13 on PLACES, while maintaining AUROC scores above 98% in both cases.

Table 7: Performance comparison on ResNet-50 with CIFAR-100 as InD, and TEXTURES and PLACES as OOD datasets.

Method	OOD	FPR95 ↓	AUROC ↑
WOODS	TEXTURES	11.93	97.56
Medix	TEXTURES	**1.36**	**99.66**
WOODS	PLACES	47.85	88.69
Medix	PLACES	**4.13**	**98.82**

Despite the substantially higher dimensionality of the gradient space ($d = 2048$), the L2 distance between the mean InD gradient and the exponential moving average of wild gradients remains highly discriminative. In fact, performance is on par with or better than results obtained using smaller architectures (c.f. Table 1-2).These findings indicate that Medix scales well to larger models such as ResNet-50, and that the L2-based filtering mechanism remains robust even in high-dimensional settings.

A.9 Evaluation on ImageNet-1k and Large-Scale OOD Detection

To assess Medix's generalization to high-resolution, large-scale datasets, we conduct experiments on ImageNet-1k using ResNet-50, with ImageNet-1k as the InD dataset. We evaluate on two OOD datasets of differing difficulty: SVHN, a well-separated OOD source, and TEXTURES, a more challenging one. This setup tests Medix's ability to generalize to high-resolution images (224×224) and a substantially larger number of classes than CIFAR-100. We additionally evaluate WOODS (Katz-Samuels et al., 2022) under identical conditions, adapting its open-source implementation to the ResNet-50 architecture[3].

As shown in Table 8, on the well-separated SVHN benchmark, Medix achieves near-perfect performance (FPR95 of 0.00, AUROC of 100), with an ID-vs-OOD accuracy of 98.98%; WOODS performs comparably (FPR95 of 0.01, AUROC of 99.98). Because both methods saturate on this pair, we additionally report results on TEXTURES, a harder OOD dataset where the two methods are more clearly differenti-

Table 8: OOD detection performance with ImageNet-1k as InD, using ResNet-50.

Method	OOD	FPR95 ↓	AUROC ↑
WOODS	SVHN	0.01	99.98
Medix	SVHN	**0.00**	**100.00**
WOODS	TEXTURES	**5.43**	**98.89**
Medix	TEXTURES	7.53	97.98

ated. Here, both methods remain strong: WOODS attains an FPR95 of 5.43 and AUROC of 98.89, while Medix attains an FPR95 of 7.53 and AUROC of 97.98. Although WOODS is slightly ahead on this particular benchmark, both methods maintain low false-positive rates and high AUROC at ImageNet scale, confirming that Medix's gradient-median filtering signal remains effective and competitive in high-resolution, large-class settings beyond the CIFAR benchmarks used in our main experiments.

A.10 Comparison with a Naive Two-Stage Filtering Baseline

A natural question is whether the gains of Medix stem from its two-stage architecture in general, or specifically from the median-based filtering used in Stage 1. To isolate this, we construct a baseline that retains the exact Stage 2 binary-detector training of Medix but replaces our median filter with a simple, off-the-shelf filter: we

---

[3]for WOODS, we used their opensource code: https://github.com/jkatzsam/woods_ood

score each wild sample with Maximum Softmax Probability (MSP) ([Hendrycks & Gimpel, 2017](#)) from the InD-trained model, flag the low-confidence samples as candidate outliers, and train the same binary OOD detector on the resulting set together with the labeled InD data. We refer to this as *MSP-filter + binary*. We evaluate on SVHN and TEXTURES as OOD datasets, using CIFAR-10 and CIFAR-100 as InD, and report raw (InD-only) MSP and competitive wild-data baselines for context.

Table 9: Isolating the role of median filtering. We compare Medix against a naive two-stage baseline (*MSP-filter + binary*) that uses the same Stage-2 binary detector but replaces our median filter with MSP-based filtering. Results on SVHN and TEXTURES as OOD, with CIFAR-10 and CIFAR-100 as InD. Raw InD-only MSP and wild-data baselines are shown for reference. Best results in **bold**.

Methods	CIFAR-10 (InD)				CIFAR-100 (InD)			
	SVHN		TEXTURES		SVHN		TEXTURES	
	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑
	Using $\mathbb{P}_{\text{in}}$ only							
MSP	48.49	91.89	59.28	88.50	84.59	71.44	83.29	73.34
	Using $\mathbb{P}_{\text{in}}$ and $\mathbb{P}_{\text{wild}}$							
OE	1.13	99.53	7.75	98.56	2.86	99.05	22.86	94.63
Energy (w/ OE)	5.24	98.72	10.51	97.10	2.71	99.34	30.16	94.76
WOODS	0.17	99.91	6.21	98.13	0.17	99.80	9.95	95.97
MSP-filter + binary	24.18	95.32	52.62	88.83	35.43	92.12	55.54	88.86
Medix (Ours)	**0.06**±0.01	**99.98**±0.01	**0.96**±0.13	**99.66**±0.06	**0.16**±0.02	**99.96**±0.00	**8.02**±0.75	**97.79**±0.30

As shown in Table 9, the *MSP-filter + binary* baseline does improve over the raw InD-only MSP detector in several cases (e.g., FPR95 drops from 84.59 to 35.43 on CIFAR-100/SVHN, and from 48.49 to 24.18 on CIFAR-10/SVHN), confirming that the Stage-2 binary detector recovers some signal. However, it remains dramatically worse than Medix across all four settings: Medix reduces FPR95 from 35.43 to 0.16 on CIFAR-100/SVHN and from 24.18 to 0.06 on CIFAR-10/SVHN, with similarly large margins on TEXTURES. The naive baseline also trails the existing wild-data methods (OE, Energy w/ OE, WOODS), placing it well below the rest of the $\mathbb{P}_{\text{in}} + \mathbb{P}_{\text{wild}}$ group.

This gap is explained directly by filtering precision. Because MSP separates InD from OOD poorly (its own FPR95 exceeds 80% on CIFAR-100/SVHN), the candidate outlier set it produces is heavily contaminated with InD samples. Training the Stage-2 detector on this noisy set propagates the contamination, yielding a weak final detector. In contrast, Medix extracts outliers with only a 12.5% error rate (Figure 3), and this cleaner set enables the same Stage-2 detector to reach near-perfect performance. The effect is most pronounced on the harder TEXTURES, where MSP filtering barely improves over the raw detector (e.g., CIFAR-10/TEXTURES: FPR95 from $59.28 \rightarrow 52.62$, and AUROC from $88.50 \rightarrow 88.83$), indicating that contamination dominates when the underlying scoring function is unreliable. Together, these results confirm that Medix's advantage is driven by the quality of its median-based filtering, not merely by the two-stage pipeline: replacing the median filter with a naive alternative in the identical pipeline causes performance to collapse.

A.11 Details on Statistical Operations for Outlier Removal

To avoid ambiguity, we explicitly define the two key operations used in our outlier extraction procedure.

Mean ($\bar{\nabla}_{\text{in}}$). Let $\{g_i\}_{i=1}^n$ be the set of gradient vectors computed from the labeled InD training set, where each $g_i \in \mathbb{R}^d$ (with d the number of parameters of the chosen layer). The mean gradient $\bar{\nabla}_{\text{in}}$ is the d-dimensional vector whose j-th coordinate is the average of the j-th coordinates of all g_i:

$$(\bar{\nabla}_{\text{in}})_j = \frac{1}{n} \sum_{i=1}^n g_{i,j}, \qquad j = 1, \ldots, d,$$

where $g_{i,j}$ denotes the j-th coordinate of g_i. In words, we take the element-wise average across the sample dimension.

Element-wise median (EWM). For a subset $S \subseteq S_{\text{wild}}$ with $|S| = m$, we arrange the corresponding gradient vectors into a matrix G_S of size $m \times d$, where row i corresponds to the gradient of the i-th sample in S. Then $\text{EWM}(G_S)$ is the d-dimensional vector obtained by taking the median across rows (i.e., over the samples) for each coordinate independently:

$$\big[\text{EWM}(G_S)\big]_j \ = \ \text{median}\big(\{\, [G_S]_{i,j} \mid i = 1, \ldots, m \,\}\big), \qquad j = 1, \ldots, d.$$

Thus, for each parameter coordinate, we compute the median of the values observed across all samples in S. This operation is robust to outliers and serves as the core statistic for our greedy removal algorithm (Algorithm 1).

These definitions are consistent with the implementation (e.g., `torch.mean(dim=0)` and `torch.median(dim=0)` in PyTorch, where `dim=0` indicates the sample axis).

(a) InD gradient histogram.   (b) InD gradient Q-Q plot.

Figure 5: Illustration of InD sample gradients exhibiting sub-Gaussian behavior in each coordinate. (left) Histogram of gradient values (CIFAR-100 InD data) showing concentration around the mean with light tails, consistent with sub-Gaussianity. (right) Q-Q plot comparing empirical quantiles of InD gradients against a theoretical Gaussian distribution, confirming alignment with sub-Gaussianity.

Figure 6: Illustration of InD sample gradients exhibiting sub-Gaussian behavior in each coordinate. (left) Histogram of gradient values (CIFAR-10 InD data) showing concentration around the mean with light tails, consistent with sub-Gaussianity. (right) Q-Q plot comparing empirical quantiles of InD gradients against a theoretical Gaussian distribution, confirming alignment with sub-Gaussianity.

Figure 7: Illustration of InD sample gradients exhibiting sub-Gaussian behavior in each coordinate. (left) Histogram of gradient values (ImageNet-1k InD data) showing concentration around the mean with light tails, consistent with sub-Gaussianity. (right) Q-Q plot comparing empirical quantiles of InD gradients against a theoretical Gaussian distribution, confirming alignment with sub-Gaussianity.

B Broader Impacts and Limitations

As machine learning continues to advance, tackling the challenges of OOD detection has become essential for ensuring robust and reliable model performance in real-world applications. We introduce a median-centric framework for OOD detection that enhances OOD handling and model safety. The impact of our research goes beyond theoretical advancements, with practical applications in healthcare, autonomous systems, and finance. By improving OOD detection, we address a key challenge in model deployment, fostering greater trust and adoption of machine learning technologies. Future work could explore integrating it with generative models for outlier synthesis or adapting it to dynamic environments where OOD distributions evolve over time.

A potential limitation of Medix lies in its reliance on a mixture of unlabeled InD and OOD data, which, in practice, may be noisy, corrupted, or inconsistently sampled. However, this assumption is not unique to our method—it reflects the inherent uncertainty of real-world deployment environments and is a common starting point in robust learning theory. To make our assumptions explicit and verifiable, we rigorously formalize them in the main theorems and provide a precise geometric condition in Theorem 4.4 to justify the necessary separation required for reliable filtering. Moreover, we extend our guarantees to looser settings in Corrolary 4.5, removing the need for sub-Gaussian tails and demonstrating the resilience of our framework under weaker distributional assumptions.

C Proof of Theorem

We summarize the notation used in this paper in Table 10. This includes definitions for gradient-related quantities, sample sizes, and filtering terms, as well as parameters that appear in our concentration bounds. Unless stated otherwise, we use boldface for vectors, $\mathcal{X}$ to denote the input space, and assume all gradients are computed with respect to a fixed pretrained model f_ϕ.

Table 10: Notation summary. We use bold symbols for vectors and $\mathcal{X}$ to denote the input space.

Symbol	Meaning
$\mathcal{X}$	Input space (e.g., images in $[0,1]^d$)
f_ϕ	Model parameterized by ϕ
$\ell(f_\phi(x))$	Loss function evaluated at input x
$\nabla\ell(f_\phi(x))$	Gradient of loss at point x
$\bar{\nabla}_{\text{in}}$	Empirical mean of gradients over InD points
m	Total number of unlabeled samples in $\mathcal{S}_{\text{wild}}$
M_{in}	Number of InD samples in $\mathcal{S}_{\text{wild}}$ (random under the Huber model; $\mathbb{E}[M_{\text{in}}] = (1-\pi)m$)
M_{out}	Number of OOD samples in $\mathcal{S}_{\text{wild}}$ (random; $\mathbb{E}[M_{\text{out}}] = \pi m$)
$m_{\text{in}}, m_{\text{out}}$	Realized InD/OOD counts when conditioning on the contamination outcome
$\pi \in (0,1)$	OOD contamination ratio
$\mathcal{S}_{\text{wild}}$	Unlabeled mixture of InD and OOD data
$\mathcal{I}$	True InD subset of $\mathcal{S}_{\text{wild}}$
$\mathcal{O}$	True OOD subset of $\mathcal{S}_{\text{wild}}$
$\mathcal{S}^\star$	Subset selected by the ideal size-constrained EWM filter
ERR_{in}	Fraction of InD points misclassified as OOD
ERR_{out}	Fraction of OOD points misclassified as InD
σ^2	Sub-Gaussian proxy variance of each InD gradient coordinate
σ^2_{out}	Sub-Gaussian proxy variance of each OOD gradient coordinate
μ_{out}	Mean OOD gradient vector
Δ	Separation: $\|\mu_{\text{out}} - \bar{\nabla}_{\text{in}}\|_2 \geq \Delta\sqrt{d}$
ϵ	Threshold for gradient deviation, $\epsilon = \sigma\sqrt{2\log(4dm/\delta)}$
$\delta \in (0,1)$	Confidence parameter for concentration bounds
d	Dimensionality of gradient vectors

C.1 Bound on the Inlier Misclassification Rate

Theorem C.1 (Inlier Misclassification Bound). *Assume $\mathcal{S}_{\text{wild}}$ follows the Huber contamination model: each $\tilde{x}_i \in \mathcal{S}_{\text{wild}}$ is independently InD with probability $1-\pi$ and OOD with probability π, inducing the true InD and OOD subsets $\mathcal{I}, \mathcal{O} \subseteq \mathcal{S}_{\text{wild}}$ with sizes $M_{\text{in}} = |\mathcal{I}|$, $M_{\text{out}} = |\mathcal{O}|$, and $M_{\text{in}} + M_{\text{out}} = m$. Assume the InD gradients $\{G_i\}_{i\in\mathcal{I}}$ are i.i.d. and that each centered coordinate $G_{i,j} - \bar{\nabla}_{\text{in},j}$ is sub-Gaussian with variance proxy σ^2. Fix $\delta \in (0,1)$ and set $\epsilon = \sigma\sqrt{2\log(4dm/\delta)}$. Let $\mathcal{S}^\star$ be the ideal size-constrained EWM filter of Eq. equation 7, returning a subset of size M_{in}. If*

$$m \geq \frac{2\log(2/\delta)}{(1-\pi)^2},$$

then, with probability at least $1-\delta$, both of the following hold.

1. *(Reference accuracy of the selected subset.) The element-wise median of $\mathcal{S}^\star$ deviates from the reference gradient by at most*

$$\left\|\text{EWM}(G_{\mathcal{S}^\star}) - \bar{\nabla}_{\text{in}}\right\|_2 \leq \epsilon\sqrt{d}.$$

2. (Inlier misclassification.) *The fraction of true InD points excluded by the filter satisfies*

$$\mathrm{ERR}_{\mathrm{in}} = \frac{|\mathcal{I} \setminus \mathcal{S}^\star|}{M_{\mathrm{in}}} \leq \underbrace{\frac{2}{(1-\pi)^2}\sqrt{\frac{\log(2/\delta)}{2m}}}_{\text{concentration term}} + \underbrace{\frac{\pi}{1-\pi}}_{\text{contamination term}}.$$

The concentration term arises from Hoeffding fluctuations of the contamination count $M_{\mathrm{in}} \sim \mathrm{Binomial}(m, 1-\pi)$, while the contamination term captures the nominal OOD-to-InD ratio $\pi/(1-\pi)$.

Proof. Let $\mathcal{I}$ denote the realized InD subset of $\mathcal{S}_{\mathrm{wild}}$ and $\mathcal{O}$ denote the realized OOD subset. Thus

$$|\mathcal{I}| = M_{\mathrm{in}}, \qquad |\mathcal{O}| = M_{\mathrm{out}}, \qquad M_{\mathrm{in}} + M_{\mathrm{out}} = m.$$

We first prove the EWM stability statement. Recall that the ideal size-constrained EWM filtering rule is defined as

$$\mathcal{S}^\star \in \arg \min_{\substack{\mathcal{S} \subseteq \mathcal{S}_{\mathrm{wild}} \\ |\mathcal{S}| = M_{\mathrm{in}}}} \left\| \mathrm{EWM}(G_\mathcal{S}) - \bar{\nabla}_{\mathrm{in}} \right\|_2.$$

The true InD subset $\mathcal{I}$ is feasible for this optimization problem because $|\mathcal{I}| = M_{\mathrm{in}}$. Therefore, by optimality of $\mathcal{S}^\star$,

$$\left\| \mathrm{EWM}(G_{\mathcal{S}^\star}) - \bar{\nabla}_{\mathrm{in}} \right\|_2 \leq \left\| \mathrm{EWM}(G_I) - \bar{\nabla}_{\mathrm{in}} \right\|_2.$$

We now control the right-hand side using the sub-Gaussian assumption. By the centering convention stated above, for every InD point $i \in \mathcal{I}$ and coordinate $j \in [d]$,

$$\mathbb{P}\left(|G_{i,j} - \bar{\nabla}_{\mathrm{in},j}| > \epsilon \right) \leq 2 \exp\left(-\frac{\epsilon^2}{2\sigma^2} \right).$$

Taking a union bound over all $i \in \mathcal{I}$ and $j \in [d]$, and using $M_{\mathrm{in}} \leq m$, gives

$$\mathbb{P}\left(\exists i \in \mathcal{I}, \exists j \in [d] : |G_{i,j} - \bar{\nabla}_{\mathrm{in},j}| > \epsilon \right) \leq 2dm \exp\left(-\frac{\epsilon^2}{2\sigma^2} \right).$$

With

$$\epsilon = \sigma\sqrt{2\log(4dm/\delta)},$$

the right-hand side is at most $\delta/2$. Hence, with probability at least $1 - \delta/2$, every true InD gradient coordinate lies inside the interval

$$[\bar{\nabla}_{\mathrm{in},j} - \epsilon, \bar{\nabla}_{\mathrm{in},j} + \epsilon].$$

Therefore, for each coordinate j, the coordinate-wise median of the InD gradients also lies in the same interval:

$$\left| \mathrm{median}\{G_{i,j} : i \in \mathcal{I}\} - \bar{\nabla}_{\mathrm{in},j} \right| \leq \epsilon.$$

Thus

$$\left\| \mathrm{EWM}(G_I) - \bar{\nabla}_{\mathrm{in}} \right\|_\infty \leq \epsilon,$$

and consequently,

$$\left\| \mathrm{EWM}(G_I) - \bar{\nabla}_{\mathrm{in}} \right\|_2 \leq \epsilon\sqrt{d}.$$

Combining this with the optimality inequality above gives

$$\left\| \mathrm{EWM}(G_{\mathcal{S}^\star}) - \bar{\nabla}_{\mathrm{in}} \right\|_2 \leq \epsilon\sqrt{d}.$$

It remains to bound the inlier misclassification rate. Since $|\mathcal{S}^\star| = |\mathcal{I}| = M_{\mathrm{in}}$, every InD point excluded from $\mathcal{S}^\star$ must be replaced by a point outside $\mathcal{I}$, namely by an OOD point. Therefore,

$$|\mathcal{I} \setminus \mathcal{S}^\star| = |\mathcal{S}^\star \setminus \mathcal{I}| = |\mathcal{S}^\star \cap \mathcal{O}| \leq |\mathcal{O}| = M_{\mathrm{out}}.$$

Hence

$$\text{ERR}_{\text{in}} = \frac{|\mathcal{I} \setminus \mathcal{S}^\star|}{M_{\text{in}}} \leq \frac{M_{\text{out}}}{M_{\text{in}}}.$$

Under the Huber contamination model,

$$M_{\text{in}} \sim \text{Binomial}(m, 1 - \pi).$$

Let

$$a := 1 - \pi, \qquad u := \sqrt{\frac{\log(2/\delta)}{2m}}.$$

By Hoeffding's inequality, with probability at least $1 - \delta/2$,

$$M_{\text{in}} \geq m(a - u).$$

On the same event,

$$M_{\text{out}} = m - M_{\text{in}} \leq m(\pi + u).$$

Therefore,

$$\frac{M_{\text{out}}}{M_{\text{in}}} \leq \frac{\pi + u}{a - u}.$$

The sample-size condition

$$m \geq \frac{2 \log(2/\delta)}{(1 - \pi)^2}$$

implies $u \leq a/2$. Hence

$$\frac{\pi + u}{a - u} = \frac{\pi}{a} + \frac{u}{a(a - u)} \leq \frac{\pi}{a} + \frac{2u}{a^2}.$$

Substituting $a = 1 - \pi$ gives

$$\text{ERR}_{\text{in}} \leq \frac{\pi}{1 - \pi} + \frac{2}{(1 - \pi)^2} \sqrt{\frac{\log(2/\delta)}{2m}}.$$

The EWM stability event fails with probability at most $\delta/2$, and the contamination-count event fails with probability at most $\delta/2$. A union bound completes the proof. $\qquad\square$

C.2 Bound on the Outlier Retention Rate

We now establish a non-asymptotic upper bound on the fraction of OOD points that remain in the subset returned by the ideal MEDIX filter. This result analyzes the ideal size-constrained EWM objective; the practical greedy procedure in Algorithm 1 is used as a tractable approximation.

Assumption C.2 (Reference EWM accuracy). Let $\mathcal{I} \subseteq \mathcal{S}_{\text{wild}}$ denote the true InD subset in the wild data, with $|\mathcal{I}| = m_{\text{in}}$. For the tolerance $\epsilon > 0$ used in Theorem 4.4, assume that

$$\left\| \text{EWM}(G_I) - \bar{\nabla}_{\text{in}} \right\|_2 < \epsilon \sqrt{d}.$$

Theorem C.3 (Outlier Misclassification Bound). *Assume $\mathcal{S}_{\text{wild}}$ follows the Huber contamination model, inducing the true InD and OOD subsets $I, O \subseteq \mathcal{S}_{\text{wild}}$ with realized sizes $m_{\text{in}} = |I|$ and $m_{\text{out}} = |O|$. Assume the OOD gradients $\{G_i\}_{i \in O}$ are i.i.d., and that each coordinate is sub-Gaussian with variance proxy σ_{out}^2, centered at the corresponding coordinate of the mean OOD gradient μ_{out}. Suppose μ_{out} satisfies the separation condition*

$$\left\| \mu_{\text{out}} - \bar{\nabla}_{\text{in}} \right\|_2 \geq \Delta \sqrt{d}, \qquad \Delta > 0,$$

and let $S^\star$ be the ideal size-constrained EWM filter, i.e. the exact minimizer of $\left\| \text{EWM}(G_S) - \bar{\nabla}_{\text{in}} \right\|_2$ over subsets $S \subseteq \mathcal{S}_{\text{wild}}$ with $|S| = m_{\text{in}}$. Fix a tolerance $\epsilon \in (0, \Delta)$ and a confidence level $\delta \in (0, 1)$, and suppose the

reference EWM accuracy condition (Assumption C.2) holds at this ϵ. Then, with probability at least $1 - \delta$, the fraction of true OOD points retained by the filter satisfies

$$\mathrm{ERR}_{\mathrm{out}} = \frac{|S^\star \cap O|}{m_{\mathrm{out}}} \leq \underbrace{2d \exp\left(-\frac{(\Delta - \epsilon)^2}{2\sigma_{\mathrm{out}}^2}\right)}_{\text{separation term}} + \underbrace{\sqrt{\frac{\log(1/\delta)}{2m_{\mathrm{out}}}}}_{\text{concentration term}} + \underbrace{\frac{1 - \pi}{2\pi}}_{\text{contamination term}} .$$

The separation term quantifies how far μ_{out} must lie from $\bar{\nabla}_{\mathrm{in}}$ for OOD gradients to be reliably rejected, decaying exponentially in the gap $\Delta - \epsilon$; the concentration term decays as $1/\sqrt{m_{\mathrm{out}}}$; and the contamination term $\frac{1-\pi}{2\pi}$ grows as π shrinks, capturing the difficulty of isolating OOD points when they are underrepresented.

Proof. Let

$$\Phi(\mathcal{S}) := \left\|\mathrm{EWM}(G_\mathcal{S}) - \bar{\nabla}_{\mathrm{in}}\right\|_2 .$$

We analyze the ideal size-constrained EWM solution

$$\mathcal{S}^\star \in \arg \min_{\substack{\mathcal{S} \subseteq \mathcal{S}_{\mathrm{wild}} \\ |\mathcal{S}| = m_{\mathrm{in}}}} \Phi(\mathcal{S}).$$

Since the true InD subset $\mathcal{I}$ is feasible for this objective, the optimality of $\mathcal{S}^\star$ gives

$$\Phi(\mathcal{S}^\star) \leq \Phi(\mathcal{I}).$$

By Assumption C.2,

$$\Phi(\mathcal{I}) < \epsilon \sqrt{d}.$$

Therefore,

$$\Phi(\mathcal{S}^\star) < \epsilon \sqrt{d}.$$

Step 1: Concentration of OOD gradients. Call an OOD point x bad if

$$\|g(x) - \mu_{\mathrm{out}}\|_\infty > \Delta - \epsilon.$$

By coordinate-wise sub-Gaussianity and a union bound over d coordinates,

$$\mathbb{P}(x \text{ is bad}) \leq 2d \exp\left(-\frac{(\Delta - \epsilon)^2}{2\sigma_{\mathrm{out}}^2}\right).$$

Define

$$p_{\mathrm{out}}(\epsilon) := 2d \exp\left(-\frac{(\Delta - \epsilon)^2}{2\sigma_{\mathrm{out}}^2}\right).$$

For each OOD point x_i, define the indicator

$$J_i := \mathbb{I}_{\{x_i \text{ is bad}\}}.$$

Let

$$Y := \sum_{i=1}^{m_{\mathrm{out}}} J_i$$

be the number of bad OOD points. Since the OOD points are i.i.d., Y is stochastically dominated by a sum of m_{out} Bernoulli random variables with success probability at most $p_{\mathrm{out}}(\epsilon)$. By Hoeffding's inequality, with probability at least $1 - \delta$,

$$\frac{Y}{m_{\mathrm{out}}} \leq p_{\mathrm{out}}(\epsilon) + \sqrt{\frac{\log(1/\delta)}{2m_{\mathrm{out}}}}.$$

Define
$$\eta_{\text{out}} := p_{\text{out}}(\epsilon) + \sqrt{\frac{\log(1/\delta)}{2m_{\text{out}}}}.$$

Then, with probability at least $1 - \delta$,
$$Y \leq m_{\text{out}}\eta_{\text{out}}.$$

Step 2: Optimality forces retained OOD to remain below the median threshold. Work on the high-probability event
$$Y \leq m_{\text{out}}\eta_{\text{out}}.$$

Let
$$a := |\mathcal{S}^\star \cap \text{OOD}|$$

be the number of OOD points retained by the ideal filter. Suppose, toward contradiction, that
$$\text{ERR}_{\text{out}} = \frac{a}{m_{\text{out}}} > \eta_{\text{out}} + \frac{1-\pi}{2\pi}.$$

Then
$$a > m_{\text{out}}\eta_{\text{out}} + \frac{1-\pi}{2\pi}m_{\text{out}}.$$

Using
$$m_{\text{out}} = \pi m \qquad \text{and} \qquad m_{\text{in}} = (1-\pi)m,$$

we have
$$\frac{1-\pi}{2\pi}m_{\text{out}} = \frac{m_{\text{in}}}{2}.$$

Therefore,
$$a > m_{\text{out}}\eta_{\text{out}} + \frac{m_{\text{in}}}{2}.$$

Since at most $m_{\text{out}}\eta_{\text{out}}$ OOD points are bad, the number of non-bad OOD points retained in $\mathcal{S}^\star$ is strictly larger than $m_{\text{in}}/2$. Because $|\mathcal{S}^\star| = m_{\text{in}}$, these non-bad OOD points form a strict majority of $\mathcal{S}^\star$. Hence, in every coordinate $j \in [d]$, more than half of the selected gradients lie in
$$[\mu_{\text{out},j} - (\Delta - \epsilon), \mu_{\text{out},j} + (\Delta - \epsilon)].$$

By the definition of the coordinate-wise median,
$$|\text{EWM}_j(G_{\mathcal{S}^\star}) - \mu_{\text{out},j}| \leq \Delta - \epsilon \qquad \text{for every } j \in [d].$$

Therefore,
$$\|\text{EWM}(G_{\mathcal{S}^\star}) - \mu_{\text{out}}\|_2 \leq (\Delta - \epsilon)\sqrt{d}.$$

Using the triangle inequality and the separation assumption,
$$\|\text{EWM}(G_{\mathcal{S}^\star}) - \bar{\nabla}_{\text{in}}\|_2 \geq \|\mu_{\text{out}} - \bar{\nabla}_{\text{in}}\|_2 - \|\text{EWM}(G_{\mathcal{S}^\star}) - \mu_{\text{out}}\|_2.$$

Thus,
$$\|\text{EWM}(G_{\mathcal{S}^\star}) - \bar{\nabla}_{\text{in}}\|_2 \geq \Delta\sqrt{d} - (\Delta - \epsilon)\sqrt{d} = \epsilon\sqrt{d}.$$

This contradicts
$$\Phi(\mathcal{S}^\star) < \epsilon\sqrt{d}.$$

Therefore,
$$\text{ERR}_{\text{out}} \leq \eta_{\text{out}} + \frac{1-\pi}{2\pi}.$$

Substituting the definition of η_{out}, we obtain
$$\text{ERR}_{\text{out}} \leq 2d\exp\left(-\frac{(\Delta - \epsilon)^2}{2\sigma_{\text{out}}^2}\right) + \sqrt{\frac{\log(1/\delta)}{2m_{\text{out}}}} + \frac{1-\pi}{2\pi}.$$

This completes the proof. $\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\square$

C.3 Reference EWM Accuracy without Sub-Gaussianity

Proof. For each coordinate $j \in [d]$, write

$$\mu_j := \bar{\nabla}_{\text{in},j}.$$

Fix a coordinate j. We first bound the probability that the coordinate-wise median of the InD gradients deviates from μ_j by more than ε. Define the upper-tail indicators

$$Z_{i,j}^+ := \mathbf{1}\left\{G_{i,j} - \mu_j > \varepsilon\right\}, \qquad i \in \mathcal{I}.$$

By Markov's inequality applied to the fourth moment,

$$\mathbb{P}\left(G_{i,j} - \mu_j > \varepsilon\right) \leq \mathbb{P}\left(|G_{i,j} - \mu_j| > \varepsilon\right) \leq \frac{\mathbb{E}\left[(G_{i,j} - \mu_j)^4\right]}{\varepsilon^4} \leq \frac{\mu_4}{\varepsilon^4} = p_\varepsilon.$$

Thus

$$\mathbb{E}\left[Z_{i,j}^+\right] \leq p_\varepsilon.$$

If

$$\text{med}\left(\{G_{i,j} : i \in \mathcal{I}\}\right) > \mu_j + \varepsilon,$$

then at least half of the samples must satisfy $G_{i,j} > \mu_j + \varepsilon$. Therefore,

$$\left\{\text{med}\left(\{G_{i,j} : i \in \mathcal{I}\}\right) > \mu_j + \varepsilon\right\} \subseteq \left\{\frac{1}{m_{\text{in}}}\sum_{i \in \mathcal{I}} Z_{i,j}^+ \geq \frac{1}{2}\right\}.$$

Since the samples are i.i.d. and $p_\varepsilon < 1/2$, Hoeffding's inequality gives

$$\mathbb{P}\left(\frac{1}{m_{\text{in}}}\sum_{i \in \mathcal{I}} Z_{i,j}^+ \geq \frac{1}{2}\right) \leq \exp\left(-2m_{\text{in}}\left(\frac{1}{2} - p_\varepsilon\right)^2\right).$$

Similarly, define the lower-tail indicators

$$Z_{i,j}^- := \mathbf{1}\left\{G_{i,j} - \mu_j < -\varepsilon\right\}.$$

The same fourth-moment bound gives

$$\mathbb{E}\left[Z_{i,j}^-\right] \leq p_\varepsilon.$$

If

$$\text{med}\left(\{G_{i,j} : i \in \mathcal{I}\}\right) < \mu_j - \varepsilon,$$

then at least half of the samples satisfy $G_{i,j} < \mu_j - \varepsilon$. Hence, by the same Hoeffding argument,

$$\mathbb{P}\left(\text{med}\left(\{G_{i,j} : i \in \mathcal{I}\}\right) < \mu_j - \varepsilon\right) \leq \exp\left(-2m_{\text{in}}\left(\frac{1}{2} - p_\varepsilon\right)^2\right).$$

Combining the upper and lower tails, for each coordinate j,

$$\mathbb{P}\left(\left|\text{EWM}_j(G_I) - \bar{\nabla}_{\text{in},j}\right| > \varepsilon\right) \leq 2\exp\left(-2m_{\text{in}}\left(\frac{1}{2} - p_\varepsilon\right)^2\right).$$

Taking a union bound over all d coordinates yields

$$\mathbb{P}\left(\max_{j \in [d]}\left|\text{EWM}_j(G_I) - \bar{\nabla}_{\text{in},j}\right| > \varepsilon\right) \leq 2d\exp\left(-2m_{\text{in}}\left(\frac{1}{2} - p_\varepsilon\right)^2\right).$$

On the complementary event, every coordinate satisfies

$$\left|\text{EWM}_j(G_I) - \bar{\nabla}_{\text{in},j}\right| \leq \varepsilon.$$

Therefore,

$$\left\|\text{EWM}(G_I) - \bar{\nabla}_{\text{in}}\right\|_2 \leq \varepsilon\sqrt{d}.$$

Substituting $p_\varepsilon = \mu_4/\varepsilon^4$ completes the proof. $\qquad\square$