Relational Representations Mitigation of Catastrophic Forgetting: Graph Attention Networks for Online Continual Learning

Abstract

Online Continual Learning (OCL) aims to enable models to learn from non-stationary data streams while preserving knowledge acquired from previously observed tasks. A fundamental challenge in OCL for image classification is catastrophic forgetting. Existing approaches predominantly rely on Convolutional Neural Networks (CNNs), whose grid-based representations of images emphasize local features but insufficiently model relational structures that may be re-used and built upon even under distribution shifts. In this work, we propose ReReM, a Relational Representations Mitigation framework for OCL that integrates Graph Attention Networks (GATs) with hierarchical features extracted from pretrained vision backbones. Images are transformed into multi-scale graphs, allowing models to learn interactions between semantic regions and enabling continual learning through attention-based message passing over relational structures. This design allows the model to selectively learn and update learned contextually relevant components for emphasis. To improve graph-level aggregation, we introduce a learnable weighted global pooling mechanism that adaptively prioritizes nodes. Furthermore, we propose a rehearsal duplication strategy that re-balances the influence of past and current data during training, improving knowledge retention without increasing memory storage requirements. Extensive experiments on CIFAR10, CIFAR100, and MiniImageNet demonstrate consistent improvements over existing pretrained CNN-based continual learning methods. Additional evaluations using Vision Transformer (ViT) feature extractors further show that the proposed framework generalizes across backbone architectures. Our results suggest that relational graph representations provide an effective inductive bias for mitigating forgetting in online continual learning.

1 Introduction

Online Continual Learning (OCL) for image classification seeks to enable machine learning models to learn from a sequence of tasks presented over time while retaining performance on previously acquired knowledge (Wang et al., 2024; Huo et al., 2024). This learning paradigm is essential for real-world applications operating under non-stationary data distributions, such as autonomous driving and robotic navigation, where models must continuously adapt to new information without retraining from scratch. A central challenge in OCL is *catastrophic forgetting*, whereby learning new tasks interferes with and degrades representations learned from earlier tasks (McCloskey & Cohen, 1989; van de Ven & Tolias, 2019).

Most existing approaches to continual learning for image classification rely on Convolutional Neural Networks (CNNs), which learn hierarchical feature representations through localized spatial aggregation (Jung et al., 2023; van de Ven & Tolias, 2019). While highly effective for static learning settings, CNNs inherently process images as fixed grids, emphasizing local appearance patterns rather than relationships between semantic components. As tasks evolve, such instance-centric representations may change substantially, contributing to instability across sequential learning stages and exacerbating forgetting.

In contrast, Graph Neural Networks (GNNs) provide a natural mechanism for modeling relationships among entities through message passing over structured representations. By representing images as graphs whose

nodes correspond to semantic regions and edges representing adjacency for learning contextual interactions, GNNs enable learning based on relational structure rather than solely local features. This perspective aligns with cognitive theories such as Recognition-by-Components (RBC) (Biederman, 1987), where object understanding arises from both component identification and their structural relationships.

Motivated by this observation, we propose ReReM, a novel Relational Representations Mitigation framework for online continual learning that integrates hierarchical visual representations with Graph Attention Networks (GATs). ReReM constructs graphs from multi-scale feature maps extracted by pretrained backbones, including CNNs and Vision Transformers (ViTs), enabling joint modeling of fine-grained and high-level semantic information. Attention-based message passing allows the model to dynamically emphasize informative relationships between regions, producing representations that adapt to new tasks while preserving previously learned structure.

To further improve graph-level representation learning, we introduce a new learnable weighted global pooling mechanism that adaptively prioritizes informative nodes during aggregation, overcoming limitations of conventional pooling strategies that treat all nodes uniformly. In addition, we address the imbalance between current-task data and limited rehearsal memory in continual learning by proposing a rehearsal duplication strategy that increases exposure to past-task samples without expanding memory storage, thereby improving knowledge retention under fixed resource constraints.

Our key contributions are summarized as follows:

1. We introduce a relational representation mitigation framework for online continual learning that combines hierarchical visual features with Graph Attention Networks to model interactions between semantic components of images.

2. We propose a learnable weighted global mean pooling mechanism that enhances graph-level representations by adaptively emphasizing informative nodes during aggregation.

3. We present a rehearsal duplication strategy that rebalances the influence of past and current data during training, improving stability without increasing rehearsal memory requirements.

4. Extensive experiments on CIFAR10, CIFAR100, and MiniImageNet demonstrate consistent improvements over pretrained CNN-based continual learning methods, with additional validation on Vision Transformer backbones highlighting the generality of the proposed framework.

The remainder of this paper is organized as follows. Section 2 reviews related work for continual learning in image classification, continual learning with GNNs as well as continual learning with rehearsal. Section 3 presents the proposed relational continual learning framework, including hierarchical graph construction, attention-based learning, and rehearsal duplication. Section 4 describes the experimental setup and empirical results, followed by ablation studies and analysis. Finally, Section 5 concludes the paper.

2 Related Work

2.1 Continual Learning in Image Classification

Continual Learning (CL) is a paradigm designed to enable models to sequentially learn a series of tasks while preserving performance on previously learned tasks, mitigating catastrophic forgetting, a common issue in standard training approaches where new learning overwrites prior knowledge. CL is typically categorized into three main settings which are Task-Incremental, Domain-Incremental, and Class-Incremental (van de Ven & Tolias, 2019; De Lange et al., 2022; van de Ven et al., 2022). Among these, Class-Incremental Learning is particularly challenging, as it requires the model to perform without explicit task identifiers and to classify across all encountered classes, thereby minimizing reliance on task-specific information.

In CL, pretrained models are often employed as feature extractors, leveraging representations generated by the final feature map. These approaches can be broadly divided into two categories: those that treat the pretrained model as a trainable backbone and those that use it as a fixed feature extractor (Jung et al., 2023).

Recent work, such as MuFAN, further leverages multi-granularity feature representations by utilizing feature maps from multiple layers to create richer representations for online continual learning (Jung et al., 2023). While one possibility is to directly utilize this representation for classification, our work employs GNNs to advance this concept further. By utilizing GNNs, we enable learning of relationships between features for representation update.

2.2 Continual Learning with Graph Neural Networks

GNNs have attracted considerable attention in the field of CL due to their effectiveness in handling graph-based data and enablement of methods to use graph specific information. For example, TWP (Liu et al., 2020) leverages topological information to stabilize training by measuring the gradient of attention coefficients in a GAT. However, most existing studies primarily focus on graph-structured data, making them unsuitable for image classification.

Recent research works have explored bridging the gap to utilize GNNs for CL in image classification. DGN (Carta et al., 2021) employs a static clustering method and evaluates its performance on MNIST and CI-FAR10 datasets. Similarly, GCL (Tang & Matteson, 2021) models image batches using random graphs, departing from conventional image-based methods. However, to the best of our knowledge, this is the first work to explore the use of graph attention networks on a hierarchical graph representation of images for CL for image classification.

2.3 Continual Learning with Rehearsal

The CL setup restricts the complete storage of past tasks for joint training, requiring models to learn tasks sequentially. Rehearsal-based techniques store a small subset of past tasks in a rehearsal buffer, and joint-training is then emulated through the use of both the current task and rehearsal buffer (Rolnick et al., 2018; Zhou & Cao, 2021). To better emulate joint training, methods operate on the rehearsal buffer, such as ER-GNN (Zhou & Cao, 2021) which selects from the replay buffer with replacement during training and rehearsal example selection based on class clusters and coverage metrics. However, we demonstrate that a straightforward storage and duplication strategy is capable for guiding model training and obtains competitive results.

3 Method

3.1 Background

Graph Neural Networks. A fundamental characteristic of GNNs is the structure of their layers, which directly influences the primary operation of GNNs: the message passing and update step. A common family of layers within GNNs is graph convolutional layers. In their simplest form, these layers can be expressed as:

$$Node' = Aggregate(Neighbour(Node)) \times Node \tag{1}$$

which simply aggregates the information from neighboring nodes into the node being updated. Trainable types of layers generally evolve from this basic formula, such as GraphConv (Morris et al., 2018), which adds a set of trainable weights for both the aggregate as well as node to be updated. Another component that can be swapped out would be the aggregation operation. Switching out the summation operation in GraphConv (Morris et al., 2018) to a mean operation would yield the general update formula used for SageConv (Hamilton et al., 2017). Instead of changing the aggregation operation, the weighing of neighboring nodes can be adjusted as well. GCNConv (Kipf & Welling, 2017) iterates on the general formulation by including the degree of the nodes. GATConv (Veličković et al., 2018) improves on the neighbor nodes weightage by adding learnable attention mechanisms between the neighboring nodes and the node to be updated, as well as self-attention for the node to be updated. GATv2Conv (Brody et al., 2022) further improves upon GATConv by re-arranging the order of operations to allow the attention mechanism to perform better based on the inputs.

Figure 1: Overview of ReReM, illustrated with three rehearsal images for Rehearsal Duplication. Train batches are first converted into graphs through Hierarchical Graph Construction. A Graph Attention Network is then utilized, followed by a Normalization and a Graph Pooling Layer.

3.2 Preliminaries

Given T total tasks, the image classes $C = \{c_1, ..., c_\alpha, ...\}$ can be divided into T tasks, denoted as $T = \{t_1, ...\} = \{\{c_1, ...\}, \{c_\alpha, ...\}, ...\}$, where each image associated with a specific task is represented as $i_\beta \in I_t$, $i_\beta = \{x_\beta, y_\beta\}$ such that $y_\beta = c_\beta \in t_\gamma$. We overload the notation t to present both the task and task number, and similarly i to represent both the image and image number. The graph construction step is represented as f while the GNN and pooling + classifier blocks trained till task t is represented as g_t and m_t respectively, while the rehearsal memory accumulated up to task t is denoted as R_t.

3.3 Graph Attention Network for Image-Based Continual Learning

We present an overview of the proposed ReReM framework in Figure 1, demonstrating how we first perform rehearsal duplication to enhance the representation of past tasks. Train batches are then passed into a Hierarchical Graph Construction step, which utilizes a pre-trained feature extractor to construct a multi-scale graph representation. The graph is then operated on by a Graph Attention Network, followed by Normalization and a novel Graph Pooling layer for graph level classification.

Hierarchical Graph Construction. Images are naturally structured as grid-based data rather than graph-based, making direct graph representation challenging. A naive approach for converting an image into a graph involves treating each pixel as a node and establishing edges between adjacent pixels. However, this method is highly inefficient, as it redundantly represents neighboring pixels with similar attributes as separate nodes.

To address this inefficiency, one avenue would be to employ SuperPixel methods such as Simple Linear Iterative Clustering (SLIC) to aggregate neighborhood information into nodes, representing a spatial region rather than individual pixels (Achanta et al., 2010). Although this approach reduces redundancy, it primarily captures color and spatial information.

Instead, we utilize a pretrained feature extractor to obtain a representation that is more information-rich by mapping the image into a feature space. In addition, instead of just utilizing the final output, features from different layers of the pre-trained feature extractor can be incorporated, integrating both fine-grained information with high-level semantic information. This form of hierarchical representation through a multi-level feature aggregation strategy enhances plasticity for OCL (Jung et al., 2023).

When aligning feature maps of differing spatial resolutions, we deliberately avoid the use of linear or bilinear upsampling methods, as such techniques implicitly assume smooth transitions between feature values that may not correspond to semantic relationships. For example, a feature map encoding the presence of a circular object in one spatial region and its absence in another does not imply a gradual transition between these regions at finer resolutions. Rather, each pixel contributes independently to the resulting representation.

Consequently, we instead upsample feature maps by replicating each feature value according to the ratio of spatial resolutions, thereby preserving semantic consistency and preventing the introduction of spurious interpolations. As an illustrative example, upsampling a feature map of (1, 4) yields a representation of (1, 1, 4, 4).

Node feature assignment is performed by associating each node with its corresponding spatial location across the hierarchical feature maps. Specifically, for each node, we concatenate feature vectors extracted from all aligned positions in the multi-scale feature maps, along with the explicit spatial coordinates (X,Y). This procedure produces a rich node representation that jointly encodes multi-granular semantic information and spatial information. Following the approach of SLIC (Achanta et al., 2010), we utilize a k-nearest neighbor (k-NN) approach based on the spatial information to construct edges between nodes based on spatial proximity. This method for constructing edges enables each node to be updated in the context of its neighborhood and surrounding features.

Graph Attention Network. We utilize a GAT to operate on the constructed graph during node updates to incorporate an attention mechanism into the update process. We posit that the inclusion of attention is critical for alleviating catastrophic forgetting in continual learning settings, as it enables the model to selectively emphasize relevant neighboring nodes during message passing, thereby reducing interference from less informative or redundant neighbors.

To do so, in this paper, we propose to use GATv2 (Brody et al., 2022) for learning the feature graphs. GATv2 (Brody et al., 2022) computes the normalized importance between nodes i and j as follows:

$$\alpha_{i,j} = \text{softmax}(a^\top \text{LeakyReLU}(w \cdot [h_i|h_j])) \tag{2}$$

Here, h_i and h_j represent the node features for nodes i and j respectively, where a and w are learnable weights. The node representation is then updated:

$$h_i' = \sigma(\sum_{j \in N_i} \alpha_{ij} \cdot wh_j) \tag{3}$$

whereby σ represents a non-linearity operation. This dynamic attention mechanism allows nodes to aggregate information from their neighbors based on learned importance weights.

Normalization. For normalization, we extend the hybrid SPN normalization block proposed in Jung et al. (2023) which was initially designed to normalize batch and feature dimensions in feature maps from CNNs. We modify the normalization block to operate on GNNs operating on graphs derived from feature map representations, such as the proposed graph construction and GAT-based architecture. To do so, we treat the entire graph as an analogue of a feature map. In this formulation, nodes correspond to pixel locations, while node channels correspond to feature values across the aggregated feature maps.

Graph Pooling Layer. Following the update of the graph representation, the final step for image classification is to perform graph-level classification. To serve as input to the classification component of the architecture, the graph is flattened and transformed into a vector. A naïve option, illustrated in Figure 2 (left), is to directly use the full graph representation. However, this results in a sizable input and imposes the constraint of a fixed graph size.

To address these limitations, global pooling operations can be utilized to reduce the the number of nodes by aggregating node representations across the entire graph into a single representative node, as depicted in Figure 2 (right). Common pooling strategies include max pooling, as adopted in DGN (Carta et al., 2021), as well as addition and mean pooling operations (Fey & Lenssen, 2019).

Although global mean pooling enables all nodes to contribute to the final representation, thereby capturing information from across the entire graph, it inherently assigns equal importance to all nodes. This uniform weighting can be problematic in the presence of repetitive background structures, which may dominate the aggregated representation.

Figure 2: Utilization of entire graph for classification (left), utilization of global pooling before classification (right)

Figure 3: Process of performing weighted global mean pool

To tackle this, we introduce a channel-wise weighted pooling strategy. As illustrated in Figure 3, we first reshape the graph representation such that values corresponding to the same channel across different nodes are aligned along a common dimension to enable joint processing. A linear layer is then applied to independently weigh each channel, after which the representation is reshaped back to its original graph format to produce a weighted graph representation. Finally, mean pooling is applied to obtain the graph-level representation for classification.

This weighting scheme preserves the relative importance of channel values across nodes in the final representation. By adaptively weighing each node's channel-wise contribution prior to pooling, the model can emphasize key nodes while still allowing information from all nodes to influence the aggregated representation.

While jointly weighting all nodes enables comprehensive comparison across the entire graph, it requires a fixed graph size to determine the size of the weights. To alleviate this constraint, we propose an alternative formulation that operates on smaller subsets of nodes, specifically, partitions comprising one-quarter of the graph at a time. A shared weighing layer is applied independently to each subset, allowing the approach to scale gracefully as the graph size increases in increments of the subset size. Figure 4 illustrates the partitioning procedure and the application of shared weights across subsets.

Figure 4: When weighing the entire graph at once, each node in the graph receives a separate weight when passed through the weighing layer. In the alternative form that operates on subsets, subsets of the graph, in this case, sets of 4 nodes receives separate weights, which are shared across the rest of the graph.

3.4 Training with Rehearsal Duplication

In rehearsal-based continual learning, a limited subset of data from previously encountered tasks is retained in a memory buffer and replayed during subsequent training phases. This replay buffer is typically substantially smaller than the dataset of the current task, leading to an imbalance in representation between past and present tasks during training. To mitigate this issue, we introduce a simple yet effective strategy: *duplicate rehearsal samples prior to their integration into the training stream to better approximate joint-task training.* Concretely, each stored sample is replicated multiple times before integration into the training stream, increasing its frequency of exposure to images from past tasks without expanding the memory buffer. This procedure amplifies the influence of prior-task data during learning and helps preserve previously acquired knowledge while incurring no additional storage cost.

4 Experiments

4.1 Datasets

We utilize three benchmark datasets for our experiments: 5-Task CIFAR10 (Krizhevsky, 2012; Tang & Matteson, 2021), 20-Task CIFAR100 (Krizhevsky, 2012; Lopez-Paz & Ranzato, 2017), and 20-Task MiniImageNet (Ravi & Larochelle, 2017; Vinyals et al., 2016; Jung et al., 2023).

CIFAR10 (Krizhevsky, 2012) contains 10 image classes with images of size 32x32, and Split CIFAR10 splits the said 10 classes into 5 tasks (Tang & Matteson, 2021). CIFAR100 (Krizhevsky, 2012) contains 100 image classes with images of size 32x32 as well, and Split CIFAR100 splits the mentioned 100 image classes into either 10 tasks (Zhou et al., 2024) or 20 tasks (Lopez-Paz & Ranzato, 2017).

While MiniImageNet (Ravi & Larochelle, 2017; Vinyals et al., 2016) also contains 100 image classes, with Split MiniImageNet also dividing the dataset into 20 tasks (Jung et al., 2023), the image resolution is different. The original resolution of the images is 224x224 as the images are derived from the ImageNet dataset. However, instead of utilizing this resolution, to maintain the intended level of image detail, we follow the MiniImageNet process of downscaling the images to a resolution of 84x84 before re-upscaling it to 224x224 as needed for processing.

Through utilization of the aforementioned CL setups, we ensure testing on a varied number of tasks as well as on different datasets which are split into the same number of tasks.

4.2 SuperPixel Construction

Where PyTorch Geometric (Fey & Lenssen, 2019) does not have available superpixel versions of datasets generated using SLIC (Achanta et al., 2010), the required data was constructed using the ToSLIC method,

Table 1: Simple Linear Iterative Clustering (SLIC) max nodes

Dataset	Image Resolution	Max Nodes
CIFAR100	32x32	100
MiniImageNet	84x84	700

Figure 5: Sample images from, in order, CIFAR10, CIFAR100, MiniImageNet (top) and the corresponding SuperPixel graph (bottom)

and the maximum number of nodes is configured as described in Table 1 with a visual example illustrated in Figure 5.

4.3 Architecture

We utilize a frozen pretrained ResNet18 network, stretching smaller feature maps to match the dimensions of the larger feature maps as detailed in Section 3.3: $i \rightarrow e_1 \in \mathbb{R}^{C_1 \times W_1 \times H_1}, e_2 \in \mathbb{R}^{C_2 \times W_2 \times H_2} \rightarrow e_1 \in \mathbb{R}^{C_1 \times W_1 \times H_1}, e_2 \in \mathbb{R}^{C_2 \times W_1 \times H_1} \rightarrow e_{final} \in \mathbb{R}^{(C_1+C_2) \times W_1 \times H_1}$ where W is the width, H is the height and C is the feature map's number of channels. Specifically, output representations from the final two convolutional blocks of the ResNet18 model is used.

Specifically, we utilized the ImageNet-1K (Deng et al., 2009) pre-trained model implemented by PyTorch (Ansel et al., 2024). Prior to re-scaling and combination, we obtain intermediate forms of size $256 \times 14 \times 14$ and $512 \times 7 \times 7$ as we utilize the final 2 convolutional blocks as mentioned. For edge construction using k-NN, we utilize a value of 8 for k following the SLIC (Achanta et al., 2010) approach in Dwivedi et al. (2024) The GNN is implemented utilizing 2 GATv2Conv (Fey & Lenssen, 2019) layers, specifically with 128 channels. The number of attention heads utilized is 4 attention heads for CIFAR10, and 3 attention heads for CIFAR100 and MiniImageNet Normalization is done with the extended SPN normalization block adapted to function on GNNs as detailed in Section 3.3 with reference implementation from the code base

made available by MuFAN (Jung et al., 2023). This extended SPN block is used post GNN but before the weighted global mean pooling. For classification, the classifier component has 2 linear layers of 128 features as well.

For the extended testing by swithing to a ViT (Dosovitskiy et al., 2021) backbone, HuggingFace's "vit-base-patch16-224-in21k" (Wolf et al., 2019; Wu et al., 2020; Deng et al., 2009) was utilized. For a similar hierarchical construction, the representation of size 197×768 from the final 4 blocks are utilized. As the dimensions of the representation obtained from each block is the same, scaling is not necessary and the outputs can instead be directly concatenated. Furthermore, as the output for ViT is a sequence which differs from the grid obtained from CNNs, to obtain a similar spatial reach, the edge construction is modified to use a k value of 3 instead. When applying this to CIFAR100, we utilize the same number of channels, normalization and classifier setup as described earlier but with 4 attention heads.

4.4 Training.

During training, we distill logit information by leveraging the DGN implementation (Carta et al., 2021) of the Learning without Forgetting (LwF) framework (Li & Hoiem, 2016), distilling across the combined training and rehearsal set. Soft targets are obtained by passing each batch from the combined training stream through a saved frozen copy of the model from the previous task. Specifically, the logits distillation loss is formulated as follows:

$$L_{LwF} = \lambda \frac{t^2}{t+1} \sum_{i=0}^{|R_t \cup I_t|} l_{kl}(p_i^{\text{old}}, \log(p_i^{\text{new}})), \tag{4}$$

where the output of the frozen model from the previous task is p_i^{old} and the output of the model from the current task is p_i^{new}, i: $p_i = \text{softmax}(m_t(g_t(f(x_i)))/T)$ and l_{kl} represents the Kullback-Leibler divergence. Logit distillation strength is controlled by a hyper-parameter λ and the temperature hyper-parameter is T. All results are reported as an average over 5 runs and with LwF.

4.5 Hyper-parameters

Lambda and temp for LwF was searched using a random search approach, in the range of 0.25 to 2.00 and 1.00 to 3.00 respectively. For the rehearsal budget, we follow GCL (Tang & Matteson, 2021) for CIFAR10 and utilize 5 rehearsal/class which is 10 rehearsal/task. The budget for CIFAR100 and MiniImageNet follows MuFAN (Jung et al., 2023) for 10 rehearsal/class which results in 50 rehearsal/task. When extended to ViT on CIFAR100, the budget is utilize 20 rehearsal/class following EASE (Zhou et al., 2024). The duplication level utilized is set at 15 for CIFAR10 as well as MiniImageNet and at 20 for CIFAR100. Training was performed on NVIDIA A100 and RTX A6000 GPUs, utilizing the Adam optimizer and a learning rate of 0.001.

4.6 Metrics

Performance is reported primarily using Average Accuracy (Tang & Matteson, 2021), which is defined using $Accuracy_{i,j}$, which is the accuracy of Task j after training till Task i,

$$Average\ Accuracy = \frac{1}{T} \sum_{j=0}^{T} Accuracy_{T,j} \tag{5}$$

This is supplemented with Average Forgetting as defined by GCL (Tang & Matteson, 2021) as well,

$$Average\ Forgetting = \frac{1}{T-1} \sum_{j=0}^{T-1} (Accuracy_{T,j} - Accuracy_{j,j}) \tag{6}$$

4.7 DGN Replication

We report the full results for DGN modified for the online setting across various hyper-parameters in Table 2.

Table 2: Average accuracy ↑ for replicating DGN in OCL across various hyper-parameters

Num Layer	Lambda	CIFAR10	CIFAR100	MiniImageNet
2 Layers	0.01	13.75±0.75	7.09±0.75	7.30±1.13
	0.001	**14.32±0.30**	5.49±1.37	4.76±0.65
	0.0001	14.11±0.53	6.45±0.87	6.04±1.77
4 Layers	0.01	14.00±0.33	**8.35±0.64**	7.41±1.84
	0.001	13.83±0.86	7.68±0.57	**7.86±0.53**
	0.0001	14.04±0.27	7.87±0.62	7.43±0.93

Table 3: Comparison of average accuracy ↑ with CNN and GNN methods (left), and pretrained feature extractor and GNN methods (right). (*****) denotes methods that use features from a pretrained feature extractor as input; all others operate directly on raw image pixels.

Model Family	Method	CIFAR10	Model Family	Method	CIFAR100	MiniImageNet
CNN	EWC	18.49±0.13	CNN*****	ER	20.50±0.90	11.00±0.50
	GEM	22.88±4.06		DER++	20.70±2.70	13.70±1.20
	ER	29.94±2.08		DualNet	25.50±0.70	20.90±1.60
	GCL	49.62±1.85		MuFAN	39.60±0.30	34.70±2.10
GNN	DGN	14.32±0.30	GNN	DGN	8.35±0.64	7.86±0.53
GNN*****	ReReM	**63.07±2.10**	GNN*****	ReReM	**43.95±1.16**	**41.20±2.57**

Table 4: Comparison of average forgetting ↓ with CNN and GNN methods. (*****) denotes methods that use features from a pretrained feature extractor as input; all others operate directly on raw image pixels.

Dataset	CNN				GNN	GNN*****
	EWC	GEM	ER	GCL	DGN	ReReM
CIFAR10	86.95±1.15	76.90±5.53	72.64±4.88	35.69±3.33	71.02±0.89	**24.30±4.27**

Table 5: Comparison of average accuracy ↑ with the ViT backbone on CIFAR100 with 10 Task rehearsal focused methods.

Dataset	10 Task Rehearsal			
	iCaRL	DER	MEMO	ReReM
CIFAR100	73.87	77.93	75.79	**82.55**

4.8 Results on Online Class-Incremental Learning

We first present the average accuracy results in Table 3 for an online class-incremental setting, whereby task identities are not given but the model needs to perform classification over all image classes. For the CIFAR10 benchmark, results for CNN based methods are referenced from GCL (Tang & Matteson, 2021) while on CIFAR100 and MiniImageNet, results obtained are compared against the reported performances in MuFAN (Jung et al., 2023). In addition, for GNN comparisons, we include comparison against the best reproduced DGN (Carta et al., 2021) values from Table 2. Through this evaluation protocol, we enable a comprehensive comparison against CNNs that both utilize graph representation as well as pre-trained feature extractors as well as GNN based approaches. In this comparison, our method achieves significant improvements in average accuracy over the compared methods, with accuracy gains of 27%, 10% and 18% on CIFAR10, CIFAR100, and MiniImageNet respectively.

In addition, we also compare average forgetting against the results reported by GCL (Tang & Matteson, 2021) for CIFAR10 in Table 4. When evaluating the tabled results, our method outperforms the compared approach on CIFAR10 significantly, which is consistent with the results for the average accuracy metric.

Table 6: Ablation across all three datasets for proposed utilization of Graph Attention (G. Attn) and Rehearsal Duplication (R. Duplication)

Method	CIFAR10	CIFAR100	MiniImageNet
GNN	47.40	15.15	28.26
GNN + G. Attn	49.00	15.97	32.55
GNN + G. Attn + R. Duplication	**63.07**	**43.95**	**41.20**

Table 7: Ablation across all three datasets for proposed utilization of Weighted Global Mean Pooling (Ours) compared to other global pooling operations available

Dataset	CIFAR10	CIFAR100	MiniImageNet
GlobalAddPool	12.40	21.10	34.70
GlobalMaxPool	47.45	32.15	38.60
GlobalMeanPool	58.36	43.69	40.66
Ours	**63.07**	**43.95**	**41.20**

4.9 Extension to ViT Backbone

To further assess the proposed method's generalization capability, we switch to a Vision Transformer (ViT) (Dosovitskiy et al., 2021), replacing the ResNet18 feature extractor (He et al., 2015), as described in Section 4.3. We evaluate our method against ViT-based baselines on the 10-Task split of CIFAR-100 in Table 5, referencing results from Zhou et al. (2024).

The results indicate that the proposed method consistently outperforms the baseline approaches. We highlight that the baseline results reported in Table 5 are obtained from an offline setting, which is considerably less demanding than the OCL scenario under which our method is evaluated. We contend that the performance of these baselines would likely deteriorate further when deployed in an OCL setting, thereby further highlighting the superiority of the proposed approach regardless of the backbone architectures.

4.10 Ablation Study

We conduct an ablation study to assess the contributions of the proposed attention mechanism and the rehearsal duplication strategy. As reported in Table 6, utilization of GAT for attention-based updates consistently improves average accuracy across the evaluated datasets when compared to non-attention alternatives, such as GraphConv (Morris et al., 2018). Moreover, the integration of rehearsal duplication yields additional performance gains, demonstrating that the representation imbalance issue in OCL can be mitigated with a simple rehearsal replication strategy effectively.

In addition, we evaluate the proposed weighted global mean pooling strategy's effectiveness relative to existing global pooling operations, with the results presented in Table 7. The findings indicate that additive pooling underperforms consistently, whereas mean pooling approaches achieves superior results. Notably, the proposed weighted mean pooling method consistently outperforms all alternative pooling strategies across all benchmark datasets, highlighting the advantage of enabling the model to learn node importance during graph-level aggregation.

5 Conclusion

In this work, we presented a novel OCL framework for image classification that leverages Graph Attention Networks (GATs) to effectively model contextual relationships and dynamically update class-specific representations. The proposed approach constructs information-rich graph representations by integrating multi-scale semantic information obtained from a pretrained backbone. To enhance graph-level classification, we introduced a weighted global pooling mechanism that selectively emphasizes key nodes during pooling.

In addition, we proposed a simple yet effective rehearsal duplication strategy to mitigate representational imbalance between current and previously learned tasks without increasing memory requirements.

Extensive experiments conducted on three standard benchmark datasets demonstrate that the proposed method consistently outperforms pretrained CNN-based approaches, underscoring its effectiveness in OCL scenarios. Future work could extend upon the proposed work by further leveraging the components of the described framework to construct specific techniques that better leverage the framework. Examples of such potential avenues could be graph and graph attention related techniques to further leverage the GNN component of the framework.

References

Radhakrishna Achanta, Appu Shaji, Kevin Smith, Aurélien Lucchi, Pascal Fua, and Sabine Süsstrunk. Slic superpixels. *Technical report, EPFL*, 06 2010.

Jason Ansel, Edward Yang, Horace He, Natalia Gimelshein, Animesh Jain, Michael Voznesensky, Bin Bao, Peter Bell, David Berard, Evgeni Burovski, Geeta Chauhan, Anjali Chourdia, Will Constable, Alban Desmaison, Zachary DeVito, Elias Ellison, Will Feng, Jiong Gong, Michael Gschwind, Brian Hirsh, Sherlock Huang, Kshiteej Kalambarkar, Laurent Kirsch, Michael Lazos, Mario Lezcano, Yanbo Liang, Jason Liang, Yinghai Lu, CK Luk, Bert Maher, Yunjie Pan, Christian Puhrsch, Matthias Reso, Mark Saroufim, Marcos Yukio Siraichi, Helen Suk, Michael Suo, Phil Tillet, Eikan Wang, Xiaodong Wang, William Wen, Shunting Zhang, Xu Zhao, Keren Zhou, Richard Zou, Ajit Mathews, Gregory Chanan, Peng Wu, and Soumith Chintala. PyTorch 2: Faster Machine Learning Through Dynamic Python Bytecode Transformation and Graph Compilation. In *29th ACM International Conference on Architectural Support for Programming Languages and Operating Systems, Volume 2 (ASPLOS '24)*. ACM, April 2024. doi: 10.1145/3620665.3640366. URL https://pytorch.org/assets/pytorch2-2.pdf.

Irving Biederman. Recognition-by-components: a theory of human image understanding. *Psychological review*, 94 2:115–147, 1987. URL https://api.semanticscholar.org/CorpusID:8054340.

Shaked Brody, Uri Alon, and Eran Yahav. How attentive are graph attention networks? In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=F72ximsx7C1.

Antonio Carta, Andrea Cossu, Federico Errica, and Davide Bacciu. Catastrophic forgetting in deep graph networks: an introductory benchmark for graph classification. *ArXiv*, abs/2103.11750, 2021. URL https://api.semanticscholar.org/CorpusID:232307444.

Matthias De Lange, Rahaf Aljundi, Marc Masana, Sarah Parisot, Xu Jia, Aleš Leonardis, Gregory Slabaugh, and Tinne Tuytelaars. A continual learning survey: Defying forgetting in classification tasks. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 44(7):3366–3385, 2022. doi: 10.1109/TPAMI.2021.3057446.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. *ICLR*, 2021.

Vijay Prakash Dwivedi, Chaitanya K. Joshi, Anh Tuan Luu, Thomas Laurent, Yoshua Bengio, and Xavier Bresson. Benchmarking graph neural networks. *J. Mach. Learn. Res.*, 24(1), March 2024. ISSN 1532-4435.

Matthias Fey and Jan Eric Lenssen. Fast graph representation learning with pytorch geometric, 2019. URL https://arxiv.org/abs/1903.02428.

William L. Hamilton, Zhitao Ying, and Jure Leskovec. Inductive representation learning on large graphs. In *Neural Information Processing Systems*, 2017. URL https://api.semanticscholar.org/CorpusID:4755450.

Kaiming He, X. Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, 2015. URL `https://api.semanticscholar.org/CorpusID:206594692`.

Fushuo Huo, Wenchao Xu, Jingcai Guo, Haozhao Wang, and Yunfeng Fan. Non-exemplar online class-incremental continual learning via dual-prototype self-augment and refinement. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pp. 12698–12707, 2024.

Dahuin Jung, Dongjin Lee, Sunwon Hong, Hyemi Jang, Ho Bae, and Sungroh Yoon. New insights for the stability-plasticity dilemma in online continual learning. In *International Conference on Learning Representations*, 2023. URL `https://openreview.net/forum?id=fxC7kJYwA_a`.

Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *International Conference on Learning Representations*, 2017. URL `https://openreview.net/forum?id=SJU4ayYgl`.

Alex Krizhevsky. Learning multiple layers of features from tiny images. *University of Toronto*, 05 2012.

Zhizhong Li and Derek Hoiem. Learning without forgetting. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 40:2935–2947, 2016. URL `https://api.semanticscholar.org/CorpusID:4853851`.

Huihui Liu, Yiding Yang, and Xinchao Wang. Overcoming catastrophic forgetting in graph neural networks. In *AAAI Conference on Artificial Intelligence*, 2020. URL `https://api.semanticscholar.org/CorpusID:228373664`.

David Lopez-Paz and Marc'Aurelio Ranzato. Gradient episodic memory for continual learning. In *Neural Information Processing Systems*, 2017. URL `https://api.semanticscholar.org/CorpusID:37308416`.

Michael McCloskey and Neal J. Cohen. Catastrophic interference in connectionist networks: The sequential learning problem. *Psychology of Learning and Motivation*, 24:109–165, 1989. URL `https://api.semanticscholar.org/CorpusID:61019113`.

Christopher Morris, Martin Ritzert, Matthias Fey, William L. Hamilton, Jan Eric Lenssen, Gaurav Rattan, and Martin Grohe. Weisfeiler and leman go neural: Higher-order graph neural networks. In *AAAI Conference on Artificial Intelligence*, 2018. URL `https://api.semanticscholar.org/CorpusID:52919090`.

Sachin Ravi and Hugo Larochelle. Optimization as a model for few-shot learning. In *International Conference on Learning Representations*, 2017. URL `https://openreview.net/forum?id=rJY0-Kcll`.

David Rolnick, Arun Ahuja, Jonathan Schwarz, Timothy P. Lillicrap, and Greg Wayne. Experience replay for continual learning. In *Neural Information Processing Systems*, 2018. URL `https://api.semanticscholar.org/CorpusID:53860287`.

Binh Tang and David S. Matteson. Graph-based continual learning. In *International Conference on Learning Representations*, 2021. URL `https://openreview.net/forum?id=HHSEKOnPvaO`.

Gido van de Ven, Tinne Tuytelaars, and Andreas Tolias. Three types of incremental learning. *Nature Machine Intelligence*, 4:1–13, 12 2022. doi: 10.1038/s42256-022-00568-3.

Gido M. van de Ven and Andreas Savas Tolias. Three scenarios for continual learning. *ArXiv*, abs/1904.07734, 2019. URL `https://api.semanticscholar.org/CorpusID:119309522`.

Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph attention networks. In *International Conference on Learning Representations*, 2018. URL `https://openreview.net/forum?id=rJXMpikCZ`.

Oriol Vinyals, Charles Blundell, Timothy P. Lillicrap, Koray Kavukcuoglu, and Daan Wierstra. Matching networks for one shot learning. In *Neural Information Processing Systems*, 2016. URL `https://api.semanticscholar.org/CorpusID:8909022`.

Liyuan Wang, Xingxing Zhang, Hang Su, and Jun Zhu. A comprehensive survey of continual learning: theory, method and application. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2024.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander M. Rush. Huggingface's transformers: State-of-the-art natural language processing. *ArXiv*, abs/1910.03771, 2019. URL `https://api.semanticscholar.org/CorpusID:274421273`.

Bichen Wu, Chenfeng Xu, Xiaoliang Dai, Alvin Wan, Peizhao Zhang, Zhicheng Yan, Masayoshi Tomizuka, Joseph Gonzalez, Kurt Keutzer, and Peter Vajda. Visual transformers: Token-based image representation and processing for computer vision, 2020.

Da-Wei Zhou, Hai-Long Sun, Han-Jia Ye, and De chuan Zhan. Expandable subspace ensemble for pre-trained model-based class-incremental learning. *2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 23554–23564, 2024. URL `https://api.semanticscholar.org/CorpusID:268531460`.

Fan Zhou and Chengtai Cao. Overcoming catastrophic forgetting in graph neural networks with experience replay. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pp. 4714–4722, 2021.