DIFFUSION GENERATIVE MODELS ON SO(3)

ABSTRACT

Diffusion-based generative models represent the current state-of-the-art for image generation. However, standard diffusion models are based on Euclidean geometry and do not translate directly to manifold-valued data. In this work, we develop extensions of both score-based generative models (SGMs) and Denoising Diffusion Probabilistic Models (DDPMs) to the Lie group of 3D rotations, SO(3). SO(3) is of particular interest in many disciplines such as robotics, biochemistry and astronomy/planetary science. Contrary to more general Riemannian manifolds, SO(3) admits a tractable solution to heat diffusion, and allows us to implement efficient training of diffusion models. We apply both SO(3) DDPMs and SGMs to synthetic densities on SO(3) and demonstrate state-of-the-art results.

1 INTRODUCTION

Deep generative models (DGM) are trained to learn the underlying data distribution and then generate new samples that match the empirical data. There are several classes of deep generative models, including Generative Adversarial Networks (Goodfellow et al., 2014), Variational Auto Encoders (Kingma & Welling, 2013) and Normalizing Flows (Rezende & Mohamed, 2015). Recently, a new class of DGMs based on Diffusion, such as Denoising Diffusion Probabilistic Models (DDPM) (Ho et al., 2020) and Score Matching with Langevin Dynamics (SMLD) , a subset of general score-based generative models (SGMs), (Song & Ermon, 2019), have achieved state-of-the-art quality in generating images, molecules, audio and graphs[1] (Song et al., 2021). Unlike GANs, training diffusion models is usually very stable and straightforward, they do not suffer as much from mode collapse issues, and they can generate images of similar quality.

In parallel with the success of these diffusion models, Song et al. (2021) demonstrated that both SGMs and DDPMs can mathematically be understood as variants of the same process. In both cases, the data distribution is progressively perturbed by a noise diffusion process defined by a specific Stochastic Differential Equation (SDE), which can then be time-reversed to generate realistic data samples from initial noise samples.

While the success of diffusion models has mainly been driven by data with Euclidean geometry (e.g., images), there is great interest in extending these methods to manifold-valued data, which are ubiquitous in many scientific disciplines. Examples include high-energy physics (Brehmer & Cranmer, 2020; Craven et al., 2022), astrophysics (Hemmati et al., 2019), geoscience (Gaddes et al., 2019), and biochemistry (Zelesko et al., 2020). Very recently, pioneering work has started to develop generic frameworks for defining SGMs on arbitrary compact Riemannian manifolds (De Bortoli et al., 2022), and non-compact Riemannian manifolds (Huang et al., 2022).

In this work, instead of considering generic Riemannian manifolds, we are specifically concerned with the Special Orthogonal group in 3 dimensions, SO(3), which corresponds to the Lie group of 3D rotations. Modeling 3D orientations is of particularly high interest in many fields including for instance in robotics (estimating the pose of an object, Hoque et al. 2021); and in biochemistry (finding the conformation angle of molecules that minimizes the binding energy, Mansimov et al. 2019). Contrary to more generic Riemannian manifolds, SO(3) benefits from specific properties, including a tractable heat kernel and efficient geometric ODE/SDE solvers, that will allow us to define very efficient diffusion models specifically for this manifold.

---

[1]For a comprehensive list of articles on score-based generative modeling, see `https://scorebasedgenerativemodeling.github.io/`

Figure 1: Illustration of reversible diffusion of a mixture of two $\mathcal{IG}_{\text{SO(3)}}$ blobs on SO(3). Samples from a given base distribution (right most, denoted by circles) can be evolved under the probability flow ODE (Eq. 3) towards a noisy distribution (left most), or vice-versa from the noisy distribution back to the target distribution. Each point represents a rotation matrix in SO(3) projected on the sphere according to its canonical axis, the color indicates the tilt around that axis (visualisation adopted from Murphy et al. 2021). An animation of this figure is available at this link.

The contributions of our paper are summarized as follows:

- We reformulate Euclidean diffusion models on the SO(3) manifold, and demonstrate how the tractable heat kernel solution on SO(3) can be used to recover simple and efficient algorithms on this manifold.
- We provide concrete implementations of both Score-Based Generative Model and Denoising Diffusion Probabilistic Models specialized for SO(3).
- We reach a new state-of-the-art in sample quality on synthetic SO(3) distributions with our proposed SO(3) Score-Based Generative Model.

2   PRELIMINARIES AND NOTATIONS

In this work, we are exclusively considering the SO(3) manifold, corresponding to the Lie group of 3D rotation matrices. We will denote by $\exp : \mathfrak{so}(3) \rightarrow \text{SO(3)}$ and $\log : \text{SO(3)} \rightarrow \mathfrak{so}(3)$ the exponential and logarithmic maps that connect SO(3) to its tangent space and Lie algebra $\mathfrak{so}(3)$. $\mathfrak{so}(3)$ corresponds to all skew-symmetric 3x3 matrices in $\mathbb{R}^3$, which can be parameterised in terms of a vector in $\mathbb{R}^3$, which corresponds in turn to the *axis-angle* representation of rotation matrices. For any rotation $\mathbf{x} \in \text{SO(3)}$, its axis-angle representation $\boldsymbol{\omega} \in \mathbb{R}^3$ can be computed as $\boldsymbol{\omega} = \omega \mathbf{v}$ with $\omega = \arccos\left(2^{-1}(\text{tr}(\mathbf{x}) - 1)\right) \in (-\pi, \pi]$ and $\mathbf{v} = \frac{1}{2\sin\omega}(\mathbf{x}_{32} - \mathbf{x}_{23}, \mathbf{x}_{13} - \mathbf{x}_{31}, \mathbf{x}_{21} - \mathbf{x}_{12})$ a unit vector of $\mathbb{R}^3$.

We direct the interested reader to more information on representations of SO(3) in Appendix B.1.

3   DIFFUSION PROCESS ON SO(3)

Similarly to Euclidean diffusion models (Song et al., 2021), we begin by defining a Brownian noising process that will be used to perturb the data distribution. Let us assume a Stochastic Differential Equation of the following form:

$$\mathrm{d}\mathbf{x} = \mathbf{f}(\mathbf{x}, t)\, \mathrm{d}t + g(t)\, \mathrm{d}\mathbf{w}, \tag{1}$$

where $\mathbf{w}$ is a Brownian process on SO(3), $\mathbf{f}(\cdot\,, t) : \text{SO(3)} \rightarrow T_{\mathbf{x}}\text{SO(3)}$ is a drift term, and $g(\cdot) : \mathbb{R} \rightarrow \mathbb{R}$ is a diffusion term. If we sample initial conditions for this SDE at $t = 0$ from a given data distribution $\mathbf{x}(0) \sim p_{\text{data}}$, we will denote by p_t the marginal distribution of $\mathbf{x}(t)$ at time $t > 0$. Thus $p_0 = p_{\text{data}}$, and at final time T at which we stop the diffusion process p_T will typically tend to a known target distribution that will be easy to sample from.

Just like in the Euclidean case, as demonstrated in De Bortoli et al. (2022), under mild regularity conditions Equation 1 admits a reverse diffusion process on compact Riemannian manifolds such as SO(3), defined by the following reverse-time SDE:

$$\mathrm{d}\mathbf{x} = [\mathbf{f}(\mathbf{x}, t) - g(t)^2 \nabla \log p_t(\mathbf{x})]\mathrm{d}t + g(t)\mathrm{d}\bar{\mathbf{w}}, \tag{2}$$

where $\bar{\mathbf{w}}$ is a reversed-time Brownian motion and the *score function* $\nabla \log p_t(\mathbf{x}) \in T_{\mathbf{x}}\mathrm{SO}(3)$ is the derivative of the log marginal density of the forward process at time t. Corresponding to this reverse-time SDE, one can also define a probability flow ODE (Song et al., 2021):

$$\mathrm{d}\mathbf{x} = [\mathbf{f}(\mathbf{x}, t) - g(t)^2 \nabla \log p_t(\mathbf{x})]\mathrm{d}t. \tag{3}$$

This deterministic process is entirely defined once the score is known and maps p_T to any intermediate marginal distributions $\{p_t\}_{0 \leq t < T}$ of the forward process, including p_0. In particular, it can be seen as the equivalent of Neural ODE-based Continuous Normalizing Flows (CNF, Chen et al., 2018) with an explicit parameterization in terms of the score function. We illustrate this process in Figure 1 with samples from two Gaussian-like blobs on SO(3) being transported reversibly through this ODE between $t = 0$ and $t = T$.

While these equations are direct analog of the Euclidean SDEs and ODE described in Song et al. (2021), defining diffusion generative models on SO(3) will mainly differ on the two following points:

- Defining the equivalent of the Gaussian heat kernel on SO(3): this is needed to easily sample from any intermediate p_t without having to simulate an SDE.
- Solving SDEs and ODEs on the manifold: contrary to the Euclidean case, the diffusion process must remained confined to the SO(3) manifold, which requires specific solvers.

We address these two points below before moving on to defining our generative models on SO(3).

3.1 THE ISOTROPIC GAUSSIAN DISTRIBUTION ON SO(3)

In general, the main disadvantage of working on Riemannian manifolds compared to Euclidean space is that they lack a closed form expression for the heat kernel, i.e., the solution of the diffusion process (which is a Gaussian in Euclidean space). For compact manifolds, the heat kernel is in general only available as an infinite series, which in the case of SO(3), takes the following form (Nikolayev & Savyolov, 1970):

$$f_\epsilon(\omega) = \sum_{\ell=0}^{\infty} (2\ell + 1) \exp(-l(l+1)\epsilon^2) \frac{\sin((\ell + 1/2)\omega)}{\sin(\omega/2)} \tag{4}$$

where $\omega = |\boldsymbol{\omega}| \in (-\pi, \pi]$ is the rotation angle of the axis-angle representation $\boldsymbol{\omega}$ of a given rotation matrix and ϵ is a concentration parameter.

While for $\epsilon > 1$ this series converges quickly ($\ell_{\max} = 5$ is sufficient to achieve sub-percent accuracy), the convergence gets slower as ϵ gets smaller, which makes it impractical to model concentrated distributions. Thankfully, this series has been thoroughly studied in the literature and Matthies et al. (1988) shows that an excellent approximation of Equation 4 can be achieved for $\epsilon < 1$ using the following closed-form expression:

$$f_\epsilon(\omega) \simeq \sqrt{\pi}\epsilon^{-3/2} e^{\frac{\epsilon}{4} - \frac{(\omega/2)^2}{\epsilon}} \left(\frac{\omega - e^{-\frac{\pi^2}{\epsilon}} \left((\omega - 2\pi)e^{\pi\omega/\epsilon} + (\omega + 2\pi)e^{-\pi\omega/\epsilon} \right)}{2\sin(\omega/2)} \right). \tag{5}$$

Therefore, in practical applications, one can switch between using a truncation of Equation 4 for $\epsilon \geq 1$ and the approximation Equation 5 for $\epsilon < 1$.

Because of the property of being a solution of a diffusion process on SO(3), f_ϵ can be used to define the manifold equivalent of the Euclidean isotropic Gaussian distribution, which we will refer to as $\mathcal{IG}_{\mathrm{SO}(3)}$, the Isotropic Gaussian on SO(3) (Leach et al., 2022; Ryu et al., 2022), also known in the literature as the normal distribution on SO(3) (Nikolayev & Savyolov, 1970; Matthies et al., 1988). For a given mean rotation $\boldsymbol{\mu} \in \mathrm{SO}(3)$ and scale ϵ, the probability density of a rotation $\mathbf{x} \in \mathrm{SO}(3)$ under $\mathcal{IG}_{\mathrm{SO}(3)}(\boldsymbol{\mu}, \epsilon)$ is given by:

$$\mathcal{IG}_{\mathrm{SO}(3)}(\mathbf{x}; \boldsymbol{\mu}, \epsilon) = f_\epsilon(\arccos\left[2^{-1}(\mathrm{tr}(\boldsymbol{\mu}^T\mathbf{x}) - 1)\right]). \tag{6}$$

Sampling from $\mathcal{IG}_{\mathrm{SO}(3)}(\boldsymbol{\mu}, \epsilon)$ is achieved in practice by inverse transform sampling. The cumulative distribution function over angles needed to sample with respect to the uniform distribution on SO(3) can be evaluated numerically given integrating $\frac{1-\cos(\omega)}{\pi} f_\epsilon(\omega)$ over $(-\pi, \pi]$. To form a rotation matrix $\mathbf{x} \sim \mathcal{IG}_{\mathrm{SO}(3)}(\cdot; \boldsymbol{\mu}, \epsilon)$, one therefore first samples a rotation angle by inverse transform sampling

---

Algorithm 1 Geometric ODE solver on SO(3) (Heun's method) for $\mathrm{d}\mathbf{x} = \mathbf{f}(\mathbf{x}, t)\, \mathrm{d}t$

Require: Step size h, initial condition $\mathbf{x}_0$, time steps $\{t_n\}_{n=0}^{N}$, number of steps N
1: **for** $n \in \{0, \ldots, N-1\}$ **do**
2:      $\mathbf{y}_1 = h\, \mathbf{f}(\mathbf{x}_n,\, t_n)$
3:      $\mathbf{y}_2 = h\, \mathbf{f}(\exp(\frac{1}{2}\mathbf{y}_1)\mathbf{x}_n,\, t_n + \frac{1}{2}h)$
4:      $\mathbf{x}_{n+1} = \exp(\mathbf{y}_2)\mathbf{x}_n$
5: **end for**
6: **return** $\{\mathbf{x}_n\}_{n=0}^{N}$

---

given this CDF, then samples uniformly on $\mathcal{S}^2$ a rotation axis $\mathbf{v}$, yielding an axis-angle representation of a rotation matrix $\boldsymbol{\omega} = \omega \mathbf{v}$, which is then shifted by the mean of the distribution according to $\boldsymbol{x} = \boldsymbol{\mu} \exp(\boldsymbol{\omega})$.

An important property of $\mathcal{IG}_{\mathrm{SO}(3)}(\mu, \epsilon)$, which sets it apart from other distributions on SO(3) (e.g. Bingham, Matrix Fisher, Wrapped Normal, more on this in Appendix B.3), is that it remains *closed under convolution*, as a direct consequence of being the solution of a diffusion process. The convolution of two centered $\mathcal{IG}_{\mathrm{SO}(3)}$ distributions of scale parameter ϵ_1 and ϵ_2 is an $\mathcal{IG}_{\mathrm{SO}(3)}$ distribution of scale $\epsilon_1 + \epsilon_2$.

We will also note two interesting asymptotic behaviors. For large ϵ, it tends to $\mathcal{U}_{\mathrm{SO}(3)}$, the uniform distribution on SO(3), while for small ϵ the distribution $\mathcal{IG}_{\mathrm{SO}(3)}(\mathbf{I}, \epsilon)$ can locally be approximated in the axis-angle representation of the tangent space by a normal distribution $\mathcal{N}(0, \sigma^2 \mathbf{I})$ in $\mathbb{R}^3$, with $\epsilon = \frac{\sigma^2}{2}$.

3.2   Solving Ordinary Differential Equations on SO(3)

Thanks to the existence of a tractable heat kernel on SO(3), the generative models we will define in the next section will not actually require us to solve the SDEs introduced at the beginning of this section, and we will only need to solve the probability flow ODE defined in Equation 3.

Solving differential equations on manifolds can broadly be achieved using two distinct strategies, either projection methods using a Euclidean solver followed by a projection step onto the manifold, or intrinsic methods that rely on additional structure of the manifold to define an iteration that remains by construction on the manifold. In this work, we are concerned with SO(3), which is not only a compact Riemannian manifold, but also possesses a Lie group structure, which makes it amenable to efficient solvers. In particular, we will make use of the Runge-Kutta-Munthe-Kaas (RK-MK) class of algorithms and direct the interested reader to Iserles et al. (2000) for a review of Lie group integrators. We adopt in practice the Lie group equivalent of Heun's method, which is one variant of RK-MK integrators, and we provide the details of this integrator in Algorithm 1.

While we will not require it in practice, it is also possible to build SDE solvers on SO(3) with a similar strategy, and we point the interested reader for instance to the Geodesic Random Walk algorithm described in De Bortoli et al. (2022).

4   Diffusion Generative Models on SO(3)

The core idea of diffusion models is to perturb a given empirical data distribution p_{data} by a noise process defined in terms of a stochastic differential equation of the form Equation 1. While several expressions can be proposed for this SDE, for simplicity we will consider here the case of the Variance-Exploding SDE (and for our experiments we present both Variance-Exploding and Variance-Preserving cases), with $\mathbf{f}(\mathbf{x}, \mathbf{t}) = 0$ and $g(t) = \sqrt{\frac{\mathrm{d}\epsilon(t)}{\mathrm{d}t}}$ for a given choice of noise schedule $\epsilon(t)$, which corresponds to the canonical choice of the Euclidean Score-Matching Langevin Dynamics (Song & Ermon, 2019):

$$\mathrm{d}\mathbf{x} = \sqrt{\frac{\mathrm{d}\epsilon(t)}{\mathrm{d}t}}\, \mathrm{d}\mathbf{w} \,. \tag{7}$$

For our fiducial model, and unless stated otherwise, we will further assume for simplicity the following noise schedule: $\epsilon(t) = t$. The main drawback of this SDE in Euclidean geometry is that it

Figure 2: Sampling from a Diffusion Generative Model trained on a synthetic density on SO(3). Starting from $\mathcal{U}_{SO(3)}$, the uniform distribution on SO(3) at $t = T$ (left), the sampling procedure (either based on SGMs or DDPMs) denoises this distribution back to the target density at $t = 0$ (right). For visualization this density plot shows the distribution of canonical axes of sampled rotations projected on the sphere; the tilt around that axis is discarded.

will tend to a Gaussian with infinitely large variance. However, on SO(3) this SDE will tend to the uniform distribution $\mathcal{U}_{SO(3)}$ which is a natural choice for the prior distribution at large T.

Following from this choice of SDE, we can define a noise kernel $p_\epsilon(\tilde{\boldsymbol{x}}|\boldsymbol{x}) = \mathcal{IG}_{SO(3)}(\tilde{\boldsymbol{x}}; \boldsymbol{x}, \epsilon)$ for $\boldsymbol{x}, \tilde{\boldsymbol{x}} \in SO(3)$, such that the data distribution convolved by this noise kernel becomes

$$p_\epsilon(\boldsymbol{x}) = \int_{SO(3)} p_{\text{data}}(\boldsymbol{x}') p_\epsilon(\boldsymbol{x}|\tilde{\boldsymbol{x}}) \, \mathrm{d}\boldsymbol{x} \;, \tag{8}$$

and corresponds to p_t, the marginal distribution of the diffusion process at time t: $p_{\epsilon(t)} = p_t$.

Having introduced a specific choice of kernel and SDE well suited to the SO(3) manifold, we now move on to describing the two different approaches to build generative models: Score-Based Models and Denoising Diffusion Probabilistic Models. They both will lead to sampling procedures illustrated in Figure 2.

4.1 SCORE-BASED GENERATIVE MODEL

The first strategy directly extends Euclidean SGMs (Song & Ermon, 2019; Song et al., 2021) and relies on the time-reversed diffusion process described in Equation 2. Samples from the learned distribution p_0 can be sampled by first sampling $\mathbf{x}_T \sim \mathcal{U}_{SO(3)}$ and evolving these samples either through the reverse SDE (Equation 2) or probability flow ODE (Equation 3) back to $t = 0$. This process is entirely defined as soon as the *score function* of the marginal distribution at any intermediate time t, $\nabla \log p_{\epsilon(t)}$, is known. Therefore the first step is to establish a score-matching strategy on SO(3).

Let us consider $\{X_i\}_{i=0}^3$, an orthonormal basis of the tangent space $T_{\mathbf{e}}SO(3)$. The directional derivative of the log density of the noise kernel $p_\epsilon(\boldsymbol{x}|\tilde{\boldsymbol{x}})$ can be computed as:

$$\nabla_{X_i} \log p_\epsilon(\tilde{\mathbf{x}}|\mathbf{x}) = \frac{\mathrm{d}}{\mathrm{d}s} \log p_\epsilon(\tilde{\mathbf{x}} \exp(sX_i)|\mathbf{x})\bigg|_{s=0} \;, \tag{9}$$

which can be computed in practice by automatic differentiation given the explicit approximation formulae for the $\mathcal{IG}_{SO(3)}$ distribution introduced in subsection 3.1. To match this derivative, we introduce a neural score estimator $s_\theta(\mathbf{x}, \epsilon) : SO(3) \times \mathbb{R}^{+\star} \to \mathbb{R}^3$, which can be trained directly under a conventional denoising score matching loss:

$$\mathcal{L}_{DSM} = \mathbb{E}_{p_{\text{data}}(\mathbf{x})} \mathbb{E}_{\epsilon \sim \mathcal{N}(0, \sigma_\epsilon^2)} \mathbb{E}_{p_{|\epsilon|}(\tilde{\mathbf{x}}|\mathbf{x})} \left[|\epsilon| \parallel s_\theta(\tilde{\mathbf{x}}, \epsilon) - \nabla_X \log p_{|\epsilon|}(\tilde{\mathbf{x}}|\mathbf{x}) \parallel_2^2 \right] \tag{10}$$

where we sample at training time random noise scales $\epsilon \sim \mathcal{N}(0, \sigma_\epsilon^2)$ similarly to Song & Ermon (2020). The minimum of this loss will be achieved for $s_\theta(\mathbf{x}, \epsilon) = \nabla \log p_\epsilon$.

Once the score function is estimated from data using this score matching loss, sampling from the generative model can be achieved by using the reverse SDE formula, or using the ODE flow formula. In this work, we use the latter for its simplicity and speed, so that our specific fiducial sampling strategy becomes:

$$\mathbf{x}_T \sim \mathcal{U}_{SO(3)} \qquad ; \qquad \mathrm{d}\mathbf{x}_t = -\frac{1}{2} \frac{\mathrm{d}\epsilon(t)}{\mathrm{d}t} s_\theta(\mathbf{x}_t, \epsilon(t)) \, \mathrm{d}t \tag{11}$$

which we solve down to $t = 0$ with the geometric ODE solver described in Algorithm 1. Compared to stochastic sampling strategies based on simulating the reverse SDE, this approach has several

advantages. 1) It is much faster, and can benefit from adaptive ODE solvers bringing down the number of score evaluations needed, 2) the same ODE can be used to evaluate the log likelihood of the model by applying the probability flow formula of CNFs.

4.2 DENOISING DIFFUSION PROBABILISTIC MODEL

As described in Song et al. (2021), when using a finite number of steps, the forward diffusion process defined by Equation 7 $\{\mathbf{x}_i\}_{i=0}^N$ (corresponding to times $\{0 \leq t_i \leq T\}_{i=0}^n$) can be interpreted as a Markov process:

$$p(\mathbf{x}_{0:N}) = p(\mathbf{x}_0)p_{\epsilon_1}(\mathbf{x}_1|\mathbf{x}_0)\dots p_{\epsilon_2}(\mathbf{x}_i|\mathbf{x}_{i-1})\dots p_{\epsilon_N}(\mathbf{x}_N|\mathbf{x}_{N-1}) \quad (12)$$

with the transition kernel $p_{\epsilon_{i+1}}(\mathbf{x}_{i+1}|\mathbf{x}_i) = \mathcal{IG}_{\text{SO(3)}}(\mathbf{x}_{i+1}; \mathbf{x}_i, \epsilon_{i+1})$, where $\epsilon_{i+1} = \epsilon(t_{i+1}) - \epsilon(t_i)$.

The idea of DDPMs is to introduce a reverse Markov process defined in terms of variational transition kernels $p_\theta(\boldsymbol{x}_{i-1}|\boldsymbol{x}_i)$:

$$p_\theta(\mathbf{x}_{0:N}) = p_\theta(\boldsymbol{x}_N)p_\theta(\mathbf{x}_{N-1}|\mathbf{x}_N)\dots p_\theta(\mathbf{x}_{i-1}|\mathbf{x}_i)\dots p_\theta(\mathbf{x}_0|\mathbf{x}_1). \quad (13)$$

While one could choose any distribution on SO(3) to parameterize this inverse transition kernel (e.g., Matrix Fisher, Bingham), we adopt for convenience an Isotropic Gaussian on SO(3) and use the following expression:

$$p_\theta(\boldsymbol{x}_{i-1}|\boldsymbol{x}_i) = \mathcal{IG}_{\text{SO(3)}}(\boldsymbol{x}_{i-1}; \exp(\boldsymbol{\mu}_\theta(\boldsymbol{x}_i, t_i)), \epsilon_\theta(\boldsymbol{x}_i, t_i)) \quad (14)$$

where $\boldsymbol{\mu}_\theta : \text{SO(3)} \times \mathbb{R}^+ \to \mathbb{R}^3$ is a neural network predicting the mean rotation (in axis-angle parameterization) and $\epsilon_\theta : \text{SO(3)} \times \mathbb{R}^+ \to \mathbb{R}^+$ is a neural network predicting the variance of this reverse kernel.

If the reverse Markov process can be successfully trained to match the forward process, it provides a direct sampling strategy to generate samples from p_0 by initializing the chain from p_T and iteratively sampling from the reverse kernel $p_\theta(\boldsymbol{x}_{i-1}|\boldsymbol{x}_i)$.

In DDPMs, the training strategy is to write down the Evidence Lower Bound (ELBO), given this variational approximation for the reverse Markov process, in order to train the individual transition kernels $p_\theta(\mathbf{x}_{i-1}|\mathbf{x}_i)$. To reduce the variance of this loss over a naive evaluation of the ELBO, Sohl-Dickstein et al. (2015) and Ho et al. (2020) propose to use a closed form expression of the reverse kernel $p(\mathbf{x}_{i-1}|\mathbf{x}_i, \mathbf{x}_0)$ when conditioned on $\mathbf{x}_0$. This makes it possible to rewrite the ELBO in terms of analytic KL divergences between Gaussian transitions kernels. However, contrary to the Gaussian case of Euclidean DDPMs, for $\mathcal{IG}_{\text{SO(3)}}$ we do not easily have access to a closed form expression of the reverse kernel $p(x_{t-1}|x_t, x_0)$ which is needed to derive the training loss used in Ho et al. (2020). The same approach cannot be applied.

Instead, we consider the expression for the ELBO:

$$\mathbb{E}\left[-\log p_\theta(\mathbf{x}_0)\right] \leq \mathbb{E}_p\left[-\log p(\mathbf{x}_N) - \sum_{i \geq 1} \log \frac{p_\theta(\mathbf{x}_{i-1}|\mathbf{x}_i)}{p(\mathbf{x}_i|\mathbf{x}_{i-1})}\right] =: \mathcal{L}_{\text{ELBO}} \quad (15)$$

which will be optimized by maximizing the log likelihood of individual transition kernels $\log p_\theta(\mathbf{x}_{i-1}|\mathbf{x}_i)$ over samples $\mathbf{x}_{i-1}, \mathbf{x}_i$ obtained through simulating the forward Markov diffusion process over the training set. Our strategy on SO(3), is therefore to train each transition kernel by maximum likelihood using the following loss function:

$$\mathcal{L}_{DDPM} := \sum_{i \geq 0} \mathbb{E}_{p_{\text{data}}(\mathbf{x}_0)}\mathbb{E}_{p_\epsilon(\mathbf{x}_i|\mathbf{x}_0)}\mathbb{E}_{p_{\epsilon_i}(\mathbf{x}_{i+1}|\mathbf{x}_i)}\left[-\log p_\theta(\mathbf{x}_i|\mathbf{x}_{i+1})\right] \quad (16)$$

where the log probability of the $\mathcal{IG}_{\text{SO(3)}}$ distribution used in our parameterised reverse kernel is defined in Equation 6. While this loss can indeed be used to train a DDPM (as demonstrated in the next section), compared to the strategy of Ho et al. (2020), we expect it to suffer from larger variance and is not explicitly parameterised in terms of the score function (Song et al., 2021).

Once trained, we use the sampling strategy described in Algorithm 2 to draw from the generative model.

Algorithm 2 Sampling from Denoising Diffusion Probabilistic Model on SO(3)

Require: Trained neural networks $\mu_\theta(\mathbf{x}, t), \epsilon_\theta(\mathbf{x}, t)$, number of steps N, time steps $\{t_i\}_{i=0}^N$
1: $\mathbf{x}_N \sim \mathcal{U}_{\text{SO(3)}}$
2: **for** $i = \{N, N-1, \ldots, 1\}$ **do**
3: $\quad \mathbf{x}_{i-1} \sim p_\theta(\cdot; \mathbf{x}_i) = \mathcal{IG}_{\text{SO(3)}}(\cdot; \exp(\mu_\theta(\mathbf{x}_i, t_i)), \epsilon_\theta(\mathbf{x}_i, t_i))$
4: **end for**
5: **return** $\{\mathbf{x}_n\}_{n=0}^N$

---

5 RELATED WORK

Most related to our work is Song et al. (2021) which introduces the diffusion framework we use in this paper, and served as a point of reference throughout. We survey below related works that have developed methodologies to represent distributions on SO(3).

Directional statistics The classical approach for modeling distributions on SO(3) relies on (mixtures) of analytic distributions defined over the group of rotations. Common examples of using such distributions for modeling uncertainties over orientations include the Bingham distribution (Peretroukhin et al., 2020; Srivatsan et al., 2018a; Gilitschenski et al., 2020) or the matrix Fisher distribution (Mohlin et al., 2020). The two main issues of these approaches are the lack of flexibility/expressivity of these analytic distributions, and the general difficulty of computing their normalization constant, which is typically required to train these models by maximum likelihood.

Normalizing Flows A number of approach have been proposed to build density estimators on manifolds (which include SO(3)) based on Normalizing Flows. A first class of methods proposes to use a conventional Euclidean Normalizing Flow in $\mathbb{R}^n$, which is then mapped to the target manifold using an invertible mapping (Gemici et al., 2016; Falorsi et al., 2019). This has some limitations however as the target manifold needs to be homeomorphic to $\mathbb{R}^n$ (which is the case for SO(3)), and this mapping can also present discontinuities. As an improvement over this approach, a second class of methods based on continuous normalizing flows (Chen et al., 2018) has emerged, defining directly flows on the manifold (Falorsi & Forré, 2020; Mathieu & Nickel, 2020). These approaches remain relatively costly as training requires backpropagating through an ODE solver. Rozen et al. (2021) proposes to sidestep that issue by training the CNF through penalizing the divergence of the neural network. And finally, in recent work (Ben-Hamu et al., 2022) proposes to train a flow on manifolds by penalizing a Probability Path Divergence (PPD).

Diffusion models In concurrent work, Leach et al. (2022) proposed an implementation of DDPMs on SO(3) by direct analogy with Ho et al. (2020), based on the Isotropic Gaussian on SO(3) as a replacement for the Normal distribution in $\mathbb{R}^n$. However, as mentioned in the previous section, the loss function used in Euclidan DDPMs does not directly translate to SO(3), which leads to imperfect density estimation as we will illustrate in our experiments. Finally, De Bortoli et al. (2022); Huang et al. (2022); Thornton et al. (2022) introduce generic frameworks for diffusion models on Riemannian manifolds but only for Score-Based Generative Model (SGM). Their generic approach means they do not benefit from the knowledge of a solution to the heat equation in SO(3), which we use extensively in our work to avoid the need to simulate SDEs and to efficiently generate samples from the forward diffusion process. In addition, we note that the method developed in Huang et al. (2022) is not particularly efficient on the orthogonal group as it requires a projection operation, which involves a singular value decomposition.

Other approaches Murphy et al. (2021) develops a non-parametric representation of distributions on SO(3) by introducing a neural network to implicitly represent an unnormalized density on SO(3). Training this model by maximum likelihood requires computing the normalization constant of this implicit probability density function through brute-force evaluation on a tiling of SO(3), which is very costly in memory and limits the effective resolution of the learned densities.

Model	Checkerboard	4-Gaussians	3-Stripes
SGM on SO(3)	**0.50**$\pm$ 0.01	**0.50**$\pm$ 0.01	**0.50**$\pm$ 0.01
DDPM-VExp SO(3)	0.58$\pm$ 0.03	0.62$\pm$ 0.05	0.53$\pm$ 0.01
DDPM-VPres SO(3)	0.59$\pm$ 0.03	0.60$\pm$ 0.03	0.52$\pm$ 0.01
RSGM (De Bortoli et al., 2022)	0.51$\pm$ 0.01	–	0.51 $\pm$ 0.01
Moser Flow(Rozen et al., 2021)	0.56$\pm$ 0.01	0.60$\pm$ 0.02	0.53$\pm$ 0.02
DDPM (Leach et al., 2022)	0.71$\pm$ 0.04	0.90$\pm$ 0.05	0.60$\pm$ 0.03
Implicit-PDF (Murphy et al., 2021)	0.59$\pm$ 0.04	0.81$\pm$ 0.09	0.63$\pm$ 0.04

Table 1: Sample quality metric from the C2ST (lower is better). If the learned distribution is identical to the original one, the metric should be ~ 0.5; if it is significantly different, the metric tends towards ~ 1. The errors on the metric were obtain from the standard deviation of the metric over k-fold cross validation samples for a single training of the model. – indicate a failure to evaluate the metric for a particular model.

6 EXPERIMENTS

We investigate the quality of the generative models described in the previous section on a series of synthetic test densities on SO(3). Details of the training procedures and architectural choices for all models can be found in Appendix A.

Test densities on SO(3) We adopt three different toy distributions on SO(3): a checkerboard pattern, a multi-modal distribution of 4 concentrated Gaussians and a stripe pattern that can be viewed as circles on the sphere.

Metrics We focus on evaluating the generative models in terms of the quality of their sample generation using the Classifier 2-Sample Tests (C2ST) metric (Lopez-Paz & Oquab, 2017; Dalmasso et al., 2020; Lueckmann et al., 2021). The C2ST metric has been used in particular in the context of simulation-based inference to quantify the quality of inferred distributions. Concisely, the C2ST method uses a neural network classifier to discriminate between true and the generated samples, yielding a value of 0.5 if the two distributions are perfectly indistinguishable to the classifier, up to a value of 1 if they are extremely different. In contrast to the usual Negative Log Likelihood (NLL), C2ST can be consistently computed for all generative models we compare bellow.

We present in Figure 3 and Table 1 the results of our (SGM, DDPM-VExp, DDPM-VPres) comparisons on these test densities against the implicit-pdf method of Murphy et al. (2021), the DDPM implementation of Leach et al. (2022), Moser flow of Rozen et al. (2021), and the Riemannian Score-Based Generative Model (RSGM) of De Bortoli et al. (2022) (trained under their $\ell_{t|0}$ score matching loss).

We find that in all cases our SGM implementation on SO(3) yields the best C2ST metric, which is in line with the visual quality of distributions shown in Figure 3.

Our DDPM implementation on SO(3) yields distributions that are comparatively less sharp, which we attribute to the larger variance of our training loss for that model. Compared to other models, our experiments illustrate a failure mode in the method of Leach et al. (2022) which we attribute to the fact that the usual DDPM loss function cannot be directly translated to SO(3) (as discussed in subsection 4.2). We also note that the Implicit-PDF model, in comparison, is extremely limited in resolution because of the memory cost of evaluating the pdf on a tiling of SO(3), and thus yields much lower scores. The best results after our method are achieved by the RSGM model (De Bortoli et al., 2022), which is expected due to its similarity with our work, but is slower to train and sample from in the specific case of SO(3).

7 CONCLUSIONS AND DISCUSSION

In this paper, we have presented a framework for score-based diffusion generative models on SO(3), as an extension of Euclidean SDE-based models (Song et al., 2021). Because it is developed specifically for the SO(3) manifold, our work proposes a simpler and more efficient alternative to other

Figure 3: Density plot comparing samples from learned synthetic densities on SO(3). For visualization this density plot shows the distribution of canonical axes of sampled rotations projected on the sphere; the tilt around that axis is discarded.

recent (and general) Riemannian diffusion models while reaching state-of-the-art quality on synthetic distributions on SO(3).

One of the most promising applications of this work is in robotics and computer vision, for the general task of pose-estimation, where our proposed model significantly outperforms current baselines (Murphy et al., 2021). In the natural sciences, generative models on SO(3) are also of great interest and can be used for instance to find the angle of a molecule that minimizes the binding energy. Finally we note that as an interesting extension of the models presented in this work, one could define a Schrödinger bridge approach (De Bortoli et al., 2021; Thornton et al., 2022) specifically for SO(3), which would improve both sampling efficiency and sample quality.

REFERENCES

Heli Ben-Hamu, Samuel Cohen, Joey Bose, Brandon Amos, Maximillian Nickel, Aditya Grover, Ricky T. Q. Chen, and Yaron Lipman. Matching normalizing flows and probability paths on manifolds. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 1749–1763. PMLR, 17–23 Jul 2022. URL https://proceedings.mlr.press/v162/ben-hamu22a.html.

Johann Brehmer and Kyle Cranmer. Flows for simultaneous manifold learning and density estimation. In *Proceedings of the 34th International Conference on Neural Information Processing Systems*, NIPS'20, Red Hook, NY, USA, 2020. Curran Associates Inc. ISBN 9781713829546.

Nicola De Cao and Wilker Aziz. The power spherical distribution. *ArXiv*, abs/2006.04437, 2020.

Ricky T. Q. Chen, Yulia Rubanova, Jesse Bettencourt, and David K Duvenaud. Neural Ordinary Differential Equations. In *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018. URL https://proceedings.neurips.cc/paper/2018/hash/69386f6bb1dfed68692a24c8686939b9-Abstract.html.

Sean Craven, Djuna Croon, Daniel Cutting, and Rachel Houtz. Machine learning a manifold. *Phys. Rev. D*, 105:096030, May 2022. doi: 10.1103/PhysRevD.105.096030. URL https://link.aps.org/doi/10.1103/PhysRevD.105.096030.

Niccolo Dalmasso, Ann Lee, Rafael Izbicki, Taylor Pospisil, Ilmun Kim, and Chieh-An Lin. Validation of approximate likelihood and emulator models for computationally intensive simulations. In Silvia Chiappa and Roberto Calandra (eds.), *Proceedings of the Twenty Third International Conference on Artificial Intelligence and Statistics*, volume 108 of *Proceedings of Machine Learning Research*, pp. 3349–3361. PMLR, 26–28 Aug 2020. URL https://proceedings.mlr.press/v108/dalmasso20a.html.

Valentin De Bortoli, James Thornton, Jeremy Heng, and Arnaud Doucet. Diffusion Schr\"odinger Bridge with Applications to Score-Based Generative Modeling, December 2021. URL http://arxiv.org/abs/2106.01357. arXiv:2106.01357 [cs, math, stat].

Valentin De Bortoli, Emile Mathieu, Michael Hutchinson, James Thornton, Yee Whye Teh, and Arnaud Doucet. Riemannian Score-Based Generative Modeling, May 2022. URL http://arxiv.org/abs/2202.02763. arXiv:2202.02763 [cs, math, stat].

Luca Falorsi and Patrick Forré. Neural Ordinary Differential Equations on Manifolds, June 2020. URL http://arxiv.org/abs/2006.06663. arXiv:2006.06663 [cs, stat].

Luca Falorsi, Pim de Haan, Tim R. Davidson, and Patrick Forré. Reparameterizing Distributions on Lie Groups, March 2019. URL http://arxiv.org/abs/1903.02958. arXiv:1903.02958 [cs, math, stat].

Wendelin Feiten, Muriel Lang, and Sandra Hirche. Rigid motion estimation using mixtures of projected gaussians. In *Proceedings of the 16th International Conference on Information Fusion*, pp. 1465–1472, 2013.

M. E. Gaddes, A. Hooper, and M. Bagnardi. Using machine learning to automatically detect volcanic unrest in a time series of interferograms. *Journal of Geophysical Research: Solid Earth*, 124(11): 12304–12322, 2019. doi: https://doi.org/10.1029/2019JB017519. URL https://agupubs.onlinelibrary.wiley.com/doi/abs/10.1029/2019JB017519.

Mevlana C. Gemici, Danilo Rezende, and Shakir Mohamed. Normalizing Flows on Riemannian Manifolds, November 2016. URL http://arxiv.org/abs/1611.02304. arXiv:1611.02304 [cs, math, stat].

Igor Gilitschenski, Roshni Sahoo, Wilko Schwarting, Alexander Amini, Sertac Karaman, and Daniela Rus. Deep orientation uncertainty learning based on a bingham loss. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=ryloogSKDS.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In Z. Ghahramani, M. Welling, C. Cortes, N. Lawrence, and K.Q. Weinberger (eds.), *Advances in Neural Information Processing Systems*, volume 27. Curran Associates, Inc., 2014. URL `https://proceedings.neurips.cc/paper/2014/file/5ca3e9b122f61f8f06494c97b1afccf3-Paper.pdf`.

A. Grigoryan. *Heat Kernel and Analysis on Manifolds*. AMS/IP studies in advanced mathematics. American Mathematical Society, 2009. ISBN 9780821849354. URL `https://books.google.com/books?id=R8aFAwAAQBAJ`.

Richard I. Hartley, Jochen Trumpf, Yuchao Dai, and Hongdong Li. Rotation averaging. *International Journal of Computer Vision*, 103(3):267–305, 2013. URL `https://doi.org/10.1007/s11263-012-0601-0`.

Shoubaneh Hemmati, Peter Capak, Milad Pourrahmani, Hooshang Nayyeri, Daniel Stern, Bahram Mobasher, Behnam Darvish, Iary Davidzon, Olivier Ilbert, Daniel Masters, and Abtin Shahidi. Bringing manifold learning and dimensionality reduction to SED fitters. *The Astrophysical Journal*, 881(1):L14, aug 2019. doi: 10.3847/2041-8213/ab3418. URL `https://doi.org/10.3847/2041-8213/ab3418`.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 6840–6851. Curran Associates, Inc., 2020. URL `https://proceedings.neurips.cc/paper/2020/file/4c5bcfec8584af0d967f1ab10179ca4b-Paper.pdf`.

Sabera Hoque, Md. Yasir Arafat, Shuxiang Xu, Ananda Maiti, and Yuchen Wei. A comprehensive review on 3d object detection and 6d pose estimation with deep learning. *IEEE Access*, 9:143746–143770, 2021. doi: 10.1109/ACCESS.2021.3114399.

Chin-Wei Huang, Milad Aghajohari, Avishek Joey Bose, Prakash Panangaden, and Aaron Courville. Riemannian Diffusion Models, August 2022. URL `http://arxiv.org/abs/2208.07949`. arXiv:2208.07949 [cs].

Arieh Iserles, Hans Z. Munthe-Kaas, Syvert P. Nørsett, and Antonella Zanna. Lie-group methods. *Acta Numerica*, 9:215–365, 2000. doi: 10.1017/S0962492900002154.

Diederik P Kingma and Max Welling. Auto-Encoding Variational Bayes. *arXiv e-prints*, art. arXiv:1312.6114, December 2013.

Adam Leach, Sebastian M Schmon, Matteo T Degiacomi, and Chris G Willcocks. Denoising diffusion probabilistic models on so (3) for rotational alignment. In *ICLR 2022 Workshop on Geometrical and Topological Representation Learning*, 2022.

David Lopez-Paz and Maxime Oquab. Revisiting classifier two-sample tests. In *International Conference on Learning Representations*, 2017. URL `https://openreview.net/forum?id=SJkXfE5xx`.

Jan-Matthis Lueckmann, Jan Boelts, David S. Greenberg, Pedro J. Gonçalves, and Jakob H. Macke. Benchmarking simulation-based inference. In *AISTATS*, pp. 343–351, 2021. URL `http://proceedings.mlr.press/v130/lueckmann21a.html`.

Elman Mansimov, Omar Mahmood, Seokho Kang, and Kyunghyun Cho. Molecular geometry prediction using a deep generative graph neural network. *Scientific Reports*, 9, 2019.

Emile Mathieu and Maximilian Nickel. Riemannian Continuous Normalizing Flows, December 2020. URL `http://arxiv.org/abs/2006.10605`. arXiv:2006.10605 [cs, stat].

Siegfried Matthies, J. Muller, and G. W. Vinel. On the normal distribution in the orientation space. *Textures and Microstructures*, 10:77–96, 1988.

D. Mohlin, G. Bianchi, and J. Sullivan. Probabilistic orientation estimation with matrix Fisher distributions, June 2020. URL http://arxiv.org/abs/2006.09740. arXiv:2006.09740 [cs].

Kieran A Murphy, Carlos Esteves, Varun Jampani, Srikumar Ramalingam, and Ameesh Makadia. Implicit-pdf: Non-parametric representation of probability distributions on the rotation manifold. In *International Conference on Machine Learning*, pp. 7882–7893. PMLR, 2021.

Dmitry I Nikolayev and Tatjana I Savyolov. Normal distribution on the rotation group so (3). *Textures and Microstructures*, 29, 1970.

Valentin Peretroukhin, Matthew Giamou, W. Nicholas Greene, David Rosen, Jonathan Kelly, and Nicholas Roy. A Smooth Representation of Belief over SO(3) for Deep Rotation Learning with Uncertainty. In *Proceedings of Robotics: Science and Systems*, Corvalis, Oregon, USA, July 2020. doi: 10.15607/RSS.2020.XVI.007.

Danilo Rezende and Shakir Mohamed. Variational inference with normalizing flows. In Francis Bach and David Blei (eds.), *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pp. 1530–1538, Lille, France, 07–09 Jul 2015. PMLR. URL https://proceedings.mlr.press/v37/rezende15.html.

Noam Rozen, Aditya Grover, Maximilian Nickel, and Yaron Lipman. Moser Flow: Divergence-based Generative Modeling on Manifolds, November 2021. URL http://arxiv.org/abs/2108.08052. arXiv:2108.08052 [cs, stat].

Hyunwoo Ryu, Jeong-Hoon Lee, Hong-in Lee, and Jongeun Choi. Equivariant Descriptor Fields: SE(3)-Equivariant Energy-Based Models for End-to-End Visual Robotic Manipulation Learning, June 2022. URL http://arxiv.org/abs/2206.08321. arXiv:2206.08321 [cs].

Jascha Sohl-Dickstein, Eric Weiss, Niru Maheswaranathan, and Surya Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics. In Francis Bach and David Blei (eds.), *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pp. 2256–2265, Lille, France, 07–09 Jul 2015. PMLR. URL https://proceedings.mlr.press/v37/sohl-dickstein15.html.

Yang Song and Stefano Ermon. Generative modeling by estimating gradients of the data distribution. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/3001ef257407d5a371a96dcd947c7d93-Paper.pdf.

Yang Song and Stefano Ermon. Improved Techniques for Training Score-Based Generative Models, October 2020. URL http://arxiv.org/abs/2006.09011. arXiv:2006.09011 [cs, stat].

Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=PxTIG12RRHS.

Rangaprasad Arun Srivatsan, Mengyun Xu, Nicolas Zevallos, and Howie Choset. Probabilistic pose estimation using a bingham distribution-based linear filter. *The International Journal of Robotics Research*, 37(13-14):1610–1631, 2018a. doi: 10.1177/0278364918778353. URL https://doi.org/10.1177/0278364918778353.

Rangaprasad Arun Srivatsan, Mengyun Xu, Nicolas Zevallos, and Howie Choset. Probabilistic pose estimation using a bingham distribution-based linear filter. *The International Journal of Robotics Research*, 37(13-14):1610–1631, 2018b. doi: 10.1177/0278364918778353. URL https://doi.org/10.1177/0278364918778353.

James Thornton, Michael Hutchinson, Emile Mathieu, Valentin De Bortoli, Yee Whye Teh, and Arnaud Doucet. Riemannian Diffusion Schr\"odinger Bridge, July 2022. URL http://arxiv.org/abs/2207.03024. arXiv:2207.03024 [cs, stat].

Richard von Mises. Uber die 'ganzzahligkeit' der atomgewicht und verwandte fragen. *Physikal. Z.*, 19:490–500, 1918.

Nathan Zelesko, Amit Moscovich, Joe Kileel, and Amit Singer. Earthmover-based manifold learning for analyzing molecular conformation spaces. In *2020 IEEE 17th International Symposium on Biomedical Imaging (ISBI)*, pp. 1715–1719, 2020. doi: 10.1109/ISBI45749.2020.9098723.

A Implementation and Training

We designed our neural networks with a size of $\{256,256,256,256,256\}$ neurons each with leaky ReLU activation and with a residual connection. The neural networks were implemented using the axis-angle representation of SO(3), i.e. the input and output elements were represented using axis-angle representation. Additionally, the neural networks were conditioned on the noise scheduler and the noise scales were also learned parameters. We trained our models using the Adam optimizer with learning rate of 10^{-4}, exponential decay rates of $\beta_1 = 0.90$ and $\beta_2 = 0.95$, 400 000 iterations, and a batch size of 1024. NVIDIA Tesla V100 GPU was used as the hardware, with JAX and DeepMind-Haiku Python libraries as the software.

For the choice of noising schedules, we used $\epsilon_{\min} = 0.001$ and $\epsilon_{\max} = 0.7$ for the variance exploding case, and $\epsilon_{\min} = 0.001$ and $\epsilon_{\max} = 1$ for the variance preserving case.

B Representations of and distributions on SO(3)

B.1 Representations of SO(3)

The special orthogonal group, SO(3), is the Lie group of all rotations about the origin in 3-dimensional space. There are several ways to represent the elements of the group SO(3), each with its advantages and disadvantages:

- Rotation Matrices $\in \mathbb{R}^{3\times 3}$ with determinant equal to 1. This representation has 9 parameters and can be subject to some numerical stabilities, such as when computing the inverse or trigonometric functions.

- Euler angles (also called *yaw, pitch, and roll* in robotics) are three angles α, β, ψ that can describe an orientation with respect to a fixed coordinate system. This representation is subject to the infamous Gimbal lock, where one degree of freedom is lost when two axes of the gimbal become parallel.

- Unit Quaternions defined as $\gamma = a + b\mathbf{i} + c\mathbf{j} + d\mathbf{k}$, where a, b, c, d are real number satisfying $\sqrt{a^2 + b^2 + c^2 + d^2} = 1$ with $\mathbf{i} + \mathbf{j} + \mathbf{k}$ denoting the vector (or imaginary) part of the unit quaternion. This representation has 4 parameters and has elegant operations (Hamilton product) without trigonometric functions B.2. However, quaternions are antipodally symmetric which introduces some degeneracies.

- Axis - angle representation (normalized), Tangent space (unnormalized) defined as $\theta = \theta\mathbf{e} = (\theta_1, \theta_2, \theta_3) = \theta(e_1, e_2, e_3)$, where θ is the rotation angle and $\mathbf{e}$ is the rotation axis. However, this representation does not have well defined operations to combine rotations.

Therefore, in practice it is best to use some combinations of the aforementioned representations and convert back and forth among them. In our experience, we found it is best to work with quaternions when performing operations on SO(3) and best to work with axis-angle when representing lements of SO(3). For comprehensive review on SO(3) representations and metrics, especially for computer scientists, please refer to (Hartley et al., 2013).

B.2 Quaternion operations for SO(3)

Quaternions form a group under multiplication, defined by the Hamilton product. Given quternions γ_1 and γ_2, the Hamilton product is defined by carrying out the $\gamma_1 \cdot \gamma_2 = (a_1 + b_1\mathbf{i} + c_1\mathbf{j} + d_1\mathbf{k}) \cdot (a_2 + b_2\mathbf{i} + c_2\mathbf{j} + d_2\mathbf{k})$ in a distributive manner, keeping in mind the basis multiplication identities. This operation is physically equivalent to rotating by γ_1 and then by γ_2. The identity of the group

is the quaternion $\gamma_0 = 1 + 0\mathbf{i} + 0\mathbf{j} + 0\mathbf{k}$ and the inverse of $\gamma*$ (also conjugate) is defined as $\gamma* = a - b\mathbf{i} - c\mathbf{j} - d\mathbf{k}$.

The reparametrization trick and variance preserving quaternions   In Euclidean space for a Gaussian random variable $\mathbf{x}$ from $\mathcal{N}(\mu; \sigma^2 \mathbf{I})$, the reparametrization trick is defined as $\mathbf{x} = \mu + \sigma^2 \cdot \delta$ where $\delta \sim \mathcal{N}(0; \mathbf{I})$. We can define a analogous operation in the quaternion group, as such:

$$\gamma = \theta \cdot \epsilon^\delta \tag{17}$$

Here, the quternion raised to some scalar power is defined as the $\gamma^a = \exp(\ln(\gamma)a)$, in other words we take the quaternion to the tangent space from the manifold, perform the operation of multiplication and bring it back into the manifold by using the exponential map. and the variance preserving operation analogous to $\sqrt{\alpha} \cdot \mathbf{x} + \sqrt{(1 - \alpha)}\delta$ can be defined as

$$\mathbf{x} = \mathbf{x}^{\sqrt{\alpha}} \cdot \delta^{\sqrt{(1-\alpha)}} \tag{18}$$

For the variance exploding case, we can directly sample from the heat kernel without resorting to the quaternion operations.

B.3   DISTRIBUTIONS ON SO(3)

In literature there are numerous ways to represent distributions on the hypersphere. Most of them involve taking a standard distribution from the Euclidian space $\mathcal{R}^n$ and then constraining or projecting them on to the hypersphere $\mathcal{S}^n$. Some of the popular distributions are:

- *Projected Gaussian(s)* on the sphere where standard Gaussian(s) on the tangent space of the hypersphere are projected via central projection, as done in Feiten et al. (2013);

- the *von Mises-Fisher* (vMF) distribution where an isotropic Gaussian on R^n is restricted to the unit hypersphere von Mises (1918);

- The recently developed *Power Spherical* distribution Cao & Aziz (2020), which addresses some of the challenges of the vMF distribution, such as numerical stability and scalability.

- The antipodally symmetric *Bingham* distribution. The antipodal symmetry makes it a suitable distribution to represent quaternions, since quaternions double cover the space of rotations on SO(3) Gilitschenski et al. (2020); Peretroukhin et al. (2020); Srivatsan et al. (2018b;a). However, the Bingham distribution is notorious for its normalization constant that is very hard to compute.

Unfortunately, these distributions are not closed under convolution (i.e. composition of their random variables), thus writing down an closed form diffusion process akin to the Euclidean Gaussian case is intractable. One way to circumvent this problem is to use class of functions that are closed under convolutions on the manifold. An obvious choice is the heat kernel which is the canonical solution to the diffusion equation and is closed under convolutions by definition (Grigoryan, 2009).