Stochastic Multi-Armed Bandits with Control Variates

Abstract

This paper studies a new variant of the stochastic multi-armed bandits problem where auxiliary information about the arm rewards is available in the form of control variates. In many applications like queuing and wireless networks, arm rewards are functions of some exogenous values, whose mean value is known a priori from historical data and can be used as control variates. Leveraging the theory of control variates, we obtain mean estimates with smaller variance and tighter confidence bounds and develop an improved upper confidence bound based algorithm named UCB-CV. We characterize the regret bounds in terms of the correlation between rewards and control variates when they have a multivariate normal distribution. We experimentally validate the performance of UCB-CV on the normal distribution and other distributions.

1 Introduction

Stochastic Multi-Armed Bandits (MAB) setting has been extensively used to study decision making under uncertainty (Thompson, 1933; Bubeck et al., 2012; Lattimore and Szepesvári, 2020). In the classical setting, it is assumed that the arms rewards are independent of each other, and by playing an arm, the learner observers independent and identically distributed reward samples. Explore versus exploit trade-off is a fundamental problem in the bandits setting, and a learner can accumulate more rewards if it is balanced well. A better balance can be achieved if the leaner can estimate arm's mean rewards with tighter confidence bounds (Auer et al., 2002; Garivier and Cappé, 2011) and smaller variance (Audibert et al., 2009b; Mukherjee et al., 2018). Any available side/auxiliary information can aid in building tighter confidence bounds. In this paper, we study the improvement in the performance that can be achieved when side information is available in the form of control variates.

Any observable input that is correlated with the random variable of interest can be a Control Variate (CV). When the mean of the CV is known, it is useful to reduce the variance of the mean estimator of the random variable. CV method is a popular variance reduction technique to improve the estimates' precision without altering the simulation runs or an increase in the number of samples (Lavenberg et al., 1982; Nelson, 1990). Many stochastic simulations involve inputs generated using known distributions. These inputs can be potential CVs as output could be correlated with them. This has motivated the development of rich theory to analyzes the quality of the estimators resulting from CVs (Lavenberg et al., 1982; Lavenberg and Welch, 1981; Nelson, 1989, 1990). We aim to adopt these techniques to study the stochastic multi-armed bandits problem when CVs are available for the arms.

In many real-life applications, exogenous variables influence arms' rewards and act as CVs. For example, consider a job aggregating platform that assigns jobs to one of the servers/workers in each slot. The jobs are of variable size, and the time to serve them depends on their size and other unknown extraneous factors. The platform observes the size of each job and knows their mean value from historical data. The random job sizes are correlated with service times and can be used as a CV in

estimating each server's mean service time. Another example is a wireless system where a transmitter can transmit packets on a channel in each slot. Successful transmission of the packets (quality) depends on random quantities like fading, interference, and channel noise on the selected channel. The transmitter can observe the fading value using pilot signals in each round and know their mean value from past observations. These fading values on a channel can be used as a CV to estimate the channel's quality.

The performance of a MAB algorithm depends on how good is the confidence interval of its mean reward estimators (Auer et al., 2002; Garivier and Cappé, 2011). The tightness of these intervals depends on the variance of the estimators (Audibert et al., 2009b; Mukherjee et al., 2018). Naturally, estimators with smaller variance for the same number of samples result in better performance. Thus CVs can be leveraged to improve the performance of bandits algorithms with smaller confidence intervals. The reduction depends on how strongly the reward samples and associated CVs are correlated.

Linear methods are widely used for variance reduction using CVs where the new samples are generated taking the weighted sum of reward samples and centered CV. These new samples are then used for the estimation of the mean rewards. The choice of the weight that results in maximum variance reduction depends on the variance of CV and its correlation with reward samples. In practice, both of these quantities are unknown and need to be estimated from the observed samples. However, using the estimated weight makes the new samples highly correlated and making the analysis of confidence intervals challenging.

For multivariate normal distributions, tight confidence intervals can be constructed, which hold with high probability for the estimators resulting from the linear control variates. Using these results, we develop a bandits algorithm that exploits CVs to improve the regret performance. For general distributions, we discuss statistical methods that result in unbiased estimators with better confidence intervals. Specifically, our contributions are as follows:

- For the case where rewards and CVs are normally distributed, we develop an algorithm named Upper Confidence Bounds with Control Variates (UCB-CV) that uses the estimators based on the linear control variates.

- In Section 4, we show that the regret of UCB-CV is smaller by a factor $(1 - \rho^2)$ compare to the existing algorithms when the rewards and CV have a multivariate normal distribution, where ρ is the correlation coefficient of the reward and control variates.

- In Section 5, we discuss how to adapt UCB-CV for the general distributions using estimators and associated confidence intervals based on jackknifing, splitting, and batching methods.

- We validate the performance of UCB-CV on synthetically generated data in Section 6.

1.1 Related Work

Our work uses side/auxiliary information available in the form of CVs to improve the variance of estimates. In the following, we discuss works that incorporate variance estimates and/or side information to improve the performance of multi-armed bandits algorithms.

Incorporating variance estimates: Many stochastic multi-armed bandits algorithms like UCB1 (Auer et al., 2002), DMED (Honda and Takemura, 2010), KL-UCB (Garivier and Cappé, 2011), Thompson Sampling (Chapelle and Li, 2011; Agrawal and Goyal, 2012; Kaufmann et al., 2012; Agrawal and Goyal, 2013), assume that the rewards are bounded on some interval $[0, b]$ and define index of each arm based on its estimates of the mean rewards and ignore the variance estimates. The regret of these algorithms have optimal logarithmic bound in the number of rounds (T), and grows quadratic in b, i.e., $\mathcal{O}((b^2/\Delta) \log T)$, where Δ is the smallest sub-optimality gap. UCB1-NORMAL by (Auer et al., 2002) uses the variance estimates in the index of the arms and when rewards are Gaussian with variance σ^2, to achieve regret is of order $\mathcal{O}((\sigma^2/\Delta) \log T)$. This bound is even better than that of UCB1 when the variance is smaller than b^2 though it is considered unbounded support. Further, the authors experimentally demonstrate that the UCB-Tuned algorithm (Auer et al., 2002), which uses variance estimates in arm indices, significantly improves regret performance over UCB1 when rewards are bounded. Extending the idea of using 'variance aware' indices, UCBV (Audibert et al., 2009a) algorithm achieves regret of order $\mathcal{O}((\sigma^2/\Delta + 2b) \log T)$ thus confirming that making algorithms variance aware is beneficial. EUCBV (Mukherjee et al., 2018) improves the performance of UCBV using an arm elimination strategy like used in UCB-Improved (Auer and Ortner, 2010).

Incorporating side information: In the applications like advertising and web search, whether or not users like a displayed item could depend on their profile. Users' profile is often available to the platform, which could then used as side information. Contextual bandits (Dani et al., 2008; Rusmevichientong and Tsitsiklis, 2010; Li et al., 2010; Abbasi-Yadkori et al., 2011; Li et al., 2010; Chu et al., 2011; Filippi et al., 2010; Li et al., 2017; Jun et al., 2017; Zhang et al., 2016) exploit such side information to learn the optimal arm. They assume a correlation structure (linearity, GLM, etc.) between mean reward and context where mean reward varies with side-information (context).

In contrast to contextual bandits, mean rewards do not vary in our unstructured setup with side information available in the form of CVs. We do not use CVs directly to decide which arm to select in each round but use them only to get better estimates of the mean rewards by exploiting their correlation with rewards. Our motivating examples from jobs scheduling and communication networks capture these unstructured bandits where CVs provide information about the rewards but do not alter their mean values.

Also, our confidence bounds for the mean estimators are based on the variance of estimators rather than on the variance of the reward sample, as was the case in UCBV (Audibert et al., 2009a) and EUCBV (Mukherjee et al., 2018). The samples we use to estimate mean rewards are not independent and identically distributed. Hence, we can not use the standard Bernstein inequality to get confidence bounds on mean and variance estimates.

CVs for variance reduction (James, 1985; Botev and Ridder, 2014; Chen and Ghahramani, 2016; Kreutzer et al., 2017; Vlassis et al., 2019) are used extensively in Monte-Carlo simulation of complex systems (Lavenberg and Welch, 1981; Lavenberg et al., 1982; Nelson, 1989, 1990). To the best of our knowledge, our work is the first to analyze the performance of stochastic bandits algorithms with control variates.

2 Control Variate for Variance Reduction

Let μ be the unknown quantity that needs to be estimated, and X be an unbiased estimator of μ, i.e., $\mathbb{E}[X] = \mu$. A random variable W is a CV if its expectation ω is known and it is correlated with X. Linear control methods use errors in estimates of known random variables to reduce error in estimation of unknown random variable. For any choice of a coefficient β, define a new estimator as $\bar{X} = X + \beta(\omega - W)$. It is straightforward to verify that its variance is given by

$$\text{Var}(\bar{X}) = \text{Var}(X) + \beta^2 \text{Var}(W) - 2\beta \text{Cov}(X, W). \tag{1}$$

and is minimized by setting β to

$$\beta^\star = \frac{\text{Cov}(X, W)}{\text{Var}(W)}. \tag{2}$$

The minimum value of the variance is given by $\text{Var}(\bar{X}) = (1 - \rho^2)\text{Var}(X)$, where ρ is the correlation coefficient of X and W. Larger the correlation, the greater the variance reduction achieved by the CV. In practice, the values of $\text{Cov}(X, W)$ and $\text{Var}(W)$ are unknown and need to be estimated to compute the best approximation for $\beta^\star$.

3 Problem Setting

We consider a stochastic multi-armed bandits problem with K arms. The set of arms is represented by $[K] \doteq \{1, 2, \ldots, K\}$. In round t, the environment generates a vector $(\{X_{t,i}\}_{i \in [K]}, \{W_{t,i}\}_{i \in [K]})$. The random variable $X_{t,i}$ denotes the reward of arm i in round t, and form an Independent and Identically Distributed (IID) sequence drawn from an unknown but fixed distribution with mean μ_i and variance σ_i^2. The random variable $W_{t,i}$ is the Control Variate (CV) associated with the reward of arm i in round t. These random variables are drawn from an unknown but fixed distribution with mean ω_i and variance $\sigma_{w,i}^2$ and form an IID sequence. Learner knows the values $\{\omega_i\}_{i \in [K]}$ but not the $\{\sigma_{w,i}^2\}_{i \in [K]}$. The correlation coefficient between the ith arm's rewards and its associated control variate is denoted by ρ_i.

In our setup, the learner observes the reward and associated CVs from the selected arm. We refer to this new variant of the multi-armed bandits problem as Multi-Armed Bandits with Control Variates (MAB-CV). The parameter vectors $\boldsymbol{\mu^\sigma} = \{\mu_i, \sigma_i^2\}_{i \in [K]}$, $\boldsymbol{\omega^\sigma} = \{\omega_i, \sigma_{w,i}^2\}_{i \in [K]}$, and $\boldsymbol{\rho} = \{\rho_i\}_{i \in [K]}$

138 identify an instance of MAB-CV problem, which we denote henceforth using $P = (\boldsymbol{\mu^\sigma}, \boldsymbol{\omega^\sigma}, \boldsymbol{\rho})$. The
139 collections of all MAB-CV problems are denoted by $\mathcal{P}$. For an instance $P \in \mathcal{P}$, with mean reward
140 vector $\boldsymbol{\mu}$ we denote the optimal arm as $i^\star = \arg\max_{i \in [K]} \mu_i$.

MAB-CV problem with instance $(\boldsymbol{\mu^\sigma}, \boldsymbol{\omega^\sigma}, \boldsymbol{\rho})$

For each round t:

1. **Environment** generates a vector $\boldsymbol{X_t} = (X_{t,1}, \ldots, X_{t,K}) \in \mathbb{R}^K$ and $\boldsymbol{W_t} = (W_{t,1}, \ldots, W_{t,K}) \in \mathbb{R}^K$, where $\mathbb{E}[X_{t,i}] = \mu_i$, $\mathrm{Var}(X_{t,i}) = \sigma_i^2$, $\mathbb{E}[W_{t,i}] = \omega_i$, $\mathrm{Var}(W_{t,i}) = \sigma_{w,i}^2$, and the sequence $(X_{t,i})_{t \geq 1}$ and $(W_{t,i})_{t \geq 1}$ are IID for all $i \in [K]$.

2. **Learner** selects an arm $I_t \in [K]$ based on past observation of rewards and CVs samples from the arms till round $t - 1$.

3. **Feedback and Regret:** The learner observes a random reward X_{t,I_t} and associated CV W_{t,I_t}, and then incurs penalty $(\mu_{i^\star} - \mu_{I_t})$.

---

141 Let I_t denote the arm selected by the learner in round t based on the observation of past reward and
142 control variate samples. The interaction between the environment and a learner is given in MAB-CV
143 problem. We aim to learn policies that accumulate maximum reward and measure its performance
144 by comparing its cumulative reward with that of an Oracle that plays the optimal arm in each round.
145 Specifically, we measure the performance in terms of regret defined as follows

$$\mathfrak{R}_T = T\mu_{i^\star} - \mathbb{E}\left[\sum_{t=1}^{T} X_{t,I_t}\right]. \tag{3}$$

146 Note that maximizing the mean cumulative reward of a policy is the same as minimizing the policy's
147 regret. A good policy should have sub-linear expected regret, i.e., $\mathbb{E}[\mathfrak{R}_T]/T \to 0$ as $T \to \infty$.

148 Our goal is to learn a policy that is sub-linear with small regret. To this effect, we use CVs
149 to estimate mean rewards with sharper confidence bounds so that the learner can have a better
150 exploration-exploitation trade-off and start playing the optimal arm more frequently early.

4 Arms with Normally Distributed Rewards and Control Variates

152 We first focus on the case where the rewards and associated CVs of arms have a multivariate normal
153 distribution. We discuss the general distributions in the next section. To bring out the main ideas of
154 the algorithm, we first consider the case where each arm is associated with only one CV. Motivated
155 by the linear CV technique discussed in the previous section, we consider a new sample for the ith
156 arm in round t as follows:

$$\bar{X}_{t,i} = X_{t,i} + \beta_i^*(\omega_i - W_{t,i}),$$

157 where $X_{t,i}$ is the t^{th} reward, $W_{t,i}$ is the t^{th} associated control variate with arm i, $\omega_i = \mathbb{E}[W_{t,i}]$, and
158 $\beta_i^* = \mathrm{Cov}(X_{t,i}, W_{t,i})/\mathrm{Var}(W_{t,i})$. Using s such samples, the mean reward for the ith arm is defined
159 as $\hat{\mu}_{s,i}^c = (\sum_{r=1}^{s} \bar{X}_{r,i})/s$. Let $\hat{\mu}_{s,i} = \frac{1}{s}\sum_{r=1}^{s} X_{r,i}$ and $\hat{\omega}_{s,i} = \frac{1}{s}\sum_{r=1}^{s} W_{r,i}$ denote the sample
160 mean of reward and CVs of ith arm from s samples. Then $\hat{\mu}_{s,i}^c$ can be written as follows:

$$\hat{\mu}_{s,i}^c = \hat{\mu}_{s,i} + \beta_{s,i}^*(\omega_i - \hat{\omega}_{s,i}). \tag{4}$$

161 Since the value of $\mathrm{Cov}(X_i, W_i)$ and $\mathrm{Var}(W_i)$ are unknown, the optimal coefficient $\beta_{s,i}^\star$ need to be
162 estimated. After having s samples, its estimated calculated as below and used in Eqs. (4).

$$\hat{\beta}_{s,i}^* = \frac{\sum_{r=1}^{s}(X_{r,i} - \hat{\mu}_{s,i})(W_{r,i} - \omega_i)}{\sum_{r=1}^{s}(W_{r,i} - \omega_i)^2}. \tag{5}$$

163 Let $\mathrm{Var}(\bar{X}_i) = \sigma_{c,i}^2$ denote the variance of the linear CV samples and $\nu_{s,i} = \mathrm{Var}(\hat{\mu}_{s,i}^c)$ denote the
164 variance the estimator using these samples. Note that the estimator is computed using the samples
165 $\{\bar{X}_i\}$ which are correlated. When the rewards and CVs have follow multivariate normal distribution,
166 the following result tells how to obtain an unbiased variance estimator of $\hat{\mu}_{s,i}^c$.

Lemma 1. *Let the reward and control variate of each arm have a multivariate normal distribution. After observing s samples of reward and control variate from arm i, define $\hat{\nu}_{s,i} = \frac{Z_s \hat{\sigma}_{c,i}^2(s)}{s}$, where*

$$Z_s = \left(1 - \frac{\left(\sum_{r=1}^{s}(W_r - \bar{\omega})\right)^2}{s \sum_{r=1}^{s}(W_r - \omega)^2}\right)^{-1} \quad and \quad \hat{\sigma}_{c,i}^2(s) = \frac{1}{s-2}\sum_{r=1}^{s}(\bar{X}_r - \hat{\mu}_{s,i}^c)^2,$$

then $\hat{\nu}_{s,i}$ is an unbiased variance estimator of $\hat{\mu}_{s,i}^c$, i.e., $\mathbb{E}[\hat{\nu}_{s,i}] = Var(\hat{\mu}_{s,i}^c)$.

The confidence interval for reward estimator is given by our next result.

Lemma 2. *Let s be the number of rewards and associated control variates samples from arm i in round t. Then*

$$\mathbb{P}\left\{|\hat{\mu}_{s,i}^c - \mu_i| \geq V_{t,s,1}^{(\alpha)}\sqrt{\hat{\nu}_{s,i}}\right\} \leq 2/t^\alpha,$$

where $V_{t,s,1}^{(\alpha)}$ denote $100(1 - 1/t^\alpha)^{th}$ percentile value of the $t-$distribution with $s-2$ degrees of freedom and $\hat{\nu}_{s,i}$ is an unbiased estimator for variance of $\hat{\mu}_{s,i}^c$.

We can prove Lemma 1 and Lemma 2 using regression theory. The detailed proofs are given in Appendix B. The proof uses the fact that the arm's rewards and CVs have a multivariate normal distribution. Therefore, we can use t-distribution for designing confidence intervals of mean reward estimators. Analogous to the Hoeffding inequality, this result shows that the probability of the estimate obtained by samples $\{\bar{X}_{t,i}\}$ deviating from the true mean of arm i decays fast. Further, the deviation factor $V_{t,s,1}^{(\alpha)}\sqrt{\hat{\nu}_{s,i}}$ depends on the variance of the estimator ($\hat{\mu}_{s,i}^c$), which guarantees sharper confidence intervals. As we will see later in Lemma 3, these confidence terms are smaller by a factor $(1 - \rho_i^2)$ compared to the case when no CVs are used. Equipped with these results, we next develop an UCB based algorithm for MAB-CV.

4.1 Algorithm: UCB-CV

Let $N_i(t)$ be the number of times the arm i is selected by learner until round t and $\hat{\nu}_{N_i(t),i}$ be the sample variance of mean reward estimator ($\hat{\mu}_{N_i(t),i}^c$) for arm i. Motivated from Lemma 2, we define optimistic upper bound for estimate of mean reward of arm i as follows:

$$\text{UCB}_{t,i} = \hat{\mu}_{N_i(t),i}^c + V_{t,N_i(t),1}^{(\alpha)}\sqrt{\hat{\nu}_{N_i(t),i}}. \tag{6}$$

The above values as indices of arms, we develop an algorithm named UCB-CV for MAB-CV. The algorithm works as follows: It takes the number of arms K, a constant $Q = 3$ (number of CV per arm $+$ 2), and $\alpha > 1$ (trades-off between exploration and exploitation) as input. Each arm is played Q times to ensure the sample variance for observations ($\hat{\sigma}_{c,i}^2(s)$) are computed (see Lemma 1).

UCB-CV UCB based Algorithm for MAB-CV problem

1: **Input:** K, Q, $\alpha > 1$
2: Play each arm $i \in [K]$ Q times
3: **for** $t = QK+1, QK+2, \ldots,$ **do**
4:    $\forall i \in [K]$: compute $\text{UCB}_{t-1,i}$ as given in Eq. (6)
5:    Select $I_t = \underset{i \in [K]}{\arg\max}\ \text{UCB}_{t-1,i}$
6:    Play arm I_t and observe X_{t,I_t} and associated control variates W_{t,I_t}. Increment the value of $N_{I_t}(t)$ by one and re-estimate $\hat{\beta}_{N_{I_t}(t),I_t}^*$, $\hat{\mu}_{N_{I_t}(t),I_t}^c$ and $\hat{\nu}_{t,N_{I_t}(t)}$
7: **end for**

In round t, UCB-CV computes the upper confidence bound of each arm's mean reward estimate using Eq. (6) and selects the arm having highest upper confidence bound value and this arm is denoted by I_t. After playing arm I_t, the reward X_{t,I_t} and associated control variate W_{t,I_t} are observed. After that, the value of $N_{I_t}(t)$ is updated and $\hat{\beta}_{N_{I_t}(t),I_t}^*$, $\hat{\mu}_{N_{I_t}(t),I_t}^c$ and $\hat{\nu}_{t,N_{I_t}(t)}$ are re-estimated. The same process is repeated for the subsequent rounds.

4.2 Estimator with Multiple Control Variates

In some applications it could be possible that each arm is associated with multiple CVs. We denote the number of CVs with each arm as q. Let $W_{t,i,j}$ be the j^{th} control variate of arm i that is observed in round t, . Then the unbiased mean reward estimator for arm i with associated CVs is given by

$$\hat{\mu}^c_{s,i,q} = \hat{\mu}_{s,i} + \hat{\boldsymbol{\beta}}^{*\top}_i (\boldsymbol{\omega}_i - \hat{\boldsymbol{\omega}}_{s,i}),$$

where $\hat{\boldsymbol{\beta}}^*_i = \left(\hat{\beta}_{i,1}, \ldots, \hat{\beta}_{i,q} \right)^\top$, $\boldsymbol{\omega}_i = (\omega_{i,1}, \ldots, \omega_{i,q})^\top$, and $\hat{\boldsymbol{\omega}}_{s,i} = (\hat{\omega}_{s,i,1}, \ldots, \hat{\omega}_{s,i,q})^\top$.

Let s be the number of rewards and associated CVs samples for arm i, $\boldsymbol{W}_i$ be the $s \times q$ matrix whose r^{th} row is $(W_{r,i,1}, W_{r,i,2}, \ldots, W_{r,i,q})$, and $\boldsymbol{X}_i = (X_{1,i}, \ldots, X_{s,i})^\top$. By extending the arguments used in Eq. (5) to q control variates, the estimated coefficient vector is given by

$$\hat{\boldsymbol{\beta}}^*_i = (\boldsymbol{W}^\top_i \boldsymbol{W}_i - s\hat{\boldsymbol{\omega}}_{s,i}\hat{\boldsymbol{\omega}}^\top_{s,i})^{-1}(\boldsymbol{W}^\top_i \boldsymbol{X}_i - s\hat{\boldsymbol{\omega}}_i\,\hat{\mu}_{s,i}).$$

We can generalize Lemma 1 and Lemma 2 for MAB-CV problems with q control variates and then use UCB-CV with $Q = q + 2$ and appropriate optimistic upper bound for multiple control variate case. The details are given in Appendix C.

4.3 Analysis of UCB-CV

In our next result, we describe the property of our estimator that uses control variates. This result is derived from the standard results of control variates theory (Nelson, 1990).

Lemma 3. *Let reward and control variates have a multivariate normal distribution, $\mathbb{E}[X_i | \boldsymbol{W}_i = \boldsymbol{v}] = \mu_i + \hat{\boldsymbol{\beta}}^*_i(\boldsymbol{\omega}_i - \boldsymbol{v})$, and Var$(X_i | \boldsymbol{W}_i = \boldsymbol{v}) = \sigma^2$ is independent of $\boldsymbol{W}_i$. Then after having s observations of rewards and associated control variates from arm i,*

$$\mathbb{E}\left[\hat{\mu}^c_{s,i,q}\right] = \mu_i, \text{ and}$$
$$Var(\hat{\mu}^c_{s,i,q}) = \frac{s-2}{s-q-2}(1 - \rho_i^2)Var(\hat{\mu}_{s,i}),$$

where $\rho_i^2 = \sigma_{X_i \boldsymbol{W}_i} \Sigma^{-1}_{\boldsymbol{W}_i \boldsymbol{W}_i} \sigma^\top_{\boldsymbol{W}_i X_i}/\sigma_i^2$ is the square of the multiple correlation coefficient, $\sigma_i^2 = Var(X_i)$, and $\sigma_{X_i \boldsymbol{W}_i} = (Cov(X_i, W_{i,1}), \ldots, Cov(X_i, W_{i,q}))$.

Following is our main result which upper bounds regret of UCB-CV. The detailed analysis is given in Appendix D.

Theorem 1. *Let the conditions in Lemma 3 hold, $\alpha = 2$, q be the number of control variates, $\Delta_i = \mu_{i^\star} - \mu_i$ be the sub-optimality gap for arm $i \in [K]$, and $N_i(T)$ be the number of times sub-optimal arm i selected in T rounds. Let $C_{T,i,q} = \mathbb{E}\left[\frac{N_i(T)-2}{N_i(T)-q-2}\right]$ for all i. Then the regret of UCB-CV in T rounds is upper bounded by*

$$\mathfrak{R}_T \leq \sum_{i \neq i^\star} \left(\frac{4(V^{(2)}_{T,T,q})^2 C_{T,i,q}(1 - \rho_i^2)\sigma_i^2}{\Delta_i} + \frac{\Delta_i \pi^2}{3} + \Delta_i \right).$$

Remark 1. *Unfortunately, we cannot directly compare our bound with that of UCB based stochastic MAB algorithms like UCB1-NORMAL and UCBV as $V^{(2)}_{T,T,q}$ do not have closed-form expression. $V^{(2)}_{T,T,q}$ denotes $100(1 - 1/T^2)^{th}$ percentile of t-distribution with $T - q - 1$ degrees of freedom.*

Remark 2. *As the degrees of freedom decreases in q, $V^{(2)}_{T,T,q}$ increases in q (see Fig. 1a for small value of T and Fig. 1b for large value of T). However, this does not imply that the overall regret increases in q as ρ_i^2 also increases in q. Hence dependency of regret on q is delicate. It is also observed in Nelson (1989) that having more CVs does not mean better variance reduction. One can empirically verify that $(V^{(2)}_{T,T,q})^2$ is upper bounded by $3.726 \log T$. This upper bound holds for all q as long as $T \geq q + \max(32, 0.7q)$.*

(a) $(V_{T,T,q}^{(2)})^2$ vs $3.726 \log(T)$ for small T.   (b) $(V_{T,T,q}^{(2)})^2$ vs $3.726 \log(T)$ for large T.   (c) Variation in $\frac{V_{T,N_i(T),q}^{(2)}}{V_{T,T,q}^{(2)}}$ with $N_i(T)$.

Figure 1: Properties of $(V_{T,T,q}^{(2)})^2$ and $V_{T,N_i(T),q}^{(2)}/V_{T,T,q}^{(2)}$.

Remark 3. *It is hard to bound $C_{T,i,q}$ as $V_{T,\cdot,q}^{(2)}$ does not have explicit form. However, $C_{T,i,q}$ tends to 1 as $T \to \infty$. Indeed, from lower bound argument, we know that $N_i(T) \to \infty$ as $T \to \infty$ and hence $\frac{N_i(T)-2}{N_i(T)-q-2} \searrow 1$ and $\frac{V_{T,N_i(T),q}^{(2)}}{V_{T,T,q}^{(2)}} \searrow 1$ (confidence interval shrink with more samples) as shown in Fig. 1c. However, under some assumptions, we can obtain a bound empirically. Specifically, if $q \leq 20$ and $N_i(T) > 50$, then $\frac{N_i(T)-2}{N_i(T)-q-2} \leq 1.72$ and from t-distribution tables, we get $\frac{V_{T,N_i(T),q}^{(2)}}{V_{T,T,q}^{(2)}} \leq 1.5$ (see Fig. 1c), hence the bound $C_{T,i,q} \leq 4$. We can guarantee $N_i(T) > 50$ by playing each arm 50 times at the beginning. Therefore, we can obtain one possible explicit bound in Lemma (6) by replacing $C_{T,i,q}$ with 4. However, for a general case, an explicit bound in Lemma 9 is hard.*

5   General Distribution

We now consider the general case with no distributional assumptions on reward and associated CVs of arms. The samples $\bar{X}_{t,i,q}$ resulting from the linear combination of rewards and CVs are dependent but need not be normally distributed. Hence $\hat{\mu}_{s,i,q}^c$ need not remain an unbiased estimator. Therefore, we cannot use the t-distribution properties to obtain confidence intervals. However, we can use re-sampling methods such as jackknifing, splitting to reduce the bias of the estimators and develop confidence intervals that hold approximately or asymptotically. These confidence intervals can then be used to defined indices for the arms. Below we briefly discuss these methods.

5.1   Jackknifing

In statistics, jackknifing is a well-known re-sampling technique for variance and bias estimation (Efron, 1982; Efron and Gong, 1983). We start with a classical presentation of jackknifing for CVs (Lavenberg et al., 1982). Let $\hat{\mu}_{s,i,q}^{c,-j}$ be the estimate of the mean reward that is computed without sample $\bar{X}_j$. The $Y_{j,i,q}^{\mathrm{J}} = s\hat{\mu}_{s,i,q}^c - (s-1)\hat{\mu}_{s,i,q}^{c,-j}$, which is sometimes called the j^{th} pseudo-value. Using pseudo-values mean reward estimation given as $\hat{\mu}_{s,i,q}^{c,\mathrm{J}} = \frac{1}{s}\sum_{j=1}^s Y_{j,i,q}^{\mathrm{J}}$ and its sample variance is $\hat{\nu}_{s,i,q}^{\mathrm{J}} = (s(s-1))^{-1}\sum_{j=1}^s (Y_{j,i,q}^{\mathrm{J}} - \hat{\mu}_{s,i,q}^{c,\mathrm{J}})^2$. $\hat{\mu}_{s,i,q}^{c,\mathrm{J}}$ is shown to be unbiased (Nelson, 1989)[Thm. 7] when reward variance is bounded. Further, $\hat{\mu}_{s,i,q}^{c,\mathrm{J}} \pm t_{\alpha/2}(n-1)\hat{\nu}_{s,i,q}^{\mathrm{J}}$ is a asymptotically valid confidence interval (Avramidis et al., 1991) and holds approximately for finite number of samples.

5.2   Splitting

Splitting is a technique to split the correlated observations into two or more groups, compute an estimate of $\boldsymbol{\beta}_i^*$ from each group, then exchange the estimates among the groups. Nelson (1990) considers an extreme form of splitting, where he splits s observations into s groups. The j^{th} observation is given by

$$Y_{j,i,q}^{\mathrm{S}} = X_{j,i} + \hat{\boldsymbol{\beta}}_i^{*-j}(\boldsymbol{\omega} - \boldsymbol{W}_{j,i}), \quad j \in [s],$$

where $\hat{\boldsymbol{\beta}}_i^{*-j}$ is estimated without j^{th} observation and $\boldsymbol{W}_{j,i} = (W_{j,i,1}, \ldots, W_{j,i,q})$ is the vector of CVs with q elements associated with reward $X_{j,i}$. The point estimator for splitting method is

261 $\hat{\mu}_{s,i,q}^{c,S} = \frac{1}{s}\sum_{j=1}^{s} Y_{j,i,q}^{S}$ and its sample variance is $\hat{\nu}_{s,i,q}^{S} = (s(s-1))^{-1}\sum_{j=1}^{s}(Y_{j,i,q}^{S} - \hat{\mu}_{s,i,q}^{c,S})^2$. Then
262 $\hat{\mu}_{s,i,q}^{c,J} \pm t_{\alpha/2}(n-1)\hat{\nu}_{s,i,q}^{J}$ gives an approximate confidence interval (Nelson, 1990).

263 Below we define UCB index for these methods. Let $\hat{\nu}_{N_i(t),i,q}^{G}$ be the sample variance of mean reward
264 estimator $(\hat{\mu}_{s,i,q}^{c,G})$ for arm i. We define the optimistic upper bound for mean reward for $G \in \{J, S\}$
265 as follows:

$$\text{UCB}_{t,i,q}^{G} = \hat{\mu}_{N_i(t),i,q}^{c,G} + V_{t,N_i(t),q}^{G,\alpha}\sqrt{\hat{\nu}_{N_i(t),i,q}^{G}}. \tag{7}$$

266 where $V_{t,s,q}^{G,\alpha}$ is the $100(1 - 1/t^\alpha)^{\text{th}}$ percentile value of the $t-$distribution with $s-1$ degrees of
267 freedom. Since the optimistic upper bounds defined in Eq. (7) are valid only asymptotically (Nelson,
268 1990; Avramidis et al., 1991), it cannot be used for any finite time regret guarantee. However the
269 above UCB indices can be used in UCB-CV to get an heuristic algorithm for the general case. We
270 experimentally validate its performance in the next section.

6 Experiments

272 We empirically evaluate the performance of UCB-CV by comparing it with UCB-CV with UCB1
273 (Auer et al., 2002), UCB-V (Audibert et al., 2009b), Thompson Sampling (Agrawal and Goyal, 2013),
274 and EUCBV (Mukherjee et al., 2018) on different synthetically generated problem instances. For all
275 the instance we use we use $K = 10$, $q = 1$, and $\alpha = 2$. All the experiments are repeated 100 times
276 regret bound with a 95% confidence interval (the vertical line on each curve shows the confidence
277 interval) are shown. Details of each instance are as follows:

278 *Instance 1:* The reward and associated CV of this instance have a multivariate normal distribution.
279 The reward of each arm has two components. We treated one of the components as CV. In round t,
280 the reward of arm i is given as follows:

$$X_{t,i} = V_{t,i} + W_{t,i},$$

281 where $V_{t,i} \sim \mathcal{N}(\mu_{v,i}, \sigma_{v,i}^2)$ and $W_{t,i} \sim \mathcal{N}(\mu_{w,i}, \sigma_{w,i}^2)$. Therefore, $X_{t,i} \sim \mathcal{N}(\mu_{v,i}+\mu_{w,i}, \sigma_{v,i}^2+\sigma_{w,i}^2)$.
282 We treat W_i as CV of X_i. It can be easily shown that the correlation coefficient of X_i and W_i is
283 $\rho_i = \sqrt{\sigma_{w,i}^2/(\sigma_{v,i}^2 + \sigma_{w,i}^2)}$. For each i, we set $\mu_{v,i} = 0.6 - (i-1)*0.05$, $\mu_{w,i} = 0.35$, for arm
284 $i \in [K]$. The value of $\sigma_{v,i}^2 = 0.1$ and $\sigma_{w,i}^2 = 0.1$ for all arms. Note that the problem instance has the
285 same CV for all arms, but all the CVs observations for each arm are maintained separately.

286 *Instance 2:* It is the same as the Instance 1 except each arm has a different CV associated with its
287 reward. The mean value of the CV associated with arm i is set as $\mu_{w,i} = 0.8 - (i-1)*0.05$.

288 *Instance 3:* It is the same as the Instance 2 except the samples of reward and associated control variate
289 are generated from Gamma distribution, where the value of scale is set to 1.

290 *Instance 4:* It is the same as the Instance 2 except the samples of reward and associated control variate
291 are generated from Log-normal distribution with the values of $\sigma_{v,i}^2 = 1$ and $\sigma_{w,i}^2 = 1$ for all arms.

Comparing regret of UCB-CV with existing algorithms The regret of different algorithms for
293 Instances 1 and 2 are shown in Figures Fig. 2a and Fig. 2b, respectively. As see UCB-CV outperforms
294 all the algorithms. We observe that Thomson Sampling has a large regret for normally distributed
295 reward and CVs. Hence, we have not added regret of Thomson Sampling. Note that UCB-CV does
296 not require a bounded support assumption, which is needed in all other algorithms. The regret of the
297 EUCBV algorithm is closest to UCB-CV, but EUCBV can stick with the sub-optimal arm as it uses
298 an arm elimination-based strategy, which has a small probability of eliminating the optimal arm.

Regret of UCB-CV vs Correlation Coefficient Theorem 1 shows that UCB-CV have better regret
300 bounds when correlation between arm rewards and CVs is higher. To validate this we derived problem
301 instances having different correlation coefficients as follows:

302 *Instance 5:* Similar to the Instance 1, the reward and associated CVs have a multivariate normal
303 distribution with rewards expressed as sum of two components. We set $\mu_{v,i} = 6.0 - (i-1)*0.5$
304 and $\mu_{w,i} = 4.0$ for arm $i \in [K]$. The value of $\sigma_{v,i}^2 = 1.0$ and $\sigma_{w,i}^2 = 1.0$ for all arms. The problem
305 instance has common CV for all arms but all the observations are maintained for each arm separately.

(a) Instance 1   (b) Instance 2   (c) Varying Correlation Coefficient.

Figure 2: Regret comparison of different multi-armed bandits algorithms with UCB-CV.

As the correlation coefficient of X_i and W_i is $\rho_i = \sqrt{\sigma_{w,i}^2/(\sigma_{v,i}^2 + \sigma_{w,i}^2)}$, we varied $\sigma_{v,i}^2$ over the values $\{1.0, 1.5., 2.0, 2.5, 3.0\}$ to obtain problem instances with different correlation coefficient. Increasing $\sigma_{v,i}^2$ reduces the correlation coefficient of X_i and W_i. We have plotted the regret of UCB-CV for different problem instances. As expected, we observe that the regret decreases as the correlation coefficient of reward and its associated control variates increases as shown in Fig. 2c.

Performance of Jackknifing, Splitting, and Batching Methods   We compare the regret of UCB-CV with Jackknifing, Splitting and Batching (see Appendix E for more details) methods. The regret of the batching method is worse for all the instances. Whereas, the jackknifing and splitting are performing well for heavy-tailed distributions (Instance 3 and Instance 4) and UCB-CV only performs better than Jackknifing method for normal distribution (Instance 2) as shown in Fig. 3.

(a) Instance 2   (b) Instance 3   (c) Instance 4.

Figure 3: Comparing regret of UCB-CV with Jackknifing, Splitting, and Batching method based.

7 Conclusion

In this work, we studied stochastic multi-armed bandits problem with side information available in the form of Control Variate (CV). Leveraging the linear control variates' variance reduction properties, we developed a variant of the UCB algorithm named UCB-CV. When reward and CVs have a multivariate normal distribution, we showed that the regret of UCB-CV, which is of the order $\mathcal{O}(\sigma^2(1 - \rho^2)/\Delta \log T)$ where σ^2 is the maximum variance of arm rewards and ρ is the minimum correlation between the arm rewards and CVs. As expected, our the bounds showed that when the correlation is strong, one can get significant improvement in regret performance. For the case where the reward and control variates follow a general distribution, we discussed Jackknifing and splitting resampling that will give estimators with smaller bias and sharper confidence bounds.

The variance reduction techniques based on CVs assume that the exact mean of the CVs are known. In practice, only some rough estimates of the mean of CVs rather than the exact values may be available. It would be interesting to study how does it affect the performance of the bandit algorithms. Another interesting direction to study how CVs are helpful if one has to rank the arms instead of just finding the top-ranked arm.

References

Yasin Abbasi-Yadkori, Dávid Pál, and Csaba Szepesvári. Improved algorithms for linear stochastic bandits. In *Advances in Neural Information Processing Systems*, pages 2312–2320, 2011.

Shipra Agrawal and Navin Goyal. Analysis of thompson sampling for the multi-armed bandit problem. In *Conference on Learning Theory*, pages 39–1, 2012.

Shipra Agrawal and Navin Goyal. Further optimal regret bounds for thompson sampling. In *Artificial intelligence and statistics*, pages 99–107, 2013.

Jean-Yves Audibert, Rémi Munos, and Csaba Szepesvári. Exploration–exploitation tradeoff using variance estimates in multi-armed bandits. *Theoretical Computer Science*, 410(19):1876 – 1902, 2009a.

Jean-Yves Audibert, Rémi Munos, and Csaba Szepesvári. Exploration–exploitation tradeoff using variance estimates in multi-armed bandits. *Theoretical Computer Science*, 410(19):1876–1902, 2009b.

Peter Auer and Ronald Ortner. Ucb revisited: Improved regret bounds for the stochastic multi-armed bandit problem. *Periodica Mathematica Hungarica*, 61(1-2):55–65, 2010.

Peter Auer, Nicolo Cesa-Bianchi, and Paul Fischer. Finite-time analysis of the multiarmed bandit problem. *Machine learning*, pages 235–256, 2002.

Athanassios N Avramidis, Kenneth W Bauer Jr, and James R Wilson. Simulation of stochastic activity networks using path control variates. *Naval Research Logistics (NRL)*, 38(2):183–201, 1991.

Zdravko Botev and Ad Ridder. Variance reduction. *Wiley StatsRef: Statistics Reference Online*, pages 1–6, 2014.

Sébastien Bubeck, Nicolo Cesa-Bianchi, et al. Regret analysis of stochastic and nonstochastic multi-armed bandit problems. *Foundations and Trends® in Machine Learning*, 5(1):1–122, 2012.

Olivier Chapelle and Lihong Li. An empirical evaluation of thompson sampling. In *Advances in neural information processing systems*, pages 2249–2257, 2011.

Yutian Chen and Zoubin Ghahramani. Scalable discrete sampling as a multi-armed bandit problem. In *International Conference on Machine Learning*, pages 2492–2501. PMLR, 2016.

Wei Chu, Lihong Li, Lev Reyzin, and Robert E Schapire. Contextual bandits with linear payoff functions. In *International Conference on Artificial Intelligence and Statistics*, pages 208–214, 2011.

Richard W Conway. Some tactical problems in digital simulation. *Management science*, 10(1):47–61, 1963.

Varsha Dani, Thomas P Hayes, and Sham M Kakade. Stochastic linear optimization under bandit feedback. In *COLT*, pages 355–366, 2008.

Bradley Efron. *The jackknife, the bootstrap and other resampling plans*. SIAM, 1982.

Bradley Efron and Gail Gong. A leisurely look at the bootstrap, the jackknife, and cross-validation. *The American Statistician*, 37(1):36–48, 1983.

Sarah Filippi, Olivier Cappe, Aurélien Garivier, and Csaba Szepesvári. Parametric bandits: The generalized linear case. In *Advances in Neural Information Processing Systems*, pages 586–594, 2010.

Aurélien Garivier and Olivier Cappé. The kl-ucb algorithm for bounded stochastic bandits and beyond. In *Proceedings of the 24th annual Conference On Learning Theory*, pages 359–376, 2011.

F Hayashi. *Econometrics*. Princeton University Press, 2000.

Junya Honda and Akimichi Takemura. An asymptotically optimal bandit algorithm for bounded support models. In *COLT*, pages 67–79. Citeseer, 2010.

BAP James. Variance reduction techniques. *Journal of the Operational Research Society*, 36(6): 525–530, 1985.

Kwang-Sung Jun, Aniruddha Bhargava, Robert Nowak, and Rebecca Willett. Scalable generalized linear bandits: Online computation and hashing. In *Advances in Neural Information Processing Systems*, pages 99–109, 2017.

Emilie Kaufmann, Nathaniel Korda, and Rémi Munos. Thompson sampling: An asymptotically optimal finite-time analysis. In *International Conference on Algorithmic Learning Theory*, pages 199–213. Springer, 2012.

Julia Kreutzer, Artem Sokolov, and Stefan Riezler. Bandit structured prediction for neural sequence-to-sequence learning. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1503–1513, 2017.

Tor Lattimore and Csaba Szepesvári. *Bandit Algorithms*. Cambridge University Press, 2020. doi: 10.1017/9781108571401.

Stephen S Lavenberg and Peter D Welch. A perspective on the use of control variables to increase the efficiency of monte carlo simulations. *Management Science*, 27(3):322–335, 1981.

Stephen S Lavenberg, Thomas L Moeller, and Peter D Welch. Statistical results on control variables with application to queueing network simulation. *Operations Research*, 30(1):182–202, 1982.

Lihong Li, Wei Chu, John Langford, and Robert E Schapire. A contextual-bandit approach to personalized news article recommendation. In *Proceedings of the 19th international conference on World wide web*, pages 661–670. ACM, 2010.

Lihong Li, Yu Lu, and Dengyong Zhou. Provably optimal algorithms for generalized linear contextual bandits. In *International Conference on Machine Learning*, pages 2071–2080, 2017.

Subhojyoti Mukherjee, KP Naveen, Nandan Sudarsanam, and Balaraman Ravindran. Efficient-ucbv: An almost optimal algorithm using variance estimates. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

Barry L Nelson. Batch size effects on the efficiency of control variates in simulation. *European Journal of Operational Research*, 43(2):184–196, 1989.

Barry L Nelson. Control variate remedies. *Operations Research*, 38(6):974–992, 1990.

Paat Rusmevichientong and John N Tsitsiklis. Linearly parameterized bandits. *Mathematics of Operations Research*, 35(2):395–411, 2010.

Bruce Schmeiser. Batch size effects in the analysis of simulation output. *Operations Research*, 30(3): 556–568, 1982.

William R Thompson. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25(3/4):285–294, 1933.

Sara A Van De Geer. Least squares estimation. *Encyclopedia of statistics in behavioral science*, 2005.

Nikos Vlassis, Aurelien Bibaut, Maria Dimakopoulou, and Tony Jebara. On the design of estimators for bandit off-policy evaluation. In *International Conference on Machine Learning*, pages 6468–6476. PMLR, 2019.

Lijun Zhang, Tianbao Yang, Rong Jin, Yichi Xiao, and Zhi-hua Zhou. Online stochastic linear optimization under one-bit feedback. In *International Conference on Machine Learning*, pages 392–401, 2016.