Repeated Environment Inference for Invariant Learning

Abstract

We study the problem of invariant learning when the environment labels are unknown. We focus on the Invariant representation notion when the Bayes optimal conditional label distribution is the same across different environments. Previous work conducts the Environment Inference (EI) by maximizing the penalty term in the Invariant Risk Minimization (IRM) framework. The EI step uses a reference model which focuses on spurious correlations to efficiently reach a good environment partition. However, it is not clear how to find such a reference model. In this work, we propose to repeat the EI process and retrain an ERM model on the *majority* environment inferred by the EI step in the previous step. Under mild assumptions, we find that this iterative process helps learn a representation capturing the spurious correlation better than the single step. This results in better Environment Inference and better Invariant Learning. We show that this method outperforms baselines on both synthetic and real-world datasets.

1. Introduction

In conventional machine learning, the training data is assumed to independently and identically distributed (*iid*) as the test data. This is usually violated in the real world. Samples used in training might not be representative of the whole data distribution in many applications. Therefore, performance suffers when machine learning algorithms are deployed in new *domains* or *environments* where spurious correlations learnt from the training data do not hold. To solve this problem, recent literature advocates focusing on extracting causal relationships (Peters et al., 2017) from data. However, causal discovery and inference in the high-dimensional data remains a big challenge in practice.

Recent work (Arjovsky et al., 2019; Ilse et al., 2020; Chuang et al.) have proposed to learn stable correlations that are in-

variant across different domains because they have been shown to strongly relates with Causality (Heinze-Deml et al., 2018; Peters et al., 2016). However, Invariant Learning methods usually require predefined environment labels which are not always available. For example, fair machine learning can be regarded as an Invariant Learning problem where different sub-populations correspond to different environments and the sensitive features are usually not available or even hard to define (Corbett-Davies & Goel, 2018). On the other hand, environment labels play an important role in invariant learning. Figure 1 shows how the performance of IRM increases when training samples are grouped differently (Experiment B) than the ground-truth group labels (Experiment A). We randomly shuffle the background for digits with different probabilities to create two training environments and fix the background for others. IRM benefits from the regrouping as it reflects a better differentiation between the two environments in terms of the domain-specific "optimal" representation, for predicting the labels.

Figure 1. **Left:** Data distributions in two environments in experiment A and B; **Right:** IRM test accuracy in experiment A and B; Experiment **A**: CBMNIST samples with shuffled background w.p. 1% and 2% in both environments, respectively; Experiment **B**: Samples with shuffled background are all grouped in one environment. The test environment has completely different backgrounds. IRM's performance is significantly higher in Experiment B. More details in Section 4.1).

Creager et al. (2021) proposed EIIL which enables invariant learning when environment labels are not available. It conducts Environment Inference (EI) using the representation learned by a reference model, by maximizing the penalty term in the Invariant Risk Minimization (IRM) framework. Moreover, it is shown that EIIL usually works when the reference model captures "spurious" correlations. However,

---
[1]Anonymous Institution, Anonymous City, Anonymous Region, Anonymous Country. Correspondence to: Anonymous Author <anon.email@domain.com>.

Preliminary work. Under review by the SCIS workshop.

it is not clear how to find such a model besides learning an ERM model from all the training data.

In this paper, we find that environment partition obtained in a single EI step after ERM is sub-optimal for invariant learning and propose a simple repeated EI strategy to improve the quality of Environment Inference and consequently the performance of Invariant Learning. **Our contribution can be summarized as follows:**

1. We propose a novel method that generates environment labels by repeating the EI step and training the ERM model on the *majority* environment. We call it Repeated Environment Inference for Invariant Learning (REIIL).

2. Under mild assumptions, we show that our strategy better facilitates downstream invariant learning.

3. Our approach outperforms previous methods including EIIL on previously used and a newly introduced dataset.

2. Related Work

IRM and Environment Inference Arjovsky et al. (2019) proposes a training objective for learning the invariant representations, under the assumption that the optimal conditional $P(y|\phi(x))$ remains invariant across domains. However, recent works (Rosenfeld et al., 2020; Kamath et al., 2021) have shown that IRM fails when target domains are not sufficiently similar to training domains. Besides, it also requires good environment labels beforehand. Several methods have been proposed to infer the environment labels before or along with the invariant learning. EIIL (Creager et al., 2021) takes a two-step strategy and first partitions the training data into environments using a biased reference model and then train a IRM model. However, it is unclear how to get a perfectly biased reference model to obtain the optimal environment partition. Recently, Adversarial Invariant Learning (Ye et al., 2021) uses a minimax game to robustly train the predictors while inferring the worst-case environment partition. In this paper, we follow the EIIL setup and study how to better conduct environment inference before downstream invariant learning.

Other Types of Invariance in Domain Generalization Besides IRM, other definitions of *Invariance* exist in the domain generalization literature. Dated back to early works in domain adaptation (Gretton et al., 2009; Sun & Saenko, 2016), marginal feature alignment motivates the learning of the domain-invariant features, that is $P(\phi(x))$ being invariant across domains (Ganin et al., 2016). However, the shortcoming of these methods is also obvious that it ignores the relation between the features and the labels so that it is sub-optimal especially under label shift (Zhao et al., 2019; 2020). Other work utilize tools like Information Bottleneck and propose learning objectives based on the mutual information (Li et al., 2021). Li et al. (2018) focus on con-

ditional domain invariant representation and make sure that the $P(\phi(x)|y)$ remains invariant across domains. Focusing on only one type of invariant learning has been shown to be sub-optimal (Shui et al., 2022), but choosing the right type of invariant learning algorithm can be a tricky question. In our paper, we aim to learn the invariant $P(y|\phi(x))$ distribution when environment labels are not available.

Representation Learning under Domain Shift Other representation learning techniques have been also found helpful under domain shift. For example, Liu et al. (2021) proposes that upweighting underperforming samples in a second iteration of training is sufficient to improve worst-case group performance. Kirichenko et al. (2022) suggest that last layer retraining of Neural Networks with interesting samples might be sufficient for robustness against spurious correlations. Contrastive Learning approaches (Wang et al., 2022; Kim et al., 2021) have also shown promise for domain adaptation and generalization. However, these methods do not explicitly learn any invariance and are usually hard to analyze. In our paper, we focus on the more principled IRM setting and overcome the difficulty of obtaining biased models for environment inference.

3. Method

3.1. IRM method and Environment Inference

The practical version of IRM (called IRMv1) has the following objective.

$$\min_{\Phi:\mathcal{X}\to\mathcal{Y}} \sum_{e\in\mathcal{E}_{tr}} R^e(\Phi) + \lambda \cdot \|\nabla_{w|w=1.0} R^e(w \cdot \Phi)\|^2 \quad (1)$$

In EIIL, an Environment Inference step produces the required environment labels. It uses a fixed reference classifier Φ. The **EI step** maximizes the following with respect to $\boldsymbol{q}$,

$$C^{EI}(\Phi, \boldsymbol{q}) = \|\nabla_{w|w=1.0}\tilde{R}^e(w \cdot \Phi, \boldsymbol{q})\|^2, \quad (2)$$

where $R^e(\Phi, \boldsymbol{q}) = \frac{1}{N}\sum_i \boldsymbol{q}_i(e)l(\Phi(x_i), y_i)$.

In summary, EIIL (Creager et al., 2021) takes the following steps:

1. Takes an input reference model $\tilde{\Phi}$.

2. Maximizes C^{EI} to get environment partition. $\boldsymbol{q}^* = \arg\max_q C^{EI}(\tilde{\Phi}, \boldsymbol{q})$.

3. Minimizes C^{IL} (any Invariant Learning objective of choice) to get the final model. $\Phi^* = \arg\min_{\Phi} C^{IL}(\Phi, \boldsymbol{q}^*)$.

Note that here $\boldsymbol{q}$ produces a binary partition of environments, and we assume this binary partitioning throughout this paper. EIIL works under the assumption that the reference model ($\tilde{\Phi}$) focuses only on the spurious features. It is only when $\tilde{\Phi} = \Phi_{Spurious}$, does the environment inference (EI)

process maximally violates the Invariance Principle (EIC):

$$\mathbb{E}[y|\Phi(x) = h, e_1] = \mathbb{E}[y|\Phi(x) = h, e_2], \forall h \in \mathcal{H}, e_1, e_2 \in \mathcal{E}^{obs}$$

The authors use Φ_{ERM} as an approximation for $\Phi_{Spurious}$, but this does not always work. As underlined in the paper explicitly via various experiments, it remains unexplored to find better reference models (which would be worse than ERM in terms of generalization performance) to fully exploit the EI step in EIIL.

3.2. Proposed method

We present an assumption about the training distribution and a conjecture about the resulting EI step using a model trained from such a training distribution. We then reason how finding a model that satisfies the conjecture under the assumption would help the downstream invariant learning. We finally propose a strategy to approximate such a model.

Assumption 3.1. Assume a data generating graph $x \rightarrow y \rightarrow z$, where x and z are observed features and y is the target label. A training distribution is sampled following the graph with noise. Assume that in the training distribution, anti-causal features are more informative than the causal features, i.e.,

$$I_{tr}(Y, Z) > I_{tr}(Y, X) > 0 \tag{3}$$

where I measures the overall mutual information between features and the labels across samples.

Conjecture 3.2. *There exists a model trained on such training datasets such that when it is used as a reference model for the EI step for two environments, the resulting majority environment satisfies the following:*

$$I_{e_{maj}}(Y, Z) - I_{e_{maj}}(Y, X) > I_{tr}(Y, Z) - I_{tr}(Y, X) \tag{4}$$

where e_{maj} and tr denote the majority environment after the EI step and all the training data, respectively.

Remarks: By induction, we conclude that if a model satisfies the conjecture after one step of EI, there exists such a model in the next step when we regard the majority environment as the training distribution, until a point of diminishing returns.

Therefore, we propose a simple repetition of reference model training on a biased subset of samples to get a more biased reference model better approximating $\Phi_{Spurious}$. We use ERM to approximate such a model in each step. The strategy can be defined in the following steps:

1. Perform EI step from EIIL using the ERM reference model trained on the whole dataset.

2. Instead of training an Invariant Learning algorithm directly on the obtained partition, retrain an ERM model on the *majority* environment obtained from the previous step. Repeat this step for n iterations.

3. Use the finally obtained partition for downstream Invariant Learning methods.

The repetition of the EI step is based on the proposed conjecture that majority subsets obtained would show even stronger correlation between spurious and target labels and, the ERM model trained on it would iteratively approximate $\Phi_{Spurious}$.

4. Experimental Results

We show the effectiveness of our proposed method on various datasets under different challenging conditions and find that it recovers *good* environment splits and provides boosted performance in invariant learning. We also provide empirical evidence to support our conjecture.

4.1. Datasets

Colored MNIST (CMNIST) was originally introduced in the IRM paper (Arjovsky et al., 2019). It has a synthetic binary classification task where color is introduced as an anti-causal spurious correlation.

CIFAR-Background MNIST (CBMNIST) We introduce this new dataset, which is based on the simple concept of putting MNIST (Deng, 2012) digits on CIFAR (Krizhevsky et al., 2009) backgrounds. The classification task for the resultant images remains same as the MNIST digit classification task. This process results in a dataset which is easily accessible, modifiable and has more complex "real-world" features than simple colors. The resulting images have the same size as CIFAR images ($32 \times 32 \times 3$).

In our experiments, we select a random mapping of CIFAR and MNIST classes and put the CIFAR images on MNIST digit backgrounds. This mapping acts as the spurious anti-causal correlation. We only randomly shuffle this background for a small number of samples in the dataset to introduce noise. For one variant, CBMNIST [I], we split the training MNIST training data in two equally sized environments (Figure 1) and put CIFAR backgrounds on them using the training mapping. With probability ~1% and ~2% respectively in each environment, we change the background. Figure 2 shows example images from one CBMNIST [I] training environment. In the test set, we use completely different backgrounds. Design details and other variants [II, III] of this dataset can be seen in Appendix A.

4.2. Implementation details

We reuse the code [anonymous link], model architectures and hyperparameters from EIIL, which follows the IRM for CMNIST experiments. For CMNIST, we increase the number of training steps to 900. For CBMNIST, we use an MLP with a similar structure but instead of down sampling

as in CMNIST, we use all the $32 \times 32 \times 3$ input dimensions to help the model learn any complex background features. For REIIL, we found that in $n = 9$ iterations, the performance usually saturates. Note that for EIIL and REIIL, the environment labels are not used in the training. We also used L2 regularization on the parameters for all methods.

Figure 2. CBMNIST [I] samples.

4.3. Result Analysis

Better Invariant Learning Results on CMNIST and CBMNIST [I] can be seen in Figure 3. In both the datasets, REIIL outperforms other methods. For CMNIST, the performance gains are not big because the Φ_{ERM} approximates $\Phi_{Spurious}$ quite well in the first EIIL step. However, REIIL's performance is more stable than EIIL across 5 runs. For CBMNIST [I], the performance gains are quite substantial. Because the *shuffled* samples are very scarce and IRM fails to beat even ERM. But REIIL consistently performs better than other methods. Results on other CBMNIST variants and synthetic data are deferred to the Appendix B.

(a) CMNIST   (b) CBMNIST [I]

Figure 3. Comparison with baseline methods on CMNIST and CBMNIST [I].

Dynamics of Repeated EI We study the environment inference dynamics in the REIIL. Repeated EI finds *more biased* reference models which produce better environment splits. Recall that a good environment split regroups data such that the spurious features are more informative about the labels in the majority environment (for example, corresponding to the *non-shuffled* images in CBMNIST [I]). The minority environment's test accuracy would be low under the reference model trained in the majority environment. Figure 4 shows

the accuracies of the reference models in each step for the samples in the *minority* environment, and the percentage of *shuffled* samples assigned in the minority environment with each EI step. The accuracy in the minority domain keeps decreasing while the proportion of *shuffled* samples is getting higher. For CMNIST, this effect is not as pronounced as CBMNIST [I], and *shuffled* samples correspond to those which do not exhibit the color-based spurious correlation. This provides empirical evidence that the ERM model trained on the majority environment obtained from the previous EI step captures spurious features (background or color) increasingly and produces a better environment partition.

(a) CMNIST   (b) CBMNIST [I]

Figure 4. Accuracy of reference model drops for the minority environment and percentage of *shuffled* samples increase in the minority environment with REIIL iterations.

5. Conclusion and Discussion

In this paper, we propose a novel strategy to find a *more biased* reference model for environment inference. By repeating the EI step iteratively and training the reference model on the majority environment, our method helps find a better environment partition for downstream Invariant Learning tasks. Our assumption often holds in practice where most training samples exhibit strong spurious correlations. We conduct experiments on both CMNIST and our newly designed CBMNIST and demonstrate that our method achieves better predictive performance in invariant learning.

What if our assumption is violated? In practice, it may not be easy to test whether our assumption is valid. Therefore, we conduct experiments on the synthetic data (Appendix B) where there is no clear "optimal" data split. We find that even though REIIL usually achieves the best test error, it may not recover the models close to the true ones. We leave further exploration of this setting to our future work.

What if there are more than two environments? With multiple types of spurious correlations (or multiple training environments), a good environment split is hard to define. It is not clear whether a binary partition is sufficient. Therefore, we want to investigate these more complicated scenarios in invariant learning in the future.

References

Arjovsky, M., Bottou, L., Gulrajani, I., and Lopez-Paz, D. Invariant risk minimization. *arXiv preprint arXiv:1907.02893*, 2019.

Chuang, C.-Y., Torralba, A., and Jegelka, S. Estimating generalization under distribution shifts via domain-invariant representations. *arXiv preprint arXiv:2007.03511*.

Corbett-Davies, S. and Goel, S. The measure and mismeasure of fairness: A critical review of fair machine learning. *arXiv preprint arXiv:1808.00023*, 2018.

Creager, E., Jacobsen, J.-H., and Zemel, R. Environment inference for invariant learning. In *International Conference on Machine Learning*, pp. 2189–2200. PMLR, 2021.

Deng, L. The mnist database of handwritten digit images for machine learning research [best of the web]. *IEEE signal processing magazine*, 29(6):141–142, 2012.

Ganin, Y., Ustinova, E., Ajakan, H., Germain, P., Larochelle, H., Laviolette, F., Marchand, M., and Lempitsky, V. Domain-adversarial training of neural networks. *The journal of machine learning research*, 17(1):2096–2030, 2016.

Gretton, A., Smola, A., Huang, J., Schmittfull, M., Borgwardt, K., and Schölkopf, B. Covariate shift by kernel mean matching. *Dataset shift in machine learning*, 3(4): 5, 2009.

Heinze-Deml, C., Peters, J., and Meinshausen, N. Invariant causal prediction for nonlinear models. *Journal of Causal Inference*, 6(2), 2018.

Ilse, M., Tomczak, J. M., Louizos, C., and Welling, M. Diva: Domain invariant variational autoencoders. In *Medical Imaging with Deep Learning*, pp. 322–348. PMLR, 2020.

Kamath, P., Tangella, A., Sutherland, D., and Srebro, N. Does invariant risk minimization capture invariance? In *International Conference on Artificial Intelligence and Statistics*, pp. 4069–4077. PMLR, 2021.

Kim, D., Yoo, Y., Park, S., Kim, J., and Lee, J. Selfreg: Self-supervised contrastive regularization for domain generalization. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 9619–9628, 2021.

Kirichenko, P., Izmailov, P., and Wilson, A. G. Last layer re-training is sufficient for robustness to spurious correlations. *arXiv preprint arXiv:2204.02937*, 2022.

Krizhevsky, A., Hinton, G., et al. Learning multiple layers of features from tiny images. 2009.

Li, B., Shen, Y., Wang, Y., Zhu, W., Reed, C. J., Zhang, J., Li, D., Keutzer, K., and Zhao, H. Invariant information bottleneck for domain generalization. *arXiv preprint arXiv:2106.06333*, 2021.

Li, Y., Tian, X., Gong, M., Liu, Y., Liu, T., Zhang, K., and Tao, D. Deep domain generalization via conditional invariant adversarial networks. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 624–639, 2018.

Liu, E. Z., Haghgoo, B., Chen, A. S., Raghunathan, A., Koh, P. W., Sagawa, S., Liang, P., and Finn, C. Just train twice: Improving group robustness without training group information. In *International Conference on Machine Learning*, pp. 6781–6792. PMLR, 2021.

Peters, J., Bühlmann, P., and Meinshausen, N. Causal inference by using invariant prediction: identification and confidence intervals. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 78(5):947–1012, 2016.

Peters, J., Janzing, D., and Schölkopf, B. *Elements of causal inference: foundations and learning algorithms*. The MIT Press, 2017.

Rosenfeld, E., Ravikumar, P., and Risteski, A. The risks of invariant risk minimization. *arXiv preprint arXiv:2010.05761*, 2020.

Shui, C., Wang, B., and Gagné, C. On the benefits of representation regularization in invariance based domain generalization. *Machine Learning*, pp. 1–21, 2022.

Sun, B. and Saenko, K. Deep coral: Correlation alignment for deep domain adaptation. In *European conference on computer vision*, pp. 443–450. Springer, 2016.

Wang, R., Wu, Z., Weng, Z., Chen, J., Qi, G.-J., and Jiang, Y.-G. Cross-domain contrastive learning for unsupervised domain adaptation. *IEEE Transactions on Multimedia*, 2022.

Ye, N., Tang, J., Deng, H., Zhou, X.-Y., Li, Q., Li, Z., Yang, G.-Z., and Zhu, Z. Adversarial invariant learning. In *2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 12441–12449. IEEE, 2021.

Zhao, H., Des Combes, R. T., Zhang, K., and Gordon, G. On learning invariant representations for domain adaptation. In *International Conference on Machine Learning*, pp. 7523–7532. PMLR, 2019.

Zhao, H., Dan, C., Aragam, B., Jaakkola, T. S., Gordon, G. J., and Ravikumar, P. Fundamental limits and trade-offs in invariant representation learning. *arXiv preprint arXiv:2012.10713*, 2020.

A. CBMNIST

CBMNIST [I] This dataset was created in the following manner:

- One random CIFAR image from each class is chosen to act as background for MNIST images. This results in 10 different backgrounds with different visual properties.

- Each MNIST class is mapped with a randomly selected CIFAR class. This mapping between classes acts as the anti-causal spurious correlation in the training set. For the test set, a completely different random mapping of classes is chosen such that there is no overlap.

- Training data is split in two environments with 25000 samples each (from 60000 MNIST training samples). Test data has the remaining 10000 samples.

- All training samples are filled with the mapped CIFAR background from the corresponding class. In Environment 1, backgrounds of ~1% of samples are *shuffled*. Shuffled here means a random background which is not equal to the one in train or test mapping of that class (one of the remaining 8), is assigned to this sample. Similarly, in Environment 2 ~2% samples have their background shuffled.

The resulting dataset has ~97% samples exhibiting a strong anti-causal relationship with the target class label and the background. The rest ~3% samples have shuffled backgrounds so the only *invariant* features in them are the actual digit shapes. The causal graph can be seen in Figure 5. This ensures that the dataset satisfies the assumption for our conjecture to hold.

Figure 5. CBMNIST Data generating process. Here X_{INV} is the abstract concept of a not varying *digit shape*, X_{SP} is the spurious correlation between the target label Y (MNIST class) and background [Mapping]. X_{dig} is the actual observed digit shape which varies across samples according to some inherent noise N_{Ed}, while N_{Eb} controls the noise between the anti-causal relationship of Y and X_{SP} to give the actual observed background X_{back}.

CBMNIST [II] only had a slight variation of the concept of *shuffled*. The shuffled samples don't have their background shuffled randomly to one of the remaining 8, but to exactly one other background (which is already decided). In this way, even the ~3% shuffled samples exhibit a spurious correlation with the background and a particular digit is only ever seen with at most 2 different backgrounds in the training set. The test set remains the same with a completely different mapping of classes and backgrounds. This correlates more to the CMNIST setting where only 2 colors are used and the *shuffled* samples do not exhibit the anti-causal spurious correlation with color.

CBMNIST [III] only had the percentage of samples having shuffled backgrounds change from CBMNIST [I]. In this case, we changed the numbers ~1% and ~2% to ~10% and ~20% respectively. This simulates a case where even ERM has a lot of variation in the dataset to learn invariant causal features from.

B. Other Experiments

CBMNIST Results on the variations of CBMNIST can be seen in Figure 6. For CBMNIST [II] the results were similar, but a lot changed with CBMNIST [III] where ERM emerged as the best performing model. This is because a higher percentage of *shuffled* background samples can regularize the ERM model's training to learn the invariant feature which is the digit shape. This also changes the fact that for the first EI step, a reference model which is very far from $\Phi_{Spurious}$ is used. This in turn produces a bad environment split and hampers the progress of REIIL. REIIL still beats EIIL but because of the poor starting point, it was not able to reach the performance of even IRM. Interestingly, this could be an issue with the downstream Invariant Learning method. Inspired from (Liu et al., 2021), we trained a Weighted ERM (WERM) model on the EI obtained environment splits (REIWERM). Weighted ERM simply weighs samples from each environment equally

rather than weighing each individual sample equally as in ERM. This model surprisingly matched the performance of IRM. We defer investigating this further for future work.

Synthetic Data We used all variants of the synthetic data defined in IRM (Arjovsky et al., 2019) as well as the synthetic data defined in (Creager et al., 2021). The data was originally split in 3 environments with noises 0.2, 2 and 5 respectively. We found an interesting detail in the previous implementations where ERM was trained on all three environments and IRM/EIIL were trained only on the first two and the last was used as a validation set to pick the IRM regularizer. We changed this detail by introducing a validation set explicitly using noise = 3.5 and treating the last environment with noise = 5 as the test set.

The IRM data experiment results can be summarized in Table 1. In almost all experiments, IRM found the best solutions. Interestingly, REIIL almost always found models with lowest validation and test errors (always lower than EIIL) but that did not translate to the corresponding solutions having lower Causal and Non-Causal Errors with the ground truth solutions.

We found that the validation set in both previous and current settings had high noise (5 and 3.5), which is not representative of the real causal graph (which would have no noise). Therefore, we infer that selecting a model based on lower validation error does not necessarily yield the best solutions. But in a learning setting with fixed number of samples, finding a model with lower validation error is usually the best we can do. REIIL often achieves the lowest validation error, which is always lower than EIIL, suggesting that repeating the EI step improves performance.

We found similar results with the synthetic data defined in EIIL, where REIIL usually found models with lowest validation and test errors.

Method/Type	FOU	FOS	FEU	FES	POU	POS	PEU	PES
ERM val	9.50 (0.26)	9.29 (0.23)	10.02 (0.40)	9.34 (0.47)	10.89 (0.46)	12.61 (1.28)	12.29 (2.23)	**11.68** (1.06)
ERM test	16.39 (0.76)	16.28 (1.14)	16.95 (1.13)	16.01 (1.04)	20.09 (0.95)	22.42 (2.00)	22.47 (5.43)	**20.45** (2.06)
IRM val	**5.11** (0.09)	7.66 (0.17)	14.84 (0.48)	13.96 (0.68)	**6.50** (0.57)	**8.74** (0.43)	16.16 (1.62)	16.26 (1.38)
IRM test	**5.50** (0.19)	12.52 (0.81)	27.12 (1.52)	26.18 (2.09)	**9.06** (1.06)	**13.67** (1.33)	30.23 (3.69)	30.22 (2.75)
EIIL val	10.38 (0.26)	7.57 (0.35)	14.01 (3.30)	18.32 (1.39)	10.07 (0.98)	12.38 (2.58)	19.01 (5.68)	18.78 (5.10)
EIIL test	17.67 (0.64)	9.51 (1.51)	26.06 (8.6)	32.75 (3.43)	18.06 (2.50)	19.89 (4.91)	35.37 (11.46)	35.92 (11.33)
REIIL val	7.17 (0.45)	**6.58** (0.88)	**8.97** (0.51)	**8.96** (0.33)	8.75 (0.49)	10.40 (1.91)	**11.81** (2.51)	11.72 (1.42)
REIIL test	10.77 (0.72)	**8.31** (1.96)	**14.72** (1.29)	**15.63** (1.36)	14.06 (1.50)	17.09 (4.13)	**21.41** (6.00)	20.86 (2.97)
ERM CE	0.11 (0.01)	0.12 (0.00)	0.44 (0.02)	0.45 (0.00)	0.12 (0.02)	0.14 (0.00)	0.44 (0.01)	0.47 (0.01)
ERM NCE	0.11 (0.00)	-	0.44 (0.01)	-	0.11 (0.01)	-	0.42 (0.02)	-
IRM CE	**0.01** (0.00)	0.09 (0.01)	**0.25** (0.01)	**0.29** (0.01)	**0.01** (0.00)	**0.04** (0.01)	**0.22** (0.02)	**0.29** (0.01)
IRM NCE	**0.01** (0.00)	-	**0.32** (0.00)	-	**0.01** (0.00)	-	**0.33** (0.01)	-
EIIL CE	0.12 (0.02)	**0.02** (0.00)	0.40 (0.05)	0.46 (0.02)	0.10 (0.03)	0.09 (0.03)	0.31 (0.10)	0.42 (0.05)
EIIL NCE	0.10 (0.02)	-	0.45 (0.01)	-	0.05 (0.04)	-	0.39 (0.08)	-
REIIL CE	0.05 (0.00)	**0.02** (0.00)	0.49 (0.04)	0.45 (0.02)	0.05 (0.04)	0.09 (0.02)	0.42 (0.06)	0.47 (0.02)
REIIL NCE	0.04 (0.01)	-	0.51 (0.02)	-	0.04 (0.03)	-	0.47 (0.05)	-

Table 1. Results of synthetic data experiments. val and test denote validation and test set errors of the model after training. CE and NCE denote Causal and Non-Causal errors. (standard deviation across 3 runs in brackets)

(a) CBMNIST [II]   (b) CBMNIST [III]

Figure 6. Performance of different methods on CBMNIST [II] and CBMNIST [III].