GIR Framework: Learning Graph Positional Embeddings with Anchor Indication and Path Encoding

Abstract

The majority of existing graph neural networks (GNNs) following the message passing neural network (MPNN) pattern have limited power in capturing position information for a given node. To solve such problems, recent works exploit positioning nodes with selected anchors, mostly in a process that first explicitly assign distances information and then perform message passing encoding. However, this two-stage strategy may ignore potentially useful interaction between intermediate results of the distance computing and encoding stages. In this work, we propose a novel framework which follows the anchor-based idea and aims at conveying distance information implicitly along the MPNN message passing steps for encoding position information, node attributes, and graph structure in a more flexible way. Specifically, we first leverage a simple anchor indication strategy to enable the position-aware ability for well-designed MPNNs. Then, following this strategy, we propose the Graph Inference Representation (GIR) model, which acts as a generalization of MPNNs with a more specific propagation path design for position-aware scenarios. Meanwhile, we theoretically and empirically explore the ability of the proposed framework to get position-aware embeddings, and experimental results show that our proposed method generally outperforms previous position-aware GNN methods.

1 Introduction

Graph, as an important data structure, is a powerful tool to represent ubiquitous relationships in the real world. Learning vector representations for graph data, benefits many downstream tasks on the graph such as node classification (Kipf & Welling, 2017) and link prediction (Zhang & Chen, 2018). Many graph representation learning methods have been proposed recently, among those, Graph Neural Networks (GNNs), inheriting the merits of neural networks, have shown superior performance and become a much popular choice.

Existing GNN models mainly follow the message passing neural network (MPNN) (Gilmer et al., 2017) pattern, which stacks message passing layers that aggregate information from neighborhoods and then update representations for each node. Typical MPNNs are limited by 1-Weisfeiler-Lehman test (Xu et al., 2019), and lack of ability to capture the position information within the graph (You et al., 2019), without distinguishable node/edge attributes, nodes in a different part of the graph with topologically equivalent neighborhood structures or even with different substructures may be embedded into the identical representation by typical MPNNs alone (You et al., 2019; Li et al., 2020), as shown in figure 1 (b), A_1 and B_2 cannot be distinguished with MPNNs and no distinguishable attributes (when ignoring colored anchor nodes).

Researchers have developed methods to alleviate this issue. Some earlier works adopt one-hot encodings as extended node attributes (Kipf & Welling, 2017). More recent methods utilize graph distance information to get position-aware embeddings. Anchor-based GNNs (You et al., 2019; Liu et al., 2019) select anchor nodes as positioning bases, and use position information related to anchors to break the structural symmetry (Figure 1 (c)). Distance encoding (Li et al., 2020) utilizes distance information to push typical MPNNs beyond the 1-Weisfeiler-Lehman test limitation (Figure 1 d). Those existing position-aware GNN methods mainly explicitly pre-compute the distance

Figure 1: Comparison of position-aware GNN methods. **(a)** (Modified from (Li et al., 2020))Example unattributed input graph, nodes start with the same letter (A, B or C) are structurally equivalent. Nodes in a doubled circle (A_1 and B_1) are selected for demonstrating different position-aware GNN methods; the colored node (C_1) will be chosen as an anchor for anchor-based GNNs. **(b-e)** Different position aware GNN methods: MPNN (with anchor labeling); PGNN/AGNN; Distance Encoding; GIR model.

between node pairs, utilizing them as node attributes or controlling of message passing steps, and then perform message passing encoding, this two-stage strategy considers graph structure and attributes information encoded by GNN propagation and position information in a relatively separate manner, potentially useful interaction between intermediate results of the distance computing and encoding stages may be ignored.

In this paper, we follow the anchor-based GNN strategy and focus on conveying position information implicitly to perform a more flexible interaction with graph structure and attribute information. Our motivation comes from the structural similarity between GNN message passing and distance relaxation process of the Bellman-Ford shortest path algorithm (Bellman, 1958), we show that with a simple indication of anchors and appropriate design for message passing functions, MPNNs can keep track of the shortest paths from anchors. Further, inspired by a relaxation order improved variant of Bellman-Ford algorithm (Moore, 1959), we propose a generalized MPNN architecture, termed Graph Inference Representation (GIR), as a more specialized model for the position-aware scenario. The GIR model propagates messages from anchors along paths to each node, and outputs of the k-th layer encode k-step representations related to anchors. On an unweighted graph with no distinguishable node attributes, the proposed strategies provide natural ways to help break the structural symmetry as the previous anchor-based GNNs could (Figure 1 (b&e)).

Our contributions are summarized as follows:

1. We propose a general anchor labeling strategy, enabling MPNNs for mimicking the Bellman-Ford algorithm and getting position-aware embeddings implicitly under anchor-based GNN pattern and discuss theoretical implications and experimental realizations.

2. We propose the Graph Inference Representation (GIR) model that contains more specialized structure for learning position-aware embeddings.

3. Empirically, we evaluate the performance of proposed methods for tasks in position-aware datasets, experimental results show that our position-aware GIRs achieve generally higher performance.

The rest of the paper is organized as follows. Section 2 reviews related works. Section 3 introduces notations and definitions, theoretical implications are discussed. Section 4 details the proposed GIR framework. Section 5 presents the experiment and gives a discussion of the results. Finally, section 6 presents our conclusion.

2 RELATED WORKS

Our work follows the anchor-based GNN pattern from the position-aware GNN literature, with the design inspired by the Bellman-Ford algorithm.

2.1 POSITION-AWARE GNNS

Position-aware GNNs leverage distance information in the message propagating encoding process. Distance encoding (Li et al., 2020) follows the MPNN propagation design and extends it with pre-assigned graph distance to each target node. Anchor-based GNNs (A-GNNs) use selected anchor nodes as a positioning base, existing methods mainly follow the two-stage pattern: select anchor nodes first, and then encode the information related to anchors. Position-aware GNN (PGNN) (You et al., 2019) selects anchor node sets randomly before running every forward of the model to get a low distortion embedding capturing global position information, a PGNN layer directly propagates message from the selected anchor node set to each target node, weighted by the pairwise distance. The random anchor selecting strategy of PGNNs leads to unstable limitation, some more recent work uses fixed anchor nodes instead to overcome this issue. AGNN (Liu et al., 2019) pre-selects fixed anchors by minimum point cover nodes algorithm; GraphReach (Nishad et al., 2020) follows the fix anchor setting and adopts random walk reachability estimations instead of the shortest path distance.

Our GIR framework follows the A-GNN pattern and differs from previous works in the position information encoding and utilizing strategy. The major difference is that GIRs encode position information implicitly, more differences in message propagation strategy are depicted in figure 1.

2.2 BELLMAN-FORD ALGORITHM

The Bellman-Ford algorithm (Bellman, 1958) computes the shortest path distance from a single source node to each node in a weighted digraph. For a graph $\mathcal{G} = (\mathbb{V}, \mathcal{E})$, source node s, the algorithm performs $|\mathbb{V}| - 1$ relaxation iterations, maintaining the shortest path from s with at most i edges in the i-th iteration. A relaxation step iterate over all edges, correct distance to better ones. The relaxation of distance on i-th iteration and edge $\langle u, v \rangle$ with weight w is defined as,

$$dist_v^i = min(dist_v^{i-1}, dist_u^{i-1} + w) \quad i > 0 \tag{1}$$

where $dist^0$ is initialized as,

$$dist_v^0 = \begin{cases} 0 & v = s \\ \infty & otherwise \end{cases} \tag{2}$$

A variant of Bellman-Ford algorithm (Moore, 1959) notices that if the distance value of node v has not been changed since its last relaxed, edges out of v are no need to perform relaxation.

Learning graph algorithm including the Bellman-Ford algorithm with MPNN has been experimented in Velikovi et al. (2020), they show the effectiveness of adopting max-pooling, and propose to learn with intermediate results of graph algorithms. Our work goes further toward the implication from the Bellman-Ford algorithm, proposing more specialized strategies for this, and aims to perform as a general anchor-based GNN encoder.

3 PRELIMINARIES

3.1 NOTATIONS

A graph can be represented as $\mathcal{G} = (\mathbb{V}, \mathcal{E})$, where $\mathbb{V} = \{v_1, \cdots, v_n\}$ is the node set and $\mathcal{E} = \{\langle v_i, v_j \rangle | v_i, v_j \in \mathbb{V}\}$ is the edge set. Nodes are augmented with the feature matrix X, which is either input attributes or placeholders if no attributes available. Edges may augmented with the optional weights W. In-neighborhoods of node v are represented as $\mathcal{N}(v)$. Notations are summarized in table 1.

Table 1: Notations

Notation	Description
$\mathcal{G}$	the input graph
$\mathbb{V}, \mathcal{E}$	the node/edge set of $\mathcal{G}$
v_i	the i-th node in $\mathcal{G}$
X	the node attributes of $\mathcal{G}$
W	the edge weights of $\mathcal{G}$
Z	the node representations of $\mathcal{G}$
x_i, z_i	the attribute/representation of v_i
$\mathcal{N}(v)$	in-neighborhoods of node v in $\mathcal{G}$
$\mathbb{A}$	the anchor node set
$Successors(\mathcal{G}, \mathbb{N})$	successors of any node in $\mathbb{N}$ in $\mathcal{G}$
$[\boldsymbol{a} \vert\vert \boldsymbol{b}]$	concat vector $\boldsymbol{a}$ and $\boldsymbol{b}$

3.2 POSITION-AWARE EMBEDDINGS

One goal of the anchor-based GNN model is to utilize anchors as bases to encode position-aware information for each node. To capture this intuition, PGNNs (You et al., 2019) view embeddings as position-aware if the shortest path distance between node pairs could be reconstructed from their embeddings, which is hard for models with fixed anchors to satisfy. Here we define position-aware embeddings related to anchors (Definition 2), focusing on the limited hop multi-source distance from anchors.

Definition 1 (Position-aware Embeddings). *For $\mathbb{B} \subseteq \mathcal{P}(\mathbb{A}), \bigcup_{\mathbb{B}} = \mathbb{A}$, where $\mathcal{P}(\mathbb{A})$ is the power set of node set $\mathbb{A}$, a node embedding $z_i = f_p(v_i), \forall v_i \in \mathbb{V}$ is k-hop $\mathbb{B}$-position-aware if there exists functions $\{g_{\mathbb{N}}(\cdot) \vert \forall \mathbb{N} \in \mathbb{B}\}$ such that $g_a(z_i) = d_{sp}(v_i, \mathbb{N})$ where $d_{sp}(v, \mathbb{N})$ is the shortest path distance under k-hop between node v and any node in the node set $\mathbb{N}$ in the graph $\mathcal{G}$. If all elements in $\mathbb{B}$ are singleton, brakets of sets inner $\mathbb{B}$ could be omitted.*

3.3 INDICATABILITY

Here we discuss the theoretical implicitly of our GIR framework design. We begin with our motivation of mimicking the Bellman-Ford algorithm with MPNNs, the concept of indicatability is introduced as an effective tool for the design of the GIR framework.

A natural idea for an MPNN to mimic the Bellman-Ford algorithm is to perform neural relaxation functions and enable the capacity of keeping track of the intermediate limited hop shortest path distances. The motivation of mimicking the Bellman-Ford algorithm and getting position-aware embeddings implies the capability for reconstructing k-hop limited shortest path distance. To capture this intuition, we introduce the concept of **indicatability** that implies the existence and constructibility of functions that reconstruct specific information related to a node-set from a vector representation.

Definition 2 (Indicatability). *For $\mathbb{N} \subseteq \mathbb{A}$, the function set f is $\mathbb{N}$-indicatable over function f if there exists a function $f_{\mathbb{N}}$ such that $f_{\mathbb{N}}(z) = f(z, N)$.*

As a working example, for output representations z^k of the k-th layer of an MPNN, node set $\mathbb{N}$, the function set f-dist^k is $\mathbb{N}$-indicatable over the multi-source shortest path distance function if there exists a function f-dist$_{\mathbb{N}}$, such that for all node i in $\mathcal{G}$, f-dist$_{\mathbb{N}}^k(z_i^k)$ equals the shortest path distance between v_i and any node in $\mathbb{N}$. And the k-hop $\mathbb{A}$-position-aware definition (Definition 2) can be restated as the existence of f-dist^k with $\mathbb{N}$-indicatability, for all $\mathbb{N}$ in $\mathbb{A}$.

3.4 NEURAL BELLMAN-FORDS WITH MPNNS

Here we show that a well-designed and parameterized MPNN is capable for representing the process of updating the existence of an $\mathbb{N}$-indicatable f-dist^{k-1} over z^{k-1} to $\mathbb{N}$-indicatable f-dist^k over z^k in the k-th layer, the mentioned corresponding functions are directly implemented or implicitly mimicked by well-learned parameterized multi-layer perceptrons (MLP), and the effectiveness is

guaranteed by the inductive proof of the Bellman-Ford algorithm and the universal approximation theorem (Hornik, 1991).

Firstly, a well-learned MLP is expected to reconstruct $k-1$ hop limited shortest path distances from the inputs of k-th layer, with the existence of $\mathbb{N}$-indicatable f-dist^{k-1}, which can be written as,

$$[dist_{\mathbb{N}}^{k-1}]_{v_i} = \text{f-dist}_{\mathbb{N}}^{k-1}(z_i^{k-1}) \tag{3}$$

then, considering the aggregate and update pattern of MPNNs, we expect an MPNN layer performed on node v to mimic a relaxation iteration on v. Deriving from the Bellman-Ford relaxation function (Equation 1), the expected function for an MPNN layer to mimick could be,

$$[dist_{\mathbb{N}}^{k}]_{v} = \min(\{\min([dist_{\mathbb{N}}^{k-1}]_{v}, [dist_{\mathbb{N}}^{k-1}]_{u} + W_{e=\langle u,v \rangle})|\forall u \in \mathcal{N}(v)\}) \tag{4}$$

or equivalently,

$$[dist_{\mathbb{N}}^{k}]_{v} = \min([dist_{\mathbb{N}}^{k-1}]_{v}, \min(\{[dist_{\mathbb{N}}^{k-1}]_{u} + W_{e=\langle u,v \rangle}|\forall u \in \mathcal{N}(v)\})) \tag{5}$$

where the binary $\min$ function is expected to be mimicked by well-learned MLPs before pooling in the aggregator or the update function, while the $\min$ function over the set is expected to be mimicked by a well-learned parameterized sequential encoder like Recurrent Neural Networks (RNNs) or more commonly used max-pooling. A simple ordering of $\{dist_{\mathbb{N}}^{k}|\forall N \in \mathbb{A}\}$ as part of output z^k would maintain the existence of $\mathbb{N}$-indicatable f-dist^k, for all $\mathbb{N}$ in $\mathbb{A}$.

There remains an issue of initialization. For the first layer, there is no natural existence of $\mathbb{N}$-indicatable f-dist^0, as in the Bellman-Ford algorithm, the distance value of source nodes is initialized as 0, while others ∞. We would expect the updated distance value used in the $\min$ functions to be an enough large value, but it is not a natural way to explicitly assign it as node attributes, and we instead adopt a simple anchor indication strategy, or the f-ind with $\mathbb{N}$-indicatability, where $[\text{f-ind}_{\mathbb{N}}]_v$ is an indicator function discriminating whether the node v is in $\mathbb{N}$. And the expected function for the first MPNN layer to mimic, corresponding with quation 4 and 5, would be,

$$[dist_{\mathbb{N}}^{1}]_{v} = \min(\{W_{e=\langle u,v \rangle}|u \in \mathcal{N}(v) \wedge \text{f-ind}_{\mathbb{N}}(x_u)\}) \tag{6}$$

3.5 PROBLEM DEFINITION

The GIR framework is designed for node representation learning tasks, paying special attention to the capacity for getting position-aware embeddings. As a general encode for node representation learning, GIR takes graph $\mathbb{G} = (\mathbb{V}, \mathcal{E})$ with node attributes X and optional edge weights W as inputs, and embed nodes into d-dimensional vectors, represented as $Z \in \mathbb{R}^{|\mathbb{V}| \times d}$. The node representations are normally used in downstream tasks like node classification and link prediction.

4 METHODOLOGY

Here we proposed the GIR framework, acting as an extension of MPNNs to get position-aware embeddings. The GIR framework is based on the f-ind idea (Section 3.4) and a further specialization on the propagation paths, which we will introduce first, the overall design of the GIR framework will be elaborated then.

4.1 GIR MODEL: MORE SPECIFIC PROPAGATION PATHS

Motivated by the relaxation order improved variant of the Bellman-Ford algorithm (Moore, 1959), we consider designing an MPNN architecture with more specific propagation paths. As the condition of whether relaxed is dependent not only on the graph structure, we loose this condition to whether a node is reached by the breadth-first search from the source nodes.

Under these considerations, we propose the Graph Inference Representation (GIR) model, which acts as a generalization of MPNNs, propagating messages from anchors along breath first search paths (Figure 2). The GIR model would be degraded to an MPNN or a non-graph encoder if selecting all nodes or no node for the anchor set.

There is a general consideration in MPNNs that how to deal with nodes without in-edge in the propagation step, and a common workaround is adding a self-loop to the input graph. In the GIR

(a) Input Graph   (b) Message Propagating Paths

Figure 2: (a) Example input graph, colored nodes are chosen as anchors. (b) Message propagating edges for each layer in a 2-layer GIR model, Colored nodes highlight propagating source nodes.

Algorithm 1 The GIR framework.

Input: Graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$; Node input attributes $\{x_v, \forall v \in \mathbb{V}\}$; Edge weights W (optional)
Parameter: Number of layers L; Anchor selection function $SelectAnchor$; Anchor indicatability mark function $IndicatableMark$; Message functions M; Neighborhood aggregator functions $AGGR$; Node update functions U.
Output: A-position-aware embedding $\{z_v, \forall v \in \mathbb{V}\}$

 1: $\mathbb{A} \leftarrow SelectAnchor(\mathcal{G})$
 2: $h_v^0 \leftarrow [x_v || IndicatableMark(v, \mathbb{A})], \forall v \in \mathbb{V}$
 3: $bfs \leftarrow \mathbb{A}$
 4: **for** $l \leftarrow 1$ **to** L **do**
 5:    **for** v in $\mathbb{V}$ **do**
 6:       $src \leftarrow \mathcal{N}(v) \cap bfs \subseteq src \subseteq \mathcal{N}(v)$
 7:       $m_v \leftarrow AGGR_{u \in src}^l M^l(h_u^{l-1}, h_v^{l-1}, W_{e=\langle u,v \rangle})$
 8:       $h_v^l \leftarrow U^l(h_v^{l-1}, m_v)$
 9:    **end for**
10:    $bfs \leftarrow Successors(\mathcal{G}, bfs)$
11: **end for**
12: $z \leftarrow h^L$
13: **return** z

---

model, this becomes a more important issue as we additionally introduced this situation for nodes with the important role (anchor nodes that without other anchor nodes as a neighborhood). We take zero vector as a message if no in-neighborhood exists. In fact, considering a graph with only the same placeholders as node attributes and no node has zero in-degree, whatever the structure of the propagation tree is, all nodes are embedded identically. Adopting zero vector as dummy message is a simple but effective strategy for guaranteeing the existence of f-ind with $\mathbb{A}$-indicatability, thus a k-layer GIR with an anchor set $\mathbb{A}$ is k-hop $\{\mathbb{A}\}$-position-aware.

4.2 THE GIR FRAMEWORK

Having discussed the design choices for MPNNs and the propagating path variated GIR model, here we summarize the working process of the whole proposed framework for getting position-aware embeddings (Algorithm 1), building blocks are elaborated as follows.

Anchor Selection: (Algorithm 1, line 1) The intuition behind anchor-based GNNs is that some nodes perform a more important role in the graph for the specific task (Liu et al., 2019; Xu et al., 2020). For getting position-aware embeddings on general tasks with no nodes performing the special role, we heuristically prefer anchors to have high centrality and effective coverage through k-step message passing. We adopt GA-MPCA algorithm used in AGNN (Liu et al., 2019) as a default choice, which selects anchors according to degree centrality, giving attention to coverage and information interaction intensity.

Anchor Indication: (Algorithm 1, line 2) Assigning extend attributes for each node for guaranteeing the existence of f-ind with $\mathbb{N}$-indicatability for $\mathbb{N} \subseteq \mathbb{A}$.

Here we introduce two simple strategies as the realization of f-inds,

- **Anchor Labeling:** Assigning one for anchor nodes as an extended attribute, and zero for others. It guarantees the existence of f-ind with $\mathbb{A}$-indicatability, by checking whether the extended attribute is one.

- **Anchor ID Labeling:** Assigning one-hot labeling for anchors as extend attribute and zeros for others. For all anchor node $a \in \mathbb{A}$, the existence of f-ind with $\{a\}$-indicatability is guaranteed by indexing the ID of a in the extended attributes. This strategy is similar to the node one-hot labeling trick but introducing much fewer input dimensions. Note that the anchor ID labeling is not capable of inductive settings, for it is sensible to the order of anchor nodes.

The anchor indication is optional for using the GIR model (Section 4.1) if only $\{\mathbb{A}\}$-position-aware capability is expected.

Message Propagation: (Algorithm 1, line 3–12) For the propagation paths, the GIR model (Section 4.1) gives a limitation for determining neighborhoods in the MPNN message-passing steps (tracked as bfs in algorithm 1), and we take this limitation as lower bound in the whole framework. The message functions M are preferred to be a parameterized encoder over node representations and optional edge weight, and the update functions M are preferred to be a parameterized encoder over node message and representations, we commonly choose MLP as the parameterized encoders. Max-pooling is the most preferred choice for the aggregator $AGGR$.

5 EXPERIMENTS

In this section, we first take experiments on a synthetic dataset to validate the effectiveness of the GIR framework for getting position-aware embeddings, then we demonstrate the performance of GIRs on real world datasets used in position-aware GNN literature.

Datasets Based on our position-aware definition (Definition 2), we construct four synthetic datasets, ranging from weighted/unweighted, $\{\mathbb{A}\}/\mathbb{A}$-position-aware cases. For $\{\mathbb{A}\}$-position-aware setting, we generate 160 graphs with 100 nodes each for training, 20/20 graphs with 200 nodes each as valid/test set, the task is to predict the shortest path distance to any anchor for each node, following Velikovi et al. (2020), limited hop shortest path distances are predicted for each layer. For $\mathbb{A}$-position-aware setting, as anchor ID labeling strategy is not inductive, we generate one graph with 2000 nodes, the shortest path distances to every anchor node are predicted, train/valid/test sets are randomly split by 6:2:2. In the weighted setting, we assign edge weights as a uniformly sampled integer from 2 to 10, and in the unweighted setting, the distance between every connected node pair would be 1. We generate 5 datasets randomly for each case, details of those synthetic datasets are listed in table 2.

We take real-world datasets from previous position-aware GNN literature (You et al., 2019; Li et al., 2020). Those datasets with too few scales or in an inductive setting are filtered out. The graphs in these datasets are unattributed, the graph structure makes the major contribution to the tasks, and previous works have demonstrated the effectiveness of position information in those tasks, here we set node input attributes to ones as placeholders for a more fair comparison. Details of those real-world datasets are listed in table 3.

Baselines We choose baselines from MPNNs and anchor-based methods literature. The MPNN baseline uses a linear transformation for message and update functions, which keep the same as in our proposed models in the GIR framework. PGNN and AGNN are chosen as anchor-based baselines, PGNN learns global position by random select anchors before each run, while AGNN is a representative GNN method using a fixed anchor. Two variants of PGNN and AGNN are considered: using truncated 2-hop shortest-path distance (PGNN-E/AGNN-F) and using exact shortest-path distance (PGNN-E/AGNN-E).

Table 2: Details of synthetic position-aware datasets.

Dataset	$|\mathcal{G}|$	$|\mathbb{V}|$	avg. $|\mathcal{E}|$	weighted	position-aware setting	avg. label	$|\mathbb{A}|$	layers
dist	200	100, 200	907.2	✓	$\{\mathbb{A}\}$-position-aware	8.1	5	3
dist-u	200	100, 200	907.2	✗	$\{\mathbb{A}\}$-position-aware	1.6	5	3
dist-a	1	2000	20000	✓	$\mathbb{A}$-position-aware	17.9	20	4
dist-au	1	2000	20000	✗	$\mathbb{A}$-position-aware	3.3	20	4

Table 3: Details of position-aware real-world datasets.

Dataset	$|\mathbb{V}|$	$|\mathcal{E}|$	$|\mathbb{A}|$	Cite
Email	1005	25571	50	Leskovec et al. (2007)
Europe	399	5995	20	Ackland et al. (2005)
USA	1190	13599	50	Ackland et al. (2005)
C.ele	297	2148	20	Kaiser (2006)
NS	1461	2742	50	Newman (2006)
PB	1222	16714	50	Ackland et al. (2005)

For synthetic datasets, we evaluate only on models in the GIR framework and the corresponding MPNN backbone for demonstrating the effectiveness for getting position-aware embeddings implicitly, while those previous anchor-based baselines assign distance information explicitly.

We take experiments for the GIR framework over variants as follows, (1) MPNN with anchor labeling (MPNN-AA); (2) the GIR model; (3) MPNN and GIR with anchor ID labeling (MPNN-A/GIR-A); (4) MPNN and GIR with node one-hot labeling (MPNN-O/GIR-O); (5) Apply GIR model on each anchor node and concatenation for outputs (GIR-MIX). Variants using mean aggregator (*M) are also evaluated.

Experimental setup For real-world datasets, following Li et al. (2020), we split train/valid/test sets by 8:1:1. For each dataset, we report the test set performance at the best model with the valid set, and the final results are reported over 20 runs with different random seeds on 5 generated synthetic data samples or on the randomly split dataset for real-world datasets.

Our implementation is based on Deep Graph Library (DGL) (Wang et al., 2019), with PyTorch (Paszke et al., 2017) backend. For synthetic datasets, we use Adam optimizer for training, hyperparameters are set heuristically, listed in table 2. For real-world datasets, we mainly follow the hyperparameters settings in Li et al. (2020), with learning rate tuning in 1e-3 and 1e-4; hidden size set to 100; dropout set to 0.2; using 3 layer models for all datasets; the number of anchors are set heuristically according to the scale of each dataset and is also restricted by the GA-MPCA anchor selecting algorithm, listed in table 3.

Results and analysis For synthetic datasets, we report the mean absolute error (MAE) for mean outputs of every layer (mean) and on the last layer (last) in table 4. Considering that the average label value for these datasets (Table 2), the performance of the GIR framework with corresponding position-aware capability is quite promising. Models using mean aggregator are generally inferior to the corresponding max-pooling models, which supports our design of adopting max-pooling as preferred aggregator. Variants using GIR propagation (GIR-*) get outperformed results in $\mathbb{A}$-position-aware datasets (*dist-a*, *dist-au*) but inferior in $\{\mathbb{A}\}$-position-aware datasets (*dist*, *dist-u*). We owe the outperformed results to the more specific propagation paths in GIR models, thus more easily to learn the expected functions in the relatively complicated cases, while in the $\{\mathbb{A}\}$-position-aware datasets, both $\{\mathbb{A}\}$-position-aware models archives nearly perfect results, and the higher capacity of MPNN leads to a slight superiority.

Results of experiments on real-world datasets are reported in table 5, where the DE record the best performance of DE variants reported in the original paper (Li et al., 2020) for datasets except *Email*. Results show that with the same input feature, the MPNN baseline fails to distinguish different nodes. With $\{\mathbb{A}\}$-position-aware modeling ability, MPNNs with anchor labeling and vanilla GIRs generally get higher results, yet inferior to models with more powerful position-aware capability.

Table 4: Results on synthetic datasets position-aware scenario. **Bold font** highlights the best results.

	dist		dist-u		dist-a		dist-au	
	mean	last	mean	last	mean	last	mean	last
MPNN	3.4±0.1	3.6±0.2	0.6±0.0	0.7±0.0	4.0±0.3	4.0±0.5	0.5±0.0	0.5±0.0
MPNN-AA	**0.1±0.3**	**0.1±0.3**	**0.0±0.0**	**0.0±0.0**	3.5±0.2	3.5±0.4	0.5±0.0	0.5±0.0
GIR	0.2±0.0	0.2±0.0	0.0±0.0	0.0±0.0	3.5±0.3	3.5±0.5	0.5±0.0	0.5±0.0
GIR-M	0.9±0.0	1.1±0.0	0.1±0.0	0.0±0.0	3.6±0.3	3.6±0.5	0.4±0.0	0.5±0.0
MPNN-A	—	—	—	—	2.7±0.1	3.0±0.2	0.1±0.0	0.1±0.0
GIR-A	—	—	—	—	2.5±0.2	2.7±0.3	**0.1±0.0**	**0.1±0.0**
GIR-AM	—	—	—	—	2.9±0.2	3.1±0.3	0.1±0.0	0.1±0.0
GIR-MIX	—	—	—	—	**2.3±0.1**	**2.4±0.1**	0.1±0.0	0.1±0.0

Table 5: Results on the position-aware scenario, measured in test ROC AUC (in %) for link prediction (-lp) and node pair classification (-npc) task, and in test accuracy (in %) for node classification (-nc) task. **Bold font** highlights top-3 results, * highlights the best results.

	Email-npc	Europe-nc	USA-nc	C.ele-link	NS-link	PB-link
MPNN	50.0±0.0	25.4±0.8	25.2±0.0	50.0±0.0	50.0±0.0	50.0±0.0
PGNN-F	53.3±2.2	54.2±7.2	58.8±3.6	79.4±2.5	**94.3±1.2**	88.5±0.8
PGNN-E	53.2±2.2	54.0±5.6	58.5±4.2	78.3±2.1	**94.9±0.9**	88.6±0.6
AGNN-F	89.6±1.0	50.5±5.7	61.4±4.2	83.3±1.6	89.7±0.9	93.4±0.5
AGNN-E	87.9±1.3	52.4±6.6	59.5±4.0	84.9±2.0	89.6±1.4	93.4±0.5
DE	87.5±0.5	**58.4±3.2**	64.2±1.7	**90.0±0.3***	**99.4±0.6***	95.0±0.4
MPNN-AA	51.0±0.6	26.4±3.5	25.4±3.5	52.7±5.6	79.3±1.9	65.2±5.8
MPNN-AAM	72.6±1.7	52.7±7.1	52.6±4.3	84.8±2.6	79.5±2.9	92.3±0.6
MPNN-A	99.8±0.0	52.2±9.5	66.0±3.4	89.6±1.5	85.9±2.1	**95.3±0.3**
MPNN-AM	99.6±0.0	51.4±7.0	66.1±4.0	89.0±1.3	67.0±3.3	94.7±0.4
MPNN-O	**100.0±0.0***	48.5±8.8	61.3±4.3	87.9±1.1	91.8±2.0	93.7±0.4
GIR	50.1±0.4	25.3±2.2	26.7±4.2	55.3±1.9	81.1±1.9	63.4±2.6
GIR-M	50.3±0.7	27.9±4.1	32.4±2.0	55.9±2.1	80.3±1.7	60.4±3.3
GIR-A	99.8±0.0	**56.7±7.8**	**67.6±4.1**	**89.9±1.3**	89.9±1.3	**95.1±0.3**
GIR-AM	**99.9±0.0**	51.2±8.9	**66.3±4.6**	**89.9±1.8**	89.6±0.9	**95.3±0.3***
GIR-O	**100.0±0.0**	**59.5±6.9***	**68.6±3.1***	88.4±1.9	86.6±1.1	94.1±0.4
GIR-MIX	65.6±3.4	27.9±7.4	35.4±7.2	81.3±2.7	86.3±1.5	84.6±2.0

Anchor ID labeling and node one-hot labeling improve performance by a large margin, this demonstrates the effectiveness of $\mathbb{A}$-position-aware capability, among those, GIR models show superior results, which demonstrate the effectiveness of the more specific GIR propagation strategy in position-aware scenarios. However, the GIR-MIX, with $\mathbb{A}$-position-aware, performs only superior to $\{\mathbb{A}\}$-position-aware models, and largely inferior to models with anchor ID labeling, we ascribe it to the extremely limited propagation path, though efficient in the synthetic datasets (*dist-a*, *dist-au*), vanilla GIR-MIX may not be an efficient general encoder.

The GIR framework performs inferior on *NS-link*, we ascribe it to the sparsity of *NS*, unreachable nodes from anchors on the input graph will be not benefited from the GIR framework, and previous position-aware methods with special propagation strategy get relatively higher results.

6 CONCLUSION AND FUTURE WORK

We propose the GIR (Graph Inference Representation) framework, following the anchor-based GNN pattern and aims at conveying distance information implicitly along the MPNN message-passing steps. Theoretical implications and experimental results show the effectiveness of proposed strategies. Our empirical evaluations are taken on the synthetic datasets and relatively small scale real-world position-aware datasets used in the previous position-aware GNN literature, we leave the potential usage of GIR on larger scale scenarios for future work.

REFERENCES

Robert Ackland et al. Mapping the us political blogosphere: Are conservative bloggers more prominent? In *BlogTalk Downunder 2005 Conference, Sydney*. BlogTalk Downunder 2005 Conference, Sydney, 2005.

R. Bellman. On a routing problem. *Quarterly of Applied Mathematics*, 16:87–90, 1958.

Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. In *International Conference on Machine Learning*, pp. 1263–1272. PMLR, 2017.

Kurt Hornik. Approximation capabilities of multilayer feedforward networks. *Neural networks*, 4 (2):251–257, 1991.

M. Kaiser. Nonoptimal component placement, but short processing paths, due to long-distance projections in neural systems. *PLOS Computational Biology*, 2, 2006.

Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *International Conference on Learning Representations (ICLR)*, 2017.

Jure Leskovec, Jon Kleinberg, and Christos Faloutsos. Graph evolution: Densification and shrinking diameters. *ACM transactions on Knowledge Discovery from Data (TKDD)*, 1(1):2–es, 2007.

Pan Li, Yanbang Wang, Hongwei Wang, and Jure Leskovec. Distance encoding–design provably more powerful gnns for structural representation learning. 2020.

Chao Liu, Xinchuan Li, Dongyang Zhao, Shaolong Guo, Xiaojun Kang, Lijun Dong, and Hong Yao. A-gnn: Anchors-aware graph neural networks for node embedding. In *International Conference on Heterogeneous Networking for Quality, Reliability, Security and Robustness*, pp. 141–153. Springer, 2019.

E. F. Moore. The shortest path through a maze. In *Proc. of the International Symposium on the Theory of Switching*, 1959.

Mark EJ Newman. Finding community structure in networks using the eigenvectors of matrices. *Physical review E*, 74(3):036104, 2006.

Sunil Nishad, Shubhangi Agarwal, Arnab Bhattacharya, and Sayan Ranu. GraphReach: Position-Aware Graph Neural Networks using Reachability Estimations. *arXiv:2008.09657 [cs, stat]*, September 2020. URL http://arxiv.org/abs/2008.09657. arXiv: 2008.09657.

Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. Automatic differentiation in pytorch. 2017.

Petar Velikovi, Rex Ying, Matilde Padovano, Raia Hadsell, and Charles Blundell. Neural execution of graph algorithms. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=SkgKO0EtvS.

Minjie Wang, Da Zheng, Zihao Ye, Quan Gan, Mufei Li, Xiang Song, Jinjing Zhou, Chao Ma, Lingfan Yu, Yu Gai, Tianjun Xiao, Tong He, George Karypis, Jinyang Li, and Zheng Zhang. Deep graph library: A graph-centric, highly-performant package for graph neural networks. *arXiv preprint arXiv:1909.01315*, 2019.

Chunyan Xu, Zhen Cui, Xiaobin Hong, Tong Zhang, Jian Yang, and Wei Liu. Graph inference learning for semi-supervised classification. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=r1evOhEKvH.

Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=ryGs6iA5Km.

Jiaxuan You, Rex Ying, and Jure Leskovec. Position-aware graph neural networks. In *International Conference on Machine Learning*, pp. 7134–7143. PMLR, 2019.

M Zhang and Y Chen. Link prediction based on graph neural networks. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, pp. 5171–5181, 2018.